

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 748 864 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

18.12.1996 Bulletin 1996/51

(51) Int. Cl.⁶: **C11D 3/02, C11D 3/20**

(21) Application number: **95870134.4**

(22) Date of filing: **18.12.1995**

(84) Designated Contracting States:

AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT SE

(30) Priority: **12.06.1995 EP 95870067**

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
Cincinnati, Ohio 45202 (US)

(72) Inventor: **Evers, Marc François Theophile**

B-1853 Strombeek-Bever (BE)

(74) Representative: **Engisch, Gautier et al**

Procter & Gamble
European Technical Center N.V.
Ternselaan 100
1853 Strombeek-Bever (BE)

(54) Cleaning composition and method for the cleaning of delicate surfaces

(57) Compositions are disclosed which are suitable for the safe cleaning of delicate surfaces, i.e. marble and painted and lacquered surfaces, e.g. lacquered wooden floors. The compositions disclosed herein comprise at least one surfactant, they are formulated in the mildly acidic to mildly alkaline pH range, they comprise a builder or a combination of builders, and positive divalent ions in amounts so as to saturate the builder in the composition.

EP 0 748 864 A1

DescriptionTechnical Field

5 The present invention relates to hard surface cleaning compositions. The compositions herein are specifically designed for the safe cleaning of marble and painted and lacquered surfaces, especially painted and lacquered wood.

Background

10 A wide variety of cleaning compositions for hard surfaces have been disclosed in the prior art. Most of these compositions are concerned only with performance, on a wide variety of stains and in a wide variety of conditions. And most hard surfaces are rather resistant to the point that it is generally not a concern that these surfaces may be permanently damaged by the cleaning composition.

15 However marble and lacquered surfaces are two types of surfaces which do require particular attention, when formulating cleaning compositions for their cleaning. Indeed, marble is mainly composed of calcium carbonate, and is therefore incompatible with cleaning compositions which would be acidic to neutral and/or which would comprise a builder. Indeed, acidity would "dissolve" marble, while the builder, whose function is specifically to bind ions which are present in water and dirt particles, would also bind the calcium in the marble, thereby turning the surface from very shiny to dull, as the introduced surface irregularities lower the reflectance of the surface. More surprisingly, we have found that
20 most cleaning products formulated at neutral pH, containing builders and/or anionics, also damage marble. Thus the formulation of an alkaline, builder free composition would seem indicated in the present circumstances.

25 However, the formulation of an alkaline composition does not accommodate the cleaning of lacquered and painted surfaces, such as painted metal surfaces, or lacquered and painted wooden surfaces e.g. lacquered wooden floors. As used herein, lacquers are typically made out of polyurethanes or polyacrylates or mixtures of both, and paint is mainly pigmented polyacrylates, polyvinylacetates or alkydresins. Indeed such surfaces are permanently damaged by alkalinity. Specifically, alkalinity would destroy the lacquer and therefore give the lacquered surface the appearance of dullness or a colour change. Thus it would appear that formulating a cleaning composition which is suitable for cleaning both marble and lacquered surfaces is hindered by incompatible pH requirements.

30 Also, the absence of a builder, which is desirable for preserving the marble, is somewhat incompatible with a good performance for the cleaning of grease/particulate soil. Indeed, it has been observed that dirt comprises Ca^{2+} , Mg^{2+} and/or metal ions which, in turn, most probably bind the charged ends of the fat molecules in grease, thereby forming a dirt-grease complex which is difficult to removal. The presence of a builder which binds the metal ions loosens the complex and therefore helps its removal.

35 Thus it is an object of the present invention to formulate a liquid composition which is suitable for the cleaning of both marble and painted and lacquered surfaces, and which provides good cleaning performance, in particular which performs well on grease removal.

In response to this object, we have formulated a liquid composition which comprises at least one surfactant, which is formulated at a mildly acidic to mildly alkaline pH, which comprises a builder, and positive divalent ions in amounts so as to saturate the builder in the composition.

40 Indeed, we have found that in the present compositions, the mildly acidic to neutral pH does damages neither marble nor lacquers. Also, the builder saturated with the positive divalent ions prevents the damage on marble, while it still displays its building action, as evidenced by improved grease cleaning performance.

Cleaning composition which are said to be for delicate surfaces are described in EP 511 091, CN 1055198 (title) and CN 10 32 360 (title).

45

Summary of the Invention

50 The present invention encompasses a liquid cleaning composition which comprises at least one surfactant, which is formulated in the mildly acidic to mildly alkaline pH range, which comprises a builder and positive divalent ions in an amount so as to saturate the builder in the composition.

The present invention further encompasses a method of cleaning marble or lacquered surfaces, where an effective amount of the composition is applied to clean said marble or lacquered surfaces, and said composition is removed.

Detailed description of the invention

55

The compositions herein are liquid compositions. They are typically aqueous and typically comprise from 10 % to 99 % by weight of the total composition, preferably from 15 % to 95 %, most preferably from 30 % to 92 % of water.

As a first essential characteristic, the compositions herein comprise at least one surfactant. The surfactant herein is required for cleaning. Suitable surfactants for use herein include anionic, nonionic, cationic and amphoteric sur-

factants. Non limiting examples of surfactants useful herein typically include the conventional alkyl benzene sulphonates ("LAS"), typically C₁₁-C₁₈ LAS, alkyl sulphonates, typically C₈-C₁₈ alkyl sulphonates and primary, branched-chain and random alkyl sulphates ("AS"), typically C₁₀-C₂₀ AS, the secondary (2,3) alkyl sulphates, typically C₁₀-C₁₈ ones, of the formula CH₃(CH₂)_x(CHOSO₃⁻M⁺) CH₃ and CH₃ (CH₂)_y(CHOSO₃⁻M⁺) CH₂CH₃ where x and (y+1) are integers of at least about 7, preferably at least about 9, and M is a water-solubilizing cation, especially sodium, unsaturated sulphates such as oleyl sulphate, the alkyl alkoxy sulphates ("AE_xS"), especially C₁₀-C₁₈ AE_xS, especially EO 1-7 ethoxy sulphates, alkyl alkoxy carboxylates, especially the C₁₀-C₁₈ ones, especially EO 1-5 ethoxycarboxylates, the glycerol ethers, preferably the C₁₀-C₁₈ ones, the alkyl polyglycosides and their corresponding sulphated polyglycosides, and alpha-sulphonated fatty acid esters, preferably the C₁₀-C₁₈ ones. If desired, the conventional nonionic and amphoteric surfactants such as the alkyl ethoxylates ("AE") preferably C₁₂-C₁₈ AE, including the so-called narrow peaked alkyl ethoxylates and alkyl phenol alkoxyates, especially the C₆-C₁₂ ones, especially ethoxylates and mixed ethoxy-propoxy, betaines and sulfobetaines ("sultaines"), preferably the C₁₂-C₁₈ ones, amine oxides, typically the C₁₀-C₁₈ ones, and the like, can also be included in the overall compositions. The N-alkyl polyhydroxy fatty acid amides, typically C₁₀-C₁₈ ones, can also be used. Typical examples include the C₁₂-C₁₈ N-methylglucamides, see WO 9,206,154. Other sugar-derived surfactants include the N-alkoxy polyhydroxy fatty acid amides, such as C₁₀-C₁₈ N-(3-methoxypropyl) glucamide. The N-propyl through N-hexyl glucamides, preferably C₁₂-C₁₈ ones, can be used for low sudsing. C₁₀-C₂₀ conventional soaps may also be used. If high sudsing is desired, the branched-chain C₁₀-C₁₆ soaps may be used. Mixtures of anionic and nonionic surfactants are especially useful. Other conventional useful surfactants are listed in standard texts.


The compositions herein comprise from 0.1 % to 90 % by weight of the total composition, preferably from 5 % to 85 %, most preferably from 5 % to 70 % of at least one surfactant. The preferred surfactants for use herein are the non-ionic surfactants or mixtures of anionics and nonionics, for their cleaning action on grease. It is another benefit of the present invention that anionic surfactants can be used herein without damaging marble. Indeed, it has been observed that anionic surfactants usually also damage marble probably because, like builders, they bind with the calcium in the marble. However the compositions of the present invention can surprisingly afford the presence of anionic surfactants for improved cleaning without having to suffer any negative on safety to marble.

As a second essential characteristic, the compositions herein comprise a builder. The compositions herein comprise from 0.1 % to 20 %, preferably from 0.2 % to 10 %, most preferably from 0.3 % to 6 % by weight of the total composition of builder, or mixtures thereof.

Suitable builders for use herein include polycarboxylates and polyphosphates, and salts thereof.

Suitable and preferred polycarboxylates for use herein are organic polycarboxylates where the highest LogK_a, measured at 25°C/0.1 M ionic strength is between 3 and 8, wherein the sum of the LogK_{Ca} + LogK_{Mg}, measured at 25°C/0.1 M ionic strength is higher than 4, and wherein LogK_{Ca} = LogK_{Mg} ± 2 units, measured at 25°C/0.1M ionic strength.


Such suitable and preferred polycarboxylates include citrate and complexes of the formula



wherein A is H or OH; B is H or -O-CH(COOX)-CH₂(COOX); and X is H or a salt-forming cation. For example, if in the above general formula A and B are both H, then the compound is oxydisuccinic acid and its water-soluble salts. If A is OH and B is H, then the compound is tartrate monosuccinic acid (TMS) and its water-soluble salts. If A is H and B is -O-CH(COOX)-CH₂(COOX), then the compound is tartrate disuccinic acid (TDS) and its water-soluble salts. Mixtures of these builders are especially preferred for use herein. Particularly TMS to TDS, these builders are disclosed in U.S. Patent 4,663,071, issued to Bush et al., on May 5, 1987.

Still other ether polycarboxylates suitable for use herein include copolymers of maleic anhydride with ethylene or vinyl methyl ether, 1, 3, 5-trihydroxy benzene-2, 4, 6-trisulfonic acid, and carboxymethyloxysuccinic acid.

Other useful polycarboxylate builders include the ether hydroxypolycarboxylates represented by the structure:



wherein M is hydrogen or a cation wherein the resultant salt is water-soluble, preferably an alkali metal, ammonium or substituted ammonium cation, n is from about 2 to about 15 (preferably n is from about 2 to about 10, more preferably n averages from about 2 to about 4) and each R is the same or different and selected from hydrogen, C₁₋₄ alkyl or C₁₋₄ substituted alkyl (preferably R is hydrogen).

Suitable ether polycarboxylates also include cyclic compounds, particularly alicyclic compounds, such as those described in U.S. Patents 3,923,679; 3,835,163; 4,158,635; 4,120,874 and 4,102,903, all of which are incorporated herein by reference.

Preferred amongst those cyclic compounds are dipicolinic acid and chelidonic acid.

Also suitable polycarboxylates for use herein are mellitic acid, succinic acid, polymaleic acid, benzene 1,3,5-tricarboxylic acid, benzene pentacarboxylic acid, and carboxymethyloxysuccinic acid, and soluble salts thereof.

Still suitable carboxylate builders herein include the carboxylated carbohydrates disclosed in U.S. Patent 3,723,322, Diehl, issued March 28, 1973, incorporated herein by reference.

Other suitable carboxylates for use herein, but which are less preferred because they do not meet the above criteria are alkali metal, ammonium and substituted ammonium salts of polyacetic acids. Examples of polyacetic acid builder salts are sodium, potassium, lithium, ammonium and substituted ammonium salts of ethylenediamine, tetraacetic acid and nitrilotriacetic acid.

Other suitable but less preferred polycarboxylates are those also known as alkyliminoacetic builders such as methyl imino diacetic acid, alanine diacetic acid, methyl glycine diacetic acid, hydroxy propylene imino diacetic acid and other alkyl imino acetic acid builders.

Also suitable in the compositions of the present invention are the 3,3-dicarboxy-4-oxa-1,6-hexanediotes and the related compounds disclosed in U.S. Patent 4,566,984, Bush, issued January 28, 1986, incorporated herein by reference. Useful succinic acid builders include the C₅-C₂₀ alkyl succinic acids and salts thereof. A particularly preferred compound of this type is dodecenylsuccinic acid. Alkyl succinic acids typically are of the general formula R-CH(COOH)CH₂(COOH) i.e., derivatives of succinic acid, wherein R is hydrocarbon, e.g., C₁₀-C₂₀ alkyl or alkenyl, preferably C₁₂-C₁₆ or wherein R may be substituted with hydroxyl, sulfo, sulfoxy or sulfone substituents, all as described in the above-mentioned patents.

The succinate builders are preferably used in the form of their water-soluble salts, including the sodium, potassium, ammonium and alkanolammonium salts.

Specific examples of succinate builders include : laurylsuccinate, myristylsuccinate, palmitylsuccinate, 2-dodecenylsuccinate (preferred), 2-pentadecenylsuccinate, and the like. Laurylsuccinates are the preferred builders of this group, and are described in European Patent Application 86200690.5/0 200 263, published November 5, 1986.

Examples of useful builders also include sodium and potassium carboxymethyloxymalonate, carboxymethyloxysuccinate, cis-cyclohexanhexacarboxylate, cis-cyclopentane-tetracarboxylate, water-soluble polyacrylates and the copolymers of maleic anhydride with vinyl methyl ether or ethylene.

Other suitable polycarboxylates are the polyacetal carboxylates disclosed in U.S. Patent 4,144,226, Crutchfield et al., issued March 13, 1979, incorporated herein by reference. These polyacetal carboxylates can be prepared by bringing together, under polymerization conditions, an ester of glyoxylic acid and a polymerization initiator. The resulting polyacetal carboxylate ester is then attached to chemically stable end groups to stabilize the polyacetal carboxylate against rapid depolymerization in alkaline solution, converted to the corresponding salt, and added to a surfactant.

Polycarboxylate builders are also disclosed in U.S. Patent 3,308,067, Diehl, issued March 7, 1967, incorporated herein by reference. Such materials include the water-soluble salts of homo- and copolymers of aliphatic carboxylic acids such as maleic acid, itaconic acid, mesaconic acid, fumaric acid, aconitic acid, citraconic acid and methylenemalonic acid.

Suitable polyphosphonates for use herein are the alkali metal, ammonium and alkanolammonium salts of polyphosphates (exemplified by the tripolyphosphates, pyrophosphates, and glassy polymeric meta-phosphates), phosphonates. The most preferred builder for use herein is citrate.

As a third essential ingredient, the compositions herein comprise positive divalent ions in amounts so as to saturate the builder present in the composition. By "saturate", it is meant herein that there should be enough ions to bind substantially all the builder present in the composition, i.e. at least 75% of the builder, preferably at least 80%, most preferably at least 90% or all of the builder. Thus, for a 100% saturation, the ions should be present most preferably in a molar ratio of builder ions to builder of at least X:2, where X is the maximum potential number of negative charges carried per mole of builder. For instance, if said builder is citrate, then said molar ratio should be at least 3:2, because each mole of citrate can carry 3 negative charges. For the purpose of the present invention and the amount of ions needed therein, the form in which the carboxylate or phosphate groups in the builder are present is not critical. In other words, at certain pH values between 6 to 8 where some of the carboxylate or phosphate groups in the builder are in their protonated form, the preferred X:2 ratio still applies.

The ions can be introduced in the compositions in any form. MgSO₄, MgCl₂, Mg Phosphates and MgNO₃ are a suitable source of Mg ions for the compositions herein. Without wishing to be bound by theory, we speculate that the ions herein somehow prevent the builder from binding with the calcium in the marble, without preventing the builder from performing in the cleaning operation.

Suitable positive divalent ions for use herein include Mg²⁺, Ba²⁺, Fe²⁺, Ca²⁺, Zn²⁺ and Ni²⁺. Most Preferred are Mg²⁺ and Ca²⁺, or mixtures thereof.

As a fourth essential characteristic, the compositions herein are formulated in a mildly acidic to mildly alkaline range. Accordingly, the compositions herein preferably have a pH between 6 and 9, more preferably between 6.5 and 8, and most preferably between 7 and 7.5. At lower pH, the composition would damage marble while, at higher pH, it would damage lacquers. Interestingly, even in neutral pH in which the compositions herein can be formulated, damage to marble would be observed in the absence of the saturated citrate. The pH of the compositions herein can be adjusted by any of the means well known to the man skilled in the art, such as addition of NaOH, KOH, MEA, TEA, MDEA, K₂CO₃, Na₂CO₃ and the like, or citric acid, sulphuric acid, nitric acid, hydrochloric acid, maleic acid,

acetic acid and the like.

Particularly preferred compositions herein comprise an effective amount of a carbonate of the formula XHCO_3 or, if the builder used is not a phosphate-type builder, a phosphate of the formula $\text{X}_a\text{H}_b\text{PO}_4$, where $a+b=3$ and a or b can be 0, $\text{X}_a\text{H}_b\text{P}_2\text{O}_7$ where $a+b=4$ and a or b can be 0, or $\text{X}_a\text{H}_b\text{P}_3\text{O}_{10}$ where $a+b=5$ and a or b can be 0, and where X is an alkali metal, particularly K^+ , Na^+ , or NH_4^+ . Indeed, apart from the pH adjusting effect just described, we have found that the presence of those compounds further improves the safety of the compositions herein to delicate surfaces. Without wishing to be bound by theory, it is believed that the compounds react with the calcium on the surface of marble, to form an insoluble calcium carbonate salt at the marble/solution interface, creating a protective layer. Using these compounds in addition to the saturation technology described hereinabove provides a synergetic effect on delicate surface safety. The amount of these compounds needed in the compositions herein can be determined by trial and error, but appears to lie in the range of from 0.05% to 0.4% by weight of the total composition, preferably from 0.05% to 0.1%. Caution needs to be exercised however in that we have observed that too high an amount of XHCO_3 may raise be detrimental to surface safety on lacquered wood.

The compositions herein can further comprise a variety of well known optional ingredients, including perfumes, dyes, alkanolamines.

The present invention further encompasses a method of cleaning marble or lacquered surfaces. In that method, an effective amount of a composition as herein before described is applied onto said marble or lacquered surface, and said composition is optionally removed.

Depending on the surface which is being cleaned, the compositions herein can be used undiluted, i.e. neat, or diluted. Typically, when used on large surfaces, such as floors, the compositions herein are used in diluted form, i.e. at dilution levels of from about 0.5% to 1.5%, depending on how concentrated the product is. In such diluted conditions, the compositions herein are applied to said surface, and left to dry, i.e. no rinsing is required. In order to remove tough stains on these surfaces the product can also be applied neat on the surface to remove the encrusted dirt much more easily. When used on smaller surfaces, e.g. bathroom walls which can be made out of marble, neat usage of the composition will be preferred. In neat usage, it is preferable that the composition should be removed, i.e. rinsed off after it has been applied to clean.

The present invention will be further illustrated by the following examples.

Examples

The following compositions were made by mixing the listed ingredients in the listed proportions. These compositions were used neat to clean marble and dilute to clean lacquered wooden floors. Excellent cleaning and surface safety performance was observed.

Ingredients	Compositions (weight %)							
	1	2	3	4	5	6	7	8
$\text{C}_{7-9}, \text{C}_{9-11}\text{EO}_6$	3.0	3.0	5.0	3.2	3.2	3.2	8.0	8.0
Dobanol® 23-3	1.0	1.0	1.5	1.3	1.3	1.5	3.0	3.5
Empilan KBE21 +	2.0	2.0	2.5	1.9	1.9	2.0	5.0	6.0
NaPS	1.2	1.5	1.2	1.2	1.0	1.7	3.0	2.5
NaCS	2.0	2.0	2.2	2.0	2.0	1.5	4.0	5.0
MgSO_4	0.50	0.6	0.30	0.50	1.3	2.0	1.0	3.0
Citrate	0.75	1.0	0.5	0.75	1.8	3.0	1.5	6.0
NaHCO_3	-	0.1	-	0.1	-	0.1	-	-
Na_2HPO_4	-	-	0.1	-	0.3	0.2	-	-
$\text{Na}_2\text{H}_2\text{P}_2\text{O}_7$	-	-	-	-	-	-	0.2	0.5
pH	7.3	7.5	7.0	7.25	8.0	7.4	7.5	7.2
Water and Minors	-----up to 100%-----							

As used hereinabove:

- NaPS stands for Na paraffin sulphonate
- NaCS stands for Na cumene sulphonate
- Dobanol® 23-3 is a C12-13 alcohol ethoxylated with an average ethoxylation degree of 3.
- Empilan KBE21 is a C12-14 alcohol ethoxylated with an average ethoxylation degree of 3.

Claims

1. A liquid cleaning composition which comprises at least one surfactant, which is formulated at a mildly acidic to mildly alkaline pH, which comprises a builder and positive divalent ions in amounts so as to saturate the builder in the composition.
2. A composition according to claim 1 which is formulated in a pH range of from 6 to 9, preferably 6.5 to 8, most preferably 7 to 7.5.
3. A composition according to any of the preceding claims which comprises from 0.1% to 90 % by weight of the total composition, preferably from 5% to 85%, most preferably from 5 % to 70% of said surfactant.
4. A composition according to any of the preceding claims wherein said surfactant includes a nonionic surfactant.
5. A composition according to claim 4 wherein said surfactant is a mixture of an anionic surfactant with a nonionic surfactant.
6. A composition according to any of the preceding claims wherein said positive divalent ions are Mg^{2+} or Ca^{2+} or mixtures thereof.
7. A composition according to the preceding claims which further comprises an effective amount of a carbonate of the formula $XHCO_3$ or, if said builder is not a phosphate-type builder, a phosphate of the formula $X_aH_bPO_4$, where $a+b=3$ and a or b can be 0, $X_aH_bP_2O_7$ where $a+b=4$ and a or b can be 0, or $X_aH_bP_3O_{10}$ where $a+b=5$ and a or b can be 0, and where X is an alkali metal, particularly K^+ , Na^+ , or NH_4^+ .
8. A composition according to the preceding claims wherein said builder is a polycarboxylate builder or a polyphosphate builder.
9. A composition according to claim 8 wherein said polycarboxylate builder is an organic polycarboxylate wherein the highest $LogK_a$, measured at 25°C/0.1M ionic strength is between 3 and 8, wherein the sum of the $LogKCa + LogKMg$, measured at 25°C/0.1M ionic strength is higher than 4, and wherein $LogKCa = LogKMg \pm 2$ units, measured at 25°C/0.1M ionic strength.
10. A composition according to claim 9, wherein said builder is citrate.
11. A composition according to any of the preceding claims which comprises from 0.1% to 20% by weight of the total composition, preferably from 0.2% to 10%, most preferably from 0.3% to 6% of said builder.
12. A method of cleaning marble or lacquered surfaces, where an effective amount of a composition according to any of the preceding claims is applied to clean said marble or lacquered surfaces, and said composition is optionally removed.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 95 87 0134

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP-A-0 070 587 (PROCTER & GAMBLE) * the whole document *	1-12	C11D3/02 C11D3/20
A	WO-A-94 04644 (UNILEVER PLC ET AL.) * claims 1,2,7-9 *	1-12	
A	FR-A-2 246 630 (PROCTER & GAMBLE EUROP) * page 2, line 34 - line 40 * * page 3, line 1 - line 16 * * claims *	1-6	
A	GB-A-2 144 763 (PROCTER & GAMBLE) * page 1, line 8 * * page 2, line 16 - line 44 * * page 4; example 1 *	1-6,10	
A	EP-A-0 125 711 (UNILEVER NV ET AL.) * page 4, line 20 - line 33 * * page 8, line 26 *	1-6,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			C11D
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 7 October 1996	Examiner Pelli Wablat, B
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)