



US010463850B2

(12) **United States Patent**
Fisk et al.

(10) **Patent No.:** **US 10,463,850 B2**
(45) **Date of Patent:** **Nov. 5, 2019**

(54) **METHODS OF MANUFACTURING DEVICES FOR THE NEUROREHABILITATION OF A PATIENT**

(58) **Field of Classification Search**
CPC A61B 5/682; A61B 5/02438; H05K 1/11; Y10T 29/49155; Y10T 29/49169
(Continued)

(71) Applicant: **Neurohabilitation Corporation**,
Newtown, PA (US)

(56) **References Cited**

(72) Inventors: **Justin Fisk**, Newtown, PA (US); **Mark Guarraia**, Newtown, PA (US); **Aidan Petrie**, Newtown, PA (US); **Joseph M. Gordon**, Newtown, PA (US); **Faith David-Hegerich**, Newtown, PA (US); **Shane Siwinski**, Newtown, PA (US); **Adam Muratori**, Newtown, PA (US); **Jeffrey M. Wallace**, Newtown, PA (US)

U.S. PATENT DOCUMENTS

2,055,540 A 9/1936 Karnofsky
3,851,651 A 12/1974 Icenbice
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2671612 A1 12/2013
KR 20110038314 A 4/2011
(Continued)

(73) Assignee: **Helius Medical, Inc.**, Newtown, PA (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 12 days.

Danilov, Y.P. et al., "Emerging Noninvasive Neurostimulation Technologies: CN-NINM and Sympatocorection," Journal of Behavioral and Brain Science, 2014, 9 pages (pp. 105-113).

(Continued)

(21) Appl. No.: **15/602,055**

(22) Filed: **May 22, 2017**

Primary Examiner — Thiem D Phan

(65) **Prior Publication Data**

US 2017/0354817 A1 Dec. 14, 2017

(74) *Attorney, Agent, or Firm* — Proskauer Rose LLP

(57) **ABSTRACT**

Related U.S. Application Data


(63) Continuation of application No. 14/559,118, filed on Dec. 3, 2014, now Pat. No. 9,656,060.

(51) **Int. Cl.**
H05K 3/02 (2006.01)
A61N 1/05 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61N 1/0548** (2013.01); **A61N 1/0456** (2013.01); **A61N 1/0476** (2013.01);
(Continued)

A mouthpiece for providing non-invasive neuromodulation to a patient, the mouthpiece including an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar exterior top surface and internal structural members disposed within the housing, the internal structural members elastically responding to biting forces generated by the patient, a spacer attached to the top surface of the housing for limiting contact between a patient's upper teeth and the exterior top surface of the elongated housing, and a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue.

10 Claims, 29 Drawing Sheets



- | | | | | | | |
|------|---|--|--|--|-----------------|-------------------------|
| (51) | Int. Cl. | | | | | |
| | <i>A61N 1/04</i> | (2006.01) | | | D663,714 S | 7/2012 Kang et al. |
| | <i>H05K 3/28</i> | (2006.01) | | | D669,881 S | 10/2012 Clements et al. |
| | <i>A61N 1/36</i> | (2006.01) | | | 8,290,582 B2 | 10/2012 Lin et al. |
| (52) | U.S. Cl. | | | | D687,018 S | 7/2013 Afshar |
| | CPC | <i>A61N 1/0484</i> (2013.01); <i>A61N 1/0529</i> | | | D706,745 S | 6/2014 Nakagawa |
| | | (2013.01); <i>A61N 1/36014</i> (2013.01); <i>A61N</i> | | | D707,199 S | 6/2014 Cepress et al. |
| | | <i>1/36025</i> (2013.01); <i>H05K 3/284</i> (2013.01); | | | D709,673 S | 7/2014 Aimone et al. |
| (58) | Field of Classification Search | | | | D710,718 S | 8/2014 Ichihashi et al. |
| | USPC | 29/846, 825, 854, 874 | | | 8,805,548 B2 | 8/2014 Mignolet et al. |
| | See application file for complete search history. | | | | D713,531 S | 9/2014 Way et al. |
| | | <i>Y10T 29/49155</i> (2015.01); <i>Y10T 29/49169</i> | | | 8,849,407 B1 | 9/2014 Danilov et al. |
| (56) | References Cited | | | | | |
| | U.S. PATENT DOCUMENTS | | | | D716,759 S | 11/2014 Ha et al. |
| | | | | | D721,673 S | 1/2015 Park et al. |
| | | | | | D723,510 S | 3/2015 Ishikura |
| | 4,865,048 A | 9/1989 Eckerson | | | D724,197 S | 3/2015 Hughes |
| | 4,924,880 A | 5/1990 O'Neill et al. | | | D725,262 S | 3/2015 Chowdhury |
| | 4,995,404 A | 2/1991 Nemir | | | D728,109 S | 4/2015 Ko |
| | 5,259,762 A | 11/1993 Farrell | | | D730,867 S | 6/2015 Park |
| | 5,265,624 A | 11/1993 Bowman | | | D731,999 S | 6/2015 Cepress et al. |
| | 5,269,303 A | 12/1993 Wernicke et al. | | | 9,072,889 B1 | 7/2015 Guarraia et al. |
| | 5,299,569 A | 4/1994 Wernicke et al. | | | D739,122 S | 9/2015 Aimone et al. |
| | 5,540,734 A | 7/1996 Zabara | | | 9,124,979 B2 | 9/2015 O'Grady et al. |
| | 5,553,626 A | 9/1996 Burger et al. | | | D744,658 S | 12/2015 Hilkey-Boyatt |
| | 5,792,067 A | 8/1998 Karell | | | 9,993,641 B2 | 6/2018 Williams et al. |
| | 5,794,621 A | 8/1998 Hogan et al. | | | 2003/0220677 A1 | 11/2003 Doan et al. |
| | 5,878,154 A | 3/1999 Schimmelpfennig | | | 2004/0073270 A1 | 4/2004 Firlik et al. |
| | D409,307 S | 5/1999 Phleps et al. | | | 2004/0073271 A1 | 4/2004 Harry et al. |
| | 6,066,163 A | 5/2000 John | | | 2005/0089829 A1 | 4/2005 Wasowicz |
| | 6,089,864 A | 7/2000 Buckner et al. | | | 2005/0197529 A1 | 9/2005 Hoshihara et al. |
| | 6,161,044 A | 12/2000 Silverstone | | | 2005/0203582 A1 | 9/2005 Healy et al. |
| | D437,058 S | 1/2001 Gozani | | | 2005/0240253 A1 | 10/2005 Tyler et al. |
| | 6,169,781 B1 | 1/2001 Doeber et al. | | | 2006/0161218 A1 | 7/2006 Danilov |
| | 6,267,733 B1 | 7/2001 Peterson et al. | | | 2006/0241718 A1 | 10/2006 Tyler et al. |
| | D449,376 S | 10/2001 McDonald et al. | | | 2007/0248238 A1 | 10/2007 Abreu |
| | D449,883 S | 10/2001 McDonald et al. | | | 2007/0250119 A1 | 10/2007 Tyler et al. |
| | D451,598 S | 12/2001 McDonald et al. | | | 2007/0293917 A1 | 12/2007 Thompson et al. |
| | 6,326,901 B1 | 12/2001 Gonzales | | | 2007/0293918 A1 | 12/2007 Thompson et al. |
| | 6,339,725 B1 | 1/2002 Naritoku et al. | | | 2008/0009772 A1 | 1/2008 Tyler et al. |
| | 6,366,813 B1 | 4/2002 DiLorenzo | | | 2008/0027510 A1 | 1/2008 McClure et al. |
| | 6,366,814 B1 | 4/2002 Boveja et al. | | | 2008/0082131 A1 | 4/2008 Llanos |
| | 6,405,079 B1 | 6/2002 Ansarinia | | | 2008/0208287 A1 | 8/2008 Palermo et al. |
| | 6,430,450 B1 | 8/2002 Bach-y-Rita et al. | | | 2008/0222670 A1 | 9/2008 Lee et al. |
| | D462,357 S | 9/2002 Jenkins | | | 2008/0228239 A1 | 9/2008 Tyler et al. |
| | 6,463,328 B1 | 10/2002 John | | | 2008/0233541 A1 | 9/2008 De Vreese et al. |
| | 6,526,318 B1 | 2/2003 Ansarinia | | | 2008/0234604 A1 | 9/2008 Burgmans |
| | 6,54 | | | | | |

(56)

References Cited

FOREIGN PATENT DOCUMENTS

SU	1068128 A	1/1984
WO	02066111 A1	8/2002
WO	2014150090 A1	9/2014

OTHER PUBLICATIONS

Helius Medical Technologies, Inc., "Interchange PoNS Unit," Listing Statement, Form 2A, Jun. 20, 2014, 3 pages.

Helius Medical Technologies, Inc., "The PoNS Device," www.heliusmedical.com/divisions/neurohabilitation/pons-device, last visited Dec. 2, 2015, 4 pages.

Sidyakina I.V., "Swallowing rehabilitation of patients with serious diseases and brain injuries," Restorative medicine bulletin, 2011, No. 4, pp. 14-17.

Tyler, M.E. et al., "Non-invasive neuromodulation to improve gait in chronic multiple sclerosis: a randomized double blind controlled pilot trial," Journal of Neuroengineering and Rehabilitation, 2014, 10 pages.

US Army "Mouth Device in Clinical Trials as Possible Treatment for TBI," <https://www.army.mil/article/96521> (last visited Dec. 2, 2015), Feb. 14, 2013, 2 pages.

Hamilton, "Impact of Acoustic and Tactile Multi-Modal Stimulation on Objective and Subjective Measures of Permanent Intractable Tinnitus: A Prospective Research Study," Hamilton Institute, National University of Ireland Maynooth, Jun. 2014, 141 pages.

* cited by examiner




FIG. 1




FIG. 2A





FIG. 2B

FIG. 2C





FIG. 3A

FIG. 3B




FIG. 3C






FIG. 3D

FIG. 4AFIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A





FIG. 10B






FIG. 11A




FIG. 11B





FIG. 11C

FIG. 12




FIG. 13A




FIG. 13B




FIG. 14

1

METHODS OF MANUFACTURING DEVICES FOR THE NEUROREHABILITATION OF A PATIENT

CROSS REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 14/559,118, filed Dec. 3, 2014, now U.S. Pat. No. 9,656,060, which is incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

In general, the invention relates to devices and methods for non-invasive neurostimulation of a subject's brain. More specifically, the invention relates to devices and methods for non-invasive neurostimulation of a subject's brain to effect treatment of various maladies.

BACKGROUND OF THE INVENTION

Traumatic brain injury (TBI) is a leading cause of disability around the world. Each year in the United States, about two million people suffer a TBI, with many suffering long term symptoms. Long term symptoms can include impaired attention, impaired judgment, reduced processing speed, and defects in abstract reasoning, planning, problem-solving and multitasking.

A stroke is a loss of brain function due to a disturbance in the blood supply to the brain. Every year, about 800,000 people in the United States will have a stroke. Stroke is a leading cause of long-term disability in the United States, with nearly half of older stroke survivors experiencing moderate to severe disability. Long term effects can include seizures, incontinence, vision disturbance or loss of vision, dysphagia, pain, fatigue, loss of cognitive function, aphasia, loss of short-term and/or long-term memory, and depression.

Multiple sclerosis (MS) is a disease that causes damage to the nerve cells in the brain and spinal cord. Globally, there are about 2.5 million people who suffer from MS. Symptoms can vary greatly depending on the specific location of the damaged portion of the brain or spinal cord. Symptoms include hypoesthesia, difficulties with coordination and balance, dysarthria, dysphagia, nystagmus, bladder and bowel difficulties, cognitive impairment and major depression to name a few.

Alzheimer's disease (AD) is a neurodegenerative disorder affecting over 25 million people worldwide. Symptoms of AD include confusion, irritability, aggression, mood swings, trouble with language, and both short and long term memory loss. In developed countries, AD is one of the most costly diseases to society.

Parkinson's disease (PD) is a degenerative disorder of the central nervous system, affecting more than 7 million people globally. Symptoms of PD include tremor, bradykinesia, rigidity, postural instability, cognitive disturbances, and behavior and mood alterations.

One approach to treating the long term symptoms associated with TBI, stroke, MS, AD, and PD is neurorehabilitation. Neurorehabilitation involves processes designed to help patients recover from nervous system injuries. Traditionally, neurorehabilitation involves physical therapy (e.g., balance retraining), occupational therapy (e.g., safety training, cognitive retraining for memory), psychological therapy, speech and language therapy, and therapies focused on daily function and community re-integration.

2

Another approach to treating the long term symptoms associated with TBI, stroke, MS, AD, and PD is neurostimulation. Neurostimulation is a therapeutic activation of part of the nervous system. For example, activation of the nervous system can be achieved through electrical stimulation, magnetic stimulation, or mechanical stimulation. Typical approaches focused mainly on invasive techniques, such as deep brain stimulation (DBS), spinal cord stimulation (SCS), cochlear implants, visual prosthesis, and cardiac electrostimulation devices. Only recently have non-invasive approaches to neurostimulation become more mainstream.

Despite many advances in the areas of neurorehabilitation and neurostimulation, there exists an urgent need for treatments that employ a combined approach, including both neurorehabilitation and neurostimulation to improve the recovery of patients having TBI, stroke, multiple sclerosis, Alzheimer's, Parkinson's, depression, memory loss, compulsive behavior, or any other neurological impairment.

SUMMARY OF THE INVENTION

The invention, in various embodiments, features methods and devices for combining non-invasive neuromodulation with traditional neurorehabilitation therapies. Clinical studies have shown that methods combining neurostimulation with neurorehabilitation are effective in treating the long term neurological impairments due to a range of maladies such as TBI, stroke, MS, AD, and PD.

In one aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having (i) a non-planar exterior top surface and (ii) internal structural members disposed within the housing, the internal structural members elastically responding to biting forces generated by the patient. The mouthpiece also includes a spacer attached to the top surface of the housing for limiting contact between a patient's upper teeth and the exterior top surface of the elongated housing. The mouthpiece also includes a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. In some embodiments, the mouthpiece also includes ribs aligned parallel to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes ribs aligned parallel to a longitudinal axis of the elongated housing and ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes an interpenetrating network of ribs, with at least some of the ribs aligned parallel to a longitudinal axis of the elongated housing and at least some of the ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes pockets in a posterior portion of the elongated housing formed by the interpenetrating network of ribs. In some embodiments, the mouthpiece also includes integrated circuits located in the pockets. In some embodiments, the ribs have a rectangular cross section. In some embodiments, the ribs are comprised of arches. In some embodiments, the mouthpiece also includes one or more columns extending away from an interior surface of the elongated housing, the one or more columns configured to contact the mounted printed circuit board. In some embodiments, the structural elements can withstand a force of 700

3

Newtons without causing plastic deformation of the mouthpiece. In some embodiments, the mouthpiece also includes a rectangular sheet embedded on an interior surface of the elongated housing and located in a posterior region of the elongated housing, the rectangular sheet connecting the interpenetrating network of ribs. In some embodiments, the mouthpiece also includes a curvilinear sheet embedded on an interior surface of the elongated housing and located in a region connecting the anterior region and the posterior region of the elongated housing, the curvilinear sheet connecting the ribs aligned parallel to a longitudinal axis of the elongated housing.

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having (i) a non-planar exterior top surface and (ii) internal structural members disposed within the housing, the internal structural members elastically responding to biting forces generated by the patient. The mouthpiece also includes a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. In some embodiments, the mouthpiece also includes ribs aligned parallel to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes ribs aligned parallel to a longitudinal axis of the elongated housing and ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes an interpenetrating network of ribs, with at least some of the ribs aligned parallel to a longitudinal axis of the elongated housing and at least some of the ribs aligned perpendicular to a longitudinal axis of the elongated housing. In some embodiments, the mouthpiece also includes pockets in a posterior portion of the elongated housing formed by the interpenetrating network of ribs. In some embodiments, the mouthpiece also includes integrated circuits located in the pockets. In some embodiments, the ribs have a rectangular cross section. In some embodiments, the ribs are comprised of arches. In some embodiments, the mouthpiece also includes one or more columns extending away from an interior surface of the elongated housing, the one or more columns configured to contact the mounted printed circuit board. In some embodiments, the structural elements can withstand a force of 700 Newtons without causing plastic deformation of the mouthpiece.

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar interior top surface and internal fins located between the non-planar interior top surface and a bottom surface defined by a perimeter of the elongated housing, the internal fins forming a channel at the anterior region of the elongated housing. The mouthpiece also includes a spacer attached to the top surface of the housing for minimizing contact between a patient's upper teeth and the exterior top surface of the elongated housing. The mouthpiece also includes a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The mouthpiece also includes a cable having a first segment disposed within the housing and a second segment extending

4

from the housing, the cable mounted in an s-shaped pattern along the channel formed by the internal fins, one end of the first segment of the cable connected to the printed circuit board. In some embodiments, the mouthpiece also includes a right angled grommet mounted to an anterior region of the elongated housing, the grommet surrounding the cable as it exits the channel formed by the internal fins, the grommet forcing the cable to make an approximately ninety degree turn as it exits the elongated housing. In some embodiments, the cable forms two consecutive s-shapes along the channel formed by the internal fins. In some embodiments, the mouthpiece also includes a grommet mounted to an anterior region of the elongated housing, the grommet surrounding the cable as it exits the channel formed by the internal fins. In some embodiments, the mouthpiece also includes a cylindrically symmetric elastomeric element, the elastomeric element surrounding a portion of the cable and having a trench in a central portion thereof and surrounded by two regions having radii that decrease in relation to a distance from the trench. In some embodiments, the mouthpiece also includes an aperture located at an anterior region of the elongated housing, the aperture configured to form mechanical connection with the trench. In some embodiments, the mouthpiece also includes a cap, the cap having an elastomeric portion in contact with the printed circuit board and a rigid portion in contact with the elongated housing, the cap in cooperation with the elongated housing forming an aperture at an anterior region of the mouthpiece, the aperture configured to form mechanical connection with the trench. In some embodiments, the mouthpiece also includes a valley located in the interior surface of the elongated housing, the valley configured to receive the cable. In some embodiments, the mouthpiece also includes an elastomeric sleeve, the elastomeric sleeve in contact with the cable, and an anterior region of the elongated housing, the elastomeric sleeve providing resistance to bending and tensile strains in the cable.

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar interior top surface and a bottom surface defined by a perimeter of the elongated housing. The mouthpiece also includes a spacer attached to the top surface of the elongated housing for minimizing contact between a patient's upper teeth and the exterior top surface of the elongated housing. The mouthpiece also includes a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The mouthpiece also includes a first elastomeric ring located along an interior sidewall of the elongated housing, the first elastomeric ring forming a sealing surface with the printed circuit board. The mouthpiece also includes a plurality of mechanical protrusions extending from the interior sidewall of the elongated housing, the mechanical protrusions in contact with the printed circuit board. The mouthpiece also includes a cable having a first segment disposed within the housing and a second segment extending from the housing, one end of the first segment of the cable connected to the printed circuit board. In some embodiments, the mouthpiece also includes a valley located in the interior surface of the elongated housing, the valley configured to receive the cable. In some embodiments, the mouthpiece also includes internal fins extending from the interior top surface of the elongated housing, the internal fins forming a channel at an anterior

5

region of the elongated housing. In some embodiments, the cable forms at least two consecutive s-shapes along the channel formed by the internal fins. In some embodiments, the mouthpiece also includes a second elastomeric ring attached to the first elastomeric ring, the second elastomeric ring surrounding a portion of the cable and forming a connection between an anterior portion of the elongated housing and the cable. In some embodiments, the mouthpiece also includes a second elastomeric ring attached to the first elastomeric ring, the second elastomeric ring surrounding a portion of the cable and forming a connection between an anterior portion of the elongated housing and the cable, the second elastomeric ring causing the cable to exit the mouthpiece at an angle of 90 degrees.

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar interior top surface and internal fins located between the non-planar interior top surface and a bottom surface defined by a perimeter of the elongated housing, the internal fins forming a channel at the anterior region of the elongated housing. The mouthpiece also includes a printed circuit board mounted to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The mouthpiece also includes a cable having a first segment disposed within the housing and a second segment extending from the housing, the cable mounted in an s-shaped pattern along the channel formed by the internal fins, one end of the first segment of the cable connected to the printed circuit board. In some embodiments, the mouthpiece also includes a right angled grommet mounted to an anterior region of the elongated housing, the grommet surrounding the cable as it exits the channel formed by the internal fins, the grommet forcing the cable to make an approximately ninety degree turn as it exits the elongated housing. In some embodiments, the cable forms two consecutive s-shapes along the channel formed by the internal fins. In some embodiments, the mouthpiece also includes a grommet mounted to an anterior region of the elongated housing, the grommet surrounding the cable as it exits the channel formed by the internal fins. In some embodiments, the mouthpiece also includes a cylindrically symmetric elastomeric element, the elastomeric element surrounding a portion of the cable and having trench in a central portion thereof and surrounded by two regions having radii that decrease in relation to a distance from the trench. In some embodiments, the mouthpiece also includes an aperture located at an anterior region of the elongated housing, the aperture configured to form mechanical connection with the trench. In some embodiments, the mouthpiece also includes a cap, the cap having an elastomeric portion in contact with the printed circuit board and a rigid portion in contact with the elongated housing, the cap in cooperation with the elongated housing forming an aperture at an anterior region of the mouthpiece, the aperture configured to form mechanical connection with the trench. In some embodiments, the mouthpiece also includes a valley located in the interior surface of the elongated housing, the valley configured to receive the cable. In some embodiments, the mouthpiece also includes an elastomeric sleeve, the elastomeric sleeve in contact with the cable, and an anterior region of the elongated housing, the elastomeric sleeve providing resistance to bending and tensile strains in the cable.

6

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar exterior top surface. The mouthpiece also includes a spacer attached to the top surface of the housing for minimizing contact between a patient's upper teeth and the exterior top surface of the elongated housing. The mouthpiece also includes a first printed circuit board mounted to a bottom portion of the elongated housing, the first printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The mouthpiece also includes a rim extending from a bottom portion of the elongated housing, the rim surrounding a perimeter of the first printed circuit board and having a u-shaped cross section. The mouthpiece also includes a well shaped to accommodate an adhesive, the adhesive bonding the first printed circuit board to the elongate housing. In some embodiments, a portion of the rim rests below the first printed circuit board and prevents a patient's teeth from contacting the printed circuit board. In some embodiments, the first printed circuit board is non-planar and the plurality of electrodes are located on a non-planar surface of the first printed circuit board. In some embodiments, the first printed circuit board has a curved shape and the plurality of electrodes are located on a curved surface of the first printed circuit board. In some embodiments, the plurality of electrodes has a first density at an anterior region of the first printed circuit board and a second density at a posterior region of the first printed circuit board, wherein the first density is greater than the second density. In some embodiments, the mouthpiece also includes a second printed circuit board mounted above the first printed circuit board. In some embodiments, the rim is an integral part of the elongated housing. In some embodiments, the rim is dimensioned to define the glue well between the bottom portion of the elongated housing and the perimeter of the first printed circuit board. In some embodiments, the rim is concentric with the perimeter of the first printed circuit board. In some embodiments, the rim covers a bottom portion of the first printed circuit board along the perimeter thereof. In some embodiments, the rim covers a side portion of the first printed circuit board along the perimeter thereof. In some embodiments, the rim covers a bottom portion and a side portion of the first printed circuit board along the perimeter thereof.

In another aspect, the invention features a mouthpiece for providing non-invasive neuromodulation to a patient. The mouthpiece includes an elongated housing having an anterior region and a posterior region, the elongated housing having a non-planar exterior top surface. The mouthpiece also includes a spacer attached to the top surface of the housing for minimizing contact between a patient's upper teeth and the exterior top surface of the elongated housing. The mouthpiece also includes a first printed circuit board mounted to a bottom portion of the elongated housing, the first printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The mouthpiece also includes a rim extending from a bottom portion of the elongated housing, the rim surrounding a perimeter of the first printed circuit board. The mouthpiece also includes a beveled well configured to accommodate an adhesive, the adhesive bonding at least two orthogonal surfaces of the first printed circuit board to the elongated housing. In some embodiments, a portion of the rim rests below the first printed circuit board and prevents a patient's teeth from contacting the first printed circuit board.

In some embodiments, the first printed circuit board is non-planar and the plurality of electrodes are located on a non-planar surface of the first printed circuit board. In some embodiments, the first printed circuit board has a curved shape and the plurality of electrodes are located on a curved surface of the first printed circuit board. In some embodiments, the plurality of electrodes has a first density at an anterior region of the first printed circuit board and a second density at a posterior region of the first printed circuit board, wherein the first density is greater than the second density. In some embodiments, the mouthpiece also includes a second printed circuit board mounted above the first printed circuit board. In some embodiments, the rim is an integral part of the elongated housing. In some embodiments, the rim is dimensioned to define the glue well between the bottom portion of the elongated housing and the perimeter of the first printed circuit board. In some embodiments, the rim is concentric with the perimeter of the first printed circuit board. In some embodiments, the rim covers a bottom portion of the first printed circuit board along the perimeter thereof. In some embodiments, the rim covers a side portion of the first printed circuit board along the perimeter thereof. In some embodiments, the rim covers a bottom portion and a side portion of the first printed circuit board along the perimeter thereof.

In another aspect, the invention features a method of manufacturing a mouthpiece, the mouthpiece providing non-invasive neuromodulation to a patient. The method includes providing an elongated housing having internal fins located between a non-planar interior top surface and a bottom surface defined by a perimeter of the elongated housing, the internal fins forming a channel at the anterior region of the elongated housing. The method also includes attaching a spacer to the top surface of the elongated housing for minimizing contact between a patient's upper teeth and the exterior top surface of the elongated housing. The method also includes mounting a cable in an s-shaped pattern along the channel formed by the internal fins. The method also includes mounting a printed circuit board to a bottom portion of the elongated housing, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The method also includes connecting one end of the cable to the printed circuit board. In some embodiments, the method also includes forming a 90 degree bend in the cable at an exit of elongated housing. In some embodiments, the method also includes threading the cable through an elastomeric element located at the exit of the elongated housing. In some embodiments, the method also includes forming two consecutive s-shapes along the cable. In some embodiments, the method also includes mounting a cylindrically symmetric elastomeric element to the cable, the elastomeric element surrounding a portion of the cable and having a trench in a central portion thereof and surrounded by two regions having radii that decrease in relation to a distance from the trench. In some embodiments, the method also includes forming an aperture at an anterior region of the elongated housing, the aperture configured to form mechanical connection with the trench. In some embodiments, the method also includes providing a cap having an elastomeric portion and a rigid portion. In some embodiments, the method also includes contacting the elastomeric portion of the cap with the printed circuit board and contacting the rigid portion of the cap with the elongated housing. In some embodiments, the method also includes cooperatively forming an aperture with the cap and the elongated housing, the aperture forming a mechanical connection with the trench. In some embodi-

ments, the method also includes forming a valley located in the interior surface of the elongated housing. In some embodiments, the method also includes receiving a cable in the valley. In some embodiments, the method also includes forming an elastomeric sleeve around the cable, the elastomeric sleeve in contact with an anterior region of the elongated housing, the elastomeric sleeve providing resistance to bending and tensile strains in the cable. In some embodiments, the method also includes applying an adhesive along the perimeter of the printed circuit board, the adhesive bonding at least two orthogonal surfaces of the first printed circuit board to the elongated housing.

In another aspect, the invention features a method of manufacturing a mouthpiece, the mouthpiece providing non-invasive neuromodulation to a patient. The method includes providing an elongated housing having a plurality of mechanical protrusions extending from an interior sidewall thereof and first elastomeric ring located along an interior sidewall of the elongated housing. The method also includes attaching a spacer to the top surface of the elongated housing for minimizing contact between a patient's upper teeth and a top surface of the elongated housing. The method also includes contacting a printed circuit board to the first elastomeric ring of the elongated housing to form a seal, the printed circuit board having a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The method also includes providing a cable having a first segment disposed within the housing and a second segment extending from the housing. The method also includes connecting one end of the first segment of the cable connected to the printed circuit board. In some embodiments, the method also includes forming a 90 degree bend in the cable at an exit of elongated housing. In some embodiments, the method also includes threading the cable through an elastomeric element located at the exit of the elongated housing. In some embodiments, the method also includes forming two consecutive s-shapes along the cable. In some embodiments, the method also includes mounting a cylindrically symmetric elastomeric element to the cable, the elastomeric element surrounding a portion of the cable and having a trench in a central portion thereof and surrounded by two regions having radii that decrease in relation to a distance from the trench. In some embodiments, the method also includes forming an aperture at an anterior region of the elongated housing, the aperture configured to form mechanical connection with the trench. In some embodiments, the method also includes forming a valley located in the interior surface of the elongated housing. In some embodiments, the method also includes receiving a cable in the valley. In some embodiments, the method also includes forming an elastomeric sleeve around the cable, the elastomeric sleeve in contact with an anterior region of the elongated housing, the elastomeric sleeve providing resistance to bending and tensile strains in the cable.

In another aspect, the invention features a method of manufacturing a mouthpiece, the mouthpiece providing non-invasive neuromodulation to a patient. The method includes providing a printed circuit board, the printed circuit board having electronic circuitry and a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue. The method also includes forming an elongated housing directly onto the printed circuit board. The method also includes attaching a spacer to the top surface of the elongated housing for minimizing contact between a patient's upper teeth and a top surface of the elongated housing.

In some embodiments, the method also includes forming a strain relief mechanism integral with the elongated housing. In some embodiments, the method also includes providing a cable having a first segment disposed within the housing and a second segment extending from the housing. In some embodiments, the method also includes connecting one end of the first segment of the cable connected to the printed circuit board. In some embodiments, the method also includes encapsulating the electronic circuitry located on the printed circuit board.

As used herein, the terms “approximately,” “roughly,” and “substantially” mean $\pm 10\%$, and in some embodiments, $\pm 5\%$. Reference throughout this specification to “one example,” “an example,” “one embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the example is included in at least one example of the present technology. Thus, the occurrences of the phrases “in one example,” “in an example,” “one embodiment,” or “an embodiment” in various places throughout this specification are not necessarily all referring to the same example. Furthermore, the particular features, structures, routines, steps, or characteristics may be combined in any suitable manner in one or more examples of the technology. The headings provided herein are for convenience only and are not intended to limit or interpret the scope or meaning of the claimed technology.

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages of the invention described above, together with further advantages, may be better understood by referring to the following description taken in conjunction with the accompanying drawings. The drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

FIG. 1 is a drawing of a patient engaged in a non-invasive neurostimulation therapy session according to an illustrative embodiment of the invention.

FIGS. 2A and 2B are diagrams showing a neurostimulation system according to an illustrative embodiment of the invention.

FIG. 2C is a diagram showing a neurostimulation system according to an illustrative embodiment of the invention.

FIG. 3A is a diagram showing a more detailed view of the neurostimulation system depicted in FIGS. 2A and 2B.

FIG. 3B is a diagram showing a more detailed view of the neurostimulation system depicted in FIG. 2C.

FIG. 3C is a diagram showing a more detailed view of an electrode array.

FIG. 3D is a graph showing an exemplary sequence of pulses for effecting neurostimulation of a patient.

FIG. 4A is a flow chart illustrating a method in accordance with one embodiment for operating a neurostimulation system.

FIG. 4B is a flow chart illustrating a method in accordance with one embodiment for operating a neurostimulation system.

FIG. 5A is a diagram showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 5B is a diagram showing a side view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 5C is a diagram showing a top view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 5D is a diagram showing a bottom view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIGS. 5E and 5F are diagrams showing a bottom view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 6A is a diagram showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 6B is a diagram showing a bottom view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 6C is a diagram showing a glue well in accordance with an illustrative embodiment of the invention.

FIG. 6D is a diagram showing a glue well in accordance with an illustrative embodiment of the invention.

FIG. 7A is a diagram showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 7B is a diagram showing a bottom view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 7C is a diagram showing a sectional view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIGS. 8A and 8B are diagrams showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 8C is a diagram showing a sectional view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 8D is a diagram showing a sectional view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIGS. 9A and 9B are diagrams showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 9C is a diagram showing a sectional view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIGS. 10A and 10B are diagrams showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 10C is a diagram showing a sectional view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIGS. 11A and 11B are diagrams showing an isometric view of a mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 11C is a diagram showing an isometric view of the mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 12 is a flow chart illustrating a method in accordance with one embodiment for manufacturing a mouthpiece.

FIGS. 13A-B are diagrams showing an overmolded mouthpiece in accordance with an illustrative embodiment of the invention.

FIG. 14 is a diagram showing an overmolded mouthpiece in accordance with an illustrative embodiment of the invention.

DETAILED DESCRIPTION

FIG. 1 shows a patient 101 undergoing non-invasive neuromodulation therapy (NINM) using a neurostimulation system 100. During a therapy session, the neurostimulation system 100 non-invasively stimulates various nerves located

11

within the patient's oral cavity, including at least one of the trigeminal and facial nerves. In combination with the NINM, the patient engages in an exercise or other activity specifically designed to assist in the neurorehabilitation of the patient. For example, the patient can perform a physical therapy routine (e.g., moving an affected limb, or walking on a treadmill) engage in a mental therapy (e.g., meditation or breathing exercises), or a cognitive exercise (e.g., computer assisted memory exercises) during the application of NINM. The combination of NINM with an appropriately chosen exercise or activity has been shown to be useful in treating a range of maladies including, for example, traumatic brain injury, stroke (TBI), multiple sclerosis (MS), balance, gait, vestibular disorders, visual deficiencies, tremor, headache, migraines, neuropathic pain, hearing loss, speech recognition, auditory problems, speech therapy, cerebral palsy, blood pressure, relaxation, and heart rate. For example, a useful non-invasive neuromodulation (NINM) therapy routine has been recently developed as described in U.S. Pat. No. 8,849,407, the entirety of which is incorporated herein by reference.

FIGS. 2A and 2B show a non-invasive neurostimulation system 100. The non-invasive neurostimulation system 100 includes a controller 120 and a mouthpiece 140. The controller 120 includes a receptacle 126 and pushbuttons 122. The mouthpiece 140 includes an electrode array 142 and a cable 144. The cable 144 connects to the receptacle 126, providing an electrical connection between the mouthpiece 140 and the controller 120. In some embodiments, the controller 120 includes a cable. In some embodiments, the mouthpiece 140 and the controller 120 are connected wirelessly (e.g., without the use of a cable). During operation, a patient activates the neurostimulation system 100 by actuating one of the pushbuttons 122. In some embodiments, the neurostimulation system 100 periodically transmits electrical pulses to determine if the electrode array 142 is in contact with the patient's tongue and automatically activates based on the determination. After activation, the patient can start an NINM treatment session, stop the NINM treatment session, or pause the NINM treatment session by pressing one of the pushbuttons 122. In some embodiments, the neurostimulation system 100 periodically transmits electrical pulses to determine if the electrode array 142 is in contact with the patient's tongue and automatically pauses the NINM treatment session based on the determination. During an NINM treatment session, the patient engages in an exercise or other activity designed to facilitate neurorehabilitation. For example, during an NINM treatment session, the patient can engage in a physical exercise, a mental exercise, or a cognitive exercise. In some embodiments, the controller 120 has pushbuttons on both arms. In some embodiments, a mobile device can be used in conjunction with the controller 120 and the mouthpiece 140. The mobile device can include a software application that allows a user to activate the neurostimulation system 100 and start or stop an NINM treatment session by for example, pressing a button on the mobile device, or speaking a command into the mobile device. The mobile device can obtain patient information and treatment session information before, during, or after an NINM treatment session. In some embodiments, the controller 120 includes a secure cryptoprocessor that holds a secret key, to be described in more detail below in connection with FIGS. 9A and 9B. The secure cryptoprocessor is in communication with a microcontroller. The secure cryptoprocessor can be tamper proof. For example, if outer portions of the cryptoprocessor are removed in an

12

attempt to access the secret key, the cryptoprocessor erases all memory, preventing unauthorized access of the secret key.

FIG. 2C shows a non-invasive neurostimulation system 100. As shown, a mobile device 121 is in communication with a mouthpiece 140. More specifically, the mobile device 121 includes a processor running a software application that facilitates communications with the mouthpiece 140. The mobile device 121 can be, for example, a mobile phone, a portable digital assistant (PDA), or a laptop. The mobile device 121 can communicate with the mouthpiece 140 by a wireless or wired connection. During operation, a patient activates the neurostimulation system 100 via the mobile device 121. After activation, the patient can start an NINM treatment session, stop the NINM treatment session, or pause the NINM treatment session by manipulating the mobile device 121. During an NINM treatment session, the patient engages in an exercise or activity designed to provide neurorehabilitation. For example, during an NINM treatment session, the patient can engage in a physical exercise, a mental exercise, or a cognitive exercise.

FIG. 3A shows the internal circuitry housed within the controller 120. The circuitry includes a microcontroller 360, isolation circuitry 379, a universal serial bus (USB) connection 380, a battery management controller 382, a battery 362, a push-button interface 364, a display 366, a real time clock 368, an accelerometer 370, drive circuitry 372, tongue sense circuitry 374, audio feedback circuitry 376, vibratory feedback circuitry 377, and a non-volatile memory 378. The drive circuitry 372 includes a multiplexor, and an array of resistors to control voltages delivered to the electrode array 142. The microcontroller 360 is in electrical communication with each of the components shown in FIG. 3A. The isolation circuitry 379 provides electrical isolation between the USB connection 380 and all other components included in the controller 120. Additionally, the circuitry shown in FIG. 3A is in communication with the mouthpiece 140 via the external cable 144. During operation, the microcontroller 360 receives electrical power from battery 362 and can store and retrieve information from the non-volatile memory 378. The battery can be charged via the USB connection 380. The battery management circuitry controls the charging of the battery 362. A patient can interact with the controller 120 via the push-button interface 122 that converts the patient's pressing of a button (e.g. an info button, a power button, an intensity-up button, an intensity-down button, and a start/stop button) into an electrical signal that is transmitted to the microcontroller 360. For example, a therapy session can be started when the patient presses a start/stop button after powering on the controller 120. During the therapy session, the drive circuitry 372 provides an electrical signal to the mouthpiece 140 via the cable 144. The electrical signal is communicated to the patient's intraoral cavity via the electrode array 142. The accelerometer 370 can be used to provide information about the patient's motion during the therapy session. Information provided by the accelerometer 370 can be stored in the non-volatile memory 378 at a coarse or detailed level. For example, a therapy session aggregate motion index can be stored based on the number of instances where acceleration rises above a predefined threshold, with or without low pass filtering. Alternatively, acceleration readings could be stored at a predefined sampling interval. The information provided by the accelerometer 370 can be used to determine if the patient is engaged in a physical activity. Based on the information received from the accelerometer 370, the microcontroller 360 can determine an activity level of the patient during a therapy session. For

13

example, if the patient engages in a physical activity for 30 minutes during a therapy session, the accelerometer 370 can periodically communicate (e.g. once every second) to the microcontroller 360 that the sensed motion is larger than a predetermined threshold (e.g. greater than 1 m/s^2). In some embodiments, the accelerometer data is stored in the non-volatile memory 378 during the therapy session and transmitted to the mobile device 121 after the therapy session has ended. After the therapy session has ended, the microcontroller 360 can record the amount of time during the therapy session in which the patient was active. In some embodiments, the recorded information can include other data about the therapy session (e.g., the date and time of the session start, the average intensity of electrical neurostimulation delivered to the patient during the session, the average activity level of the patient during the session, the total session time the mouthpiece has been in the patient's mouth, the total session pause time, the number of session shorting events, and/or the length of the session or the type of exercise or activity performed during the therapy session) and can be transmitted to a mobile device. A session shorting event can occur if the current transmitted from the drive circuitry to the electrode array 142 exceeds a predetermined threshold or if the charge transmitted from the drive circuitry to the electrode array exceeds a predetermined threshold over a predetermined time interval. After a session shorting event has occurred, the patient must manually press a pushbutton to resume the therapy session. The real time clock (RTC) 368 provides time and date information to the microcontroller 360. In some embodiments, the controller 120 is authorized by a physician for a predetermined period of time (e.g., two weeks). The RTC 368 periodically communicates date and time information to the microcontroller 360. In some embodiments, the RTC 368 is integrated with the microcontroller. In some embodiments, the RTC 368 is powered by the battery 362, and upon failure of the battery 362, the RTC 368 is powered by a backup battery. After the predetermined period of time has elapsed, the controller 120 can no longer initiate the delivery of electrical signals to the mouthpiece 140 and the patient must visit the physician to reauthorize use of the controller 120. The display 366 displays information received by the microcontroller 360 to the patient. For example, the display 366 can display the time of day, therapy information, battery information, time remaining in a therapy session, error information, and the status of the controller 120. The audio feedback circuitry 376 and vibratory feedback circuitry 377 can give feedback to a user when the device changes state. For example, when a therapy session begins, the audio feedback circuitry 376 and the vibratory feedback circuitry 377 can provide auditory and/or vibratory cues to the patient, notifying the patient that the therapy session has been initiated. Other possible state changes that may trigger audio and/or vibratory cues include pausing a therapy session, resuming a therapy session, the end of a timed session, canceling a timed session, or error messaging. In some embodiments, a clinician can turn off one or more of the auditory or vibratory cues to tailor the feedback to an individual patient's needs. The tongue sense circuitry 374 measures the current passing from the drive circuitry to the electrode array 142. Upon sensing a current above a predetermined threshold, the tongue sense circuitry 374 presents a high digital signal to the microcontroller 360, indicating that the tongue is in contact with the electrode array 142. If the current is below the predetermined threshold, the tongue sense circuitry 374 presents a low digital signal to the microcontroller 360, indicating that the tongue is not in contact or is in partial contact with the

14

electrode array 142. The indications received from the tongue sense circuitry 374 can be stored in the non-volatile memory 378. In some embodiments, the display 366 can be an organic light emitting diode (OLED) display. In some embodiments, the display 366 can be a liquid crystal display (LCD). In some embodiments, a display 366 is not included with the controller 120. In some embodiments, neither the controller 120 nor the mouthpiece 140 includes a cable, and the controller 120 communicates wirelessly with the mouthpiece 140. In some embodiments, neither the controller 120 nor the mouthpiece 140 includes an accelerometer. In some embodiments, the drive circuitry 372 is located within the mouthpiece. In some embodiments, a portion of the drive circuitry 372 is located within the mouthpiece 140 and a portion of the drive circuitry 372 is located within the controller 120. In some embodiments, neither the controller 120 nor the mouthpiece 140 includes tongue sense circuitry 374. In some embodiments, the mouthpiece 140 includes a microcontroller and a multiplexer.

FIG. 3B shows a more detailed view of FIG. 2C. The mouthpiece 140 includes a battery 362, tongue sense circuitry 374, an accelerometer 370, a microcontroller 360, drive circuitry 372, a non-volatile memory 378, a universal serial bus controller (USB) 380, and battery management circuitry 382. During operation, the microcontroller receives electrical power from battery 362 and can store and retrieve information from the non-volatile memory 378. The battery can be charged via the USB connection 380. The battery management circuitry 382 controls the charging of the battery 362. A patient can interact with the mouthpiece 140 via the mobile device 121. The mobile device 121 includes an application (e.g. software running on a processor) that allows the patient to control the mouthpiece 140. For example, the application can include an info button, a power button an intensity-up button, an intensity-down button, and a start/stop button that are presented to the user visually via the mobile device 121. When the patient presses a button presented by the application running on the mobile device 121, a signal is transmitted to the microcontroller 360 housed within the mouthpiece 140. For example, a therapy session can be started when the patient presses a start/stop button on the mobile device 121. During the therapy session, the drive circuitry 372 provides an electrical signal to an electrode array 142 located on the mouthpiece 140. The accelerometer 370 can be used to provide information about the patient's motion during the therapy session. The information provided by the accelerometer 370 can be used to determine if the patient is engaged in a physical activity. Based on the information received from the accelerometer 370, the microcontroller 360 can determine an activity level of the patient during a therapy session. For example, if the patient engages in a physical activity for 30 minutes during a therapy session, the accelerometer 370 can periodically communicate (e.g. once every second) to the microcontroller 360 that the sensed motion is larger than a predetermined threshold (e.g. greater than 1 m/s^2). After the therapy session has ended, the microcontroller 360 can record the amount of time during the therapy session in which the patient was active. In some embodiments, the accelerometer 370 is located within the mobile device 121 and the mobile device 121 determines an activity level of a patient during the therapy session based on information received from the accelerometer 370. The mobile device can then record the amount of time during the therapy session in which the patient was active. The mobile device 121 includes a real time clock (RTC) 368 that provides time and date information to the microcontroller 360. In some embodiments, the

15

mouthpiece **140** is authorized by a physician for a predetermined period of time (e.g., two weeks). After the predetermined period of time has elapsed, the mouthpiece **140** can no longer deliver electrical signals to the patient via the electrode array **142** and the patient must visit the physician to reauthorize use of the mouthpiece **140**. In some embodiments, the mouthpiece **140** includes pushbuttons (e.g., an on/off button) and a patient can manually operate the mouthpiece **140** via the pushbuttons. After a therapy session, the mouthpiece **140** can transmit information about the therapy session to a mobile device. In some embodiments, the mouthpiece **140** does not include a USB controller **380** and instead communicates only via wireless communications with the controller.

FIG. 3C shows a more detailed view of the electrode array **142**. The electrode array **142** can be separated into 9 groups of electrodes, labelled a-i, with each group having 16 electrodes, except group b which has 15 electrodes. Each electrode within the group corresponds to one of 16 electrical channels. During operation, the drive circuitry can deliver a sequence of electrical pulses to the electrode array **142** to provide neurostimulation of at least one of the patient's trigeminal or facial nerve. The electrical pulse amplitude delivered to each group of electrodes can be larger near a posterior portion of the tongue and smaller at an anterior portion of the tongue. For example, the pulse amplitude of electrical signals delivered to groups a-c can be 19 volts or 100% of a maximum value, the pulse amplitude of electrical signals delivered to groups d-f can be 14.25 volts or 75% of the maximum value, the pulse amplitude of electrical signals delivered to groups g-h can be 11.4 volts or 60% of the maximum value, and the pulse amplitude of electrical signals delivered to group i can be 9.025 volts or 47.5% of the maximum value. In some embodiments, the maximum voltage is in the range of 0 to 40 volts. The pulses delivered to the patient by the electrode array **142** can be random or repeating. The location of pulses can be varied across the electrode array **142** such that different electrodes are active at different times, and the duration and/or intensity of pulses may vary from electrode. For oral tissue stimulation, currents of 0.5-50 mA and voltages of 1-40 volts can be used. In some embodiments, transient currents can be larger than 50 mA. The stimulus waveform may have a variety of time-dependent forms, and for cutaneous electrical stimulation, pulse trains and bursts of pulses can be used. Where continuously supplied, pulses may be 1-500 microseconds long and repeat at rates from 1-1000 pulses/second. Where supplied in bursts, pulses may be grouped into bursts of 1-100 pulses/burst, with a burst rate of 1-100 bursts/second.

In some embodiments, pulsed waveforms are delivered to the electrode array **142**. FIG. 3D shows an exemplary sequence of pulses that can be delivered to the electrode array **142** by the drive circuitry **372**. A burst of three pulses, each spaced apart by 5 ms is delivered to each of the 16 channels. The pulses in neighboring channels are offset from one another by 312.5 μ s. The burst of pulses repeats every 20 ms. The width of each pulse can be varied from 0.3-60 μ s to control an intensity of neurostimulation (e.g., a pulse having a width of 0.3 μ s will cause a smaller amount of neurostimulation than a pulse having a width of 60 μ s).

FIG. 4A shows a method of operation **400** of a controller **120** as described in FIGS. 2A, 2B and 3A. A patient attaches a mouthpiece **140** to a controller **120** (step **404**). The patient turns on the controller **120** (step **408**) using, for example, a power button. The patient places the controller **120** around his/her neck (step **412**) as shown in FIG. 1B. The patient places a mouthpiece **140** in his/her mouth (step **416**). The

16

patient initiates a therapy session by pressing a start/stop button (step **420**). During the therapy session, the controller **120** delivers electrical signals to the mouthpiece **140**. The patient calibrates the intensity of the electrical signals (step **424**). The patient raises the intensity of the electrical signals delivered to the mouthpiece by pressing an intensity-up button until the neurostimulation is above the patient's sensitivity level. The patient presses an intensity-down button until the neurostimulation is comfortable and non-painful. After the calibration step, the patient performs a prescribed exercise (step **428**). The exercise can be cognitive, mental, or physical. In some embodiments, physical exercise includes the patient attempting to maintain a normal posture or gait, the patient moving his/her limbs, or the patient undergoing speech exercises. Cognitive exercises can include "brain training" exercises, typically computerized, that are designed to require the use of attention span, memory, or reading comprehension. Mental exercises can include visualization exercises, meditation, relaxation techniques, and progressive exposure to "triggers" for compulsive behaviors.

In some embodiments, the patient can rest for a period of time during the therapy session (e.g. the patient can rest for 2 minutes during a 30 minute therapy session). After a predetermined period of time (for example, thirty minutes) has elapsed, the therapy session ends (step **432**) and the controller **120** stops delivering electrical signals to the mouthpiece **140**. In some embodiments, the intensity of electrical signals increases from zero to the last use level selected by the patient over a time duration in the range of 1-5 seconds after the patient starts a therapy session by pressing the start/stop button. In some embodiments, the intensity of electrical signals is set to a fraction of the last use level selected by the patient (e.g. $\frac{3}{4}$ of the last level selected) after the patient starts a therapy session by pressing the start/stop button. In some embodiments, the intensity of electrical signals increases from zero to a fraction of the last use level selected by the patient (e.g. $\frac{3}{4}$ of the last level selected) over a time duration in the range of 1-5 seconds after the patient starts a therapy session by pressing the start/stop button. In some embodiments, the intensity of electrical signals increases instantaneously from zero to the last use level selected by the patient after the patient starts a therapy session by pressing the start/stop button.

In some embodiments, the mouthpiece **140** is connected to the controller **120** after the controller **120** is turned on. In some embodiments, the mouthpiece **140** is connected to the controller **120** after the controller **120** is donned by the patient. In some embodiments, the patient calibrates the intensity of the electrical signals before initiating a therapy session. In some embodiments, a patient performs an initial calibration of the intensity of electrical signals in the presence of a clinician and does not calibrate the intensity of the electrical signals during subsequent treatments performed in the absence of a clinician.

FIG. 4B shows a method of operation **449** of the non-invasive neurostimulation system **100** described in FIGS. 2C and 3B. A patient activates a mobile device **121** (step **450**). The patient places a mouthpiece **140** in his/her mouth (step **454**). The patient initiates a therapy session by pressing a start/stop button within an application running on the mobile device **121** (step **458**). During the therapy session, circuitry within the mouthpiece **140** delivers electrical signals to an electrode array **142** located on the mouthpiece **140**. The patient calibrates the intensity of the electrical signals (step **462**). The patient first raises the intensity of the electrical signals delivered to the mouthpiece **140** by pressing an

intensity-up button located within an application running on the mobile device **121** until the neurostimulation is above the patient's sensitivity level. The patient presses an intensity-down button running within an application on the mobile device **121** until the neurostimulation is comfortable and non-painful. After the calibration step, the patient performs a prescribed exercise (step **464**). The exercise can be cognitive, mental, or physical. In some embodiments, the patient can rest for a period of time during the therapy session (e.g. the patient can rest for 5 minutes during a 30 minute therapy session). After a predetermined period of time (for example, thirty minutes) has elapsed, the therapy session ends (step **468**) and the circuitry located within the mouthpiece **140** stops delivering electrical signals to the electrode array **142**. In some embodiments, the calibration of the intensity of the electrical signals takes place before the patient initiates a therapy session.

FIGS. **5A-5F** show a mouthpiece **500**. The mouthpiece **500** includes a housing **504**, a spacer **508**, a transition region **520**, a posterior region **524**, an anterior region **528**, a printed circuit board **532**, internal circuitry **533**, an electrode array **542**, and a cable **544**. The housing **504** includes an outer shell **505**, longitudinal ribs **550**, transverse ribs **551**, columns **552**, valleys **553**, shoring **554**, pockets **555**, and a platform **558**. The mouthpiece **500** has three regions, a posterior region **524**, a transition region **520**, and an anterior region **528**. The transition region **520** smoothly connects the anterior region **528** with the posterior region **524**. The printed circuit board **532** attaches to the bottom side of the housing **504**. The internal circuitry **533** is mounted to the top side of the printed circuit board **532** and is covered by the housing **504**. The cable **544** is in communication with the internal circuitry **533** and the internal circuitry **533** is in communication with the electrode array **542**. The outer shell **505** of the housing **504** has an exemplary thickness in the range of 0.5 to 2 mm. The outer shell can be made of glass filled nylon, nylon, acrylonitrile butadiene styrene (ABS), polycarbonate (PC), polyether ether ketone (PEEK), alloy metal, or metal, having a compression strength in the range of 375 to 590N. In some embodiments, the outer shell **505** has two different thicknesses. For example, the anterior region of the outer shell **505** can have a thickness in the range of 1.2 to 2 mm and the posterior region can have a thickness in the range of 0.5 to 1.2 mm. The thickness of the outer shell **505** can vary smoothly in the transition region such that there are no discontinuities or steps in the thickness of the outer shell **505**. In some embodiments, the thickness of the outer shell **505** in the anterior region is chosen to withstand biting by the patient. In some embodiments, the thickness of the outer shell **505** in the posterior region is selected to provide retention of the mouthpiece **500**, thereby preventing accidental ejection of the mouthpiece **500**. By itself, the outer shell **505** cannot withstand biting forces from the patient (e.g., the outer shell undergoes significant deflections and/or experiences plastic deformation). The longitudinal ribs **550**, transverse ribs **551**, columns **552**, shoring **554**, and platform **558** can provide structural support for the outer shell **505** to prevent damage due to biting by the patient. The longitudinal ribs **550** can extend longitudinally along the housing **504**. The longitudinal ribs **550** can be regularly spaced, creating valleys **553** therebetween as shown in FIG. **5E**. Internal circuitry **533** can be located in the valleys **553**. In an exemplary embodiment, the longitudinal ribs **550** have a width in the range of 0.5 to 2 mm, and a height that varies from approximately 6 mm in the posterior region **524** to 1 mm in the anterior region **528**. In some embodiments, the longitudinal ribs are irregularly spaced,

with the spacing between ribs being larger towards the perimeter of the outer shell **505** and smaller towards a central portion of the outer shell **505**. In some embodiments, the longitudinal ribs are separated by a distance in the range of 4 to 9.0 mm as measured from center to center. The transverse ribs **551** can be located in the posterior region **524** and traverse a width of the housing **504**. The transverse ribs can be spaced regularly, as shown in FIG. **5E**. In an exemplary embodiment, the transverse ribs **551** have a width of in the range of 0.5 to 1.5 mm, and a height of in the range of 4 to 7 mm. In some embodiments, the transverse ribs **551** can intersect with the longitudinal ribs **550**, creating pockets **555** as shown in FIG. **5E**. Internal circuitry **533** can be located in the pockets **555**. In some embodiments, the transverse ribs are irregularly spaced, with the spacing between ribs being larger towards the perimeter of the outer shell **505** and smaller towards a central portion of the outer shell **505**. The column **552** can have a rectangular cross section and be located in an anterior region **528** of the housing **504**. In some embodiments, one or more columns **552** are regularly spaced and traverse a width of the housing **504**. The columns **552** can provide resistance to compressive forces exerted on the mouthpiece **500**, thereby providing protection of the internal circuitry **533**. The columns **552** can have a thickness in the range of 0.5 to 2 mm. In some embodiments, the height of the columns **552** is greater than the thickness of the internal circuitry **533**, thereby providing a clearance between the internal circuitry **533** and the outer shell **505**. In some embodiments, the height of the columns **552** is at least 1 mm greater than the thickness of the internal circuitry **533**. In some embodiments, the platform **558** is directly connected to one or more longitudinal ribs and one or more transverse ribs, thereby providing increased capacity to withstand shear and compressive loads. The thickness of the platform **558** can be in the range of 1.5 to 3.5 mm. In some embodiments, the shoring **554** includes a layer of material with a thickness greater than the thickness of the outer shell **505**. The thickness of the shoring **554** can be in the range of 0.5 to 2 mm. In some embodiments, the thickness of the outer shell **505** is smaller in the region of the shoring **554** than in other regions to accommodate the spacer **508**. For example, the thickness of the outer shell can be 1.5 mm in the anterior and posterior regions and 0.5 mm in the region of the shoring **554**. During operation, a patient places a portion of the mouthpiece **500** in his/her mouth to engage in an NINM therapy session. The patient bites down on the mouthpiece **500** with his/her front teeth to secure a position of the mouthpiece. The patient's bottom teeth contact the printed circuit board **532** and the patient's tongue contacts the electrode array **542**. In some embodiments, the patient relaxes his/her mouth to secure a position of the mouthpiece. The internal circuitry delivers electrical neurostimulation signals to the patient's tongue via the electrode array **542**. In some embodiments, the spacer **508** can provide a soft and comfortable bite surface so that stress is not concentrated at small areas where the patient's teeth contact the mouthpiece **500** during biting. For example, the spacer **508** can be made from thermoplastic polyurethane (TPU), thermoplastic elastomer (TPE), or silicone. In some embodiments, the transverse ribs **551** are located in the anterior region and traverse a width of the housing **504**.

FIGS. **6A-6B** show a more detailed view of the outer shell **505**. The outer shell includes a glue well **570**, internal fins **561** and **562**, and a central longitudinal axis **590**. The internal fins include at least one pair of entrance fins **561**. The entrance fins **561** can be symmetric about the longitudinal axis **590** and can guide the cable **544** along the

longitudinal axis **590** without causing substantial bending thereof. A glue, adhesive, or epoxy can provide a rigid mechanical connection between the cable **544** and the entrance fins **561**. For example, the glue, adhesive, or epoxy can be a UV cured adhesive, or cyanoacrylate. The internal fins also include an even number of guiding fins **562**. In some embodiments, the internal fins include an odd number of guiding fins **562**. For example, the internal fins can include three guiding fins. In some embodiments, the guiding fins **562** are not symmetric about the longitudinal axis **590**, with each guiding fin **562** causing an approximately 90 degree bend in the cable **544**, and each bend having a radius of curvature approximately equal to two diameters of the cable **544**. In some embodiment, each guiding fin **562** causes a bend in the cable **544** of greater than 90 degrees, but less than 180 degrees. The guiding fins provide frictional resistance greater than the weight of the mouthpiece. In some embodiments, the guiding fins provide frictional resistance greater than the forces required to disconnect the mouthpiece **140** from the controller **120**. In some embodiments, a rubber grommet **563** provides an elastic mechanical attachment between the outer shell **505** and the cable **544** with the outer shell **505** providing a resistance that counteracts any bending strain applied to the cable **544** (e.g., the patient may accidentally pull or tug on the cable while the mouthpiece **500** is secured within the patient's mouth). In some embodiments, the spacer **508** includes an elastomeric element that provides a mechanical connection between the cable **544** and the entrance fins **561**. The elastomeric element provides a frictional force that provides a frictional resistance that counteracts any bending stress applied to the cable **544**. In some embodiments, the cable **544** can exit the outer shell at a 90 degree angle and be attached to the outer shell by an epoxy, the epoxy providing mechanical resistance of up to 100 Newtons to accommodate bending strains induced by the patient. In some embodiments, the cable **544** is attached to the outer shell by an adhesive or glue. In some embodiments, the cable **544** can exit the outer shell at a 90 degree angle and be mechanically attached to the outer shell by a right-angled elastomeric element, the right-angled elastomeric element interlocking with the outer shell and providing mechanical resistance of up to 100 Newtons to accommodate both bending and tensile strains induced by the patient.

FIG. 6C shows a more detailed cross sectional view of the glue well **570**. The glue well **570** is located along an outer boundary of the outer shell **505** and accommodates an adhesive (e.g., a biomedical compatible epoxy or glue) that provides a mechanical connection between the printed circuit board **532** and the outer shell **505**. The glue well **570** includes a beveled lip **571**, and a discontinuously connected cross-section that includes a concave portion **572** and a vertical portion **573** that intersect to form a lowest point of the glue well **570**. In some embodiments, the shape of the glue well can be trapezoidal. In some embodiments, the shape of the glue well can be wedged. In some embodiments, the shape of the glue well can be triangular. In some embodiments, the shape of the glue well can be rectangular. In some embodiments, a portion of the glue well can overhang the printed circuit board **532**, thereby protecting portions of the printed circuit board from the teeth of the

patient. In some embodiments, the adhesive is in contact with the outer shell **505** and the top of the printed circuit board **532**. In some embodiments, the adhesive is in contact with the outer shell **505** and the top and side portions of the printed circuit board **532**. In some embodiments, the glue well is shaped such that the adhesive is in contact with the outer shell **505** and the side portions of the printed circuit board **532**, but only has negligible contact with the top portion of the printed circuit board **532** (e.g., the glue well can have a width greater than a depth).

FIG. 6D shows an embodiment where the outer shell **505** includes two glue wells, **570** and **574**. A first glue well **570** and a second glue well **574** are located along an outer boundary of the outer shell **505** and accommodate an adhesive (e.g., a biomedical compatible epoxy) that provides a mechanical connection between the printed circuit board **532** and the outer shell **505**. The second glue well **574** is designed to accommodate a glue or adhesive that overflows from the first glue well **570**, thereby preventing glue or adhesive from overflowing onto the bottom side of the printed circuit board. A step **578** is positioned between the first and second glue well to define the height of the first glue well.

FIGS. 7A-7C show a mouthpiece **700**. The mouthpiece **700** includes an outer shell **705** having a central longitudinal axis **790**, a spacer **708**, a cable **744**, a sleeve **764**, exit fins **761**, a glue well **770**. The sleeve **764** is integrated with the cable **744** and mechanically couples the cable **744** with the outer shell **705**. The sleeve **764** includes two tapered outer portions **765** and a gap **766** separating the two tapered outer portions. The cable **744** can be pulled towards the outer shell **705** until the gap **766** is aligned with an outer boundary of the mouthpiece **700**. Once aligned with the outer shell **705**, the sleeve **764** provides a mechanical resistance of up to 100 Newtons to counteract both tensile and bending stresses applied to the cable **744**. The cable **744** may additionally be clamped between the printed circuit board **732** and the outer shell **705** as shown in FIG. 7C. The additional clamping can provide additional mechanical resistance to tensile stresses applied to the cable **744**.

FIGS. 8A-8D show a mouthpiece **800**. The mouthpiece **800** includes an outer shell **805**, a spacer **808**, a printed circuit board **832**, a cable **844**, a sleeve **864**, a glue well **870**, and a clamp **809**. A posterior portion of the cable **844** is connected to the printed circuit board **832** via solder, ribbon connector, or other mechanical connection. The sleeve **864** is integrated with the cable **844** and mechanically couples the cable **844** with the outer shell **805** and clamp **809**. The sleeve **864** is similar to the sleeve **764**, having two tapered outer portions and a gap. Instead of being pulled through the outer shell **805** as shown in FIGS. 7A and 7B, the sleeve **864** is secured by a clamp **809** that connects to a bottom portion of the outer shell **805**. The clamp **809** mechanically secures the printed circuit board **832** to the outer shell **805** and in addition, secures the sleeve **864** to the outer shell **805**. In some embodiments, adhesive or glue is added to the glue well **870** to secure the printed circuit board **832** to the outer shell **805**. The sleeve **864** provides mechanical resistance (up to 100 Newtons) to bending stresses and tensile stresses in the cable **844**. The clamp **809** includes a rigid plastic portion **809b** and an elastomeric portion **809a**. The rigid plastic portion **809b** provides structural integrity, while the elastomeric portion **809a** provides a sealing mechanism. For example, the clamp **809** can be placed into contact with the outer shell **805** as shown in FIG. 8D. A narrow protrusion **810** extends from the rigid plastic portion **809b** of the clamp **809**, the narrow protrusion **810** interlocking with a recessed

21

portion **806** of the outer shell **805**. The elastomeric portion **809a** contacts the outer shell **805**, the glue well **870**, and the printed circuit board **832**, forming an air tight seal. The air tight seal can protect portions of the printed circuit board **832** from moisture. In some embodiments, the clamp **809** is secured to the outer shell **805** by adding an adhesive or glue to the glue well **870** that contacts both the outer shell and the clamp.

FIGS. 9A-9C show a mouthpiece **900**. The mouthpiece **900** includes an outer shell **905**, a printed circuit board **932**, a cable **944**, a glue well **970**, a boot **945**. The outer shell **905** includes a valley **971** and a glue well **970**. The valley **971** guides the cable **944** within the outer shell **905**, and the glue well **970** accommodates an epoxy or other adhesive to provide a mechanical connection between the printed circuit board **932**, the outer shell **905**, and the cable **944**. The shape of the glue well **970** can be a wedge shape to advantageously provide an interface between the adhesive or epoxy and the printed circuit board **932**, the outer shell **905**, and the cable **944**. A protrusion **946** extends from the outer shell **905** and interlocks with a recessed portion **947** of the boot **945**. The interlocked boot **945** is in mechanical contact along an outer diameter of the cable **944** (e.g., the interlocked boot **945** can be in contact with the outer diameter of the cable **944** for a distance in the range of 0.5 to 10 mm). In some embodiments, the interlocked boot **945** can be overmolded, or glued onto the cable **944**. In some embodiments, the interlocked boot **945** is mechanically coupled to the cable **944**. The interlocked boot **945** can provide mechanical resistance to tugging or pulling (e.g., up to 100 Newtons) of the cable by the patient. In some embodiments, the interlocked boot can provide resistance to both bending strains and tensile strains. In some embodiments, the boot **945** can cover the glue well **970**. In some embodiments, the boot **945** can be extended to cover portions of the printed circuit board **932** that are not covered by an electrode array.

FIGS. 10A-10C show a mouthpiece **1000**. The mouthpiece **1000** includes an outer shell **1005**, a printed circuit board **1032**, a cable **1044**, a valley **1071**, a sealing ring **1081**, and clips **1080**. Epoxy and/or adhesives are not present in mouthpiece **1000**. The printed circuit board **1032** contacts the sealing ring **1081** and is held in place by clips **1080**. The clips **1080** can have vertical sidewall and a downward sloping overhang as shown in FIG. 10B. In some embodiments, the clips are spaced along an inner boundary of the outer shell **1005**. The cable **1044** is electrically connected to the printed circuit board **1032**. Additionally, the sealing ring **1081** forms an aperture at an anterior region of the outer shell **1005**, with the cable **1044** passing through the aperture. The valley **1071** guides the cable **1044** from the printed circuit board **1132** to the aperture. The aperture is in contact with the cable **1044** and provides resistance to tugging or pulling of the cable **1044** by the patient. In some embodiments, the aperture can provide resistance to both bending and tensile strains on the cable **1044**. In some embodiments, the sealing ring **1081** is composed of a low durometer elastomer such as TPE, TPU, or silicone. In some embodiments, the sealing ring can be replaced by a glue well or a layer of glue.

FIGS. 11A-11C show a mouthpiece **1100**. The mouthpiece **1100** includes an outer shell **1105**, a printed circuit board **1132**, a cable **1144**, and a fastener **1191**. The outer shell includes a glue well **1170**, a valley **1171**, and a port **1172** shaped to accommodate the fastener **1191**. The glue well **1170** can accommodate an epoxy or other adhesive that connects the outer shell **1105** to the printed circuit board **1132**. The cable **1144** is attached to the printed circuit board

22

1132 via solder, ribbon cable, or other mechanical connector. The cable rests in the valley **1171** before exiting at port **1172**. An O-ring surrounds the cable **1144** at the port **1172**. The fastener **1191** attaches to the outer shell **1105** at the position of the port **1172**. The fastener applies a force to the O-ring that holds the cable in place at the port. The O-ring together with the fastener **1172** protect the cable from pulling or tugging by the patient. In some embodiments, the O-ring and the fastener **1172** provide resistance to both bending and tensile strain. In some embodiments, an epoxy or adhesive surrounds the cable **1144** at the port **1172**.

FIG. 12 shows a method **1200** of manufacturing a mouthpiece such as the mouthpiece shown in FIGS. 5A-5F. Initially, a housing is provided (step **1204**). A spacer is attached to the housing (step **1208**). In some embodiments, the spacer is molded directly onto the housing. In some embodiments, the spacer attached to the housing via an adhesive or glue. The housing is attached to the printed circuit board (step **1212**). In some embodiments, the housing is molded directly onto the printed circuit board. The molded housing can wrap around the edge of the printed circuit board and create a lip on the bottom side of the printed circuit board for better engagement. In some embodiments, features can be added to the printed circuit board (e.g., countersunk holes, beveled edge of the board, stepped edge of the board, tongue and groove edge of the board) such that when the molded housing is molded onto the board, the plastic hardens around the features to create better engagement. In some embodiments, the housing is attached to the printed circuit board via an adhesive and/or mechanical clips. In some embodiments, the housing is attached to the printed circuit board by a mechanical bond. In some embodiments, the housing is attached to the printed circuit board by a chemical bond. In some embodiments, the attached housing covers and encapsulates surface mounted electronics on the printed circuit board, while leaving the electrode array exposed such that the electrode array can be placed in contact with a patient's tongue for NINM therapy. A cable is provided (step **1216**). The cable is connected to the printed circuit board (step **1220**). In some embodiments, the cable is connected to the printed circuit board prior to the housing being molded onto the printed circuit board. The cable can be partially encapsulated by the housing after the molding process. In some embodiments, the housing is molded onto the printed circuit board in two steps. In a first step a first shot of plastic can be molded onto the board, where the mold temperatures and pressures are low enough that it is not hazardous to the electrical components on the board. The first shot can be used to pot the components, thereby protecting them. The first shot can be a softer material (TPE, TPU) or a rigid material with a lower mold pressure and/or temperature (Polyamide, Polyolefin). A second shot is molded over at least a portion of the first shot, where mold temperatures and pressures are higher than the first shot. This second shot may be of harder, more durable materials (e.g., nylon or glass filled nylon, ABS, PC, etc.). In some embodiments, the housing is molded onto, and completely surrounds the printed circuit board, such that only the electrode array is not covered by the housing. In this situation, the printed circuit board material would not come into contact with the patient, thereby protecting the patient in the case of harmful printed circuit board materials. In some embodiments, the electrode array is non-planar with the printed circuit board (e.g., the electrode array can protrude by a distance in the range of 0.1 to 1 mm from the printed circuit board). In some embodiments, the electrode array is an array of pins that protrude from the printed circuit

23

board. The array of pins remains exposed after molding the housing onto the printed circuit board.

FIGS. 13A and 13B show a mouthpiece 1300 that has been manufactured by overmolding a housing 1304 directly onto a printed circuit board 1332. The mouthpiece 1300 includes a spacer 1308 and a cable 1344. In some embodiments, the printed circuit 1332 board includes features for mechanically engaging the molded housing 1304 (e.g., a beveled edge of the board, a stepped edge of the board, a notched edge of the board etc.). In some embodiments, the molded housing 1304 can wrap around the edge of the printed circuit board 1332 and create a lip on the bottom side of the printed circuit board to mechanically engage the printed circuit board 1332. In some embodiments, the printed circuit board includes countersunk holes 1340. The countersunk holes are filled with plastic as the housing 1304 is molded onto the printed circuit board. A rivet forms inside the countersunk hole 1340, with the rivet being an integral portion of the housing 1304. The tapered shape of the rivet provides a force that holds the printed circuit board 1332 in mechanical contact with the housing 1304.

FIG. 14 shows a mouthpiece 1400 according to a two shot injection molding manufacturing method wherein a shot refers to the volume of material that is used to fill a mold cavity and compensate for material shrinkage. The mouthpiece 1400 includes a housing 1404, a printed circuit board 1432, a cable 1444, and a frame 1450. The frame 1450 is formed around the printed circuit board (one or both sides) 1432 during a first shot, which provides a seal between the printed circuit board and the external environment. The housing 1404 is formed around the printed circuit board 1432 and frame 1450 during a second shot, thereby encapsulating the components on the printed circuit board 1432 and chemically bonding to the frame 1450. The first and second shots can be rigid, elastomeric, or a combination of both.

The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting of the inventive concepts. It will be understood that, although the terms first, second, third etc. are used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present application.

While the present inventive concepts have been particularly shown and described above with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art, that various changes in form and detail can be made without departing from the spirit and

24

scope of the present inventive concepts described and defined by the following claims.

What is claimed is:

1. A method of manufacturing a mouthpiece, the mouthpiece providing non-invasive neuromodulation to a patient, the method comprising:

providing a printed circuit board, the printed circuit board having electronic circuitry and a plurality of electrodes for delivering subcutaneous local electrical stimulation to the patient's tongue;

forming an elongated housing directly onto the printed circuit board; and

attaching a spacer to the top surface of the elongated housing using an adhesive, the spacer for minimizing contact between a patient's upper teeth and a top surface of the elongated housing.

2. The method of claim 1 further comprising forming a strain relief mechanism integral with the elongated housing.

3. The method of claim 2 further comprising providing a cable having a first segment disposed within the housing and a second segment extending from the housing.

4. The method of claim 3 further comprising connecting one end of the first segment of the cable connected to the printed circuit board.

5. The method of claim 1 further comprising encapsulating the electronic circuitry located on the printed circuit board.

6. The method of claim 1 wherein forming the elongated housing further comprises forming a frame around at least one side of the printed circuit board, the frame providing a seal between the printed circuit board and an external environment.

7. The method of claim 6 further comprising forming the elongated housing around the printed circuit board and the frame to encapsulate one or more components mounted on the printed circuit board and chemically bond the elongated housing to the frame.

8. The method of claim 1 wherein forming the elongated housing further comprises:

providing a cable having a first segment and a second segment;

connecting one end of the first segment of the cable to the printed circuit board; and

encapsulating a portion of the cable such that the first segment of the cable is disposed within the elongated housing and the second segment of the cable extends from the elongated housing.

9. The method of claim 1 further comprising mechanically engaging the elongated housing with the printed circuit board using one or more features of the printed circuit board.

10. The method of claim 9 wherein the one or more features of the printed circuit board comprises at least one of a beveled edge, a stepped edge, a notched edge, and a countersunk hole.

* * * * *