

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)
(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
7 January 2016 (07.01.2016)



(10) International Publication Number
WO 2016/004209 A1

- (51) International Patent Classification:
A61J 7/02 (2006.01)
- (21) International Application Number:
PCT/US2015/038842
- (22) International Filing Date:
1 July 2015 (01.07.2015)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
14/321,485 1 July 2014 (01.07.2014) US
- (71) Applicant: CVS PHARMACY, INC. [US/US]; One CVS Drive, Woonsocket, RI 02895 (US).
- (72) Inventors; and
(71) Applicants : DEVITA, James, T. [US/US]; 37 Old Haswell Park Road, Middleton, MA 01949 (US). DAVIS, Thomas, G.; 12 Hines Farm Drive, Cumberland, RI 02864 (US). ROCCHIO, John; 115 Fisher Avenue #2, Roxbury, MA 02120 (US). BERTON, Lauren [US/US]; 166 Glen Hills Drive, Cranston, RI 02920 (US). MACEY, Rory [US/US]; 29 W. Scenic View Drive, Johnston, RI 02919 (US). AMIN, Vishal [US/US]; 2 Regency Plaza, Apt. 910W, Providence, RI 02908 (US). PATEL, Swati [US/US]; 29 Horizon Drive, Cranston, RI 02921 (US).
- (74) Agent: BLUNI, Scott, T.; Kacvinsky Daisak Bluni Pllc, 50 Doaks Lane, Marblehead, Massachusetts 01945 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

- Published:
- with international search report (Art. 21(3))
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: VISUAL VERIFICATION PHARMACY TRAY




Figure 6

(57) Abstract: The present invention provides a pill tray that allows a user to efficiently and reliably verify the contents of an auto-filled prescription. Design features that avoid the presence of sharp edges and allow visualization of the entire surface of the pill tray help reduce and/or eliminate the risk of commingling of pills between separate prescriptions.

WO 2016/004209 A1

Visual Verification Pharmacy Tray

Field of the Invention

[0001] The present invention relates generally to a pill tray for pharmacy use, and more particularly to a pill tray that allows full visual verification of the contents therein to ensure prescription consistency. Specifically, the present invention relates to a pill tray that prevents the commingling of pills and minimizes prescription fill errors during the often repetitive process of prescription verification.

Background

[0002] The filling of prescriptions by automated systems has been implemented in many pharmacy practice settings to improve drug distribution, control inventory, reduce labor and decrease medication errors (*See, e.g.*, “Implementation and evaluation of an automated dispensing system,” *Am. J. Health-Syst Pharm.* 1995, 52:823-8; “Medication cart-filling time, accuracy, and cost with an automated dispensing system,” *Am. J. Hosp. Pharm.* 1994; 51:1193-6). Despite these benefits, and contrary to expectations, studies have demonstrated that the number of prescription filling errors tends to increase with the implementation of automated systems.

[0003] In 2012 all automatically filled prescriptions were required to undergo a process known as Full Visual Verification (FVV). This process requires a pharmacist to pour the contents of each automatically filled prescription vial onto a counting tray to ensure product consistency. Upon verification that a prescription contains the correct type and number of pills, the pharmacist transfers the contents of the counting tray back into the prescription vial. The high volume of prescriptions filled in a typical pharmacy each day often requires the pharmacists to perform FVV for multiple automatically filled prescriptions in sequence. The highly repetitive process of transferring large numbers of pills to and from their respective containers naturally lends itself to errors. One such error, with potentially life threatening consequences, is commingling of medications due to the inadvertent transfer of stray pill(s) from one prescription vial to another. Structural features of the pill tray itself, such as crevices in which pills become temporarily lodged and/or blind spots that limit the pharmacist’s ability to identify stray pills, are a significant factor in these comingling events.

In view of the unlimited variety of pill sizes, colors and shapes (e.g., round, oblong, oval, elliptical, square, cylindrical, rectangular, diamond-shaped, cone-shaped triangular, crescent-shaped, trapezoidal, pentagonal, hexagonal, heptagonal, octagonal etc.) even minor surface disruptions within a pill tray represent potential areas in which a pill may become lodged. What is needed is an improved pill tray that allows the pharmacists to verify the accuracy and consistency of prescription contents in a safe and efficient manner.

Summary of the Invention

[0004] In one aspect, the present invention is directed to a pill counting apparatus comprising a first trapezoidal portion comprising a substantially planar first floor surface comprising first, second, third and fourth sides; the first and third sides of the first trapezoidal portion being substantially parallel to each other; the first side of the first trapezoidal portion characterized by a length that is shorter than the third side of the first trapezoidal portion; a second trapezoidal portion comprising a substantially planar second floor surface comprising first, second, third and fourth sides; the first and third sides of the second trapezoidal portion being substantially parallel to each other; the first side of the second trapezoidal portion characterized by a length that is shorter than the third side of the second trapezoidal portion; the third side of the second trapezoidal portion adjoining the first side of the first trapezoidal portion; the substantially planar second floor surface forming an obtuse angle with respect to the substantially planar first floor surface; an open-ended spout extending from the second trapezoidal portion, the spout comprising a third floor surface adjoining the first side of the second trapezoidal portion; a common sidewall extending upwards from the first floor surface, the second floor surface and the third floor surface; wherein the first trapezoidal portion, the second trapezoidal portion, the spout and the sidewall together define a base portion; and a substantially transparent surface covering the second floor surface, the substantially transparent surface being immovable with respect to the base portion.

[0005] In another aspect, the present invention is directed to a method of verifying the consistency of a prescription using the pill counting apparatus of the present invention.

Brief Description of the Drawings

[0006] Non-limiting embodiments of the present invention will be described by way of reference to the accompanying figures, which are schematic and are not intended to be drawn to scale. In the figures, each identical or nearly identical component illustrated is typically represented by a single numeral. For purposes of clarity, not every component is labeled in every figure, nor is every component of each embodiment of the invention shown where illustration is not necessary to allow those of ordinary skill in the art to understand the invention. In the figures:

[0007] FIG. 1 depicts a top view of a pill tray, in accordance with an embodiment of the present invention.

[0008] FIG. 2 depicts a top view of a pill tray, in accordance with an embodiment of the present invention.

[0009] FIG. 3 depicts a top view of a pill tray, in accordance with an embodiment of the present invention.

[0010] FIG. 4 depicts a top view of a pill tray, in accordance with an embodiment of the present invention.

[0011] FIG. 5 is a cross-sectional view of a pill tray, in accordance with an embodiment of the present invention.

[0012] FIG. 6 is a front elevational view of a pill tray, in accordance with an embodiment of the present invention.

[0013] FIG. 7 is a front view of a pill tray, in accordance with an embodiment of the present invention.

[0014] Figure 8 is a top view of a pill tray, in accordance with an embodiment of the present invention.

[0015] Figure 9 is a side-elevational view of a pill tray, in accordance with an embodiment of the present invention.

[0016] Figure 10 is a side-elevational view of a pill tray, in accordance with an embodiment of the present invention.

[0017] Various objects, features, aspects, and advantages of the present invention will become more apparent from the following detailed description of preferred embodiments of

WO 2016/004209

PCT/US2015/038842

the invention, along with the accompanying drawings in which like numerals represent like components.

Detailed Description of the Preferred Embodiments

[0018] While various embodiments of the present invention are discussed in detail below, it should be appreciated that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention and do not delimit the scope of the invention.

[0019] To facilitate the understanding of this invention, a number of terms are defined below. Terms defined herein have meanings as commonly understood by a person of ordinary skill in the areas relevant to the present invention. Terms such as “a,” “an” and “the” are not intended to refer to only a singular entity, but include the general class of which a specific example may be used for illustration. The terminology herein is used to describe specific embodiments of the invention, but their usage does not delimit the invention, except as outlined in the claims.

[0020] The phrase “and/or,” as used herein should be understood to mean “either or both” of the elements being referred to, *i.e.*, elements that are conjunctively present in some instances and disjunctively present in other instances. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified unless clearly indicated to the contrary. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to B without A (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

[0021] It will be understood that the term “preferably” as used throughout the specification refers to one or more exemplary embodiments of the invention and therefore is not to be interpreted in any limiting sense. It will be further understood that terms of orientation and/or position as may be used throughout the specification, such as upper, lower, rear, side, forward, downward, upward, inner and so on, as well as their derivatives and equivalent terms, relate to relative rather than absolute orientations and/or positions.

[0022] Referring to the drawings, and to FIG. 1 in particular, a pill counting apparatus **1** in accordance with an exemplary embodiment of the present invention is illustrated. The apparatus **1** may be interchangeably referred to herein as a “pill tray” or a “pharmacy tray.” As referred to herein, a “pill” is any suitable pharmaceutical dosage form. The pill counting apparatus preferably comprises a first trapezoidal portion **9**, second trapezoidal portion **19**, open-ended spout **40**, common sidewall **50** and substantially transparent surface **70**. Together the first trapezoidal portion **9**, second trapezoidal portion **19**, spout **40** and sidewall **50** define base portion **60** (FIG. 2).

[0023] As illustrated in FIGS. 3 and 4, first trapezoidal portion **9** comprises a substantially planar first floor surface **10** having first **11**, second **12**, third **13** and fourth **14** sides. First side **11** and third side **13** are substantially parallel to each other, with first side **11** having a length that is less (*i.e.*, shorter) than that of third side **13**. The second trapezoidal portion **19** comprises a substantially planar second floor surface **20** having first **21**, second **22**, third **23** and fourth **24** sides. First side **21** and third side **23** are substantially parallel to each other, with first side **21** having a length that is less (*i.e.*, shorter) than that of third side **23**. Third side **23** of second trapezoidal portion **19** adjoins first side **11** of second trapezoidal portion **9**. As shown in FIG. 5, second floor surface **20** form an obtuse angle **30** with respect to first floor surface **10**. Common sidewall **50** extends upward from first floor surface **10**, second floor surface **20** and third floor surface **43** (below), as shown in FIGS. 5 and 6.

[0024] Without intending to limit the present invention to any specific dimensions, in one embodiment, the height of sidewall **50** as measured from first floor surface **10** is preferably at least 1.5 inches and more preferably at least 2.0 inches. The height of sidewall **50** as measured from third floor surface **43** is preferably within the range of 1.0 to 1.5 inches. The thickness of sidewall **50**, first floor surface **10** and second floor surface **20** are all preferably within the within the range of 0.10 to 0.30 inches. The third side **13** of first trapezoidal surface portion **9** preferably has a length of at least 7.0 inches, more preferably at least 8.0 inches. The overall length of the pill counting apparatus (*i.e.*, from third side **13** to spout **40**) is at least 7.0 inches.

[0025] As illustrated in FIGS. 6 and 7, open-ended spout **40** extends from second trapezoidal portion **19**, and includes a third floor surface **43** that adjoins first side **21** of the second trapezoidal portion **19**. As used herein, the term “spout” refers to any nozzle, funnel

other opening through which the liquid or solids contents of a container may be passed or poured. Spout **40** is preferably shaped to fit within the opening of standard prescription vials such that the contents of apparatus **1** may be poured directly into a container such as a prescription vial. Without intending to limit the present invention to any specific dimensions, in one embodiment, open-ended spout **40** has a height of at least 1.0 inches.

[0026] As illustrated in FIGS. 8-10, substantially transparent surface **70** covers second floor surface **20** and is immovable with respect to base portion **60**. In another embodiment, substantially transparent surface **70** covers second floor surface **20** and a portion of first floor surface **10**. In yet another embodiment, substantially transparent surface **70** covers a portion of third floor surface **43** (not shown). As illustrated in FIG. 6 and 7, in one embodiment the substantially transparent surface **70** comprises a downwardly extending lip **72** that engages side wall **50**. Substantially transparent surface **70** is preferably fixed to side wall **50** by a variety of attaching means known in the art including, but not limited to adhesives, glues, cements, welding, thermal bonding, injection molding and soldering. Alternatively, substantially transparent surface **70** is removably attached (*i.e.*, for cleaning) to side walls **50** by a variety of attaching means such as clips, clamps, bolts and the like. Regardless of whether the substantially transparent surface **70** is fixed or removeably attached to the base portion **60**, it is said to be immovable with respect thereto because, when in use, the portion of the substantially transparent surface **70** is fixed relative to the base portion **60**. The location of substantially transparent cover **70** relative to second floor surface **20** allows a user to visualize the entire base portion **60** such any pills lodged within pill counting apparatus **1** may be identified. Without intending to limit the present invention to any specific dimensions, in one embodiment, substantially transparent surface **70** is preferably characterized by a thickness within the range of 0.05 to 0.15 inches, a length of within the range of 6.5 to 7.5 inches and a width within the range of 2.5 to 3.5 inches.

[0027] Firm plastics and flexible adhesives known in the art may be used to provide an apparatus capable of withstanding repetitive use as well as high impact forces, such as when inadvertently dropped to the floor. In one embodiment, first trapezoidal portion **9**, second trapezoidal portion **19** and spout **40** are comprised of one or more polymers such as high density polyethylene (HDPE), low density polyethylene (LDPE) and polypropylene (PP). Similarly, transparent cover **70** is comprised of polymers such as high density

polyethylene (HDPE), low density polyethylene (LDPE) and polypropylene (PP). Due to the wide variety pill colors and compositions (*i.e.*, hard shelled capsule, soft shell capsules, gelatin capsules, capsules enclosing liquids, capsules enclosing powders etc.) the polymers used to form the first trapezoidal portion **9**, second trapezoidal portion **19** and spout **40** preferably include a color that provides a high contrast (for example, light blue) with such pills while limiting the build-up of chalky binding agents.

[0028] It will be understood that polymers such as the ones listed above are amenable to a variety of forming methods including, for example, vacuum forming and injection molding. These forming methods provide smoothly contoured transitions between the components of a pill tray, thereby avoiding edges, crevices, ledges, burrs etc. within which pills may become temporarily lodged. As best illustrated by FIG. 6 (shadowed lines), sidewall **50** extends upward from first floor surface **10** and second floor surface **20** with a smooth (*e.g.*, rounded, tapered, gradual) contour that prevents pills from getting temporarily stuck. Spout **40** extends from second trapezoidal portion **19** with a similar smooth contour.

[0029] Pill counting apparatus **1** may comprise a variety of sizes and shapes, and is in no way limited to the dimensions provided in the present figures. In a preferred embodiment, pill counting apparatus **1** with the approximate dimensions of 8"x 6"x 2" (length x width x height) is able to hold the contents of a standard 60 dram prescription flat across first floor surface **10**. The greater length of third side **13** of first floor **10** relative to first side **11** maximizes the area in which pills may be poured and counted. A user may count pills on first floor surface **10** while advancing them with a spatula towards spout **40**. The dimensions of pill counting apparatus **1** defined by first trapezoidal portion **9** and second trapezoidal portion **19** permits the user to tip pill counting apparatus **1** such that the pills slide and/or roll towards spout **40**. The height of sidewall **50** permits the entire contents of a prescription to be poured back into the original prescription vial without any spillage. Substantially transparent cover **70** allows the user to visually verify that no stray pills remain lodged within the pill counting apparatus. In the unlikely event that a stray pill is identified, the user may gently tap spout **40** against the outer rim of the prescription vial to dislodge the pill.

[0030] All of the compositions and/or methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the compositions and methods of this invention have been described in terms of preferred

WO 2016/004209

PCT/US2015/038842

embodiments, it will be apparent to those of skill in the art that variations can be applied to the compositions and/or methods and in the steps or in the sequence of steps of the method described herein without departing from the concept, spirit and scope of the invention. All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the spirit, scope and concept of the invention as defined by the appended claims.

WO 2016/004209

PCT/US2015/038842

We claim:

1. A pill counting apparatus comprising:

a first trapezoidal portion comprising a substantially planar first floor surface comprising first, second, third and fourth sides, the first and third sides of the first trapezoidal portion being substantially parallel to each other, the first side of the first trapezoidal portion characterized by a length that is shorter than the third side of the first trapezoidal portion;

a second trapezoidal portion comprising a substantially planar second floor surface comprising first, second, third and fourth sides, the first and third sides of the second trapezoidal portion being substantially parallel to each other, the first side of the second trapezoidal portion characterized by a length that is shorter than the third side of the second trapezoidal portion, the third side of the second trapezoidal portion adjoining the first side of the first trapezoidal portion, the substantially planar second floor surface forming an obtuse angle with respect to the substantially planar first floor surface;

an open-ended spout extending from the second trapezoidal portion, the spout comprising a third floor surface adjoining the first side of the second trapezoidal portion;

a common sidewall extending upwards from the first floor surface, the second floor surface and the third floor surface;

wherein the first trapezoidal portion, the second trapezoidal portion, the spout and the sidewall together define a base portion; and

a substantially transparent surface covering the second floor surface, the substantially transparent surface being immovable with respect to the base portion.

2. The apparatus of claim 1, wherein the substantially transparent surface covers a portion of the first floor surface.
3. The apparatus of claim 2, wherein the substantially transparent surface covers a portion of the third floor surface.
4. The apparatus of claim 1, wherein the substantially transparent surface is fixed to the sidewall.

5. The apparatus of claim 4, wherein the substantially transparent surface comprises a downwardly extending lip that engages the sidewall.
6. The apparatus of claim 1, wherein the first trapezoidal portion, the second trapezoidal portion and the spout comprise a polymer selected from the group consisting of high density polyethylene (HDPE), low density polyethylene (LDPE) and polypropylene (PP).
7. The apparatus of claim 1, wherein the substantially transparent surface comprises a polymer selected from the group consisting of high density polyethylene (HDPE), low density polyethylene (LDPE) and polypropylene (PP).
8. The apparatus of claim 1, wherein the sidewall is characterized by a height of at least 1.5 inches as measured from the first floor surface.
9. The apparatus of claim 8, wherein the sidewall is characterized by a height less than 1.5 inches as measured from the third floor surface.
10. The apparatus of claim 1, wherein the sidewall is characterized a thickness within the range of 0.10 to 0.30 inches.
11. The apparatus of claim 1, wherein each of the first and second floor surfaces are characterized by a thickness within the range of 0.10 to 0.30 inches.
12. The apparatus of claim 1, wherein the third side of the first trapezoidal portion is characterized by a length of at least 7.0 inches.
13. The apparatus of claim 12, wherein the apparatus is characterized by an overall length of at least 7.0 inches.
14. The apparatus of claim 1, wherein the substantially transparent surface is characterized by a thickness within the range of 0.05 to 0.15 inches.
15. The apparatus of claim 14, wherein the substantially transparent surface is characterized by a length within the range of 6.5 to 7.5 inches.
16. The apparatus of claim 15, wherein the substantially transparent surface is characterized by a width within the range of 2.5 to 3.5 inches.
17. The apparatus of claim 1, wherein the open-ended spout is characterized by a height of at least 1.0 inches.





Figure 1

**Figure 2**






Figure 3

**Figure 4**

**Figure 5**




Figure 6





Figure 7

**Figure 8**




Figure 9




Figure 10




Figure 6