



(51) International Patent Classification:

B60W 10/06 (2006.01) *B60K 6/48* (2007.10)
B60W 10/08 (2006.01) *B60W 20/00* (2006.01)
B60W 30/14 (2006.01) *B60W 30/18* (2012.01)

(21) International Application Number:

PCT/EP2011/071879

(22) International Filing Date:

6 December 2011 (06.12.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

10425373.7 6 December 2010 (06.12.2010) EP

(71) Applicant (for all designated States except US): IVECO
S.P.A. [IT/IT]; Via Puglia 35, I-10156 Torino (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): AIMO BOOT, Marco
[IT/IT]; Via Audello 28, I-10072 Caselle Torinese (IT).(74) Agents: CINQUANTINI, Bruno et al.; Notarbartolo &
Gervasi S.p.A., Corso di Porta Vittoria 9, I-20122 Milan
(IT).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) Title: METHOD FOR ACTUATING THE CRUISE CONTROL FUNCTION IN A VEHICLE EQUIPPED WITH HYBRID
DRIVING, ESPECIALLY AN INDUSTRIAL OR COMMERCIAL VEHICLE




FIG. 3

(57) Abstract: The present invention describes a method for actuating the cruise control function in a vehicle equipped with hybrid driving, comprising at least a primary driving and an electric driving. The method comprises the steps of: - cyclic check of the possibility of activation of the cruise control function; if positive - activation of the electric driving of the type "electric cruise-control" (EICC), and deactivation of the primary driving, if a cyclic check of the conditions of activation of the electric driving is positive; otherwise - activation of the primary driving of the type "engine cruise-control" (EnCC), and deactivation of the electric driving.

**Method for actuating the cruise control function in a
vehicle equipped with hybrid driving, especially an
industrial or commercial vehicle**

Application field of the invention

5 The present invention refers to a method for actuating the
cruise control function in a vehicle equipped with hybrid
driving, especially an industrial or commercial vehicle.

Description of the prior art

The cruise control function, as it is known, maintains a
10 steady vehicle's speed, by means of a control usually
activated by hand, which works by controlling the
functioning of the internal combustion engine.

If said function is adopted on a vehicle equipped with a
hybrid driving system, which usually includes at least a
15 internal combustion engine and an electric motor-generator,
the problem of controlling the functioning of the hybrid
driving system arises, during the activation steps of the
function itself, in order to optimize the reduction of fuel
consumption and of vehicle noise and the increase of
20 driving comfort which characterize such driving system.

Summary of the invention

Therefore the aim of the present invention is to
provide a method for actuating the cruise control function
in a moving vehicle, especially an industrial or commercial
25 vehicle, suitable for overcoming all the drawbacks

mentioned above.

The object of the present invention, according to claim 1, is a method for actuating the cruise control function in a vehicle equipped with hybrid driving, especially an industrial or commercial vehicle, said hybrid driving comprising at least a primary driving and an electric driving, the method comprising, when said cruise control function is required, the steps of:

- cyclic check of the possibility of activation of said cruise control function; if positive
- activation of said electric driving of the type "electric cruise-control", and deactivation of said primary driving, if a cyclic check of the conditions of activation of the electric driving is positive; otherwise
- activation of said primary driving of the type "engine cruise-control", and deactivation of said electric driving.

The object of the present invention is also a vehicle, especially an industrial or commercial vehicle, comprising control means configured in order to realize the method.

In particular the object of the present invention is a method for actuating the cruise control function in a vehicle equipped with hybrid driving, especially an industrial or commercial vehicle, as described more fully

in the claims, which are an integral part of this description.

Brief description of the Figures

Further purposes and advantages of the present invention will become clear from the following detailed description of a preferred embodiment (and its alternative embodiments) and the drawings that are attached hereto, which are merely illustrative and non-limitative, in which:

figure 1 shows a general scheme of a hybrid driving system of a vehicle which applies the method according to the present invention;

figure 2 shows a block diagram of an electronic system for controlling the functioning of the different elements of figure 1;

figures 3 and 4 show flowcharts of the operations that characterize the method of the present invention.

Detailed description of the invention

A non-limitative example of a hybrid driving system of an industrial or commercial vehicle of the type known in the art, wherein it is possible to apply the present invention, is shown in figure 1.

The system is characterized by a parallel hybrid driving system, comprising a primary driving system formed by a internal combustion engine 1, an electric motor-generator 2, equipped with a DC/AC inverter 4 and with a high-voltage

electric driving battery 5, a single clutch unit 3 placed between the engine and the motor, and a transmission system 6 comprising an automated manual transmission. The latter is substantially a mechanical gearbox wherein electric actuators are present and are controlled by a specially provided control unit which manages shifting and clutch control requests, according to the driving management strategies of the internal combustion engine and electric motor.

10 An electronic system for controlling the functioning of the different elements of figure 1 is present. For example the system may include, as shown in figure 2, a vehicular electronic control unit VCU which receives at least the signals from the sensors of the accelerator pedal ACC and

15 of the brake pedal BRK, and a signal from a switch, that can be manually activated, which indicates the activation of the cruise control function CC. An electronic control unit of the hybrid driving system HCU controls the functioning of the internal combustion engine by means of a

20 control unit ECU, and the functioning of the electric motor-generator by means of a control unit MGC. The unit HCU also receives data relating at least to the battery state of charge from the battery control unit BCU, and to the indication of the road slope from a road slope sensor

25 RSS. The unit HCU preferably has at its disposal

indications and data deriving from a vehicular navigation system NS, preferably of the three-dimensional type, comprising both the instant and the predictive indication of the road slope, and the indication of the vehicle weight
5 from an evaluation system VPE of the vehicle weight when moving.

The method for actuating the cruise control function that is object of the invention may be activated by means of an electronic control system as the one shown in fig. 2.

10 According to such method, in the instant when the cruise control function CC is activated, the vehicle maintains the set speed preferably by using the electric motor, better if it is of the motor-generator type, if all the predetermined enabling conditions exist, which are described below in an
15 example, and secondarily by using the traditional internal combustion engine, when the electric motor alone is no longer able to ensure that required target speed is maintained.

The method may be implemented on any vehicle equipped with
20 a hybrid driving system, wherein at least two propulsion systems are present, and wherein at least an electric driving and a primary driving are present.

With reference to figure 3, an embodiment of the method is described.

25 When the cruise control function CC is manually activated,

for example by pressing the corresponding button (CC ON), a sequence of checks verify if the conditions are satisfied: if all these conditions are satisfied, the "Electric Cruise Control" function ElCC is activated and the driving in
5 cruise control mode is ensured by the electric engine alone, otherwise even if only one of these conditions is not satisfied, the "Engine Cruise Control" function EnCC is activated, and the driving in cruise control mode is ensured in the traditional way, for example by means of the
10 primary driving alone, with internal combustion engine.

The conditions to be checked are the following:

- If vehicle's speed $> VS$, where VS is a threshold value of vehicle's speed, below which the cruise control function cannot be activated (block NO CC), for example $VS = 25$
15 km/h.
- If the vehicle is moving forward, namely if the transmission is in Reverse (R): if the car is reversing, the cruise control function (block NO CC) cannot be activated.
- 20 - If the road slope is lower than a threshold value which is preferably variable within certain limits, namely if $Road\ Slope < (P_{max} \pm P_{max_Hyst})$, where P_{max} is the nominal upper limit of the road slope (e.g. $P_{max} = 8\%$), and P_{max_Hyst} is a tolerated percentage variation around the
25 value P_{max} (e.g. $P_{max_Hyst} = \pm 1\%$): if the slope exceeds

said limit, the "Engine Cruise Control" function EnCC is activated. Such tolerated percentage variation of the slope threshold is necessary to avoid a repeated switching between ON and OFF of the activation control of the cruise control function for minimal variations of road slope, or also to avoid continual and repeated switching between "Electric Cruise Control" ElCC and "Engine Cruise Control" EnCC. The Road Slope value is to be intended as an absolute value, namely the road slope may be either positive (uphill) or negative (downhill).

- If the target speed set for the activation of the cruise control function Vset is lower than a speed threshold value Vmax which is preferably variable within certain limits, namely if $Vset < (Vmax \pm Vmax_Hyst)$, where Vmax is the maximum speed (e.g. $Vmax = 65 \text{ km/h}$, which does not corresponds to the maximum vehicle's speed, but is correlated to the maximum power limit of the motor-generator) above which it is not possible to activate the "Electric Cruise Control" function ElCC, but only the "Engine Cruise Control" function EnCC, and Vmax_Hyst is a tolerated percentage variation around the value Vmax (e.g. $Vmax_Hyst = \pm 5 \text{ km/h}$), with equivalent considerations with respect to Pmax_Hyst.

- If the state of charge of the driving battery SOC exceeds a state of charge threshold value which is preferably

- variable within certain limits, namely if $SOC > (SOC_s \pm SOC_Hyst)$, where SOC is the percentage expressing the instant charging level of the driving battery, SOC_s is the state of charge threshold below which it is not possible to
- 5 activate the "Electric Cruise Control" function $ElCC$, but only the "Engine Cruise Control" function $EnCC$ (e.g. $SOC_s = \pm 4\%$), and SOC_Hyst is a tolerated percentage variation around the value SOC_s (e.g. $SOC_Hyst \pm 4\%$), with equivalent considerations with respect to $Pmax_Hyst$ and $Vmax_Hyst$.
- 10 - If the instant power request to the driving system is lower than a power limit value $P_{LIMIT-Mot}$ that can be provided by the electric motor (constructive parameter of the motor), namely if $Power\ Request < P_{LIMIT-Mot}$, otherwise the "Engine Cruise Control" function $EnCC$ is activated.
- 15 It is to be noted that if indications and data deriving from the vehicular navigation system NS of the three-dimensional type are available, and include both the instant and the predictive indication of the road slope, and the indication of the vehicle weight from an evaluation
- 20 system VPE of the vehicle weight when moving, it is possible to obtain a further functionality. The speed value $Vmax$, the battery state of charge value SOC_s and its tolerated percentage variation SOC_Hyst , the threshold speed value VS may be dynamically changed as a function of
- 25 the road conditions and of the route defined by the

navigation system or by the user itself, being it possible to suppose for how much time it will be possible to keep the cruise control function working. In this case, the road slope sensor RSS may not be used, since such piece of information is provided by the navigation system that is equipped with a three-dimensional cartography.

All the previous conditions are continuously and iteratively checked, until the cruise control function CC is deactivated.

10 When the "Electric Cruise Control" function ElCC is enabled, the internal combustion engine of the primary driving may be stopped or run at idle, according to the configuration of the driving system.

When the "Engine Cruise Control" function EnCC is enabled, 15 the electric motor may be controlled in order to work as a generator, and is able to provide negative torque for decelerating the vehicle when the speed exceeds the upper threshold value Vset. Such negative torque may be required for example by the control unit HCU when the "Electric 20 Cruise Control" function is enabled. This situation is typical of a vehicle travelling on a road with negative slope. Thus it is possible to obtain a recovery of the kinetic energy into electric energy that is stored in the high-tension battery of the hybrid system. Otherwise such 25 contribution would be dissipated in the form of heat on the

service brakes, and the vehicle braking should be exclusively actuated by hand by the driver, when the vehicle's speed exceeds the threshold V_{set} with engine torque equal to zero.

5 With reference to figure 4, the sequence of the activation steps of the "Electric Cruise Control" function ElCC and of the "Engine Cruise Control" functions EnCC are described below, especially relating to the hybrid driving example described above with reference to figure 1.

10 When the "Electric Cruise Control" function ElCC is activated, the control unit HCU determines the clutch 3 opening, if the clutch is closed when the function is activated, otherwise it keeps it open; then it shifts the gear 6 to neutral (position "N"); after than it activates
15 the rpm control and the torque delivery of the motor-generator 2. In this situation the vehicle driving is ensured by the electric motor-generator alone.

When the "Electric Cruise Control" function ElCC is activated, the control unit HCU keeps the gear in drive
20 (position "D"); then it determines the closing of the clutch, if the clutch is open when the function is activated, otherwise it keeps it closed; after than it activates the rpm control and the torque delivery of the internal combustion engine 1. In this situation the vehicle
25 driving is ensured by the primary driving (internal

combustion engine) alone.

During the transition from the "Electric Cruise Control" function ElCC to the "Engine Cruise Control" function EnCC, the control unit HCU shifts to drive (position "D"), then
5 determines the closing of the clutch in order to activate the primary driving (internal combustion engine), and finally it activated the rpm control and the torque delivery of the internal combustion engine.

During the transition from the "Engine Cruise Control" function EnCC to the "Electric Cruise Control" function ElCC, the control unit HCU determines the opening of the
10 clutch, then shifts to neutral (position "N") in order to activate the electric motor by means of the rpm and torque control.

15 The transitions between the two modes are determined by the continuous verification of the conditions described above.

The method of the present invention may advantageously be realized by means of computer programs loaded on the various electronic control units of the vehicle, which
20 comprise program code means performing one or more steps of said method, when said programs are run on a computer. Therefore the scope of the present patent is meant to cover also said computer programs and the computer-readable means that comprise a recorded message, such computer-readable
25 means comprising the program code means for performing one

or more steps of such method, when said programs are run on a computer.

It will be apparent to the person skilled in the art that other alternative and equivalent embodiments of the invention can be conceived and reduced to practice without departing from the scope of the invention.

From the description set forth above it will be possible for the person skilled in the art to embody the invention with no need of describing further construction details.

CLAIMS

1. Method for actuating the cruise control function in a vehicle equipped with hybrid driving, especially an industrial or commercial vehicle, said hybrid driving comprising at least a primary driving and an electric driving, the method comprising, when said cruise control function is required, the steps of:
- cyclic check of the possibility of activation of said cruise control function; if positive
 - 10 - activation of said electric driving of the type "electric cruise-control" (ElCC), and deactivation of said primary driving, if a cyclic check of the conditions of activation of the electric driving is positive; otherwise
 - activation of said primary driving of the type "engine
 - 15 cruise-control" (EnCC), and deactivation of said electric driving.
2. Method for actuating the cruise control function according to claim 1, wherein said cyclic check of the possibility of activation of the cruise control function
- 20 comprises:
- check if the vehicle's speed exceeds a speed threshold value (VS);
 - check if the vehicle is moving forward.
3. Method for actuating the cruise control function
- 25 according to claim 2, wherein said cyclic check of the

activation conditions of the electric driving comprises:

- if a road slope is lower than a slope threshold value (Pmax);
- if a target speed (Vset) set for the activation of the
- 5 cruise control function is lower than a speed threshold value (Vmax);
- if the state of charge (SOC) of the driving battery of said electric driving is higher than a state of charge threshold value (SOC_s);
- 10 - if an instant power required to said electric driving is lower than a power limit value (P_{LIMIT-Mot}) deliverable by said electric driving.

4. Method for actuating the cruise control function according to claim 3, wherein one or more values of said

15 slope threshold values (Pmax), speed threshold value (Vmax), state of charge threshold value (SOC_s), deliverable power limit value (P_{LIMIT-Mot}), are variable within respective tolerated percentage variations around the respective values.

20 5. Method for actuating the cruise control function according to claim 3, wherein at least one of said speed threshold values (Vmax), of battery state of charge (SOC_s), of its tolerated percentage variation SOC_Hyst, of the threshold speed VS, is variable as a function of

25 indications and data deriving from a vehicular navigation

system (NS) of the three-dimensional type, comprising both an instant and a predictive road slope indication, and an indication of the weight of the vehicle.

6. Method for actuating the cruise control function according to claim 1, said hybrid driving comprising a clutch (3) between said primary and electric driving, and an automated manual transmission (6), wherein:

said activation of said electric driving of the type "electric cruise-control" (ElCC) comprises the steps of:

- 10 - clutch opening (3);
- shifting the gear (6) to neutral "N";
- activation of an rpm and a torque delivery control of said electric driving; and

said activation of said primary driving of the type "engine cruise-control" (EnCC) comprises the steps of:

- 15 - keeping the gear (6) in position "drive D";
- clutch closing (3);
- activation of an rpm and a torque delivery control of said primary driving.

20 7. Method for actuating the cruise control function according to any of the previous claims, wherein when said primary driving of the type "engine cruise-control" (EnCC) is enabled, said electric driving is controlled so that it provides a negative torque in order to decelerate the

vehicle when the speed exceeds said target speed value (Vset).

8. Industrial or commercial vehicle, comprising a hybrid driving system comprising at least a primary driving (1), an electric driving (2), at least a clutch (3) between said primary and electric driving, and an automated manual transmission (6), and comprising control means configured to realize the method according to any of the previous claims.

10 9. Computer program comprising program code means suitable for performing the steps of claims from 1 to 7, when such program is run on a computer.

10. Computer-readable means comprising a recorded program, said computer-readable means comprising program code means suitable for performing the steps according to claims from 1 to 7, when said program is run on a computer.




FIG. 1






FIG. 2

3/4

**FIG. 3**

4/4

**FIG. 4**

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2011/071879

A. CLASSIFICATION OF SUBJECT MATTER INV. B60W10/06 B60W10/08 B60W30/14 B60K6/48 B60W20/00 B60W30/18 ADD. According to International Patent Classification (IPC) or to both national classification and IPC																																
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) B60W B60K Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data																																
C. DOCUMENTS CONSIDERED TO BE RELEVANT <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Category*</th> <th style="width: 70%;">Citation of document, with indication, where appropriate, of the relevant passages</th> <th style="width: 20%;">Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">X</td> <td>DE 199 37 381 A1 (DAIMLER CHRYSLER AG [DE]) 22 March 2001 (2001-03-22)</td> <td style="text-align: center;">1,2,9,10</td> </tr> <tr> <td style="text-align: center;">Y</td> <td>the whole document</td> <td style="text-align: center;">3-8</td> </tr> <tr> <td colspan="3" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">X</td> <td>WO 2009/136819 A1 (VOLVO LASTVAGNAR AB [SE]; STERVIK HANS [SE]) 12 November 2009 (2009-11-12) page 1, lines 13-23; figure 1 page 3, paragraph 15-19</td> <td style="text-align: center;">8</td> </tr> <tr> <td style="text-align: center;">L</td> <td>-& US 2011/034296 A1 (STERVIK HANS [SE]) 10 February 2011 (2011-02-10) the whole document</td> <td style="text-align: center;">8</td> </tr> <tr> <td colspan="3" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">Y</td> <td>US 6 116 363 A (NN) 12 September 2000 (2000-09-12) the whole document</td> <td style="text-align: center;">3-8</td> </tr> <tr> <td colspan="3" style="text-align: center;">-----</td> </tr> <tr> <td colspan="3" style="text-align: center;">-/-</td> </tr> </tbody> </table>			Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	X	DE 199 37 381 A1 (DAIMLER CHRYSLER AG [DE]) 22 March 2001 (2001-03-22)	1,2,9,10	Y	the whole document	3-8	-----			X	WO 2009/136819 A1 (VOLVO LASTVAGNAR AB [SE]; STERVIK HANS [SE]) 12 November 2009 (2009-11-12) page 1, lines 13-23; figure 1 page 3, paragraph 15-19	8	L	-& US 2011/034296 A1 (STERVIK HANS [SE]) 10 February 2011 (2011-02-10) the whole document	8	-----			Y	US 6 116 363 A (NN) 12 September 2000 (2000-09-12) the whole document	3-8	-----			-/-		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																														
X	DE 199 37 381 A1 (DAIMLER CHRYSLER AG [DE]) 22 March 2001 (2001-03-22)	1,2,9,10																														
Y	the whole document	3-8																														

X	WO 2009/136819 A1 (VOLVO LASTVAGNAR AB [SE]; STERVIK HANS [SE]) 12 November 2009 (2009-11-12) page 1, lines 13-23; figure 1 page 3, paragraph 15-19	8																														
L	-& US 2011/034296 A1 (STERVIK HANS [SE]) 10 February 2011 (2011-02-10) the whole document	8																														

Y	US 6 116 363 A (NN) 12 September 2000 (2000-09-12) the whole document	3-8																														

-/-																																
<div style="display: flex; justify-content: space-between;"> <div> <input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. </div> <div> <input checked="" type="checkbox"/> See patent family annex. </div> </div>																																
<div style="display: flex;"> <div style="flex: 1;"> <p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>																																
Date of the actual completion of the international search <div style="text-align: center; font-size: 1.2em;">7 February 2012</div>	Date of mailing of the international search report <div style="text-align: center; font-size: 1.2em;">14/02/2012</div>																															
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer <div style="text-align: center; font-size: 1.2em;">Plenk, Rupert</div>																															

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2011/071879

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2007/114084 A1 (HUELSEH HOLGER [AT] ET AL) 24 May 2007 (2007-05-24) the whole document	7
A	----- "Automotive Handbook", 1 January 2001 (2001-01-01), Robert Bosch GmbH, Stuttgart, XP002633740, ISBN: 0837606136 vol. 5, pages 714-715, the whole document -----	2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2011/071879

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19937381	A1	22-03-2001	NONE	
WO 2009136819	A1	12-11-2009	CN 102015401 A	13-04-2011
			EP 2285636 A1	23-02-2011
			JP 2011521822 A	28-07-2011
			US 2011034296 A1	10-02-2011
			WO 2009136819 A1	12-11-2009
US 2011034296	A1	10-02-2011	CN 102015401 A	13-04-2011
			EP 2285636 A1	23-02-2011
			JP 2011521822 A	28-07-2011
			US 2011034296 A1	10-02-2011
			WO 2009136819 A1	12-11-2009
US 6116363	A	12-09-2000	NONE	
US 2007114084	A1	24-05-2007	DE 10162017 A1	10-07-2003
			EP 1458586 A1	22-09-2004
			JP 2005512498 A	28-04-2005
			US 2004129470 A1	08-07-2004
			US 2007114084 A1	24-05-2007
			WO 03051663 A1	26-06-2003