

**(12) STANDARD PATENT**  
**(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. **AU 2019288576 B2**

(54) Title  
**Instrument alignment feedback system and method**

(51) International Patent Classification(s)  
**A61B 17/70** (2006.01)                      **A61B 17/90** (2006.01)  
**A61B 17/00** (2006.01)                      **A61B 34/20** (2016.01)  
**A61B 17/17** (2006.01)                      **A61B 90/00** (2016.01)  
**A61B 17/88** (2006.01)

(21) Application No: **2019288576**                      (22) Date of Filing: **2019.06.20**

(87) WIPO No: **WO19/246432**

(30) Priority Data

(31) Number	(32) Date	(33) Country
<b>62/763,564</b>	<b>2018.06.21</b>	<b>US</b>

(43) Publication Date: **2019.12.26**

(44) Accepted Journal Date: **2025.04.03**

(71) Applicant(s)  
**Ruthless, Llc D/B/A Ruthless Spine**

(72) Inventor(s)  
**PAK, Shane S.;SPINDLE, Karlton E.**

(74) Agent / Attorney  
**Spruson & Ferguson, GPO Box 3898, Sydney, NSW, 2001, AU**

(56) Related Art  
**WO 2016/131016 A2**  
**US 2017/0231709 A1**  
**EP 2901957 A1**  
**WO 2017/116751 A2**  
**US 2010/0249658 A1**  
**US 8981914 B1**



(51) International Patent Classification:

A61B 17/70 (2006.01) A61B 90/00 (2016.01)  
A61B 17/17 (2006.01) A61B 17/00 (2006.01)  
A61B 34/20 (2016.01) A61B 17/90 (2006.01)  
A61B 17/88 (2006.01)

(21) International Application Number:

PCT/US2019/038298

(22) International Filing Date:

20 June 2019 (20.06.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/763,564 21 June 2018 (21.06.2018) US

(71) Applicant: **RUTHLESS, LLC D/B/A RUTHLESS SPINE** [US/US]; 6750 Central Ave., Blvd. B, Riverside, CA 92504 (US).

(72) Inventors: **PAK, Shane S.**; P.O. Box 661357, Arcadia, CA 91066 (US). **SPINDLE, Karlton E.**; P.O. Box 391, Cedar Glen, CA 92321 (US).

(74) Agent: **MACEIKO, Theodore S.** et al.; Maceiko IP, 420 2nd Street, Manhattan Beach, CA 90266 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: INSTRUMENT ALIGNMENT FEEDBACK SYSTEM AND METHOD




FIG. 1

(57) Abstract: The invention relates to the alignment of instrument, including the angular alignment of surgical instruments such as those used in spinal stabilization surgeries, and a system to measure and display the orientation of a handheld instrument, wherein the handheld instrument adapted to provide feedback regarding its orientation may include at least one measurement sensor.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
KM, ML, MR, NE, SN, TD, TG).

**Published:**

- *with international search report (Art. 21(3))*
- *with amended claims and statement (Art. 19(1))*

**Date of publication of the amended claims and statement:**

23 January 2020 (23.01.2020)

## **INSTRUMENT ALIGNMENT FEEDBACK SYSTEM AND METHOD**

### **Cross-Reference to Related Application**

[0001] This application claims the benefit of U.S. Provisional Application No. 62/763,564, filed June 21, 2018, the contents of which are incorporated herein by reference.

### **Copyright Statement**

[0002] This patent document contains material subject to copyright protection. The copyright owner has no objection to the reproduction of this patent document or any related materials in the files of the United States Patent and Trademark Office, but otherwise reserves all copyrights whatsoever.

### **Field of the Invention**

[0003] This invention relates to the alignment of instruments, including the angular alignment of surgical instruments such as those used in spinal stabilization surgeries.

#### Background of the Invention

[0004] Thousands of spinal stabilization surgeries are performed every year. During the procedures, stabilizing structures, such as spinal rods and/or plates, are implanted to provide support to the patient's spine. The procedures may also involve the use of pedicle screws that may be embedded into the patient's spine to secure the rods/plates.

[0005] The implantation of the pedicle screws may involve first drilling a pilot hole through the pedicle and into the vertebral body of the patient's spine. The pedicle screw may then be implanted into the pilot hole.

[0006] In order to properly place the pedicle screw and avoid damaging the patient's spinal column, the position, angular orientation and trajectory of the pilot hole must be precisely executed.

[0007] Imaging instrumentation (such as fluoroscopic imaging systems) may provide images of the patient's spine to assist in the placement of the pilot holes, but the images may be limited in the real time information that they may provide during the procedure. In addition, the use of such systems may expose the patient and the doctors/nurses to high levels of ionized radiation, such that extended use of such systems may be undesirable. Also, a skilled surgeon may rely on his/her experience in order to properly place the pilot holes, but the experience level of each surgeon may vary and may not be adequate in many cases.

[0008] In fact, studies have shown that up to 4% of pedicle screws implanted during spinal stabilization surgeries may be misaligned. Such misalignment may cause significant health complications to the patients and in many cases the pedicle screws may require revision, thus requiring additional surgeries.

[0009] Other types of surgical/medical procedures may also require the precise alignment of the surgical instruments used. For example, hypodermic needles may often times require proper positioning and alignment during use.

[0010] Accordingly, there is a need for a system and method that provides real time feedback regarding the angular orientation, position and trajectory of surgical instruments.

### **Summary of the Invention**

[0011] The present invention is specified in the claims as well as in the below description.

[0012] In one aspect, there is provided a system for providing feedback regarding the angular orientation of a handheld surgical instrument, comprising:

a measurement sensor assembly that is initially separate from the handheld surgical instrument, that is attached to the handheld surgical instrument at or around the time of a surgical procedure so that it is longitudinally aligned with the axis or shaft of the handheld surgical instrument,

and that includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld surgical instrument with respect to gravity and provides a signal based on the measured angular orientation to the processor, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information;

a display that is remotely located from the handheld surgical instrument, that is in communication with the measurement sensor assembly, and that receives the processed angular information; and

an application that runs on the display, and that based on the processed angular information causes the display to provide a visual display of the angular orientation of the handheld surgical instrument.

**[0013]** In one implementation, the measurement sensor assembly includes a unique electronic identifier that identifies the particular handheld surgical instrument to which the measurement sensor assembly is attached.

**[0014]** In one implementation, the measurement sensor assembly includes an integrated circuit on a chip, and at least the processor is mounted on the chip.

**[0015]** In one implementation, the measurement sensor assembly includes at least one gyroscope.

**[0016]** In one implementation, the measured angular orientation is an orientation in two-dimensional or three-dimensional space.

**[0017]** In one implementation, the visual display of the angular orientation of the handheld surgical instrument includes axial and sagittal angles of the handheld surgical instrument.

**[0018]** In one implementation, the measurement sensor assembly is operable for only one use and/or is disposable.

**[0019]** In one implementation, the transmitter transmits the processed angular information to the display wirelessly.

[0020] In one implementation, the measurement sensor assembly is housed in a package that is small enough so that the package at least partially fits within a profile of the handheld surgical instrument when attached thereto.

[0021] In one implementation, the accelerometer is a three-axis accelerometer.

[0022] In one implementation, the transmitter is a Bluetooth enabled transmitter.

[0023] In one implementation, the handheld surgical instrument includes a handle and the measurement sensor assembly.

[0024] In one implementation, the handle includes a flat section, a slot or an internal cavity, and the measurement sensor assembly is securely attached thereto.

[0025] In one implementation, the handheld surgical instrument includes an awl, a probe or a screwdriver attached to the handle.

[0026] In one implementation, the measurement sensor assembly includes a battery and the measurement sensor assembly is operable only for a life of the battery.

[0027] In another aspect, there is provided a method for displaying the angular orientation of a handheld surgical instrument comprising:

providing a measurement sensor assembly that is initially separate from the handheld surgical instrument;

attaching the measurement sensor assembly to the handheld surgical instrument at or around the time of a surgical procedure so that it is longitudinally aligned with the axis or shaft of the handheld surgical instrument, wherein the measurement sensor assembly includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld surgical instrument in relation to gravity and provides a signal to the processor regarding the axial and sagittal angles of the

handheld instrument in relation to the patient's spine based on the measured angular orientation, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information;

transmitting the processed angular information from the transmitter to a display that is remotely located from the handheld surgical instrument, that is in communication with the measurement assembly, and that receives the processed angular information;

running an application on the display regarding the processed angular information thereby causing the display to provide a visual display of the axial and sagittal angles of the handheld surgical instrument in relation to the patient's spine.

**[0028]** In one implementation, the method further comprises positioning the spine in relation to a vertical plumb line so that the spine is positioned and the measurements of the angular orientation of the handheld surgical instrument are both in relation to gravity.

**[0029]** In another aspect, there is provided a system for displaying the angular orientation of a handheld instrument during spinal surgery where the spine has been positioned in relation to a vertical plumb line, comprising:

a measurement sensor assembly that is initially separate from the handheld instrument, that is attached to the handheld instrument at or around the time of the spinal surgery so that it is longitudinally aligned with the axis or shaft of the handheld instrument, and that includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld instrument with respect to gravity and provides a signal based on the measured angular orientation to the processor, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information; and

a display that is remotely located from the handheld instrument, that is in communication with the measurement sensor assembly, that receives the processed angular information, and that provides a visual display of the axial and sagittal angles of the handheld instrument relative to the spine and gravity.

[0030] In one implementation, pre-spinal surgery spinal images are taken to determine how to position the spine in relation to the vertical plumb line to facilitate the displayed axial and sagittal angles of the handheld instrument being relative to the spine and gravity.

[0031] In one implementation, the handheld instrument includes an awl, a drill or a screwdriver.

[0032] In one implementation, the pre-surgery spinal images are taken by a fluoroscopic imaging system.

[0033] A person of ordinary skill in the art will understand, that any method described above or below and/or claimed and described as a sequence of steps is not restrictive in the sense of the order of steps.

#### **Brief Description of the Drawings**

[0034] Various objects, features and attendant advantages of the present invention will become fully appreciated when considered in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the several views, and wherein:

[0035] **FIG. 1** shows aspects of a pedicle screw and rod according to exemplary embodiments hereof;

[0036] **FIGS. 2A, 2B** and **2C** show the manners in which a pedicle screw may be implanted, *e.g.*, properly as in **Fig. 2A** according to exemplary embodiments hereof; and improperly as in **Figs. 2B-2C**.

[0037] **FIG. 3** shows aspects of an alignment feedback system according to exemplary embodiments hereof;

[0038] FIGS. 4-6 show aspects of a measurement assembly according to exemplary embodiments hereof;

[0039] FIG. 7 shows aspects of an active instrument according to exemplary embodiments hereof;

[0040] FIGS 8 and 9 show aspects of a data layout and/or display according to exemplary embodiments hereof; and

[0041] FIGS. 10-12 show aspects of an active instrument according to exemplary embodiments hereof.

#### Detailed Description of the Preferred Embodiments

[0042] In general, the system according to exemplary embodiments hereof provides devices, tools, instrumentation, software and methods to assist in the proper alignment of devices. The devices to be aligned may include hand tools and/or instruments of any kind, for example, including but not limited to: surgical instruments, hand drills, screw drivers, awls, probes, taps, saws, files, pliers, tweezers, scalpels, hypodermic needles and other types of hand held devices, non-hand held devices and tools. It will be understood by a person of ordinary skill in the art, upon reading this specification, that the system and method may be used with any type of device that may benefit from being aligned in one, two or three dimensions, and that the scope of the system and method is not limited in any way by the types of devices that it may be used with.

[0043] For the purpose of this specification and for demonstration, the system and method will be described in relation to its use with surgical instruments (*e.g.*, instruments used for orthopedic surgery). However, it is appreciated that the system and method may be applied to and used with any type of device that may benefit from it.

[0044] Referring now to FIGS. 1-12, the system 10 according to exemplary embodiments hereof will be described in further detail. In a presently preferred implementation, the system 10 may be used to provide feedback relating to the

three-dimensional navigation and alignment of handheld surgical instruments. In one presently preferred implementation, the surgical instruments may include instruments used to perform orthopedic surgery, *e.g.*, spinal stabilization surgery.

[0045] In one implementation, the surgical instruments may include devices used to implant pedicle screws into a patient's spine. As shown in **FIG. 1**, the pedicle screws **20** may preferably be implanted through the pedicle **22** and into the vertebral body **24** of the patient. A linkage unit **26** (*e.g.*, a spinal rod or plate) may then be attached to the pedicle screws **20**. Two or more pedicle screws **20** may typically be used to secure each rod/plate **26** (*e.g.*, one pedicle screw **20** on each end of each rod **26**) so that the rod/plate **26** may be generally oriented parallel to the spinal column **28** of the patient. In this way, the linkage **26** may be held secure by the pedicle screws **20** and provide stability to the particular segment of the spine on which it may be attached.

[0046] It may be preferable that the spinal rod **26** be intraoperatively contoured during the surgical procedure to properly fit between the implanted pedicle screws **20**. For instance, it may be preferable to use an intraoperative spinal rod contouring system as described in U.S. Provisional Application Number 62/762,478 filed May 7, 2018, and U.S. Application Serial No. 16/140,491 (attorney docket no. 999/002), entitled Surgical Implant Preparation System and Method, filed on even date herewith, the entire contents of which are incorporated herein for any purposes.

[0047] The sagittal angle  $\beta$  of the right pedicle screw **20** is shown in **FIG. 1**. The angle  $\beta$  of the angular trajectory  $\mathbf{P}_s$  of the pedicle screw **20** may be measured with respect to the vertical axis  $\mathbf{S}$  (*e.g.*, the vertical plumb line) along the sagittal plane. The placement of the pedicle screws **20** in **FIG. 1** may be deemed as accurate as the screws **20** pass from the pedicle **22** into the vertebral body **24** without perforating any cortical walls.

[0048] FIGS. 2A, 2B and 2C are taken from the perspective along cut line A-A in FIG. 1 (along the axial or transverse plane).

[0049] FIG. 2A shows a pedicle screw 20 within a pilot hole 21 and with an axial angle  $\alpha$  (lateral to medial trajectory). The angle  $\alpha$  of the angular trajectory  $P_a$  of the pedicle screw 20 may be measured with respect to the vertical axis  $S$  (e.g., the vertical plumb line) along the axial plane. The placement of the screw 20 may be deemed as accurate as it passes through the pedicle 22 and into the vertebral body 24 without breaching and/or perforating the lateral or medial cortical walls.

[0050] FIG. 2B depicts a pedicle screw 20 within a pilot hole 21 breaching and/or perforating the lateral cortical wall, and FIG. 2C depicts a pedicle screw 20 within a pilot hole 21 breaching and/or perforating the medial cortical wall. The pedicle screw placements shown in FIGS. 2B and 2C are deemed inaccurate, and may cause significant neurological problems for the patient, including but not limited to, chronic pain, numbness, limited mobility and paralysis. Thus, depending on the patient's neurological symptoms, inaccurately placed pedicle screws 20 may need to be revised with an additional surgery, adding additional risks and complications to the patient.

[0051] In addition, given that the linkage unit 26 may be secured between two or more pedicle screws 20 (as shown in FIG. 1), it can be seen that the pedicle screws 20 may also be required to be properly aligned with respect to one another such that the linkage unit 26 may safely pass between the pedicle screws 20 without obstruction and without applying undesired strain or torque onto the screws 20 or onto the patient's spinal column 28.

[0052] Given these considerations, it can be understood that an accurate lateral to medial and cephalic to caudal trajectory and alignment for each pedicle screw 20 is paramount for a successful surgical outcome.

The System

[0053] In one exemplary embodiment hereof, the system **10** may include a measurement assembly **100**, a controller **200** and other elements, components and mechanisms as necessary to perform its various functionalities. As shown in **FIG. 3**, the measurement assembly **100** may be configured with an instrument **117** (*e.g.*, a hand tool) that may require proper alignment. In general, the measurement assembly **100** may measure the real time three-dimensional position, orientation and trajectory of the instrument. In this way, the user of the instrument may utilize this positional information to ensure that the instrument is in the proper orientation during its use. As such, for example, the instrument **117** associated with implanting the pedicle screws **20** may be properly aligned so that the pedicle screws **20** may be implanted correctly as shown in **FIG. 2A**.

[0054] The controller **200** may be in communication with the measurement assembly **100** and may generally receive information and data from the measurement assembly **100**, and send information and data to the measurement assembly **100**. The controller **200** may also process information received from the measurement assembly **100** and provide feedback to the user of the system **10** based on the information received. The controller **200** may also receive inputs from the user as well as interface with other systems including other controllers and systems.

[0055] The controller **200** may include any type of controller **200** including but not limited to: a tablet computer, a smartphone, a mobile device, a laptop computer, a PC, a networked controller, a server (*e.g.*, a network, backend or cloud platform), a micro-controller and any other types or combinations of types of controller **200**. The controller **200** may include one or more displays **202** that may be used to display data, feedback or other types of information. The controller **200** may also include one or more interfaces **204** (such as touchscreens, keyboards, mouse, etc.) that may be used by the user to interact with the controller **200** (*e.g.*, for data input).

[0056] Using spinal stabilization surgery as an example implementation, a surgeon may utilize a surgical hand tool **117** (*e.g.*, an awl) that may be configured

with the measurement assembly **100**. In one example, the awl may be used to prepare a pilot hole within the patient's spine for insertion of a pedicle screw **20**. The measurement assembly **100** may, in real time, measure the three-dimensional position, alignment, orientation and trajectory of the awl, and may provide this positional data to the controller **200**.

[0057] The controller **200** may then process the data and provide feedback (*e.g.*, visual, textual, audible, etc.) to the surgeon regarding the trajectory of the awl and thus, that of the resulting pilot hole. In this way, the surgeon may utilize real time feedback from the system **10** in order to accurately guide the awl in the correct orientation to result in a properly oriented pilot hole. The pedicle screw **20** may then be inserted into the pilot hole and be thereby properly positioned.

[0058] It is understood that the above example is meant for demonstration, and that the system **10** may be used with other types of instruments performing other types of procedures.

[0059] The various elements of the system **10** will next be described in further detail.

#### The Measurement Assembly

[0060] Referring to **FIG. 4**, according to exemplary embodiments hereof, the measurement assembly **100** may generally include at least one sensor **102**, at least one processor **104**, memory **106**, at least one radio **108**, a power supply **110**, a voltage converter **112** and other components and elements that may be necessary for the assembly **100** to perform its desired functionalities. Depending on the application of the instrument **117** and of the measurement assembly **100**, the assembly **100** may include some or all of the elements described above, and/or additional elements as required.

[0061] The sensor **102** may include any type of sensor **102** that may measure, sense or otherwise allow for the determination of the one, two or three-dimensional orientation of the assembly **100**. In one exemplary embodiment hereof, the sensor **102** may be an accelerometer, such as a tri-axial (three-axis)

micro-electro-mechanical system (MEMS) accelerometer. As is known in the art, an accelerometer **102** may measure both dynamic and static acceleration. By measuring the amount of static acceleration due to terrestrial gravity, the orientation (angle and/or tilt) of the sensor **102** may be determined.

[0062] A tri-axial MEMS accelerometer **102** may provide simultaneous measurements in three orthogonal directions, thus providing three-dimensional orientation and trajectory information. The output of the accelerometer **102** may be an electrical charge (*e.g.*, a voltage waveform) that may be proportional to the force exerted on it at any given moment in time. This electrical charge may then be processed to provide real time positional and trajectory data of the unit **100**.

[0063] The sensor(s) **102** may include piezoelectric, piezoresistive, capacitive or other components to convert mechanical or physical motion into an electrical signal. In one example, the sensor **102** may include three micro-machined pivot arms that may deflect upon acceleration (*e.g.*, gravity). The deflection may be detected by a capacitive sensor and converted into a numerical value (*e.g.*, in units of micro-g or  $\mu\text{g}$ ). In another example, the sensor **102** may include one or more cantilever beams each with a proof mass (also referred to as a seismic mass) that may deflect under the influence of external accelerations. In another example, the sensor may include one or more gyroscopes (preferably MEMS gyroscopes). Other types and architectures of sensors **102** may also be used, and it is understood that the scope of the system **10** and of the measurement assembly **100** is not limited in any way by the types of sensors **102** that the assembly **100** may utilize.

[0064] In one presently preferred implementation, the sensor **102** may be a three-axis accelerometer manufactured by STMicroelectronics (*e.g.*, part number LIS3DSH). It is understood that other sensors **102** manufactured by other manufacturers may also be used.

[0065] In one exemplary embodiment hereof, the processor **104** and the memory **106** may be formed together as a microcontroller **114**. The microcontroller **114** may also include programmable input/output peripherals

as well as other elements such as a voltage regulator **116**. The microcontroller **114**, radio **108**, voltage regulator **116** (as well as other elements and components) may be provided as an integrated system-on-a-chip (SoC) **115**. In this way, the unit **100** may be reduced in size. **FIG. 4** shows one presently preferred electrical layout of the assembly **100**. Note however that other electronic layouts may also be used. In one example, the device **100** may measure 0.8 inches x 1.5 inches x 0.5 inches, but the device **100** may also be formed in other sizes.

**[0066]** The radio **108** may be a Bluetooth radio that may transmit and receive information at 2.45 GHz to and from the controller **200** (and/or to and from other devices). In one presently preferred implementation the radio **108** may have an output power of 0.0023 watts (*e.g.*, Bluetooth low energy protocol), but other output powers may also be used. In addition, the transmission rate may be 1-2 times per second, but other transmission rates may also be used.

**[0067]** The radio **108** may also be any other kind of radio **108** or combinations of radios **108** that may transmit and receive information at any other frequencies using any types of communication protocols, analog or digital, or any combination thereof. For example, the radio **108** may utilize RF, millimeter wave, Wi-Fi, LAN, WAN, Internet, cellular connectivity, telephony, IR or other types of communication protocol or methods. The radio **108** may also include an antenna, I/O ports and any other type of communications mechanisms as necessary.

**[0068]** In one presently preferred implementation, the transmitter **108** may be manufactured by Raytac Corp. (*e.g.*, part number MDBT42Q, FCC identifier SH6MDBT42Q, certificate number 162181172/AA/00). It is understood that other transmitters **108** manufactured by other manufacturers may also be used.

**[0069]** The power supply **110** may preferably be a battery but may also comprise other types of power storage devices. In one example, the battery **110** may be a 1.5v coin cell and the voltage converter **112** may be a DC-DC converter

**112** that may boost the 1.5v to 2.7v as required by the other components in the assembly **100**.

[0070] In addition, the measurement assembly **100** may also include one or more external non-volatile (E2PROM) memory chips **116** that may be used to augment the internal memory **106** of the SoC **115**.

[0071] The assembly **100** may preferably be packaged as a small single unit device as shown in the different views depicted in **FIG. 6**.

[0072] In one exemplary embodiment hereof, the measurement assembly **100** may be configured with a handheld instrument **117**, the use of which may benefit from being properly aligned. Following the example of using surgical instruments, the instrument **117** may be an awl **118** as shown in **FIG. 7**. The awl **118** may include a handle **120** configured with a shaft **122** as shown. The shaft **122** may include a distal tip that may be sharpened to a point with two or more sharpened side edges. As is known in the art, an awl **118** may be used to bore a hole in a material, and in this example, the awl **118** may be used to bore a pilot hole **21** through the pedicle **22** and into the vertebral body **24** of a patient's spine for the insertion of a pedicle screw **20**.

[0073] The surgeon may hold the awl **118** by the handle **120** and place the distal tip of the shaft **122** at the position on the bone where the hole may be desired. The awl **118** may be rotated back and forth along the axis defined by the shaft **122** and the sharpened tip of the shaft **122** may bore the hole **21**.

[0074] It can be seen that the orientation and alignment of the awl's shaft **122** during this procedure may determine the orientation and trajectory of the resulting pilot hole **21**. It can also be seen that when the pedicle screw **20** may be screwed into the resulting pilot hole **21**, the screw **20** may also follow the trajectory of the hole **21**.

[0075] During this procedure, the measurement assembly **100** may measure the orientation and trajectory of the awl **118** (the shaft **122**) and provide this information to the controller **200**. The controller **200** may process

the information and provide it to the user. The user of the awl **118** may then utilize this real time positional information to properly manipulate the awl **118** in the correct orientation to result in a properly oriented pilot hole **21** (and thus, a properly oriented pedicle screw **20** once inserted). This will be described in further detail in later sections.

[0076] In one presently preferred implementation as shown, the measurement assembly **100** may be configured with the handle **120** of the awl **118**. However, it is understood that the assembly **100** may also be configured with the shaft **122** and/or any other element of the awl **118**, and in any position on the awl **118**.

[0077] The measurement assembly **100** may be attached to or otherwise configured with the instrument **117** during the manufacturing process of the instrument **117**, or may be retrofitted with the instrument **117** as an after-market component. The measurement assembly **100** may be longitudinally aligned with the axis defined by the shaft **122** of the instrument so that the coordinate system used by the sensor **102** may be aligned with that of the instrument **117**. This will be described in further detail in later sections. However, the assembly **100** may also be aligned in other orientations with respect to the instrument **117**.

[0078] The instrument's handle **120** may include a section that may be provided to receive the assembly **100**, such as a flat section, a slot, an internal cavity, or any other type of section that may accommodate the assembly **100** and allow for its secure attachment. However, this may not be required (*e.g.*, when the assembly **100** may be configured with the instrument **117** as an after-market component). The measurement assembly **100** may be secured to the instrument (*e.g.*, the handle **120**) with adhesive (*e.g.*, 3M sterile surgical adhesive), double-sided tape, screws, bolts, straps, bands, latches, pressure fit or any other type of attachment mechanism(s). For the purposes of this specification, an instrument **117** configured with a measurement assembly **100** may be referred to as an active instrument **124**.

[0079] Prior to use, it may be preferable to calibrate the measurement assembly **100** (the active instrument **124**) to verify the measurement assembly's amplitude response, system linearity and other performance characteristics over the intended range of use. In this way, the sensor **102** may be verified as performing within its specifications. The calibration may also provide a set of scale factors (calibration factors, correction factors, etc.) that may be used to correlate the electrical outputs of the assembly **100** with the real world physical coordinates of the assembly **100**.

[0080] The calibration factors may be applied to the output signals of the assembly **100** in order to correct for the sensor's known deficiencies. In general, the calibration procedure may typically include the measurement and calibration of the sensor's reference sensitivity, frequency response, output bias level, transverse sensitivity, resonant frequency, time constant and other characteristics. In this way, during use, the calibration factors may be applied to the raw data received from the measurement assembly **100** and the real time angular position and trajectory of the assembly **100** may be determined within a calculated level of accuracy and uncertainty.

[0081] A reference standard, such as a standard calibrated at the United States National Institute of Standards and Technology (NIST), may be used to calibrate the active instrument **124**. Alternatively, and more typically, a reference standard may be used to calibrate a transfer standard that may then be used to calibrate the active instrument **124**. In either case, this may allow for the absolute accuracy and the measurement uncertainty of the measurement assembly **100** (and the active instrument **124**) to be assessed and optimized. It may be preferable to also test the measurement repeatability of the active instrument **124** across a series of measurements and to use this information when calculating the assembly's uncertainty.

[0082] A number of different types of calibration procedures may be used to calibrate the active instrument **124**, and the proper calibration technique may be chosen depending on the type of sensor **102** employed in the assembly **100**

and the instrument's desired range of use. The active instrument **124** may be calibrated prior to each use, after each use (to verify that the instrument **124** did not change or drift during use), periodically (preferably on a periodic schedule), or during any other times. It is understood that the scope of the system **10**, of the measurement assembly **100** and of the active instrument **124** is not limited in any way by the types of calibration procedures used or the intervals over which the calibrations may be performed.

#### The Controller

**[0083]** In one exemplary embodiment hereof, the controller **200** may include a tablet computer, a smartphone, a mobile device, a laptop computer, a PC, a networked controller, a server (*e.g.*, a network, backend or cloud platform), a micro-controller and any other types or combinations of types of controllers **200**. The controller **200** may also include an operating system and software, scripts, applications (including mobile applications) and other types of code that the controller **200** may run or otherwise utilize.

**[0084]** The controller **200** may receive information from and send information to the active instrument **124** in real time. The controller **200** may be paired with the active instrument **124** via Bluetooth communications, or may utilize other types of communication protocols or methods such as RF, millimeter wave, Wi-Fi, LAN, WAN, Internet, cellular connectivity, telephony, IR or other types of communication methods, digital or analog or any combination thereof. The controller **200** may also communicate with other instrumentation (*e.g.*, imaging instrumentation) as required using the same or different communication methods.

**[0085]** In one exemplary embodiment hereof, the controller **200** may receive information from the active instrument **124** indicating the instrument's real time orientation and trajectory (preferably in three dimensions) during use. The controller **200** may then process the positional data and provide it to the user in meaningful real world formats, preferably correlated with one or more

three-dimensional coordinate systems (described later). The controller may also apply the calibration factors (*e.g.*, scale factors or correction factors) of the particular active instrument **124** to increase the accuracy of the data.

[0086] Details of how the controller **200** may be used during the use of the active instrument **124** will be described in later sections.

[0087] The controller **200** may also be used to automate the calibration procedure described in prior sections. For example, the controller **200** may provide software wizards or other types of interactive tools that may guide the user during the calibration processes.

[0088] The controller **200** may also provide software wizards or other types of interactive tools that may guide the user during the use of the active instrument **124** as will be described in later sections.

[0089] Note that any number of measurement assemblies **100** may be configured with the system **10**, and that each assembly **100** may be configured with a different active instrument **124**. For example, a first measurement assembly **100** may be configured with an awl **117** as described above, a second measurement assembly **100** may be configured with a probe **117**, a third measurement assembly **100** may be configured with a driver **117**, and so on. Each measurement assembly **100** may include a unique electronic identifier (*e.g.*, a serial number, an IP address, etc.) that the controller **200** may query, identify and record. In this way, the controller **200** may simultaneously monitor (or otherwise communicate) with each measurement assembly **100** individually.

In Use

[0090] Prior to surgery, the patient's spine may be stabilized by placing the patient on a radiolucent operating table in the prone position. With the patient's spine stabilized, imaging instrumentation (*e.g.*, C-arm fluoroscopic imaging instrumentation) may be used to take sequences of images of the patient's spine from different perspectives. The images may then be used to construct one, two

and/or three-dimensional representations of the spine. It may be preferable that the imaging instrumentation also be calibrated per its specifications as required.

[0091] In one exemplary embodiment hereof, the controller **200** (or possibly the imaging instrumentation) may use the imaging data to model, calculate or otherwise determine the proper (optimal) position, alignment (preferably in three-dimensions) and trajectory of each pilot hole for each pedicle screw **20** to be implanted. Alternatively, the controller may allow the user to interact with the controller **200** to lay out the proposed position, orientation and trajectory of each proposed pilot hole manually. For example, the controller **200** may display the representations of the patient's spine such that the user may draw (or otherwise input) the proposed position, orientation and trajectory of each pilot hole onto the layout.

[0092] The controller **200** may also provide software wizards or other types of interactive tools that may assist the user in laying out and/or otherwise determining the position of the proposed pilot holes. For the purposes of this specification, the proposed pilot holes (whether determined by the controller **200**, the user, any other system or any combination thereof) may be referred to as modeled pilot holes **23** as shown in **FIG. 8**.

[0093] The controller **200** may also perform quality checks on each modeled pilot hole **23** to ensure that the modeled holes **23** are indeed in the proper positions and orientations. And if potential problems are discovered, the controller **200** may bring this to the attention of the user for review. For example, the controller **200** may check to ensure that the axial and sagittal angles ( $\alpha$  and  $\beta$  respectively) of each pedicle screw **20** are correct and that no cortical perforations exist. The controller **200** may also ensure that the pedicle screws **20** may be properly aligned with respect to one another such that the linkage unit **26** may be attached between the screws **20** without obstruction and without applying undesired strain or torque on the screws **20** or on the patient's spinal column **28**.

[0094] The position and alignment information for each modeled pilot hole **23** may include, but may not be limited to, the modeled pilot hole **23** entry point information, angular orientation, trajectory information, length information, the location, orientation and/or position of any adjacent pedicle screw pilot holes **23**, the location, orientation and/or position of any associated linkage unit(s) **26**, as well as other information and/or any combinations of information thereof. It may be preferable that the modeled orientation and trajectory of each modeled pilot hole **23** describe/show the hole **23** as passing through the pedicle **22** and into the vertebral body **24** without cortical perforations (as shown in **FIG. 2A**). The information may be complex (vector) information.

[0095] As is known in the art, three commonly used coordinate systems may be used in imaging applications and surgical procedures, including but not limited to, a world coordinate system, the anatomical coordinate system and the image coordinate system. The world coordinate system may typically include a Cartesian coordinate system and may be used to represent the position and orientation of the patient. The anatomical coordinate system (also referred to as the patient coordinate system) may consist of three planes that describe the standard anatomical position of a human body: 1) the axial plane may be parallel to the ground and may separate the head (Superior) from the feet (Inferior), 2) the coronal plane may be perpendicular to the ground and may separate the front (Anterior) from the back (Posterior), and 3) the sagittal plane may be perpendicular to the ground and may separate the Left from the Right. The image coordinate system may describe how each image was acquired with respect to the anatomy, and may consist of an origin, an *i*-axis increasing to the right, a *j*-axis increasing to the bottom, and a *k*-axis increasing backwards (all orthogonally).

[0096] It may be preferable that the coordinate systems used by the various instrumentation (*e.g.*, the active instrument **124**, the controller **200**, the fluoroscopic imaging system, etc.) be correlated. In this way, real time angular orientation and trajectory data taken from the active instrument **124** may be

accurately correlated and overlaid with the imaging data taken by the fluoroscopic imaging system. This may also allow the surgeon to understand the coordinate system he/she may use while manipulating the active instrument **124**. For example, the surgeon may manipulate the axial angle  $\alpha$  (**FIG. 2**) and the sagittal angle  $\beta$  (**FIG. 1**) of the active instrument **124** with respect to a vertical reference such as a plumb line. The plumb line may be generally parallel or generally correspond to the vector that may represent the acceleration due to the force of gravity as measured by the sensor **102** (*e.g.*, accelerometer). The starting position of the pilot hole **21** may be determined from the modeled pilot hole **23** or from anatomical landmarks using the surgeon's personal knowledge and/or experience.

**[0097]** As the active instrument **124** may be used to create the pilot hole **21**, the controller **200** may overlay (or utilize other types of data presentations) the real time orientation/trajectory of the active instrument **124** with the modeled pilot hole **23** orientation/trajectory in real time. For example, as shown in **FIG. 8**, the controller **200** may display a cross section of the patient's vertebrae taken along the axial plane with the actual axial angle  $\alpha_a$  of the active instrument **124** (shown as the dashed line **C**) overlaid with the modeled axial angle  $\alpha_m$  of the modeled pilot hole **23** (the solid line **23**), each taken with respect to the vertical axis **S** (*e.g.*, the plumb line along the mid-sagittal plane). Other reference planes and/or coordinate systems may also be used as a reference.

**[0098]** Using this information, along with the starting point information for the pilot hole **23**, the surgeon may manipulate the active instrument **124** during the drilling procedure such that the instrument's orientation/trajectory may match that of the modeled pilot hole **23**. This may result in a properly aligned pilot hole **21** in the patient's spine that may generally match that of the modeled hole **23**.

**[0099]** In another example as shown in **FIG. 9**, the controller **200** may display the angle information ( $\alpha$  and  $\beta$ ) measured by each measurement

assembly **100** directly. In this way, the user may read the angles and manipulate the corresponding active instrument **124** accordingly.

[00100] **FIG. 9** shows the angle information ( $\alpha$  and  $\beta$ ) for six individual measurement assemblies **100** configured with the system **10**. Because each measurement assembly **100** may be configured with a different active instrument **124**, the controller may display the name of the active instrument **124** along with each instrument's corresponding angular information. Other information may also be displayed. While **FIG. 9** depicts positional data of six measurement assemblies **100** displayed by the controller **200**, any number of measurement assemblies **100** may be configured with the system **10**, and the controller **200** may display information received from any number of them.

[00101] In addition, the controller **200** may provide software wizards and/or any other types of interactive tools that may assist or otherwise guide the surgeon during the procedure.

[00102] The controller **200** may also provide other types of real time feedback to the surgeon such as warnings, *e.g.*, if the alignment of the active instrument **124** may deviate from that of the modeled pilot hole **23** by a particular threshold. For example, if the angular orientation of the active instrument **124** may be deemed to be deviating from the modeled angular orientation of the pilot hole **23** along any plane beyond a pre-determined threshold, an audible warning may sound to alert the user. Other types of feedback and warnings such as visual, sensory, or any other type of feedback or any combination thereof may also be used.

[00103] The controller **200** may include at least one display **202** that may be easily viewable by the user of the system **10**. For example, the display **202** may be positioned such that the surgeon may simply glance upward slightly in order to view the display **202** and the feedback that it may show. In another example, the display **202** of the controller **200** may be embedded into the eye glasses of the user so that the user may view both the display **202** and the patient at the

same time. It is understood that the display(s) **202** may be preferably positioned anywhere where they may be viewed by at least some of the users of the system **10**.

[00104] The surgeon need not be required to utilize all of the information provided by the system **10** during any particular surgery. For example, the surgeon may determine the entry point of a pilot hole **21** based on cortical landmarks and then utilize the orientation and trajectory information provided by the system **10** to bore the pilot hole **21**. It is understood that some, any and/or all of the information provided by the system **10** may be utilized by the surgeon at the surgeon's discretion, and that the scope of the system **10** is not limited in any way by the information provided that the surgeon may or may not utilize.

[00105] It is understood by a person of ordinary skill in the art, upon reading this specification, that the above example describing the active instrument **124** as an awl **118** is meant for demonstration purposes, and that the active instrument **124** may be any type of instrument **117**.

[00106] For example, the instrument **117** may be a probe **126** as shown in **FIG. 10**. The probe **126** may include a handle **128** and a shaft **130**. A measurement assembly **100** may be configured with the probe **126** (with its handle **128** or elsewhere) such that the probe **128** may be an active instrument **124**.

[00107] In one preferred implementation, the probe **126** may be used to measure the angular orientation and trajectory of the bored pilot hole **21** described above. The probe **126** may be inserted into the bored pilot hole **21** and the angular orientation and trajectory of the probe **126** (and thus that of the pilot hole **21**) may be measured, processed and displayed by the system **10**. In this way, the angular orientation and trajectory of the pilot hole **21** may be verified as adequately correlating with the modeled pilot hole **23** as described in previous sections.

[00108] In another example as shown in **FIG. 11**, the instrument **117** may be a driver **132** (*e.g.*, a screw driver) that may be used to screw each pedicle screw **20** into its corresponding pilot hole **21**. The driver **132** may include a handle **134** and a shaft **136**. A measurement assembly **100** may be configured with the driver **132** (*e.g.*, with its handle **134**) such that the driver **132** may be an active instrument **124**. In this way, the trajectory of the screw **20** during its insertion may be monitored to match that of the modeled pilot hole **23** (and the actual pilot hole **21**). This may ensure that the pedicle screw **20** may not pursue an alternate track outside the pilot hole **21** during its insertion.

[00109] In another preferred implementation, the instrument **117** may be a hypodermic needle **138** as shown in **FIG. 12**. The hypodermic needle **138** may include a handle **140**, a body **142** and a needle **144**. A measurement assembly **100** may be configured with the hypodermic needle **132** (with its body **136** or elsewhere) such that the hypodermic needle may be an active instrument **124**.

[00110] In one preferred implementation, the hypodermic needle **132** may be used to make an injection into the body of a patient. In some such procedures, it may be required that the orientation of the needle **138** be held at a particular angle in order to properly perform the injection. As an active instrument **124**, the system **10** may measure, process and display the real time angular orientation of the hypodermic needle **132** such that the surgeon may manipulate it to the preferred position.

[00111] In this example, the system **10** may or may not use imaging information of the patient, and may instead use theoretical modelled data to guide the user through the procedure. Alternatively, the user may simply use the positional data provided by the system **10** and manipulate the active instrument **124** with respect to a known reference coordinate system (*e.g.*, a vertical plumb line).

[00112] While the system **10**, including the measurement assembly **100** and the controller **200**, has been described above with reference to surgical

procedures such as spinal stabilization surgery and injections using a hypodermic needle, other types of surgical procedures may also benefit from the use of the system **10**. For example, kyphoplasty, percutaneous bone biopsies of a known lesion within a bone, neurosurgical procedures within the brain that may require stereotactic surgery, as well as other surgical procedures, may also be used with, and benefit from, the system **10**.

**[00113]** In all of the embodiments disclosed or otherwise, the measurement assembly **100** and/or the active instrument **124** may be disposable and may be designed to be used once and then discarded. Alternatively, the measurement assembly **100** and/or the active instrument **124** may be designed to be used multiple times.

**[00114]** In addition, in all of the embodiments disclosed or otherwise, it may be preferable that the measurement assembly **100** and/or the active instrument **124** be sterilized and/or otherwise be provided as a sterile device.

**[00115]** Where a process is described herein, those of ordinary skill in the art will appreciate that the process may operate without any user intervention. In another embodiment, the process includes some human intervention (*e.g.*, a step is performed by or with the assistance of a human).

**[00116]** As used herein, including in the claims, the phrase “at least some” means “one or more,” and includes the case of only one. Thus, *e.g.*, the phrase “at least some ABCs” means “one or more ABCs”, and includes the case of only one ABC.

**[00117]** As used herein, including in the claims, term “at least one” should be understood as meaning “one or more”, and therefore includes both embodiments that include one or multiple components. Furthermore, dependent claims that refer to independent claims that describe features with “at least one” have the same meaning, both when the feature is referred to as “the” and “the at least one”.

**[00118]** As used in this description, the term “portion” means some or all. So, for example, “A portion of X” may include some of “X” or all of “X”. In the context of a conversation, the term “portion” means some or all of the conversation.

**[00119]** As used herein, including in the claims, the phrase “using” means “using at least,” and is not exclusive. Thus, *e.g.*, the phrase “using X” means “using at least X.” Unless specifically stated by use of the word “only”, the phrase “using X” does not mean “using only X.”

**[00120]** As used herein, including in the claims, the phrase “based on” means “based in part on” or “based, at least in part, on,” and is not exclusive. Thus, *e.g.*, the phrase “based on factor X” means “based in part on factor X” or “based, at least in part, on factor X.” Unless specifically stated by use of the word “only”, the phrase “based on X” does not mean “based only on X.”

**[00121]** In general, as used herein, including in the claims, unless the word “only” is specifically used in a phrase, it should not be read into that phrase.

**[00122]** As used herein, including in the claims, the phrase “distinct” means “at least partially distinct.” Unless specifically stated, distinct does not mean fully distinct. Thus, *e.g.*, the phrase, “X is distinct from Y” means that “X is at least partially distinct from Y,” and does not mean that “X is fully distinct from Y.” Thus, as used herein, including in the claims, the phrase “X is distinct from Y” means that X differs from Y in at least some way.

**[00123]** It should be appreciated that the words “first,” “second,” and so on, in the description and claims, are used to distinguish or identify, and not to show a serial or numerical limitation. Similarly, letter labels (*e.g.*, “(A)”, “(B)”, “(C)”, and so on, or “(a)”, “(b)”, and so on) and/or numbers (*e.g.*, “(i)”, “(ii)”, and so on) are used to assist in readability and to help distinguish and / or identify, and are not intended to be otherwise limiting or to impose or imply any serial or numerical limitations or orderings. Similarly, words such as “particular,”

“specific,” “certain,” and “given,” in the description and claims, if used, are to distinguish or identify, and are not intended to be otherwise limiting.

**[00124]** As used herein, including in the claims, the terms “multiple” and “plurality” mean “two or more,” and include the case of “two.” Thus, *e.g.*, the phrase “multiple ABCs,” means “two or more ABCs,” and includes “two ABCs.” Similarly, *e.g.*, the phrase “multiple PQRs,” means “two or more PQRs,” and includes “two PQRs.”

**[00125]** The present invention also covers the exact terms, features, values and ranges, etc. in case these terms, features, values and ranges etc. are used in conjunction with terms such as about, around, generally, substantially, essentially, at least etc. (i.e., “about 3” or “approximately 3” shall also cover exactly 3 or “substantially constant” shall also cover exactly constant).

**[00126]** As used herein, including in the claims, singular forms of terms are to be construed as also including the plural form and vice versa, unless the context indicates otherwise. Thus, it should be noted that as used herein, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.

**[00127]** Throughout the description and claims, the terms “comprise”, “including”, “having”, and “contain” and their variations should be understood as meaning “including but not limited to”, and are not intended to exclude other components unless specifically so stated.

**[00128]** It will be appreciated that variations to the embodiments of the invention can be made while still falling within the scope of the invention. Alternative features serving the same, equivalent or similar purpose can replace features disclosed in the specification, unless stated otherwise. Thus, unless stated otherwise, each feature disclosed represents one example of a generic series of equivalent or similar features.

**[00129]** The present invention also covers the exact terms, features, values and ranges, etc. in case these terms, features, values and ranges etc. are used in

conjunction with terms such as about, around, generally, substantially, essentially, at least etc. (i.e., "about 3" shall also cover exactly 3 or "substantially constant" shall also cover exactly constant).

**[00130]** Use of exemplary language, such as "for instance", "such as", "for example" ("*e.g.*") and the like, is merely intended to better illustrate the invention and does not indicate a limitation on the scope of the invention unless specifically so claimed.

**[00131]** While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiment, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

**[00132]** Any reference to prior art in this specification is not to be taken as an admission such prior art is well known or forms part of the common general knowledge in Australia or any other country.

What is claimed is:

1. A system for providing feedback regarding the angular orientation of a handheld surgical instrument, comprising:

a measurement sensor assembly that is initially separate from the handheld surgical instrument, that is attached to the handheld surgical instrument at or around the time of a surgical procedure so that it is longitudinally aligned with the axis or shaft of the handheld surgical instrument, and that includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld surgical instrument with respect to gravity and provides a signal based on the measured angular orientation to the processor, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information;

a display that is remotely located from the handheld surgical instrument, that is in communication with the measurement sensor assembly, and that receives the processed angular information; and

an application that runs on the display, and that based on the processed angular information causes the display to provide a visual display of the angular orientation of the handheld surgical instrument.

2. The system of claim 1 wherein the measurement sensor assembly includes a unique electronic identifier that identifies the particular handheld surgical instrument to which the measurement sensor assembly is attached.

3. The system of claim 1 wherein the measurement sensor assembly includes an integrated circuit on a chip, and at least the processor is mounted on the chip.

4. The system of claim 1 wherein the measurement sensor assembly includes at least one gyroscope.

5. The system of claim 1 wherein the measured angular orientation is an orientation in two-dimensional or three-dimensional space.

6. The system of claim 1 wherein the visual display of the angular orientation of the handheld surgical instrument includes axial and sagittal angles of the handheld surgical instrument.

7. The system of claim 1 wherein the measurement sensor assembly is operable for only one use and/or is disposable.

8. The system of claim 1 wherein the transmitter transmits the processed angular information to the display wirelessly.

9. The system of claim 1 wherein the measurement sensor assembly is housed in a package that is small enough so that the package at least partially fits within a profile of the handheld surgical instrument when attached thereto.

10. The system of claim 1 wherein the accelerometer is a three-axis accelerometer.

11. The system of claim 1 wherein the transmitter is a Bluetooth enabled transmitter.

12. The system of claim 1 wherein the handheld surgical instrument includes a handle and the measurement sensor assembly.

13. The system of claim 12 wherein the handle includes a flat section, a slot or an internal cavity, and the measurement sensor assembly is securely attached thereto.

14. The system of claim 12 wherein the handheld surgical instrument includes an awl, a probe or a screwdriver attached to the handle.

15. The system of claim 12 wherein the measurement sensor assembly includes a battery and the measurement sensor assembly is operable only for a life of the battery.

16. A method for displaying the angular orientation of a handheld surgical instrument comprising:

providing a measurement sensor assembly that is initially separate from the handheld surgical instrument;

attaching the measurement sensor assembly to the handheld surgical instrument at or around the time of a surgical procedure so that it is longitudinally aligned with the axis or shaft of the handheld surgical instrument, wherein the measurement sensor assembly includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld surgical instrument in relation to gravity and provides a signal to the processor regarding the axial and sagittal angles of the handheld instrument in relation to the patient's spine based on the measured angular orientation, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information;

transmitting the processed angular information from the transmitter to a display that is remotely located from the handheld surgical instrument, that is in communication with the measurement assembly, and that receives the processed angular information;

running an application on the display regarding the processed angular information thereby causing the display to provide a visual display of the axial and sagittal angles of the handheld surgical instrument in relation to the patient's spine.

17. The method of claim 16 further comprising positioning the spine in relation to a vertical plumb line so that the spine is positioned and the measurements of the angular orientation of the handheld surgical instrument are both in relation to gravity.

18. A system for displaying the angular orientation of a handheld instrument during spinal surgery where the spine has been positioned in relation to a vertical plumb line, comprising:

a measurement sensor assembly that is initially separate from the handheld instrument, that is attached to the handheld instrument at or around the time of the spinal surgery so that it is longitudinally aligned with the axis or shaft of the handheld instrument, and that includes an accelerometer, a processor and a transmitter, wherein the accelerometer measures the angular orientation of the handheld instrument with respect to gravity and provides a signal based on the measured angular orientation to the processor, wherein the processor processes the signal provided by the accelerometer to provide processed angular information, and wherein the transmitter transmits the processed angular information; and

a display that is remotely located from the handheld instrument, that is in communication with the measurement sensor assembly, that receives the processed angular information, and that provides a visual display of the axial and sagittal angles of the handheld instrument relative to the spine and gravity.

19. The system of claim 18 wherein pre-spinal surgery spinal images are taken to determine how to position the spine in relation to the vertical plumb line to facilitate the displayed axial and sagittal angles of the handheld instrument being relative to the spine and gravity.


20. The system of claim 18, wherein the handheld instrument includes an awl, a drill or a screwdriver.

21. The system of claim 18, wherein the pre-surgery spinal images are taken by a fluoroscopic imaging system.


**Ruthless, LLC D/B/A Ruthless Spine**

**Patent Attorneys for the Applicant/Nominated Person**

**SPRUSON & FERGUSON**



**FIG. 1**



Medial Breach


Lateral Breach

Accurate Placement


**FIG. 2C**

**FIG. 2B**

**FIG. 2A**



**FIG. 3**



**FIG. 4**





FIG. 5



7/12





FIG. 7




**FIG. 8**

**RJB Display**


<b>Device 1</b> <input type="text" value="Device Name"/> $\alpha$ +10.2 $\beta$ -20.3 <input type="button" value="Register New Device"/>	<b>Device 2</b> <input type="text" value="Device Name"/> $\alpha$ +30.3 $\beta$ +45.1 <input type="button" value="Register New Device"/>
<b>Device 3</b> <input type="text" value="Device Name"/> $\alpha$ $\beta$ <input type="button" value="Register New Device"/>	<b>Device 4</b> <input type="text" value="Device Name"/> $\alpha$ $\beta$ <input type="button" value="Register New Device"/>
<b>Device 5</b> <input type="text" value="Device Name"/> $\alpha$ $\beta$ <input type="button" value="Register New Device"/>	<b>Device 6</b> <input type="text" value="Device Name"/> $\alpha$ $\beta$ <input type="button" value="Register New Device"/>

*$\alpha$  - Axial Angle*  
 *$\beta$  - Sagittal Angle*


**FIG. 9**



**FIG. 10**



**FIG. 11**



**FIG. 12**