



(22) Date de dépôt/Filing Date: 1998/03/19

(41) Mise à la disp. pub./Open to Public Insp.: 1999/09/23

(45) Date de délivrance/Issue Date: 2009/11/24

(62) Demande originale/Original Application: 2 324 331

(51) Cl.Int./Int.Cl. *A61C 17/08* (2006.01)


(72) Inventeurs/Inventors:
DAVIS, WARREN, US;
WASSERMAN, DAVID, US

(73) Propriétaires/Owners:
DAVIS, WARREN, US;
WASSERMAN, DAVID, US

(74) Agent: SMART & BIGGAR

(54) Titre : OUTIL D'ASPIRATION ECLAIRE AVEC POINTE JETABLE

(54) Title: ILLUMINATED SUCTION TOOL WITH A DISPOSABLE TIP



(57) Abrégé/Abstract:

A dental suction tool has a disposable sanitary plastic suction tip to prevent cross contamination from one patient to the next. Additionally, a light source such as a fiberoptic bundle with or without a ring light is provided on the interior of the dental suction tool

(57) **Abrégé(suite)/Abstract(continued):**

to provide light to the end of the plastic disposable suction tip. Illumination from the ring light or directly from the fiberoptic bundle is transmitted along the length of the suction tip and is emitted from the end thereof to illuminate the oral cavity during dental procedures.

Abstract

A dental suction tool has a disposable sanitary plastic suction tip to prevent cross contamination from one patient to the next. Additionally, a light source such as a fiberoptic bundle with or without a ring light is provided on the interior of the dental suction tool to provide light to the end of the plastic disposable suction tip. Illumination from the ring light or directly from the fiberoptic bundle is transmitted along the length of the suction tip and is emitted from the end thereof to illuminate the oral cavity during dental procedures.

WO 99/47068

PCT/US98/05508

ILLUMINATED SUCTION TOOL WITH A DISPOSABLE TIP

1

2

Background of the Invention

3

4

5

This invention relates to a suction tool, and more particularly to suction tool with a disposable tip that also provides illumination to the oral cavity of the patient.

6

7

8

9

10

11

12

13

The present invention was developed to add further function to the widely accepted evacuation systems currently used for suction or aspiration. The concept of suction or aspiration in the dental office has its roots in the old fashioned spittoon. The spittoon was later replaced by the gravity flow cuspidor, then by the flush cup and finally by the suction tip/aspirator tip/vacuum tip which are interchangeable terms varying by the user and based on the size of the aperture in the device.

14

15

16

17

18

19

20

21

These dental suction instruments are used by dentists to remove fluids and other foreign objects that accrue in the patient's oral cavity during typical dental procedures. The conventional dental suction tool comprises a suction tip connected by a long tubing to a vacuum source. The dental suction tool can be configured to hang in the corner of the patient's mouth or is manipulated by the dentist to suction the oral cavity.

22

23

24

25

26

With the rising incidence of communicable diseases such as hepatitis and acquired immune deficiency syndrome, extreme care must be taken to prevent the transmission of germs (viral or bacteria) from one patient to the next. With the conventional suction devices, it is necessary to sterilize at least the tip

WO 99/47068

PCT/US98/05508

1 of the suction device after each patient use. During the use of
2 the suction device, water, saliva and blood from the patient's
3 mouth is drawn into the tip for removal from the oral cavity.
4 If cleaning and sterilization is not effected, it would be very
5 easy to transfer infection from one patient to the next. Also,
6 latent bacterial growth can be promoted in both the tip and the
7 entire vacuum suction system lines because of the existence of
8 this potentially contaminating material. To further mitigate
9 this possibility of cross-contamination from one patient to the
10 next, the routine sterilization of suction tips is desirable.

11 It is desirable to also supply light into the oral cavity
12 to assist the dentist in performing necessary dental procedures.
13 Most dental operatories have an overhead task lighting system
14 with reflective surfaces that help concentrate the light on the
15 patient's mouth. However, the dentist will often stand in the
16 path of the light which minimizes the effectiveness of the
17 overhead light. One of the major nuisances and frustrations in
18 the practice of dentistry is the constant need for the dentist
19 to spend time adjusting the direction of this overhead lighting.

20 Various dental tools have been provided with a light source
21 to assist the dentist during various dental activities. For
22 example, a typical dental drill will include a fiberoptic bundle
23 that transmits light from a light source to the end of the dental
24 drill which allows the dentist to provide light directly to the
25 area in which the drilling is occurring. Representative of this
26 technology are the disclosures shown in U.S. Patent No. 4,507,085

WU 99/47068

PCT/US98/05508

1 (Mosimann) and U.S. Patent No. 5,088,924 (Woodward).

2 Dental syringe tip handpieces have also been provided with
3 a light source to illuminate the area into which the air and/or
4 water are to be sprayed. Representative of these devices is the
5 disclosure of U.S. Patent No. 4,619,612 (Weber) which shows a
6 fiberoptic bundle disposed down the center of a metal syringe tip
7 assembly. A light bulb acts as the light source and is disposed
8 in the interior of the handpiece. The syringe tip used in the
9 disclosure of the Weber patent is a metal, non-disposable syringe
10 tip which must be autoclaved prior to use on the next patient.

11 Previous attempts to use light in conjunction with a suction
12 tip were done by running a fiberoptic bundle tangent and parallel
13 to the suction tip. The optical conduit for the fiberoptic
14 bundle was fixed to the suction tip by a series of clamps along
15 the length of the suction tip. However, the results from this
16 configuration were less than desirable for several reasons.

17 The fiberoptic bundles that were attached to the suction
18 tips still needed to be sterilized before being used on the next
19 patient. Fiberoptic bundles are not particularly amenable to the
20 heat of sterilization and the expense and inconvenience of
21 frequent replacement of these fiberoptic bundles can be prohibi-
22 tive. It is also necessary to clean up the areas on the suction
23 tip at which the clamps are attached and this can be quite
24 cumbersome and time consuming. Another problem with this
25 fiberoptic bundle configuration is that the light is positioned
26 off-center from the suction tip so that the light being transmit-

WO 99/47068

PCT/US98/05508

1 ted into the oral cavity of the patient still casts shadows from
2 the suction tip, itself, which can do more harm than good.

3 The novel concept developed herein is to transmit light to
4 the field of operation by transmitting a light source through a
5 transparent plastic material which simultaneously serves as the
6 suction tip of the dental suction device. The fact that the
7 light is centered relative to the suction tip minimizes any
8 shadows in the oral cavity and reduces the need for the dentist
9 to rely on his overhead task lighting, which is constantly in
10 need of adjustment.

11 It is proposed that the use of the present invention in
12 conjunction with the light source that is coupled to the
13 air/water syringe tip will provide sufficient light in the
14 patient's oral cavity to obviate the need for the overhead task
15 lighting and eliminate the time spent constantly adjusting this
16 task lighting.

17 It is an object of the present invention to provide a
18 disposable suction tip as part of the dental suction tool so that
19 each patient can receive a clean and uncontaminated suction tip.

20 It is a feature of the present invention that the suction
21 tip portion of a dental suction tool is made from a disposable
22 plastic material.

23 It is an advantage of the present invention that cross-
24 contamination between patients due to improperly cleaned or
25 sterilized suction tips is eliminated because each patient is
26 provided with a new, clean and uncontaminated suction tip that

WO 99/47068

PCT/US98/05508

1 is only used on that patient.

2 It is a further object of the present invention to provide
3 means for properly aligning the suction tip in the dental suction
4 tool.

5 It is a further feature of the present invention to provide
6 at one end of the suction tip at least one beveled section along
7 an outer wall surface of the suction tip so that the suction tip
8 can be properly aligned in the dental suction tool. Alterna-
9 tively, one end of the suction tip is provided with at least one
10 recess that is adapted to cooperate with a keying element in the
11 dental suction tool to properly align the suction tip in the
12 dental suction tool.

13 It is a further advantage of the present invention that a
14 dentist will be able to properly align the suction tip in the
15 dental suction tool.

16 It is a further object of the present invention to provide
17 a useful source of light that can be transmitted into the oral
18 cavity of the patient whenever the dentist is using a dental
19 suction tool.

20 It is a further feature of the present invention to provide
21 a light source at one end of the suction tip on the interior of
22 the adaptor that holds the suction tip in the dental tool. Light
23 from the light source is directed into one end of the suction tip
24 and carried along the length thereof. At the opposite end of the
25 suction tip, the light radiates from the suction tip and can be
26 used to illuminate the oral cavity of the patient.

WO 99/47068

PCT/US98/05508

1 It is a further advantage of the present invention that a
2 dentist will be able to illuminate the oral cavity using the same
3 instrument that he is using to suction liquids and other foreign
4 matter from the oral cavity of the patient. Any dental proce-
5 dures that require use of the dental suction tool will be more
6 easily, safely and effectively carried out because the dentist
7 will be able to see exactly where in the oral cavity he is
8 working.

9 Other objects, features and advantages of the present
10 invention will become apparent from a consideration of the
11 following detailed description.

12 13 Summary of the Invention

14 A dental suction tool has a disposable sanitary plastic
15 suction tip to prevent cross contamination from one patient to
16 the next. The suction tip is formed as a generally cylindrical
17 hollow tubing and made of disposable plastic material. One end
18 of the suction tip has at least one beveled section along an
19 outer wall surface of the suction tip so that the suction tip can
20 be properly aligned in the dental suction tool. Alternatively,
21 one end of the suction tip has at least one recess that is
22 adapted to cooperate with a keying element in the dental suction
23 tool to properly align the suction tip in the dental suction
24 tool.

25 Additionally, a light source such as a fiberoptic bundle
26 with or without a ring light is provided on the interior of the

74904-12D

dental suction tool to provide light to the end of the plastic disposable suction tip. Illumination from the ring light or directly from the fiberoptic bundle is transmitted along the length of the suction tip and is emitted from the
5 end thereof to illuminate the oral cavity during dental procedures.

According to a broad aspect of the invention, there is provided a suction tip for use in a dental suction tool comprising a material capable of transmitting light
10 along the length thereof and formed as a generally cylindrical hollow tubing, a first end of the suction tool having at least one axial slot therein so that the suction tip can be secured in the dental suction tool.

According to another broad aspect of the
15 invention, there is provided a suction tip for use in a dental suction tool comprising a material capable of transmitting light along the length thereof and formed as a generally cylindrical hollow tubing, a first end of the suction tool having a plurality of axial slots therein
20 forming a plurality of flexible fingers so that the suction tip can be secured in the dental suction tool.

According to a further broad aspect of the invention, there is provided a suction tip for use in a dental suction tool comprising a plastic material formed as
25 a generally cylindrical hollow tubing, one end of the suction tip having at least one beveled section formed in an outer wall surface of the suction tip so that the suction tip can be properly aligned in the dental suction tool.

According to yet another broad aspect of the
30 invention, there is provided a suction tip for use in a dental suction tool comprising a plastic material formed as

74904-12D

a generally cylindrical hollow tubing, one end of the suction tip having at least one recess formed in an outer wall surface of the suction tip so that the suction tip can be properly aligned in the dental suction tool.

5 According to yet a further broad aspect of the invention, there is provided a suction tip for use in a dental suction tool comprising a plastic material formed as a generally cylindrical hollow tubing, one end of the suction tip having at least one recess formed in an outer
10 wall surface of the suction tip so that the suction tip can be properly aligned in the dental suction tool, the suction tip further comprising an inner layer of light transmitting material and an outer layer of opaque material.

 According to still a further broad aspect of the
15 invention there is provided a suction tip for use in a dental suction tool comprising a plastic material formed as a generally cylindrical hollow tubing, one end of the suction tip having at least one beveled section formed in an outer wall surface of the suction tip so that the suction
20 tip can be properly aligned in the dental suction tool, the suction tip further comprising an inner layer of light transmitting material and an outer layer of opaque material.

Brief Description of the Drawings

Figure 1 shows an isometric exploded view of the
25 dental suction tool of the present invention.

Figure 2 is a cross sectional view of one embodiment of the dental suction tool of the present invention with the suction valve in the open position.

74904-12D

Figure 3 is a cross sectional view of the dental suction tool of the present invention with the suction valve in the closed position.

Figure 4 shows an isometric exploded view of a
5 modified dental suction tool of the present invention.

Figure 5 shows an isometric view of a modified suction tip of the present invention.

Figure 6 is a cross sectional view of the modified dental suction tool shown in Figure 4 with the suction valve
10 in the open position.

Figure 7 shows an end view of another modified suction tip of the present invention.

WO 99/47068

PCT/US98/05508

1 Figure 8 is a cross sectional view of another modified
2 dental suction tool with the suction valve in the open position.

3 Figure 9 is an isometric exploded view of a modified suction
4 tip and its corresponding key element of the present invention.

5 Figure 10 shows an end view of still another modified
6 suction tip of the present invention.

7 Figure 11 is a cross sectional view of still another
8 modified dental suction tool with the suction valve in the open
9 position.

10 Figure 12 is an isometric exploded view of another modified
11 dental suction tool of the present invention.

12 Figure 13 is an end view of the valve body of the modified
13 dental suction tool taken along line 13-13 of Figure 12.

14 Figure 14 is an end view of the valve body of the modified
15 dental suction tool taken along line 14-14 of Figure 12.

16 Figure 15 is a cross section view of the modified dental
17 suction tool of Figure 12 before the suction tip is mounted onto
18 the tip bushing.

19 Figure 16 is a cross section view of the modified dental
20 suction tool of Figure 12 with the suction tip mounted onto the
21 tip bushing.

22 Figure 17 is an isometric view of the suction tip used in
23 the modified dental suction tool of Figure 12.

24 Figure 18 is an isometric view of a modified suction tip
25 used in the modified dental suction tool of Figure 12.

WO 99/47068

PCT/US98/05508

1 Figure 19 is a cross sectional view of another modified
2 suction tip used in the modified dental suction tool of Figure
3 12.

4 Figure 20 is a cross sectional view of the modified suction
5 tip of Figure 19 used in the modified dental suction tool of
6 Figure 12.

7
8 Detailed Description of the Preferred Embodiments

9 The dental suction tool of the present invention is shown
10 generally at 10 in Figure 1. The dental suction tool 10
11 comprises a valve cap 20, a valve body 40, a lever 50 and a light
12 assembly 70. A suction tip 80 is mounted in the valve body 40
13 and the entire dental suction tool 10 is connected to a source
14 of vacuum and electrical power (not shown).

15 The valve cap 20 comprises an externally threaded cap
16 section 22, preferably configured as a hollow cylinder. On each
17 of the diametrically opposite sides of the threaded cap section
18 22, a cylinder aperture 24 is provided of sufficient diameter to
19 receive the rotating cylinder 60 therethrough when the dental
20 suction tool 10 is assembled. Toward the rear of the threaded
21 cap section 22, there is provided a cap top 26 and a cap
22 extension 30. The cap extension 30 is provided with an annular
23 groove 32 to receive the tubing connector base 38. The tubing
24 connector base 38 is attached to the tubing (not shown) that runs
25 from the power supply and the vacuum suction supply typically
26 provided at a remote location from the dentist's chair.

WO 99/47068

PCT/US98/05508

1 The valve body 40 includes a generally hollow threaded body
2 section 42 with a set of internal threads 46 that cooperate and
3 receive the threaded cap section 22 of the valve cap 20 when the
4 valve cap 20 is assembled with the valve body 40. The valve body
5 40 has a cylinder aperture 44 on its one side and another
6 cylinder aperture (not shown) on the opposite side of the
7 threaded body section 42. These cylinder apertures receive the
8 rotating cylinder 60 when the dental suction tool 10 is assem-
9 bled.

10 The rotating cylinder 60 is a generally cylindrical body
11 with a cylinder passageway 62 diametrically therethrough. Each
12 end of the rotating cylinder 60 has a fastening recess shaped to
13 correspond to the fastening pins on the lever 50. One end of the
14 rotating cylinder 60 has an annular groove 66 that receives an
15 O ring 67 and the other end of the rotating cylinder 60 has a
16 like annular groove 64 that receives an O ring 65.

17 The lever 50 can be of any suitable configuration such as
18 the generally U-shaped configuration shown. The lever 50 has a
19 first side arm 51 with a first fastening connector 53 mounted
20 thereon that fits in the associated first fastening recess (not
21 shown) on the rotating cylinder 60 and a second side arm 52 with
22 a second fastening connector (not shown) that fits in the
23 associated second fastening recess 63 on the rotating cylinder
24 60. Each of the first side arm 51 and the second side arm 52 are
25 connected by the cross piece 56 so that each arm moves with the
26 other to rotate the rotating cylinder 60 upon movement of the

WO 99/47068

PCT/US98/05508

1 lever 50.

2 The dental suction tool 10 also includes a light assembly
3 70 comprising a light ring 72 at one end of a fiberoptic bundle
4 74 that extends the length of the dental suction tool 10.
5 Adjacent, but slightly separated from the light ring 72 is an
6 alignment cylinder 78 which assists in properly aligning the
7 light assembly 70 on the interior of the dental suction tool 10
8 when all of the elements of the dental suction tool 10 are
9 assembled together into its working state.

10 The valve body 40 includes a suction tip passageway 48 which
11 opens at the end of the conical end section 43 in which is
12 inserted the disposable suction tip 80. The suction tip 80 may
13 have a number of configurations as will be further explained
14 herein.

15 Figure 2 shows in cross section the dental suction tool 10
16 in an assembled condition with the lever 50 set so that the
17 rotating cylinder 60 is open to allow the vacuum source to
18 provide suction to the suction tip 80. The valve body 40 has a
19 light ring cavity 45 that receives the light ring 72 and the
20 alignment cylinder 78. When the suction tip 80 is inserted into
21 the suction tip passageway 48 of the valve body 40, the end of
22 the suction tip 80 abuts the light ring 72. The suction tip 80
23 is held securely inside the valve body 40 by means of one or more
24 O rings 49 provided therein along the length of the suction tip
25 passageway 48. By simply pulling out the suction tip 80, a new
26 suction tip 80 can be inserted into the valve body 40 for each

WO 99/47068

PCT/US98/05308

1 new patient thereby maintaining a clean and sanitary suction tool
2 and the elimination of any possible cross contamination between
3 patients.

4 Activation of the power supply to the light assembly 70
5 transmits light through the fiberoptic bundle 74 and into the
6 light ring 72. The light emitting from the light ring 72 is
7 transmitted along the length of the suction tip 80 and out the
8 end thereof into the patient's oral cavity.

9 In the embodiment of the invention shown in Figure 2, the
10 suction tip 80 is a bi-layered extrusion. The inner layer is a
11 fiberoptic tubing 86 which will transmit the light from the light
12 ring 72 along the length of the fiberoptic tubing 86 and out its
13 end into the patient's mouth. The outer layer is plastic layer
14 84 which can be clear or opaque as desired. In the preferred
15 embodiment, the plastic layer 84 should be a clear light-
16 transmitting plastic material which can also transmit light from
17 the light ring 72 along the length of the plastic layer 84.

18 When the lever 50 is rotated approximately 90° as shown in
19 Figure 3, the rotating cylinder 60 likewise rotates approximately
20 90°. This disassociates the cylinder passageway 62 from the
21 alignment cylinder passageway 79 and no suction will be provided
22 to the suction tip 80. However, light from the light ring 72
23 will continue to be transmitted along the length of the suction
24 tip 80 and into the patient's oral cavity as long as power is
25 supplied to the fiberoptic bundle 74. This allows the dental
26 suction tool 10 to function as a light source even when suction

WO 99/47068

PCT/US98/05508

1 is not required for a particular dental procedure.

2 Figures 4-6 show a modification of the dental suction tool
3 10 of the present invention. Like reference numerals are used
4 to identify the elements from Figures 1-3 that are the same in
5 Figure 4-6.

6 In Figures 4 and 6, a tip insertion block 90 is added to the
7 rear cavity 45 in front of the light ring 72. As shown in
8 Figures 5 and 6, the tip insertion block 90 has beveled top and
9 bottom portions on its internal bore that correspond to the
10 beveled sections 82 on diametrically opposed sides in the outer
11 wall surface of the suction tip 80. In the preferred embodiment
12 of the present invention as shown in Figure 5, the beveled
13 sections 82 are formed in the outer wall surface of the suction
14 tip 80. As the suction tip 80 is inserted into the valve body
15 40, the beveled sections 82 align with the beveled top and bottom
16 portions on the interior of the tip insertion block 90 and effect
17 the proper alignment of the suction tip 80 in the valve body 40.

18 Figures 7, 8 and 9 show another modification of the dental
19 suction tool 10 of the present invention. Like reference
20 numerals are used to identify the elements from Figures 1-3 that
21 are the same in Figure 7 and 8.

22 In Figures 7, 8 and 9, a key 96 is added to the interior of
23 the valve body 40 in front of the light ring 72. This key 96
24 will act as an alignment device when the suction tip 180 is
25 inserted into the valve body 40.

WO 99/47068

PCT/US98/05508

1 As shown in Figures 7 and 9, the suction tip 180 has a
2 plurality of recesses 182 that are positioned around the
3 circumference of the suction tip 180 in the outer wall surface
4 thereof in equally spaced locations. In the preferred embodiment
5 of the present invention as shown in Figures 7 and 9, the
6 recesses 182 are formed in the outer wall surface of the suction
7 tip 180. When the suction tip 180 is inserted into the valve
8 body 40, one of the recesses 182 aligns with the key 96 and
9 effects the proper alignment of the suction tip 180 in the valve
10 body 40. Since the suction tip 180 has a slight bend therein,
11 by providing a plurality of recesses 182 around the circumference
12 of the suction tip 180, a dentist may orient the suction tip 180
13 in a number of directions to permit the suction tip 180 to be
14 utilized in any desired manner by the dentist.

15 Figure 8 also shows another embodiment of the suction tip
16 180 which eliminates the fiberoptic layer on the inside of the
17 suction tip. In this embodiment, a clear plastic material that
18 is light transmitting is used for the suction tip 180. When the
19 light ring 72 is activated, light emitting therefrom will travel
20 through the body of the suction tip 180 and be emitted from the
21 end thereof. This embodiment simplifies the manufacturing of the
22 suction tip 180 and lowers its cost.

23 Figures 10 and 11 show still another modification of the
24 dental suction tool 10 of the present invention. Like reference
25 numerals are used to identify the elements from Figures 1-3 that
26 are the same in Figures 9 and Figure 10.

WO 99/47068

PCT/US98/05508

1 The embodiment of the invention shown in Figures 9 and 10
2 also use the key 96 that is added to the rear cavity 45 in front
3 of the light ring 72. This key 96 will act as an alignment
4 device when the suction tip 280 is inserted into the valve body
5 40.

6 The suction tip 280 also eliminates the fiberoptic layer on
7 the inside of the suction tip. In this embodiment, the suction
8 tip 280 is comprised of two extruded layers of plastic material,
9 an outer layer 284 of opaque material and an inner layer 286 of
10 clear plastic material that is light transmitting. The suction
11 tip 280 has a plurality of recesses 282 that are positioned
12 around the circumference of the suction tip 280 in the outer wall
13 surface thereof in equally spaced locations. In the preferred
14 embodiment of the present invention as shown in Figures 9 and 10,
15 the recesses 282 are formed in the outer wall surface of the
16 suction tip 280. When the light ring 72 is activated, light
17 emitting therefrom will travel through the inner layer 286 of the
18 suction tip 280 and be emitted from the end thereof. The outer
19 layer 284 being opaque will prevent light loss through the
20 lateral sides of the suction tip 280 so that the light intensity
21 emitted from the end of the suction tip 280 is increased.
22 Alternatively, instead of using an opaque outer layer that has
23 been coextruded, it is also within the scope of the invention to
24 apply a coating of opaque material to the outer surface of the
25 inner layer to minimize the loss of light through the outer
26 surface of the suction tip 280.

WO 99/47068

PCT/US98/05508

1 Another embodiment of the dental suction tool of the present
2 invention is shown generally at 300 in Figure 12. The dental
3 suction tool 300 comprises a valve body 320, a tip holder 340,
4 a rotating cylinder 350 and a plurality of fiberoptic bundles
5 312. A suction tip 380 is mounted in the tip holder 340 and the
6 entire dental suction tool 300 is connected to a source of vacuum
7 and electrical power (not shown).

8 The valve body 320 comprises a main section 321 including
9 a suction line connector 316 integrally formed therewith. The
10 main section 321 and the suction line connector 316 have a
11 passageway 318 extending therethrough so that the source of
12 vacuum can be provided to the suction tip 380. On the top of the
13 main section 321 are a plurality of fiberoptic bundle channels
14 326 in which are seated the fiberoptic bundles 312 and a top
15 valve body cover 322 is placed thereover by any suitable
16 fastening means, such as the interlocking shoulder assembly shown
17 in Figure 15. The bottom of the main section 321 also has a
18 plurality of fiberoptic bundle channels (not shown, but similar
19 to channels 326) which also seat the fiberoptic bundles 312 and
20 are covered by the bottom valve body cover 324 which is also held
21 in place by any suitable fastening means, such as the interlock-
22 ing shoulder assembly shown in Figure 15. The fiberoptic bundles
23 312 extend through the main section 321 and terminate on the
24 interior of the main section 321 at the point in which the main
25 section 321 joins to the main section extension 329. This allows
26 the light emitting from the end of the fiberoptic bundles 312 to

WO 99/47068

PCT/JP98/05508

1 interact with the end of the suction tip 380 as will be explained
2 further herein. As an alternative to the use of fiberoptic
3 bundles 312, any suitable light transmitting conduits may be
4 used; as few as one light transmitting conduit can be used as
5 long as the intensity of the light transmitted through the light
6 transmitting conduit to the suction tip and from there into the
7 patient's oral cavity is sufficient to provide the desired amount
8 of illumination.

9 On each of the diametrically opposite sides of the valve
10 body 320, an aperture 327 is provided of sufficient diameter to
11 receive the rotating cylinder 350 therethrough when the dental
12 suction tool 300 is assembled. The rotating cylinder 350
13 comprises a cylinder body 354 having a passageway 356 there-
14 through and the rotating cylinder 350 is held in place inside the
15 valve body 320 by means of O ring 355 and O ring 357. The
16 rotating cylinder 350 also has a cylinder cap 352 which can be
17 gripped by the user to effect rotation of the rotating cylinder
18 350 to open and close the passageway 356 relative to the
19 passageway 318 to control the suction provided to the suction tip
20 380.

21 At one end of the main section 321 there is a main section
22 extension 329 that comprises a hollow cylindrical body. This
23 main section extension 329 surrounds a bushing extension 330
24 which is press fit into a recess in the main section 321. The
25 bushing extension 330 has a tip bushing 332 thereon. The tip
26 bushing 332 preferably has a circumferential conical shape to

WO 99/47068

PCT/US98/05508

1 receive the end of the suction tip 380 as will be explained
2 herein. The bushing extension 330 also has an internal passage-
3 way 331 aligned with the passageway 318. At the approximate
4 junction of the main section extension 330 with the main section
5 321, there is provided a groove 334 which receives an O ring 349.

6 Also provided is a tip holder 340 which is preferably a
7 conically-shaped member. The wide end of the tip holder 340 has
8 an interior circumferential shoulder 342 that cooperates with the
9 O ring 349 to hold the tip holder 340 in place when it is
10 assembled onto the valve body 320.

11 The tip holder 340 includes a suction tip passageway 348
12 which opens at the end of the tip holder 340 and in which is
13 inserted the disposable suction tip 380.

14 The details of one of the preferred embodiments of the
15 suction tip 380 are shown in Figure 17. The suction tip 380 is
16 a generally cylindrical hollow member having at one end a beveled
17 section 382. At the opposite end of the suction tip 380, there
18 are provided a plurality of fingers 384. In the preferred
19 embodiment of the present invention, four slots 388 are shown
20 equally spaced around the circumference of the suction tip 380.
21 While the maximum depth of the slots 388 should not exceed the
22 axial length of the tip holder 340 (in order to maintain the
23 vacuum inside the suction tip 380), the minimum depth of the
24 slots 388 should not be less than 0.125". The slots 388 create
25 a plurality of fingers 384 at the end of the suction tip 380.
26 The end of each finger 384 is provided with an interior shoulder

WO 99/47068

PCT/US98/05508

1 386 of the appropriate size to interact with the tip bushing 332
2 on the bushing extension 330.

3 Figures 15 and 16 show the assembly of the dental suction
4 tool 300. The O ring 349 is mounted into the groove 334. The
5 tip holder 340 is positioned over the bushing extension 330 and
6 is snapped into place by means of the shoulder 342 interacting
7 with the O ring 349. The end of the suction tip 380 having the
8 fingers 384 is inserted into the tip holder 340 and pushed
9 therein until the fingers 384 spread out and hook over the tip
10 bushing 332 on the bushing extension 330. The shoulders 386 on
11 the interior of the fingers 384 interact with the tip bushing 332
12 to prevent the suction tip 380 from simply falling out of the tip
13 holder 340, but the suction tip 380 is flexible enough to allow
14 the suction tip 380 to be manually removed and replaced with a
15 new suction tip 380 when needed.

16 When the suction tip 380 is inserted into the suction tip
17 passageway 348 of the tip holder 340 and pushed onto the tip
18 bushing 332, the end of the suction tip 380 is positioned
19 adjacent the ends of the fiberoptic bundles 312 so that light
20 emitting from the ends of the fiberoptic bundles 312 can be
21 transmitted into the suction tip 380. By simply pulling out the
22 suction tip 380, a new suction tip 380 can be inserted into the
23 tip holder 340 for each new patient thereby maintaining a clean
24 and sanitary suction tool and the elimination of any possible
25 cross contamination between patients.

WO 99/47068

PCT/US98/05508

1 Activation of the power supply transmits light through the
2 fiberoptic bundles 312. The light emitting from the fiberoptic
3 bundles 312 is transmitted along the length of the suction tip
4 380 and out the end thereof into the patient's oral cavity.

5 Other modifications can be made to this embodiment. As
6 shown in Figure 18, the suction tip 380 can be made with a single
7 slot 388 instead of the four slots 388 shown in Figure 17. In
8 this single slot 388 embodiment, there is still enough flexibil-
9 ity in the plastic material so that the open end of the suction
10 tip 380 can expand around the tip bushing 332 and be held in
11 place. As long as at least one slot 388 is used, the suction tip
12 380 is functional. More than one slot may also be used.

13 Figures 19 and 20 show another modification of the suction
14 tip 380 of the present invention. In this embodiment, the
15 shoulder 386 is omitted and an internal groove 392 is used in its
16 place. When the suction tip 380 is pushed onto the tip bushing
17 332, the tip bushing 332 sets into the internal groove 392 to
18 hold the suction tip 380 in place. One or more slots 388 are
19 required, such as the two diametrically opposed slots 388 shown
20 in Figures 19 and 20. Additionally, a vacuum relief aperture 394
21 can be provided at the closed end of the slot 388. Also, to
22 provide additional gripping pressure on the suction tip 380, an
23 O ring 396 can be included in the tip holder 340.

24 In the preferred embodiment of this modification, a clear
25 plastic material that is light transmitting is used for the
26 suction tip 380. Suitable materials that can be used are

WO 99/47068

PCT/US98/05508

1 acrylics, cellulosics and other light conducting plastics.

2 While the invention has been illustrated with respect to
3 several specific embodiments thereof, these embodiments should
4 be considered as illustrative rather than limiting. Various
5 modifications and additions may be made and will be apparent to
6 those skilled in the art. Accordingly, the invention should not
7 be limited by the foregoing description, but rather should be
8 defined only by the following claims.

74904-12D

CLAIMS:

1. A suction tip for use in a dental suction tool comprising a plastic material formed as a generally cylindrical hollow tubing, one end of the suction tip having
5 at least one recess formed in an outer wall surface of the suction tip so that the suction tip can be properly aligned in the dental suction tool.
2. The suction tip of claim 1 in which a plurality of recesses are provided circumferentially around the perimeter
10 of the suction tip.
3. The suction tip of claim 1 in which a plurality of recesses are provided circumferentially and equally spaced around the perimeter of the suction tip.
4. The suction tip of claim 1 in which the suction
15 tip comprises a single layer of light transmitting material.
5. A suction tip for use in a dental suction tool comprising a plastic material formed as a generally cylindrical hollow tubing, one end of the suction tip having
20 at least one recess formed in an outer wall surface of the suction tip so that the suction tip can be properly aligned in the dental suction tool, the suction tip further comprising an inner layer of light transmitting material and an outer layer of opaque material.
6. The suction tip of claim 5 in which the outer
25 layer is a coating applied to the inner layer.

SMART & BIGGAR
OTTAWA, CANADA

PATENT AGENTS




FIG-1






FIG-2








FIG-5




FIG-6




FIG-7




FIG-8




FIG-9





FIG-10






FIG-12




FIG-14




FIG-13




FIG-15




FIG-16




FIG-17




FIG-18





FIG-19

FIG-20

