

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2010200234 B2**

(54) Title
Reduction of constituents in tobacco

(51) International Patent Classification(s)
A24B 15/28 (2006.01) **A24B 15/26** (2006.01)
A24B 15/24 (2006.01)

(21) Application No: **2010200234** (22) Date of Filing: **2010.01.21**

(43) Publication Date: **2010.02.11**

(43) Publication Journal Date: **2010.02.11**

(44) Accepted Journal Date: **2012.06.21**

(62) Divisional of:
2003261187

(71) Applicant(s)
Phasex Corporation;U.S. Smokeless Tobacco Company

(72) Inventor(s)
Bennett, Clifford Brown;Gudinas, Anthony;Johnston, Kathleen S.;Krukonis, Val;Midgett, Carl H.;Wetmore, Paula M.;Schonemann, Hans;Williams, Kara;Zheng, Harry Y.

(74) Agent / Attorney
Spruson & Ferguson, Level 35 St Martins Tower 31 Market Street, Sydney, NSW, 2000

(56) Related Art
US 4506682 A
US 6048404 A

REDUCTION OF CONSTITUENTS IN TOBACCO

Abstract

Methods of selectively reducing constituents in tobacco as well as the tobacco obtained by such methods are disclosed. Subcritical fluids, e.g., liquid carbon dioxide, serve as the reduction media.

AUSTRALIA
PATENTS ACT 1990
COMPLETE SPECIFICATION

FOR A STANDARD PATENT

Name and Address of Applicants:	Phasex Corporation, of 360 Merrimack Street, Lawrence, Massachusetts, 01843, United States of America U.S. Smokeless Tobacco Company, of 100 West Putnam Avenue, Greenwich, Connecticut, 06830, United States of America
Actual Inventor(s):	Clifford Brown Bennett Anthony Gudinas Kathleen S. Johnston Val Krukonis Carl H. Midgett Hans Schonemann Paula M. Wetmore Kara Williams Harry Y. Zheng
Address for Service:	Spruson & Ferguson St Martins Tower Level 35 31 Market Street Sydney NSW 2000 (CCN 3710000177)
Invention Title:	Reduction of constituents in tobacco

The following statement is a full description of this invention, including the best method of performing it known to me/us:

REDUCTION OF CONSTITUENTS IN TOBACCO

5

BACKGROUND OF THE INVENTION

The present invention relates to tobacco (*Nicotiana* spp.) and preparations thereof that have reduced concentrations of certain constituents.

10 Plants contain a myriad of compounds that have industrial, agricultural, and medical uses. Such compounds may often be obtained by extraction using a variety of methods. In addition, plant matter itself is often employed in a variety of industries, e.g., textiles, and the chemical content of the plant matter may be altered prior to use, for example, by extraction processes, chemical treatment, heat treatment, or biological treatment.

15 Several processes have been employed to extract compounds from plant matter. For example, extractions have employed aqueous based and organic solvents, gases, and supercritical fluids. The process employed determines the compounds that are removed from the plant matter and the compounds that are retained in association with the plant matter.

20 In addition, the various processes used for extraction may differ according to cost, equipment needs, hazardous nature of the chemicals, complexity of the extraction, and adverse affects on the plant matter. For example, supercritical extraction in the manufacture of a plant-based product may negatively impact the economic feasibility of commercialization because the process is complex and expensive and requires specialized equipment. Other extraction methods may
25 have a lower cost and be less complex but lead to an unsatisfactory product, e.g., one that has a negatively impacted flavor, aroma, or quality. Other processes may also be difficult to employ on a scale suitable for mass production.

Thus, there is a need for a simple, scaleable, environmentally sound, and
30 commercially viable process to reduce unwanted constituents in plant matter, such as tobacco, without otherwise substantially altering the attributes of the product.

SUMMARY OF THE INVENTION

The invention features methods of reducing the amount of constituents in tobacco, as well as the tobacco obtained by such methods. More specifically, such methods are performed on the tobacco itself rather than on aqueous tobacco extracts. These methods are capable of reducing constituents without significant reduction in tobacco attributes. For example, the methods of the invention may be used to reduce secondary alkaloids selectively compared to primary alkaloids.

Accordingly, the invention features a method of reducing an amount of a constituent, e.g., a secondary alkaloid or polycyclic aromatic hydrocarbon (PAH), in tobacco by providing a vessel containing tobacco comprising the constituent; contacting the tobacco with a subcritical fluid; and removing the subcritical fluid from the vessel, e.g., by venting to the atmosphere or a second vessel. Preferably, the methods of the invention selectively reduce the amount of the constituent relative to a primary alkaloid.

In another aspect, the invention features a method of reducing the amount of a constituent in tobacco by providing a plurality of valved vessels connected to form a system, wherein the plurality of vessels contains tobacco comprising the constituent; contacting tobacco in a first vessel with a subcritical fluid; removing the subcritical fluid from the first vessel; and directing subcritical fluid, e.g., that from the first vessel, to a second vessel, to additional vessels, or to a waste vessel (or vented to atmosphere) as desired. The method may further include the steps of isolating the first vessel (or any other) from the system; and removing the tobacco from the first vessel, wherein the tobacco has a reduced amount of the constituent. This further step may occur before, during, or after the subcritical fluid has been removed from the first vessel.

In various embodiments of the above aspects of the invention, the method may include the step of separating a constituent from the subcritical fluid. This separation from the subcritical fluid may include the step of flowing the subcritical fluid containing the constituent into a second vessel that may or may not contain a substance capable of extracting a given constituent from the

subcritical fluid. Exemplary substances include solid citric acid, an aqueous solution of citric acid, activated carbon, and solid magnesium silicate. Upon exiting a vessel or entering a second vessel (e.g., a separator vessel), the pressure or temperature of the subcritical fluid may be changed. In certain embodiments, a decrease in pressure causes a precipitation of the dissolved constituents. In other embodiments, the method further includes recirculating the subcritical fluid, after separation of the constituent, to a vessel containing tobacco. During recirculation, any flavor or aroma compounds removed from the tobacco with a constituent may be re-deposited in the tobacco.

10 A variety of subcritical fluids, as disclosed herein, may be employed in the methods of the invention. The temperature and pressures employed for each subcritical fluid (or mixture thereof) may vary depending on the subcritical fluids employed. The subcritical fluid may be in liquid form, e.g., a compressed gas, or in gas form.

15 In various embodiments, the methods reduce the amount of a constituent, e.g., secondary alkaloids or PAHs, in the tobacco by at least 10%, 20%, 30%, 40%, 50%, 60%, 70%, 75%, 85%, or 95%.

In yet another embodiment, the methods selectively reduce the amount of a constituent, e.g., secondary alkaloids or PAHs, in the tobacco by at least 10%, 20%, 30%, 40%, 50%, 60%, 70%, 75%, 85%, or 95%. The methods preferably retain at least 30%, 40%, 50%, 75%, 85%, 95%, or 99% of a primary alkaloid or a particular attribute, such as flavor or aroma compounds.

25 The tobacco employed typically has a moisture content of between 5-60%, e.g., at least 10%, 15%, 20%, 30%, 40%, or 50%. The pH of the tobacco is typically between 4 and 9, e.g., at least pH 5, 6, 7, or 8.

The invention further features tobacco or a tobacco product treated by the above-described methods.

By a "chlorofluorocarbon" is meant a compound including only carbon, fluorine, and chlorine atoms.

30 By a "chlorofluorohydrocarbon" is meant a compound including only carbon, hydrogen, fluorine, and chlorine atoms.

By "constituent" is meant secondary alkaloids and polycyclic aromatic hydrocarbons (PAH) found in tobacco. By "PAHs" is meant anthracene, anthanthrene, benzo(a)pyrene, coronene, fluoranthene, fluorene, naphthalene, phenanthrene, pyrene, and perylene. By "secondary alkaloid" is meant N-
5 nitrosodimethylamine, N-nitrosodiethylamine, N-nitrosopyrrolidine, N-nitrosodiethanolamine, N-nitrosonornicotine (NNN), 4-(methylnitrosamino)-1-(3-pyridyl)-1-butanone (NNK), N-nitrosoanatabine (NAT), or N-nitrosoanabasine (NAB).

By "primary alkaloid" is meant any alkaloid other than a secondary
10 alkaloid.

By "tobacco attribute" is meant a flavor or aroma compound.

By a "hydrocarbon" is meant a compound including only carbon and hydrogen atoms.

By "reducing" is meant a lowering the detectable amount of a constituent
15 in tobacco.

By "subcritical fluid" is meant a compound, or mixture of compounds, that is a gas at ambient temperature and pressure. The term encompasses both the liquid and gaseous phases for such a compound. Exemplary subcritical fluids include, without limitation, carbon dioxide, chlorofluorocarbons,
20 chlorofluorohydrocarbons (e.g., Freon 22), hydrocarbons (e.g., ethane, propane, and butane), nitrous oxide, and combinations thereof.

By "tobacco" is meant any part of any member of the genus *Nicotiana*, e.g., leaves and stems. The tobacco may be whole, shredded, cut, cured, fermented, or otherwise processed. Tobacco may also be in the form of finished
25 products, including but not limited to smokeless tobacco, snuff (moist or dry), chewing tobacco, cigarettes, cigars, and pipe tobacco.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic representation of a system suitable for an industrial
30 setting, utilizing, e.g., liquid carbon dioxide under subcritical conditions to reduce the amount of a constituent in tobacco.

Fig. 2 is a schematic representation of a laboratory-scale apparatus, e.g., utilizing liquid carbon dioxide under subcritical conditions to reduce the amount of a constituent in tobacco.

5 DETAILED DESCRIPTION OF THE INVENTION

Laboratory scale and suitable industrial scale methods of selectively reducing the amount of certain constituents in tobacco are described along with test data detailing the effectiveness of such methods. Notably, these methods are performed on tobacco itself. In addition, the tobacco can be from any source,
10 including dried, cured, or processed, and can further be in the form of finished products, e.g., cigarettes, snuff (moist or dry), and cigars. These methods can reduce the amount of one or more constituents without substantially removing tobacco attributes.

As shown in Fig. 1, an industrial type system utilizing, e.g., liquid carbon
15 dioxide under subcritical conditions, can be used to reduce the amount of one or more constituents in tobacco. Although only one vessel 6 is shown in Figure 1, it is understood that a plurality of such vessels can be utilized, in series, in a large-scale system.

As further shown in Fig. 1, tobacco 5 is charged to vessel 6, which is then
20 sealed so as to be able to operate under elevated pressure conditions, e.g., necessary to maintain a subcritical fluid as a liquid therein. Subcritical fluid 2, e.g., carbon dioxide, initially stored as shown in supply vessel 1, is directed through and is pumped to a desired pressure by inlet pump 3. After pressurized subcritical fluid 2 passes through inlet pump 3, the liquid proceeds, via circulation
25 pump 4 into vessel 6 and through the charge of tobacco 5. As the liquid subcritical fluid 2 flows through tobacco 5, the amount of constituents in tobacco 5 is reduced. After exiting vessel 6, a subcritical fluid stream, which at this point may be gaseous, flows into and through separator vessel 7. The separator vessel may contain a substance 8, which traps basic constituents and, thereby, depletes
30 the subcritical fluid of any dissolved or suspended constituents. The substance 8 can be drained from separator vessel 7 via drain valve 9, particularly after the

solution accumulates a significant amount of constituents. A suitable substance 8 is an aqueous citric acid solution. Other possible substances effective for separating out constituents include, for example, solid magnesium silicate or any other such solution or solid capable of binding the desired constituents.

5 The subcritical fluid, once depleted of any dissolved or suspended constituents may be recirculated to the vessel 6, as shown, via line R. Circulation pump 4 may be designed such that subcritical fluid entering its inlet from line R may, once again, be pressurized so as to liquify before entering vessel 6. Those having ordinary skill in the art will recognize that pump 4 may thus act to re-

10 pressurize the subcritical fluid entering pump 4 from either supply vessel 1 or line R. Following completion of the reduction process, the system may be depressurized and constituent-reduced tobacco 5 removed. The process time may vary depending on a variety of processing parameters. One of ordinary skill in the art will readily be able to determine suitable process times. Ranges of

15 appropriate process times are discussed below in connection with trial runs performed on a laboratory-scale system.

 The virtually continuous circulation of subcritical fluid and the inherent capability of reducing constituents from multiple charges of tobacco residing in a plurality of vessels are two clear advantages to be exploited. Elimination of

20 costly down time brought about by emptying and recharging of a single vessel 6 is achievable with use of several (typically three or four) valved vessels 6 operating in series. Vessels may also be operated in parallel. As noted above, subcritical fluid is pumped in series through the several vessels 6. When the charge of tobacco in one of the vessels has become constituent-reduced and is

25 ready to be removed, the subcritical fluid can be diverted from that vessel to another vessel containing tobacco or a separation vessel. This subcritical fluid may still be effective for reducing constituents from other charges of tobacco in other vessels. The vessel from which tobacco is ready to be removed may be isolated from the system without interfering with on-going reductions in other

30 vessels. New tobacco may then be placed into the vessel, and the process can continue without overall system interruption.

Preferably, treated tobacco substantially retains the taste and aroma of untreated tobacco. Alternatively, any flavor or aroma compounds removed during treatment may be re-deposited in the tobacco, e.g., after removal of any constituents from the subcritical fluid. The flavor and aroma content of tobacco
5 can be determined by taste and smell tests.

The following examples illustrate various embodiments of the present invention and are not intended to be limiting in any way.

10 **Example 1. Reduction of constituents using subcritical carbon dioxide.**

Fig. 2 shows a schematic representation of a laboratory-scale system that can be used to produce reduced constituent content in tobacco. The representative data of Table 1 were developed using such a system, which was operated in the following manner. A sample of tobacco 16 was placed in vessel
15 15, and the vessel was sealed. Gaseous subcritical fluid 12 was supplied from cylinder 11 and admitted to the system. When pressure (as measured by gauges A and B) reached cylinder pressure, compressor pump 13 was energized to liquify the fluid 12. Temperature was adjusted and controlled using preheater 14 and was measured with thermocouples C and D. Flow of subcritical fluid 12 was
20 then started using adjustable flow control valve 17 that was set so as to operate at a selected flow rate measured by flow meter 19. The range of flow rate may be between about 5 grams/min to 150 grams/min; for convenience 20-30 grams/min rate was chosen for the experimental runs. Pressure was reduced across valve 17, resulting in the gaseous subcritical fluid passing into filter flask 18 into which
25 constituent-rich extract could be collected. Alternatively, the subcritical fluid was vented to a waste vessel. The total flow of subcritical fluid 12 passed through the charge of tobacco 16 during the duration of a run was measured by dry test meter 20. In this laboratory system, no separation vessel was used to facilitate recirculation of subcritical fluid 12. Vessel 15 was a stainless steel tube having a
30 length of 10 inches, an outside diameter of 1 inch, and a volume of about 60 ml. After treatment, the tobacco 16 was analyzed for its constituent content and the

percent reduction of constituent content. The run time necessary to produce such tobacco may be anywhere between about 2 and 14 hours, preferably in the range of about 4-8 hours.

The carbon dioxide utilized according to the present invention should be a subcritical fluid (critical point 31 °C and 1070 psi), e.g., a liquid. In practicing the process of the present invention, carbon dioxide temperature, pressure, or both can be adjusted to ensure that it is a subcritical fluid, for example, by an inlet heat exchanger (not shown). The run pressure was held essentially constant (in the range of between about 1000 and 2200 psi) for a given run. Runs were performed at essentially constant temperatures ranging between about 0 °C and 24 °C. Although a range of mass of subcritical fluid: mass of tobacco ratios can be used, typically between 21 to 50 grams of carbon dioxide per gram of tobacco were used to reduce the maximum amount of constituent.

Table 1 shows data on the reduction of constituents in tobacco employing the laboratory-scale system described above. As shown in Table 1, the process is selective for the reduction of secondary alkaloids relative to primary alkaloids.

Table 1. Reduction of constituents in tobacco with carbon dioxide

Sample	Conditions (°C/psi)	pH	Mass of CO ₂ : Mass of Tobacco	% Moisture Content	% Secondary Alkaloids Reduction	% Primary Alkaloids Reduction
1	17/ 1200	6	21	15	39	4
2	17/ 1200	6	23	30	81	0
3	14/ 1200	6	24	52	74	0
4	19/ 1200	8	50	58	91	2

Example 2. Reduction of constituents using subcritical Freon 22.

Additional experiments according to the method of Example 1 were carried out using Freon 22 (chlorodifluoromethane) (critical point 96 °C, 716 psi) instead of carbon dioxide. The data are shown in Table 2. Exemplary conditions for use of Freon 22 include 0 to 50 °C, 100 to 2000 psi, and a mass of Freon 22 to mass of tobacco ratio of 20 to 100.

Table 2. Reduction of constituents in tobacco with Freon 22

Sample	Conditions (°C/psi)	pH	Mass of Freon 22: Mass of Tobacco	% Moisture Content	% Secondary Alkaloids Reduction	% Primary Alkaloids Reduction
1	27/ 1200	6	53	15	65	52
2		6		55	98	77
3	34/ 1000	8	33	55	95	44

Example 3. Reduction of secondary alkaloids using subcritical propane.

Additional experiments according to the method of Example 1 were carried out using propane (critical point 96.7 °C, 617 psi) instead of carbon dioxide. The data are shown in Table 3. In general, the conditions for use of propane are 0 to 50 °C, 100 to 2000 psi, and a mass of propane to a mass of tobacco ratio of 20 to 100.

Table 3. Reduction of secondary alkaloids in tobacco with propane

Sample	Conditions (°C/psi)	pH	Mass of Propane: Mass of Tobacco	% Moisture Content	% Secondary Alkaloids Reduction	% Primary Alkaloids Reduction
1	20/ 1200	6	22	15	13	10
2	20/ 1200	6	22	60	58	3
3	20/ 1200	8	25	60	51	67

Example 4. Reduction of PAHs using subcritical propane

Table 4 shows data from an experiment according to Example 1 on the
 5 reduction of PAHs in tobacco by treatment with subcritical propane.

Table 4. Reduction of PAHs in tobacco with propane

Sample	Conditions (°C/psi)	pH	Mass of Propane: Mass of Tobacco	% Moisture Content	% PAHs Reduction	% Primary Alkaloids Reduction
1	30/ 1000	6	24	16	77	14

Example 5. Reduction of constituents using other subcritical fluids.

10 The amount of constituents in tobacco may also be reduced using the
 methods of the invention by employing ethane (critical point 32.2 °C, 708 psi) or
 nitrous oxide (critical point 36.5 °C, 1046 psi). Exemplary conditions for use of
 ethane include 0 to 30 °C, 500 to 2000 psi, and a mass of ethane to a mass of
 tobacco ratio of 20 to 100. Exemplary conditions for use of nitrous oxide include
 15 0 to 35 °C, 500 to 2000 psi, and a nitrous oxide to tobacco ratio of 20 to 100.

OTHER EMBODIMENTS

The description of the specific embodiments of the methods and tobacco obtained therefrom is presented for the purposes of illustration. It is not intended to be exhaustive nor to limit the scope of the invention to the specific forms
5 described herein. Although the invention has been described with reference to several embodiments, it will be understood by one of ordinary skill in the art that various modifications can be made without departing from the spirit and the scope of the invention, as set forth in the claims.

Other embodiments are within the claims.

10 What is claimed is:

The claims defining the invention are as follows:

1. A method of reducing an amount of a constituent in tobacco, said method comprising the steps of:

a) providing a vessel containing said tobacco comprising said constituent;

b) contacting said tobacco with subcritical fluid, wherein said subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is ethane at 0-30 °C and 500-2000 psi; said subcritical fluid is propane at 0-50 °C and 100-2000 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is Freon 22 at 0-50 °C and 100-2000 psi; or said subcritical fluid is butane; and

c) removing said subcritical fluid from said vessel, thereby reducing the amount of said constituent in said tobacco.

2. A method of selectively reducing an amount of a secondary alkaloid relative to a primary alkaloid in tobacco, said method comprising the steps of:

(a) providing a vessel containing said tobacco comprising said secondary alkaloid and said primary alkaloid;

(b) contacting said tobacco with a subcritical fluid, wherein said subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is ethane at 0-30 °C and 500-2000 psi; said subcritical fluid is propane at 0-50 °C and 100-2000 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is Freon 22 at 0-50 °C and 100-2000 psi; or said subcritical fluid is butane; and

(c) removing said subcritical fluid from said vessel, thereby selectively reducing the amount of said secondary alkaloid relative to said primary alkaloid in said tobacco.

3. A method of reducing an amount of a polycyclic aromatic hydrocarbon (PAH) in tobacco, said method comprising the steps of:

(a) providing a vessel containing said tobacco comprising said PAH;

(b) contacting said tobacco with a subcritical fluid, wherein said subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is ethane at 0-30 °C and 500-2000 psi; said subcritical fluid is propane at 0-50 °C and 100-2000 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is Freon 22 at 0-50 °C and 100-2000 psi; or said subcritical fluid is butane; and

(c) removing said subcritical fluid from said vessel, thereby reducing the amount of said PAH in said tobacco.

4. A method of selectively reducing an amount of a PAH relative to a primary alkaloid in tobacco, said method comprising the steps of:

5 (a) providing a vessel containing said tobacco comprising said PAH and said primary alkaloid;

(b) contacting said tobacco with a subcritical fluid, wherein said subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is ethane at 0-30 °C and 500-2000 psi; said subcritical
10 fluid is propane at 0-50 °C and 100-2000 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is Freon 22 at 0-50 °C and 100-2000 psi; or said subcritical fluid is butane; and

(c) removing said subcritical fluid from said vessel, thereby selectively reducing the amount of said PAH relative to said primary alkaloid in said tobacco.

15 5. A method of reducing an amount of a constituent in tobacco, said method comprising the steps of:

(a) providing a system comprising a plurality of connected vessels containing said tobacco comprising said constituent;

(b) contacting tobacco in a first vessel with a subcritical fluid, wherein said
20 subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is ethane at 0-30 °C and 500-2000 psi; said subcritical fluid is propane at 0-50 °C and 100-2000 psi and the tobacco has a moisture content of at least 30%; said subcritical fluid is Freon 22 at 0-50 °C and 100-2000 psi; or said subcritical fluid is butane;

25 (c) removing said subcritical fluid from said first vessel; and

(d) directing said subcritical fluid to a second vessel, thereby reducing the amount of said constituent in said tobacco in said first vessel.

6. The method of claim 5, further comprising the steps, before, during, or after step (c) of:

30 (i) isolating said first vessel from said system; and

(ii) removing said tobacco from said first vessel.

7. The method of claim 5, wherein in step (d), said subcritical fluid is that of step (c).

8. The method of any one of claims 1 to 5, wherein in step (b), said subcritical fluid is a liquid.

5 9. The method of claim 8, wherein said liquid is a compressed gas.

10. The method of any one of claims 1 to 5, wherein in step (b), said subcritical fluid is a compressible gas.

11. The method of claim 1 or 5, further comprising, after step (c), the step of separating said constituent from said subcritical fluid.

10 12. The method of claim 2, further comprising, after step (c), the step of separating said secondary alkaloid from said subcritical fluid.

13. The method of claim 3 or 4, further comprising, after step (c), the step of separating said PAH from said subcritical fluid.

15 14. The method of claim 11, wherein said separating comprises flowing said fluid containing said constituent from step (c) into a separator vessel containing a substance capable of separating said constituent from said subcritical fluid.

20 15. The method of claim 12, wherein said separating comprises flowing said fluid containing said secondary alkaloid from step (c) into a separator vessel containing a substance capable of separating said secondary alkaloid from said subcritical fluid.

16. The method of claim 14 or 15, wherein said substance comprises citric acid or magnesium silicate.

25 17. The method of claim 13, wherein said separating comprises flowing said fluid containing said PAH from step (c) into a separator vessel containing a substance capable of separating said PAH from said subcritical fluid.

18. The method of claim 11, wherein said separating comprises flowing said subcritical fluid containing said constituent from step (c) into a separator vessel,

wherein said subcritical fluid undergoes a change in pressure or temperature and said constituent precipitates.

19. The method of claim 12, wherein said separating comprises flowing said subcritical fluid containing said secondary alkaloid from step (c) into a separator vessel, wherein said subcritical fluid undergoes a change in pressure or temperature and said secondary alkaloid precipitates.

20. The method of claim 13, wherein said separating comprises flowing said subcritical fluid containing said PAH from step (c) into a separator vessel, wherein said subcritical fluid undergoes a change in pressure or temperature and said PAH precipitates.

21. The method of claim 11, further comprising, after said separating, the step of recirculating said subcritical fluid to said vessel.

22. The method of claim 12 or 13, further comprising, after said separating, the step of recirculating said subcritical fluid to said vessel.

23. The method of claim 21 or 22, wherein during said recirculating, flavor or aroma compounds removed in step (b) are deposited in said tobacco.

24. The method of any one of claims 1 to 5, wherein said subcritical fluid is carbon dioxide at 0-24 °C and 1000-2200 psi, and the tobacco has a moisture content of at least 30%.

25. The method of any one of claims 1 to 5, wherein the subcritical fluid is ethane at 0-30 °C and 500-2000 psi, Freon 22 at 0-50 °C and 100-2000 psi, or butane, and the tobacco has a moisture content of at least 20%.

26. The method of any one of claims 1, 3, 4 or 5, wherein the pH of said tobacco is between 4 and 9.

27. The method of claim 1 or 5, wherein said constituent is a PAH or a secondary alkaloid.

28. Tobacco processed by any one of the methods of claims 1 to 5.

29. The method of any one of claims 1 to 5, wherein the subcritical fluid is CO₂ at 0-24 °C and 1000-2200 psi or propane at 0-50 °C and 100-2000 psi, and the tobacco has a moisture content of at least 40%.


5 30. The method of any one of claims 1 to 5, wherein the subcritical fluid is CO₂ at 0-24 °C and 1000-2200 psi or propane at 0-50 °C and 100-2000 psi, and the tobacco has a moisture content of at least 50%.

31. The method of any one of claims 1 to 5, wherein the subcritical fluid is ethane at 0-30 °C and 500-2000 psi, Freon 22 at 0-50 °C and 100-2000 psi, or butane, and the tobacco has a moisture content of at least 30%.

10 32. The method of any one of claims 1 to 5, wherein the subcritical fluid is ethane at 0-30 °C and 500-2000 psi, Freon 22 at 0-50 °C and 100-2000 psi, or butane, and the tobacco has a moisture content of at least 40%.

15 **Dated 28 January, 2010**
Phasex Corporation
U.S. Smokeless Tobacco Company

Patent Attorneys for the Applicant/Nominated Person
SPRUSON & FERGUSON






Figure 2