



HU000035135T2

(19) **HU**(11) Lajstromszám: **E 035 135**(13) **T2****MAGYARORSZÁG****Szellemi Tulajdon Nemzeti Hivatala**

EURÓPAI SZABADALOM SZÖVEGÉNEK FORDÍTÁSA

(21) Magyar ügyszám: **E 07 862581**(22) A bejelentés napja: **2007. 12. 06.**(51) Int. Cl.: **H04N 19/597** (2006.01)**H04N 19/70** (2006.01)

(96) Az európai bejelentés bejelentési száma:

EP 20070862581

(86) A nemzetközi (PCT) bejelentési szám:

PCT/US 07/024986

(97) Az európai bejelentés közzétételi adatai:

EP 2103136 A2 **2008. 07. 24.**

(87) A nemzetközi közzétételi szám:

WO 08088497

(97) Az európai szabadalom megadásának meghirdetési adatai:

EP 2103136 B1 **2017. 11. 01.**

(30) Elsőbbségi adatok:

871401 P **2006. 12. 21.** **US**

(73) Jogosult(ak):

**Thomson Licensing, 92130
Issy-les-Moulineaux (FR)**

(72) Feltaláló(k):

**PANDIT, Purvin, Bibhas, Franklin Park, New Jersey
08823 (US)****SU, Yeping, Camas, Washington 98607 (US)****YIN, Peng, West Windsor, New Jersey 08550 (US)**

(74) Képviselő:

SBGK Szabadalmi Ügyvivői Iroda, Budapest

(54) **Eljárások és berendezés továbbfejlesztett jelzéshez magas szintű szintaxis segítségével többnézetes
videokódoláshoz és dekódoláshoz**

Az európai szabadalom ellen, megadásának az Európai Szabadalmi Közlönyben való meghirdetésétől számított kilenc hónapon belül, felszólalást lehet benyújtani az Európai Szabadalmi Hivatalnál. (Európai Szabadalmi Egyezmény 99. cikk(1))

A fordítást a szabadalmat az 1995. évi XXXIII. törvény 84/H. §-a szerint nyújtotta be. A fordítás tartalmi helyességét a Szellemi Tulajdon Nemzeti Hivatala nem vizsgálta.



(11) **EP 2 103 136 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
01.11.2017 Bulletin 2017/44

(21) Application number: **07862581.1**

(22) Date of filing: **06.12.2007**

(51) Int Cl.:
H04N 19/597 (2014.01) H04N 19/70 (2014.01)

(86) International application number:
PCT/US2007/024986

(87) International publication number:
WO 2008/088497 (24.07.2008 Gazette 2008/30)

(54) **METHODS AND APPARATUS FOR IMPROVED SIGNALING USING HIGH LEVEL SYNTAX FOR MULTI-VIEW VIDEO CODING AND DECODING**

VERFAHREN UND VORRICHTUNGEN ZUR VERBESSERTEN SIGNALISIERUNG UNTER
VERWENDUNG VON SYNTAX AUF HOHER EBENE FÜR DIE
MEHRANSICHTS-VIDEOCODIERUNG UND -DECODIERUNG

PROCÉDÉS ET APPAREIL PERMETTANT D'AMÉLIORER LA SIGNALISATION À L'AIDE D'UNE
SYNTAXE DE HAUT NIVEAU POUR LE CODAGE ET DÉCODAGE VIDÉO MULTIVUE

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE
SI SK TR**

(30) Priority: **21.12.2006 US 871401 P**

(43) Date of publication of application:
23.09.2009 Bulletin 2009/39

(60) Divisional application:
**11188626.3 / 2 418 850
11188629.7 / 2 418 851
11188630.5 / 2 418 852**

(73) Proprietor: **Thomson Licensing
92130 Issy-les-Moulineaux (FR)**

(72) Inventors:
• **PANDIT, Purvin, Bibhas**
Franklin Park, New Jersey 08823 (US)
• **SU, Yeping**
Camas, Washington 98607 (US)
• **YIN, Peng**
West Windsor, New Jersey 08550 (US)

(74) Representative: **Le Dantec, Claude et al**
TECHNICOLOR
1-5, rue Jeanne d'Arc
92130 Issy-les-Moulineaux (FR)

(56) References cited:
WO-A-2006/110007

- **SHIM W S ET AL: "High-level syntax for flexible I frame position JVT-U046" JOINT VIDEO TEAM (JVT) OF ISO/IEC MPEG & ITU-T VCEG (ISO/IEC JTC1/SC29/WG11 AND ITU-T SG16 Q.6), [Online] 24 October 2006 (2006-10-24), XP030006692 Hangzhou, China Retrieved from the Internet: URL: http://ftp3.itu.ch/av-arch/jvt-site/2006_10_Hangzhou/JVT-U046.zip [retrieved on 2008-06-19]**
- **VETRO A. ET AL.: "Joint Multiview Video Model (JMVM) 1.0" JOINT VIDEO TEAM (JVT) OF ISO/IEC MPEG & ITU-T VCEG, [Online] 16 August 2006 (2006-08-16), XP002485056 Klagenfurt, Austria Retrieved from the Internet: URL: http://ftp3.itu.ch/av-arch/jvt-site/2006_07_Klagenfurt/JVT-T208.ZIP [retrieved on 2008-06-19]**
- **LIFEN ZHAO ET AL: "The performance study of transmitting MPEG4 over SCTP" NEURAL NETWORKS AND SIGNAL PROCESSING, 2003. PROCEEDINGS OF THE 2003 INTERNATIONAL CONFERENCE ON NANJING, CHINA DEC. 14-17, 2003, PISCATAWAY, NJ, USA, IEEE, vol. 2, 14 December 2003 (2003-12-14), pages 1639-1642, XP010691835 ISBN: 978-0-7803-7702-8**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 103 136 B1

Description**TECHNICAL FIELD**

5 **[0001]** The present principles relate generally to video encoding and decoding and, more particularly, to methods and apparatus for improved signaling using high level syntax for multi-view video coding and decoding.

BACKGROUND

10 **[0002]** In the current version of multi-view video coding (MVC) extension based on the International Organization for Standardization/International Electrotechnical Commission (ISO/IEC) Moving Picture Experts Group-4 (MPEG-4) Part 10 Advanced Video Coding (AVC) standard/International Telecommunication Union, Telecommunication Sector (ITU-T) H.264 recommendation (hereinafter the "MPEG-4 AVC standard"), new syntax is added in the sequence parameter set MVC extension to signal the inter-view references. That is, this syntax is used to indicate the inter-view references to be used for anchor and non-anchor pictures. The document VETRO A. ET AL.: "Joint Multiview Video Model (JMVM) 1.0", JOINT VIDEO TEAM (JVT) OF ISO/IEC MPEG & ITU-T VCEG, [Online] 16 August 2006 (2006-08-16), Klagenfurt, Austria discloses this MVC syntax. This syntax can also serve the purpose of building the view dependency map, which can be used for view random access, an implicit decoded reference picture marking process, and so forth. The syntax is defined by looping the variable view_id from 0 to number of views minus 1. view_id indicates the view identifier for a view. It does not include any coding order information.

[0003] This definition puts some restriction on how to assign view_id for each view. The definition does not allow gaps in view_ids. If later, some views are not coded, the definition will cause some ambiguity. In addition, this definition lacks some features. For example, the definition does not specify the coding order of each view.

[0004] TABLE 1 illustrates the sequence parameter set (SPS) Multi-view Video Coding (MVC) extension syntax.

TABLE 1

seq_parameter_set_mvc_extension() {	C	Descriptor
num_views_minus_1		ue(v)
for(i = 0; i <= num_views_minus_1; i++) {		
num_anchor_refs_l0[i]		ue(v)
for(j = 0; j < num_anchor_refs_l0[i]; j++)		
anchor_ref_l0[i][j]		ue(v)
num_anchor_refs_l1[i]		ue(v)
for(j = 0; j < num_anchor_refs_l1[i]; j++)		
anchor_ref_l1[i][j]		ue(v)
}		
for(i = 0; i <= num_views_minus_1; i++) {		
num_non_anchor_refs_l0[i]		ue(v)
for(j = 0; j < num_non_anchor_refs_l0[i]; j++)		
non_anchor_ref_l0[i][j]		ue(v)
num_non_anchor_refs_l1[i]		ue(v)
for(j = 0; j < num_non_anchor_refs_l1[i]; j++)		
non_anchor_ref_l1[i][j]		ue(v)
}		
}		

[0005] The semantics of the syntaxes in TABLE 1 are defined as follows:

num_views_minus_1 plus 1 identifies the total number of views in the bitstream. The value of the number_of_view_minus_1 shall be in the range of 0 to 1023.

num_anchor_refs_I0[i] specifies the number of inter-view prediction references for list0 for anchor pictures with view_id equal to i. The value of num_anchor_refs_I0[i] shall be less than or equal to num_ref_frames.

anchor_ref_I0[i][j] identifies the view_id of the view that is used as the jth reference of list0, for anchor pictures of the view with view_id equal to i.

num_anchor_refs_I1[i] specifies the number of inter-view prediction references for list1 of the anchor picture with view_id equal to i. The value of num_anchor_refs_I1[i] shall be less than or equal to num_ref_frames.

anchor_ref_I1[i][j] identifies the view_id of the view that is used as the jth reference of list1, for anchor pictures of the view with view_id equal to i.

num_non_anchor_refs_I0[i] specifies the number of inter-view prediction references for list0 for non-anchor pictures with view_id equal to i. The value of num_non_anchor_refs_I0[i] shall be less than or equal to num_ref_frames.

non_anchor_ref_I0[i][j] identifies the view_id of the view that is used as the jth reference of list0, for non-anchor pictures of the view with view_id equal to i.

num_non_anchor_refs_I1[i] specifies the number of inter-view prediction references for list1 for non-anchor pictures with view_id equal to i. The value of num_non_anchor_refs_I1[i] shall be less than or equal to num_ref_frames.

non_anchor_ref_I1[i][j] identifies the view_id of the view that is used as the jth reference of list1, for non-anchor pictures of the view with view_id equal to i.

[0006] The following procedure shall be conducted to place reference pictures from a view that is different from the current view into the reference prediction lists. If the current picture is an anchor picture, then for each value of i from 0 to num_anchor_refs_IX-1, the picture with view_id equal to anchor_ref_IX[i] and with the same PicOrderCnt() as the current picture shall be appended to RefPicListX. Otherwise, if the current picture is not an anchor picture, then for each value of i from 0 to num_non_anchor_refs_IX-1, the picture with view_id equal to non_anchor_ref_IX[i] and with the same PicOrderCnt() as the current picture shall be appended to RefPicListX.

[0007] From TABLE 1, it can be seen that the syntax in the sequence parameter set (SPS) of the Multi-view Video Coding (MVC) extension is defined by looping over the variable view_id from 0 to number of views minus 1. This definition puts some restriction on how to assign view_id for each view. The definition does not allow gaps in view_ids. If later, due to some reason(s), such as bandwidth limitation or a user's interest, some views are not coded, this definition will cause some ambiguity. To keep the continuity of view_id assignment, the following can be implemented.

[0008] In a first prior art method for keeping the continuity of view_id assignment, un-coded view information in maintained in the sequence parameter set and the number of inter-view references is set to 0. However, this is not desirable as the decoder will not know if the un-coded view is intentionally missing or due to transmission errors.

[0009] In a second prior art method for keeping the continuity of view_id assignment, the un-coded view information is removed from the sequence parameter set. However, this will cause view_id gaps. Thus, view_ids have to be re-assigned. This is also not desirable since view_id is no longer unique to each view.

SUMMARY

[0010] These and other drawbacks and disadvantages of the prior art are addressed by the present principles, which are directed to methods and apparatus for improved signaling using high level syntax for multi-view video coding and decoding.

[0011] According to an aspect of the present principles, there is provided an apparatus. The apparatus includes an encoder for encoding at least one picture for at least one view corresponding to multi-view video content in a resultant bitstream, wherein said encoder signals video coding order information for at least the at least one picture in a high level syntax.

[0012] According to another aspect of the present principles, there is provided a method. The method includes encoding at least one picture for at least one view corresponding to multi-view video content in a resultant bitstream, wherein said encoding step comprises signaling video coding order information for at least the at least one picture in a high level syntax.

[0013] According to yet another aspect of the present principles, there is provided an apparatus. The apparatus includes a decoder for decoding at least one picture for at least one view corresponding to multi-view video content in a resultant bitstream, wherein said decoder determines video coding order information for at least the at least one picture from a high level syntax.

[0014] According to a further aspect of the present principles, there is provided a method. The method includes decoding at least one picture for at least one view corresponding to multi-view video content in a resultant bitstream, wherein said decoding step comprises determining video coding order information for at least the at least one picture from a high level syntax.

[0015] These and other aspects, features and advantages of the present principles will become apparent from the following detailed description of exemplary embodiments, which is to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The present principles may be better understood in accordance with the following exemplary figures, in which:

FIG. 1 is a block diagram for an exemplary Multi-view Video Coding (MVC) encoder to which the present principles may be applied, in accordance with an embodiment of the present principles;

FIG. 2 is a block diagram for an exemplary Multi-view Video Coding (MVC) decoder to which the present principles may be applied, in accordance with an embodiment of the present principles;

FIG. 3 is a diagram for a time-first coding structure for a multi-view video coding system with 8 views to which the present principles may be applied, in accordance with an embodiment of the present principles;

FIG. 4 is a flow diagram for an exemplary method for encoding multi-view video content, in accordance with an embodiment of the present principles;

FIG. 5 is a flow diagram for another exemplary method for encoding multi-view video content, in accordance with an embodiment of the present principles;

FIG. 6 is a flow diagram for an exemplary method for decoding multi-view video content, in accordance with an embodiment of the present principles; and

FIG. 7 is a flow diagram for another exemplary method for decoding multi-view video content, in accordance with an embodiment of the present principles.

DETAILED DESCRIPTION

[0017] The present principles are directed to methods and apparatus for improved signaling using high level syntax for multi-view video coding and decoding.

[0018] The present description illustrates the present principles. It will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the present principles and are included within its spirit and scope.

[0019] All examples and conditional language recited herein are intended for pedagogical purposes to aid the reader in understanding the present principles and the concepts contributed by the inventor(s) to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions.

[0020] Moreover, all statements herein reciting principles, aspects, and embodiments of the present principles, as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents as well as equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure.

[0021] Thus, for example, it will be appreciated by those skilled in the art that the block diagrams presented herein represent conceptual views of illustrative circuitry embodying the present principles. Similarly, it will be appreciated that any flow charts, flow diagrams, state transition diagrams, pseudocode, and the like represent various processes which may be substantially represented in computer readable media and so executed by a computer or processor, whether or not such computer or processor is explicitly shown.

[0022] The functions of the various elements shown in the figures may be provided through the use of dedicated hardware as well as hardware capable of executing software in association with appropriate software. When provided by a processor, the functions may be provided by a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term "processor" or "controller" should not be construed to refer exclusively to hardware capable of executing software, and may implicitly include, without limitation, digital signal processor ("DSP") hardware, read-only memory ("ROM") for storing software, random access memory ("RAM"), and non-volatile storage.

[0023] Other hardware, conventional and/or custom, may also be included. Similarly, any switches shown in the figures are conceptual only. Their function may be carried out through the operation of program logic, through dedicated logic, through the interaction of program control and dedicated logic, or even manually, the particular technique being selectable by the implementer as more specifically understood from the context.

[0024] In the claims hereof, any element expressed as a means for performing a specified function is intended to

encompass any way of performing that function including, for example, a) a combination of circuit elements that performs that function or b) software in any form, including, therefore, firmware, microcode or the like, combined with appropriate circuitry for executing that software to perform the function. The present principles as defined by such claims reside in the fact that the functionalities provided by the various recited means are combined and brought together in the manner which the claims call for. It is thus regarded that any means that can provide those functionalities are equivalent to those shown herein.

[0025] Reference in the specification to "one embodiment" or "an embodiment" of the present principles means that a particular feature, structure, characteristic, and so forth described in connection with the embodiment is included in at least one embodiment of the present principles. Thus, the appearances of the phrase "in one embodiment or "in an embodiment" appearing in various places throughout the specification are not necessarily all referring to the same embodiment.

[0026] As used herein, "high level syntax" refers to syntax present in the bitstream that resides hierarchically above the macroblock layer. For example, high level syntax, as used herein, may refer to, but is not limited to, syntax at the slice header level, the sequence parameter set (SPS) level, the picture parameter set (PPS) level, the view parameter set (VPS) level, the network abstraction layer (NAL) unit header level, and in a supplemental enhancement information (SEI) message.

[0027] For the sake of illustration and brevity, the following embodiments are described herein with respect to the use of a high level syntax in the sequence parameter set. However, it is to be appreciated that the present principles are not limited to solely the use of the sequence parameter set with respect to the improved signaling disclosed herein and, thus, such improved signaling may be implemented with respect to at least the above-described types of high level syntaxes including, but not limited to, syntaxes at the slice header level, the sequence parameter set (SPS) level, the picture parameter set (PPS) level, the view parameter set (VPS) level, the network abstraction layer (NAL) unit header level, and in a supplemental enhancement information (SEI) message, while maintaining the spirit of the present principles.

[0028] It is to be further appreciated that while one or more embodiments of the present principles are described herein with respect to the Multi-view extension of the MPEG-4 AVC standard, the present principles are not limited to solely this standard and, thus, may be utilized with respect to other video coding standards, recommendations, and extensions thereof, including extensions of the Multi-view extension of the MPEG-4 AVC standard, while maintaining the spirit of the present principles.

[0029] Moreover, it is to be appreciated that the use of the term "and/or", for example, in the case of "A and/or B", is intended to encompass the selection of the first listed option (A), the selection of the second listed option (B), or the selection of both options (A and B). As a further example, in the case of "A, B, and/or C", such phrasing is intended to encompass the selection of the first listed option (A), the selection of the second listed option (B), the selection of the third listed option (C), the selection of the first and the second listed options (A and B), the selection of the first and third listed options (A and C), the selection of the second and third listed options (B and C), or the selection of all three options (A and B and C). This may be extended, as readily apparent by one of ordinary skill in this and related arts, for as many items listed.

[0030] Turning to FIG. 1, an exemplary Multi-view Video Coding (MVC) encoder is indicated generally by the reference numeral 100. The encoder 100 includes a combiner 105 having an output connected in signal communication with an input of a transformer 110. An output of the transformer 110 is connected in signal communication with an input of quantizer 115. An output of the quantizer 115 is connected in signal communication with an input of an entropy coder 120 and an input of an inverse quantizer 125. An output of the inverse quantizer 125 is connected in signal communication with an input of an inverse transformer 130. An output of the inverse transformer 130 is connected in signal communication with a first non-inverting input of a combiner 135. An output of the combiner 135 is connected in signal communication with an input of an intra predictor 145 and an input of a deblocking filter 150. An output of the deblocking filter 150 is connected in signal communication with an input of a reference picture store 155 (for view i). An output of the reference picture store 155 is connected in signal communication with a first input of a motion compensator 175 and a first input of a motion estimator 180. An output of the motion estimator 180 is connected in signal communication with a second input of the motion compensator 175.

[0031] An output of a reference picture store 160 (for other views) is connected in signal communication with a first input of a disparity estimator 170 and a first input of a disparity compensator 165. An output of the disparity estimator 170 is connected in signal communication with a second input of the disparity compensator 165.

[0032] An output of the entropy decoder 120 is available as an output of the encoder 100. A non-inverting input of the combiner 105 is available as an input of the encoder 100, and is connected in signal communication with a second input of the disparity estimator 170, and a second input of the motion estimator 180. An output of a switch 185 is connected in signal communication with a second non-inverting input of the combiner 135 and with an inverting input of the combiner 105. The switch 185 includes a first input connected in signal communication with an output of the motion compensator 175, a second input connected in signal communication with an output of the disparity compensator 165, and a third

input connected in signal communication with an output of the intra predictor 145.

[0033] Turning to FIG. 2, an exemplary Multi-view Video Coding (MVC) decoder is indicated generally by the reference numeral 200. The decoder 200 includes an entropy decoder 205 having an output connected in signal communication with an input of an inverse quantizer 210. An output of the inverse quantizer is connected in signal communication with an input of an inverse transformer 215. An output of the inverse transformer 215 is connected in signal communication with a first non-inverting input of a combiner 220. An output of the combiner 220 is connected in signal communication with an input of a deblocking filter 225 and an input of an intra predictor 230. An output of the deblocking filter 225 is connected in signal communication with an input of a reference picture store 240 (for view i). An output of the reference picture store 240 is connected in signal communication with a first input of a motion compensator 235.

[0034] An output of a reference picture store 245 (for other views) is connected in signal communication with a first input of a disparity compensator 250.

[0035] An input of the entropy coder 205 is available as an input to the decoder 200, for receiving a residue bitstream. Moreover, a control input of the switch 255 is also available as an input to the decoder 200, for receiving control syntax to control which input is selected by the switch 255. Further, a second input of the motion compensator 235 is available as an input of the decoder 200, for receiving motion vectors. Also, a second input of the disparity compensator 250 is available as an input to the decoder 200, for receiving disparity vectors.

[0036] An output of a switch 255 is connected in signal communication with a second non-inverting input of the combiner 220. A first input of the switch 255 is connected in signal communication with an output of the disparity compensator 250. A second input of the switch 255 is connected in signal communication with an output of the motion compensator 235. A third input of the switch 255 is connected in signal communication with an output of the intra predictor 230. An output of the mode module 260 is connected in signal communication with the switch 255 for controlling which input is selected by the switch 255. An output of the deblocking filter 225 is available as an output of the decoder.

[0037] In accordance with the present principles, methods and apparatus are provided for improved signaling using high level syntax for multi-view video coding and decoding.

[0038] As noted above, the current multi-view video coding extension of the MPEG-4 AVC Standard includes syntax that signals inter-view references. However, as further noted above, the syntax definition lacks some features. For example, the syntax definition does not specify the coding order of each view. This information is very useful for error resiliency. If defined properly, it can help the decoder to detect that some pictures in certain views were missing and the decoder would be able to conceal the lost picture in certain views without losing track of what was going on.

[0039] Turning to FIG. 3, a time-first coding structure for a multi-view video coding system with 8 views is indicated generally by the reference numeral 300. In the example of FIG. 3, all pictures at the same time instance from different views are coded contiguously. Thus, if we know coding order information, then we can quickly detect which view is lost at one time instant by tracking the view_id. This information can also help speed up the construction of the dependency map. For example, earlier coded views will not use later coded views as references. The dependency map may be used for, for example, random access, an implicit decoded reference picture marking process, and so forth.

[0040] In order to construct dependency map information from the current view dependency information in the sequence parameter set, a recursive call may be used. In the following example, the indication of an anchor/non-anchor picture is dropped since the algorithm is applicable to both.

[0041] We propose constructing picture_dependency_maps[i][j] with the following semantics:

picture_dependency_maps[i][j] equal to 1 indicates the picture with view_id equal to j will depend on the picture with view_id equal to i.

[0042] It is presumed that we are using static data structures. It is desirable to obtain the following information in order to build the picture_dependency_maps:

- num_refs[k], indicating number of inter-view references for the view with view_id equals to k
- The list of view_id's that are referred to by the view with view_id equal to k: refs[k][l] where l is looped from 0 to num_refs[k]-1.

```
// picture_dependency_maps[N][N], num_refs[N], refs[N][N] are global
build_picture_dependency_maps()
{
    int p, q;
    for (p=0; p<N; p++)
        for (q=0; q<N; q++)
            picture_dependency_maps[p][q] = 0;
    for (p=0; p<N; p++)
```

```

{
    for (q=0; q<num_refs[p]; q++)
        add_dep(refs[p][q], p);
}
5  }
    add_dep(m, n)
    {
        int p, q;
        picture_dependency_map[m][n] = 1;
        if (num_refs[m] == 0)
10         return;
        for (p=0; p<num_refs[m]; p++)
            add_dep(refs[m][p], n);
    }

```

[0043] In accordance with various embodiments of the present principles, we propose improvements to the existing sequence parameter set (SPS) in the multi-view video coding (MVC) extension of the MPEG-4 AVC Standard. The improved sequence parameter set can indicate view coding order information and allow flexible view identifier (view_id) assignment. It is considered flexible since the view identifier (view_id) is explicitly sent in the high level syntax instead of treating the loop variable as the view identifier. Of course, as noted above, while the present principles are primarily described herein with respect to the implementation of improvements to the existing sequence parameter set in the multi-view video coding extension of the MPEG-4 AVC Standard, such signaling improvements relating to indicating view coding order information and allowing flexible view identifier (view_id) assignment is not limited to solely the sequence parameter set and may be implemented by a high level syntax at the slice header level, the picture parameter set (PPS) level, the view parameter set (VPS) level, the network abstraction layer (NAL) unit header level, and in a supplemental enhancement information (SEI) message, while maintaining the spirit of the present principles.

[0044] A description will now be given regarding an embodiment of the present principles.

[0045] TABLE 2 shows the proposed sequence parameter set multi-view video coding (MVC) extension syntax in accordance with the embodiment.

TABLE 2

seq_parameter_set_mvc_extension() {	C	Descriptor
num_views_minus_1		ue(v)
for(i = 0; i <= num_views_minus_1; i++)		
view_id[i]		ue(v)

	for(i = 0; i <= num_views_minus_1; i++) {		
	num_anchor_refs_l0[i]		ue(v)
5	for(j = 0; j < num_anchor_refs_l0[i]; j++)		
	anchor_ref_l0[i][j]		ue(v)
	num_anchor_refs_l1[i]		ue(v)
	for(j = 0; j < num_anchor_refs_l1[i]; j++)		
10	anchor_ref_l1[i][j]		ue(v)
	}		
	for(i = 0; i <= num_views_minus_1; i++) {		
	num_non_anchor_refs_l0[i]		ue(v)
15	for(j = 0; j < num_non_anchor_refs_l0[i]; j++)		
	non_anchor_ref_l0[i][j]		ue(v)
	num_non_anchor_refs_l1[i]		ue(v)
	for(j = 0; j < num_non_anchor_refs_l1[i]; j++)		
20	non_anchor_ref_l1[i][j]		ue(v)
	}		
	}		

25 **[0046]** In the embodiment, we propose to use the loop variable i to indicate view coding order. The loop variable i is always incremented for each view. Thus, the view coding order number is unique for each view.

30 **[0047]** As noted above, the prior art indicates the loop variable i as view_id and loops from 0 to num_view_minus_1. In contrast, we use the loop variable i as the view coding order and loop from 0 to num_view_minus_1. Additionally, we signal the view_id inside the loop. Thus, we can assign any view_id to the views and are not restricted to the loop variable as is the case in the current multi-view video coding extension of the MPEG-4 AVC Standard. The semantics of the syntaxes are redefined as:

35 **num_views_minus_1** plus 1 identifies the total number of coded views in the bitstream. The value of the number_of_view_minus_1 shall be in the range of 0 to 1023.

view_id[i] specifies the view_id of the view with coding order indicate by i.

40 **num_anchor_refs_l0[i]** specifies the number of inter-view prediction references for list0 for anchor pictures with view_id equal to view_id[i]. The value of num_anchor_refs_l0[i] shall be less than or equal to num_ref_frames.

anchor_ref_l0[i][j] identifies the view_id of the view that is used as the jth reference of list0, for anchor pictures of the view with view_id equal to view_id[i].

45 **num_anchor_refs_l1[i]** specifies the number of inter-view prediction references for list1 of the anchor picture with view_id equal to view_id[i]. The value of num_anchor_refs_l1[i] shall be less than or equal to num_ref_frames.

anchor_ref_l1[i][j] identifies the view_id of the view that is used as the jth reference of list1, for anchor pictures of the view with view_id equal to view_id[i].

50 **num_non_anchor_refs_l0[i]** specifies the number of inter-view prediction references for list0 for non-anchor pictures with view_id equal to view_id[i]. The value of num_non_anchor_refs_l0[i] shall be less than or equal to num_ref_frames.

non_anchor_ref_l0[i][j] identifies the view_id of the view that is used as the jth reference of list0, for non-anchor pictures of the view with view_id equal to view_id[i].

55 **num_non_anchor_refs_l1[i]** specifies the number of inter-view prediction references for list1 for non-anchor pictures with view_id equal to view_id[i]. The value of num_non_anchor_refs_l1[i] shall be less than or equal to num_ref_frames.

non_anchor_ref_l1[i][j] identifies the view_id of the view that is used as the jth reference of list1, for non-anchor pictures of the view with view_id equal to view_id[i].

[0048] The advantage of the embodiment is that view_ids that are assigned to views do not have any restriction except for their range as defined in the semantics. The current specification of the multi-view video coding extension always starts the view_ids from 0 and increments by 1. By explicitly sending the view_id, this restriction is no longer needed in implementation in accordance with the present principles.

[0049] During the decoding process, a picture may or may not require inter-view reference pictures. To determine the required inter-view reference pictures for a certain picture, the following steps are carried out in accordance with an embodiment of the present principles: (1) read the view_id of current picture from NAL unit header; (2) search for this view_id in the view_id[] array of the SPS (This array has the view_id stored in the coding order. Thus, the index of this array indicates the coding order.); (3) determine the index (i) of the current picture's view_id, this is the coding order number; and (4) use this index value (i) to index into the other arrays of the sequence parameter set to determine the inter-view references needed for the current picture.

[0050] The present principles are also useful in order to determine if a picture is lost during transmission. This can be done as follows. In the current specification of the multi-view video coding (MVC) extension, we know that time-first coding is done. Before decoding starts for a particular time instance, we can set a counter view_num to 0. For each picture that is received for this time instance, we increment the view_num value. Before we begin decoding this picture, we index into the view_id[view_num] array of the sequence parameter set using the view_num counter. We determine the view_id corresponding to this index. If this view_id is the same as the current picture's view_id, then there is no loss. However, if these view_id's are different, then we know that the indexed view_id was lost. This picture can then be concealed by an appropriate error concealment algorithm. We can also know how many views are lost by incrementing view_id until we hit (match) the current picture's view_id.

[0051] For the example of FIG. 3, the view_id is assigned incrementally from the top downward. The mapping between view_num and view_id is as following:

view_num	0	1	2	3	4	5	6	7
view_id	0	2	1	4	3	6	5	7

[0052] The construction of dependency map information from the current view dependency information could be simplified with the coding order available. In the following example, the indication of an anchor/non-anchor is dropped since the algorithm applies for both.

[0053] It is presumed that we are using static data structures. It is desirable to have the following information in order to build the picture_dependency_maps:

- num_refs[k], indicating number of inter-view references for the view with view_id equals to k
- The list of view_id's that are referred by the view with view_id equals to k: refs[k][l] where l is looped from 0 to num_refs[k]-1 - view_in_coding_order[k], indicating the list of view_id in the coding order

```
// picture_dependency_maps[N][N], view_in_coding_order[N], num_refs[N],
refs[N][N] are global
build_picture_dependency_maps_in_order()
{
    int p, q, pp, s;
    for (p=0; p<N; p++)
        for (q=0; q<N; q++)
            picture_dependency_maps[p][q] = 0;
    for (p=0; p<N; p++)
    {
        pp = view_in_coding_order[p];
        for (q=0; q<num_refs[pp]; q++)
        {
            for (s=0; s<N; s++)
                if (picture_dependency_maps[s][refs[pp][q]])
                    picture_dependency_maps[s][pp] = 1;
            picture_dependency_maps[refs[pp][q]][pp] = 1;
        }
    }
}
```

}

[0054] Turning to FIG. 4, an exemplary method for encoding multi-view video content is indicated generally by the reference numeral 400.

[0055] The method 400 includes a start block 405 that passes control to a function block 410. The function block 410 reads the encoder configuration file, and passes control to a function block 415. The function block 415 sets view_direction, view_level, and view_id to user defined values, and passes control to a function block 420. The function block 420 flexibly sets view_id[i] (differentially) in the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or in a supplemental enhancement information (SEI) message, based on view coding order (from the encoder configuration file), sets the other sequence parameter set parameters based on the encoder configuration file, and passes control to a function block 425. The function block 425 lets the number of views be equal to a variable N, initializes a variable i and a variable j both to zero, and passes control to a decision block 430. The decision block 430 determines whether or not i is less than N. If so, then control is passed to a function block 435. Otherwise, control is passed to a function block 485.

[0056] The decision block 435 determines whether or not j is less than the number of pictures in view i. If so, then control is passed to a function block 440. Otherwise, control is passed to the function block 485.

[0057] The function block 440 starts encoding the current macroblock (MB), and passes control to a function block 445. The function block 445 chooses the macroblock mode, and passes control to a function block 450. The function block 450 encode the current macroblock, and passes control to a decision block 455. The decision block 455 determines whether or not all macroblocks have been encoded. If so, then control is passed to a function block 460. Otherwise, control is returned to the function block 440.

[0058] The function block 460 increments the variable j, and passes control to a function block 465. The function block 465 increments frame_num and picture order count (POC), and passes control to a decision block 470. The decision block 470 determines whether or not to signal the sequence parameter set (SPS) and/or the picture parameter set (PPS) in-band. If so, the control is passed to a function block 475. Otherwise, control is passed to a function block 490.

[0059] The function block 475 sends the sequence parameter set (SPS), the picture parameter set (PPS), and/or the view parameter set (VPS) to a file (i.e., in-band), and passes control to a function block 480. The function block 480 writes the bitstream to a file or streams the bitstream over a network(s), and passes control to an end block 499.

[0060] The function block 485 increments the variable i, resets frame_num, and picture order count (POC), and returns control to the decision block 430.

[0061] The function block 490 sends the sequence parameters set (SPS), the picture parameter set (PPS), and/or the view parameter set (VPS) out-of-band, and passes control to the function block 480.

[0062] Turning to FIG. 5, an exemplary method for decoding multi-view video content is indicated generally by the reference numeral 500.

[0063] The method 500 includes a start block 505 that passes control to a function block 510. The function block 510 parses view_id, view_direction, and view_level from either the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or a supplemental enhancement information (SEI) message, and passes control to a function block 515. The function block 515 parses (differentially coded) view_id[i] from the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or a supplemental enhancement information (SEI) message where the loop variable i indicates the view coding order, and passes control to a function block 520. The function block 520 parses other sequence parameter set parameters, and passes control to a function block 525. The function block 525 uses view_direction, view_level, and view_id to determine if the current picture needs to be decoded (check dependency), and passes control to a decision block 530. The decision block 530 determines whether or not the current picture needs decoding. If so, then control is passed to a decision block 540. Otherwise, control is passed to a function block 535.

[0064] The function block 540 determines whether or not the picture order count (POC) of the current picture is equal to the picture order count (POC) of the previous picture, namely $POC(curr) = POC(prev)$. If so, then control is passed to a function block 545. Otherwise, control is passed to a function block 550.

[0065] The function block 545 sets view_num equal to zero, and passes control to the function block 550. The function block 550 indexes the view_id information at the high level to determine the view coding order, increments view_num, and passes control to a decision block 555. The decision block 555 determines whether or not the current picture is in the expected coding order. If so, then control is passed to a function block 560. Otherwise, control is passed to a function block 590.

[0066] The function block 560 parses the slice header, and passes control to a function block 555. The function block 555 parses the macroblock (MB) mode, the motion vector (mv), and the reference index (ref_idx), and passes control to a function block 570. The function block 570 decodes the current macroblock, and passes control to a decision block 575. The decision block 575 determines whether or not all macroblocks have been decoded in the current picture. If so,

then control is passed to a function block 580. Otherwise, control is returned to the function block 565.

[0067] The function block 580 inserts the current picture in the decoded picture buffer (DPB), and passes control to a decision block 585. The decision block 585 determines whether or not all pictures have been decoded. If so, then control is passed to an end block 599. Otherwise, control is returned to the function block 560.

[0068] The function block 590 conceals the current picture, and returns control to the function block 535.

[0069] A description will now be given regarding another embodiment of the present principles.

[0070] In the embodiment, we signal the view coding order explicitly in the bitstream. The view coding order information can be indicated in any high level syntax including, but not limited to, syntax at the slice header level, the sequence parameter set (SPS) level, the picture parameter set (PPS) level, the view parameter set (VPS) level, the network abstraction layer (NAL) unit header level, and in a supplemental enhancement information (SEI) message.

[0071] TABLE 3 shows the proposed sequence parameter set multi-view video coding (MVC) extension syntax in accordance with the embodiment. Thus, TABLE 3 illustrates the insertion of the view coding order for the current specification of the multi-view video coding (MVC) extension. This keeps the structure of the sequence parameter set design in the current specification of the multi-view video coding (MVC) extension, but adds view_num into the loop. This view_num signals the coding order.

TABLE 3

seq_parameter_set_mvc_extension() {	C	Descriptor
num_views_minus_1		ue(v)
for(i = 0; i <= num_views_minus_1; i++)		
view_num[i]		ue(v)
for(i = 0; i <= num_views_minus_1; i++) {		
num_anchor_refs_l0[i]		ue(v)
for(j = 0; j < num_anchor_refs_l0[i]; j++)		
anchor_ref_l0[i][j]		ue(v)
num_anchor_refs_l1[i]		ue(v)
for(j = 0; j < num_anchor_refs_l1[i]; j++)		
anchor_ref_l1[i][j]		ue(v)
}		
for(i = 0; i <= num_views_minus_1; i++) {		
num_non_anchor_refs_l0[i]		ue(v)
for(j = 0; j < num_non_anchor_refs_l0[i]; j++)		
non_anchor_ref_l0[i][j]		ue(v)
num_non_anchor_refs_l1[i]		ue(v)
for(j = 0; j < num_non_anchor_refs_l1[i]; j++)		
non_anchor_ref_l1[i][j]		ue(v)
}		
}		

[0072] The newly added semantics are defined as follows:

view_num[i] specifies view coding order of view_id equal to i. view_num shall be incremented by one for each coded view in the coding order.

[0073] For the example of FIG. 3, the view_id is assigned incrementally from the top downward. The view_num is assigned based on view coding order as:

view_id	0	1	2	3	4	5	6	7
view_num	0	2	1	4	3	6	5	7

[0074] We note that in the current design, we code an inter-view reference for the current view using absolute view_id as opposed to the difference between the current view_id and the reference view_id. Since in most cases the reasonable inter-view reference should be the view which is closer to the current view, we can code the difference between the current view_id and the inter-view reference view_id.

Application for error detection:

[0075] One example that involves the use of the proposed view_num to detect a lost picture is as follows. In time-first coding, at time instance T8, we receive a packet in order of view_id, 0 1 4 3 5 7. After we receive view_id 0 and view_id 1, we know view_id 2 is lost, because view_id 2 should be received before view_id 1. Then, we get view_id 4, 3, and 5, and we know view_id 6 is lost, since view_id 6 should be received before view_id 5.

[0076] We can determine whether the missing picture in view_id 2 and view_id 6 is lost due to transmission error or if it is intentionally missing if we use the syntax example in TABLE 3. Thus, if we want to intentionally not code certain views, we do not need to put the un-coded view_ids into the sequence parameter set.

[0077] Turning to FIG. 6, another exemplary method for encoding multi-view video content is indicated generally by the reference numeral 600.

[0078] The method 600 includes a start block 605 that passes control to a function block 610. The function block 610 reads the encoder configuration file, and passes control to a function block 615. The function block 615 sets view_direction, view_level, and view_id to user defined values, and passes control to a function block 620. The function block 620 flexibly sets view_num[i] in the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or in a supplemental enhancement information (SEI) message, based on view coding order for view_id i (from the encoder configuration file), sets the other sequence parameter set parameters based on the encoder configuration file, and passes control to a function block 625. The function block 625 lets the number of views be equal to a variable N, initializes a variable i and a variable j both to zero, and passes control to a decision block 630. The decision block 630 determines whether or not i is less than N. If so, then control is passed to a function block 635. Otherwise, control is passed to a function block 685.

[0079] The decision block 635 determines whether or not j is less than the number of pictures in view i. If so, then control is passed to a function block 640. Otherwise, control is passed to the function block 685.

[0080] The function block 640 starts encoding the current macroblock (MB), and passes control to a function block 645. The function block 645 chooses the macroblock mode, and passes control to a function block 650. The function block 650 encode the current macroblock, and passes control to a decision block 655. The decision block 655 determines whether or not all macroblocks have been encoded. If so, then control is passed to a function block 660. Otherwise, control is returned to the function block 640.

[0081] The function block 660 increments the variable j, and passes control to a function block 665. The function block 665 increments frame_num and picture order count (POC), and passes control to a decision block 670. The decision block 670 determines whether or not to signal the sequence parameter set (SPS) and/or the picture parameter set (PPS) in-band. If so, the control is passed to a function block 675. Otherwise, control is passed to a function block 690.

[0082] The function block 675 sends the sequence parameter set (SPS), the picture parameter set (PPS), and/or the view parameter set (VPS) to a file (i.e., in-band), and passes control to a function block 680. The function block 680 writes the bitstream to a file or streams the bitstream over a network(s), and passes control to an end block 699.

[0083] The function block 685 increments the variable i, resets frame_num, and picture order count (POC), and returns control to the decision block 630.

[0084] The function block 690 sends the sequence parameters set (SPS), the picture parameter set (PPS), and/or the view parameter set (VPS) out-of-band, and passes control to the function block 680.

[0085] Turning to FIG. 7, an exemplary method for decoding multi-view video content is indicated generally by the reference numeral 700.

[0086] The method 600 includes a start block 705 that passes control to a function block 710. The function block 710 parses view_id, view_direction, and view_level from either the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or a supplemental enhancement information (SEI) message, and passes control to a function block 715. The function block 715 parses view_num[i] from the slice header, the sequence parameter set (SPS), the picture parameter set (PPS), the view parameter set (VPS), the network abstraction layer (NAL) unit header, and/or a supplemental enhancement information (SEI) message where the loop variable i indicates the view_id, and passes control to a function block 720. The function block 720 parses other sequence parameter set parameters, and passes control to a function block 725. The function block 725 uses view_direction, view_level, and view_id to determine if the current picture needs to be decoded (check dependency), and passes control to a decision block 730. The decision block determines whether or not the current picture needs decoding. If so, then control is passed to a decision block 740. Otherwise, control is passed to a function block 735.

[0087] The function block 740 determines whether or not the picture order count (POC) of the current picture is equal to the picture order count (POC) of the previous picture, namely $POC(curr) = POC(prev)$. If so, then control is passed to a function block 745. Otherwise, control is passed to a function block 750.

[0088] The function block 745 sets view_num equal to zero, and passes control to the function block 750. The function block 750 indexes the view_id information at the high level to determine the view coding order, increments view_num, and passes control to a decision block 755. The decision block 755 determines whether or not the current picture is in the expected coding order. If so, then control is passed to a function block 760. Otherwise, control is passed to a function block 790.

[0089] The function block 760 parses the slice header, and passes control to a function block 755. The function block 755 parses the macroblock (MB) mode, the motion vector (mv), and the reference index (ref_idx), and passes control to a function block 770. The function block 770 decodes the current macroblock, and passes control to a decision block 775. The decision block 775 determines whether or not all macroblocks have been decoded in the current picture. If so, then control is passed to a function block 780. Otherwise, control is returned to the function block 765.

[0090] The function block 780 inserts the current picture in the decoded picture buffer (DPB), and passes control to a decision block 785. The decision block 785 determines whether or not all pictures have been decoded. If so, then control is passed to an end block 799. Otherwise, control is returned to the function block 760.

[0091] The function block 790 conceals the current picture, and returns control to the function block 735.

[0092] A description will now be given of some of the many attendant advantages/features of the present invention, some of which have been mentioned above. For example, one advantage/feature is an apparatus having an encoder for encoding at least one picture for at least one view corresponding to multi-view video content in a resultant bitstream, wherein the encoder signals video coding order information for at least the at least one picture in a high level syntax.

[0093] Another advantage/feature is the apparatus having the encoder as described above, wherein the high level syntax element is included in at least one of a Sequence Parameter Set, a Picture Parameter Set, a View Parameter Set, a Supplemental Enhancement Information message, a slice header, and a Network Abstraction Layer unit header.

[0094] Yet another advantage/feature is the apparatus having the encoder as described above, wherein the multi-view video content corresponds to at least two views, including the at least one view, and, said encoder signals the view coding order information in the high level syntax by performing a plurality of iterations to loop through a view identifier in the high level syntax for each of the at least two views in coding order.

[0095] Moreover, another advantage/feature is the apparatus having the encoder as described above, wherein the multi-view video content corresponds to at least two views, including the at least one view, and, said encoder signals the view coding order information in the high level syntax by performing a plurality of iterations to loop through a view coding order in the high level syntax for each of the at least two views.

[0096] Further, another advantage/feature is the apparatus having the encoder as described above, wherein the high level syntax is signaled at least one of in-band and out-of-band.

[0097] Also, another advantage/feature is the apparatus having the encoder as described above, wherein said encoder differentially codes a view identifier for an inter-view reference picture used to encode the at least one picture, when said encoder encodes view dependency information for the at least one picture.

[0098] Additionally, another advantage/feature is the apparatus having the encoder as described above, wherein said encoder flexibly assigns a view identifier for the at least one view in another high level syntax.

[0099] Moreover, another advantage/feature is the apparatus having the encoder that flexibly assigns a view identifier for the at least one view in another high level syntax as described above, wherein the other high level syntax element is included in at least one of a Sequence Parameter Set, a Picture Parameter Set, a View Parameter Set, a Supplemental Enhancement Information message, a slice header, and a Network Abstraction Layer unit header.

[0100] Further, another advantage/feature is the apparatus having the encoder that flexibly assigns a view identifier for the at least one view in another high level syntax as described above, wherein the multi-view video content corresponds to at least two views, including the at least one view, and, said encoder flexibly assigns the view identifier for each of the at least two views in the other high level syntax by performing a plurality of iterations to loop through the view identifier in the other high level syntax for each of the at least two views in coding order.

[0101] Moreover, another advantage/feature is the apparatus having the encoder that performs the plurality of iterations to loop through the view identifier in the other high level syntax for each of the at least two views in coding order as described above, wherein the flexible assignment of the view identifier for each of the at least two views allows for gaps between consecutive view identifiers.

[0102] Also, another advantage/feature is the apparatus having the encoder that flexibly assigns a view identifier for the at least one view in another high level syntax as described above, wherein the multi-view video content corresponds to at least two views, including the at least one view, and, said encoder flexibly assigns the view identifier for each of the at least two views in the other high level syntax by performing a plurality of iterations to loop through a view coding order in the other high level syntax for each of the at least two views.

[0103] Additionally, another advantage/feature is the apparatus having the encoder that flexibly assigns a view identifier

for the at least one view in another high level syntax as described above, wherein the other high level syntax is signaled at least one of in-band and out-of-band.

[0104] Moreover, another advantage/feature is the apparatus having the encoder as described above, wherein the encoder flexibly signals inter-view dependency information in the high level syntax.

[0105] These and other features and advantages of the present principles may be readily ascertained by one of ordinary skill in the pertinent art based on the teachings herein. It is to be understood that the teachings of the present principles may be implemented in various forms of hardware, software, firmware, special purpose processors, or combinations thereof.

[0106] Most preferably, the teachings of the present principles are implemented as a combination of hardware and software. Moreover, the software may be implemented as an application program tangibly embodied on a program storage unit. The application program may be uploaded to, and executed by, a machine comprising any suitable architecture. Preferably, the machine is implemented on a computer platform having hardware such as one or more central processing units ("CPU"), a random access memory ("RAM"), and input/output ("I/O") interfaces. The computer platform may also include an operating system and microinstruction code. The various processes and functions described herein may be either part of the microinstruction code or part of the application program, or any combination thereof, which may be executed by a CPU. In addition, various other peripheral units may be connected to the computer platform such as an additional data storage unit and a printing unit.

[0107] It is to be further understood that, because some of the constituent system components and methods depicted in the accompanying drawings are preferably implemented in software, the actual connections between the system components or the process function blocks may differ depending upon the manner in which the present principles are programmed. Given the teachings herein, one of ordinary skill in the pertinent art will be able to contemplate these and similar implementations or configurations of the present principles.

Claims

1. A storage medium having video signal data encoded thereupon, the video signal data being encoded in the multi-view video coding extension of a video coding standard, and the video signal data comprising:

a bitstream having multi-view video content and high level syntax information, said high level syntax information including a sequence parameter set, wherein the sequence parameter set includes:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

2. The storage medium of claim 1, wherein the parameter view_id[i] of the video signal data explicitly signals a view identifier which indicates a view of said multi-view video content.

3. The storage medium of any of claims 1 to 2, wherein the view identifier for each of a plurality of views of said multi-view video content is assigned such that gaps are allowed between consecutive view identifiers.

4. The storage medium of any of claims 1 to 3, wherein indicating the view coding order by the index i allows the use of the ordered view_id[i] parameters to determine if a picture is lost during transmission.

5. A video signal formatted to include information according to the multi-view video coding extension of a video coding standard, the video signal including:

a bitstream having multi-view video content and high level syntax information, said high level syntax information including a sequence parameter set, wherein the sequence parameter set includes:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

6. A method for encoding according to the multi-view video coding extension of a video coding standard, comprising:

encoding at least one picture for at least one view corresponding to multi-view video content into a bitstream having high level syntax information, said high level syntax information including:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

7. A method for decoding according to the multi-view video coding extension of a video coding standard, comprising:

decoding at least one picture for at least one view corresponding to multi-view video content from a bitstream having high level syntax information, said high level syntax information including:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

8. The method of claim 6 or 7, wherein the view identifier for each of a plurality of views of said multi-view video content is assigned such that gaps are allowed between consecutive view identifiers.

9. The method of any of claims 6-8, wherein indicating the view coding order by the index i allows the use of the ordered view_id[i] parameters to determine if a picture is lost during transmission.

10. A machine readable medium having stored thereon machine executable instructions that, when executed, implement a method according to any of claims 6-9.

11. An apparatus for encoding according to the multi-view video coding extension of a video coding standard, comprising:

means for encoding at least one picture for at least one view corresponding to multi-view video content into a bitstream having high level syntax information, said high level syntax information including:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

12. An apparatus for decoding according to the multi-view video coding extension of a video coding standard, comprising:

means for decoding at least one picture for at least one view corresponding to multi-view video content from a bitstream having high level syntax information, said high level syntax information including:

a parameter representing a total number of coded views in the bitstream minus one, and
a view coding order and view identifier indicated by a parameter, view_id[i], which specifies the view identifier of the view with view coding order indicated by index i, wherein index i ranges from 0 to the parameter representing the total number of coded views minus one.

13. The apparatus of claim 11 or 12, wherein the view identifier for each of a plurality of views of said multi-view video content is assigned such that gaps are allowed between consecutive view identifiers.

14. The apparatus of any of claims 11-13, wherein indicating the view coding order by the index i allows the use of the ordered view_id[i] parameters to determine if a picture is lost during transmission.

Patentansprüche

1. Speichermedium, auf dem Videosignaldaten codiert sind, wobei die Videosignaldaten in einer Multiview-Video-codierungserweiterung einer Videocodierungsnorm codiert sind, und wobei die Videosignaldaten umfassen:

einen Bitstrom mit einem Multiview-Videoinhalt und mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene eine Sequenzparametermenge enthalten, wobei die Sequenzparametermenge enthält:

5 einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter, der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

10 2. Speichermedium nach Anspruch 1, wobei der Parameter view_id[i] der Videosignalaten explizit einen Ansichtsidentifizierer signalisiert, der eine Ansicht des Multi-view-Videoinhalts angibt.

15 3. Speichermedium nach einem der Ansprüche 1 bis 2, wobei der Ansichtsidentifizierer für jede von mehreren Ansichten des Multiview-Videoinhalts so zugewiesen ist, dass zwischen aufeinanderfolgenden Ansichtsidentifizierern Lücken zugelassen sind.

20 4. Speichermedium nach einem der Ansprüche 1 bis 3, wobei die Angabe der Ansichtscodierungsreihenfolge durch den Index i die Verwendung der geordneten view_id[i]-Parameter, um zu bestimmen, ob ein Bild während der Übertragung verlorenght, ermöglicht.

5. Videosignal, das in der Weise formatiert ist, dass es Informationen gemäß der Multiview-Videocodierungserweiterung einer Videocodierungsnorm enthält, wobei das Videosignal enthält:

25 einen Bitstrom mit einem Multiview-Videoinhalt und mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene eine Sequenzparametermenge enthalten, wobei die Sequenzparametermenge enthält:

30 einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter, der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

35 6. Verfahren zum Codieren gemäß der Multiview-Videocodierungserweiterung einer Videocodierungsnorm, wobei das Verfahren umfasst:

40 Codieren mindestens eines Bilds für mindestens eine Ansicht, die einem Multiview-Videoinhalt entspricht, in einen Bitstrom mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene enthalten:

45 einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter, der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

50 7. Verfahren zum Decodieren gemäß der Multiview-Videocodierungserweiterung einer Videocodierungsnorm, wobei das Verfahren umfasst:

Decodieren mindestens eines Bilds für mindestens eine Ansicht, die einem Multiview-Videoinhalt entspricht, aus einem Bitstrom mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene enthalten:

55 einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter,

der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

8. Verfahren nach Anspruch 6 oder 7, wobei der Ansichtsidentifizierer für jede von mehreren Ansichten des Multiview-Videoinhalts so zugewiesen ist, dass zwischen aufeinanderfolgenden Ansichtsidentifizierern Lücken zugelassen sind.

9. Verfahren nach einem der Ansprüche 6-8, wobei die Angabe der Ansichtscodierungsreihenfolge durch den Index i die Verwendung der geordneten view_id[i]-Parameter, um zu bestimmen, ob ein Bild während der Übertragung verlorengeht, ermöglicht.

10. Maschinenlesbares Medium, auf dem maschinenausführbare Anweisungen gespeichert sind, die, wenn sie ausgeführt werden, ein Verfahren nach einem der Ansprüche 6-9 implementieren.

11. Vorrichtung zum Codieren gemäß der Multiview-Videocodierungserweiterung einer Videocodierungsnorm, wobei die Vorrichtung umfasst:

Mittel zum Codieren mindestens eines Bilds für mindestens eine Ansicht, die einem Multiview-Videoinhalt entspricht, in einen Bitstrom mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene enthalten:

einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter, der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

12. Vorrichtung zum Decodieren gemäß der Multiview-Videocodierungserweiterung einer Videocodierungsnorm, wobei die Vorrichtung umfasst:

Mittel zum Decodieren mindestens eines Bilds für mindestens eine Ansicht, die einem Multiview-Videoinhalt entspricht, aus einem Bitstrom mit Syntaxinformationen höherer Ebene, wobei die Syntaxinformationen höherer Ebene enthalten:

einen Parameter, der eine Gesamtanzahl codierter Ansichten in dem Bitstrom minus eins repräsentiert, und eine Ansichtscodierungsreihenfolge und einen Ansichtsidentifizierer, der durch einen Parameter view_id[i] angegeben ist, der den Ansichtsidentifizierer der Ansicht mit der durch den Index i angegebenen Ansichtscodierungsreihenfolge spezifiziert, wobei der Index i in dem Bereich von 0 bis zu dem Parameter, der die Gesamtanzahl codierter Ansichten minus eins repräsentiert, liegt.

13. Vorrichtung nach Anspruch 11 oder 12, wobei der Ansichtsidentifizierer für jede von mehreren Ansichten des Multiview-Videoinhalts so zugewiesen ist, dass zwischen aufeinanderfolgenden Ansichtsidentifizierern Lücken zugelassen sind.

14. Vorrichtung nach einem der Ansprüche 11-13, wobei die Angabe der Ansichtscodierungsreihenfolge durch den Index i die Verwendung der geordneten view_id[i]-Parameter, um zu bestimmen, ob ein Bild während der Übertragung verlorengeht, ermöglicht.

Revendications

1. Support de stockage contenant des données de signal vidéo codées, les données de signal vidéo étant codées dans l'extension de codage vidéo multivue d'une norme de codage vidéo, et les données de signal vidéo comprenant :

un train de bits ayant du contenu vidéo multivue et des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant un ensemble de paramètres de séquence, dans lequel l'ensemble de paramètres de séquence inclut :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et

un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, view_id[i], qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice i, dans lequel l'indice i est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

2. Support de stockage selon la revendication 1, dans lequel le paramètre view_id[i] des données de signal vidéo signale explicitement un identificateur de vue qui indique une vue dudit contenu vidéo multivue.

3. Support de stockage selon l'une des revendications 1 à 2, dans lequel l'identificateur de vue pour chacune d'une pluralité de vues dudit contenu vidéo multivue est attribué de sorte que des espaces soient autorisés entre des identificateurs de vue consécutifs.

4. Support de stockage selon l'une des revendications 1 à 3, dans lequel l'indication de l'ordre de codage de vue par l'indice i autorise l'utilisation des paramètres view_id[i] ordonnés pour déterminer si une image est perdue pendant la transmission.

5. Signal vidéo formaté pour inclure des informations selon l'extension de codage vidéo multivue d'une norme de codage vidéo, le signal vidéo incluant :

un train de bits ayant du contenu vidéo multivue et des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant un ensemble de paramètres de séquence, dans lequel l'ensemble de paramètres de séquence inclut :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et

un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, view_id[i], qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice i, dans lequel l'indice i est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

6. Procédé de codage selon l'extension de codage vidéo multivue d'une norme de codage vidéo, comprenant :

le codage d'au moins une image pour au moins une vue correspondant à du contenu vidéo multivue dans un train de bits ayant des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et
un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, view_id[i], qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice i, dans lequel l'indice i est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

7. Procédé de décodage selon l'extension de codage vidéo multivue d'une norme de codage vidéo, comprenant :

le décodage d'au moins une image pour au moins une vue correspondant à du contenu vidéo multivue depuis un train de bits ayant des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et
un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, view_id[i], qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice i, dans lequel l'indice i est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

8. Procédé selon la revendication 6 ou 7, dans lequel l'identificateur de vue pour chacune d'une pluralité de vues dudit contenu vidéo multivue est attribué de sorte que des espaces soient autorisés entre des identificateurs de vue consécutifs.

9. Procédé selon l'une des revendications 6 à 8, dans lequel l'indication de l'ordre de codage de vue par l'indice i autorise l'utilisation des paramètres view_id[i] ordonnés pour déterminer si une image est perdue pendant la transmission.

10. Support lisible sur une machine sur lequel sont stockées des instructions de machine exécutables qui, lorsqu'elles sont exécutées, implémentent un procédé selon l'une quelconque des revendications 6 à 9.

11. Appareil de codage selon l'extension de codage vidéo multivue d'une norme de codage vidéo, comprenant :

un moyen pour coder au moins une image pour au moins une vue correspondant à du contenu vidéo multivue dans un train de bits ayant des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, `view_id[i]`, qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice `i`, dans lequel l'indice `i` est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

12. Appareil de décodage selon l'extension de codage vidéo multivue d'une norme de codage vidéo, comprenant :


un moyen pour décoder au moins une image pour au moins une vue correspondant à du contenu vidéo multivue depuis un train de bits ayant des informations de syntaxe de haut niveau, lesdites informations de syntaxe de haut niveau incluant :

un paramètre représentant un nombre total de vues codées dans le train de bits moins un, et un ordre de codage de vue et un identificateur de vue indiqués par un paramètre, `view_id[i]`,

qui spécifie l'identificateur de vue de la vue avec l'ordre de codage de vue indiqué par l'indice `i`, dans lequel l'indice `i` est compris entre 0 et le paramètre représentant le nombre total de vues codées moins un.

13. Appareil selon la revendication 11 ou 12, dans lequel l'identificateur de vue pour chacune d'une pluralité de vues dudit contenu vidéo multivue est attribué de sorte que des espaces soient autorisés entre des identificateurs de vue consécutifs.

14. Appareil selon l'une des revendications 11 à 13, dans lequel l'indication de l'ordre de codage de vue par l'indice `i` autorise l'utilisation des paramètres `view_id[i]` ordonnés pour déterminer si une image est perdue pendant la transmission.






FIG. 2








FIG. 3





**FIG. 6**

**FIG. 7**

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Non-patent literature cited in the description

- **VETRO A. et al.** Joint Multiview Video Model (JMVM).
JOINT VIDEO TEAM (JVT) OF ISO/IEC MPEG &
ITU-T VCEG, 16 August 2006 [0002]

ELJÁRÁSOK ÉS BERENDEZÉS TOVÁBBFEJLESZTETT JELZÉSHEZ MAGAS SZINTŰ SZINTAXIS SEGÍTSÉGÉVEL TÖBBNÉZETES VIDEOKÓDOLÁSHOZ ÉS DEKÓDOLÁSHOZ


Szabadalmi igénypontok

1. Tároló közeg, amely rajta kódolt video jeladatokkal rendelkezik, a video jeladatok egy video kódolási szabvány video többnézetes video kódolási kiterjesztésében vannak kódolva, a video jeladatok pedig a következőket tartalmazzák:

bitfolyam, amely többnézetes video tartalommal és magas szintű szintaxis információval rendelkezik, beleértve egy sorrend paraméterkészletet, ahol a sorrend paraméterkészlet a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és
nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az *i* index által jelzett nézetkódolási sorrenddel, ahol az *i* index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

2. Az 1. igénypont szerinti tároló közeg, ahol a video jeladatok `view_id[i]` paramétere kifejezetten jelez egy nézetazonosítót, amely jelzi a többnézetes video tartalom egyik nézetét.
3. Az 1 – 2. igénypontok egyike szerinti tároló közeg, ahol a többnézetes video tartalom nézetei sokasága mindegyikének nézetazonosítója ki van jelölve úgy, hogy az egymást követő nézetazonosítók között rések vannak engedélyezve.
4. Az 1 – 3. igénypontok egyike szerinti tároló közeg, ahol a nézet kódolási sorrendjének jelzése az *i* indexszel lehetővé teszi a sorba rendezett `view_id[i]` paraméterek használatát annak meghatározására, hogy egy kép elveszett-e átvitel közben.



5. Videojel, amely arra van kialakítva, hogy információt tartalmazzon egy video kódolási szabvány többnézetes video kódolási kiterjesztése szerint, a videojel a következőket tartalmazza:

bitfolyam, amely többnézetes video tartalommal és magas szintű szintaxis információval rendelkezik, beleértve egy sorrend paraméterkészletet, ahol a sorrend paraméterkészlet a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és
nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az *i* index által jelzett nézetkódolási sorrenddel, ahol az *i* index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

6. Eljárás egy video kódolási szabvány többnézetes video kódolási kiterjesztése szerinti kódolásra, amely a következőket tartalmazza:

legalább egy kép bitfolyamba való kódolása legalább egy nézethez, amely többnézetes video tartalomnak felel meg és magas szintű szintaxis információval rendelkezik, a magas szintű információ a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és
nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az *i* index által jelzett nézetkódolási sorrenddel, ahol az *i* index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

7. Eljárás egy video kódolási szabvány többnézetes video kódolási kiterjesztése szerinti dekódolásra, amely a következőket tartalmazza:

legalább egy kép bitfolyamból való dekódolása legalább egy nézethez, amely többnézetes video tartalomnak felel meg és magas szintű szintaxis információval rendelkezik, a magas szintű információ a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és
nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az *i* index által jelzett nézetkódolási sorrenddel, ahol az *i* index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

8. A 6. vagy 7. igénypont szerinti eljárás, ahol a többnézetes video tartalom nézetei sokasága mindegyikének nézetazonosítója ki van jelölve úgy, hogy az egymást követő nézetazonosítók között rések vannak engedélyezve.
9. A 6 – 8. igénypontok egyike szerinti eljárás, ahol a nézet kódolási sorrendjének jelzése az *i* indexszel lehetővé teszi a sorba rendezett `view_id[i]` paraméterek használatát annak meghatározására, hogy egy kép elveszett-e átvitel közben.
10. Géppel olvasható adathordozó, amelyen géppel végrehajtható utasítások vannak tárolva, amelyek végrehajtáskor megvalósítják a 6 – 9. igénypontok egyike szerinti eljárást.
11. Berendezés egy video kódolási szabvány többnézetes video kódolási kiterjesztése szerinti kódolásra, amely a következőket tartalmazza:

eszköz legalább egy kép bitfolyamba legalább egy nézethez való kódolására, amely többnézetes video tartalomnak felel meg és magas szintű szintaxis információval rendelkezik, a magas szintű információ a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és
nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az *i* index által jelzett

nézetkódolási sorrenddel, ahol az i index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

12. Berendezés egy video kódolási szabvány többnézetes video kódolási kiterjesztése szerinti dekódolásra, amely a következőket tartalmazza:

eszköz legalább egy kép bitfolyamból legalább egy nézethez való dekódolására, amely többnézetes video tartalomnak felel meg és magas szintű szintaxis információval rendelkezik, a magas szintű információ a következőket tartalmazza:

a bitfolyamban lévő kódolt nézetek eggyel csökkentett teljes számát képviselő paraméter, és

nézetkódolási sorrend és nézetazonosító, amelyet egy `view_id[i]` paraméter jelez, amely meghatározza a nézet nézetazonosítóját az i index által jelzett nézetkódolási sorrenddel, ahol az i index 0-tól a kódolt nézetek eggyel csökkentett számát képviselő paraméterig terjed.

13. A 11. vagy 12. igénypont szerinti berendezés, ahol a többnézetes video tartalom nézetei sokasága mindegyikének nézetazonosítója ki van jelölve úgy, hogy az egymást követő nézetazonosítók között rések vannak engedélyezve.
14. A 11 – 13. igénypontok egyike szerinti berendezés, ahol a nézet kódolási sorrendjének jelzése az i indexszel lehetővé teszi a sorba rendezett `view_id[i]` paraméterek használatát annak meghatározására, hogy egy kép elveszett-e átvitel közben.