



US011423641B2

(12) **United States Patent**
Ross et al.

(10) **Patent No.:** **US 11,423,641 B2**

(45) **Date of Patent:** ***Aug. 23, 2022**

(54) **DATABASE FOR DETECTING COUNTERFEIT ITEMS USING DIGITAL FINGERPRINT RECORDS**

G06V 10/478 (2022.01); *G06V 20/46* (2022.01); *G06V 30/412* (2022.01); *G09C 5/00* (2013.01);

(Continued)

(71) Applicant: **Alitheon, Inc.**, Bellevue, WA (US)

(58) **Field of Classification Search**

USPC 382/100, 305
See application file for complete search history.

(72) Inventors: **David Justin Ross**, Bellevue, WA (US);
Brian J. Elmenhurst, Bellevue, WA (US);
Mark Tocci, Bellevue, WA (US);
John Forbes, Bellevue, WA (US);
Heather Wheelock Ross, Bellevue, WA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Alitheon, Inc.**, Bellevue, WA (US)

4,218,674 A 8/1980 Brosow et al.
4,423,415 A 12/1983 Goldman

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 93 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

DE 102006005927 A1 8/2007
EP 0439669 A2 8/1991

(Continued)

(21) Appl. No.: **17/102,115**

OTHER PUBLICATIONS

(22) Filed: **Nov. 23, 2020**

Stern et al., EMFORCED: EM-Based Fingerprinting Framework for Remarked and Cloned Counterfeit IC Detection Using Machine Learning Classification, 1063-8210 2019 IEEE, pp. 363-375. (Year: 2020).*

(Continued)

(65) **Prior Publication Data**

US 2021/0103760 A1 Apr. 8, 2021

Related U.S. Application Data

(60) Continuation of application No. 15/862,556, filed on Jan. 4, 2018, now Pat. No. 10,872,265, which is a (Continued)

Primary Examiner — Ishrat I Sherali

(74) *Attorney, Agent, or Firm* — Cozen O'Connor

(51) **Int. Cl.**

G06V 10/75 (2022.01)
G06T 7/00 (2017.01)

(Continued)


(57) **ABSTRACT**

Improvements are disclosed for detecting counterfeit objects, based on comparison to digital fingerprints that describe features found in images of objects known to be counterfeit.

(52) **U.S. Cl.**

CPC *G06V 10/751* (2022.01); *G06T 1/005* (2013.01); *G06T 7/0004* (2013.01); *G06V 10/225* (2022.01); *G06V 10/245* (2022.01);

21 Claims, 14 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/208,339, filed on Jul. 12, 2016, now Pat. No. 10,192,140, which is a division of application No. 14/531,724, filed on Nov. 3, 2014, now Pat. No. 9,443,298, which is a continuation-in-part of application No. 14/290,653, filed on May 29, 2014, now Pat. No. 9,350,552, which is a continuation of application No. 13/410,753, filed on Mar. 2, 2012, now Pat. No. 8,774,455.

(60) Provisional application No. 61/448,465, filed on Mar. 2, 2011, provisional application No. 61/914,722, filed on Dec. 11, 2013, provisional application No. 61/898,780, filed on Nov. 1, 2013.

(51) **Int. Cl.**

G06T 1/00 (2006.01)
H04L 9/32 (2006.01)
G09C 5/00 (2006.01)
G06V 10/22 (2022.01)
G06V 10/24 (2022.01)
G06V 10/46 (2022.01)
G06V 20/40 (2022.01)
G06V 30/412 (2022.01)
G06Q 50/32 (2012.01)

(52) **U.S. Cl.**

CPC **H04L 9/3247** (2013.01); **G06Q 50/32** (2013.01); **G06T 2201/0065** (2013.01); **G06T 2207/30128** (2013.01); **G06T 2207/30144** (2013.01); **G06T 2207/30148** (2013.01); **G06T 2207/30164** (2013.01); **G06T 2207/30204** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,677,435 A 6/1987 Causse et al.
 4,700,400 A 10/1987 Ross
 4,883,971 A 11/1989 Jensen
 4,921,107 A 5/1990 Hofer
 5,031,223 A 7/1991 Rosenbaum et al.
 5,079,714 A 1/1992 Manduley et al.
 5,393,939 A 2/1995 Nasuta et al.
 5,422,821 A 6/1995 Allen et al.
 5,514,863 A 5/1996 Williams
 5,518,122 A 5/1996 Tilles et al.
 5,521,984 A 5/1996 Denenberg et al.
 5,703,783 A 12/1997 Allen et al.
 5,719,939 A 2/1998 Tel
 5,734,568 A 3/1998 Borgendale et al.
 5,745,590 A 4/1998 Pollard
 5,883,971 A 3/1999 Bolle et al.
 5,923,848 A 7/1999 Goodhand et al.
 5,974,150 A 10/1999 Kaish et al.
 6,205,261 B1 3/2001 Goldberg
 6,246,794 B1 6/2001 Kagehiro et al.
 6,292,709 B1 9/2001 Uhl et al.
 6,327,373 B1 12/2001 Yura
 6,343,327 B2 1/2002 Daniels et al.
 6,360,001 B1 3/2002 Berger et al.
 6,370,259 B1 4/2002 Hobson et al.
 6,400,805 B1 6/2002 Brown et al.
 6,424,728 B1 7/2002 Ammar
 6,434,601 B1 8/2002 Rollins
 6,470,091 B2 10/2002 Koga et al.
 6,539,098 B1 3/2003 Baker et al.
 6,549,892 B1 4/2003 Sansone
 6,597,809 B1 7/2003 Ross et al.
 6,643,648 B1 11/2003 Ross et al.
 6,697,500 B2 2/2004 Woolston et al.
 6,741,724 B1 5/2004 Bruce et al.

6,768,810 B2 7/2004 Emanuelsson et al.
 6,778,703 B1 8/2004 Zlotnick
 6,805,926 B2 10/2004 Cote et al.
 6,816,602 B2 11/2004 Coffelt et al.
 6,829,369 B2 12/2004 Poulin et al.
 6,961,466 B2 11/2005 Imagawa et al.
 6,985,925 B2 1/2006 Ogawa
 6,985,926 B1 1/2006 Ferlauto et al.
 7,016,532 B2 3/2006 Bonczyk et al.
 7,031,519 B2 4/2006 Elmenhurst
 7,096,152 B1 8/2006 Ong
 7,120,302 B1 10/2006 Billester
 7,121,458 B2 10/2006 Avant et al.
 7,152,047 B1 12/2006 Nagel
 7,171,049 B2 1/2007 Snapp
 7,204,415 B2 4/2007 Payne et al.
 7,212,949 B2 5/2007 Bachrach
 7,333,987 B2 2/2008 Ross et al.
 7,343,623 B2 3/2008 Ross
 7,356,162 B2 4/2008 Caillon
 7,379,603 B2 5/2008 Ross et al.
 7,436,979 B2 10/2008 Bruce et al.
 7,477,780 B2 1/2009 Bonczyk et al.
 7,518,080 B2 4/2009 Amato
 7,602,938 B2 10/2009 Prokoski
 7,674,995 B2 3/2010 Desprez et al.
 7,676,433 B1 3/2010 Ross et al.
 7,680,306 B2 3/2010 Boutant et al.
 7,720,256 B2 5/2010 Desprez et al.
 7,726,457 B2 6/2010 Maier et al.
 7,726,548 B2 6/2010 Delavergne
 7,748,029 B2 6/2010 Ross
 7,822,263 B1 10/2010 Prokoski
 7,834,289 B2 11/2010 Orbke et al.
 7,853,792 B2 12/2010 Cowburn
 8,022,832 B2 9/2011 Vogt et al.
 8,032,927 B2 10/2011 Ross
 8,108,309 B2 1/2012 Tan
 8,180,174 B2 5/2012 Di et al.
 8,180,667 B1 5/2012 Baluja et al.
 8,194,938 B2 6/2012 Wechsler et al.
 8,316,418 B2 11/2012 Ross
 8,374,020 B2 2/2013 Katti
 8,374,399 B1 2/2013 Talwerdi
 8,374,920 B2 2/2013 Hedges et al.
 8,391,583 B1 3/2013 Mennie et al.
 8,428,772 B2 4/2013 Miette et al.
 8,437,530 B1 5/2013 Mennie et al.
 8,457,354 B1 6/2013 Kolar et al.
 8,477,992 B2 7/2013 Paul et al.
 8,520,888 B2 8/2013 Spitzig et al.
 8,526,743 B1 9/2013 Campbell et al.
 8,774,455 B2 7/2014 Elmenhurst et al.
 8,959,029 B2 2/2015 Jones et al.
 9,031,329 B1 5/2015 Farid et al.
 9,058,543 B2 6/2015 Campbell et al.
 9,152,862 B2 10/2015 Ross et al.
 9,170,654 B2 10/2015 Bonczyk et al.
 9,224,196 B2 12/2015 Duerksen et al.
 9,234,843 B2 1/2016 Sopori et al.
 9,245,133 B1 1/2016 Durst et al.
 9,350,552 B2* 5/2016 Elmenhurst G06F 16/583
 9,350,714 B2 5/2016 Freeman et al.
 9,361,507 B1 6/2016 Hoyos et al.
 9,361,596 B2 6/2016 Ross et al.
 9,424,461 B1 8/2016 Yuan et al.
 9,443,298 B2 9/2016 Ross et al.
 9,558,463 B2 1/2017 Ross et al.
 9,582,714 B2 2/2017 Ross et al.
 9,646,206 B2 5/2017 Ross et al.
 9,665,800 B1 5/2017 Kuffner
 9,741,724 B2 8/2017 Seshadri et al.
 10,037,537 B2 7/2018 Withrow et al.
 10,043,073 B2 8/2018 Ross et al.
 10,192,140 B2* 1/2019 Ross G06V 10/751
 10,199,886 B2 2/2019 Li et al.
 10,346,852 B2 7/2019 Ross et al.
 10,505,726 B1 12/2019 Andon et al.
 10,540,664 B2 1/2020 Ross et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

10,572,883	B2	2/2020	Ross et al.	2009/0057207	A1	3/2009	Orbke et al.	
10,614,302	B2	4/2020	Withrow et al.	2009/0106042	A1	4/2009	Maytal et al.	
10,621,594	B2	4/2020	Land et al.	2009/0134222	A1	5/2009	Ikeda	
10,740,767	B2	8/2020	Withrow	2009/0154778	A1	6/2009	Lei et al.	
10,872,265	B2*	12/2020	Ross G06T 7/0004	2009/0157733	A1	6/2009	Kim et al.	
10,936,838	B1	3/2021	Wong	2009/0223099	A1	9/2009	Versteeg	
11,238,146	B2*	2/2022	Ross G06V 20/80	2009/0232361	A1	9/2009	Miller	
2001/0010334	A1	8/2001	Park et al.	2009/0245652	A1	10/2009	Bastos	
2001/0054031	A1	12/2001	Lee et al.	2009/0271029	A1	10/2009	Doutre	
2002/0015515	A1	2/2002	Lichtermann et al.	2009/0287498	A2	11/2009	Choi	
2002/0073049	A1	6/2002	Dutta	2009/0307005	A1	12/2009	Omartin et al.	
2002/0134836	A1	9/2002	Cash et al.	2010/0027834	A1	2/2010	Spitzig et al.	
2002/0168090	A1	11/2002	Bruce et al.	2010/0054551	A1	3/2010	Decoux	
2003/0015395	A1	1/2003	Hallowell et al.	2010/0070527	A1	3/2010	Chen	
2003/0046103	A1	3/2003	Amato et al.	2010/0104200	A1	4/2010	Baras et al.	
2003/0091724	A1	5/2003	Mizoguchi	2010/0157064	A1	6/2010	Cheng et al.	
2003/0120677	A1	6/2003	Vernon	2010/0163612	A1	7/2010	Caillon	
2003/0138128	A1	7/2003	Rhoads	2010/0166303	A1	7/2010	Rahimi	
2003/0179931	A1	9/2003	Sun	2010/0174406	A1	7/2010	Miette et al.	
2003/0182018	A1	9/2003	Snapp	2010/0286815	A1	11/2010	Zimmermann	
2003/0208298	A1	11/2003	Edmonds	2010/0289627	A1*	11/2010	McAllister H04L 9/3226	340/10.42
2003/0219145	A1	11/2003	Smith	2011/0026831	A1	2/2011	Perronnin et al.	
2004/0027630	A1	2/2004	Lizotte	2011/0064279	A1	3/2011	Uno	
2004/0101174	A1	5/2004	Sato et al.	2011/0081043	A1	4/2011	Sabol et al.	
2004/0112962	A1	6/2004	Farrall et al.	2011/0091068	A1	4/2011	Stuck et al.	
2004/0218791	A1	11/2004	Jiang et al.	2011/0161117	A1	6/2011	Busque et al.	
2004/0218801	A1	11/2004	Houle et al.	2011/0188709	A1	8/2011	Gupta et al.	
2004/0250085	A1	12/2004	Tattan et al.	2011/0194780	A1	8/2011	Li et al.	
2005/0007776	A1	1/2005	Monk et al.	2011/0235920	A1	9/2011	Iwamoto et al.	
2005/0038756	A1	2/2005	Nagel	2011/0267192	A1	11/2011	Goldman et al.	
2005/0065719	A1	3/2005	Khan et al.	2012/0042171	A1	2/2012	White et al.	
2005/0086256	A1	4/2005	Owens et al.	2012/0089639	A1	4/2012	Wang	
2005/0111618	A1	5/2005	Sommer et al.	2012/0130868	A1	5/2012	Loeken	
2005/0119786	A1	6/2005	Kadaba	2012/0177281	A1	7/2012	Frew	
2005/0125360	A1	6/2005	Tidwell et al.	2012/0185393	A1	7/2012	Atsmon et al.	
2005/0131576	A1	6/2005	De et al.	2012/0199651	A1	8/2012	Glazer	
2005/0137882	A1	6/2005	Cameron et al.	2012/0242481	A1	9/2012	Germandt et al.	
2005/0160271	A9	7/2005	Brundage et al.	2012/0243797	A1	9/2012	Di Venuto Dayer et al.	
2005/0169529	A1	8/2005	Owechko et al.	2012/0250945	A1	10/2012	Peng et al.	
2005/0188213	A1	8/2005	Xu	2013/0110719	A1	5/2013	Carter et al.	
2005/0204144	A1	9/2005	Mizutani	2013/0162394	A1	6/2013	Etchegoyen	
2005/0251285	A1	11/2005	Boyce et al.	2013/0212027	A1	8/2013	Sharma et al.	
2005/0257064	A1	11/2005	Boutant et al.	2013/0214164	A1	8/2013	Zhang et al.	
2005/0289061	A1	12/2005	Kulakowski et al.	2013/0256415	A1*	10/2013	Callegari B42D 15/0073	235/494
2006/0010503	A1	1/2006	Inoue et al.	2013/0273968	A1	10/2013	Rhoads et al.	
2006/0083414	A1	4/2006	Neumann et al.	2013/0277425	A1	10/2013	Sharma et al.	
2006/0109520	A1	5/2006	Gossaye et al.	2013/0284803	A1	10/2013	Wood et al.	
2006/0131518	A1	6/2006	Ross et al.	2014/0032322	A1	1/2014	Schwieger et al.	
2006/0177104	A1	8/2006	Prokoski	2014/0140570	A1	5/2014	Ross et al.	
2006/0253406	A1*	11/2006	Caillon G06V 10/40	2014/0140571	A1	5/2014	Elmenhurst et al.	
			705/410	2014/0184843	A1	7/2014	Campbell et al.	
2007/0056041	A1	3/2007	Goodman	2014/0201094	A1	7/2014	Herrington et al.	
2007/0071291	A1	3/2007	Yumoto et al.	2014/0270341	A1	9/2014	Elmenhurst et al.	
2007/0085710	A1	4/2007	Bousquet et al.	2014/0314283	A1	10/2014	Harding	
2007/0094155	A1	4/2007	Dearing	2014/0380446	A1	12/2014	Niu et al.	
2007/0211651	A1	9/2007	Ahmed et al.	2015/0058142	A1	2/2015	Lenahan et al.	
2007/0211964	A1	9/2007	Agam et al.	2015/0067346	A1	3/2015	Ross et al.	
2007/0230656	A1	10/2007	Lowes et al.	2015/0078629	A1	3/2015	Gottmukkula et al.	
2007/0263267	A1	11/2007	Ditt	2015/0086068	A1	3/2015	Mulhearn et al.	
2007/0269043	A1	11/2007	Launay et al.	2015/0110364	A1	4/2015	Ninuma et al.	
2007/0282900	A1	12/2007	Owens et al.	2015/0117701	A1	4/2015	Ross et al.	
2008/0005578	A1	1/2008	Shafir	2015/0127430	A1	5/2015	Hammer	
2008/0008377	A1	1/2008	Andel et al.	2015/0248587	A1	9/2015	Oami et al.	
2008/0011841	A1	1/2008	Self et al.	2015/0294189	A1	10/2015	Benhimane et al.	
2008/0013804	A1	1/2008	Moon et al.	2015/0309502	A1*	10/2015	Breitgand G06Q 30/0185	700/98
2008/0016355	A1	1/2008	Beun et al.	2015/0371087	A1	12/2015	Ross et al.	
2008/0128496	A1	6/2008	Bertranou et al.	2016/0034913	A1	2/2016	Zavarehi et al.	
2008/0130947	A1	6/2008	Ross et al.	2016/0034914	A1	2/2016	Gonen et al.	
2008/0219503	A1	9/2008	Di et al.	2016/0055651	A1	2/2016	Oami	
2008/0250483	A1	10/2008	Lee	2016/0057138	A1	2/2016	Hoyos et al.	
2008/0255758	A1	10/2008	Graham et al.	2016/0072626	A1	3/2016	Kouladjie	
2008/0272585	A1	11/2008	Conard et al.	2016/0117631	A1	4/2016	McCloskey et al.	
2008/0290005	A1	11/2008	Bennett et al.	2016/0162734	A1	6/2016	Ross et al.	
2008/0294474	A1	11/2008	Furka	2016/0180485	A1	6/2016	Avila et al.	
2009/0028379	A1	1/2009	Belanger et al.	2016/0180546	A1	6/2016	Kim et al.	
				2016/0189510	A1	6/2016	Hutz	

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0203387 A1 7/2016 Lee et al.
 2016/0300234 A1 10/2016 Moss-Pultz et al.
 2016/0335520 A1 11/2016 Ross et al.
 2017/0004444 A1 1/2017 Krasko et al.
 2017/0032285 A1 2/2017 Sharma et al.
 2017/0076132 A1 3/2017 Sezan et al.
 2017/0132458 A1 5/2017 Short et al.
 2017/0153069 A1 6/2017 Huang et al.
 2017/0243230 A1 8/2017 Ross et al.
 2017/0243231 A1 8/2017 Withrow et al.
 2017/0243232 A1 8/2017 Ross et al.
 2017/0243233 A1 8/2017 Land et al.
 2017/0249491 A1 8/2017 Macintosh et al.
 2017/0251143 A1 8/2017 Peruch et al.
 2017/0253069 A1 9/2017 Kerkar et al.
 2017/0295301 A1 10/2017 Liu et al.
 2017/0300905 A1 10/2017 Withrow et al.
 2017/0344823 A1 11/2017 Withrow et al.
 2017/0344824 A1 11/2017 Martin
 2017/0372327 A1 12/2017 Withrow
 2018/0000359 A1 1/2018 Watanabe
 2018/0012008 A1 1/2018 Withrow et al.
 2018/0018627 A1 1/2018 Ross et al.
 2018/0018838 A1 1/2018 Fankhauser et al.
 2018/0024074 A1 1/2018 Ranieri et al.
 2018/0024178 A1 1/2018 House et al.
 2018/0047128 A1 2/2018 Ross et al.
 2018/0053312 A1 2/2018 Ross et al.
 2018/0121643 A1 5/2018 Talwerdi et al.
 2018/0144211 A1 5/2018 Ross et al.
 2018/0315058 A1 11/2018 Withrow et al.
 2018/0349694 A1 12/2018 Ross et al.
 2019/0026581 A1 1/2019 Leizeron
 2019/0034518 A1 1/2019 Liu et al.
 2019/0034694 A1 1/2019 Ross
 2019/0102873 A1 4/2019 Wang et al.
 2019/0102973 A1 4/2019 Oyama et al.
 2019/0130082 A1 5/2019 Alameh et al.
 2019/0228174 A1 7/2019 Withrow et al.
 2019/0266373 A1 8/2019 Hirokawa
 2019/0279017 A1 9/2019 Graham et al.
 2019/0287118 A1 9/2019 Ross et al.
 2019/0342102 A1 11/2019 Hao et al.
 2019/0362186 A1 11/2019 Irshad et al.
 2020/0153822 A1 5/2020 Land et al.
 2020/0226366 A1 7/2020 Withrow et al.
 2020/0233901 A1 7/2020 Crowley et al.
 2020/0250395 A1 8/2020 Ross et al.
 2020/0257791 A1 8/2020 Shannon et al.
 2020/0334689 A1 10/2020 Withrow
 2020/0349379 A1 11/2020 Ross
 2020/0356772 A1 11/2020 Withrow et al.

FOREIGN PATENT DOCUMENTS

EP 0759596 A2 2/1997
 EP 1016548 A2 7/2000
 EP 1016549 A1 7/2000
 EP 1719070 B1 4/2009
 EP 2107506 A1 10/2009
 EP 2166493 A1 3/2010
 EP 2195621 B1 11/2013
 EP 2866193 A1 4/2015
 EP 2257909 B1 5/2015
 EP 2869240 A2 5/2015
 EP 2869241 A2 5/2015
 EP 3208744 A1 8/2017
 EP 3249581 A1 11/2017
 EP 3267384 A1 1/2018
 EP 3270342 A1 1/2018
 EP 3435287 A2 1/2019
 EP 3514715 A1 7/2019
 GB 2097979 A 11/1982
 GB 2482127 A 1/2012
 JP 61234481 A 10/1986

JP H07192112 7/1995
 JP 2007213148 A 8/2007
 JP 2010146158 A 7/2010
 KR 20120009654 A 2/2012
 WO 2005086616 A2 9/2005
 WO 2006038114 A1 4/2006
 WO 2007028799 A1 3/2007
 WO 2007031176 A1 3/2007
 WO 2007071788 A1 6/2007
 WO 2007090437 A1 8/2007
 WO 2007144598 A1 12/2007
 WO 2009030853 A1 3/2009
 WO 2009089126 A1 7/2009
 WO 2009115611 A2 9/2009
 WO 2010018464 A2 2/2010
 WO 2010018646 A1 2/2010
 WO 2012145842 A1 11/2012
 WO 2013051019 A1 4/2013
 WO 2013126221 A1 8/2013
 WO 2013173408 A1 11/2013
 WO 2015004434 A1 1/2015
 WO 2016081831 A1 5/2016

OTHER PUBLICATIONS

Anonymous, "Intrinsic Characteristics for Authentication" & "Alp Vision Advances Security Through Digital Technology," Authentication News vol. 12, (No. 9) pp. 2, 7 and 8, dated Sep. 2006, 3 pages total.
 Beekhof et al., "Secure Surface Identification Codes," Proceeding of the SPIE 6819: Security Forensics, Steganography, and Watermarking of Multimedia Contents X:68190D, 2008. (12 pages).
 Boa et al., "Local Feature based Multiple Object Instance Identification using Scale and Rotation Invariant Implicit Shape Model," 12th Asian Conference on Computer Vision, Singapore, Singapore, Nov. 1-5, 2014, pp. 600-614.
 Buchanan et al., "Fingerprinting documents and packaging," Nature 436 (7050): 475, 2005.
 Cavoukian et al., "Biometric Encryption: Technology for Strong Authentication Security and Privacy, Office of the Info. and Privacy Commissioner, Toronto, Ontario, CA," 2008, in WE, International Federation of Information Processing, Vol. 261; pp. 57-77.
 Di Paola et al., "An Autonomous Mobile Robotic System for Surveillance of Indoor Environments," International Journal of Advanced Robotic Systems 7(1): 19-26, 2010.
 Drew, M. S., et al., "Sharpening from Shadows: Sensor Transforms for Removing Shadows using a Single Image," Color and Imaging Conference, vol. 5, Society for Imaging Science and Technology, 2009, pp. 267-271.
 Ebay, "eBay Launches Must-Have iPhone App RedLaser 3.0" <https://www.ebayinc.com/stories/news/ebay-launches-musthave-iphon-app-redlaser30/>, Nov. 18, 2011 (Year: 2011), 8 pages.
 Entropy.com Website History, Wayback Machine; <https://web.archive.org/web/20160330060808/https://www.entrupty.com/>; Mar. 30, 2016 (Year: 2016), 2 pages.
 Farid, "Digital Image Forensics", Dartmouth CS 89/189, Sprint 2013; 199 pages.
 Fischler et al., "Random Sample Consensus: A Paradigm for Model Fitting with Applications to Image Analysis and Automated Cartography," Communication of the ACM 24(6); 381-395, 1981.
 Huang et al., "A Novel Binarization Algorithm for Ballistic Imaging Systems," 3rd International Congress on Image and Signal Processing, Yantai, China, Oct. 16-18, 2010, pp. 1287-1291.
 Huang, et al., "An Online Ballistics Imaging System for Firearm Identification"; 2nd International Conference on Signal Processing Systems, Dalian, China, Jul. 5-7, 2010, vol. 2, pp. 68-72.
 Kartik et al., "Security System with Face Recognition, SMS Alert and Embedded Network Video Monitoring Terminal," International Journal of Security, Privacy and Trust Management 2(5):9-19, 2013.
 Li, "Image Processing for the Positive Identification of Forensic Ballistics Specimens," Proceedings of the 6th International Conference of Information Fusion, Cairns, Australia, Jul. 8-11, 2003, pp. 1494-1498.

(56)

References Cited

OTHER PUBLICATIONS

- Li, "Firearm Identification System Based on Ballistics Image Processing," Congress on Image and Signal Processing, School of Computer and Information Science, Faculty of Computing, Health and Science Edith Cowan University, Perth, Australia pp. 149-154.
- Maddern et al., "Illumination Invariant Imaging: Applications in Robust Vision-based Localization, Mapping and Classification for Autonomous Vehicles," IEEE International Conference on Robotics and Automation, Hong Kong, May 31-Jun. 7, 2014, 8 pages.
- Matsumoto et al., "Nano-artifact metrics based on random collapse of resist," Scientific Reports 4:6142, 2014 (5 pages).
- Mistry et al., "Comparison of Feature Detection and Matching Approaches: SIFT and SURF," Global Research and Development Journal for Engineering, vol. 2, Issue 4, Mar. 2017, 8 pages.
- NCOA Link at http://ribbs.usps.gov/ncoalink/ncoalink_print.htm; dated May 27, 2009; 3 pages.
- Online NCOALink® Processing Acknowledgement Form (PAF) Released by Lorton Data, Jun. 2, 2009, URL=<http://us.generation-nt.com/online-ncoalink-processing-acknowledgement-form-paf-released-by-press-1567191.html>, download date Jun. 25, 2010, 1 page.
- Rublee et al., "ORB: an efficient alternative to SIFT or SURF," IEEE International Conference on Computer Vision, Barcelona, Spain, Nov. 6-13, 2011, 8 pages.
- Schneider et al., "A Robust Content Based Digital Signature for Image Authentication," Proceeding of the International Conference on Image Processing Lausanne, Switzerland, Sep. 19, 1996, pp. 227-230.
- Schwabe Williamson & Wyatt, PC—Listing of Related Cases; dated Sep. 16, 2017; 2 pages.
- Sharma et al., "The Fake vs Real Goods Problem: Microscopy and Machine Learning to the Rescue," KDD 2017 Applied Data Science Paper, Aug. 13-17, 2017, Halifax, NS, Canada, 9 pages.
- Shi et al., "Smart Cameras: Fundamentals and Classification," Chapter 2, Belbachir (ed.), Smart Cameras, Springer, New York, New York, USA 2010, pp. 19-34.
- Shields, "How To Shop Savvy With Red Laser," published online on Mar. 22, 2010; <https://i.phone.appstomn.net/reviews/lifestyle/how-to-shop-savvy-with-redlaser/>, downloaded Mar. 22, 2010, 8 pages).
- Smith, "Fireball: A Forensic Ballistic Imaging System: Proceedings of the 31st Annual International Carnahan Conference on Security Technology," Canberra, Australia, Oct. 15-17, 1997, pp. 64-70.
- Takahashi et al., "Mass-produced Parts Traceability System Based on Automated Scanning of Fingerprint of Things," 15th IAPR International Conference on Machine Vision Applications, Nagoya, Japan, May 8-12, 2017, 5 pages.
- United States Postal Service Publication 28 "Postal Addressing Standards", dated Jul. 2008; text plus Appendix A only; 55 pages.
- United States Postal Service, "NCOALink Systems", <http://www.usps.com/ncsc/addressservices/moveupdate/changeaddress.htm>, website accessed Jun. 23, 2010, 2 pages.
- Veena et al., "Automatic Theft Security System (Smart Surveillance Camera)," Computer Science & Information Technology 3:75-87, 2013.
- Woods, "Counterfeit-spotting truth machine launches out of Dumbo," published online on Feb. 11, 2016, downloaded from <http://technically/brooklyn/2016/02/11/entropy-counterfeit-scanner/> on Mar. 20, 2019, 3 pages.
- Farid, Ahmed, et al., "Integrated fingerprint verification method using a composite signature-based watermarking technique", Optical Engineering, The Catholic University of America, (Year: 2007), 6 pages.
- Non-Final Office Action Issued in U.S. Appl. No. 16/866,468, dated Sep. 9, 2021, 24 pages.
- European Search Report, dated Feb. 25, 2021, for European Application No. 20202130.9, 9 pages.
- Extended European Search Report Application No. 21153877.2, dated Jun. 15, 2021, 8 pages.
- Extended European Search Report, dated Aug. 18, 2021, for European Application No. 21164207.9—17 pages.
- Extended European Search Report, dated Aug. 18, 2021, for European Application No. 21164207.9, 13 pages.
- Extended European Search Report, dated Aug. 19, 2021, for European Application No. 21164353.1, 9 pages.
- Extended European Search Report, dated Jun. 18, 2021, for European Application No. 21153355.9, 8 pages.
- Non-Final Office Action Issued in U.S. Appl. No. 16/553,943, dated Sep. 1, 2021, 13 pages.
- Non-Final Office Action Issued in U.S. Appl. No. 16/827,701, dated Aug. 17, 2021, 19 pages.
- Non-Final Office Action Issued in U.S. Appl. No. 16/917,355, dated May 18, 2021, 26 pages.
- Hensler, J., et al., "Hybrid Face Recognition Based on Real-time Multi-camera Stereo-Matching", ICIAP: International Conference on Image Analysis and Processing, 17th International Conference, Naples, Italy, Sep. 9-13, 2013, 10 pages.
- Jain, Anil K, et al., "Biometric Cryptosystems: Issues and Challenges", Proceedings of the IEEE, IEEE, New York, US, vol. 92, No. 6, Jun. 1, 2004, XP011112757, pp. 948-960.
- Scott, Von Duhn, et al., "Three-View Surveillance Video Based Face Modeling For Recognition", Biometrics Symposium, 2007, IEEE, PI, Sep. 30, 2007, 6 pages XP031202430.
- Truong, Hieu C, et al., "Royal Canadian Mint/Signoptic Technologies Coin DNA Technology", World Money Fair (WMF) Berlin Feb. 1-3, 2011, <http://www.amisdeleuro.org/upload/1340734488.pptx>, 22 pages.
- Zaeri, Naser, "Minutiae-based Fingerprint Extraction and Recognition, 2020 (year 2010)", 47 pages.

* cited by examiner





FIG. 1






FIG. 3




FIG. 4






FIG. 5



FORGERIES AND ALTERATIONS

FIG. 6



FORGERIES AND ALTERATION DETECTION

FIG. 7

FIG. 8


		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0
	->	0	1	1	1	1	0		0	1	1	1	1	0		0	0	0	0	0	0
		0	1	0	0	1	0	XOR	0	1	0	0	1	0	=	0	0	0	0	0	0
		0	1	0	0	1	0		0	1	0	0	1	0		0	0	0	0	0	0
		0	1	1	1	1	0		0	1	1	1	1	0		0	0	0	0	0	0
		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0
Original Image		Image (Pixel Values)						Comparison Image						No Differences Images Match							

FIG. 9




FIG. 13A




FIG. 13B



FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B



FIG. 16A




FIG. 16B





FIG. 17



**DATABASE FOR DETECTING
COUNTERFEIT ITEMS USING DIGITAL
FINGERPRINT RECORDS**

RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 15/862,556, filed Jan. 4, 2018, which is a continuation of U.S. application Ser. No. 15/208,328, filed Jul. 12, 2016 (now U.S. Pat. No. 10,192,140), which is a divisional of U.S. application Ser. No. 14/531,724, filed Nov. 3, 2014 (now U.S. Pat. No. 9,443,298), which is a non-provisional, pursuant to 35 U.S.C. § 119(e), of U.S. provisional application No. 61/914,722 filed Dec. 11, 2013 and U.S. provisional application No. 61/898,780 filed Nov. 1, 2013, both incorporated herein by reference. application Ser. No. 14/531,724 is a continuation-in-part of U.S. application Ser. No. 14/290,653 filed May 29, 2014 (now U.S. Pat. No. 9,350,552) which is a continuation of U.S. application Ser. No. 13/410,753 filed Mar. 2, 2012 (now U.S. Pat. No. 8,774,455) which is a non-provisional, pursuant to 35 U.S.C. § 119(e), of U.S. provisional application No. 61/448,465 filed Mar. 2, 2011, each of which is incorporated herein by reference.

COPYRIGHT NOTICE

© 2018 Alitheon, Inc. A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever. 37 CFR § 1.71(d).

TECHNICAL FIELD

This invention pertains to methods and apparatus to identify and/or authenticate physical items, including documents, and more specifically to using a secure database of digital fingerprint records to detect a counterfeit item.

BACKGROUND OF THE INVENTION

Counterfeiting of manufactured goods is a worldwide problem, with recent studies estimating that 8% of the world's total GDP is now generated by the manufacturing and sales of counterfeit products. Many classes of counterfeit goods create substantial risks to public health including counterfeit pharmaceutical drugs, auto parts, pesticides, and children's toys. In addition, counterfeit computer chips, aerospace parts, and identification documents present significant risks to national security.

Many different approaches have been tried to uniquely identify and authenticate objects, including serial numbers, bar codes, holographic labels, RFID tags, and hidden patterns using security inks or special fibers. All of these methods can be duplicated, and many add a substantial extra cost to the production of the goods being protected. In addition, physically marking certain objects such as artwork, gemstones, and collector-grade coins can damage or destroy the value of the object.

If identifying or certifying information is stored separately from the object in the form of a label, tag, or certificate the entire identification/certification process must typically be performed again if the object is lost and later recovered, or its chain of control is otherwise compromised. There is a

need for solutions that can prove the provenance of an object once the chain of custody is disrupted by the removal of the object from safe custody and/or the loss of the associated identification or certification information.

5 Other known techniques call for comparing bitmaps of images of the objects themselves, or selected regions of interest. Referring now to FIG. 8, the image of the original object is taken and stored for reference. The whole image is stored, although it may be compressed for efficiency. When 10 a new object is encountered, an image is taken of the new object and directly compared to the original image using XOR or similar algorithms. If there are no (or only statistically insignificant) differences, the images are declared a match and the object is authenticated. Further, FFT or 15 similar transforms may be used to generate a “digital signature” of the image that can be used for comparison. See FIG. 9. However, as in the previous case the same method is used—the resultant bitmapped image is compared with another bitmapped image, and if the pixels match the object 20 is authenticated. Such methods are disclosed in U.S. Pat. No. 7,680,306 to Boutant et al. Bitmapped techniques are inefficient due to issues like file size, and have serious limitations that make them effectively unusable in most real world applications, due to variable lighting and orientation of the 25 images, and the authentication of worn, damaged or otherwise altered objects.

SUMMARY OF THE INVENTION

30 The following is a summary of the invention in order to provide a basic understanding of some aspects of the invention. This summary is not intended to identify key/critical elements of the invention or to delineate the scope of the invention. Its sole purpose is to present some concepts of the 35 invention in a simplified form as a prelude to the more detailed description that is presented later.

A physical object is scanned and a digital image of the object is created from the scan. A subset of the image known as an “authentication region” is selected. A set of features is extracted from the authentication region, which is sufficient 40 to create a unique identifier or “digital fingerprint” for that object. The digital fingerprint may be registered in a database.

To select locations in an image to extract fingerprint 45 features, a software process automatically selects a large number—typically hundreds or even thousands per square mm—of preferred areas of interest for purposes of digital fingerprint. A location may be of interest because of a relatively high level of content. That “content” in a preferred 50 embodiment may comprise a gradient or vector, including a change in value and a direction.

In a preferred embodiment, each such area of interest is identified as a circle, for example, by centroid location and radius. Within each circular area of interest, the software 55 then extracts one or more fingerprint features that define the relevant shapes within the corresponding circular location of the image. Each fingerprint feature preferably is stored as a feature vector as illustrated below. A feature vector preferably is an array of integer or floating point values describing 60 an individual shape.

When an object is to be authenticated, a suitable system compares the digital fingerprint of the object to digital fingerprints previously stored in the database, and based on that comparison determines whether the object has been 65 registered before, and is thus authentic. The digital fingerprint data specifies a set of features. Preferably, an “object feature template” may be created which has a list of specific

features and attributes that are relevant for authenticating a particular class of objects. A template may identify locations of particular features. One of the key advantages of the feature based method is that when the object is very worn from handling or use, the system can still identify the object as original, may be impossible with the bitmapped approach.

Another aspect of this disclosure relates to detecting a counterfeit or forged object, for example a document such as a drivers license or passport. In this case, there may be no "original" or source object digital fingerprint for comparison. Rather, "fingerprints" of known indicia of counterfeit or forged objects can be acquired and stored. For example, a large number of counterfeit New York State driver's licenses might be obtained by law enforcement officials in a raid or the like. Digital images of those forged documents can be acquired, and analyzed to form digital fingerprints, as described in more detail below. "Forgery feature vectors" of typical features that occur in the counterfeit licenses can be collected and stored in a database. Such indicia may include, for example, sharp, non-bleeding edges where a photograph has been replaced or torn paper fibers where an erasure occurred. These stored features from the counterfeit licenses can then be analyzed and stored as a reference set of fraudulent methods which can then be compared to new license fingerprints to detect a forged document. A count of "fraud indicator matches" can be compared to an empirical threshold to determine and quantify a confidence that a document is forged (or not).

Further, the fingerprinting approach described below can be used to determine whether a manufactured object meets its manufactured specifications. Applications of the system include but are not limited to object authentication, anti-counterfeiting, determining the provenance of an object, and compliance with manufacturing specifications.

Additional aspects and advantages of this invention will be apparent from the following detailed description of preferred embodiments, which proceeds with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an example of an authentication region and object feature template definition for a U.S. passport.

FIG. 2 is a simplified flow diagram of a process for digital fingerprint generation and registration.

FIG. 3 is a simplified flow diagram of a process for authentication of a previously fingerprinted object.

FIG. 4 is a simplified flow diagram illustrating a process for object inspection to detect evidence of counterfeits.

FIG. 5 is a simplified flow diagram illustrating an object manufacturing inspection process.

FIG. 6 is a simplified flow diagram illustrating a method for building a database for use in detecting forged or altered documents.

FIG. 7 is a simplified flow diagram illustrating a method for using a digital fingerprint of a suspect document to detect a potential forger or alteration associated with the document.

FIG. 8 is a simplified diagram of a prior art bitmap comparison method for comparing images.

FIG. 9 is an example of a photograph and an image created by Fast Fourier Transform (FFT) of the image data.

FIG. 10 is a simple illustration of fingerprint feature extraction from an original digital image.

FIG. 11 is a simple illustration of fingerprint feature extraction from a comparison or candidate image.

FIG. 12 is a simple illustration of fingerprint feature comparison for identifying or authenticating an object.

FIG. 13A shows an image of the numeral "3" representing the first digit in a serial number of an "original" or known U.S. dollar bill.

FIG. 13B shows an image of the numeral "3" representing the first digit in a serial number a U.S. dollar bill to be authenticated.

FIG. 14A is an illustration of results of feature extraction showing selected areas of interest in the image of FIG. 13A.

FIG. 14B is an illustration of results of feature extraction showing selected areas of interest in the image of FIG. 13B.

FIG. 15A shows the same dollar bill image as in FIG. 13A, juxtaposed with FIG. 15B for comparison.

FIG. 15B shows an image of the numeral "3" that has been damaged or degraded.

FIG. 16A shows detail of two fingerprint feature locations on the numeral 3.

FIG. 16B shows detail of the damaged bill with the corresponding fingerprint feature locations called out for comparison.

FIG. 17 is a simplified illustration of a rotational transformation in the process of comparing digital fingerprints of two images.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The methods described in this disclosure enable the identification of objects without attaching or associating any physical tags or materials with the object. A system does this by creating a unique digital signature for the object, which is referred to as a digital fingerprint. Digital fingerprinting utilizes the natural structure of the object, or essentially random features created incidental to the manufacturing process, to generate a unique digital signature for that object, much like a human fingerprint. Also like a human fingerprint, the digital fingerprint can be stored and retrieved to identify objects when they are encountered at a later date.

Eliminating the need to add tags or any physical modifications to the object offers a number of advantages to manufacturers, distributors, sellers and owners of goods. It reduces the cost of manufacturing, and is more secure than physical tagging. Physical tags may be lost, modified, stolen, duplicated, or counterfeited; digital fingerprints cannot.

Unlike prior art approaches that simply utilize a comparison of pixels, a system in accordance with this disclosure utilizes the extraction of features to identify and authenticate objects. Feature extraction enables us to take a large amount of information and reduce it to a smaller set of data points that can be processed more efficiently. For example, a large digital image that contains tens of thousands of pixels may be reduced to just a few features that can effectively identify the object. This reduced set of data we call a digital fingerprint. This digital fingerprint contains a set of individual fingerprint features which are stored as feature vectors. These vectors make image processing more efficient and reduce storage requirements, as the entire image need not be stored in the database, only the feature vectors. Examples of feature extraction algorithms include but are not limited to edge detection, corner detection, blob detection, wavelet features; Gabor, gradient and steerable output filter histograms, scale-invariant feature transformation, active contours, shape contexts and parameterized shapes.

While the most common applications of our system may be in the authentication of manufactured goods and documents, the system is designed to be applicable to any object that can be identified, characterized, quality tested, or authenticated with a digital fingerprint. These include but are

not limited to mail pieces, parcels, art, coins, currency, precious metals, gems, jewelry, apparel, mechanical parts, consumer goods, integrated circuits, firearms, pharmaceuticals and food and beverages. Here we use the term “system” in a broad sense, including our methods as well as apparatus arranged to implement such methods.

Scanning

In an embodiment, an object is scanned and identified either at initial manufacture or at the time of first contact with the system. This point of identification is preferably done when the item is either in the possession of its manufacturer, or has been transferred by secure means to the current holder so that its legitimacy at point of identification is adequately established. When such a process is impossible, as in the example of artworks or old coins, the object may be fingerprinted after the object is authenticated by an expert while its provenance is still secure.

In this application, we use the term “scan” in a broad sense. We refer to any means for capturing an image or set of images, which may be in digital form or transformed into digital form. The images may be two dimensional, three dimensional, or be in the form of a video. Thus a “scan” may refer to an image (or digital data that defines an image) captured by a scanner, a camera, a specially-adapted sensor array such as CCD array, a microscope, a smart phone camera, a video camera, an x-ray machine, etc. Broadly, any device that can sense and capture electromagnetic radiation that has traveled through an object, or reflected off of an object, is a candidate to create a “scan” of the object. Other means to extract “fingerprints” or features from an object may be used; for example, through sound, physical structure, chemical composition, or many others. The remainder of this application will use terms like “image” but when doing so, the broader uses of this technology should be implied. In other words, alternative means to extract “fingerprints” or features from an object should be considered equivalents within the scope of this disclosure.

Authentication Regions

Because the system works with many different types of objects, it is necessary to define what parts of the digital images of the objects are to be used for the extraction of features for authentication purposes. This can vary widely for different classes of objects. In some cases it is the image of the entire object; in other cases it will be a specific sub-region of the image of the object.

For instance, for a photograph we may want to use the digital image of the entire photograph for feature extraction. Each photograph is different, and there may be unique feature information anywhere in the photograph. So in this case, the authentication region will be the entire photograph.

Multiple regions may be used for fingerprints for several reasons, two of which are particularly important. It may be that there are several regions where significant variations take place among different similar objects that need to be distinguished while, in the same objects, there may be regions of little significance, i.e., in which there is little or no variation among different objects. In that case, the authentication region is used primarily to eliminate regions of little interest.

A bank note, for example, has a sufficient number of unique features that it can be authenticated if a few small arbitrary regions scattered across the surface are fingerprinted, along with recognizing the contents of a region telling the value of the bank note and one containing the bank note’s serial number. In such a case the fingerprints of any region (along with sufficient additional information to determine the bank note’s value and its purported identity)

may be sufficient to establish the authenticity of the bill and multiple fingerprinted regions are used solely in the event that one or more regions may be absent (through, for example, tearing) when the bill is later presented for authentication.

Sometimes, however, specific regions of an item must be authenticated to ensure the item is both authentic and has not been altered. A passport provides an example. On a passport the features preferably used for authentication are extracted from regions containing such specific identification information as the passport number, recipient name, and recipient photo. In that case, we define a template of all those regions whose alteration from the original would invalidate the passport, such regions including the passport holder’s photo and unique personal data.

FIG. 1 illustrates an example of an authentication region and object feature template definition for a U.S. passport. In this figure, brace **100** refers to a simplified flow diagram of a process as follows. At process block **102**, an object is scanned to generate an original “image”—technically a digital data file in any suitable format. We will simply refer to this data as an image. The original image is illustrated as the front page of a U.S. passport **150**. Next, the system processes the image data to determine an authentication region. For example, here the authentication region is the lower portion of image **150**, identified by dashed box **154**. Next the process generates an authentication image for feature extraction, block **106**. The image is illustrated at reference **156**. Next, at block **108**, the process defines one or more features for extraction. These are shown in the image **158** by dashed boxes **160**, for example, surname, given name, and passport number regions.

Finally, at block **110**, the process **100** comprises creating a feature template **120**. In this example, template **120** identifies an object class (U.S. Passport), defines an authentication regions (for example, by X-Y coordinates), and it lists one or more features within that authentication region. Here, the list comprises passport number, photo, first name and last name.

The ability to define and store the optimal authentication region for a given class of objects offers significant benefits to the user. In many cases it is much easier to scan a limited region of an object than the entire object. For instance, in the case of an article of designer clothing, it is much easier to take a picture of the manufacturer’s label than it is to take a picture of the entire garment. Further, defining such regions enable the detection of partial alteration of the object.

Once an authentication region is defined, specific applications can be created for different markets and classes of objects that can assist the user in locating and scanning the optimal authentication region. For instance, an appropriately sized location box and crosshairs can automatically appear in the viewfinder of a smartphone camera application to help the user center the camera on the authentication region, and automatically lock onto the region and take the picture when the camera is focused on the correct area.

In many cases, objects may have permanent labels or other identifying information attached to them. These can also be used as features. For instance, wine may be put into a glass bottle and a label affixed to the bottle. Since it is possible for a label to be removed and reused, simply using the label itself as the authentication region is often not sufficient. In this case we may define the authentication region to include both the label and the substrate it is attached to—in this case some portion of the glass bottle. This “label and substrate” approach may be useful in defining authentication regions for many types of objects, such as

consumer goods and pharmaceutical packaging. If a label has been moved from its original position, this can be an indication of tampering or counterfeiting. If the object has “tamper-proof” packaging, this may also be useful to include in the authentication region.

In some cases, we will want to use multiple authentication regions to extract unique features. For a firearm, for example, we might extract features from two different parts of the weapon. It is, of course, important that both match the original, but since the two parts may both have been taken from the original weapon and affixed to a weapon of substandard quality, it may also be important to determine whether their relative positions have changed as well. In other words it may be necessary to determine that the distance (or other characteristic) between Part A's authentication region and Part B's authentication region is effectively unchanged, and only if that is accomplished can the weapon be authenticated.

Object Feature Template Definition

When a new type or class of object is being scanned into the system for the first time, the system can create an Object Feature Template (as shown in FIG. 1) that can be used to optimize subsequent authentication operations for that class of objects. This template can either be created automatically by the system, or by using a human-assisted process.

An Object Feature Template is not required for the system to authenticate an object, as the system can automatically extract features and create a digital fingerprint of an object without it. However, the presence of a template can greatly optimize the authentication process and add additional functionality to the system.

TABLE 1

Example Object Feature Template.	
CLASS:	[Description of the object]
	United States Passport
AUTHENTICATION REGION:	[Description of the authentication regions for the object]
	Region 1: (x1, y1, z1), (x2, y2, z2)
	.
	Region n
REGION MATCH LIST	[List of the regions that are required to match to identify an object]
	Region List: 1..n
FEATURES:	[Key features of the object]
	Feature 1: Passport Number
	Feature 2: Photo
	Feature 3: First Name
	Feature 4: Last Name
	.
	Feature n
METHODS:	[Programs that can be run on features of an object]
	Feature 2:
	Photo Method 1: [checkphoto.exe] Check for uneven edges indicating photo substitution
	.
	Method n

TABLE 1-continued

Example Object Feature Template.	
Feature n	
Method n	
ADDITIONAL DATA	[Additional data associated with the object]
	Data 1: example data
	.
	Data n

The uses of the Object Feature Template include but are not limited to determining the regions of interest on the object, the methods of extracting fingerprinting and other information from those regions of interest, and methods for comparing such features at different points in time. The name “object feature template” is not important; other data with similar functionality (but a different moniker) should be considered equivalent.

Four different but related uses for this technology are particularly in view in this disclosure. These are illustrative but are not intended to be limiting of the scope of the disclosure. These applications may be classified broadly as (1) authentication of a previously scanned original, (2) detection of alteration of a previously scanned original, (3) detection of a counterfeit object without benefit of an original, and (4) determination whether a manufactured item is within manufacturing or other applicable specification.

In case (1), the object is fingerprinted during the creation process (or while its provenance is unquestioned), or at the point where an expert has determined its authenticity and then the object is later re-fingerprinted, and the two sets of fingerprints are compared to establish authenticity of the object. This may be done by extracting a single fingerprint from the entire object or by extracting multiple sets of features from different authentication regions. It may also be facilitated by reading or otherwise detecting a serial number or other identifying characteristic of the object using optical character recognition or other means to make determining which original to compare it with easier. In many cases, manufacturing databases use serial numbers as identifiers. If we know the serial number we can directly access the database record for the object, and can directly compare the digital fingerprint to the original that was stored during the creation process, rather than searching the entire digital fingerprinting database for a match.

In case (2), the object is compared region by region with the original looking for low or nonexistent match of the fingerprint features from those regions. While case (1) is designed to determine whether the original object is now present, this case (2) is to determine whether the original object has been modified and if so, detecting how. In some embodiments, regions of interest having poor or no matching fingerprint features are presumed to have been altered.

In case (3), the item may not have been fingerprinted while its provenance was secure. An example would be legacy bills or passports created prior to initiating the use of a digital fingerprinting system during the creation process. In this case, the fingerprints of regions of interest may be compared with fingerprints from examples of known counterfeit objects, or with both those and fingerprints of known good objects. As an example, if a photo is added to a passport, the edge of the photo is liable to be sharper than the edge of the original, unaltered photo, indicating a cut and paste operation. Fingerprint characteristics of known good passports and those of passports known to have been altered

by changing the photograph can be compared with the passport being inspected to determine whether it shows features of alteration.

FIG. 6 is a simplified flow diagram of a process 600 for building a database for use in detecting counterfeit (forged or altered) objects. At process block 602, digital image data is acquired of a known forged or altered document. Next, we extract features from the image data, as discussed above, block 604. Continuing, at block 606 a digital fingerprint is created based on the extracted features.

The digital fingerprint data is stored in a database record, block 608. Further, the record (digital fingerprint) is designated in the database as having features tending to evidence a forgery, block 610. The basic process may be repeated, loop 650, to acquire more images, and more features, to build the database.

Returning to case (4), the question of authenticity or alteration is not at issue. Instead we use the fingerprinting process to determine whether an object was manufactured sufficiently close to the manufacturing specification. In this case comparison of fingerprint features is against the ideal features of a presumed-perfect object, referred to as the "reference object". The reference object may exist (e.g. be one or more examples of the object that has been inspected by hand and declared good enough to serve as a standard) or may be a programmatic ideal. In this latter case the "ideal" fingerprint features will be generated manually or by a program rather than scanned off an original.

The Object Feature Template can contain a variety of information related to that class of objects. For instance, it would typically include the authentication region(s) for that class of objects, which authentication regions are required to determine a match, and a list of key features that are typically used in authenticating that object.

Additionally, a template can define methods to be applied to features that can be used to examine an object for signs of unauthorized modification or counterfeiting. For instance, every time a passport is scanned into the system, a program can automatically be run to examine the passport photo for signs of alteration. If the passport was fingerprinted at creation, fingerprints extracted from each such region at creation will be compared to fingerprints from corresponding regions when the passport is presented for authentication. If the passport was not fingerprinted at creation, the region template can be used, for example, to look for sharp, non-bleeding edges that can indicate where a photograph has been replaced or torn paper fibers can indicate where an erasure occurred. In addition to the examples discussed above, the Object Feature Template is designed to be extensible, and can store any additional data that is related to the object.

Digital Fingerprint Generation

Once an object has been scanned and at least one authentication region has been identified, the final digital image that will be used to create the unique digital fingerprint for the object is created. This image (or set of images) will provide the source information for the feature extraction process.

A "digital fingerprinting feature" is a feature of the object that is innate to the object itself, a result of the manufacturing process, a result of external processes, or of any other random or pseudo random process. For example, gemstones have a crystal pattern which provides an identifying feature set. Every gemstone is unique and every gem stone has a

series of random flaws in its crystal structure. This crystal pattern may be used to generate feature vectors for identification and authentication.

A "feature" in this description is typically not concerned with reading or recognizing meaningful content by using methods like OCR (optical character recognition). For example, a label on a scanned object with a printed serial number may give rise to various features in fingerprint processing, some of which may become part of a digital fingerprint feature set or vector that is associated with the object. The features may refer to light and dark areas, locations, spacing, ink blobs, etc. This information may refer to the printed serial number on the label, but in the normal course of feature extraction during the fingerprinting process there is no effort to actually "read" or recognize the printed serial number.

As part of identifying the object, however, for ease of comparison of fingerprint features with those of the original which are stored in the object database, such information may in fact be read and stored by utilizing such techniques as optical character recognition. In many cases, serial numbers may be used as the primary index into a manufacturer's database, which may also contain the digital fingerprints. It would be far faster, for example, to determine whether a bank note being inspected is a match with a particular original if we can use the serial number, say "A93188871A" as an index into the digital fingerprinting database, rather than trying to determine which one it matches by iterating through many thousands of fingerprints. In this case (and in similar cases of weapon and passport serial numbers), the index recognition speeds up the comparison process but is not essential to it.

Once a suitable digital fingerprint of an object is generated, it may be stored or "registered" in a database. For example, in some embodiments, the digital fingerprint may comprise one or more fingerprint features which are stored as feature vectors. The database should be secure. In some embodiments, a unique ID such as a serial number also may be assigned to an object. An ID may be a convenient index in some applications. However, it is not essential, as a digital fingerprint itself can serve as a key for searching a database. In other words, by identifying an object by the unique features and characteristics of the object itself, arbitrary identifiers, labels, tags, etc. are unnecessary.

FIG. 2 is a simplified flow diagram of a process 200 for digital fingerprint generation and registration. In this case, the process begins with scanning the object, block 202. An image 250 is acquired, in this illustration an U.S. passport is used. The next step is to identify or generate an authentication region, block 204. For example, the authentication region may be the portion 252. The authentication region may be identified, as discussed above, from an object feature template (see Table 1). Next an object class of the object is determined, block 206. The result is used to check a database for a corresponding object class template, decision 208. If there is no matching template, the process proceeds to extract features, block 210 without the aid of a template. A digital fingerprint is created based on the extracted feature, block 212, and that digital fingerprint is stored in an object database 220. Alternatively, if a matching object class template is found at decision 208, the process continues to extract features, block 222, utilizing the class template 223 to identify and locate the features. Then, a digital fingerprint is created from the resulting feature data, block 224, and stored in a database 230.

Authentication and Inspection Processes

When an object is presented, it is scanned and an image is generated. At that point, the steps to be followed depend on the operation to be performed. Several illustrative cases are discussed below.

Case #1: For authentication of a previously fingerprinted object, the following steps may be followed (see FIG. 3, discussed below):

1. The authentication region (or regions) is either determined automatically by the system, or by utilizing the authentication region definitions stored in an Object Feature Template.
2. The relevant features are extracted from the authentication region(s) and the digital fingerprint is created. This will typically be in the form of feature vectors, but other data structures may be used as appropriate.
3. Optionally, a unique identifier such as a serial number may be extracted and stored to augment subsequent search and identification functions.
4. The digital fingerprint of the object to be authenticated is compared to the digital fingerprints stored in the database.
5. The system reports whether the object is authentic; i.e. whether it matches one of the digital fingerprints stored in the database.
6. The system may then store the digital fingerprint of the object to be authenticated in the database along with the results of the authentication process. Normally only the extracted features will be stored in the database, but the authentication image and/or the original image may be stored in the database for archival or audit purposes.

FIG. 3 illustrates such a process 300 in diagrammatic form. Beginning at start block 302, the process scans an object and creates an authentication image, block 304. The image is represented at 350, again using the passport example. Features are extracted, block 306, and optionally a serial number or similar ID number, preferably unique, may be extracted as well, block 310.

The extracted data is processed to create a digital fingerprint, block 312. An object database 320 may be queried for a matching fingerprint, block 314. A “match” may be defined by a probability or similarity metric. Results of the database query may be reported to a user, block 322. Finally, a new digital fingerprint may be stored into the database 320, shown at process block 330.

Case #2: For inspection of specific features of a previously fingerprinted object to determine whether they have been altered, the steps are similar to Case #1, but the process is used for the detection of alterations rather than authentication of the object:

1. The authentication region (or regions) is either determined automatically by the system, or by utilizing the authentication region definitions stored in an Object Feature Template.
2. The features to be inspected are extracted from the authentication region and the digital fingerprint is created. This will typically be in the form of feature vectors for the features to be inspected but other data structures may be used as appropriate.
3. Optionally, a unique identifier such as a serial number may be extracted and stored to be used to augment subsequent search and identification functions.
4. The digital fingerprint of the features to be inspected for alteration is compared to the fingerprint of the corresponding features from the original object stored in the database.

5. The system reports whether the object has been altered; i.e. whether the digital fingerprint of the features to be inspected match those previously stored in the database from the original object.

6. The system may then store the digital fingerprint of the features to be inspected in the database along with the results of the inspection process. Normally only the features will be stored in the database, but the authentication image and/or the original image may be stored in the database for archival or audit purposes.

Case #3: For inspection of the specific features of an object that has not been previously fingerprinted to determine whether the features have been altered, the following steps may be followed, referring now to FIG. 4.

The system scans the object, block 404, and creates an authentication image 450 that includes at least one authentication region. The authentication region (or regions) may be determined automatically by the system, or by utilizing the authentication region definitions defined in a stored Object Feature Template 406 as noted earlier. Either way, the process next extracts features from the authentication region(s), block 408, and a digital fingerprint is created. This will typically be in the form of feature vectors, but other data structures may be used as appropriate.

The features of the object are then analyzed, block 420, and examined for attributes indicative of a counterfeit, block 402. Methods may be applied to the features by running programs that are listed in the Object Feature Template that check features for signs of counterfeiting. Features can also be statistically compared to features of other objects of the same class that are stored in the database using Bayesian algorithms or other methods to find suspect variations that the standard methods may not catch. Optionally, a serial number or similar ID may be extracted, block 410.

The system preferably reports whether the object shows signs of alteration or counterfeiting, block 422. The system may then store the digital fingerprint of the object to be inspected, block 424, in the database 430 along with the results of the inspection process. Normally only the extracted features will be stored in the database, but the authentication image and/or the original image may be stored in the database for archival or audit purposes.

Case #4: For inspection of an object to determine whether it was manufactured in conformance with the manufacturer’s specification, the following steps are followed; referring now to FIG. 5. The authentication region (or regions) for an object 502 is determined by utilizing the authentication region definitions stored in an Object Feature Template 506. In this illustration, the object 502 is a U.S. \$100 bill. Scanning and creation of an authentication image are indicated at process block 504.

The manufacturing features are extracted from the regions of interest, block 508, and the digital fingerprint is created (not shown). This will typically be in the form of feature vectors for the manufacturing features, but other data structures may be used as appropriate. Optionally, a unique identifier such as a serial number may be extracted, block 510, and stored to be used to augment subsequent search and identification functions.

Next, the digital fingerprint of the manufacturing features of the object to be checked is analyzed, block 520, and compared to a fingerprint of the manufacturing features from a reference object (i.e., a perfect manufactured object) stored in the database, illustrated at block 521. In other words, in some embodiments, a reference object may be “fingerprinted” and used as a proxy for manufacture specifications. In other cases, the digital fingerprint of the object, and more

specifically the extracted feature vectors, may be compared to reference feature vectors that are based on manufacture specifications. This type of comparison speaks to quality of the object, but may not indicate provenance.

The system reports, block 522, whether the manufactured object meets specifications; i.e. whether the digital fingerprint of the manufacturing features sufficiently match those stored in the database from the reference object. The system may then store the digital fingerprint of the manufacturing features in the database 530, process block 524, along with the results of the manufacturing inspection process. Normally only the extracted manufacturing features will be stored in the database, but the manufacturing inspection image and/or the original image may be stored in the database for archival or audit purposes.

Because in all of the above cases we may be extracting features from images produced under variable lighting conditions, it is highly unlikely two different “reads” will produce the exact same digital fingerprint. In a preferred embodiment, the system is arranged to look up and match items in the database when there is a “near miss.” For example, two feature vectors [0, 1, 5, 5, 6, 8] and [0, 1, 6, 5, 6, 8] are not identical but by applying an appropriate difference metric the system can determine that they are close enough to say that they are from the same item that has been seen before. One example is to calculate Euclidean distance between the two vectors in multi-dimensional space, and compare the result to a threshold value. This is similar to the analysis of human fingerprints. Each fingerprint taken is slightly different, but the identification of key features allows a statistical match with a high degree of certainty.

FIG. 7 is a simplified flow diagram illustrating a method 700 for using a digital fingerprint of a suspect document to detect a potential forgery or alteration associated with the document. First, image data is acquired of a suspect document, block 702. Then the process extracts features from a selected region of the document, block 704. The extracted features are used to form a digital fingerprint, block 706. Next the digital fingerprint or the extracted features are used to form a query, and the query is used to access a forgery/alteration database in search of a matching record, block 708. If a matching record is returned, decision block 710, then the system may report a potential forgery or alteration associated with the suspect document, block 712. Optionally, multiple results may be combined in reaching a conclusion, block 720, where such are available.

Referring again to decision block 710, if no match is returned (i.e. no record matches the query criteria within a selected tolerance or confidence), then the process optionally may be repeated, block 714, for comparison to additional database records. In other words, the database search may be expanded, see loop 718. Again, multiple query results may be combined. Further, the entire process, defined by loop 730, may be repeated for inspecting and analyzing additional or different regions of the document, block 722. As discussed earlier, multiple regions of interest may be defined. Terminal conditions, not shown, may be implemented.

FIG. 10 is an illustration of an example of feature extraction from a digital image. The original image data, on the left, is searched by any of various software processes to detect and locate a feature in the image. In this case, the only important shape in this image is a square, and it extracts that feature, as shown in the middle of the figure, with “1” pixel values. (Most real implementations will have greater than one-bit pixel values.) Then, the extracted fingerprint feature

may be stored as a feature vector as illustrated on the right side of the figure. A feature vector is an n-dimensional vector of numerical values that represent the shape.

In this approach, we may store only the features, not the entire image. In fact, after feature extraction the original image can be discarded. This has obvious advantages in terms of reduced storage requirements. Typical algorithms used for extracting features include but are not limited to edge detection, corner detection, blob detection, wavelet features; Gabor, gradient and steerable output filter histograms, scale-invariant feature transformation, active contours, shape contexts and parameterized shapes.

Referring now to FIG. 11, it illustrates essentially the same process for accessing a comparison or candidate image, extracting features from that image, and again storing each of them as a feature vector. Note that the example above is presented solely for the purpose of explanation, and actual implementations will vary. For instance, many shapes can be parameterized and stored even more efficiently. Instead of storing all the pixels along the boundaries, the square in FIG. 10 could actually just be stored as the lower left and upper right corner points ((x1, y1), (x2, y2)). Similarly, a circle could be stored with just the center point and radius. Feature vectors can store a wide variety of n-dimensional representations such as point, lines, polylines, edges, ridges, histograms and many others.

Once the features are extracted from the original image and the candidate image, the features can be compared directly to determine if there is a match. Typical algorithms for comparing features include but are not limited to nearest neighbor, hashing, indexing feature sets with visual vocabularies, support vector machines, multilayer perceptron and random forests and ferns. A comparison of these feature vectors is illustrated in FIG. 12, resulting in a match.

FIG. 13A illustrates an image of the numeral “3” representing a number printed on an “original” or known U.S. dollar bill. This bill may have been fingerprinted, for example, at the time of manufacture or public release, as described herein. As noted below, fingerprint databases of currency and the like may be secured. And such databases preferably exclude raw image data. This image, on the order of about 40x magnification, shows a couple of distinctive features visible to the naked eye.

FIG. 13B illustrates an image of a number printed on a second or unknown U.S. dollar bill. This second bill may be fingerprinted using the same process, and then the resulting digital fingerprints, i.e., the respective fingerprint feature vectors, may be compared as further explained below, to determine whether or not the second bill is in fact the same one as the first bill, even though it may have changed from wear and tear.

FIG. 14A is a simplified illustration of the results of feature extraction applied to the numeral 3 of FIG. 13A. (Only the ends of the numeral are shown.) Two areas of interest are called out by circles 1720 and 1750. Below we discuss how these areas may be selected in an image. Fingerprint feature extraction is applied to each of these circular regions. The results for each location are stored in fingerprint feature vectors. A collection of feature vectors, say for location 1750, may be stored as a feature vector array. FIG. 14B is a simplified illustration of the results of feature extraction applied to the numeral 3 of FIG. 13B. The same fingerprinting process is applied to this image. The same locations of interest as in FIG. 14A are labeled 1720 and 1760, respectively. Then the stored features (from the original object) are compared with the features extracted

15

from the new object. As in this case, if the features are not encountered in the second object, it is not a match.

One of the key advantages to the feature-based method is that when the object is very worn from handling or use, the system can still identify the object as original, which may be impossible with the bitmapped approach. FIG. 15A shows the same dollar bill image as in FIG. 13A, juxtaposed with FIG. 15B for comparison. FIG. 15B shows the same bill after machine washing, perhaps in someone's pocket.

In FIG. 15B, the image (actually the dollar bill) has been degraded; there is significant loss of ink and destruction of the paper surface in multiple locations. A bit mapped approach would clearly fail to match up here, as the number of pixels that are different is significant—only relatively few of the pixels are the same as the original.

FIG. 16A shows the detail of two fingerprint feature locations as before, 1610 and 1650. FIG. 16B shows detail of the damaged bill with the corresponding locations called out as 1620 and 1660, respectively. Here, one can see visually why a comparison of the corresponding fingerprint feature vectors would be adequate to result in a match. In practice, a much larger number of features would be used.

The image of the damaged bill is analyzed by a processor. The processor accesses a database of previously stored fingerprint data. If the dollar bill serial number is legible (by eye or machine), the record for the corresponding bill may be accessed from the datastore using the serial number as an index. Similarly, if any portion of the serial number is legible, the search for a matching record can be narrowed on that basis. Either way, a candidate record, containing a set of stored regions of interest may be compared to the suspect image.

As explained above, in addition to being able to recognize a worn object, the feature-based approach can deal with problems like rotated images. This is especially important in a system where the retail customer may be taking a picture of an object to be authenticated. In this case external factors like lighting and rotation are not under the manufacturer's control.

Referring now to FIG. 17, it shows the original image on the left side, with a small set of fingerprint features marked as small diamond shapes. This is merely a callout symbol for illustration. In a preferred implementation, as noted, circular areas are used. For each feature (preferably identified in the database record), a search is conducted of the suspect image on the right side of FIG. 17 for a matching feature. The position may not match exactly, due to "stretch"—an effective difference in magnification, and/or due to rotation of the image. Although it may not match locations literally; a mathematical transformation can be defined that maps one image to the other, thereby accounting for rotation and stretch as appropriate. Thus, a bounding rectangle A indicated by the box in the left side image may be mapped to a quadrilateral indicated by the line B in the right side image.

Once an appropriate transformation is found, further matching can be done to increase the level of confidence of the match if desired. In some applications, a number of matches on the order of tens or hundreds of match points is sufficient. On the other hand, the number of non-match points also should be taken into account. That number should be relatively very low, but it may be non-zero due to random dirt, system "noise" and the like. Preferably, the allowed mapping or transformation should be restricted depending on the type of objects under inspection. For instance, some objects may be inflexible, which may restrict the possible deformations of the object.

16

To summarize the imaging requirements for a typical fingerprinting system, for example for inspecting documents, it should provide sufficient imaging capability to show invariant features. The particulars will depend on the regions used for authentication. For many applications, 10× magnification is adequate. For ink bleeds on passports, bills and other high-value authentication, 40× power is more than sufficient. In preferred embodiments, the software should implement a flexible response to accommodate misalignment (rotation), orientation and scale changes. Color imaging and analysis is generally not required for using the processes described above.

Hardware and Software

Most of the equipment discussed above comprises hardware and associated software. For example, the typical portable device is likely to include one or more processors and software executable on those processors to carry out the operations described. We use the term software herein in its commonly understood sense to refer to programs or routines (subroutines, objects, plug-ins, etc.), as well as data, usable by a machine or processor. As is well known, computer programs generally comprise instructions that are stored in machine-readable or computer-readable storage media. Some embodiments of the present invention may include executable programs or instructions that are stored in machine-readable or computer-readable storage media, such as a digital memory. We do not imply that a "computer" in the conventional sense is required in any particular embodiment. For example, various processors, embedded or otherwise, may be used in equipment such as the components described herein.

Memory for storing software again is well known. In some embodiments, memory associated with a given processor may be stored in the same physical device as the processor ("on-board" memory); for example, RAM or FLASH memory disposed within an integrated circuit microprocessor or the like. In other examples, the memory comprises an independent device, such as an external disk drive, storage array, or portable FLASH key fob. In such cases, the memory becomes "associated" with the digital processor when the two are operatively coupled together, or in communication with each other, for example by an I/O port, network connection, etc. such that the processor can read a file stored on the memory. Associated memory may be "read only" by design (ROM) or by virtue of permission settings, or not. Other examples include but are not limited to WORM, EPROM, EEPROM, FLASH, etc. Those technologies often are implemented in solid state semiconductor devices. Other memories may comprise moving parts, such as a conventional rotating disk drive. All such memories are "machine readable" or "computer-readable" and may be used to store executable instructions for implementing the functions described herein.

A "software product" refers to a memory device in which a series of executable instructions are stored in a machine-readable form so that a suitable machine or processor, with appropriate access to the software product, can execute the instructions to carry out a process implemented by the instructions. Software products are sometimes used to distribute software. Any type of machine-readable memory, including without limitation those summarized above, may be used to make a software product. That said, it is also known that software can be distributed via electronic transmission ("download"), in which case there typically will be

a corresponding software product at the transmitting end of the transmission, or the receiving end, or both.

Integration with Bill Processing Equipment

We propose creation of fingerprint data at the U.S. Treasury or any other producer (printer) of negotiable bills or notes. Preferably, such a system utilizes random, microscopic features unique to each bill's paper and printing. For example, the system may extract features from unpublished locations on the bills. In other words, the specific locations used for authentication are maintained in secrecy. The extracted features may be converted into encrypted feature vectors and associated in a data store with the corresponding bill serial number (the serial number having been readily captured by the same scanner or a separate one). In this way, a protected database may be created that is addressable or searchable by serial number or feature vector, but only by authorized users. (Here, a "user" may be a machine with electronic access to the database.)

Equipment is known for stacking, counting, and "strapping" paper money notes. A "strap" is a package of 100 notes, held together by a single paper band, as required for deposit by U.S. Federal Reserve rules. Various note handling equipment may be modified to include a digital scanner, for example, an optical scanner, to capture images of each bill or note as it is processed. The scanner may be coupled to a suitable processor, as explained above, for storing the captured images, and for processing the images to authenticate them and/or to detect counterfeit items.

Preferably, such a system is granted access to the protected database that is searchable by serial number or digital fingerprint. It may then look up each bill scanned, and compare features of the digital image to the digital fingerprint stored in protected database for the corresponding serial number. This process may be done by batch or in real time or near real time. The comparison, as further described above, may provide a confidence metric, or a simple yes/no (authentic/counterfeit) result for each note. It may identify a counterfeit note by serial number, but also by sequence number to facilitate locating the bill ("the 28th bill in the strap #218"). In this way, a bank or other institution can detect counterfeit notes in a timely manner.

In another embodiment, a scanner, which may be portable and optionally wireless, may be made available at a bank teller station for the teller to authenticate bills presented for deposit or exchange. Further, such a system may be installed at an ATM machine to automatically authenticate bills presented for deposit. The ATM may be programmed to accept the bills to get them "off the street" but flag them as counterfeit or suspect.

The term "note" is commonly used in the U.K. with regard to paper money, while the term "bill" is more common in the U.S. We use them interchangeably here. Not to be confused with U.S. Treasury "bills" and "notes" which are not currency but debt instruments. That said, the inventions disclosed herein are applicable to those as well as currency, although nowadays such things are mainly processed by electronic "book entries" rather than paper documents. Older U.S. Savings Bonds, and any other bearer instruments in any country, can all be authenticated by various embodiments of the present invention.

Having described and illustrated the principles of the disclosure and some illustrative embodiments thereof, it should be apparent that the invention may be modified in arrangement and detail without departing from such principles. For convenience, we summarize below some aspects

of the disclosure. The following list is merely illustrative and not intended to limit or define all the inventions disclosed. The scope of the present invention should, therefore, be determined only by the following claims.

The invention claimed is:

1. A machine comprising:
 - an input device that captures image data of at least a portion of a suspect physical object; and
 - a digital fingerprint system having a processor and a memory wherein the processor is configured to create a digital fingerprint of the suspect physical object based on the image data, wherein the digital fingerprint includes a first piece of data identifying a plurality of regions of interest of the suspect physical object and, for each region of interest, a second piece of data forming at least one fingerprint feature vector that describes a fingerprint feature extracted from the region of interest of the suspect physical object;
 - store the created digital fingerprint for the suspect physical object in a database, the database having stored therein multiple digital fingerprints associated with multiple physical objects, wherein the digital fingerprint identifies the suspect physical object as being unique among the multiple physical objects.
2. The machine of claim 1, wherein the input device includes at least one optical sensor.
3. The machine of claim 1, wherein the fingerprint feature includes manufacturing features of the suspect physical object.
4. The machine of claim 1, wherein the processor of the digital fingerprint system is further configured to extract a unique identifier from the suspect physical object; and store the unique identifier in the database to augment search and identification of the suspect physical object.
5. The machine of claim 1, wherein the input device further captures image data of at least a portion of a reference physical object that is manufactured according to a specification of a manufacturer; and the processor of the digital fingerprint system is further configured to create a digital fingerprint of the reference physical object, wherein the digital fingerprint of the reference physical object includes a first piece of data identifying a plurality of regions of interest of the reference physical object and, for each region of interest, a second piece of data forming at least one reference feature vector that describes a fingerprint feature extracted from the region of interest of the reference physical object, wherein the digital fingerprint of the reference physical object serves as a proxy for the specification of the manufacturer; and store the digital fingerprint of the reference physical object in the database.
6. The machine of claim 5, wherein processor of the digital fingerprint system is further configured to compare the digital fingerprint of the suspect physical object to the digital fingerprint of the reference physical object to generate a result that determines whether the suspect physical object was manufactured in conformance with the specification of the manufacturer;
 - determine the result indicates a match between the at least one fingerprint feature vector included in the digital fingerprint of suspect physical object and the at least one reference feature vector included in the digital fingerprint of the reference physical object; and
 - determine the suspect physical object is manufactured in conformance with the specification of the manufacturer based on the match.

7. The machine of claim 1, wherein the fingerprint feature of the suspect physical object includes dimensional qualities associated with at least one physical feature of the suspect physical object.

8. The machine of claim 1, wherein the fingerprint feature of the suspect physical object includes non-alpha-numeric, optically discernible features of the suspect physical object.

9. The machine of claim 1, wherein the fingerprint feature of the suspect physical object includes multiple known indicia of a counterfeit or forged object.

10. The machine of claim 1, wherein the processor of the digital fingerprint system is further configured to parse the image data into the plurality of regions of interest;

collect a piece of region-of-interest data from each region of interest of the image data;

generate identifier data for each region of interest, the identifier data pairing an identifier with the region-of-interest data of a corresponding region of interest;

and

associate the identifier data with the digital fingerprint of the suspect physical object.

11. The machine of claim 10, wherein the database includes at least one list of classification elements and individual element values for each of the classification elements, wherein each classification element and its corresponding individual element values together define a corresponding pattern, and wherein the database is arranged to support searching a plurality of patterns for a match based on identifier data associated with digital fingerprints stored in the database.

12. The machine of claim 1, wherein the digital fingerprint of the suspect physical object is based on image data of the portion of the suspect physical object, wherein the image data is independent from identifying information about the suspect physical object included in tags, labels, or other materials added to the suspect physical object.

13. The machine of claim 1, wherein the processor of the digital fingerprint system is further configured to extract information from the image data;

categorize the extracted information to determine a category; and

include a category indicator in the digital fingerprint of the suspect physical object.

14. The machine of claim 1, wherein the pieces of data of the digital fingerprint of the suspect physical object are responsive to one or more characteristics appearing in a presentable image generated from the image data, the one or more characteristics including a plurality of markings discernible in the presentable image together with respective region data of each of the plurality of markings.

15. The machine of claim 14, wherein the pieces of data of the digital fingerprint of the suspect physical object include size data for each of the plurality of markings.

16. The machine of claim 14, wherein the pieces of data of the digital fingerprint of the suspect physical object include dimension data for each of the plurality of markings, the dimension data defined, at least in part, by corresponding dimensions of each respective marking.

17. The machine of claim 14, wherein the pieces of data of the digital fingerprint of the suspect physical object

include pixel-count data for each of the plurality of markings, the pixel-count data defined, at least in part, by a total pixel count of each respective marking.

18. A system comprising:

a processor and memory connected to each other;

a database connected to the processor, wherein the database stores multiple digital fingerprints associated with multiple physical objects;

an input device connected to the processor;

a network interface configured to communicate with the processor and the input device over a network; and

a plurality of lines of instructions stored in the memory and executed by the processor of the system that is configured to

acquire, from the input device, image data of at least a portion of a suspect physical object;

create a digital fingerprint of the suspect physical object based on the image data, wherein the digital fingerprint includes a first piece of data identifying a plurality of regions of interest of the suspect physical object and, for each region of interest, a second piece of data forming at least one fingerprint feature vector that describes a fingerprint feature extracted from the region of interest; and

store the digital fingerprint in the database, wherein the digital fingerprint identifies the suspect physical object as being unique among the multiple physical objects.

19. The system of claim 18, wherein the fingerprint feature includes manufacturing features of the suspect physical object.

20. The system of claim 18, wherein the processor is further configured to acquire, from the input device, image data of at least a portion of a reference physical object that is manufactured according to a specification of a manufacturer;

create a digital fingerprint of the reference object, wherein the digital fingerprint of the reference physical object includes a first piece of data identifying a plurality of regions of interest of the reference physical object and, for each region of interest, a second piece of data forming at least one reference feature vector that describes a fingerprint feature extracted from the region of interest of the reference physical object; and store the digital fingerprint of the reference physical object in the database.

21. The system of claim 20, wherein the processor is further configured to compare the digital fingerprint of the suspect physical object to the digital fingerprint of the reference physical object to generate a result that determines whether the suspect physical object was manufactured in conformance with the specification of the manufacturer;

determine the result indicates a match between the at least one fingerprint feature vector included in the digital fingerprint of the suspect physical object and the at least one reference feature vector included in the digital fingerprint of the reference physical object; and

determine the suspect physical object is manufactured in conformance with the specification of the manufacturer based on the match.

* * * * *