

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
17 April 2008 (17.04.2008)

PCT

(10) International Publication Number  
WO 2008/045862 A1(51) International Patent Classification:  
*H02K 1/27* (2006.01)      *H02K 15/03* (2006.01)

AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:  
PCT/US2007/080790

(22) International Filing Date: 9 October 2007 (09.10.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
11/545,320 10 October 2006 (10.10.2006) US(71) Applicant (for all designated States except US): CANOPY  
TECHNOLOGIES, LLC [US/US]; 901 North Fourth  
Street, Jeannette, Pennsylvania 15644 (US).(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,  
PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): TAPPER, Kevin,  
L. [US/US]; 1527 Elm Street, Greensburg, Pennsylvania  
15601 (US).(74) Agents: BYRNE, Richard, L. et al.; The Webb Law Firm,  
700 Koppers Building, 436 Seventh Avenue, Pittsburgh,  
Pennsylvania 15219 (US).(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,


## Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

## Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(54) Title: METHOD AND APPARATUS FOR ASSEMBLING ROTOR OF PERMANENT MAGNET MOTOR



WO 2008/045862 A1

(57) Abstract: Apparatus and method for assembling a permanent magnet rotor comprising a rotor fixture configured to slide over a smaller diameter bearing section of the rotor and abutting one end of a center axial section of the rotor and a split compression ring having an inner diameter that is sized to ride over the outer diameter of magnets in magnet carriers assembled on the rotor fixture.

## METHOD AND APPARATUS FOR ASSEMBLING ROTOR OF PERMANENT MAGNET MOTOR

### BACKGROUND OF THE INVENTION

#### Field of the Invention

**[0001]** This invention relates to assembly of the rotor of a permanent magnet motor. The rotor has a plurality of recesses and overhung slots. Permanent magnet carriers and C-shaped lamination stacks are assembled in ring-shaped units interfitting with the recesses and overhung slots.

#### Description of Related Art

**[0002]** This invention relates to the assembly of the rotor of a permanent magnet motor generally as described in U.S. Patent No. 6,933,645.

### SUMMARY OF THE INVENTION

**[0003]** Briefly, according to this invention, there is provided an apparatus for assembling a permanent magnet rotor. The rotor is comprised of a non-magnetic cylindrical shaft having a larger diameter central axial section and two smaller diameter bearing sections. The central section has an even number of recesses defining an even number of ribs and overhung slots. The apparatus comprises a temporary rotor fixture configured to slide over a smaller diameter bearing section of the rotor and to abut one end of the center section. The axial end of the fixture adjacent the center section has a configuration matching the center section including ribs and overhung slots whereby magnets in magnet carriers and C-shaped lamination stacks can be assembled over the ribs of the rotor fixture. The apparatus further comprises a split compression ring having an inner diameter that is sized to ride over the outer diameter of the C-shaped lamination stacks. Fasteners are provided for joining the split compression ring to compress the C-shaped lamination stacks sufficiently to provide a riding clearance between the C-shaped lamination stacks and the overhung slots.

**[0004]** Briefly, according to this invention, there is provided a method for assembling a permanent magnet rotor. The rotor is comprised of a non-magnetic cylindrical shaft having a larger diameter central axial section and two smaller diameter bearing sections, the central section having an even number of recesses defining an even number of ribs with overhung slots. The method comprises placing a fixture over a smaller diameter bearing section of the rotor abutting one end of the center section. The axial end of the fixture adjacent the center section has a configuration matching the center section including ribs and overhung slots. Next, the magnets in magnet carriers and the C-shaped lamination stacks are slid over the ribs

of the fixture. Next, a split compression ring having an inner diameter that is sized to ride over the outer diameter of the C-shaped lamination stacks assembled on the ribs is placed over the row of assembled magnets and lamination stacks and joined so that the split compression ring compresses the C-shaped lamination stacks sufficiently to provide a riding clearance between the C-shaped lamination stacks and the overhung slots. Next, the assembled row of magnets in magnet carriers and C-shaped lamination stacks are slid onto the rotor. Finally, the compression ring is removed leaving an assembled row of magnets in magnet carriers and C-shaped lamination stacks in place on the rotor.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Further features and other objects and advantages will become clear from the following detailed description made with reference to the drawings in which:

[0006] Fig. 1 shows a single row of magnet carriers and C-shaped laminations assembled on the temporary rotor fixture abutting one end of the rotor shaft;

[0007] Fig 2 shows the split compression ring placed over the single row of magnet carriers and C-shaped laminations;

[0008] Fig. 3 shows the single row of magnet carriers and C-shaped laminations after being slid onto the rotor shaft and the split compression ring removed;

[0009] Fig. 4 is a perspective view of the temporary rotor fixture for assembling a row of magnet carriers and C-shaped laminations off the rotor shaft;

[0010] Fig. 5 is a perspective view of the split compression ring with the adjustment screws indicated;

[0011] Fig. 6 is an end view of a row of magnet carriers and C-shaped laminations assembled on the temporary rotor fixture and with the split compression ring in place to remove pressure on the overhung portions of the ribs; and

[0012] Fig. 7 is a perspective view in section of the assembled permanent magnet rotor.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0013] Referring to Fig. 7, there is shown an assembled permanent magnet rotor shaft according to U.S. Patent No. 6,933,645. The details of the magnet carriers and the C-shaped lamination stacks are set forth in that patent which is incorporated herein by reference. One of the challenges in assembling a permanent magnet rotor is to safely and securely assemble the rotor components on the shaft. The rotor is designed with tight tolerances and clearances. One of the major risks is gouging the shaft when sliding parts into position.

[0014] Referring to Fig. 7, the shaft 10 comprises the foundation of the permanent magnet rotor. The shaft 10 is made of non-magnetic, high-strength material, such as nickel cobalt alloy. The shaft 10 has an interrupted cylindrical surface defined relative to the rotational axis of the rotor. At each end of the shaft, provisions are made for bearings 12. The bearings 12 establish the rotational axis of the rotor. The shaft 10 has an even number of substantially identical recessed slots 13. The slots 13 define substantially identical generally T-shaped ribs 11 with overhung dovetail surfaces 15 adjacent the slots. The magnets 19 are positioned within the slots held by a cradle or carrier 18.

[0015] A plurality of generally C-shaped lamination stacks 17 comprised of magnetic, high-permeability material, such as electrical steel, surrounds the T-shaped ribs 11 as is clearly seen in Fig. 7. The stacks are made up of individual sheets positioned perpendicular to the axis of rotation of the shaft. The sheets have edges that abut the overhung dovetail surfaces of the ribs. In this way, the C-shaped lamination stacks are mechanically secured to resist centrifugal forces when the shaft rotates.

[0016] A plurality of non-magnetic cradles 18 hold the permanent magnets in position in each slot. Each cradle 18 carries laminated permanent magnets 19. Each cradle has a top wall and a bottom wall. These walls generally lie in the axial and circumferential directions when the cradle is installed in a slot on the rotor. The top wall abuts the magnets and resists the centrifugal force tending to throw out the magnets when the rotor rotates. The cradles are formed of lightweight, non-magnetic structural material, such as titanium. The cradles have axial end walls joined to the top and bottom walls. The bottom wall secures the axial end walls so that they do not collapse on the magnets when the top wall is urged radially outward at high rotation speeds. The axial end walls have edges that are configured to abut the overhung dovetail surface 15 of the ribs. The space between the axial end walls of the cradles is large enough to span the axial length of the magnets and also the axial length of the laminated stacks. Preferably, the axial length of the magnets and the laminated stacks is identical. The cradles are secured against centrifugal force by the engagement of the dovetail surfaces on the cradles and the overhung ribs. It is important to note that centrifugal force exerted by the cradle is applied directly to the ribs.

[0017] The assembly rotor, as shown in Fig. 7, has multiple stages (circumferential rows of magnets and C-shaped lamination stacks forming ring-shaped units) which are slid axially into position. As stated, the rotor assembly comprises a non-magnetic, cylindrical shaft 10 having an axis of rotation and a generally cylindrical surface. An even number of recessed slots define an even number of ribs. The ribs have an overhung configuration. The overhung

surfaces after assembly of the magnet carriers and C-shaped lamination stacks restrain the magnet carriers and C-shaped lamination stacks from moving radially outward from the axis of the rotor during rotation of the rotor.

[0018] Once assembled, the permanent magnets attempt to draw the C-shaped lamination stacks radially inward. This causes the components of a row to push radially outward as a reaction to the forces generated by the permanent magnets. This, in turn, results in a force across the overhung surfaces 15. Forcing the stage axially along the shaft under these conditions can result in scoring or gouging of the ribs.

[0019] To overcome this problem, the stages are first assembled on a temporary rotor fixture 30 that at one axial end has a configuration substantially identical to the rotor. The temporary rotor fixture slides over the bearing 12 at one axial end of the rotor 10 and abuts the end of the ribs. The rotor fixture is rotated so that ribs 31 on the rotor fixture align with the ribs 11 on the rotor.

[0020] The magnet carriers 18 are slid onto the rotor fixture and axially positioned with one edge of each magnet carrier engaging the overhung portion of ribs on the rotor fixture. The C-shaped lamination stacks 17 are then placed in contact with the C-shaped lamination stacks held by the magnet carriers. Fig. 1 shows the assembled row on the rotor fixture.

[0021] The split compression ring 40 is then secured over the assembled row as shown in Figs. 2 and 6. The screws 41 are then turned in to compress the stage and remove pressure from the overhung surfaces of the ribs on the rotor fixture. The entire stage is then moved axially over the rotor into position as shown at Fig. 3.

[0022] The split compression ring 40 forms a clamp. The clamp is made so that it can apply pressure to push the components of the stage off the overhung surface of the ribs. The clearances of the components are set in a way that when components are pushed inward toward the center of the shaft, the components have acceptable clearances for sliding along the shaft.

[0023] After the stage is in position, the split compression ring or clamp 40 is removed allowing the components of the row to expand into the final assembly position. The process is then repeated to place an additional row in place on the rotor.

[0024] Referring to Fig. 4, the rotor fixture is shown in more detail. At one axial end, the fixture has ribs corresponding to the ribs on the rotor. The rotor fixture is formed of a non-magnetic material.

[0025] Referring to Fig. 5, the split compression ring 40 is formed of a non-magnetic material, such as 300 Series stainless steel. Adjustment screws 41 have swivel heads at the

end near the inner diameter of the compression ring so as to conform to the inner diameter when tightened in place. Thus, pressure can be applied to each component of the stage individually. This is accomplished by the adjustment screws aligned radially with each component. Preferably, a sleeve of soft material, such as Teflon®, is provided between the clamp and the rotor components so that the spit compression ring or clamp does not damage the components of the stage.

**[0026]** Having thus described my invention with the detail and particularity required by the Patent Laws, what is desired protected by Letters Patent is set forth in the following claims.

## THE INVENTION CLAIMED IS

1. Apparatus for assembling a permanent magnet rotor, the rotor being comprised of a non-magnetic cylindrical shaft having a larger diameter central axial section and two smaller diameter bearing sections, the central section having an even number of recesses defining an even number of ribs with overhung slots, said apparatus comprising a fixture configured to slide over a smaller diameter bearing section of the rotor and abutting one end of the center section, the axial end of the fixture adjacent the center section having a configuration matching the center section including ribs and overhung slots whereby magnets in magnet carriers and C-shaped lamination stacks can be assembled over the ribs of the fixture, said apparatus further comprising a split compression ring having an inner diameter that is sized to ride over the outer diameter of the C-shaped lamination stacks and means for joining the split compression ring to compress the C-shaped lamination stacks sufficiently to provide a riding clearance between the C-shaped lamination stacks and the overhung slots.

2. A method for assembling a permanent magnet rotor, the rotor being comprised of a non-magnetic cylindrical shaft having a larger diameter central axial section and two smaller diameter bearing sections, the central section having an even number of recesses defining an even number of ribs with overhung slots, said method comprising the steps of:

a) placing a fixture over a smaller diameter bearing section of the rotor and abutting one end of the center section, the axial end of the fixture adjacent the center section having a configuration matching the center section including ribs and overhung slots;


b) sliding the magnets in magnet carriers and the C-shaped lamination stacks over the ribs of the fixture to assemble a row;

c) placing a split compression ring over the outer diameter of the C-shaped lamination stacks assembled on the ribs and joining the split compression ring to compress the C-shaped lamination stacks sufficiently to provide a riding clearance between the C-shaped lamination stacks and the overhung slots;


d) sliding the compression ring and the assembled row of magnets in magnet carriers and C-shaped lamination stacks onto the rotor; and

e) removing the compression ring leaving an assembled row of magnets in magnet carriers and C-shaped lamination stacks in place on the rotor.


1 / 7



2/7



3/7



4/7




FIG.4

5/7




FIG. 5

6/7





FIG. 6

7/7

FIG. 7



PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference 5039-073585	<b>FOR FURTHER ACTION</b> see Form PCT/ISA/220 as well as, where applicable, item 5 below.	
International application No. PCT/US2007/080790	International filing date (day/month/year) 09/10/2007	(Earliest) Priority Date (day/month/year) 10/10/2006
Applicant  CANOPY TECHNOLOGIES, LLC		

This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This international search report consists of a total of 3 sheets.

It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

a. With regard to the language, the international search was carried out on the basis of:

the international application in the language in which it was filed  
 a translation of the international application into \_\_\_\_\_, which is the language of a translation furnished for the purposes of international search (Rules 12.3(a) and 23.1(b))

b.  This international search report has been established taking into account the **rectification of an obvious mistake** authorized by or notified to this Authority under Rule 91 (Rule 43.6bis(a)).

c.  With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, see Box No. I.

2.  **Certain claims were found unsearchable** (See Box No. II)

3.  **Unity of invention is lacking** (see Box No III)

4. With regard to the title,

the text is approved as submitted by the applicant  
 the text has been established by this Authority to read as follows:

5. With regard to the abstract,

the text is approved as submitted by the applicant  
 the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box No. IV. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority

6. With regard to the drawings,

a. the figure of the **drawings** to be published with the abstract is Figure No. 2

as suggested by the applicant  
 as selected by this Authority, because the applicant failed to suggest a figure  
 as selected by this Authority, because this figure better characterizes the invention

b.  none of the figures is to be published with the abstract

## INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2007/080790

A. CLASSIFICATION OF SUBJECT MATTER  
INV. H02K1/27 H02K15/03

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2004/245884 A1 (SMITH JAMES S [US]) 9 December 2004 (2004-12-09) paragraph [0033] - paragraph [0044]; figures 1-9 -----	1,2
A	US 3 818 586 A (HARKNESS J ET AL) 25 June 1974 (1974-06-25) column 4, line 22 - column 4, line 29; figures 3,4 -----	1

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the International filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

13 February 2008

26/02/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kugler, Daniel

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No  
PCT/US2007/080790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2004245884	A1 09-12-2004	NONE	
US 3818586	A 25-06-1974	NONE	