



US00RE43939E

(19) **United States**
(12) **Reissued Patent**
Sapiejewski et al.

(10) **Patent Number:** **US RE43,939 E**
(45) **Date of Reissued Patent:** **Jan. 22, 2013**

(54) **HEADSET NOISE REDUCING**
(75) Inventors: **Roman Sapiejewski**, Boston, MA (US);
Michael J. Monahan, Southborough,
MA (US)
(73) Assignee: **Bose Corporation**, Framingham, MA
(US)

4,572,324 A 2/1986 Fidi et al.
4,644,581 A 2/1987 Sapiejewski
4,669,129 A 6/1987 Chance et al.
4,809,811 A 3/1989 Gorike
4,893,695 A 1/1990 Tamura et al.
4,922,542 A 5/1990 Sapiejewski
5,020,163 A 6/1991 Aileo et al.
5,134,659 A 7/1992 Moseley
(Continued)

(21) Appl. No.: **10/754,094**
(22) Filed: **Jan. 8, 2004**

FOREIGN PATENT DOCUMENTS

CN 1101203 4/1995
(Continued)

Related U.S. Patent Documents

Reissue of:
(64) Patent No.: **6,597,792**
Issued: **Jul. 22, 2003**
Appl. No.: **09/353,425**
Filed: **Jul. 15, 1999**

OTHER PUBLICATIONS

Translation of DE003212519C1.*
Examination Report, dated Mar. 10, 2008, issued in corresponding
European Application Serial No. EP 05 113 070.6.
(Continued)

(51) **Int. Cl.**
H03B 29/00 (2006.01)
H04R 25/00 (2006.01)
H04R 1/10 (2006.01)
(52) **U.S. Cl.** **381/71.6; 381/372; 381/74; 381/371;**
381/71.1
(58) **Field of Classification Search** **381/71.6,**
381/74, 71.1, 312, 371, 372, 71.5; 181/129
See application file for complete search history.

Primary Examiner — Ping Lee
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**


[A headset has an earcup with front opening adjacent to an annular cushion formed with a plurality of openings facing the inside of the earcup that acoustically couples the earcup volume to the cushion volume. A driver is seated inside the earcup with a microphone adjacent to the driver. Active noise reducing circuitry interconnects the driver and microphone. An acoustic load that may comprise a wire mesh resistive cover and/or air mass adjacent the microphone is constructed and arranged to reduce the effect of resonances in the earcup volume.] *A headset has an earcup with front opening adjacent to an annular cushion. A driver is seated inside the earcup with a microphone adjacent to the driver. Active noise reducing circuitry interconnects the driver and microphone. An acoustic load is constructed and arranged to reduce the effect of resonances in the earcup volume.*

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,498,727 A 6/1924 Haskel
1,514,152 A 11/1924 Gernsback
2,622,159 A 12/1952 Herman
2,714,134 A 7/1955 Touger et al.
3,644,939 A 2/1972 Beguin
3,645,354 A 2/1972 Kliewer
4,005,267 A * 1/1977 Gorike et al. 381/62
4,027,117 A 5/1977 Nakamura
4,455,675 A 6/1984 Bose et al.
4,529,058 A 7/1985 Emery

28 Claims, 4 Drawing Sheets



U.S. PATENT DOCUMENTS

5,182,774	A	1/1993	Bourk	
5,208,868	A	5/1993	Sapiejewski	
5,343,523	A	8/1994	Bartlett et al.	
5,729,605	A	3/1998	Bobisuthi et al.	
5,913,178	A *	6/1999	Olsson	455/575.3
5,970,160	A	10/1999	Nilsson et al.	
5,979,593	A *	11/1999	Rice et al.	381/71.5
6,831,984	B2	12/2004	Sapiejewski	
7,103,188	B1 *	9/2006	Jones	381/71.9

FOREIGN PATENT DOCUMENTS

CN	1213262	4/1999
DE	3212519	1/1991
DE	003212519	C1 * 1/1991
EP	0582404	A 2/1994
EP	0582404	A2 2/1994
EP	0688143	A 12/1995
EP	0688143	A2 12/1995
EP	0873040	10/1998
EP	0873040	A 10/1998
JP	62002798	1/1987
JP	62-061593	4/1987
JP	62061593	4/1987
JP	1196999	8/1989
JP	5036991	5/1993

OTHER PUBLICATIONS

Joint Notice of Prior Art for U.S. Patent 5,181,252 and U.S. Patent 6,597,792, United States International Trade Commission, Washington, D.C. 20436, Honorable Charles E. Bullock, Administrative Law Judge, Dated Apr. 21, 2008.

Public Version of Joint Motion to Terminate Investigation, dated Dec. 1, 2008.

Commission Notice of Determination, dated Jan. 2, 2009.

The extended European Search Report in corresponding European application, dated Apr. 9, 2009.

Translation of Japanese Office Action in counterpart Application No. 2000-214735 dated Nov. 17, 2009, 5 pages.

CN Office Action dated Mar. 24, 2010 for CN 200610084225.5.

CN Office Action dated Jun. 22, 2010 for CN 200410097494.6.

Japanese Patent Office Action in counterpart Application No. 2000-214735 dated Oct. 12, 2010, 4 pages.

Chinese Second Office Action in counterpart Application No. 200610084225.5 dated Oct. 9, 2010, 10 pages.

Notice of Allowance for the corresponding U.S. Appl. No. 12/576,699 dated Oct. 18, 2011.

Japanese Office Action in counterpart Application No. 2011-028867, dated Mar. 13, 2013, 3 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5

HEADSET NOISE REDUCING

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

The present invention relates in general to headset noise reducing and more particularly concerns novel apparatus and techniques for actively and/or passively reducing the noise perceived by the user of a headset.

BACKGROUND OF THE INVENTION

For background reference is made to U.S. Pat. Nos. 5,305,387, 5,208,868, 5,181,252, 4,989,271, 4,922,542, 4,644,581 and 4,455,675. Reference is also made to the Bose active noise-reducing headsets that are or were commercially available from Bose Corporation that are incorporated by reference herein.

It is an important object of the invention to provide improved noise-reducing for headsets.

BRIEF SUMMARY OF THE INVENTION

According to the invention, there is an earcup closed at the back away from the ear of a user and open at the front adjacent to the ear of the user. There is a driver inside the earcup. The earcup has a cushion that is seated in the front opening and formed with an ear opening for accommodating the ear of the user and an annular ridge surrounding the ear opening formed with a plurality of openings with adjacent openings typically spaced from each other by of the order of the width of an opening measured along the circumference of the ear opening with each opening having a radial width generally perpendicular to the circumference of the ear opening slightly less than the radial width of the annular ridge. For active noise reduction, there is a microphone adjacent to the driver coupled to the driver by electronic circuitry that furnishes active noise reduction and an acoustical load around the microphone and driver. The acoustic load may comprise a resistive mesh screen and/or air in a tube. Other features, objects and advantages will become apparent from the following detailed description when read in connection with the accompanying drawings in which:

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1A is a perspective view of a headset earcup assembly embodying the invention with the cushion shown in FIG. 1B according to the invention removed;

FIG. 2 is a sectional view of an earcup assembly according to the invention;

FIG. 3 is a pictorial perspective view into the earcup assembly with the microphone and resistive cover plate removed;

FIG. 4 is a perspective view showing the outside of an earcup; and

FIG. 5 is a block diagram of a system embodying the invention.

DETAILED DESCRIPTION

With reference now to the drawings and, more particularly, FIGS. 1A and 1B thereof, there is shown a perspective view of

an earcup assembly according to the invention with the perforated cushion of FIG. 1B removed. Earcup 11 is closed at the rear away from the ear of a user and supports driver 12 and a closely adjacent microphone (not seen in FIG. 1A) that is covered by resistive mesh screen 13 typically formed with an opening 13A exposing the microphone and comprising an acoustical load. Electronic circuitry interconnects the microphone and driver 12 to provide active noise reduction and exchange audio signals through cable 14 for transduction by driver 12 into desired sound signal for the wearing user and by the microphone into a noise-reducing audio signal.

Referring also to FIG. 1B, cushion 15 covers the exposed front opening adjacent to the ear of the wearing user and is formed with an ear opening 15A for accommodating the ear of the wearing user and an annular ridge 16 surrounding ear opening 15A that is formed with a plurality of openings, such as 16A, through which an annular ring of foam is visible that rests against driver 12 when assembled.

Referring to FIG. 2, there is shown a diagrammatic sectional view through an assembled earcup. Driver 12 is seated in earcup 11 with driver plate 12A extending rearward from a lip 11A of earcup 11 to a ridge 11B with microphone 17 closely adjacent to driver 12 and covered by wire mesh resistive cover 13. Cushion 15 covers the front opening of earcup 11 and includes foam 15B.

Referring to FIG. 3, there is shown a pictorial perspective view into earcup 11 with cushion 15, microphone 17 and wire mesh resistive cover 13 removed to illustrate certain structural details. Earcup 11 is formed with a cable entry 11C for accommodating cable 14 for receiving audio signals for transduction by driver 12 and intercoupling external electronic circuitry with the driver and microphone. Driver plate 12A carries resistive cover holders 21A and 21B for supporting the wire mesh resistive cover 13. Microphone holder 22 extends from the rear wall of earcup 11 for supporting microphone 17 and encloses air that comprises acoustical loading. Driver plate mounting bosses 12B and 12C furnish a means for attaching driver plate 12A to earcup 11. Driver 12 divides earcup 11 into a front volume typically about 50 CC adjacent to the front opening and a rear volume typically about 15 CC enclosed by the closed end of earcup 11.

Referring to FIG. 4, there is shown a rear view of earcup 11 showing mass port 11C and resistive port 11D covered by a wire mesh.

With reference now to the drawing and more particularly FIG. 5 thereof, there is shown a block diagram illustrating the logical arrangement of a system incorporating the invention corresponding substantially to FIG. 1 of the aforesaid '881 patent. A signal combiner 30 algebraically combines the signal desired to be reproduced by the earphone on input terminal 24 with a feedback signal provided by microphone preamplifier 35. Signal combiner 30 provides the combined signal to compressor 31 which limits the level of the high level signals. The output of compressor 31 is applied to compensator 31A. Compensator 31A includes compensation circuits to insure that the open loop gain meets the Nyquist stability criteria, so that the system will not oscillate when the loop is closed. The system shown is duplicated once each for the left and right ears.

Power amplifier 31 amplifies the signal from compensator 31A and energizes earphone driver 2 to provide an acoustical signal in the front cavity that is combined with an outside noise signal that enters the front cavity from a region represented as acoustical input terminal 25 to produce a combined acoustic pressure signal in the front cavity represented as a circle 36 to provide a combined acoustic pressure signal

applied to and transduced by microphone 7. Microphone amplifier 35 amplifies the transduced signal and delivers it to signal combiner 30.

Having described the structural arrangement of an embodiment of the invention, principles of operation will be described. A problem in active noise-reducing circumaural headphones arises from earcup resonances causing a rough acoustic response that is a function of the head of the user, making electronic compensation difficult.

One approach for smoothing the acoustic response is to place damping material, typically highly absorptive foam, around the walls of the earcup. This approach typically requires a significant thickness of foam to provide sufficient damping and requires earcups of relatively large volume to accommodate the thick foam. Furthermore, the damping of the highly absorptive foam is a sensitive function of the physical dimensions of the foam and atmospheric conditions, causing inconsistent acoustical response.

Resonance in the earcup may produce instability by causing oscillation at certain frequencies that typically limits the amount of feedback for active noise reduction. By acoustically loading the microphone and driver with the wire mesh resistive cover 13 and/or the enclosed air, resonances are significantly reduced, allowing increased gain in the feedback loop and significantly improved active noise reduction in an earcup of relatively small volume.

By forming openings in annular ridge 16 of cushion 15 to expose foam material 15B, the effective volume of the earcup is significantly increased to embrace the volume occupied by cushion 15 and thereby increase passive attenuation and provides additional damping to help smooth the audio response at the ear and control stability with the headset off the head.

The invention has a number of advantages. Cup size is relatively small, yet there is considerable effective volume with the additional effective volume afforded by cushion 15 accessed through openings such as 16A. The effect of resonances inside earcup 11 is significantly reduced with wire mesh resistive cover 13 and/or the enclosed air, thereby allowing a significant increase in loop gain of the active noise reducing system.

It is evident that those skilled in the art may now make numerous uses and modifications of and departures from the specific apparatus and techniques herein disclosed without departing from the inventive concepts. Consequently, the invention is to be construed as embracing each and every novel feature and novel combination of features present in or possessed by the apparatus and techniques herein disclosed and limited solely by the spirit and scope of the appended claims.

What is claimed is:

1. A headset comprising,
 - an earcup having a front opening adapted to be adjacent to the ear of the user,
 - a driver inside said earcup,
 - a cushion around the periphery of said front opening formed with an ear opening constructed and arranged to accommodate the ear of a user and formed with a plurality of openings around said opening constructed and arranged to acoustically add the volume of said cushion to the volume of said earcup and enhance passive attenuation.]
2. A headset [in accordance with claim 1 and further] comprising,
 - an earcup having a front opening adapted to be adjacent to the ear of the user, a driver inside said earcup, a cushion around the periphery of said front opening formed with an ear opening constructed and arranged to accommo-

date the ear of a user and formed with a plurality of openings around said opening constructed and arranged to acoustically add the volume of said cushion to the volume of said ear cup and enhance passive attenuation,

a microphone inside said earcup adjacent to said driver, and active noise reducing circuitry intercoupling said microphone and said driver constructed and arranged to provide active noise reduction,

whereby said cushion with said plurality of openings is further constructed and arranged to furnish additional damping to help smooth the audio response at the ear of a user and control stability with the headset off the head.

3. A headset in accordance with claim 2 and further comprising,

- an acoustic load in close proximity to said microphone constructed and arranged to reduce the effects of resonances in said earcup.

4. A headset in accordance with claim 3 wherein said acoustic load comprises a wire mesh resistive cover.

5. A headset in accordance with claim 4 wherein said wire mesh resistive cover is formed with an opening near said microphone.

6. A headset in accordance with claim 4 wherein said wire mesh resistive cover coacts with said driver to substantially enclose said microphone.

7. The headset in accordance with claim 2, wherein said cushion comprises foam.

8. The headset in accordance with claim 7, wherein said foam is visible through the plurality of openings.

9. The headset in accordance with claim 2, wherein said cushion is formed with a plurality of discrete openings having substantially the same area.

10. The headset in accordance with claim 2, wherein said cushion comprises an annular ridge surrounding said ear opening.

11. The headset in accordance with claim 10 wherein said plurality of openings are formed along the circumferential length of said annular ridge.

12. The headset in accordance with claim 11 wherein said plurality of openings are equidistantly spaced along the circumferential length of the annular ridge.

13. The headset in accordance with claim 2 further comprising a mass port extending through a closed end of said earcup.

14. The headset in accordance with claim 13 further comprising a resistive port extending through said closed end of said earcup.

15. The headset in accordance with claim 2 further comprising a resistive port extending through a closed end of the earcup.

16. The headset in accordance with claim 14 wherein said resistive port is covered by a wire mesh.

17. The headset in accordance with claim 2 further comprising a driver plate to support said driver.

18. The headset in accordance with claim 17 wherein said driver plate is positioned and arranged to substantially divide said earcup into a front volume adjacent said front opening and a rear volume enclosed by a closed end of the earcup.

19. The headset in accordance with claim 18 wherein said front volume is substantially larger than said rear volume.

20. A headset comprising,

- an earcup having a front opening adapted to be adjacent to the ear of the user, a driver inside said earcup, a cushion around the periphery of said front opening formed with

5

an ear opening constructed and arranged to accommodate the ear of a user and formed with a plurality of openings around said opening constructed and arranged to acoustically add the volume of said cushion to the volume of said ear cup and enhance passive attenuation, a microphone inside said earcup adjacent to said driver, and active noise reducing circuitry intercoupling said microphone and said driver constructed and arranged to provide active noise reduction, whereby said cushion with said plurality of openings is further constructed and arranged to furnish additional damping to help smooth the audio response at the ear of a user and control stability with the headset off the head, a driver plate to support said driver, wherein said driver plate is positioned and arranged to substantially divide said earcup into a front volume adjacent said front opening and a rear volume enclosed by a closed end of the earcup, wherein said front volume is substantially larger than said rear volume, wherein said front volume is about 50 cubic centimeters.

21. A headset comprising, an earcup having a front opening adapted to be adjacent to the ear of the user, a driver inside said earcup, a cushion around the periphery of said front opening formed with an ear opening constructed and arranged to accommodate the ear of a user and formed with a plurality of openings around said opening constructed and arranged to acoustically add the volume of said cushion to the volume of said ear cup and enhance passive attenuation, a microphone inside said earcup adjacent to said driver, and active noise reducing circuitry intercoupling said microphone and said driver constructed and arranged to provide active noise reduction, whereby said cushion with said plurality of openings is further constructed and arranged to furnish additional damping to help smooth the audio response at the ear of a user and control stability with the headset off the head, a driver plate to support said driver, wherein said driver plate is positioned and arranged to substantially divide said earcup into a front volume adjacent said front opening and a rear volume enclosed by a closed end of the earcup, wherein said front volume is substantially larger than said rear volume, wherein said rear volume is about 15 cubic centimeters.

22. A headset comprising, an earcup, a driver inside said earcup, a microphone disposed between said driver and ear of the user,

6

feedback active noise reducing circuitry intercoupling said microphone and said driver constructed and arranged to provide active noise reduction, a wire mesh screen disposed between the ear of a user and said microphone to load at least one of said microphone and said driver and thereby improve stability of the headset as compared to an otherwise identical headset without such wire mesh screen, and a cushion extending around the periphery of said open end of earcup formed with openings through the cushion along an annular ring to acoustically add the volume of said cushion to the volume of said earcup and thereby improve the stability of said feedback active noise reducing circuitry when the headset is off of the head of the user, as compared to an otherwise identical headset without such cushion.

23. A headset comprising, an earcup having open end adapted to be adjacent to the ear of the user, a driver inside said earcup, a microphone inside said earcup adjacent to said driver, feedback active noise reducing circuitry intercoupling said microphone and said driver constructed and arranged to provide active noise reduction, and a cushion extending around the periphery of said open end of earcup formed with openings along an annular ring to acoustically add the volume of said cushion to the volume of said earcup and thereby improve the stability of said feedback active noise reducing circuitry when the headset is off of the head of the user, as compared to an otherwise identical headset without such cushion.

24. The headset in accordance with claim 23 wherein said cushion comprises foam.

25. The headset in accordance with claim 24 wherein said foam is substantially visible through said openings along said annular ring.

26. The headset in accordance with claim 25 wherein said openings area plurality of discrete openings each having substantially the same area.

27. The headset in accordance with claim 23 wherein said plurality of openings are equidistantly spaced along the circumferential length of said annular ring.

28. The headset in accordance with claim 23 further comprising a mass port extending through a closed end of said earcup.

29. The headset in accordance with claim 23 further comprising a resistive port extending through a closed end of said earcup.

* * * * *