

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 February 2012 (09.02.2012)

PCT

(10) International Publication Number
WO 2012/018656 A2

(51) International Patent Classification:
B01D 17/05 (2006.01) **C10G 33/04** (2006.01)
C07D 309/04 (2006.01)

(21) International Application Number:
PCT/US2011/045513

(22) International Filing Date:
27 July 2011 (27.07.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/848,514 2 August 2010 (02.08.2010) US

(71) Applicant (for all designated States except US): **MO-
MENTIVE PERFORMANCE MATERIALS INC.**
[US/US]; 22 Corporate Woods Blvd., 2nd Floor, Albany,
NY 12211 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KOCZO, Kalman**
[US/US]; 241 Parkside Drive, Suffern, NY 10901 (US).
FALK, Benjamin [US/US]; 3308 Old Crompond Road,
Yorktown Heights, NY 10598 (US). **PALUMBO, Anto-
nio** [IT/IT]; Via Teofane No 3, I-96400 Siracusa (IT).

(74) Agent: **WHEELLOCK, Kenneth, S.**; Momenive Perfor-
mance Materials Inc., One Plastics Avenue, Pittsfield,
MA 01201 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii))

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: COMPOSITIONS AND METHODS FOR SEPARATING EMULSIONS USING THE SAME

(57) Abstract: The present invention provides for a demulsifying composition comprising a blend of a) an emulsion; and b) a demulsifying-effective amount of a silicon containing co-polymer. The present invention also provides for a method for separating emulsions using the demulsifying composition discussed.



WO 2012/018656 A2

- 1 -

**COMPOSITIONS AND METHODS FOR SEPARATING
EMULSIONS USING THE SAME**

FIELD OF THE INVENTION

5 **[0001]** The present invention relates to silicon containing copolymers, demulsifying compositions comprising the silicon containing copolymers, processes for their preparation, and their use as demulsifying agents.

BACKGROUND OF THE INVENTION

10 **[0002]** It is well known that emulsions often cause difficulties in industrial processing operations. For this reason, the emulsified components need to be separated. Often, one or more chemicals, known as demulsifiers, are used for this purpose.


15 **[0003]** For example, during crude oil processing, it is commonplace for water to become emulsified in the oil. The emulsified water is problematic from several standpoints, most notably as a corrosive to pipelines and as a disruptor to oil distillation processes. The resulting water-in-oil emulsion is typically highly stable as a result of natural surfactants (e.g., naphthenic acids, asphaltenes, and resins) in the crude oil.

20 **[0004]** To disrupt the stabilized water-in-oil emulsions in crude oil, specialized organic and silicone demulsifiers have been used. See, for example, U.S. Patent Nos. 5,004,559, 4,183,820, 3,677,962, and British Patent No. GB 1439793, all of which disclose the use of polyoxyalkylene-polysiloxane copolymers as demulsifiers in crude oil or petroleum processing. However, there remains a need for demulsifiers capable of breaking and/or separating such emulsions more effectively.

SUMMARY OF THE INVENTION

25 **[0005]** A demulsifying composition is provided herein, said demulsifying composition comprising a blend of (a) an emulsion; and (b) a demulsifying-effective amount of a silicon containing co-polymer comprising at least one compound having the following formula:

- 2 -



where R^2 is a group defined as $M_f D_g T_h Q_i R_j^6$ with

$$M = R^7 R^8 R^9 Si Z_{1/2},$$

$$D = R^{10} R^{11} Si Z_{2/2},$$

$$5 \quad T = R^{12} Si Z_{3/2},$$

$$Q = Si Z_{4/2},$$

$$R^6 = -(CH_2)_{1/2} (R^{13})_k (CH_2)_{1/2} -,$$

wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having 1 to about 40 carbon atoms,

R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having from about 1 to about 40 carbon atoms,

15 Z is O or CH_2 group subject to the limitation that the molecule contains even number of $O_{1/2}$ and even number of $(CH_2)_{1/2}$ groups and they both are all paired in the molecule,

R^3 is a trivalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having 1 to about 40 carbon atoms,

20 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals optionally containing heteroatoms and hydroxyl groups having 1 to about 20 carbon atoms,

R^4 is a divalent, linear or branched unsaturated or saturated hydrocarbon radical containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

25 R^{13} is oxygen or divalent linear or branched unsaturated or saturated hydrocarbon radicals containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

- 3 -

R^{14} is a monovalent, linear or branched unsaturated or saturated hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having 1 to about 20 carbon atoms,

subscripts a, b, c, d and e are zero or positive subject to the limitation

5 $3 < a+b+c+d+e < \text{about } 1000$,

subscripts d+e > 1,

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f+g+h+i+j < \text{about } 300$, and,

subscript k is either 0 or 1.

10

DETAILED DESCRIPTION OF THE INVENTION

[0006] In the specification and claims herein, the following terms and expressions are to be understood as indicated.

15 **[0007]** The expression "hydrocarbon radicals" means any hydrocarbon group from which one or more hydrogen atoms have been removed and is inclusive of alkyl, alkenyl, alkynyl, cyclic alkyl, cyclic alkenyl, cyclic alkynyl, aryl, aralkyl and arenyl, and optionally it is substituted with oxygen, nitrogen, or sulfur.

[0008] The term "alkyl" means any monovalent, saturated, straight, branched or
20 cyclic hydrocarbon group; the term "alkenyl" means any monovalent straight, branched, or cyclic hydrocarbon group containing one or more carbon-carbon double bonds where the site of attachment of the group can be either at a carbon-carbon double bond or elsewhere therein; and, the term "alkynyl" means any monovalent straight, branched, or cyclic
hydrocarbon group containing one or more carbon-carbon triple bonds and, optionally, one
25 or more carbon-carbon double bonds, where the site of attachment of the group can be either at a carbon-carbon triple bond, a carbon-carbon double bond or elsewhere therein. Examples of alkyls include methyl, ethyl, propyl and isobutyl. Examples of alkenyls include vinyl, propenyl, allyl, methallyl, ethylidenyl norbornane, ethylidene norbornyl, ethylidenyl norbornene and ethylidene norbornenyl. Examples of alkynyls include
30 acetylenyl, propargyl and methylacetylenyl.

- 4 -

[0009] Other than in the working examples or where otherwise indicated, all numbers expressing amounts of materials, reaction conditions, time durations, quantified properties of materials, and so forth, stated in the specification and claims are to be understood as being modified in all instances by the term "about."

5 **[00010]** It will be understood that any numerical range recited herein includes all sub-ranges within that range and any combination of the various endpoints of such ranges or sub-ranges.

[00011] It will be further understood that any compound, material or substance which is expressly or implicitly disclosed in the specification and/or recited in a claim as
10 belonging to a group of structurally, compositionally and/or functionally related compounds, materials or substances includes individual representatives of the group and all combinations thereof.

[00012] Reference is made to substances, components, or ingredients in existence at the time just before first contacted, formed *in situ*, blended, or mixed with one or more
15 other substances, components, or ingredients in accordance with the present disclosure. A substance, component or ingredient identified as a reaction product, resulting mixture, or the like may gain an identity, property, or character through a chemical reaction or transformation during the course of contacting, *in situ* formation, blending, or mixing operation if conducted in accordance with this disclosure with the application of common
20 sense and the ordinary skill of one in the relevant art (e.g., chemist). The transformation of chemical reactants or starting materials to chemical products or final materials is a continually evolving process, independent of the speed at which it occurs. Accordingly, as such a transformative process is in progress there may be a mix of starting and final materials, as well as intermediate species that may be, depending on their kinetic lifetime,
25 easy or difficult to detect with current analytical techniques known to those of ordinary skill in the art.

[00013] Reactants and components referred to by chemical name or formula in the specification or claims hereof, whether referred to in the singular or plural, may be identified as they exist prior to coming into contact with another substance referred to by
30 chemical name or chemical type (e.g., another reactant or a solvent). Preliminary and/or

- 5 -

transitional chemical changes, transformations, or reactions, if any, that take place in the resulting mixture, solution, or reaction medium may be identified as intermediate species, master batches, and the like, and may have utility distinct from the utility of the reaction product or final material. Other subsequent changes, transformations, or reactions may
5 result from bringing the specified reactants and/or components together under the conditions called for pursuant to this disclosure. In these other subsequent changes, transformations, or reactions the reactants, ingredients, or the components to be brought together may identify or indicate the reaction product or final material.

[00014] Other optional ingredients may be added in the compositions of the present
10 invention including coupling agents, e.g., silane coupling agents, curing aids, e.g., including activators, retarders and accelerators, processing additives such as oils, plasticizers, tackifying resins, silicas, other fillers, pigments, fatty acids, zinc oxide, waxes, antioxidants and antiozonants, peptizing agents, reinforcing materials such as, for example, carbon black; wetting agents, anticorrosion additives, hydrogen sulfide
15 scavengers, biocides and so forth. Such additives are selected based upon the intended use and such selection is within the knowledge of one of skill in the art, as are the required amounts of such additives known to one of skill in the art.

[00015] In describing the products of the instant invention as a reaction product of
initial materials reference is made to the initial species recited and it is to be noted that
20 additional materials may be added to the initial mixture of synthetic precursors. These additional materials may be reactive or non-reactive. The defining characteristic of the instant invention is that the reaction product is obtained from the reaction of at least the components listed as disclosed. Non-reactive components may be added to the reaction mixture as diluents or to impart additional properties unrelated to the properties of the
25 composition prepared as a reaction product. Thus for example finely divided solids such as pigments may be dispersed into the reaction mixture, before during or after reaction to produce a reaction product composition that additionally comprises the non-reactive component, e.g. a pigment. Additional reactive components may also be added; such components may react with the initial reactants or they may react with the reaction
30 product; the phrase "reaction product" is intended to include those possibilities as well as including the addition of non-reactive components.

- 6 -

[00016] For the purpose of this disclosure, the term “immiscible” means that the two liquids have no or limited solubility in each other. Further, emulsions may also contain gases and solids. One of the immiscible liquids in an emulsion is generally polar, and often water based and the other liquid is generally non-polar, generally defined as an oil phase. The emulsion can be, for example, a water-in-oil, or an oil-in-water emulsion. In addition, it is also possible to prepare emulsions of emulsions and these are generally known as multiple emulsions, such as water-in-oil-in-water, oil-in-water-in-oil etc.

[00017] The emulsions of the present invention are those wherein the discontinuous (emulsified) component is in the form of droplets with droplet sizes in the range of about 0.1 microns up to about 500 microns and more, typically in the range of about 1 to about 100 microns. The emulsified component can be unstabilized, but is more typically stabilized by a stabilizing amount of a surfactant, a polymer and/or dispersed particulate solid.

[00018] The aqueous phase can be essentially pure water, or alternatively, water with varying amounts of solid (particulate) materials, minerals, salts or other chemicals.

[00019] The oil phase of the emulsion of the present invention is any hydrophobic phase substantially insoluble with the aqueous phase. For example, the oil phase can be composed of one or more hydrophobic chemicals, typically liquids, which individually or in combination are mainly insoluble in the aqueous phase. Such hydrophobic chemicals can be, for example, linear or branched, cyclic or acyclic, saturated or unsaturated, aliphatic or aromatic hydrocarbons. The hydrocarbons of the present invention typically contain at least about six carbon atoms and can be unsubstituted, or alternatively, substituted with one or more heteroatom- containing group (e.g., hydroxyl, amino, carboxyl, amide, anhydride, ester, or ether groups) as long as the hydrocarbons remain mainly insoluble with the aqueous phase.


[00020] Some examples of oil phases include, but are not limited to, halogenated or non-halogenated hydrocarbons having about 2 to about 30 carbons atoms, and more particularly, halogenated or non-halogenated ethenes, butadienes, pentanes, hexanes, heptanes, octanes, benzenes, toluene, ethylbenzenes, xylenes, naphthalene, cresols, naphtha, fats, lubrication oils, petroleum, gasoline, diesel fuel, crude oil, fuel oils, jet fuels,

- 7 -

heating oils, cleaning oils, vegetable oils, mineral oils, crude oil, gas condensates and tar or bitumen derivatives.

[00021] According to the invention, a demulsifying composition is provided comprising a blend of

- 5 a. an emulsion; and
- b. a demulsifying-effective amount of a silicon containing co-polymer comprising at least one compound having the following molecular formula:



- 10 where R^2 is a group defined as

$M_fD_gT_hQ_iR^6_j$ with

$M = R^7R^8R^9SiZ_{1/2}$;

$D = R^{10}R^{11}SiZ_{2/2}$;

$T = R^{12}SiZ_{3/2}$;

- 15 $Q = SiZ_{4/2}$;

$R^6 = -(CH_2)_{1/2}(R^{13})_k(CH_2)_{1/2}-$;

wherein

- R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups from about 1 to about 40 carbon atoms, preferably from about 1 to about 30 carbon atoms, and more preferably from about 1 to about 20 carbon atoms;

- R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups from about 1 to about 40 carbon atoms, preferably from about 1 to about 30 carbon atoms, and more preferably from about 1 to about 20 carbon atoms;

- 8 -

Z is O or CH₂ group subject to the limitation that the molecule contains even number of O_{1/2} and even number of (CH₂)_{1/2} groups and they both are all paired in the molecule;

5 R³ is a trivalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups with 1-40 carbon atoms, preferably from about 1 to about 30 carbon atoms, and more preferably from about 1 to about 20 carbon atoms;

10 R⁷, R⁸, R⁹, R¹⁰, R¹¹ and R¹² are each independently selected from the group of OR¹⁴ or monovalent hydrocarbon radicals optionally containing heteroatoms and hydroxyl groups having from about 1 to about 20 carbon atoms, preferably from about 1 to about 15 carbon atoms and more preferably from about 1 to about 10 carbon atoms;

15 R⁴ is a divalent, linear or branched unsaturated or saturated hydrocarbon radical containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

20 R¹³ is oxygen or divalent linear or branched unsaturated or saturated hydrocarbon radicals containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

25 R¹⁴ is a monovalent, linear or branched unsaturated or saturated hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having from about 1 to about 20 carbon atoms, preferably from about 1 to about 15 carbon atoms and more preferably from about 1 to about 10 carbon atoms;

30 subscripts a, b, c, d and e are zero or positive subject to the limitation that $3 < a+b+c+d+e < 1000$, preferably $3 < a+b+c+d+e < 750$, and more preferably $3 < a+b+c+d+e < 500$;

subscripts d+e > 1;


- 9 -

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f+g+h+i+j < 300$, preferably $f+g+h+i+j < 200$, more preferably $f+g+h+i+j < 100$; and

subscript k is either 0 or 1.


5

[00022] Another aspect of the present invention is a silicon containing co-polymer composition (b) of the present invention comprising the compound having the following formula:



10


where R^2 is a group defined as



where


15

$$1 \leq l \leq 10;$$



[00023] Still another aspect of the present invention is a silicon containing co-polymer composition (b) of the present invention comprising the compound having the following formula:

20



where

R^2 is a group defined as $M_fD_gT_hQ_iR^6_j$ with

25

$$M = R^7R^8R^9Si(O)_{1/2};$$

$$T = R^{12}Si(O)_{2/2}(CH_2)_{1/2};$$

$$f=2;$$

$$g=0;$$


$$h=1;$$

30


$$i=0;$$

$$j=1; \text{ and}$$

- 10 -



[00024] Still another aspect of the present invention is a silicon containing co-polymer composition (b) of the present invention comprising the compound having the following formula:




where R^2 is a group defined as



10 where $1 \leq i \leq 10$.


[00025] Still another aspect of the present invention is a silicon containing co-polymer composition (b) of the present invention comprising the compound having the following formula:





wherein

R^2 is a group defined as $M_fD_gT_hQ_iR^6_j$ with

20



25 $h=1;$



30 $R^4 = -(CH_2)_{1/2}R^{13}(CH_2)_{1/2} - .$

Applications for Embodiments of the Invention

[00026] Emulsions can create problems in many industrial applications because the emulsions often do not separate into the liquid components for a prolonged time. In this case typically chemical additives, so-called demulsifying agents, are added to initiate, accelerate and complete the separation process. Demulsifying agents break emulsions and mixtures of polar solutes like water, and non-polar solvents like oil.

[00027] Demulsifiers are used to separate emulsions into polar (typically water) and non-polar liquids by incorporating the demulsifying agent into the emulsion. Demulsifiers are known in the art and usually comprise blends of surface-active chemicals. Typical organic demulsifier structures include, but not limited to sulfonates, sulfosuccinates, polyol esters, polyester amines, polymeric elastomers, sulfated polyol ester, oxyalkylated phenolic resins, alkylphenol alkoxyates, amine alkoxyates, quaternary amines, ethoxylated amines, bisamides, polyalkylene glycols, polymerized polyols, resin esters, polyether polyols, resin alkoxyates, modified polyols, polyimine alkoxyates and diepoxides.

[00028] The compositions of the present invention may be utilized in mining and petroleum processing applications, especially for demulsification. Using the compositions of the present invention for demulsifying is accomplished by

- i. incorporating a demulsifying-effective amount of at least one silicon containing co-polymer (b) of the present invention into an emulsion (a) including crude oil or the like;
- ii. allowing the emulsion to separate into at least two phases; and
- iii. separating said at least two phases from each other.

[00029] The compositions described in the present invention can be used for demulsifying alone or accompanied by additional silicone and/or organic demulsifiers and these components can be utilized in the form of a blend, a solution, a dispersion, or either an oil-in-water or a water-in-oil emulsion or microemulsion or the various demulsifying agents can be added separately. When applied in solution suitable solvents can be selected from linear or branched, cyclic or acyclic, saturated or unsaturated, aliphatic or aromatic

- 12 -

hydrocarbons, alcohol, ketones, esters, ethers and their blends or whatever solvent is commonly used in the particular application.

[00030] When the organic and/or silicone demulsifier is included, the weight ratio of the compositions of the present invention to the organic and silicone demulsifier is typically in the range of about 100:1 to about 1:1000, more typically in the range of about 5:1 to about 1:200.

[00031] The method of separating emulsions comprises the incorporation of a demulsifying-effective amount of demulsifier into the emulsion, allowing the emulsion to separate into at least two phases and separating these at least two phases from each other. The incorporation of the demulsifier into the emulsion to be separated can be achieved by any method known in the art for integrally mixing the demulsifier with the emulsion. The mixing procedure can use, for example, standard mixers, high-speed mixers or blenders, or shakers. The temperature can be unadjusted within room temperature limits (~20-40°C), or adjusted as required, for example, to 40-150°C for a suitable amount of time.

15

A. Mining and Petroleum Industry

[00032] A typical application of the compositions in the present invention is the separation of crude oil emulsions. During extraction and production of crude oil, water or brine gets emulsified into the crude oil yielding a water-in-oil emulsion, which can be unstabilized or stabilized by surface active materials, organic solids, such as asphaltenes and resins, or inorganic solids. This water-in-oil emulsion gives rise to several downstream problems; corrosion during refinery processes, disruption of distillation processes and greater energy requirement to pump the more viscous emulsion are to name a few. Thus, demulsifiers are extensively used in the petroleum industry to break water-in-oil and oil-in-water emulsions; and before transportation, refining or processing the water content of the crude oil has to be reduced to pipeline specification levels (typically less than 0.05-2%) and this is typically achieved by injecting demulsifiers into the well, into the crude oil stream, at the separation equipment or at any other suitable points.

[00033] The compositions of the present invention will cause improved demulsifying action in the Mining and Petroleum Industry, both in the oil field and

30

– 13 –

refineries, including, but not limited to desalters; bitumen extraction from oils sands (separating bitumen froth and solvent diluted bitumen emulsions); in steam assisted gravity drainage (SAGD); in enhanced oil recovery with surfactants and/or polymers or using supercritical carbon dioxide; in the separation of waste oils, slop oils, sludges, such as oily waste from desalters, waste water skimmings, refinery and petrochemical plant waste (tank bottom washes, coker drum waste, “dirty bleeds” etc.), steel and aluminum industrial waste, including synthetic lubes, high lithium grease, lube oil from rollers, metalworking fluid waste and paper plant waste.

[00034] The compositions of the present invention can be also used for demulsification and antifoaming in gas/oil/water separators.

[00035] Dehazing (demulsification) of lubrication oils and lubrication oil waste, such as automotive waste (motor oil etc.), bunker oil are also possible applications of the compositions in the present invention.

[00036] The compositions of the present invention can be also applied in emulsion preventors (“non-emulsifiers”) in drilling and well completion operations.

[00037] Another typical industrial use of the reaction products in the present invention is diesel fuel (including bio-diesel) dehazing when the demulsifier eliminates small amount of emulsified water from the diesel fuel and diesel fuel antifoaming.

[00038] The compositions of the present invention will improve ore recovery from mining operations. The inclusion of the present compositions to mining processes such as flocculation, separation, purification, concentration, leaching & chemical extraction improves the separation of minerals from their gangue.

[00039] Further applications of the present invention in oil and gas include asphaltene dispersants and drag reduction.

B. Water Processing

[00040] Compositions of the present invention are useful for applications involving commercial and industrial open recirculating cooling water towers, closed cooling water

- 14 -


systems, cooling water conduits, heat exchangers, condensers, once-through cooling systems, Pasteurizers, air washers, heat exchange systems, air conditioning/humidifiers/dehumidifiers, hydrostatic cookers, safety and/or fire water protection storage systems, water scrubbers, disposal wells, influent water systems, including filtration and
5 clarifiers, wastewater treatment, wastewater treatment tanks, conduits, filtration beds, digesters, clarifiers, holding ponds, settling lagoons, canals, odor control, ion exchange resin beds, membrane filtration, reverse osmosis, micro- and ultra-filtration, assisting in the removal of biofilms in cooling tower applications, heat exchangers and process water systems, and the like.

10

EXAMPLES

Preparation of Example 1:


[00041] A polyether with the average structure:



15 was combined with 1,1,1,3,5,5,5-heptamethyltrisiloxane (86.64 g) and sodium propionate (0.1g) in a 500 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 75 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to the exotherm and peaked at 99 °C at 30 minutes. The reaction was held at 85 °C
20 for an additional 1 hour. The reaction was determined to be complete by placing a sample in a digestion tube with a base. The absence of hydrogen evolution indicates complete consumption of Si-H groups. The product was transferred to a rotary evaporator and stripped at 120 °C with a nitrogen sparge at 50 mm Hg for 1 hour. Celite 545 (5g) was added and the product was pressure filtered through a 5-micron pressure filter. The
25 resulting product was an opaque yellow wax at room temperature.

Preparation of Example 2

[00042] A polyether with the average structure



- 15 -

was combined with 1,1,1,3,5,5,5-heptamethyltrisiloxane (86.64 g), isopropanol (200g) and sodium propionate (0.1g) in a 500 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 75 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to the exotherm and peaked at 86 °C at 15 minutes and began to reflux. The reaction was held at 85 °C for an additional 1 hour. 1 cc / g of Si-H was found so an additional Karstedt's catalyst (5ppm) was added. After an additional hour the reaction was determined to be complete. The product was transferred to a rotary evaporator and stripped at 120 °C with a nitrogen sparge at 20 mm Hg for 1 hour. Celite 545 (5g) was added and the product was pressure filtered through a 5-micron pressure filter. The resulting product was an opaque yellow wax at room temperature.

Preparation of Example 3

[00043] A polyether with the average structure

15 $\text{HO}(\text{CH}_2\text{CH}_2\text{O})_{120}(\text{CH}_2\text{CH}(\text{CH}_2\text{OCH}_2\text{CHCH}_2)\text{O})_{10}\text{H}$ (400 g)

was combined with 1,1,1,3,5,5,5-heptamethyltrisiloxane (129.88 g), isopropanol (132.33 g) and sodium propionate (0.1g) in a 500 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 80 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to the exotherm and peaked at 85 °C at 15 minutes and began to reflux. The reaction was held at 80 °C for an additional 24 hours. The reaction was determined to be complete. The product was transferred to a rotary evaporator and stripped at 90 °C with a nitrogen sparge at 20 mm Hg for 3 hour. Celite 545 (5g) was added and the product was pressure filtered through a 5-micron pressure filter. The resulting product was an opaque yellow wax at room temperature.

Preparation of Example 4

[00044] A polyether with the average structure


$\text{HO}(\text{CH}_2\text{CH}_2\text{O})_{31}(\text{CH}_2\text{CH}(\text{CH}_2\text{OCH}_2\text{CHCH}_2)\text{O})_{2.8}\text{H}$ (60.19 g)

- 16 -

was combined with 1-trimethylsilyl-2-dimethylsilylethane (16.04 g) in a 250 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 85 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to the exotherm and peaked at 99 °C at 10 minutes accompanied by a strong reflux. The reaction was held at 85 °C for an additional 2 hour. The reaction was determined to be complete by infrared spectroscopy. The product was transferred to a rotary evaporator and stripped at 90 °C at 50 mm Hg for 1 hour. The resulting product was an opaque yellow wax at room temperature.

Preparation of Example 5


[00045] A polyether with the average structure



was combined with 1-(2-dimethylsilyl-ethyl)-1,1,3,3,3-pentamethyl-disiloxane (23.46 g) and of isopropanol (16.23 g) in a 250 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 85 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to the exotherm and peaked at 99.9 °C at 10 minutes accompanied by a strong reflux. The reaction was held at 85 °C for an additional 2 hour. The reaction was determined to be complete by infrared spectroscopy. The product was transferred to a rotary evaporator and stripped at 90 °C at 50 mm Hg for 1 hour. The resulting product was an opaque yellow wax at room temperature.

Preparation of Example 6

[00046] A polyether with the average structure



was combined with di-*t*-butoxymethylsilane (79.95 g) and of isopropanol (66.54 g) in a 500 mL round bottom flask. The flask was equipped with an overhead stirrer, heating mantle, reflux condenser, and a temperature controller. The flask was heated to 85 °C and Karstedt's catalyst was added (10ppm based on Pt). The temperature began to rise due to

- 17 -

the exotherm and peaked at 90 °C at 10 minutes accompanied by a strong reflux. The reaction was held at 85 °C overnight. The reaction was determined to be complete by infrared spectroscopy. The product was transferred to a rotary evaporator and stripped at 90 °C at 50 mm Hg for 1 hour. The resulting product was an opaque yellow wax at room temperature.

Testing examples:

[00047] The following testing examples illustrate the use of copolymers in the present invention as demulsifying agents.

Testing method

[00048] Crude oil demulsifiers were tested in the Middle East with fresh crude oil samples from three different oil fields. Field 1 produced heavy crude oil with about 15 °API, Field 2 produced a medium crude oil with about 25 °API and Field 3 produced heavy crude oil with about 18-19 °API.

The following test method was used to evaluate demulsifiers:

[00049] First the water cut was determined by blending 50 part (vol.) of crude oil with 50 parts (vol.) of xylenes and with a highly efficient demulsifier in sufficient dose to completely separate the water from the crude. Then this blend was centrifuged for 5 min and the water cut was determined.

[00050] Crude oil emulsions were tested near the wells, making sure that the samples were not older than 1-2 days. After homogenizing the sample by hand shaking, one hundred ml of crude oil emulsion was carefully poured into prescription glass bottles, which had marks at 10 ml intervals.

[00051] The various demulsifiers were added and the bottles were hand shaken 100 times and then the samples were kept in a water bath at the required temperature for a period of time characteristic of the separators at the field. The amount of the separated water was determined at regular intervals. At the end of the separation process the bottles were removed from the bath and the appearance of the separated crude oil, the separated water phase and crude oil/water interface, respectively, were observed. Then a sample was

- 18 -

taken from the top 80% of the separated crude oil phase and the residual water content of this top cut was determined in two steps. First 50 parts (vol.) of crude oil sample was blended with 50 parts (vol.) of xylenes in a centrifuge tube (about 12.5ml). Then this blend was vigorously shaken by hand and centrifuged for 5 min and the amount of separated water ("free water", W1) was recorded. Then two drops of a highly efficient demulsifier (knockout dropper) was added, followed by vigorous shaking and centrifuged again, to determine the total water (W2) content. The difference between the total and free water content is the unresolved emulsion (ΔW) and it characterized the efficiency of a demulsifier. The mixed cut was analyzed after the separation, by carefully siphoning out the separated water phase from the bottom of the and then homogenizing the sample by hand-shaking. A sample from the homogenized crude was then analyzed by centrifugation as above.

Organic Demulsifiers:

15 **[00052]** Org 1, Org 2, Org 3, Org 4, Org 5 and Org 6 are designations for fully formulated organic demulsifier packages, which were developed for Field 1, Field 2 and Field 3 or typically used there.

TESTING EXAMPLE 1: Separation of crude oil emulsion from Field 1.

20 **[00053]** The original crude oil emulsion sample contained 24% free water and 38% total water. Table 1 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 1. Bottle tests with crude oil emulsion from Field 1, at 40 °C

#	Demulsifier	Dose	WATER DROP			TOP CUT (80%)			MIXED CUT		
		ppm	60 min	120	22	W1	W2	Δ W	W1	W2	Δ W
1	Org 1	100	4	13	21	7.0	19	12.0	7	19	12
2	Org 1+ Ex. 2	50+2	5	17	25	6.0	14	8.0	11	18	7
3	Org 2	100	3	9	19	1.0	13	12.0	1.6	22	20.4
4	Org 2 + Ex. 2	50+2	3	19	22	9.0	16	7.0	13	18	5
5	Org 3	100	8	11	17	1.0	16	15.0	9	23	14
6	Org 3 + Ex. 2	50+2	5	13	21	8.0	14	6.0	11	18	7
7	Org 4	100	5	16	28	2.0	15	13.0	5.2	18	12.6
8	Org 4 + Ex. 2	50+2	5	13	25	7.0	14	7.0	9	17	8
9	BLANK	0	0	0	5						

TESTING EXAMPLE 2: Separation of crude oil emulsion from Field 1.

- 5 [00054] The original crude oil emulsion sample contained 13% free water and 32% total water. Table 2 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

10 **Table 2. Bottle tests with crude oil emulsion from Field 1, at 60 °C**

#	Demulsifier	Dose	WATER DROP		TOP CUT (80%)			MIXED CUT		
		ppm	30 min	19 h	W1	W2	Δ W	W1	W2	Δ W
1	Org 5	70	1	16	1.8	4	2.2	2.2	4.8	2.6
2	Org 5+ Ex. 2	35+1.25	1	18	2.0	5.6	2.4	3.6	7	4.6
3	Org 3	70	2	14	0.0	9.5	9.5	2.8	9.5	6.7
4	Org 3+ Ex. 2	35+1.25	2	15	4.8	10	5.2	8	12	4
5	Org 4	70	tr	13	1.6	9	7.4	7	12	5
6	Org 4+ Ex. 2	35+1.25	2	16	2.8	10	7.2	5.8	9	3.2

tr: trace

TESTING EXAMPLE 3: Separation of crude oil emulsion from Field 1.

- [00055] The original crude oil emulsion sample contained 13% free water and 32% total water. Table 3 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was significantly reduced.
- 15

Table 3. Bottle tests with crude oil emulsion from Field 1, at 60 °C

#	Demulsifier	Dose	WATER DROP				TOP CUT (80%)			MIXED CUT		
		ppm	20 min	60 min	3 hours	20	W1	W2	Δ W	W1	W2	Δ W
1	Org 3	50	tr	13	19	27	0.0	10	10.0	1.2	4.4	3.2
2	Org 3	100	12	20	22	36	0.8	2	1.2	2.4	4	1.6
3	Org 3 + Ex. 2	50+1	7	20	21	33	1.2	5.2	4.0	3.2	6	2.8
4	Org 3 + Ex. 2	50+2	4	22	22	30	4.0	8	4.0	6	9	3
5	Org 3 + Ex. 2	60+3	13	23	24	32	4.4	8	3.6	6	8	2
6	Org 3 + Ex. 2	70+3.5	10	21	23	30	4.4	7	2.6	5.2	7	1.8
7	Org 3 + Ex. 2	50+1	2	22	23	35	0.4	3.2	2.8	2.4	4.8	2.4
8	Org 3 + Ex. 2	50+2	10	23	26	32	2.0	4.4	2.4	3.2	5.2	2
9	Org 1	50	2	15	20	27	0.8	12	11.2	2	14	12
10	Org 1	100	5	21	25	33	0.4	4.8	4.4	1.2	5.6	4.4
11	Org 6	50	1	16	20	22	0.0	13	13.0	2.4	13	10.6
12	Org 6	100	12	23	25	32	0.0	3.2	3.2	2.4	12	9.6
13	Org 2	50	2	10	16	28	0.0	8	8.0	0.6	11	10.4
14	Org 2	100	9	21	25	32	2.0	3.6	1.6	2.8	6	3.2

tr: trace

TESTING EXAMPLE 4: Separation of crude oil emulsion from Field 1.

- 5 **[00056]** The original crude oil emulsion sample contained 13% free water and 32% total water. Table 4 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was significantly reduced.

Table 4. Bottle tests with crude oil emulsion from Field 1, at 40 °C

#	Demulsifier	Dose	WATER DROP			TOP CUT (80%)			MIXED CUT		
		ppm	120 min	150 min	20 h	W1	W2	Δ W	W1	W2	Δ W
1	Org 3	50	tr	9	18	4.0	21	17.0	7	23	16
2	Org 3	100	6	11	22	6.0	22	14.0	10	22	12
3	Org 3 + Ex. 2	50+1	4	11	23	8.0	15	7.0	10	17	7
4	Org 3 + Ex. 2	50+2	5	14	30	7.0	13	6.0	10	13	3
5	Org 3 + Ex. 2	60+3	5	15	28	7.0	13	6.0	11	15	4
6	Org 3 + Ex. 2	70+3.5	5	16	29	7.0	12	5.0	11	12	1
7	Org 3 + Ex. 1	50+1	5	11	25	8.0	16	8.0	7	15	8
8	Org 3 + Ex. 1	50+2	1	6	27	8.0	14	6.0	8	12	4
9	Org 1	50	3	5	18	7.0	23	16.0	9	26	17
10	Org 1	100	3	8	21	2.8	14	0.5	3.2	16	12.8
11	Org 6	50	1	4	15	5.2	22	16.8	10	26	16
12	Org 6	100	8	12	19	4.0	19	15.0	11	23	12
13	Org 2	50	tr	1	18	1.8	22	20.2	10	24	14
14	Org 2	100	5	10	23	1.6	15	13.4	10	16	6

tr: trace

TESTING EXAMPLE 5: Separation of crude oil emulsion from Field 1.

- [00057]** The original crude oil emulsion sample contained 18% free water and 28% total water. Table 5 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 5. Bottle tests with crude oil emulsion from Field 1, at 60 °C

#	Demulsifier	Dose	WATER DROP	TOP CUT (80%)			MIXED CUT		
		ppm	17 hours	W1	W2	Δ W	W1	W2	Δ W
1	Org 6	100	19	0.8	12	11.2	4.4	14	9.6
2	Org 6 + Ex. 2	50+2	19	8.0	14	6.0	9	15	6
3	Org 1	100	15	2.0	14	12.0	2	14	12
4	Org 1 + Ex. 2	50+2	18	1.2	14	12.8	6	14	8

10

TESTING EXAMPLE 6: Separation of crude oil emulsion from Field 2.

- [00058]** The original crude oil emulsion sample contained 32% free water and 48% total water. Table 6 shows the results at 40 °C using organic formulations with and

without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 6. Bottle tests with crude oil emulsion from Field 2, at 40 °C

#	Demulsifier	Dose	WATER DROP				TOP CUT (80%)			MIXED CUT		
		ppm	10min	20 min	60 min	90 min	W1	W2	Δ W	W1	W2	Δ W
1	Org 1	100	6	20	29	30	3.2	11	7.8	0.8	14	13.2
2	Org 2	100	2	7	10	15	4.0	11	7.0	4.8	15	10.2
3	Org 3	100	6	19	30	32	6.0	9	3.0	7	12	5
4	Org 4	100	5	28	30	32	2.4	9	6.6	0.8	10	9.2
5	Org 1 + Ex. 2	50+2	2	19	29	31	10.0	15	5.0	9	14	5
6	Org 2 + Ex. 2	50+2	3	20	28	31	12.0	13	1.0	11	12	1
7	Org 3 + Ex. 2	50+2	2	18	29	30	9.0	11	2.0	8	11	3
8	Org 4 + Ex. 2	50+2	2	11	21	29	10.0	13	3.0	11	14	3
11	BLANK	0	tr	tr	tr							

tr: trace

5

TESTING EXAMPLE 7: Separation of crude oil emulsion from Field 2.

[00059] The original crude oil emulsion sample contained 50% free water and 60% total water. Table 7 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

10

Table 7. Bottle tests with crude oil emulsion from Field 2, at 40 °C

#	Demulsifier	Dose	WATER DROP				TOP CUT (80%)			MIXED CUT		
		ppm	10min	20 min	30 min	60 min	W1	W2	Δ W	W1	W2	Δ W
1	Org 1	100	15	42	45	45	2.8	8	5.2	1.6	7	5.4
2	Org 1 + Ex. 2	50+2	15	40	45	47	5.2	9	3.8	6	9	3
3	Org 2	100	8	11	13	21	1.6	6	4.4	0.4	4.4	4
4	Org 2 + Ex. 2	50+2	11	41	50	52	7.0	7	0.0	7	8	1
5	Org 3	100	40	50	53	54	3.8	6	3.2	2.4	5.2	2.8
6	Org 3 + Ex. 2	50+2	25	50	57	56	4.0	6	2.0	4.4	6	1.6
7	Org 4	100	45	55	57	57	0.0	4	4.0	1.6	4	2.4
8	Org 4 + Ex. 2	50+2	21	50	55	55	4.0	7	3.0	4	7	3
10	BLANK	0	0	0	0	0						

TESTING EXAMPLE 8: Separation of crude oil emulsion from Field 2.

[00060] The original crude oil emulsion sample contained 40% free water and 48% total water. Table 8 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 8. Bottle tests with crude oil emulsion from Field 2, at 60 °C

#	Demulsifier	Dose	WATER DROP				TOP CUT (80%)			MIXED CUT		
		ppm	5 min	10 min	30 min	60 min	W1	W2	Δ W	W1	W2	Δ W
1	Org 5	50	12	22	30	34	2.8	15	12.2	4.8	18	13.2
2	Org 5 + Ex. 2	25+1	18	25	30	32	10.0	20	10.0	10	20	10
3	Org 3	50	15	21	29	33	1.6	12	10.4	3.2	13	9.8
4	Org 3 + Ex. 2	25+1	25	28	31	35	9.0	15	6.0	7	14	7
5	Org 4	50	20	31	34	37	0.8	11	10.2	2	11	9
6	Org 4 + Ex. 2	25+1	25	33	36	38	9.0	13	4.0	8	16	8

10

TESTING EXAMPLE 9: Separation of crude oil emulsion from Field 2.

[00061] The original crude oil emulsion sample contained 20% free water and 40% total water. Table 9 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

15

Table 9. Bottle tests with crude oil emulsion from Field 2, at 40 °C

#	Demulsifier	Dose	WATER DROP					TOP CUT (80%)			MIXED CUT		
		ppm	5 min	10 min	15 min	40 min	60 min	W1	W2	Δ W	W1	W2	Δ W
1	Org 6	100	tr	1	5	32	35	0.0	2.4	2.4	0	3	3
2	Org 6 + Ex. 2	50+2	3	7	25	36	37	4.8	6	1.2	4	5	1
3	Org 1	100	13	30	34	37	38	0.0	2.4	2.4	0.2	4	3.8
4	Org 1 + Ex. 2	50+2	3	11	31	36	35	4.0	8	4.0	3.2	8	4.6

tr: trace

TESTING EXAMPLE 10: Separation of crude oil emulsion from Field 2.

[00062] The original crude oil emulsion sample contained 20% free water and 40% total water. Table 10 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 10. Bottle tests with crude oil emulsion from Field 2, at 60 °C

#	Demulsifier	Dose	WATER DROP			TOP CUT (80%)			MIXED CUT		
		ppm	5 min	10 min	60 min	W1	W2	Δ W	W1	W2	Δ W
1	Org 6	100	tr	2	35	1.6	5.6	4.0	1.6	6	4.4
2	Org 6 + Ex. 2	50+2	16	30	39	8.5	10	1.5	7	8	1
3	Org 1	100	36	36	38	0.6	7	6.4	0.2	8	7.8
4	Org 1 + Ex. 2	50+2	36	36	37	8.0	12	4.0	9	14	5

TESTING EXAMPLE 11: Separation of crude oil emulsion from Field 3.

[00063] The original crude oil emulsion sample contained 14% free water and 28% total water. Table 11 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 11. Bottle tests with crude oil emulsion from Field 3, at 40 °C

#	Demulsifier	Dose	WATER DROP		TOP CUT (80%)			MIXED CUT		
		ppm	2 hours	22 hours	W1	W2	Δ W	W1	W2	Δ W
1	Org 1	100	2	19	4.8	10	5.2	7	11	4
2	Org 1 + Ex. 2	50+2	2	19	8.0	13	5.0	7.5	12	4.5
3	Org 2	100	4	20	2.8	6	3.2	4	8	4
4	Org 2 + Ex. 2	50+2	1	19	7.0	9	2.0	8	10	2
5	Org 3	100	3	20	2.4	9	6.6	4.4	10	5.6
6	Org 3 + Ex. 2	50+2	3	19	7.0	12	5.0	7	11	4
7	Org 4	100	2	21	2.8	9	6.2	4.8	8	3.2
8	Org 4 + Ex. 2	50+2	2	22	3.2	8	4.4	5.2	8	2.8
10	BLANK	0	0	0						

TESTING EXAMPLE 12: Separation of crude oil emulsion from Field 3.

[00064] The original crude oil emulsion sample contained 8% free water and 20% total water. Table 12 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 12. Bottle tests with crude oil emulsion from Field 2, at 60 °C

#	Demulsifier	Dose	WATER DROP		TOP CUT (80%)			MIXED CUT		
		ppm	30 min	19 h	W1	W2	Δ W	W1	W2	Δ W
1	Org 5	70	1	16	1.8	4	2.2	2.2	4.8	2.6
2	Org 5+ Ex. 2	35+1.25	1	18	2.0	5.6	2.4	3.6	7	4.6
3	Org 3	70	2	14	0.0	9.5	9.5	2.8	9.5	6.7
4	Org 3+ Ex. 2	35+1.25	2	15	4.8	10	5.2	8	12	4
5	Org 4	70	tr	13	1.6	9	7.4	7	12	5
6	Org 4+ Ex. 2	35+1.25	2	16	2.8	10	7.2	5.8	9	3.2

tr: trace

TESTING EXAMPLE 13: Separation of crude oil emulsion from Field 3.

[00065] The original crude oil emulsion sample contained 13% free water and 26% total water. Table 13 shows the results at 40 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 13. Bottle tests with crude oil emulsion from Field 2, at 40 °C

#	Demulsifier	Dose	WATER DROP	TOP CUT (80%)			MIXED CUT		
		ppm	17 hours	W1	W2	Δ W	W1	W2	Δ W
1	Org 6	100	10	7.0	12	5.0	6	13	7
2	Org 6+ Ex. 2	50+2	11	8.0	17	9.0	11	17	6
3	Org 1	100	14	5.2	11	5.8	3.8	13	9.2
4	Org 1+ Ex. 2	50+2	12	7.0	13	6.0	9	15	6

- 26 -

TESTING EXAMPLE 14: Separation of crude oil emulsion from Field 3.

[00066] The original crude oil emulsion sample contained 13% free water and 26% total water. Table 14 shows the results at 60 °C using organic formulations with and without the silicone example, respectively. When the silicone was also added the organic demulsifier dose was halved.

Table 14. Bottle tests with crude oil emulsion from Field 3, at 60 °C

#	Demulsifier	Dose	WATER DROP	TOP CUT (80%)			MIXED CUT		
		ppm	17 hours	W1	W2	Δ W	W1	W2	Δ W
1	Org 6	70	9	8.0	16	8.0	7	13	6
2	Org 6+ Ex. 2	35+1.25	9	9.0	18	9.0	8.5	15	6.5
3	Org 1	70	11	7.0	14	7.0	9	14	5
4	Org 1+ Ex. 2	35+1.25	11	7.0	14	7.0	9.5	15	5.5

10

[00067] It can be seen in the test results above that combining small amount of silicones (typically 5%) with any of the organic formulations, at significantly lower total demulsifier doses, either reduced the amount of unresolved emulsion (ΔW) or resulted in a similar performance as the organic alone, at the higher dose.


15 **[00068]** It is understood that any compound, material or substance which is expressly or implicitly disclosed in the specification and/or recited in a claim as belonging to a group of structurally, compositionally and/or functionally related compounds, materials or substances includes individual representatives of the group and all combinations thereof.

20 **[00069]** Other embodiments of the invention will be apparent to those skilled in the art from a consideration of this specification or practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with the true scope and spirit of the invention being defined by the following claims.

- 27 -

WHAT IS CLAIMED IS:

1. A demulsifying composition comprising a blend of
- a. an emulsion; and
 - b. a demulsifying-effective amount of a silicon containing co-polymer
- 5 comprising at least one compound having the following molecular formula:



where R^2 is a group defined as $M_fD_gT_hQ_iR_j^6$ with

10 $M = R^7R^8R^9SiZ_{1/2},$

$D = R^{10}R^{11}SiZ_{2/2},$

$T = R^{12}SiZ_{3/2},$

$Q = SiZ_{4/2},$

$R^6 = -(CH_2)_{1/2}(R^{13})_k(CH_2)_{1/2}-,$

15 wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

20 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

Z is oxygen subject to the limitation that the co-polymer molecule contains an even number of $O_{1/2}$ groups,

25 R^3 is a trivalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

$R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

- 28 -


R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

subscripts a, b, c, d and e are zero or positive subject to the limitation $3 < a + b + c + d + e < \text{about } 1000$,
 subscripts d+e > 1,
 subscripts f, g, h, i and j are 0 or positive subject to the limitation $f + g + h + i + j < \text{about } 300$, and,
 subscript k is either 0 or 1.

2. The demulsifying composition of claim 1 wherein (b) comprises the compound having the following formula:



20

wherein R^2 is a group defined as $M_fD_gT_hQ_iR^6_j$ wherein

$M = R^7R^8R^9Si(O)_{1/2}$;

$T = R^{12}Si(O)_{2/2}(CH_2)_{1/2}$;

f=2;

25 g=0;

h=1;

i=0;


j=1; and

$R^6 = -(CH_2)_{1/2}R^{13}(CH_2)_{1/2}$.

30

- 29 -

3. The composition of claim 1 wherein said silicon containing co-polymer (b) comprises the compound having the following formula:



wherein R^2 is a group defined as $M_f D_g T_h Q_i R_j^6$

wherein $M = R^7 R^8 R^9 Si(O)_{1/2}$;

10 $T = R^{12} Si(O)_{2/2} (CH_2)_{1/2}$;

$f=2$;

$g=0$;

$h=1$;

$i=0$;

15 $j=1$;

$R^6 = -(CH_2)_{1/2} R^{13} (CH_2)_{1/2} -$;

$R^3 = -CH_2CH_2CH[(CH_2)_{1/2}-]CH_2-$; and

$R^4 = -(CH_2)_{1/2} R^{13} (CH_2)_{1/2} -$.

20 4. The silicon containing co-polymer (b) of claim 1 wherein:

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

25 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^3 is a trivalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

30 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

– 30 –

R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 25 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

5 R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 25 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

10 subscripts a, b, c, d and e are zero or positive subject to the limitation $3 < a+b+c+d+e < \text{about } 750$; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f+g+h+i+j < \text{about } 200$.

15 5. The silicon containing co-polymer (b) of claim 1 wherein:

R^1 is independently selected from $-\text{OH}$ or $-\text{OC}(\text{O})\text{CH}_3$ or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

20 R^5 is independently selected from hydrogen or a $-\text{C}(\text{O})\text{CH}_3$ group or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^3 is a trivalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

25 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

- 31 -

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;


subscripts a, b, c, d and e are zero or positive subject to the limitation $3 < a + b + c + d + e < \text{about } 500$; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f + g + h + i + j < \text{about } 100$.

6. A method for separating emulsions comprising:

- (i) combining a demulsifying composition comprising a blend of an emulsion (a) and a demulsifying-effective amount of a silicon containing co-polymer (b) of claim 1 to produce a new composition;
- (ii) allowing the new composition to separate into at least two phases; and
- (iii) separating said at least two phases from each other.

7. The method for separating emulsions of claim 6 wherein component (b) is a silicon containing co-polymer having the following molecular formula:



wherein R^2 is a group defined as $M_fD_gT_hQ_iR_j^6$ wherein

$$M = R^7R^8R^9SiZ_{1/2};$$

$$D = R^{10}R^{11}SiZ_{2/2};$$

$$T = R^{12}SiZ_{3/2};$$

$$Q = SiZ_{4/2};$$

$$R^6 = -(CH_2)_{1/2}(R^{13})_k(CH_2)_{1/2}-;$$

- 32 -

wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

5 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

Z is oxygen subject to the limitation that the co-polymer molecule contains an even number of $O_{1/2}$ groups;

10 R^3 is a trivalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^7 , R^8 , R^9 , R^{10} , R^{11} and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

15 R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 30 carbon atoms and optionally
20 containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

subscripts a , b , c , d and e are zero or positive subject to the limitation
25 $3 < a + b + c + d + e < \text{about } 1000$;

subscripts $d + e > 1$;

subscripts f , g , h , i and j are 0 or positive subject to the limitation $f + g + h + i + j < \text{about } 300$; and

subscript k is 0 or 1.

30

- 33 -

8. The method for separating emulsions of claim 7 wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

5 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^3 is a trivalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

10 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 25 carbon atoms and optionally containing
15 heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 25 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon
20 radical having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

subscripts a, b, c, d and e are zero or positive subject to the limitation
 $3 < a+b+c+d+e < \text{about } 750$; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f+g+h+i+j < \text{about } 200$.
25

9. The method for separating emulsions of claim 8 wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing
30 heteroatoms and hydroxyl groups;

- 34 -

R⁵ is independently selected from hydrogen or a -C(O)CH₃ group or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R³ is a trivalent hydrocarbon radical optionally containing heteroatoms and hydroxyl groups having 1 to about 20 carbon atoms;

R⁷, R⁸, R⁹, R¹⁰, R¹¹ and R¹² are each independently selected from the group of OR¹⁴ or monovalent hydrocarbon radicals having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R⁴ is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,


R¹³ is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R¹⁴ is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

subscripts a, b, c, d and e are zero or positive subject to the limitation 3 < a+b+c+d+e < about 500; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation f+g+h+i+j < about 100.





10. A silicon containing co-polymer composition comprising at least one compound with the following molecular formula:



wherein R² is a group defined as M_fD_gT_hQ_iR_j⁶; wherein

M = R⁷R⁸R⁹SiZ_{1/2};

- 35 -



5 wherein

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

10 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

Z is O or CH_2 group subject to the limitation that the co-polymer molecule contains even number of $O_{1/2}$ and even number of $(CH_2)_{1/2}$ groups wherein said $O_{1/2}$ and $(CH_2)_{1/2}$ groups are all paired and that the copolymer contains at least one $Si-R^{15}-Si$ group;

15 R^{15} is a divalent linear or branched, unsaturated or saturated hydrocarbon radical containing 1 to about 30 carbon atoms, optionally containing heteroatoms and hydroxyl groups with the proviso that at least one carbon is located in a backbone of the copolymer;

R^3 is a trivalent hydrocarbon radical having 1 to about 40 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

20 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 20 carbon atoms optionally containing heteroatoms and hydroxyl groups;

25 R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

30 R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

- 36 -

subscripts a, b, c, d and e are zero or positive subject to the limitation $3 < a + b + c + d + e < \text{about } 1000$;

subscripts d+e > 1;

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f + g + h + i + j < \text{about } 300$; and
subscript k is either 0 or 1.

11. The silicon containing co-polymer composition of claim 10 wherein:

R^1 is independently selected from $-\text{OH}$ or $-\text{OC}(\text{O})\text{CH}_3$ or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^5 is independently selected from hydrogen or a $-\text{C}(\text{O})\text{CH}_3$ group or a monovalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^3 is a trivalent hydrocarbon radical having 1 to about 30 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^7 , R^8 , R^9 , R^{10} , R^{11} and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 25 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 25 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon radical having 1 to about 15 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

subscripts a, b, c, d and e are zero or positive subject to the limitation $3 < a + b + c + d + e < \text{about } 750$; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f + g + h + i + j < \text{about } 200$.

- 37 -

12. The silicon containing co-polymer composition of claim 10 wherein:

R^1 is independently selected from $-OH$ or $-OC(O)CH_3$ or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

5 R^5 is independently selected from hydrogen or a $-C(O)CH_3$ group or a monovalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^3 is a trivalent hydrocarbon radical having 1 to about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

10 $R^7, R^8, R^9, R^{10}, R^{11}$ and R^{12} are each independently selected from the group of OR^{14} or monovalent hydrocarbon radicals having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

R^4 is a divalent, linear or branched, unsaturated or saturated hydrocarbon radical containing at least one and less than about 20 carbon atoms and optionally containing
15 heteroatoms and hydroxyl groups,

R^{13} is oxygen or divalent linear or branched, unsaturated or saturated hydrocarbon radicals containing at least one and less than about 20 carbon atoms and optionally containing heteroatoms and hydroxyl groups,

R^{14} is a monovalent, linear or branched, unsaturated or saturated hydrocarbon
20 radical having 1 to about 10 carbon atoms and optionally containing heteroatoms and hydroxyl groups;

subscripts a, b, c, d and e are zero or positive subject to the limitation
3 $3 < a+b+c+d+e < \text{about } 500$; and

subscripts f, g, h, i and j are 0 or positive subject to the limitation $f+g+h+i+j < \text{about } 100$.
25

13. The demulsifying composition of claim 10 wherein (b) comprises the compound having the following formula:

30 $R^1(CH_2CH_2O)_a(CH(CH_3)CH_2O)_b(CH[(CH_2)_{1/2}R^2]CH_2O)_dR^5$;


- 38 -

wherein R^2 is a group defined as $R^7R^8R^9Si(CH_2)_lSi(R^{10})(R^{11})R^{13}(CH_2)_{1/2-}$;

wherein $1 \leq l \leq$ about 10; and

$R^6 = -(CH_2)_{1/2}R^{13}(CH_2)_{1/2-}$.

- 5 14. The composition of claim 10 wherein said silicon containing co-polymer (b) comprises the compound having the following formula:




wherein R^2 is a group defined as

- 10 $R^7R^8R^9Si(CH_2)_lSi(R^{10})(R^{11})OSi(R^{10})(R^{11})R^{13}(CH_2)_{1/2-}$; and

where $1 \leq l \leq$ about 10.

15. The composition of claim 10 wherein said silicon containing co-polymer (b) comprises a compound having the formula



15

where R^2 is a group defined as $M_fD_gT_hQ_iR^6_j$

wherein $M = R^7R^8R^9SiZ_{1/2}$,

$T = R^{12}SiZ_{3/2}$,

$f=2$

- 20 $g=0$

$h=1$

$i=0$

$j=1$

$R^6 = -(CH_2)_{1/2}R^{13}(CH_2)_{1/2-}$

- 25 $R^3 = -CH_2CH_2CH[(CH_2)_{1/2-}]CH_2-$; and,

$R^4 = -(CH_2)_{1/2}R^{13}(CH_2)_{1/2-}$.

- 39 -

16. A demulsifying composition comprising a blend of
- a. an emulsion; and
 - b. a demulsifying-effective amount of said silicon containing co-polymer composition of claim 10.

5

17. A demulsifying composition comprising a blend of
- a. an emulsion; and
 - b. a demulsifying-effective amount of said silicon containing co-polymer composition of claim 11.

10

18. A demulsifying composition comprising a blend of
- a. an emulsion; and
 - b. a demulsifying-effective amount of said silicon containing co-polymer composition of claim 12.

15

19. A method for separating emulsions comprising:
- (i) combining a demulsifying composition comprising a blend of an emulsion (a) and a demulsifying-effective amount of a silicon containing co-polymer composition (b) of claim 16 to produce a new composition;
 - (ii) allowing the new composition to separate into at least two phases; and
 - (iii) separating said at least two phases from each other.

20

20. A method for separating emulsions comprising:
- (i) combining a demulsifying composition comprising a blend of an emulsion (a) and a demulsifying-effective amount of a silicon containing co-polymer composition (b) of claim 17 to produce a new composition;
 - (ii) allowing the new composition to separate into at least two phases; and
 - (iii) separating said at least two phases from each other.

30

- 40 -

21. A method for separating emulsions comprising:

- (i) combining a demulsifying composition comprising a blend of an emulsion (a) and a demulsifying-effective amount of a silicon containing co-polymer composition (b) of claim 18 to produce a new composition;
- 5 (ii) allowing the new composition to separate into at least two phases; and
- (iii) separating said at least two phases from each other.

22. The demulsifying composition of claim 1 wherein said composition further
10 comprises one or more additional organic or silicone demulsifier components and the weight ratio of the silicon containing co-polymer (b) to the total amount of organic and silicone demulsifiers is in the range of about 100:1 to about 1:1000.

23. The demulsifying composition of claim 1 wherein the concentration of said
15 demulsifying effective amount of silicon containing co-polymer (b) in said emulsion component (a) is from about 0.1ppm to about 10,000ppm.

24. The demulsifying composition of claim 1 wherein the concentration of said
20 demulsifying effective amount of silicon containing co-polymer (b) in said emulsion component (a) is from about 0.1ppm to about 1000ppm.