



US009036529B2

(12) **United States Patent**
Erickson et al.

(10) **Patent No.:** **US 9,036,529 B2**
(45) **Date of Patent:** **May 19, 2015**

(54) **EFFICIENT COMMUNICATION FOR
DEVICES OF A HOME NETWORK**

(71) Applicant: **Google Inc.**, Mountain View, CA (US)

(72) Inventors: **Grant M. Erickson**, Sunnyvale, CA (US); **Jay D. Logue**, San Jose, CA (US); **Christopher A. Boross**, San Francisco, CA (US); **Zachary B. Smith**, San Francisco, CA (US); **Osborne B. Hardison**, Palo Alto, CA (US); **Richard J. Schultz**, Mountain View, CA (US); **Sunny P. Gujjaru**, Sunnyvale, CA (US); **Matthew G. Neeley**, San Mateo, CA (US)

(73) Assignee: **Google Inc.**, Mountain View, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/506,274**

(22) Filed: **Oct. 3, 2014**

(65) **Prior Publication Data**

US 2015/0023294 A1 Jan. 22, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/926,335, filed on Jun. 25, 2013.

(51) **Int. Cl.**
H04L 12/28 (2006.01)
H04L 12/937 (2013.01)
H04L 29/12 (2006.01)
H04L 12/58 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 49/254** (2013.01); **H04L 61/6059** (2013.01); **H04L 12/58** (2013.01)

(58) **Field of Classification Search**

USPC 370/254, 311
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,101,545	A *	8/2000	Balcerowski et al.	709/230
6,484,200	B1 *	11/2002	Angal et al.	709/224
7,035,634	B2 *	4/2006	Mead et al.	455/431
8,539,567	B1	9/2013	Logue et al.	
2002/0184208	A1 *	12/2002	Kato	707/4
2003/0135556	A1 *	7/2003	Holdsworth	709/206
2006/0067360	A1 *	3/2006	Ohara	370/465
2007/0054674	A1 *	3/2007	Cohen et al.	455/456.1
2008/0141274	A1 *	6/2008	Bhogal et al.	719/313
2009/0024498	A1 *	1/2009	Berezuk et al.	705/35
2009/0040103	A1 *	2/2009	Chansarkar et al.	342/357.12
2009/0116463	A1 *	5/2009	Hirano et al.	370/338

(Continued)

OTHER PUBLICATIONS

Invitation to Pay Additional Fees for PCT Application No. PCT/US2014/043699 dated Sep. 30, 2014; 6 pgs.


(Continued)

Primary Examiner — Farah Farouli

(57) **ABSTRACT**

Systems and methods are provided for efficient communication through a fabric network of devices in a home environment or similar environment. For example, an electronic device may efficiently control communication to balance power and reliability concerns, may efficiently communicate messages to certain preferred networks by analyzing Internet Protocol version 6 (IPv6) packet headers that use an Extended Unique Local Address (EULA), may efficiently communicate software updates and status reports throughout a fabric network, and/or may easily and efficiently join a fabric network.

19 Claims, 38 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0323690 A1 * 12/2009 Lu et al. 370/392
 2010/0232433 A1 * 9/2010 Morris 370/392
 2010/0262650 A1 10/2010 Chauhan et al.
 2011/0275384 A1 11/2011 Barbeau et al.
 2012/0207163 A1 * 8/2012 Schrum 370/392

2013/0078985 A1 * 3/2013 Savolainen et al. 455/418
 2014/0089671 A1 3/2014 Logue et al.

OTHER PUBLICATIONS

U.S. Appl. No. 13/926,302, filed Jun. 25, 2013, Jay D. Logue.
 U.S. Appl. No. 13/926,312, filed Jun. 25, 2013, Grant M. Erickson.

* cited by examiner





FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A






FIG. 7B






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60





FIG. 61







FIG. 63



1900




FIG. 65




FIG. 66




FIG. 67

EFFICIENT COMMUNICATION FOR DEVICES OF A HOME NETWORK

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a Continuation Application of, and claims priority to, U.S. patent application Ser. No. 13/926,335, entitled "Efficient Communication for Devices of a Home Network", filed Jun. 25, 2013, the entirety of which is incorporated by reference herein for all purposes.

BACKGROUND

This disclosure relates to efficient communication to enable various devices, including low-power or sleepy devices, to communicate in a home network or similar environment.

This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present techniques, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

Network-connected devices appear throughout homes. Some of these devices are often capable of communicating with each other through a single network type (e.g., WiFi connection) using a transfer protocol. It may be desired to use less power intensive connection protocols for some devices that are battery powered or receive a reduced charge. However, in some scenarios, devices connected to a lower power protocol may not be able to communicate with devices connected to a higher power protocol (e.g., WiFi).

Moreover, numerous electronic devices are now capable of connecting to wireless networks. For example, smart meter technology employs a wireless network to communicate electrical energy consumption data associated with residential properties back to a utility for monitoring, billing, and the like. As such, a number of wireless networking standards are currently available to enable electronic devices to communicate with each other. Some smart meter implementations, for instance, employ Internet Protocol version 6 (IPv6) over Low power Wireless Personal Area Networks (6LoWPAN) to enable electronic devices to communicate with a smart meter. However, the currently available wireless networking standards such as 6LoWPAN may not be generally well equipped to support electronic devices dispersed throughout a residence or home for one or more practical scenarios. That is, the currently available wireless networking standards may not efficiently connect all electronic devices of a network in a secure yet simple, consumer-friendly manner in view of one or more known practical constraints. Moreover, for one or more practical scenarios, the currently available wireless networking standards may not provide an efficient way to add new electronic devices to an existing wireless network in an ad hoc manner.

Additionally, when providing a wireless network standard for electronic devices for use in and around a home, it would be beneficial to use a wireless network standard that provides an open protocol for different devices to learn how to gain access to the network. Also, given the number of electronic devices that may be associated with a home, it would be beneficial that the wireless network standard be capable of supporting Internet Protocol version 6 (IPv6) communication such that each device may have a unique IP address and may

be capable of being accessed via the Internet, via a local network in a home environment, and the like. Further, it would be beneficial for the wireless network standard to allow the electronic devices to communicate within the wireless network using a minimum amount of power. With these features in mind, it is believed that one or more shortcomings is presented by each known currently available wireless networking standard in the context of providing a low power, IPv6-based, wireless mesh network standard that has an open protocol and can be used for electronic devices in and around a home. For example, wireless network standards such as Bluetooth®, Dust Networks®, Z-Wave®, WiFi, and ZigBee® fail to provide one or more of the desired features discussed above.

Bluetooth®, for instance, generally provides a wireless network standard for communicating over short distances via short-wavelength radio transmissions. As such, Bluetooth's® wireless network standard may not support a communication network of a number of electronic devices disposed throughout a home. Moreover, Bluetooth's® wireless network standard may not support wireless mesh communication or IPv6 addresses.

As mentioned above, the wireless network standard provided by Dust Networks® may also bring about one or more shortcomings with respect to one or more features that would enable electronic devices disposed in a home to efficiently communicate with each other. In particular, Dust Networks'® wireless network standard may not provide an open protocol that may be used by others to interface with the devices operating on Dust Networks' network. Instead, Dust Networks® may be designed to facilitate communication between devices located in industrial environments such as assembly lines, chemical plants, and the like. As such, Dust Networks'® wireless network standard may be directed to providing a reliable communication network that has predefined time windows in which each device may communicate to other devices and listen for instructions from other devices. In this manner, Dust Networks'® wireless network standard may require sophisticated and relatively expensive radio transmitters that may not be economical to implement with consumer electronic devices for use in the home.

Like Dust Networks'® wireless network standard, the wireless network standard associated with Z-Wave® may not be an open protocol. Instead, Z-wave's® wireless network standard may be available only to authorized clients that embed a specific transceiver chip into their device. Moreover, Z-wave's® wireless network standard may not support IPv6-based communication. That is, Z-wave's® wireless network standard may require a bridge device to translate data generated on a Z-Wave® device into IP-based data that may be transmitted via the Internet.

Referring now to ZigBee's® wireless network standards, ZigBee® has two standards commonly known as ZigBee® Pro and ZigBee® IP. Moreover, ZigBee® Pro may have one or more shortcomings in the context of support for wireless mesh networking. Instead, ZigBee® Pro may depend at least in part on a central device that facilitates communication between each device in the ZigBee® Pro network. In addition to the increased power requirements for that central device, devices that remain on to process or reject certain wireless traffic can generate additional heat within their housings that may alter some sensor readings, such as temperature readings, acquired by the device. Since such sensor readings may be useful in determining how each device within the home may operate, it may be beneficial to avoid unnecessary gen-

eration of heat within the device that may alter sensor readings. Additionally, ZigBee® Pro may not support IPv6 communication.

Referring now to ZigBee® IP, ZigBee® IP may bring about one or more shortcomings in the context of direct device-to-device communication. ZigBee® IP is directed toward the facilitation of communication by relay of device data to a central router or device. As such, the central router or device may require constant powering and therefore may not represent a low power means for communications among devices. Moreover, ZigBee® IP may have a practical limit in the number of nodes (i.e., ~20 nodes per network) that may be employed in a single network. Further, ZigBee® IP uses a “Ripple” routing protocol (RPL) that may exhibit high bandwidth, processing, and memory requirements, which may implicate additional power for each ZigBee® IP connected device.

Like the ZigBee® wireless network standards discussed above, WiFi’s wireless network may exhibit one or more shortcomings in terms of enabling communications among devices having low-power requirements. For example, WiFi’s wireless network standard may also require each networked device to always be powered up, and furthermore may require the presence of a central node or hub. As known in the art, WiFi is a relatively common wireless network standard that may be ideal for relatively high bandwidth data transmissions (e.g., streaming video, syncing devices). As such, WiFi devices are typically coupled to a continuous power supply or rechargeable batteries to support the constant stream of data transmissions between devices. Further, WiFi’s wireless network may not support wireless mesh networking. Even so, WiFi sometimes may offer better connectivity than some lower-powered protocols.

SUMMARY

A summary of certain embodiments disclosed herein is set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure. Indeed, this disclosure may encompass a variety of aspects that may not be set forth below.

Systems and methods are provided for efficient communication through a fabric network of devices in a home environment or similar environment. For example, an electronic device may efficiently control communication to balance power and reliability concerns, may efficiently communicate messages to certain preferred networks by analyzing Internet Protocol version 6 (IPv6) packet headers that use an Extended Unique Local Address (EULA), may efficiently communicate software updates and status reports throughout a fabric network, and/or may easily and efficiently join a fabric network.

For instance, an electronic device may include memory or storage storing instructions to operate a network stack, a processor to execute the instructions, and a network interface to join a network-connected fabric of devices and communicate a message to a target device of the fabric of devices using the network stack. The network stack may include an application layer to provide an application payload with data to be transmitted in the message, a platform layer to encapsulate the application payload in a general message format of the message, a transport layer to selectably transport the message using either User Datagram Protocol (UDP) or Transmission Control Protocol (TCP), and a network layer to communicate the message using Internet Protocol Version 6 (IPv6) via one

or more networks. These networks may include, for example, an 802.11 wireless network, an 802.15.4 wireless network, a powerline network, a cellular network, and/or an Ethernet network. Moreover, the application layer, the platform layer, the transport layer, and/or the network layer may determine a property of the manner of communication of the message to the target node based at least in part on a type of the message, the network over which the message is to be sent, a distance over which the message may travel through the fabric, power consumption behavior of the electronic device, power consumption behavior of the target device, and/or power consumption behavior of an intervening device of the fabric of devices that is to communicate the message between the electronic device and the target device. Further, varying the property of the manner of communication may cause the electronic device, the target device, and/or the intervening device to consume different amounts of power and cause the message to more reliably or less reliably reach the target node.

In another example, a tangible, non-transitory computer-readable medium may include to be executed by a first electronic device communicably coupled to other electronic devices of a fabric of devices in a home environment. The instructions may include those to receive an Internet Protocol version 6 (IPv6) message at the first electronic device from a second electronic device over a first network of the fabric of devices. The message may be bound for a target electronic device. The instructions may further include instructions to identify an Extended Unique Local Address encoded in an IPv6 header of the message. Here, the Extended Unique Local Address may indicate that a second network is preferred to reach the target electronic device. The instructions also may include instructions to communicate the message through the fabric of devices toward the target electronic device using second network based at least in part on the Extended Unique Local Address.

A method for transferring a software update over a fabric network may include sending an image query message from a first device in the fabric network to a second device in the fabric network or a local or remote server. The image query message may include information regarding software stored on the first device and transfer capabilities of the first device. An image query response may be received by the first device from the second device or the local or remote server. The image query response may indicate whether the software update is available and includes download information having a uniform resource identifier (URI) to enable the first device to download the software update. The image query message may include sender information regarding software stored on a sender device and transfer capabilities of the sender device and an update priority. Using the URI, the software update may be downloaded at the first device from the sender device. The software may be downloaded at a time based at least in part on the update priority and network traffic in the fabric network, and may be downloaded in a manner based at least in part on common transfer capabilities indicated in the image query and the image query response.

In a further example, a tangible, non-transitory computer-readable medium may store a status reporting format. The status reporting format may include a profile field to indicate a status update type of a plurality of status update types, a status code to indicate a status being reported—the status code may be interpreted in a manner based at least in part on the status update type—and a next status field to indicate whether an additional status is included in a status report formed using the status reporting format.

Another example of an electronic device includes memory to store instructions to enable the first electronic device to pair

5

with a fabric network comprising a second electronic device, a processor to execute the instructions, and a network interface to access 802.11 and 802.15.4 logical networks. The instructions may include instructions to establish communication with the second electronic device via a first 802.15.4 logical network. The second electronic device may be paired with the fabric network and may communicate with a service via another logical network in the fabric network. The instructions may also include instructions to receive network configuration information from the service via the second electronic device to enable the first electronic device to join a first 802.11 logical network and to establish communication over the first 802.11 logical network, connect to the service via the first 802.11 logical network, and register to pair with the fabric network via communication with the service.

Various refinements of the features noted above may be used in relation to various aspects of the present disclosure. Further features may also be incorporated in these various aspects as well. These refinements and additional features may be used individually or in any combination. For instance, various features discussed below in relation to one or more of the illustrated embodiments may be incorporated into any of the above-described aspects of the present disclosure alone or in any combination. The brief summary presented above is intended only to familiarize the reader with certain aspects and contexts of embodiments of the present disclosure without limitation to the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings in which:

FIG. 1 illustrates a block diagram of a general device that may communicate with other devices disposed in a home environment using an efficient network layer protocol, in accordance with an embodiment;

FIG. 2 illustrates a block diagram of a home environment in which the general device of FIG. 1 may communicate with other devices via the efficient network layer protocol, in accordance with an embodiment;

FIG. 3 illustrates an example wireless mesh network associated with the devices depicted in the home environment of FIG. 2, in accordance with an embodiment;

FIG. 4 illustrates a block diagram of an Open Systems Interconnection (OSI) model that characterizes a communication system for the home environment of FIG. 2, in accordance with an embodiment;

FIG. 5 illustrates a detailed view an efficient network layer in the OSI model of FIG. 4, in accordance with an embodiment;

FIG. 6 illustrates a flowchart of a method for implementing a Routing Information Protocol—Next Generation (RIPng) network as a routing mechanism in the efficient network layer of FIG. 5, in accordance with an embodiment;

FIG. 7A-7D illustrates an example of how the RIPng network of the method of FIG. 6 can be implemented, in accordance with an embodiment;

FIG. 8 illustrates a block diagram of a manufacturing process that includes embedding a security certificate into the general device of FIG. 1, in accordance with an embodiment;

FIG. 9 illustrates an example handshake protocol between devices in the home environment of FIG. 2 using a Datagram Transport Layer Security (DTLS) protocol in the efficient network layer of FIG. 5, in accordance with an embodiment;

FIG. 10 illustrates the fabric network having a single logical network topology, in accordance with an embodiment;

6

FIG. 11 illustrates the fabric network having a star network topology, in accordance with an embodiment;

FIG. 12 illustrates the fabric network having a overlapping networks topology, in accordance with an embodiment;

FIG. 13 illustrates a service communicating with one or more fabric networks, in accordance with an embodiment;

FIG. 14 illustrates two devices in a fabric network in communicative connection, in accordance with an embodiment;

FIG. 15 illustrates a unique local address format (ULA) that may be used to address devices in a fabric network, in accordance with an embodiment;

FIG. 16 illustrates a process for proxying periphery devices on a hub network, in accordance with an embodiment;

FIG. 17 illustrates a tag-length-value (TLV) packet that may be used to transmit data over the fabric network, in accordance with an embodiment;

FIG. 18 illustrates a general message protocol (GMP) that may be used to transmit data over the fabric network that may include the TLV packet of FIG. 17, in accordance with an embodiment;

FIG. 19 illustrates a message header field of the GMP of FIG. 18, in accordance with an embodiment;

FIG. 20 illustrates a key identifier field of the GMP of FIG. 18, in accordance with an embodiment;

FIG. 21 illustrates an application payload field of the GMP of FIG. 18, in accordance with an embodiment;

FIG. 22 illustrates a status reporting schema that may be used to update status information in the fabric network, in accordance with an embodiment;

FIG. 23 illustrates a profile field of the status reporting schema of FIG. 22, in accordance with an embodiment;

FIG. 24 illustrates a protocol sequence that may be used to perform a software update between a client and a server, in accordance with an embodiment;

FIG. 25 illustrates an image query frame that may be used in the protocol sequence of FIG. 24, in accordance with an embodiment;

FIG. 26 illustrates a frame control field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 27 illustrates a product specification field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 28 illustrates a version specification field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 29 illustrates a locale specification field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 30 illustrates an integrity types supported field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 31 illustrates an update schemes supported field of the image query frame of FIG. 25, in accordance with an embodiment;

FIG. 32 illustrates an image query response frame that may be used in the protocol sequence of FIG. 24, in accordance with an embodiment;

FIG. 33 illustrates a uniform resource identifier (URI) field of the image query response frame of FIG. 32, in accordance with an embodiment;

FIG. 34 illustrates a integrity specification field of the image query response frame of FIG. 32, in accordance with an embodiment;

FIG. 35 illustrates an update scheme field of the image query response frame of FIG. 32, in accordance with an embodiment;

FIG. 36 illustrates a sequence used to employ a data management protocol to manage data between devices in the fabric network, in accordance with an embodiment;

7

FIG. 37 illustrates a snapshot request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 38 illustrates an example profile schema that may be accessed using the snapshot request frame of FIG. 37, in accordance with an embodiment;

FIG. 39 is a binary format of a path that may indicate a path in a profile schema, in accordance with an embodiment;

FIG. 40 illustrates a watch request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 41 illustrates a periodic update request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 42 illustrates a refresh request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 43 illustrates a cancel view request that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 44 illustrates a view response frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 45 illustrates an explicit update request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 46 illustrates a view update request frame that may be used in the sequence of FIG. 36, in accordance with an embodiment;

FIG. 47 illustrates an update item frame that may be updated using the sequence of FIG. 36, in accordance with an embodiment;

FIG. 48 illustrates an update response frame that may be sent as an update response message in the sequence FIG. 36, in accordance with an embodiment;

FIG. 49 illustrates a communicative connection between a sender and a receiver in a bulk data transfer, in accordance with an embodiment;

FIG. 50 illustrates a SendInit message that may be used to initiate the communicative connection by the sender of FIG. 49, in accordance with an embodiment;

FIG. 51 illustrates a transfer control field of the SendInit message of FIG. 50, in accordance with an embodiment;

FIG. 52 illustrates a range control field of the SendInit message of FIG. 51, in accordance with an embodiment;

FIG. 53 illustrates a SendAccept message that may be used to accept a communicative connection proposed by the SendInit message of FIG. 50 sent by the sender of FIG. 50, in accordance with an embodiment;

FIG. 54 illustrates a SendReject message that may be used to reject a communicative connection proposed by the SendInit message of FIG. 50 sent by the sender of FIG. 50, in accordance with an embodiment;

FIG. 55 illustrates a ReceiveAccept message that may be used to accept a communicative connection proposed by the receiver of FIG. 50, in accordance with an embodiment;

FIG. 56 is a block diagram of an example of an IPv6 packet header using an Extended Unique Local Address (EULA), in accordance with an embodiment;

FIG. 57 is a block diagram of an example of communicating an IPv6 packet having the IPv6 packet of FIG. 56 through a fabric topology having two networks, in accordance with an embodiment;

FIG. 58 is a flowchart of a method for efficiently communicating the IPv6 packet through the fabric of FIG. 57 using the IPv6 packet header of FIG. 56, in accordance with an embodiment;

8

FIG. 59 is a flowchart of a method for selecting an efficient transport protocol over which to send a message based at least in part on one or more reliability factors, in accordance with an embodiment;

FIG. 60 is a diagram illustrating a use case of a fabric of devices in which one device invokes a method on another device, in accordance with an embodiment;

FIG. 61 is a diagram illustrating a use case of a fabric of devices in which an alarm message is propagated through a number of low-power, sleepy devices, in accordance with an embodiment;

FIGS. 62-64 are flowcharts of a method for introducing a new device into a fabric of devices, in accordance with an embodiment; and

FIGS. 65-67 are flowcharts of another method for introducing a new device into a fabric of devices, in accordance with an embodiment.

DETAILED DESCRIPTION

One or more specific embodiments of the present disclosure will be described below. These described embodiments are only examples of the presently disclosed techniques. Additionally, in an effort to provide a concise description of these embodiments, all features of an actual implementation may not be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but may nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

When introducing elements of various embodiments of the present disclosure, the articles "a," "an," and "the" are intended to mean that there are one or more of the elements. The terms "comprising," "including," and "having" are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to "one embodiment" or "an embodiment" of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features.

As used herein the term "HVAC" includes systems providing both heating and cooling, heating only, cooling only, as well as systems that provide other occupant comfort and/or conditioning functionality such as humidification, dehumidification and ventilation.

As used herein the terms power "harvesting," "sharing" and "stealing," when referring to home devices, refer to deriving power from a power transformer through the equipment load without using a direct or common wire source directly from the transformer.

As used herein the term "thermostat" means a device or system for regulating parameters such as temperature and/or humidity within at least a part of an enclosure. The term "thermostat" may include a control unit for a heating and/or cooling system or a component part of a heater or air conditioner. As used herein the term "thermostat" can also refer generally to a versatile sensing and control unit (VSCU unit) that is configured and adapted to provide sophisticated, customized, energy-saving HVAC control functionality while at the same time being visually appealing, non-intimidating, elegant to behold, and delightfully easy to use.

As used herein, the term “hazard detector” refers to any home device that can detect evidence of fire (e.g., smoke, heat, carbon monoxide) and/or other hazardous conditions (e.g., extreme temperatures, buildup of dangerous gases).

This disclosure relates to efficient communication that may be used by devices communicating with each other in a home environment. The efficient communication of this disclosure may enable a fabric of devices and/or services to communicate in the home environment. Indeed, consumers living in homes may find it useful to coordinate the operations of various devices within their home such that all of their devices are operated efficiently. For example, a thermostat device may be used to detect a temperature of a home and coordinate the activity of other devices (e.g., lights) based on the detected temperature. The thermostat device may detect a temperature that may indicate that the temperature outside the home corresponds to daylight hours. The thermostat device may then convey to the light device that there may be daylight available to the home and that thus the light should turn off. In another example, a smart hazard detector may be able to detect environmental conditions that indicate occupancy. The thermostat device may query the hazard detector for these environmental conditions and vary its operation accordingly. In addition to efficiency, consumers may generally prefer user-friendly devices that involve a minimum amount of set up or initialization. That is, consumers may generally prefer devices that are fully operational after performing a few number initialization steps, especially those that may be performed by almost any individual regardless of age or technical expertise.

To effectively and efficiently communicate data between each other within the home environment, the devices may use a fabric network that includes one or more logical networks to manage communication between the devices. That is, the efficient fabric network may enable numerous devices within a home to communicate with each other using one or more logical networks. The fabric network may be supported by an efficient communication scheme involving, for example, an efficient network layer, an efficient platform layer, and/or an efficient application layer to manage communication. The fabric network may support Internet Protocol version 6 (IPv6) communication such that each connected device may have a unique local address (ULA). In some examples, the IPv6 communications may employ an Extended Unique Local Address (EULA). Moreover, to enable each device to integrate with a home, it may be useful for each device to communicate within the network using low amounts of power. That is, by enabling devices to communicate using low power, the devices may be placed anywhere in a home without being coupled to a continuous power source (e.g., battery-powered).

On a relatively lower layer of the communication protocol (e.g., the network layer), the fabric efficient network layer may establish a communication network in which numerous devices within a home may communicate with each other via a wireless mesh network. The communication network may support Internet Protocol version 6 (IPv6) communication such that each connected device may have a unique Internet Protocol (IP) address. Moreover, to enable each device to integrate with a home, it may be useful for each device to communicate within the network using low amounts of power. That is, by enabling devices to communicate using low power, the devices may be placed anywhere in a home without being coupled to a continuous power source.

The efficient network layer may thus establish a procedure in which data may be transferred between two or more devices such that the establishment of the communication network involves little user input, the communication

between devices involves little energy, and the communication network, itself, is secure. In one embodiment, the efficient network layer may be an IPv6-based communication network that employs Routing Information Protocol—Next Generation (RIPng) as its routing mechanism and a Datagram Transport Layer Security (DTLS) protocol as its security mechanism. As such, the efficient network layer may provide a simple means for adding or removing devices to a home while protecting the information communicated between the connected devices.

On relatively higher layers of the communication protocol (e.g., the platform and/or application layers), the fabric of devices may be created and maintained. These layers may enable parametric software updates and status reports throughout the fabric. These layers may also provide communication that may be aware of certain network power constraints, such as the power constraints of “sleepy” or battery-powered devices, and may communicate messages with these factors in mind.

As such, embodiments of this disclosure relate to systems and methods a fabric network that includes one or more logical networks that enables devices connected to the fabric to communicate with each other using a list of protocols and/or profiles known to the devices. The communications between the devices may follow a typical message format that enables the devices to understand communications between the devices regardless of which logical networks the communicating devices are connected to in the fabric. Within the message format, a payload of data may be included for the receiving device to store and/or process. The format and the contents of the payload may vary according to a header within the payload that indicates a profile (including one or more protocols) and/or a type of message that is being sent according to the profile.

According to some embodiments, two or more devices in a fabric may communicate using status reporting protocols or profiles. For example, in certain embodiments, a status reporting protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the status reporting protocol, devices may send or request status information to or from other devices in the fabric.

Similarly, in certain embodiments, two or more devices in a fabric may communicate using update software protocols or profiles. In some embodiments, the update software protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the update software protocol, devices may request, send, or notify the presence of updates within the fabric.

In certain embodiments, two or more devices in a fabric may communicate using data management protocols or profiles. In some embodiments, the data management protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the update data management protocol, devices may request, view, or track node-resident information that is stored in other devices.

Furthermore, in certain embodiments, two or more devices in a fabric may transfer data using bulk data transfer protocols or profiles. In some embodiments, the bulk data transfer protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the bulk data transfer protocol, devices may initiate, send, or receive bulk data using any logical networks in the fabric. In certain embodiments, either a sending or a receiving device using the bulk data transfer protocol may be able to “drive” a synchronous transfer between the devices. In other embodiments, the bulk transfer may be performed with an asynchronous transfer.

By way of introduction, FIG. 1 illustrates an example of a general device 10 that may communicate with other like devices within a home environment. In one embodiment, the device 10 may include one or more sensors 12, a user-interface component 14, a power supply 16 (e.g., including a power connection and/or battery), a network interface 18, a processor 20, and the like. Particular sensors 12, user-interface components 14, and power-supply configurations may be the same or similar with each device 10. However, it should be noted that in some embodiments, each device 10 may include particular sensors 12, user-interface components 14, power-supply configurations, and the like based on a device type or model.

The sensors 12, in certain embodiments, may detect various properties such as acceleration, temperature, humidity, water, supplied power, proximity, external motion, device motion, sound signals, ultrasound signals, light signals, fire, smoke, carbon monoxide, global-positioning-satellite (GPS) signals, radio-frequency (RF), other electromagnetic signals or fields, or the like. As such, the sensors 12 may include temperature sensor(s), humidity sensor(s), hazard-related sensor(s) or other environmental sensor(s), accelerometer(s), microphone(s), optical sensors up to and including camera(s) (e.g., charged coupled-device or video cameras), active or passive radiation sensors, GPS receiver(s) or radiofrequency identification detector(s). While FIG. 1 illustrates an embodiment with a single sensor, many embodiments may include multiple sensors. In some instances, the device 10 may include one or more primary sensors and one or more secondary sensors. Here, the primary sensor(s) may sense data central to the core operation of the device (e.g., sensing a temperature in a thermostat or sensing smoke in a smoke detector), while the secondary sensor(s) may sense other types of data (e.g., motion, light or sound), which can be used for energy-efficiency objectives or smart-operation objectives.

One or more user-interface components 14 in the device 10 may receive input from the user and/or present information to the user. The received input may be used to determine a setting. In certain embodiments, the user-interface components may include a mechanical or virtual component that responds to the user's motion. For example, the user can mechanically move a sliding component (e.g., along a vertical or horizontal track) or rotate a rotatable ring (e.g., along a circular track), or the user's motion along a touchpad may be detected. Such motions may correspond to a setting adjustment, which can be determined based on an absolute position of a user-interface component 104 or based on a displacement of a user-interface components 104 (e.g., adjusting a set point temperature by 1 degree F. for every 10° rotation of a rotatable-ring component). Physically and virtually movable user-interface components can allow a user to set a setting along a portion of an apparent continuum. Thus, the user may not be confined to choose between two discrete options (e.g., as would be the case if up and down buttons were used) but can quickly and intuitively define a setting along a range of possible setting values. For example, a magnitude of a movement of a user-interface component may be associated with a magnitude of a setting adjustment, such that a user may dramatically alter a setting with a large movement or finely tune a setting with a small movement.

The user-interface components 14 may also include one or more buttons (e.g., up and down buttons), a keypad, a number pad, a switch, a microphone, and/or a camera (e.g., to detect gestures). In one embodiment, the user-interface component

14 may include a click-and-rotate annular ring component that may enable the user to interact with the component by rotating the ring (e.g., to adjust a setting) and/or by clicking the ring inwards (e.g., to select an adjusted setting or to select an option). In another embodiment, the user-interface component 14 may include a camera that may detect gestures (e.g., to indicate that a power or alarm state of a device is to be changed). In some instances, the device 10 may have one primary input component, which may be used to set a plurality of types of settings. The user-interface components 14 may also be configured to present information to a user via, e.g., a visual display (e.g., a thin-film-transistor display or organic light-emitting-diode display) and/or an audio speaker.

The power-supply component 16 may include a power connection and/or a local battery. For example, the power connection may connect the device 10 to a power source such as a line voltage source. In some instances, an AC power source can be used to repeatedly charge a (e.g., rechargeable) local battery, such that the battery may be used later to supply power to the device 10 when the AC power source is not available.

The network interface 18 may include a component that enables the device 10 to communicate between devices. In one embodiment, the network interface 18 may communicate using an efficient network layer as part of its Open Systems Interconnection (OSI) model. In one embodiment, the efficient network layer, which will be described in more detail below with reference to FIG. 5, may enable the device 10 to wirelessly communicate IPv6-type data or traffic using a RIPv6 routing mechanism and a DTLS security scheme. As such, the network interface 18 may include a wireless card or some other transceiver connection.

The processor 20 may support one or more of a variety of different device functionalities. As such, the processor 20 may include one or more processors configured and programmed to carry out and/or cause to be carried out one or more of the functionalities described herein. In one embodiment, the processor 20 may include general-purpose processors carrying out computer code stored in local memory (e.g., flash memory, hard drive, random access memory), special-purpose processors or application-specific integrated circuits, combinations thereof, and/or using other types of hardware/firmware/software processing platforms. Further, the processor 20 may be implemented as localized versions or counterparts of algorithms carried out or governed remotely by central servers or cloud-based systems, such as by virtue of running a Java virtual machine (JVM) that executes instructions provided from a cloud server using Asynchronous JavaScript and XML (AJAX) or similar protocols. By way of example, the processor 20 may detect when a location (e.g., a house or room) is occupied, up to and including whether it is occupied by a specific person or is occupied by a specific number of people (e.g., relative to one or more thresholds). In one embodiment, this detection can occur, e.g., by analyzing microphone signals, detecting user movements (e.g., in front of a device), detecting openings and closings of doors or garage doors, detecting wireless signals, detecting an IP address of a received signal, detecting operation of one or more devices within a time window, or the like. Moreover, the processor 20 may include image recognition technology to identify particular occupants or objects.

In certain embodiments, the processor 20 may also include a high-power processor and a low-power processor. The high-power processor may execute computational intensive operations such as operating the user-interface component 14 and the like. The low-power processor, on the other hand, may

13

manage less complex processes such as detecting a hazard or temperature from the sensor 12. In one embodiment, the low-power processor may wake or initialize the high-power processor for computationally intensive processes.

In some instances, the processor 20 may predict desirable settings and/or implement those settings. For example, based on the presence detection, the processor 20 may adjust device settings to, e.g., conserve power when nobody is home or in a particular room or to accord with user preferences (e.g., general at-home preferences or user-specific preferences). As another example, based on the detection of a particular person, animal or object (e.g., a child, pet or lost object), the processor 20 may initiate an audio or visual indicator of where the person, animal or object is or may initiate an alarm or security feature if an unrecognized person is detected under certain conditions (e.g., at night or when lights are off).

In some instances, devices may interact with each other such that events detected by a first device influences actions of a second device. For example, a first device can detect that a user has pulled into a garage (e.g., by detecting motion in the garage, detecting a change in light in the garage or detecting opening of the garage door). The first device can transmit this information to a second device via the efficient network layer, such that the second device can, e.g., adjust a home temperature setting, a light setting, a music setting, and/or a security-alarm setting. As another example, a first device can detect a user approaching a front door (e.g., by detecting motion or sudden light pattern changes). The first device may, e.g., cause a general audio or visual signal to be presented (e.g., such as sounding of a doorbell) or cause a location-specific audio or visual signal to be presented (e.g., to announce the visitor's presence within a room that a user is occupying).

By way of example, the device 10 may include a thermostat such as a Nest® Learning Thermostat. Here, the thermostat may include sensors 12 such as temperature sensors, humidity sensors, and the like such that the thermostat may determine present climate conditions within a building where the thermostat is disposed. The power-supply component 16 for the thermostat may be a local battery such that the thermostat may be placed anywhere in the building without regard to being placed in close proximity to a continuous power source. Since the thermostat may be powered using a local battery, the thermostat may minimize its energy use such that the battery is rarely replaced.

In one embodiment, the thermostat may include a circular track that may have a rotatable ring disposed thereon as the user-interface component 14. As such, a user may interact with or program the thermostat using the rotatable ring such that the thermostat controls the temperature of the building by controlling a heating, ventilation, and air-conditioning (HVAC) unit or the like. In some instances, the thermostat may determine when the building may be vacant based on its programming. For instance, if the thermostat is programmed to keep the HVAC unit powered off for an extended period of time, the thermostat may determine that the building will be vacant during this period of time. Here, the thermostat may be programmed to turn off light switches or other electronic devices when it determines that the building is vacant. As such, the thermostat may use the network interface 18 to communicate with a light switch device such that it may send a signal to the light switch device when the building is determined to be vacant. In this manner, the thermostat may efficiently manage the energy use of the building.

Keeping the foregoing in mind, FIG. 2 illustrates a block diagram of a home environment 30 in which the device 10 of FIG. 1 may communicate with other devices via the efficient network layer. The depicted home environment 30 may

14

include a structure 32 such as a house, office building, garage, or mobile home. It will be appreciated that devices can also be integrated into a home environment that does not include an entire structure 32, such as an apartment, condominium, office space, or the like. Further, the home environment 30 may control and/or be coupled to devices outside of the actual structure 32. Indeed, several devices in the home environment 30 need not physically be within the structure 32 at all. For example, a device controlling a pool heater 34 or irrigation system 36 may be located outside of the structure 32.

The depicted structure 32 includes a number of rooms 38, separated at least partly from each other via walls 40. The walls 40 can include interior walls or exterior walls. Each room 38 can further include a floor 42 and a ceiling 44. Devices can be mounted on, integrated with and/or supported by the wall 40, the floor 42, or the ceiling 44.

The home environment 30 may include a plurality of devices, including intelligent, multi-sensing, network-connected devices that may integrate seamlessly with each other and/or with cloud-based server systems to provide any of a variety of useful home objectives. One, more or each of the devices illustrated in the home environment 30 may include one or more sensors 12, a user interface 14, a power supply 16, a network interface 18, a processor 20 and the like.

Example devices 10 may include a network-connected thermostat 46 such as Nest® Learning Thermostat—1st Generation T100577 or Nest® Learning Thermostat—2nd Generation T200577 by Nest Labs, Inc. The thermostat 46 may detect ambient climate characteristics (e.g., temperature and/or humidity) and control a heating, ventilation and air-conditioning (HVAC) system 48. Another example device 10 may include a hazard detection unit 50 such as a hazard detection unit by Nest®. The hazard detection unit 50 may detect the presence of a hazardous substance and/or a hazardous condition in the home environment 30 (e.g., smoke, fire, or carbon monoxide). Additionally, an entryway interface devices 52, which can be termed a “smart doorbell”, can detect a person's approach to or departure from a location, control audible functionality, announce a person's approach or departure via audio or visual means, or control settings on a security system (e.g., to activate or deactivate the security system).

In certain embodiments, the device 10 may include a light switch 54 that may detect ambient lighting conditions, detect room-occupancy states, and control a power and/or dim state of one or more lights. In some instances, the light switches 54 may control a power state or speed of a fan, such as a ceiling fan.

Additionally, wall plug interfaces 56 may detect occupancy of a room or enclosure and control supply of power to one or more wall plugs (e.g., such that power is not supplied to the plug if nobody is at home). The device 10 within the home environment 30 may further include an appliance 58, such as refrigerators, stoves and/or ovens, televisions, washers, dryers, lights (inside and/or outside the structure 32), stereos, intercom systems, garage-door openers, floor fans, ceiling fans, whole-house fans, wall air conditioners, pool heaters 34, irrigation systems 36, security systems, and so forth. While descriptions of FIG. 2 may identify specific sensors and functionalities associated with specific devices, it will be appreciated that any of a variety of sensors and functionalities (such as those described throughout the specification) may be integrated into the device 10.

In addition to containing processing and sensing capabilities, each of the example devices described above may be capable of data communications and information sharing with any other device, as well as to any cloud server or any other device that is network-connected anywhere in the

15

world. In one embodiment, the devices **10** may send and receive communications via the efficient network layer that will be discussed below with reference to FIG. **5**. In one embodiment, the efficient network layer may enable the devices **10** to communicate with each other via a wireless mesh network. As such, certain devices may serve as wireless repeaters and/or may function as bridges between devices in the home environment that may not be directly connected (i.e., one hop) to each other.

In one embodiment, a wireless router **60** may further communicate with the devices **10** in the home environment **30** via the wireless mesh network. The wireless router **60** may then communicate with the Internet **62** such that each device **10** may communicate with a central server or a cloud-computing system **64** through the Internet **62**. The central server or cloud-computing system **64** may be associated with a manufacturer, support entity or service provider associated with a particular device **10**. As such, in one embodiment, a user may contact customer support using a device itself rather than using some other communication means such as a telephone or Internet-connected computer. Further, software updates can be automatically sent from the central server or cloud-computing system **64** to the devices (e.g., when available, when purchased, or at routine intervals).

By virtue of network connectivity, one or more of the devices **10** may further allow a user to interact with the device even if the user is not proximate to the device. For example, a user may communicate with a device using a computer (e.g., a desktop computer, laptop computer, or tablet) or other portable electronic device (e.g., a smartphone) **66**. A webpage or application may receive communications from the user and control the device **10** based on the received communications. Moreover, the webpage or application may present information about the device's operation to the user. For example, the user can view a current set point temperature for a device and adjust it using a computer that may be connected to the Internet **62**. In this example, the thermostat **46** may receive the current set point temperature view request via the wireless mesh network created using the efficient network layer.

In certain embodiments, the home environment **30** may also include a variety of non-communicating legacy appliances **68**, such as old conventional washer/dryers, refrigerators, and the like which can be controlled, albeit coarsely (ON/OFF), by virtue of the wall plug interfaces **56**. The home environment **30** may further include a variety of partially communicating legacy appliances **70**, such as infra-red (IR) controlled wall air conditioners or other IR-controlled devices, which can be controlled by IR signals provided by the hazard detection units **50** or the light switches **54**.

As mentioned above, each of the example devices **10** described above may establish a wireless mesh network such that data may be communicated to each device **10**. Keeping the example devices of FIG. **2** in mind, FIG. **3** illustrates an example wireless mesh network **80** that may be employed to facilitate communication between some of the example devices described above. As shown in FIG. **3**, the thermostat **46** may have a direct wireless connection to the plug interface **56**, which may be wirelessly connected to the hazard detection unit **50** and to the light switch **54**. In the same manner, the light switch **54** may be wirelessly coupled to the appliance **58** and the portable electronic device **66**. The appliance **58** may just be coupled to the pool heater **34** and the portable electronic device **66** may just be coupled to the irrigation system **36**. The irrigation system **36** may have a wireless connection to the entryway interface device **52**. Each device in the wireless mesh network **80** of FIG. **3** may correspond to a node within the wireless mesh network **80**. In one embodiment, the

16

efficient network layer may specify that each node transmit data using a RIPng protocol and a DTLS protocol such that data may be securely transferred to a destination node via a minimum number of hops between nodes.

Generally, the efficient network layer may be part of an Open Systems Interconnection (OSI) model **90** as depicted in FIG. **4**. The OSI model **90** illustrates functions of a communication system with respect to abstraction layers. That is, the OSI model may specify a networking framework or how communications between devices may be implemented. In one embodiment, the OSI model may include six layers: a physical layer **92**, a data link layer **94**, a network layer **96**, a transport layer **98**, a platform layer **100**, and an application layer **102**. Generally, each layer in the OSI model **90** may serve the layer above it and may be served by the layer below it. In at least some embodiments, a higher layer may be agnostic to technologies used in lower layers. For example, in certain embodiments, the platform layer **100** may be agnostic to the network type used in the network layer **96**.

Keeping this in mind, the physical layer **92** may provide hardware specifications for devices that may communicate with each other. As such, the physical layer **92** may establish how devices may connect to each other, assist in managing how communication resources may be shared between devices, and the like.

The data link layer **94** may specify how data may be transferred between devices. Generally, the data link layer **94** may provide a way in which data packets being transmitted may be encoded and decoded into bits as part of a transmission protocol.

The network layer **96** may specify how the data being transferred to a destination node is routed. The network layer **96** may also provide a security protocol that may maintain the integrity of the data being transferred.

The transport layer **98** may specify a transparent transfer of the data from a source node to a destination node. The transport layer **98** may also control how the transparent transfer of the data remains reliable. As such, the transport layer **98** may be used to verify that data packets intended to transfer to the destination node indeed reached the destination node. Example protocols that may be employed in the transport layer **98** may include Transmission Control Protocol (TCP) and User Datagram Protocol (UDP).

The platform layer **100** may establish connections between devices according to the protocol specified within the transport layer **98**. The platform layer **100** may also translate the data packets into a form that the application layer **102** may use. The application layer **102** may support a software application that may directly interface with the user. As such, the application layer **102** may implement protocols defined by the software application. For example, the software application may provide services such as file transfers, electronic mail, and the like.

Efficient Network Layer

Referring now to FIG. **5**, in one embodiment, the network layer **96** and the transport layer **98** may be configured in a certain manner to form an efficient low power wireless personal network (ELoWPAN) **110**. In one embodiment, the ELoWPAN **110** may be based on an IEEE 802.15.4 network, which may correspond to low-rate wireless personal area networks (LR-WPANs). The ELoWPAN **110** may specify that the network layer **96** may route data between the devices **10** in the home environment **30** using a communication protocol based on Internet Protocol version 6 (IPv6). As such, each device **10** may include a 128-bit IPv6 address that may

17

provide each device **10** with a unique address to use to identify itself over the Internet, a local network around the home environment **30**, or the like.

In one embodiment, the network layer **96** may specify that data may be routed between devices using Routing Information Protocol—Next Generation (RIPng). RIPng is a routing protocol that routes data via a wireless mesh network based on a number of hops between the source node and the destination node. That is, RIPng may determine a route to the destination node from the source node that employs the least number of hops when determining how the data will be routed. In addition to supporting data transfers via a wireless mesh network, RIPng is capable of supporting IPv6 networking traffic. As such, each device **10** may use a unique IPv6 address to identify itself and a unique IPv6 address to identify a destination node when routing data. Additional details with regard to how the RIPng may send data between nodes will be described below with reference to FIG. 6.

As mentioned above, the network layer **96** may also provide a security protocol that may manage the integrity of the data being transferred. Here, the efficient network layer may secure data transferred between devices using a Datagram Transport Layer Security (DTLS) protocol. Generally, Transport Layer Security (TLS) protocol is commonly used to protect data transfers via the Internet. However, in order for the TLS protocol to be effective, the TLS protocol may transport data using a reliable transport channel such as Transmission Control Protocol (TCP). DTLS provides a similar level of security for transferred data while supporting unreliable transport channels such as User Datagram Protocol (UDP). Additional details with regard to the DTLS protocol will be described below with reference to FIGS. 8 and 9.

The network layer **96** depicted in FIG. 5 is characterized herein as the efficient network layer mentioned above. That is, the efficient network layer routes IPv6 data using RIPng and secures the routed data using the DTLS protocol. Since the efficient network layer uses the DTLS protocol to secure data transfer between devices, the transport layer **98** may support TCP and UDP transfer schemes for the data.

Referring now to FIG. 6, FIG. 6 depicts a flowchart of a method **120** that may be used for determining a routing table for each device **10** in the wireless mesh network **80** of FIG. 3 using RIPng. The method **120** may be performed by each device **10** in the home environment **30** such that each device **10** may generate a routing table that indicates how each node in the wireless mesh network **80** may be connected to each other. As such, each device **10** may independently determine how to route data to a destination node. In one embodiment, the processor **20** of the device **10** may perform the method **120** using the network interface **18**. As such, the device **10** may send data associated with the sensor **12** or determined by the processor **18** to other devices **10** in the home environment **30** via network interface **18**.

The following discussion of the method **120** will be described with reference to FIGS. 7A-7D to clearly illustrate various blocks of the method **120**. Keeping this in mind and referring to both FIG. 6 and FIG. 7A, at block **122**, the device **10** may send a request **132** to any other device **10** that may be directly (i.e., zero hops) to the requesting device **10**. The request **132** may include a request for all of the routing information from the respective device **10**. For example, referring to FIG. 7A, the device **10** at node 1 may send the request **132** to the device **10** at node 2 to send all of the routes (i.e., N2's routes) included in node 2's memory.

At block **124**, the requesting device **10** may receive a message from the respective device **10** that may include all of the routes included in the respective memory of the respective

18

device **10**. The routes may be organized in a routing table that may specify how each node in the wireless mesh network **80** may be connected to each other. That is, the routing table may specify which intermediate nodes data may be transferred to such that data from a source node to a destination node. Referring back to the example above and to FIG. 7B, in response to node 1's request for N2's routes, at block **124**, node 2 may send node 1 all of the routes (N2's routes **144**) included in the memory or storage of node 2. In one embodiment, each node of the wireless mesh network **80** may send the request **132** to its adjacent node as shown in FIG. 7A. In response, each node may then send its routes to its adjacent node as shown in FIG. 7B. For instance, FIG. 7B illustrates how each node sends its route data to each adjacent node as depicted with N1's routes **142**, N2's routes **144**, N3's routes **146**, N4's routes **148**, N5's routes **150**, N6's routes **152**, N7's routes **154**, N8's routes **156**, and N9's routes **158**.

Initially, each node may know the nodes in which it may have a direct connection (i.e., zero hops). For example, initially, node 2 may just know that it is directly connected to node 1, node 3, and node 4. However, after receiving N1's routes **142**, N3's routes **146**, and N4's routes **148**, the processor **20** of node 2 may build a routing table that includes all of the information included with N1's routes **142**, N3's routes **146**, and N4's routes **148**. As such, the next time node 2 receives a request for its routes or routing table (i.e., N2's routes **144**), node 2 may send a routing table that includes N1's routes **142**, N2's routes, N3's routes **146**, and N4's routes **148**.

Keeping this in mind and referring back to FIG. 6, at block **126**, the requesting device **10** may update its local routing table to include the routing information received from the adjacent device **10**. In certain embodiments, each device **10** may perform the method **120** periodically such that each device **10** includes an updated routing table that characterizes how each node in the wireless mesh network **80** may be connected to each other. As mentioned above, each time the method **120** is performed, each device **10** may receive additional information from its adjacent device **10** if the adjacent device **10** updated its routing table with the information received from its adjacent devices. As a result, each device **10** may understand how each node in the wireless mesh network **80** may be connected to each other.

FIG. 7C, for example, illustrates a routing table **172** that may have been determined by the device **10** at node 1 using the method **120**. In this example, the routing table **172** may specify each node in the wireless mesh network **80** as a destination node, the intermediate nodes between node 1 and each destination node, and a number of hops between node 1 and the destination node. The number of hops corresponds to a number of times that the data being sent to the destination node may be forwarded to an intermediate node before reaching the destination node. When sending data to a particular destination node, the RIPng routing scheme may select a route that involves the least number of hops. For instance, if node 1 intended to send data to node 9, the RIPng routing scheme would route the data via nodes 2, 4, 5, and 8, which includes four hops, as opposed to routing the data via nodes 2, 4, 6, 7, and 8, which includes five hops.

By using the RIPng routing scheme, each device **10** may independently determine how data should be routed to a destination node. Conventional routing schemes such as "Ripple" Routing Protocol (RPL) used in 6LoWPAN devices, on the other hand, may route data through a central node, which may be the only node that knows the structure of the wireless mesh network. More specifically, the RPL protocol may create a wireless mesh network according to a

directed acyclic graph (DAG), which may be structured as a hierarchy. Located at the top of this hierarchy may include a border router, which may periodically multicasts requests to lower level nodes to determine a rank for each of the node's connections. In essence, when data is transferred from a source node to a destination node, the data may be transferred up the hierarchy of nodes and then back down to the destination node. In this manner, the nodes located higher up the hierarchy may route data more often than the nodes located lower in the hierarchy. Moreover, the border router of the RPL system may also be operating more frequently since it controls how data will be routed via the hierarchy. In the conventional RPL system, in contrast to the RIPng system taught here, some nodes may route data on a more frequent basis simply due to its location within the hierarchy and not due to its location with respect to the source node and the destination node. These nodes that route data more often under the RPL system may consume more energy and thus may not be a suitable to implement with the devices **10** in the home environment **30** that operate using low power. Moreover, as mentioned above, if the border router or any other higher-level node of the RPL system corresponds to the thermostat **46**, the increased data routing activity may increase the heat produced within the thermostat **46**. As a result, the temperature reading of the thermostat **46** may incorrectly represent the temperature of the home environment **30**. Since other devices **10** may perform specific operations based on the temperature reading of the thermostat **46**, and since the thermostat **46** may send commands to various devices **10** based on its temperature reading, it may be beneficial to ensure that the temperature reading of the thermostat **46** is accurate.

In addition to ensuring that none of the devices **10** routes data a disproportionate amount of times, by using the RIPng routing scheme, new devices **10** may be added to the wireless mesh network with minimum effort by the user. For example, FIG. 7D illustrates a new node **10** being added to the wireless mesh network **80**. In certain embodiments, once the node **10** establishes a connection to the wireless mesh network **80** (e.g., via node **4**), the device **10** that corresponds to node **10** may perform the method **120** described above to determine how data may be routed to each node in the wireless mesh network **80**. If each node in the wireless mesh network **80** has already performed the method **120** multiple times, the device **10** at node **10** may receive the entire routing structure of the wireless mesh network **80** from the device **10** at node **4**. In the same manner, devices **10** may be removed from the wireless mesh network **80** and each node may update its routing table with relative ease by performing the method **120** again.

After establishing a routing scheme using the RIPng routing scheme, ELoWPAN **110** may employ a DTLS protocol to secure data communications between each device **10** in the home environment **30**. As mentioned above, by using the DTLS protocol instead of a TLS protocol, ELoWPAN **110** may enable the transport layer **98** to send data via TCP and UDP. Although UDP may be generally more unreliable as compared to TCP, UDP data transfers employs a simple communication scheme without having dedicated transmissions channels or data paths set up prior to use. As such, new devices **10** added to the wireless mesh network **80** may use UDP data transfers to effectively communicate to other devices **10** in the wireless mesh network more quickly. Moreover, UDP data transfers generally use less energy by the device **10** that is sending or forwarding the data since there is no guarantee of delivery. As such, the devices **10** may send non-critical data (e.g., presence of a person in a room) using the UDP data transfer, thereby saving energy within the device **10**. However, critical data (e.g., smoke alarm) may be

sent via TCP data transfer to ensure that the appropriate party receives the data. To reiterate, using a DTLS security scheme with ELoWPAN **110** may help facilitate UDP and TCP data transfers.

Keeping the foregoing in mind, ELoWPAN **110** may employ the DTLS protocol to secure the data communicated between the devices **10**. In one embodiment, the DTLS protocol may secure data transfers using a handshake protocol. Generally, the handshake protocol may authenticate each communicating device using a security certificate that may be provided by each device **10**. FIG. 8 illustrates an example of a manufacturing process **190** that depicts how the security certificate may be embedded within the device **10**.

Referring to FIG. 8, a trusted manufacturer **192** of the device **10** may be provided with a number of security certificates that it may use for each manufactured device. As such, while producing a device **10** that may be used in the home environment **30** and coupled to the wireless mesh network **80**, the trusted manufacturer **192** may embed a certificate **194** into the device **10** during the manufacturing process **190**. That is, the certificate **194** may be embedded into the hardware of the device **10** during manufacturing of the device **10**. The certificate **194** may include a public key, a private key, or other cryptographic data that may be used to authenticate different communicating devices within the wireless mesh network **80**. As a result, once a user receives the device **10**, the user may integrate the device **10** into the wireless mesh network **80** without initializing or registering the device **10** with a central security node or the like.

In conventional data communication security protocols such as Protocol for Carrying Authentication for Network Access (PANA) used in 6LoWPAN devices, each device **10** may authenticate itself with a specific node (i.e., authentication agent). As such, before data is transferred between any two devices **10**, each device **10** may authenticate itself with the authentication agent node. The authentication agent node may then convey the result of the authentication to an enforcement point node, which may be co-located with the authentication agent node. The enforcement point node may then establish a data communication link between the two devices **10** if the authentications are valid. Moreover, in PANA, each device **10** may communicate with each other via an enforcement point node, which may verify that the authentication for each device **10** is valid.

As such, by using the DTLS protocol rather than PANA to secure data transfers between nodes, the efficient network layer may avoid using an authorization agent node, an enforcement point node, or both excessively. That is, no one node using the efficient network layer may be processing authentication data for each data transfer between nodes in the wireless mesh network. As a result, the nodes using the efficient network layer may conserve more energy as compared to the authorization agent node or the enforcement point node in the PANA protocol system.

Keeping this in mind, FIG. 9 illustrates an example handshake protocol **200** that may be used between devices **10** when transferring data between each other. As shown in FIG. 9, the device **10** at node **1** may send a message **202** to the device **10** at node **2**. The message **202** may be a hello message that may include cipher suites, hash and compression algorithms, and a random number. The device **10** at node **2** may then respond with a message **204**, which may verify that the device **10** at node **2** received the message **202** from the device **10** at node **1**.

After establishing the connection between node **1** and node **2**, the device at node **1** may again send the message **202** to the device **10** at node **2**. The device **10** at node **2** may then respond

21

with a message **208**, which may include a hello message from node 2, a certificate **194** from node 2, a key exchange from node 2, and a certificate request for node 1. The hello message in the message **208** may include cipher suites, hash and compression algorithms, and a random number. The certificate **194** may be the security certificate embedded within the device **10** by the trusted manufacturer **192** as discussed above with reference to FIG. 8. The key exchange may include a public key, a private key, or other cryptographic information that may be used to determine a secret key for establishing a communication channel between the two nodes. In one embodiment, the key exchange may be stored in the certificate **194** of the corresponding device **10** located at the respective node.

In response to the message **208**, the device **10** at node 1 may send message **210** that may include a certificate **194** from node 1, a key exchange from node 1, a certificate verification of node 2, and a change cipher spec from node 1. In one embodiment, the device **10** at node 1 may use the certificate **194** of node 2 and the key exchange from node 1 to verify the certificate **194** of node 2. That is, the device **10** at node 1 may verify that the certificate **194** received from node 2 is valid based on the certificate **194** of node 2 and the key exchange from node 1. If the certificate **194** from node 2 is valid, the device **10** at node 1 may send the change cipher spec message to the device **10** at node 2 to announce that the communication channel between the two nodes is secure.

Similarly, upon receiving the message **210**, the device **10** at node 2 may use the certificate **194** of node 1 and the key exchange from node 2 to verify the certificate **194** of node 1. That is, the device **10** at node 2 may verify that the certificate **194** received from node 1 is valid based on the certificate **194** of node 1 and the key exchange from node 2. If the certificate **194** from node 1 is valid, the device **10** at node 2 may also send the change cipher spec message to the device **10** at node 1 to announce that the communication channel between the two nodes is secure.

After establishing that the communication channel is secure, the device **10** at node 1 may send a group-wise network key **214** to the device **10** at node 2. The group-wise network key **214** may be associated with the ELoWPAN **110**. In this manner, as new devices join the ELoWPAN **110**, devices previously authorized to communicate within the ELoWPAN **110** may provide the new devices access to the ELoWPAN **110**. That is, the devices previously authorized to communicate within the ELoWPAN **110** may provide the group-wise network key **214** to the new devices, which may enable the new devices to communicate with other devices in the ELoWPAN **110**. For example, the group-wise network key **214** may be used to communicate with other devices that have been properly authenticated and that have previously provided with the group-wise network key **214**. In one embodiment, once the change cipher spec message has been exchanged between the device **10** at node 1 and the device **10** at node 2, identification information such as model number, device capabilities, and the like may be communicated between the devices. However, after the device **10** at node 2 receives the group-wise network key **214**, additional information such as data from sensors disposed on the device **10**, data analysis performed by the device **10**, and the like may be communicated between devices.

By embedding the security certificate within the device **10** during the manufacturing process, the device **10** may not involve the user with establishing security or authentication processes for the device **10**. Moreover, since the device **10** may ensure that data is securely transferred between nodes based on a handshake protocol as opposed to a central authentication agent node, the security of the data transfers in the wireless mesh network **80** may not rely on a single node for security. Instead, the efficient network layer may ensure that data may be securely transferred between nodes even when some node becomes unavailable. As such, the efficient network layer may be much less vulnerable to security issues since it does not rely on a single node for securing data messages.

22

Efficient Platform and/or Application Layers

Using the above-described ELoWPAN **110** and/or any other suitable IPv6 logical networks, efficient platform and/or application layers may be used to generate a fabric of devices in a home environment or similar environments. The fabric of devices may enable many generally local devices to communicate, sharing data and information, invoking methods on one another, parametrically providing software updates through the network, and generally communicating messages in an efficient, power-conscious way.

Fabric—Device Interconnection

As discussed above, a fabric may be implemented using one or more suitable communications protocols, such as IPv6 protocols. In fact, the fabric may be partially or completely agnostic to the underlying technologies (e.g., network types or communication protocols) used to implement the fabric. Within the one or more communications protocols, the fabric may be implemented using one or more network types used to communicatively couple electrical devices using wireless or wired connections. For example, certain embodiments of the fabric may include Ethernet, WiFi, 802.15.4, ZigBee®, ISA100.11a, WirelessHART, MiWi™, power-line networks, and/or other suitable network types. Within the fabric devices (e.g., nodes) can exchange packets of information with other devices (e.g., nodes) in the fabric, either directly or via intermediary nodes, such as intelligent thermostats, acting as IP routers. These nodes may include manufacturer devices (e.g., thermostats and smoke detectors) and/or customer devices (e.g., phones, tablets, computers, etc.). Additionally, some devices may be “always on” and continuously powered using electrical connections. Other devices may have partially reduced power usage (e.g., medium duty cycle) using a reduced/intermittent power connection, such as a thermostat or doorbell power connection. Finally, some devices may have a short duty cycle and run solely on battery power. In other words, in certain embodiments, the fabric may include heterogeneous devices that may be connected to one or more sub-networks according to connection type and/or desired power usage. FIGS. 10-12 illustrate three embodiments that may be used to connect electrical devices via one or more sub-networks in the fabric.

A. Single Network Topology

FIG. 10 illustrates an embodiment of the fabric **1000** having a single network topology. As illustrated, the fabric **1000** includes a single logical network **1002**. The network **1002** could include Ethernet, WiFi, 802.15.4, power-line networks, and/or other suitable network types in the IPv6 protocols. In fact, in some embodiments where the network **1002** includes a WiFi or Ethernet network, the network **1002** may span multiple WiFi and/or Ethernet segments that are bridged at a link layer.

The network **1002** includes one or more nodes **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, and **1016**, referred to collectively as **1004-1016**. Although the illustrated network **1002** includes seven nodes, certain embodiments of the network **1002** may include one or more nodes interconnected using the network **1002**. Moreover, if the network **1002** is a WiFi network, each

of the nodes **1004-1016** may be interconnected using the node **1016** (e.g., WiFi router) and/or paired with other nodes using WiFi Direct (i.e., WiFi P2P).

B. Star Network Topology

FIG. **11** illustrates an alternative embodiment of fabric **1000** as a fabric **1018** having a star network topology. The fabric **1018** includes a hub network **1020** that joins together two periphery networks **1022** and **1024**. The hub network **1020** may include a home network, such as WiFi/Ethernet network or power line network. The periphery networks **1022** and **1024** may include additional network connection types different of different types than the hub network **1020**. For example, in some embodiments, the hub network **1020** may be a WiFi/Ethernet network, the periphery network **1022** may include an 802.15.4 network, and the periphery network **1024** may include a power line network, a ZigBee® network, a ISA100.11a network, a WirelessHART network, or a MiWi™ network. Moreover, although the illustrated embodiment of the fabric **1018** includes three networks, certain embodiments of the fabric **1018** may include any number of networks, such as 2, 3, 4, 5, or more networks. In fact, some embodiments of the fabric **1018** include multiple periphery networks of the same type.

Although the illustrated fabric **1018** includes fourteen nodes, each referred to individually by reference numbers **1024-1052**, respectively, it should be understood that the fabric **1018** may include any number of nodes. Communication within each network **1020**, **1022**, or **1024**, may occur directly between devices and/or through an access point, such as node **1042** in a WiFi/Ethernet network. Communications between periphery network **1022** and **1024** passes through the hub network **1020** using inter-network routing nodes. For example, in the illustrated embodiment, nodes **1034** and **1036** are connected to the periphery network **1022** using a first network connection type (e.g., 802.15.4) and to the hub network **1020** using a second network connection type (e.g., WiFi) while the node **1044** is connected to the hub network **1020** using the second network connection type and to the periphery network **1024** using a third network connection type (e.g., power line). For example, a message sent from node **1026** to node **1052** may pass through nodes **1028**, **1030**, **1032**, **1036**, **1042**, **1044**, **1048**, and **1050** in transit to node **1052**.

C. Overlapping Networks Topology

FIG. **12** illustrates an alternative embodiment of the fabric **1000** as a fabric **1054** having an overlapping networks topology. The fabric **1054** includes networks **1056** and **1058**. As illustrated, each of the nodes **1062**, **1064**, **1066**, **1068**, **1070**, and **1072** may be connected to each of the networks. In other embodiments, the node **1072** may include an access point for an Ethernet/WiFi network rather than an end point and may not be present on either the network **1056** or network **1058**, whichever is not the Ethernet/WiFi network. Accordingly, a communication from node **1062** to node **1068** may be passed through network **1056**, network **1058**, or some combination thereof. In the illustrated embodiment, each node can communicate with any other node via any network using any network desired. Accordingly, unlike the star network topology of FIG. **11**, the overlapping networks topology may communicate directly between nodes via any network without using inter-network routing.

D. Fabric Network Connection to Services

In addition to communications between devices within the home, a fabric (e.g., fabric **1000**) may include services that may be located physically near other devices in the fabric or physically remote from such devices. The fabric connects to these services through one or more service end points. FIG.

13 illustrates an embodiment of a service **1074** communicating with fabrics **1076**, **1078**, and **1080**. The service **1074** may include various services that may be used by devices in fabrics **1076**, **1078**, and/or **1080**. For example, in some embodiments, the service **1074** may be a time of day service that supplies a time of day to devices, a weather service to provide various weather data (e.g., outside temperature, sunset, wind information, weather forecast, etc.), an echo service that “pings” each device, data management services, device management services, and/or other suitable services. As illustrated, the service **1074** may include a server **1082** (e.g., web server) that stores/accesses relevant data and passes the information through a service end point **1084** to one or more end points **1086** in a fabric, such as fabric **1076**. Although the illustrated embodiment only includes three fabrics with a single server **1082**, it should be appreciated that the service **1074** may connect to any number of fabrics and may include servers in addition to the server **1082** and/or connections to additional services.

In certain embodiments, the service **1074** may also connect to a consumer device **1088**, such as a phone, tablet, and/or computer. The consumer device **1088** may be used to connect to the service **1074** via a fabric, such as fabric **1076**, an Internet connection, and/or some other suitable connection method. The consumer device **1088** may be used to access data from one or more end points (e.g., electronic devices) in a fabric either directly through the fabric or via the service **1074**. In other words, using the service **1074**, the consumer device **1088** may be used to access/manage devices in a fabric remotely from the fabric.

E. Communication Between Devices in a Fabric

As discussed above, each electronic device or node may communicate with any other node in the fabric, either directly or indirectly depending upon fabric topology and network connection types. Additionally, some devices (e.g., remote devices) may communicate through a service to communicate with other devices in the fabric. FIG. **14** illustrates an embodiment of a communication **1090** between two devices **1092** and **1094**. The communication **1090** may span one or more networks either directly or indirectly through additional devices and/or services, as described above. Additionally, the communication **1090** may occur over an appropriate communication protocol, such as IPv6, using one or more transport protocols. For example, in some embodiments the communication **1090** may include using the transmission control protocol (TCP) and/or the user datagram protocol (UDP). In some embodiments, the device **1092** may transmit a first signal **1096** to the device **1094** using a connectionless protocol (e.g., UDP). In certain embodiments, the device **1092** may communicate with the device **1094** using a connection-oriented protocol (e.g., TCP). Although the illustrated communication **1090** is depicted as a bi-directional connection, in some embodiments, the communication **1090** may be a uni-directional broadcast.

i. Unique Local Address

As discussed above, data transmitted within a fabric received by a node may be redirected or passed through the node to another node depending on the desired target for the communication. In some embodiments, the transmission of the data may be intended to be broadcast to all devices. In such embodiments, the data may be retransmitted without further processing to determine whether the data should be passed along to another node. However, some data may be

directed to a specific endpoint. To enable addressed messages to be transmitted to desired endpoints, nodes may be assigned identification information.

Each node may be assigned a set of link-local addresses (LLA), one assigned to each network interface. These LLAs may be used to communicate with other nodes on the same network. Additionally, the LLAs may be used for various communication procedures, such as IPv6 Neighbor Discovery Protocol. In addition to LLAs, each node may be assigned a unique local address (ULA). In some embodiments, this may be referred to as an Extended Unique Local Address (EULA) because it contains information regarding the fabric of devices as well as a preferred network over which to reach a device through the fabric.

FIG. 15 illustrates an embodiment of a unique local address (ULA) **1098** that may be used to address each node in the fabric. In certain embodiments, the ULA **1098** may be formatted as an IPv6 address format containing 128 bits divided into a global ID **1100**, a subnet ID **1102**, and an interface ID **1104**. The global ID **1100** includes 40 bits and the subnet ID **1102** includes 16 bits. The global ID **1100** and subnet ID **1102** together form a fabric ID **1103** for the fabric.

The fabric ID **1103** is a unique 64-bit identifier used to identify a fabric. The fabric ID **1103** may be generated at creation of the associated fabric using a pseudo-random algorithm. For example, the pseudo-random algorithm may 1) obtain the current time of day in 64-bit NTP format, 2) obtain the interface ID **1104** for the device, 3) concatenate the time of day with the interface ID **1104** to create a key, 4) compute and SHA-1 digest on the key resulting in 160 bits, 5) use the least significant 40 bits as the global ID **1100**, and 6) concatenate the ULA and set the least significant bit to 1 to create the fabric ID **1103**. In certain embodiments, once the fabric ID **1103** is created with the fabric, the fabric ID **1103** remains until the fabric is dissolved.

The global ID **1100** identifies the fabric to which the node belongs. The subnet ID **1102** identifies logical networks within the fabric. The subnet ID **1102** may be assigned monotonically starting at one with the addition of each new logical network to the fabric. For example, a WiFi network may be identified with a hex value of 0x01, and a later connected 802.15.4 network may be identified with a hex value of 0x02 continuing on incrementally upon the connection of each new network to the fabric.

Finally, the ULA **1098** includes an interface ID **1104** that includes 64 bits. The interface ID **1104** may be assigned using a globally-unique 64-bit identifier according to the IEEE EUI-64 standard. For example, devices with IEEE 802 network interfaces may derive the interface ID **1104** using a burned-in MAC address for the devices "primary interface." In some embodiments, the designation of which interface is the primary interface may be determined arbitrarily. In other embodiments, an interface type (e.g., WiFi) may be deemed the primary interface, when present. If the MAC address for the primary interface of a device is 48 bits rather than 64-bit, the 48-bit MAC address may be converted to a EUI-64 value via encapsulation (e.g., organizationally unique identifier encapsulating). In consumer devices (e.g., phones or computers), the interface ID **1104** may be assigned by the consumer devices' local operating systems.

ii. Routing Transmissions Between Logical Networks

As discussed above in relation to a star network topology, inter-network routing may occur in communication between two devices across logical networks. In some embodiments,

inter-network routing is based on the subnet ID **1102**. Each inter-networking node (e.g., node **1034** of FIG. 11) may maintain a list of other routing nodes (e.g., node **B 14** of FIG. 11) on the hub network **1020** and their respective attached periphery networks (e.g., periphery network **1024** of FIG. 11). When a packet arrives addressed to a node other than the routing node itself, the destination address (e.g., address for node **1052** of FIG. 11) is compared to the list of network prefixes and a routing node (e.g., node **1044**) is selected that is attached to the desired network (e.g., periphery network **1024**). The packet is then forwarded to the selected routing node. If multiple nodes (e.g., **1034** and **1036**) are attached to the same periphery network, routing nodes are selected in an alternating fashion.

Additionally, inter-network routing nodes may regularly transmit Neighbor Discovery Protocol (NDP) router advertisement messages on the hub network to alert consumer devices to the existence of the hub network and allow them to acquire the subnet prefix. The router advertisements may include one or more route information options to assist in routing information in the fabric. For example, these route information options may inform consumer devices of the existence of the periphery networks and how to route packets the periphery networks.

In addition to, or in place of route information options, routing nodes may act as proxies to provide a connection between consumer devices and devices in periphery networks, such as the process **1105** as illustrated in FIG. 16. As illustrated, the process **1105** includes each periphery network device being assigned a virtual address on the hub network by combining the subnet ID **1102** with the interface ID **1104** for the device on the periphery network (block **1106**). To proxy using the virtual addresses, routing nodes maintain a list of all periphery nodes in the fabric that are directly reachable via one of its interfaces (block **1108**). The routing nodes listen on the hub network for neighbor solicitation messages requesting the link address of a periphery node using its virtual address (block **1110**). Upon receiving such a message, the routing node attempts to assign the virtual address to its hub interface after a period of time (block **1112**). As part of the assignment, the routing node performs duplicate address detection so as to block proxying of the virtual address by more than one routing node. After the assignment, the routing node responds to the neighbor solicitation message and receives the packet (block **1114**). Upon receiving the packet, the routing node rewrites the destination address to be the real address of the periphery node (block **1116**) and forwards the message to the appropriate interface (block **1118**).

iii. Consumer Devices Connecting to a Fabric

To join a fabric, a consumer device may discover an address of a node already in the fabric that the consumer device wants to join. Additionally, if the consumer device has been disconnected from a fabric for an extended period of time may need to rediscover nodes on the network if the fabric topology/layout has changed. To aid in discovery/rediscovery, fabric devices on the hub network may publish Domain Name System-Service Discovery (DNS-SD) records via mDNS that advertise the presence of the fabric and provide addresses to the consumer device.

Data Transmitted in the Fabric

After creation of a fabric and address creation for the nodes, data may be transmitted through the fabric. Data passed through the fabric may be arranged in a format common to all messages and/or common to specific types of conversations in the fabric. In some embodiments, the mes-

sage format may enable one-to-one mapping to JavaScript Object Notation (JSON) using a TLV serialization format discussed below. Additionally, although the following data frames are described as including specific sizes, it should be noted that lengths of the data fields in the data frames may be varied to other suitable bit-lengths.

A. Security

Along with data intended to be transferred, the fabric may transfer the data with additional security measures such as encryption, message integrity checks, and digital signatures. In some embodiments, a level of security supported for a device may vary according to physical security of the device and/or capabilities of the device. In certain embodiments, messages sent between nodes in the fabric may be encrypted using the Advanced Encryption Standard (AES) block cipher operating in counter mode (AES-CTR) with a 128-bit key. As discussed below, each message contains a 32-bit message id. The message id may be combined with a sending nodes id to form a nonce for the AES-CTR algorithm. The 32-bit counter enables 4 billion messages to be encrypted and sent by each node before a new key is negotiated.

In some embodiments, the fabric may insure message integrity using a message authentication code, such as HMAC-SHA-1, that may be included in each encrypted message. In some embodiments, the message authentication code may be generated using a 160-bit message integrity key that is paired one-to-one with the encryption key. Additionally, each node may check the message id of incoming messages against a list of recently received ids maintained on a node-by-node basis to block replay of the messages.

B. Tag Length Value (TLV) Formatting

To reduce power consumption, it is desirable to send at least a portion of the data sent over the fabric that compactly while enabling the data containers to flexibly represents data that accommodates skipping data that is not recognized or understood by skipping to the next location of data that is understood within a serialization of the data. In certain embodiments, tag-length-value (TLV) formatting may be used to compactly and flexibly encode/decode data. By storing at least a portion of the transmitted data in TLV, the data may be compactly and flexibly stored/sent along with low encode/decode and memory overhead, as discussed below in reference to Table 7. In certain embodiments, TLV may be used for some data as flexible, extensible data, but other portions of data that is not extensible may be stored and sent in a understood standard protocol data unit (PDU).

Data formatted in a TLV format may be encoded as TLV elements of various types, such as primitive types and container types. Primitive types include data values in certain formats, such as integers or strings. For example, the TLV format may encode: 1, 2, 3, 4, or 8 byte signed/unsigned integers, UTF-8 strings, byte strings, single/double-precision floating numbers (e.g., IEEE 754-1985 format), boolean, null, and other suitable data format types. Container types include collections of elements that are then sub-classified as container or primitive types. Container types may be classified into various categories, such as dictionaries, arrays, paths or other suitable types for grouping TLV elements, known as members. A dictionary is a collection of members each having distinct definitions and unique tags within the dictionary. An array is an ordered collection of members with implied definitions or no distinct definitions. A path is an ordered collection of members that described how to traverse a tree of TLV elements.

As illustrated in FIG. 11, an embodiment of a TLV packet 1120 includes three data fields: a tag field 1122, a length field 1124, and a value field 1126. Although the illustrated fields

1122, 1124, and 1126 are illustrated as approximately equivalent in size, the size of each field may be variable and vary in size in relation to each other. In other embodiments, the TLV packet 1120 may further include a control byte before the tag field 1122.

In embodiments having the control byte, the control byte may be sub-divided into an element type field and a tag control field. In some embodiments, the element type field includes 5 lower bits of the control byte and the tag control field occupies the upper 3 bits. The element type field indicates the TLV element's type as well as the how the length field 1124 and value field 1126 are encoded. In certain embodiments, the element type field also encodes Boolean values and/or null values for the TLV. For example, an embodiment of an enumeration of element type field is provided in Table 1 below.

TABLE 1

Example element type field values.								
7	6	5	4	3	2	1	0	
			0	0	0	0	0	Signed Integer, 1byte value value
			0	0	0	0	1	Signed Integer, 2byte value
			0	0	0	1	0	Signed Integer, 4byte value
			0	0	0	1	1	Signed Integer, 8byte value
			0	0	1	0	0	Unsigned Integer, 1byte value
			0	0	1	0	1	Unsigned Integer, 2byte value
			0	0	1	1	0	Unsigned Integer, 4byte value
			0	0	1	1	1	Unsigned Integer, 8byte value
			0	1	0	0	0	Boolean False
			0	1	0	0	1	Boolean True
			0	1	0	1	0	Floating Point Number, 4byte value
			0	1	0	1	1	Floating Point Number, 8byte value
			0	1	1	0	0	UTF8-String, 1byte length
			0	1	1	0	1	UTF8-String, 2byte length
			0	1	1	1	0	UTF8-String, 4byte length
			0	1	1	1	1	UTF8-String, 8byte length
			1	0	0	0	0	Byte String, 1byte length
			1	0	0	0	1	Byte String, 2byte length
			1	0	0	1	0	Byte String, 4byte length
			1	0	0	1	1	Byte String, 8byte length
			1	0	1	0	0	Null
			1	0	1	0	1	Dictionary
			1	0	1	1	0	Array
			1	0	1	1	1	Path
			1	1	0	0	0	End of Container

The tag control field indicates a form of the tag in the tag field 1122 assigned to the TLV element (including a zero-length tag). Examples, of tag control field values are provided in Table 2 below.

TABLE 2

Example values for tag control field.							
7	6	5	4	3	2	1	0
0	0	0					Anonymous, 0 bytes
0	0	1					Context-specific Tag, 1 byte
0	1	0					Core Profile Tag, 2 bytes
0	1	1					Core Profile Tag, 4 bytes
1	0	0					Implicit Profile Tag, 2 bytes
1	0	1					Implicit Profile Tag, 4 bytes
1	1	0					Fully-qualified Tag, 6 bytes
1	1	1					Fully-qualified Tag, 8 bytes

In other words, in embodiments having a control byte, the control byte may indicate a length of the tag.

In certain embodiments, the tag field 1122 may include zero to eight bytes, such as eight, sixteen, thirty two, or sixty

29

four bits. In some embodiments, the tag of the tag field may be classified as profile-specific tags or context-specific tags. Profile-specific tags identify elements globally using a vendor Id, a profile Id, and/or tag number as discussed below. Context-specific tags identify TLV elements within a context of a containing dictionary element and may include a single-byte tag number. Since context-specific tags are defined in context of their containers, a single context-specific tag may have different interpretations when included in different containers. In some embodiments, the context may also be derived from nested containers.

In embodiments having the control byte, the tag length is encoded in the tag control field and the tag field **1122** includes a possible three fields: a vendor Id field, a profile Id field, and a tag number field. In the fully-qualified form, the encoded tag field **1122** includes all three fields with the tag number field including 16 or 32 bits determined by the tag control field. In the implicit form, the tag includes only the tag number, and the vendor Id and profile number are inferred from the protocol context of the TLV element. The core profile form includes profile-specific tags, as discussed above. Context-specific tags are encoded as a single byte conveying the tag number. Anonymous elements have zero-length tag fields **1122**.

In some embodiments without a control byte, two bits may indicate a length of the tag field **1122**, two bits may indicate a length of the length field **1124**, and four bits may indicate a type of information stored in the value field **1126**. An example of possible encoding for the upper 8 bits for the tag field is illustrated below in Table 3.

TABLE 3

Tag field of a TLV packet							
Byte	7	6	5	4	3	2	1 0 Description
0	0	—	—	—	—	—	— Tag is 8 bits
0	1	—	—	—	—	—	— Tag is 16 bits
1	0	—	—	—	—	—	— Tag is 32 bits
1	1	—	—	—	—	—	— Tag is 64 bits
—	—	0	0	—	—	—	— Length is 8 bits
—	—	0	1	—	—	—	— Length is 16 bits
—	—	1	0	—	—	—	— Length is 32 bits
—	—	1	1	—	—	—	— Length is 64 bits
—	—	—	—	0	0	0	0 Boolean
—	—	—	—	0	0	0	1 Fixed 8-bit Unsigned
—	—	—	—	0	0	1	0 Fixed 8-bit Signed
—	—	—	—	0	0	1	1 Fixed 16-bit Unsigned
—	—	—	—	0	1	0	0 Fixed 16-bit Signed
—	—	—	—	0	1	0	1 Fixed 32-bit Unsigned
—	—	—	—	0	1	1	0 Fixed 32-bit Signed
—	—	—	—	0	1	1	1 Fixed 64-bit Unsigned
—	—	—	—	1	0	0	0 Fixed 64-bit Signed
—	—	—	—	1	0	0	1 32-bit Floating Point
—	—	—	—	1	0	1	0 64-bit Floating Point
—	—	—	—	1	0	1	1 UTF-8 String
—	—	—	—	1	1	0	0 Opaque Data
—	—	—	—	1	1	0	1 Container

As illustrated in Table 3, the upper 8 bits of the tag field **1122** may be used to encode information about the tag field **1122**, length field **1124**, and the value field **1126**, such that the tag field **112** may be used to determine length for the tag field **122** and the length fields **1124**. Remaining bits in the tag field **1122** may be made available for user-allocated and/or user-assigned tag values.

The length field **1124** may include eight, sixteen, thirty two, or sixty four bits as indicated by the tag field **1122** as illustrated in Table 3 or the element field as illustrated in Table

30

2. Moreover, the length field **1124** may include an unsigned integer that represents a length of the encoded in the value field **1126**. In some embodiments, the length may be selected by a device sending the TLV element. The value field **1126** includes the payload data to be decoded, but interpretation of the value field **1126** may depend upon the tag length fields, and/or control byte. For example, a TLV packet without a control byte including an 8 bit tag is illustrated in Table 4 below for illustration.

TABLE 4

Example of a TLV packet including an 8-bit tag			
Tag	Length	Value	Description
0x0d	0x24		
0x09	0x04	0x42 95 00 00	74.5
0x09	0x04	0x42 98 66 66	76.2
0x09	0x04	0x42 94 99 9a	74.3
0x09	0x04	0x42 98 99 9a	76.3
0x09	0x04	0x42 95 33 33	74.6
0x09	0x04	0x42 98 33 33	76.1

As illustrated in Table 4, the first line indicates that the tag field **1122** and the length field **1124** each have a length of 8 bits. Additionally, the tag field **1122** indicates that the tag type is for the first line is a container (e.g., the TLV packet). The tag field **1124** for lines two through six indicate that each entry in the TLV packet has a tag field **1122** and length field **1124** consisting of 8 bits each. Additionally, the tag field **1124** indicates that each entry in the TLV packet has a value field **1126** that includes a 32-bit floating point. Each entry in the value field **1126** corresponds to a floating number that may be decoded using the corresponding tag field **1122** and length field **1124** information. As illustrated in this example, each entry in the value field **1126** corresponds to a temperature in Fahrenheit. As can be understood, by storing data in a TLV packet as described above, data may be transferred compactly while remaining flexible for varying lengths and information as may be used by different devices in the fabric. Moreover, in some embodiments, multi-byte integer fields may be transmitted in little-endian order or big-endian order.

By transmitting TLV packets in using an order protocol (e.g., little-endian) that may be used by sending/receiving device formats (e.g., JSON), data transferred between nodes may be transmitted in the order protocol used by at least one of the nodes (e.g., little endian). For example, if one or more nodes include ARM or ix86 processors, transmissions between the nodes may be transmitted using little-endian byte ordering to reduce the use of byte reordering. By reducing the inclusion of byte reordering, the TLV format enable devices to communicate using less power than a transmission that uses byte reordering on both ends of the transmission. Furthermore, TLV formatting may be specified to provide a one-to-one translation between other data storage techniques, such as JSON+ Extensible Markup Language (XML). As an example, the TLV format may be used to represent the following XML Property List:

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple Computer/DTD PLIST 1.0/EN"
"http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>
  <key>OfflineMode</key>
  <false/>
  <key>Network</key>

```

31

-continued

```

<dict>
  <key>IPv4</key>
  <dict>
    <key>Method</key>
    <string>dhcp</string>
  </dict>
  <key>IPv6</key>
  <dict>
    <key>Method</key>
    <string>auto</string>
  </dict>
</dict>
<key>Technologies</key>
<dict>
  <key>wifi</key>
  <dict>
    <key>Enabled</key>
    <true/>
    <key>Devices</key>
    <dict>
      <key>wifi_18b4300008b027</key>
      <dict>
        <key>Enabled</key>
        <true/>
      </dict>
    </dict>
  </dict>
  <key>Services</key>
  <array>
    <string>wifi_18b4300008b027_3939382d33204
    16c70696e652054657 272616365</string>
  </array>
</dict>
<key>802.15.4</key>
<dict>
  <key>Enabled</key>
  <true/>
  <key>Devices</key>
  <dict>
    <key>802.15.4_18b4300000002fac4</key>
    <dict>
      <key>Enabled</key>
      <true/>
    </dict>
  </dict>
  <key>Services</key>
  <array>
    <string>802.15.4_18b4300000002fac4_3
    939382d3320416c70696e6520546572</string>
  </array>
</dict>
</dict>
<key>Services</key>
<dict>
  <key>wifi_18b4300008b027_3939382d3320416c70696e6520546572
  72616365</key>
  <dict>
    <key>Name</key>
    <string>998-3 Alpine Terrace</string>
    <key>SSID</key>
    <data>3939382d3320416c70696e652054657272616365
    </data>
    <key>Frequency</key>
    <integer>2462</integer>
    <key>AutoConnect</key>
    <true/>
    <key>Favorite</key>
    <true/>
    <key>Error</key>
    <string/>
    <key>Network</key>
    <dict>
      <key>IPv4</key>
      <dict>
        <key>DHCP</key>
        <dict>
          <key>LastAddress</key>
          <data>0a02001e</data>
        </dict>
      </dict>
    </dict>
  </dict>
</dict>

```

32

-continued

```

    <key>IPv6</key>
    <dict/>
  </dict>
</dict>
<key>802.15.4_18b4300000002fac4_3939382d3320416c70696e
6520546572</key>
<dict>
  <key>Name</key>
  <string>998-3 Alpine Ter</string>
  <key>EPANID</key>
  <data>3939382d3320416c70696e6520546572</data>
  <key>Frequency</key>
  <integer>2412</integer>
  <key>AutoConnect</key>
  <true/>
  <key>Favorite</key>
  <true/>
  <key>Error</key>
  <string/>
  <key>Network</key>
  <dict/>
</dict>
</dict>
</plist>

```

35 As an example, the above property list may be represented in tags of the above described TLV format (without a control byte) according to Table 5 below.

TABLE 5

Example representation of the XML Property List in TLV format			
	XML Key	Tag Type	Tag Number
45	OfflineMode	Boolean	1
	IPv4	Container	3
	IPv6	Container	4
	Method	String	5
50	Technologies	Container	6
	WiFi	Container	7
	802.15.4	Container	8
	Enabled	Boolean	9
55	Devices	Container	10
	ID	String	11
	Services	Container	12
	Name	String	13
60	SSID	Data	14
	EPANID	Data	15
	Frequency	16-bit Unsigned	16
	AutoConnect	Boolean	17
65	Favorite	Boolean	18
	Error	String	19
	DHCP	String	20
	LastAddress	Data	21
70	Device	Container	22
	Service	Container	23

65 Similarly, Table 6 illustrates an example of literal tag, length, and value representations for the example XML Property List.

TABLE 6

Example of literal values for tag, length, and value fields for XML Property List			
Tag	Length	Value	Description
0x40 01	0x01	0	OfflineMode
0x4d 02	0x14		Network
0x4d 03	0x07		Network.IPv4
0x4b 05	0x04	"dhcp"	Network.IPv4.Method
0x4d 04	0x07		Network.IPv6
0x4b 05	0x04	"auto"	Network.IPv6.Method
0x4d 06	0xd6		Technologies
0x4d 07	0x65		Technologies.wifi
0x40 09	0x01	1	Technologies.wifi.Enabled
0x4d 0a	0x5e		Technologies.wifi.Devices
0x4d 16	0x5b		Technologies.wifi.Devices.Device.[0]
0x4b 0b	0x13	"wifi_18b43 . . ."	Technologies.wifi.Devices.Device.[0].ID
0x40 09	0x01	1	Technologies.wifi.Devices.Device.[0].Enabled
0x4d 0c	0x3e		Technologies.wifi.Devices.Device.[0].Services
0x0b	0x 3c	"wifi_18b43 . . ."	Technologies.wifi.Devices.Device.[0].Services.[0]
0x4d 08	0x6b		Technologies.802.15.4
0x40 09	0x01	1	Technologies.802.15.4.Enabled
0x4d 0a	0x64		Technologies.802.15.4.Devices
0x4d 16	0x61		Technologies.802.15.4.Devices.Device.[0]
0x4b 0b	0x1a	"802.15.4_18 . . ."	Technologies.802.15.4.Devices.Device.[0].ID
0x40 09	0x01	1	Technologies.802.15.4.Devices.Device.[0].Enabled
0x4d 0c	0x3d		Technologies.802.15.4.Devices.Device.[0].Services
0x0b	0x 3b	"802.15.4_18 . . ."	Technologies.802.15.4.Devices.Device.[0].Services.[0]
0x4d 0c	0xcb		Services
0x4d 17	0x75		Services.Service.[0]
0x4b 0b	0x13	"wifi_18b43 . . ."	Services.Service.[0].ID
0x4b 0d	0x14	"998-3 Alp . . ."	Services.Service.[0].Name
0x4c 0f	0x28	3939382d . . .	Services.Service.[0].SSID
0x45 10	0x02	2462	Services.Service.[0].Frequency
0x40 11	0x01	1	Services.Service.[0].AutoConnect
0x40 12	0x01	1	Services.Service.[0].Favorite
0x4d 02	0x0d		Services.Service.[0].Network
0x4d 03	0x0a		Services.Service.[0].Network.IPv4
0x4d 14	0x07		Services.Service.[0].Network.IPv4.DHCP
0x45 15	0x04	0x0a02001e	Services.Service.[0].Network.IPv4.LastAddress
0x4d 17	0x50		Services.Service.[1]
0x4b 0b	0x1a	"802.15.4_18 . . ."	Services.Service.[1].ID
0x4c 0d	0x10	"998-3 Alp . . ."	Services.Service.[1].Name
0x4c 0f	0x10	3939382d . . .	Services.Service.[1].EPANID
0x45 10	0x02	2412	Services.Service.[1].Frequency
0x40 11	0x01	1	Services.Service.[1].AutoConnect
0x40 12	0x01	1	Services.Service.[1].Favorite

The TLV format enables reference of properties that may also be enumerated with XML, but does so with a smaller storage size. For example, Table 7 illustrates a comparison of data sizes of the XML Property List, a corresponding binary property list, and the TLV format.

TABLE 7

Comparison of the sizes of property list data sizes.		
List Type	Size in Bytes	Percentage of XML Size
XML	2,199	—
Binary	730	~66.8%
TLV	450	~79.5%

By reducing the amount of data used to transfer data, the TLV format enables the fabric 1000 transfer data to and/or from devices having short duty cycles due to limited power (e.g., battery supplied devices). In other words, the TLV format allows flexibility of transmission while increasing compactness of the data to be transmitted.

C. General Message Protocol

In addition to sending particular entries of varying sizes, data may be transmitted within the fabric using a general message protocol that may incorporate TLV formatting. An embodiment of a general message protocol (GMP) 1128 is

illustrated in FIG. 18. In certain embodiments, the general message protocol (GMP) 1128 may be used to transmit data within the fabric. The GMP 1128 may be used to transmit data via connectionless protocols (e.g., UDP) and/or connection-oriented protocols (e.g., TCP). Accordingly, the GMP 1128 may flexibly accommodate information that is used in one protocol while ignoring such information when using another protocol. Moreover, the GMP 1226 may enable omission of fields that are not used in a specific transmission. Data that may be omitted from one or more GMP 1226 transfers is generally indicated using grey borders around the data units. In some embodiments, the multi-byte integer fields may be transmitted in a little-endian order or a big-endian order.

i. Packet Length

In some embodiments, the GMP 1128 may include a Packet Length field 1130. In some embodiments, the Packet Length field 1130 includes 2 bytes. A value in the Packet Length field 1130 corresponds to an unsigned integer indicating an overall length of the message in bytes, excluding the Packet Length field 1130 itself. The Packet Length field 1130 may be present when the GMP 1128 is transmitted over a TCP connection, but when the GMP 1128 is transmitted over a UDP connection, the message length may be equal to the payload length of the underlying UDP packet obviating the Packet Length field 1130.

ii. Message Header

The GMP **1128** may also include a Message Header **1132** regardless of whether the GMP **1128** is transmitted using TCP or UDP connections. In some embodiments, the Message Header **1132** includes two bytes of data arranged in the format illustrated in FIG. **19**. As illustrated in FIG. **19**, the Message Header **1132** includes a Version field **1156**. The Version field **1156** corresponds to a version of the GMP **1128** that is used to encode the message. Accordingly, as the GMP **1128** is updated, new versions of the GMP **1128** may be created, but each device in a fabric may be able to receive a data packet in any version of GMP **1128** known to the device. In addition to the Version field **1156**, the Message Header **1132** may include an S Flag field **1158** and a D Flag **1160**. The S Flag **1158** is a single bit that indicates whether a Source Node Id (discussed below) field is included in the transmitted packet. Similarly, the D Flag **1160** is a single bit that indicates whether a Destination Node Id (discussed below) field is included in the transmitted packet.

The Message Header **1132** also includes an Encryption Type field **1162**. The Encryption Type field **1162** includes four bits that specify which type of encryption/integrity checking applied to the message, if any. For example, 0x0 may indicate that no encryption or message integrity checking is included, but a decimal 0x1 may indicate that AES-128-CTR encryption with HMAC-SHA-1 message integrity checking is included.

Finally, the Message Header **1132** further includes a Signature Type field **1164**. The Signature Type field **1164** includes four bits that specify which type of digital signature is applied to the message, if any. For example, 0x0 may indicate that no digital signature is included in the message, but 0x1 may indicate that the Elliptical Curve Digital Signature Algorithm (ECDSA) with Prime256v1 elliptical curve parameters is included in the message.

iii. Message Id

Returning to FIG. **18**, the GMP **1128** also includes a Message Id field **1134** that may be included in a transmitted message regardless of whether the message is sent using TCP or UDP. The Message Id field **1134** includes four bytes that correspond to an unsigned integer value that uniquely identifies the message from the perspective of the sending node. In some embodiments, nodes may assign increasing Message Id **1134** values to each message that they send returning to zero after reaching 2^{32} messages.

iv. Source Node Id

In certain embodiments, the GMP **1128** may also include a Source Node Id field **1136** that includes eight bytes. As discussed above, the Source Node Id field **1136** may be present in a message when the single-bit S Flag **1158** in the Message Header **1132** is set to 1. In some embodiments, the Source Node Id field **1136** may contain the Interface ID **1104** of the ULA **1098** or the entire ULA **1098**. In some embodiments, the bytes of the Source Node Id field **1136** are transmitted in an ascending index-value order (e.g., EUI[0] then EUI[1] then EUI[2] then EUI[3], etc.).

v. Destination Node Id

The GMP **1128** may include a Destination Node Id field **1138** that includes eight bytes. The Destination Node Id field **1138** is similar to the Source Node Id field **1136**, but the Destination Node Id field **1138** corresponds to a destination node for the message. The Destination Node Id field **1138** may be present in a message when the single-bit D Flag **1160** in the Message Header **1132** is set to 1. Also similar to the Source Node Id field **1136**, in some embodiments, bytes of the

Destination Node Id field **1138** may be transmitted in an ascending index-value order (e.g., EUI[0] then EUI[1] then EUI[2] then EUI[3], etc.).

vi. Key Id

In some embodiments, the GMP **1128** may include a Key Id field **1140**. In certain embodiments, the Key Id field **1140** includes two bytes. The Key Id field **1140** includes an unsigned integer value that identifies the encryption/message integrity keys used to encrypt the message. The presence of the Key Id field **1140** may be determined by the value of Encryption Type field **1162** of the Message Header **1132**. For example, in some embodiments, when the value for the Encryption Type field **1162** of the Message Header **1132** is 0x0, the Key Id field **1140** may be omitted from the message.

An embodiment of the Key Id field **1140** is presented in FIG. **20**. In the illustrated embodiment, the Key Id field **1140** includes a Key Type field **1166** and a Key Number field **1168**. In some embodiments, the Key Type field **1166** includes four bits. The Key Type field **1166** corresponds to an unsigned integer value that identifies a type of encryption/message integrity used to encrypt the message. For example, in some embodiments, if the Key Type field **1166** is 0x0, the fabric key is shared by all or most of the nodes in the fabric. However, if the Key Type field **1166** is 0x1, the fabric key is shared by a pair of nodes in the fabric.

The Key Id field **1140** also includes a Key Number field **1168** that includes twelve bits that correspond to an unsigned integer value that identifies a particular key used to encrypt the message out of a set of available keys, either shared or fabric keys.

vii. Payload Length

In some embodiments, the GMP **1128** may include a Payload Length field **1142**. The Payload Length field **1142**, when present, may include two bytes. The Payload Length field **1142** corresponds to an unsigned integer value that indicates a size in bytes of the Application Payload field. The Payload Length field **1142** may be present when the message is encrypted using an algorithm that uses message padding, as described below in relation to the Padding field.

viii. Initialization Vector

In some embodiments, the GMP **1128** may also include an Initialization Vector (IV) field **1144**. The IV field **1144**, when present, includes a variable number of bytes of data. The IV field **1144** contains cryptographic IV values used to encrypt the message. The IV field **1144** may be used when the message is encrypted with an algorithm that uses an IV. The length of the IV field **1144** may be derived by the type of encryption used to encrypt the message.

ix. Application Payload

The GMP **1128** includes an Application Payload field **1146**. The Application Payload field **1146** includes a variable number of bytes. The Application Payload field **1146** includes application data conveyed in the message. The length of the Application Payload field **1146** may be determined from the Payload Length field **1142**, when present. If the Payload Length field **1142** is not present, the length of the Application Payload field **1146** may be determined by subtracting the length of all other fields from the overall length of the message and/or data values included within the Application Payload **1146** (e.g., TLV).

An embodiment of the Application Payload field **1146** is illustrated in FIG. **21**. The Application Payload field **1146** includes an APVersion field **1170**. In some embodiments, the APVersion field **1170** includes eight bits that indicate what version of fabric software is supported by the sending device. The Application Payload field **1146** also includes a Message Type field **1172**. The Message Type field **1172** may include

eight bits that correspond to a message operation code that indicates the type of message being sent within a profile. For example, in a software update profile, a 0x00 may indicate that the message being sent is an image announce. The Application Payload field **1146** further includes an Exchange Id field **1174** that includes sixteen bits that corresponds to an exchange identifier that is unique to the sending node for the transaction.

In addition, the Application Payload field **1146** includes a Profile Id field **1176**. The Profile Id **1176** indicates a “theme of discussion” used to indicate what type of communication occurs in the message. The Profile Id **1176** may correspond to one or more profiles that a device may be capable of communicating. For example, the Profile Id **1176** may indicate that the message relates to a core profile, a software update profile, a status update profile, a data management profile, a climate and comfort profile, a security profile, a safety profile, and/or other suitable profile types. Each device on the fabric may include a list of profiles which are relevant to the device and in which the device is capable of “participating in the discussion.” For example, many devices in a fabric may include the core profile, the software update profile, the status update profile, and the data management profile, but only some devices would include the climate and comfort profile. The APVersion field **1170**, Message Type field **1172**, the Exchange Id field, the Profile Id field **1176**, and the Profile-Specific Header field **1176**, if present, may be referred to in combination as the “Application Header.”

In some embodiments, an indication of the Profile Id via the Profile Id field **1176** may provide sufficient information to provide a schema for data transmitted for the profile. However, in some embodiments, additional information may be used to determine further guidance for decoding the Application Payload field **1146**. In such embodiments, the Application Payload field **1146** may include a Profile-Specific Header field **1178**. Some profiles may not use the Profile-Specific Header field **1178** thereby enabling the Application Payload field **1146** to omit the Profile-Specific Header field **1178**. Upon determination of a schema from the Profile Id field **1176** and/or the Profile-Specific Header field **1178**, data may be encoded/decoded in the Application Payload sub-field **1180**. The Application Payload sub-field **1180** includes the core application data to be retransmitted between devices and/or services to be stored, rebroadcast, and/or acted upon by the receiving device/service.

x. Message Integrity Check

Returning to FIG. 18, in some embodiments, the GMP **1128** may also include a Message Integrity Check (MIC) field **1148**. The MIC field **1148**, when present, includes a variable length of bytes of data containing a MIC for the message. The length and byte order of the field depends upon the integrity check algorithm in use. For example, if the message is checked for message integrity using HMAC-SHA-1, the MIC field **1148** includes twenty bytes in big-endian order. Furthermore, the presence of the MIC field **1148** may be determined by whether the Encryption Type field **1162** of the Message Header **1132** includes any value other than 0x0.

xi. Padding

The GMP **1128** may also include a Padding field **1150**. The Padding field **1150**, when present, includes a sequence of bytes representing a cryptographic padding added to the message to make the encrypted portion of the message evenly divisible by the encryption block size. The presence of the Padding field **1150** may be determined by whether the type of encryption algorithm (e.g., block ciphers in cipher-block chaining mode) indicated by the Encryption Type field **1162** in the Message Header **1132** uses cryptographic padding.

xii. Encryption

The Application Payload field **1146**, the MIC field **1148**, and the Padding field **1150** together form an Encryption block **1152**. The Encryption block **1152** includes the portions of the message that are encrypted when the the Encryption Type field **1162** in the Message Header **1132** is any value other than 0x0.

xiii. Message Signature

The GMP **1128** may also include a Message Signature field **1154**. The Message Signature field **1154**, when present, includes a sequence of bytes of variable length that contains a cryptographic signature of the message. The length and the contents of the Message Signature field may be determined according to the type of signature algorithm in use and indicated by the Signature Type field **1164** of the Message Header **1132**. For example, if ECDSA using the Prime256v1 elliptical curve parameters is the algorithm in use, the Message Signature field **1154** may include two thirty-two bit integers encoded in little-endian order.

Profiles and Protocols

As discussed above, one or more schemas of information may be selected upon desired general discussion type for the message. A profile may consist of one or more schemas. For example, one set of schemas of information may be used to encode/decode data in the Application Payload sub-field **1180** when one profile is indicated in the Profile Id field **1176** of the Application Payload **1146**. However, a different set of schemas may be used to encode/decode data in the Application Payload sub-field **1180** when a different profile is indicated in the Profile Id field **1176** of the Application Payload **1146**.

Additionally, in certain embodiments, each device may include a set of methods used to process profiles. For example, a core protocol may include the following profiles: GetProfiles, GetSchema, GetSchemas, GetProperty, GetProperties, SetProperty, SetProperties, RemoveProperty, RemoveProperties, RequestEcho, NotifyPropertyChanged, and/or NotifyPropertiesChanged. The Get Profiles method may return an array of profiles supported by a queried node. The GetSchema and GetSchemas methods may respectively return one or all schemas for a specific profile. GetProperty and GetProperties may respectively return a value or all value pairs for a profile schema. SetProperty and SetProperties may respectively set single or multiple values for a profile schema. RemoveProperty and RemoveProperties may respectively attempt to remove a single or multiple values from a profile schema. RequestEcho may send an arbitrary data payload to a specified node which the node returns unmodified. NotifyPropertyChanged and NotifyPropertiesChanged may respectively issue a notification if a single/multiple value pairs have changed for a profile schema.

To aid in understanding profiles and schemas, a non-exclusive list of profiles and schemas are provided below for illustrative purposes.

A. Status Reporting

A status reporting schema is presented as the status reporting frame **1182** in FIG. 22. The status reporting schema may be a separate profile or may be included in one or more profiles (e.g., a core profile). In certain embodiments, the status reporting frame **1182** includes a profile field **1184**, a status code field **1186**, a next status field **1188**, and may include an additional status info field **1190**.

i. Profile Field

In some embodiments, the profile field **1184** includes four bytes of data that defines the profile under which the information in the present status report is to be interpreted. An embodiment of the profile field **1184** is illustrated in FIG. 23

with two sub-fields. In the illustrated embodiment, the profile field **1184** includes a profile Id sub-field **1192** that includes sixteen bits that corresponds to a vendor-specific identifier for the profile under which the value of the status code field **1186** is defined. The profile field **1184** may also include a vendor Id sub-field **1194** that includes sixteen bits that identifies a vendor providing the profile identified in the profile Id sub-field **1192**.

ii. Status Code

In certain embodiments, the status code field **1186** includes sixteen bits that encode the status that is being reported. The values in the status code field **1186** are interpreted in relation to values encoded in the vendor Id sub-field **1192** and the profile Id sub-field **1194** provided in the profile field **1184**. Additionally, in some embodiments, the status code space may be divided into four groups, as indicated in Table 8 below.

TABLE 8

Status Code Range Table		
Range	Name	Description
0x0000 . . . 0x0010	success client error	A request was successfully processed.
0x0011 . . . 0x0020		An error has or may have occurred on the client-side of a client/server exchange. For example, the client has made a badly-formed request.
0x0021 . . . 0x0030		An error has or may have occurred on the server side of a client/server exchange. For example, the server has failed to process a client request to an operating system error.
0x0031 . . . 0x0040	continue/ redirect	Additional processing will be used, such as redirection, to complete a particular exchange, but no errors yet.

Although Table 8 identifies general status code ranges that may be used separately assigned and used for each specific profile Id, in some embodiments, some status codes may be common to each of the profiles. For example, these profiles may be identified using a common profile (e.g., core profile) identifier, such as 0x00000000.

iii. Next Status

In some embodiments, the next status code field **1188** includes eight bits. The next status code field **1188** indicates whether there is following status information after the currently reported status. If following status information is to be included, the next status code field **1188** indicates what type of status information is to be included. In some embodiments, the next status code field **1188** may always be included, thereby potentially increasing the size of the message. However, by providing an opportunity to chain status information together, the potential for overall reduction of data sent may be reduced. If the next status field **1186** is 0x00, no following status information field **1190** is included. However, non-zero values may indicate that data may be included and indicate the form in which the data is included (e.g., in a TLV packet).

iv. Additional Status Info

When the next status code field **1188** is non-zero, the additional status info field **1190** is included in the message. If present, the status item field may contain status in a form that may be determined by the value of the preceding status type field (e.g., TLV format)

B. Software Update

The software update profile or protocol is a set of schemas and a client/server protocol that enables clients to be made aware of or seek information about the presence of software that they may download and install. Using the software

update protocol, a software image may be provided to the profile client in a format known to the client. The subsequent processing of the software image may be generic, device-specific, or vendor-specific and determined by the software update protocol and the devices.

i. General Application Headers for the Application Payload

In order to be recognized and handled properly, software update profile frames may be identified within the Application Payload field **1146** of the GMP **1128**. In some embodiments, all software update profile frames may use a common Profile Id **1176**, such as 0x0000000C. Additionally, software update profile frames may include a Message Type field **1172** that indicates additional information and may be chosen according to Table 9 below and the type of message being sent.

TABLE 9

Software update profile message types		
Type	Message	
0x00	image announce	
0x01	image query	
0x02	image query response	
0x03	download notify	
0x04	notify response	
0x05	update notify	
0x06 . . . 0xff	reserved	

Additionally, as described below, the software update sequence may be initiated by a server sending the update as an image announce or a client receiving the update as an image query. In either embodiment, an Exchange Id **1174** from the initiating event is used for all messages used in relation to the software update.

ii. Protocol Sequence

FIG. 24 illustrates an embodiment of a protocol sequence **1196** for a software update between a software update client **1198** and a software update server **1200**. In certain embodiments, any device in the fabric may be the software update client **1198** or the software update server **1200**. Certain embodiments of the protocol sequence **1196** may include additional steps, such as those illustrated as dashed lines, that may be omitted in some software update transmissions.

1. Service Discovery

In some embodiments, the protocol sequence **1196** begins with a software update profile server announcing a presence of the update. However, in other embodiments, such as the illustrated embodiment, the protocol sequence **1196** begins with a service discovery **1202**, as discussed above.

2. Image Announce

In some embodiments, an image announce message **1204** may be multicast or unicast by the software update server **1200**. The image announce message **1204** informs devices in the fabric that the server **1200** has a software update to offer. If the update is applicable to the client **1198**, upon receipt of the image announce message **1204**, the software update client **1198** responds with an image query message **1206**. In certain embodiments, the image announce message **1204** may not be included in the protocol sequence **1196**. Instead, in such embodiments, the software update client **1198** may use a polling schedule to determine when to send the image query message **1206**.

3. Image Query

In certain embodiments, the image query message **1206** may be unicast from the software update client **1198** either in response to an image announce message **1204** or according to a polling schedule, as discussed above. The image query message **1206** includes information from the client **1198**

about itself. An embodiment of a frame of the image query message **1206** is illustrated in FIG. **25**. As illustrated in FIG. **25**, certain embodiments of the image query message **1206** may include a frame control field **1218**, a product specification field **1220**, a vendor specific data field **1222**, a version specification field **1224**, a locale specification field **1226**, an integrity type supported field **1228**, and an update schemes supported field **1230**.

a. Frame Control

The frame control field **1218** includes 1 byte and indicates various information about the image query message **1204**. An example of the frame control field **1218** is illustrated in FIG. **26**. As illustrated, the frame control field **1218** may include three sub-fields: vendor specific flag **1232**, locale specification flag **1234**, and a reserved field **S3**. The vendor specific flag **1232** indicates whether the vendor specific data field **1222** is included in the message image query message. For example, when the vendor specific flag **1232** is 0 no vendor specific data field **1222** may be present in the image query message, but when the vendor specific flag **1232** is 1 the vendor specific data field **1222** may be present in the image query message. Similarly, a 1 value in the locale specification flag **1234** indicates that a locale specification field **1226** is present in the image query message, and a 0 value indicates that the locale specification field **1226** is not present in the image query message.

b. Product Specification

The product specification field **1220** is a six byte field. An embodiment of the product specification field **1220** is illustrated in FIG. **27**. As illustrated, the product specification field **1220** may include three sub-fields: a vendor Id field **1236**, a product Id field **1238**, and a product revision field **1240**. The vendor Id field **1236** includes sixteen bits that indicate a vendor for the software update client **1198**. The product Id field **1238** includes sixteen bits that indicate the device product that is sending the image query message **1206** as the software update client **1198**. The product revision field **1240** includes sixteen bits that indicate a revision attribute of the software update client **1198**.

c. Vendor Specific Data

The vendor specific data field **1222**, when present in the image query message **1206**, has a length of a variable number of bytes. The presence of the vendor specific data field **1222** may be determined from the vendor specific flag **1232** of the frame control field **1218**. When present, the vendor specific data field **1222** encodes vendor specific information about the software update client **1198** in a TLV format, as described above.

d. Version Specification

An embodiment of the version specification field **1224** is illustrated in FIG. **28**. The version specification field **1224** includes a variable number of bytes sub-divided into two sub-fields: a version length field **1242** and a version string field **1244**. The version length field **1242** includes eight bits that indicate a length of the version string field **1244**. The version string field **1244** is variable in length and determined by the version length field **1242**. In some embodiments, the version string field **1244** may be capped at **255** UTF-8 char-

acters in length. The value encoded in the version string field **1244** indicates a software version attribute for the software update client **1198**.

e. Locale Specification

In certain embodiments, the locale specification field **1226** may be included in the image query message **1206** when the locale specification flag **1234** of the frame control **1218** is 1. An embodiment of the locale specification field **1226** is illustrated in FIG. **29**. The illustrated embodiment of the locale specification field **1226** includes a variable number of bytes divided into two sub-fields: a locale string length field **1246** and a locale string field **1248**. The locale string length field **1246** includes eight bits that indicate a length of the locale string field **1248**. The locale string field **1248** of the locale specification field **1226** may be variable in length and contain a string of UTF-8 characters encoding a local description based on Portable Operating System Interface (POSIX) locale codes. The standard format for POSIX locale codes is [language[_territory]][.codeset][[@modifier]] For example, the POSIX representation for Australian English is en_AU.UTF8.

f. Integrity Types Supported

An embodiment of the integrity types field **1228** is illustrated in FIG. **30**. The integrity types supported field **1228** includes two to four bytes of data divided into two sub-fields: a type list length field **1250** and an integrity type list field **1252**. The type list length field **1250** includes eight bits that indicate the length in bytes of the integrity type list field **1252**. The integrity type list field **1252** indicates the value of the software update integrity type attribute of the software update client **1198**. In some embodiments, the integrity type may be derived from Table 10 below.

TABLE 10

Example integrity types	
Value	Integrity Type
0x00	SHA-160
0x01	SHA-256
0x02	SHA-512

The integrity type list field **1252** may contain at least one element from Table 10 or other additional values not included.

g. Update Schemes Supported

An embodiment of the schemes supported field **1230** is illustrated in FIG. **31**. The schemes supported field **1230** includes a variable number of bytes divided into two sub-fields: a scheme list length field **1254** and an update scheme list field **1256**. The scheme list length field **1254** includes eight bits that indicate a length of the update scheme list field in bytes. The update scheme list field **1256** of the update schemes supported field **1230** is variable in length determined by the scheme list length field **1254**. The update scheme list field **1256** represents an update schemes attributes of the software update profile of the software update client **1198**. An embodiment of example values is shown in Table 11 below.

TABLE 11

Example update schemes	
Value	Update Scheme
0x00	HTTP
0x01	HTTPS
0x02	SFTP
0x03	Fabric-specific File Transfer Protocol (e.g., Bulk Data Transfer discussed below)

Upon receiving the image query message **1206**, the software update server **1200** uses the transmitted information to determine whether the software update server **1200** has an update for the software update client **1198** and how best to deliver the update to the software update client **1198**.

4. Image Query Response

Returning to FIG. **24**, after the software update server **1200** receives the image query message **1206** from the software update client **1198**, the software update server **1200** responds with an image query response **1208**. The image query response **1208** includes either information detailing why an update image is not available to the software update client **1198** or information about the available image update to enable to software update client **1198** to download and install the update.

An embodiment of a frame of the image query response **1208** is illustrated in FIG. **32**. As illustrated, the image query response **1208** includes five possible sub-fields: a query status field **1258**, a uniform resource identifier (URI) field **1260**, an integrity specification field **1262**, an update scheme field **1264**, and an update options field **1266**.

a. Query Status

The query status field **1258** includes a variable number of bytes and contains status reporting formatted data, as discussed above in reference to status reporting. For example, the query status field **1258** may include image query response status codes, such as those illustrated below in Table 12.

TABLE 12

Example image query response status codes		
Profile	Code	Description
0x00000000	0x0000	The server has processed the image query message 1206 and has an update for the software update client 1198.
0x0000000C	0x0001	The server has processed the image query message 1206, but the server does not have an update for the software update client 1198.
0x00000000	0x0010	The server could not process the request because of improper form for the request.
0x00000000	0x0020	The server could not process the request due to an internal error

b. URI

The URI field **1260** includes a variable number of bytes. The presence of the URI field **1260** may be determined by the query status field **1258**. If the query status field **1258** indicates that an update is available, the URI field **1260** may be included. An embodiment of the URI field **1260** is illustrated in FIG. **33**. The URI field **1260** includes two sub-fields: a URI length field **1268** and a URI string field **1270**. The URI length field **1268** includes sixteen bits that indicates the length of the

URI string field **1270** in UTF-8 characters. The URI string field **1270** and indicates the URI attribute of the software image update being presented, such that the software update client **1198** may be able to locate, download, and install a software image update, when present.

c. Integrity Specification

The integrity specification field **1262** may variable in length and present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. An embodiment of the integrity specification field **1262** is illustrated in FIG. **34**. As illustrated, the integrity specification field **1262** includes two sub-fields: an integrity type field **1272** and an integrity value field **1274**. The integrity type field **1272** includes eight bits that indicates an integrity type attribute for the software image update and may be populated using a list similar to that illustrated in Table 10 above. The integrity value field **1274** includes the integrity value that is used to verify that the image update message has maintained integrity during the transmission.

d. Update Scheme

The update scheme field **1264** includes eight bits and is present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. If present, the update scheme field **1264** indicates a scheme attribute for the software update image being presented to the software update server **1198**.

e. Update Options

The update options field **1266** includes eight bits and is present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. The update options field **1266** may be sub-divided as illustrated in FIG. **35**. As illustrated, the update options field **1266** includes four sub-fields: an update priority field **1276**, an update condition field **1278**, a report status flag **1280**, and a reserved field **1282**. In some embodiments, the update priority field **1276** includes two bits. The update priority field **1276** indicates a priority attribute of the update and may be determined using values such as those illustrated in Table 13 below.

TABLE 13

Example update priority values	
Value	Description
00	Normal - update during a period of low network traffic
01	Critical - update as quickly as possible

The update condition field **1278** includes three bits that may be used to determine conditional factors to determine when or if to update. For example, values in the update condition field **1278** may be decoded using the Table 14 below.

45

TABLE 14

Example update conditions	
Value	Description
0	Update without conditions
1	Update if the version of the software running on the update client software does not match the update version.
2	Update if the version of the software running on the update client software is older than the update version.
3	Update if the user opts into an update with a user interface

The report status flag **1280** is a single bit that indicates whether the software update client **1198** should respond with a download notify message **1210**. If the report status flag **1280** is set to 1 the software update server **1198** is requesting a download notify message **1210** to be sent after the software update is downloaded by the software update client **1200**.

If the image query response **1208** indicates that an update is available. The software update client **1198** downloads **1210** the update using the information included in the image query response **1208** at a time indicated in the image query response **1208**.

5. Download Notify

After the update download **1210** is successfully completed or failed and the report status flag **1280** value is 1, the software update client **1198** may respond with the download notify message **1212**. The download notify message **1210** may be formatted in accordance with the status reporting format discussed above. An example of status codes used in the download notify message **1212** is illustrated in Table 15 below.

TABLE 15

Example download notify status codes		
Profile	Code	Description
0x00000000	0x0000	The download has been completed, and integrity verified
0x0000000C	0x0020	The download could not be completed due to faulty download instructions.
0x0000000C	0x0021	The image query response message 1208 appears proper, but the download or integrity verification failed.
0x0000000C	0x0022	The integrity of the download could not be verified.

In addition to the status reporting described above, the download notify message **1208** may include additional status information that may be relevant to the download and/or failure to download.

6. Notify Response

The software update server **1200** may respond with a notify response message **1214** in response to the download notify message **1212** or an update notify message **1216**. The notify response message **1214** may include the status reporting format, as described above. For example, the notify response message **1214** may include status codes as enumerated in Table 16 below.

46

TABLE 16

Example notify response status codes		
Profile	Code	Description
0x00000000	0x0030	Continue - the notification is acknowledged, but the update has not completed, such as download notify message 1214 received but update notify message 1216 has not.
0x00000000	0x0000	Success- the notification is acknowledged, and the update has completed.
0x0000000C	0x0023	Abort - the notification is acknowledged, but the server cannot continue the update.
0x0000000C	0x0031	Retry query - the notification is acknowledged, and the software update client 1198 is directed to retry the update by submitting another image query message 1206.

In addition to the status reporting described above, the notify response message **1214** may include additional status information that may be relevant to the download, update, and/or failure to download/update the software update.

7. Update Notify

After the update is successfully completed or failed and the report status flag **1280** value is 1, the software update client **1198** may respond with the update notify message **1216**. The update notify message **1216** may use the status reporting format described above. For example, the update notify message **1216** may include status codes as enumerated in Table 17 below.

TABLE 17

Example update notify status codes		
Profile	Code	Description
0x00000000	0x0000	Success - the update has been completed.
0x0000000C	0x0010	Client error - the update failed due to a problem in the software update client 1198.

In addition to the status reporting described above, the update notify message **1216** may include additional status information that may be relevant to the update and/or failure to update.

C. Data Management Protocol

Data management may be included in a common profile (e.g., core profile) used in various electronic devices within the fabric or may be designated as a separate profile. In either situation, the device management protocol (DMP) may be used for nodes to browse, share, and/or update node-resident information. A sequence **1284** used in the DMP is illustrated in FIG. 36. The sequence **1284** illustrates a viewing node **1286** that requests to view and/or change resident data of a viewed node **1288**. Additionally, the viewing node **1286** may request to view the resident data using one of several viewing options, such as a snapshot request, a watching request that the viewing persists over a period of time, or other suitable viewing type. Each message follows the format for the Application Payload **1146** described in reference to FIG. 21. For example, each message contains a profile Id **1176** that corresponds to the data management profile and/or the relevant core profile, such as 0x235A0000. Each message also contains a message type **1172**. The message type **1172** may be used to determine various factors relating the conversation, such as viewing type for the view. For example, in some embodiments, the message type field **1172** may be encoded/decoded according to Table 18 below.

47

TABLE 18

Example software update profile message types	
Type	Message
0x00	snapshot request
0x01	watch request
0x02	periodic update request
0x03	refresh update
0x04	cancel view update
0x05	view response
0x06	explicit update request
0x07	view update request
0x08	update response

i. View Request

Although a view request message **1290** requests to view node-resident data, the type of request may be determined by the message type field **1172**, as discussed above. Accordingly each request type may include a different view request frame.

1. Snapshot Request

A snapshot request may be sent by the viewing node **1286** when the viewing node **1286** desires an instantaneous view into the node-resident data on the viewed node **1288** without requesting future updates. An embodiment of a snapshot request frame **1292** is illustrated in FIG. **37**.

As illustrated in FIG. **37**, the snapshot request frame **1292** may be variable in length and include three fields: a view handle field **1294**, a path length list field **1296**, and a path list field **1298**. The view handle field **1294** may include two bits that provide a “handle” to identify the requested view. In some embodiments, the view handle field **1294** is populated using a random 16-bit number or a 16-bit sequence number along with a uniqueness check performed on the viewing node **1286** when the request is formed. The path list length field **1296** includes two bytes that indicate a length of the path list field **1298**. The path list field **1298** is variable in length and indicated by the value of the path list length field **1296**. The value of the path list field **1298** indicates a schema path for nodes.

A schema path is a compact description for a data item or container that is part of a schema resident on the nodes. For example, FIG. **38** provides an example of a profile schema **1300**. In the illustrated profile schema **1300**, a path to data item **1302** may be written as “Foo:bicycle:mountain” in a binary format. The binary format of the path may be represented as a profile binary format **1304**, as depicted in FIG. **39**. The profile binary format **1304** includes two sub-fields: a profile identifier field **1306** and a TLV data field **1308**. The profile identifier field **1306** identifies which profile is being referenced (e.g., Foo profile). The TLV data field **1308** path information. As previously discussed TLV data includes a tag field that includes information about the enclosed data. Tag field values used to refer to the Foo profile of FIG. **38** may be similar to those values listed in Table 19.

TABLE 19

Example tag values for the Foo profile	
Name	Tag
animal	0x4301
fish	0x4302
fowl	0x4303
medium	0x4304
size	0x4305
bicycle	0x4306
road	0x4307

48

TABLE 19-continued

Example tag values for the Foo profile	
Name	Tag
mountain	0x4308
track	0x4309
# of gears	0x430A
weight	0x430B

Using Table 19 and the Foo profile of FIG. **38**, a binary string in TLV format representing the path “Foo:bicycle:mountain” may be represented as shown in Table 20 below.

TABLE 20

Example binary tag list for a schema path			
Profile ID	Tag and Length (TL)	“bicycle”	“mountain”
CD:AB:00:00	0D:02	06:43	08:43

If the viewing node **1286** desires to receive an entire data set defined in a profile schema (e.g. Foo profile schema of FIG. **39**), the view request message **1290** may request a “nil” item (e.g., 0x0D00 TL and an empty length referring to the container).

2. Watch Request

If the viewing node **1286** desires more than a snapshot, the viewing node **1286** may request a watch request. A watch request asks the viewed node **1288** to send updates when changes are made to the data of interest in viewed node **1288** so that viewing node **1286** can keep a synchronized list of the data. The watch request frame may have a different format than the snapshot request of FIG. **37**. An embodiment of a watch request frame **1310** is illustrated in FIG. **40**. The watch request frame **1310** includes four fields: a view handle field **1312**, a path list length field **1314**, a path list field **1316**, and a change count field **1318**. The view handle field **1312**, the path list length field **1314**, and the path list field may be respectively formatted similar to the view handle field **1294**, the path list length field **1296**, and the path list field **1298** of the snapshot request of FIG. **37**. The additional field, the change count field **1318**, indicates a threshold of a number of changes to the requested data at which an update is sent to the viewing node **1286**. In some embodiments, if the value of the change count field **1318** is 0, the viewed node **1288** may determine when to send an update on its own. If the value of the change count field **1318** is nonzero then after a number of changes equal to the value, then an update is sent to the viewing node **1286**.

3. Periodic Update Request

A third type of view may also be requested by the viewing node **1286**. This third type of view is referred to as a periodic update. A periodic update includes a snapshot view as well as periodic updates. As can be understood, a periodic update request may be similar to the snapshot request with additional information determining the update period. For example, an embodiment of a periodic update request frame **1320** is depicted in FIG. **41**. The periodic update request frame **1320** includes four fields: a view handle field **1322**, a path list length field **1324**, a path list field **1326**, and an update period field **1328**. The view handle field **1322**, the path list length field **1324**, and the path list field **1326** may be formatted similar to their respective fields in the snapshot request frame **1292**. The update period field **1328** is four bytes in length and contains a value that corresponds to a period of time to lapse between updates in a relevant unit of time (e.g., seconds).

4. Refresh Request

When the viewing node **1286** desires to receive an updated snapshot, the viewing node **1286** may send a view request message **1290** in the form of a refresh request frame **1330** as illustrated in FIG. **42**. The refresh request frame **1330** essentially resends a snapshot view handle field (e.g., view handle field **1294**) from a previous snapshot request that the viewed node **1288** can recognize as a previous request using the view handle value in the refresh request frame **1330**.

5. Cancel View Request

When the viewing node **1286** desires to cancel an ongoing view (e.g., periodic update or watch view), the viewing node **1286** may send a view request message **1290** in the form of a cancel view request frame **1332** as illustrated in FIG. **43**. The cancel view request frame **1332** essentially resends a view handle field from a previous periodic update or watch view (e.g., view handle fields **1310**, or **1322**) from a previous request that the viewed node **1288** can recognize as a previous request using the view handle value in the refresh request frame **1330** and to cancel a currently periodic update or watch view.

ii. View Response

Returning to FIG. **36**, after the viewed node **1288** receives a view request message **1290**, the viewed node **1288** responds with a view response message **1334**. An example of a view response message frame **1336** is illustrated in FIG. **44**. The view response message frame **1336** includes three fields: a view handle field **1338**, a view request status field **1240**, and a data item list **1242**. The view handle field **1338** may be formatted similar to any of the above referenced view handle fields **1338**. Additionally, the view handle field **1338** contains a value that matches a respective view handle field from the view request message **1290** to which the view response message **1334** is responding. The view request status field **1340** is a variable length field that indicates a status of the view request and may be formatted according to the status updating format discussed above. The data item list field **1342** is a variable length field that is present when the view request status field **1340** indicates that the view request was successful. When present, the data item list field **1342** contains an ordered list of requested data corresponding to the path list of the view request message **1290**. Moreover, the data in the data item list field **1342** may be encoded in a TLV format, as discussed above.

iii. Update Request

As discussed above, in some embodiments, the viewed node **1288** may send updates to the viewing node **1286**. These updates may be sent as an update request message **1344**. The update request message **1344** may include a specified format dependent upon a type of update request. For example, an update request may be an explicit update request or a view update request field that may be identified by the Message Id **1172**.

1. Explicit Update Request

An explicit update request may be transmitted at any time as a result of a desire for information from another node in the fabric **1000**. An explicit update request may be formatted in an update request frame **1346** illustrated in FIG. **45**. The illustrated update request frame **1346** includes four fields: an update handle field **1348**, a path list length field **1350**, a path list field **1352**, and a data item list field **1354**.

The update handle field **1348** includes two bytes that may be populated with random or sequential numbers with uniqueness checks to identify an update request or responses to the request. The path list length field **1350** includes two bytes that indicate a length of the path list field **1352**. The path list field **1352** is a variable length field that indicates a

sequence of paths, as described above. The data item list field **1354** may be formatted similar to the data item list field **1242**.

2. View Update Request

A view update request message may be transmitted by a node that has previously requested a view into a schema of another node or a node that has established a view into its own data on behalf of another node. An embodiment of a view update request frame **1356** illustrated in FIG. **46**. The view update request frame **1356** includes four fields: an update handle field **1358**, a view handle field **1360**, an update item list length field **1362**, and an update item list field **1364**. The update handle field **1358** may be composed using the format discussed above in reference to the update handle field **1348**. The view handle field **1360** includes two bytes that identify the view created by a relevant view request message **1290** having the same view handle. The update item list length field **1362** includes two bytes and indicates the number of update items that are included in the update item list field **1364**.

The update item list field **1364** includes a variable number of bytes and lists the data items constituting the updated values. Each updated item list may include multiple update items. The individual update items are formatted accordingly to the update item frame **1366** illustrated in FIG. **47**. Each update item frame **1366** includes three sub-fields: an item index field **1368**, an item timestamp field **1370**, and a data item field **1372**. The item index field **1368** includes two bytes that indicate the view under which the update is being requested and the index in the path list of that view for the data item field **1372**.

The item timestamp field **1370** includes four bytes and indicates the elapsed time (e.g., in seconds) from the change until the update being communicated was made. If more than one change has been made to the data item, the item timestamp field **1370** may indicate the most recent or the earliest change. The data item field **1372** is a variable length field encoded in TLV format that is to be received as the updated information.

iv. Update Response

After an update is received, a node (e.g., viewing node **1286**) may send an update response message **1374**. The update response message **1374** may be encoded using an update response frame **1376** illustrated in FIG. **48**. The update response frame **1376** includes two fields: an update handle field **1378** and an update request status field **1380**. The update handle field **1378** corresponds to an update handle field value of the update request message **1344** to which the update response message **1374** is responding. The update request status field **1380** reports a status of the update in accordance with the status reporting format discussed above. Additionally, a profile using the DMP (e.g., a core profile or a data management profile) may include profile-specific codes, such as those enumerated in Table 21 below.

TABLE 21

Example of status codes for a profile including the DMP		
Name	Value	Description
success	0x0000	Request successfully processed
ill-formed request	0x0010	Received request was unparseable (e.g., missing fields, extra fields, etc.)
invalid path	0x0011	A path from the path list of the view or update request did not match a node-resident schema of the responding device.
unknown view handle	0x0012	The view handle in the update request did not match a view on the receiving node.

TABLE 21-continued

Example of status codes for a profile including the DMP		
Name	Value	Description
illegal read request	0x0013	The node making a request to read a particular data item does not have permission to do so.
illegal write request	0x0014	The node making the request to write a particular data item does not have permission to do so.
internal server error	0x0020	The server could not process the request because of an internal error.
out of memory	0x0021	The update request could not be executed because it would overrun the available memory in the receiving device.
continue	0x0030	The request was successfully handled but more action by the requesting device may occur.

D. Bulk Transfer

In some embodiments, it may be desirable to transfer bulk data files (e.g., sensor data, logs, or update images) between nodes/services in the fabric 1000. To enable transfer of bulk data, a separate profile or protocol may be incorporated into one or more profiles and made available to the nodes/services in the nodes. The bulk data transfer protocol may model data files as collections of data with metadata attachments. In certain embodiments, the data may be opaque, but the metadata may be used to determine whether to proceed with a requested file transfer.

Devices participating in a bulk transfer may be generally divided according to the bulk transfer communication and event creation. As illustrated in FIG. 49, each communication 1400 in a bulk transfer includes a sender 1402 that is a node/service that sends the bulk data 1404 to a receiver 1406 that is a node/service that receives the bulk data 1404. In some embodiments, the receiver may send status information 1408 to the sender 1402 indicating a status of the bulk transfer. Additionally, a bulk transfer event may be initiated by either the sender 1402 (e.g., upload) or the receiver 1406 (e.g., download) as the initiator. A node/service that responds to the initiator may be referred to as the responder in the bulk data transfer.

Bulk data transfer may occur using either synchronous or asynchronous modes. The mode in which the data is transferred may be determined using a variety of factors, such as the underlying protocol (e.g., UDP or TCP) on which the bulk data is sent. In connectionless protocols (e.g., UDP), bulk data may be transferred using a synchronous mode that allows one of the nodes/services ("the driver") to control a rate at which the transfer proceeds. In certain embodiments, after each message in a synchronous mode bulk data transfer, an acknowledgment may be sent before sending the next message in the bulk data transfer. The driver may be the sender 1402 or the receiver 1406. In some embodiments, the driver may toggle between an online state and an offline mode while sending messages to advance the transfer when in the online state. In bulk data transfers using connection-oriented protocols (e.g., TCP), bulk data may be transferred using an asynchronous mode that does not use an acknowledgment before sending successive messages or a single driver.

Regardless of whether the bulk data transfer is performed using a synchronous or asynchronous mode, a type of message may be determined using a Message Type 1172 in the Application Payload 1146 according to the Profile Id 1176 in the Application Payload. Table 22 includes an example of message types that may be used in relation to a bulk data transfer profile value in the Profile Id 1176.

TABLE 22

Examples of message types for bulk data transfer profiles		
	Message Type	Message
5	0x01	SendInit
	0x02	SendAccept
	0x03	SendReject
	0x04	ReceiveInit
	0x05	ReceiveAccept
10	0x06	ReceiveReject
	0x07	BlockQuery
	0x08	Block
	0x09	BlockEOF
	0x0A	Ack
	0x0B	Block EOF
15	0x0C	Error

i. SendInit

An embodiment of a SendInit message 1420 is illustrated in FIG. 50. The SendInit message 1420 may include seven fields: a transfer control field 1422, a range control field 1424, a file designator length field 1426, a proposed max block size field 1428, a start offset field 1430, length field 1432, and a file designator field 1434.

The transfer control field 1422 includes a byte of data illustrated in FIG. 51. The transfer control field includes at least four fields: an Asynch flag 1450, an RDrive flag 1452, an SDrive flag 1454, and a version field 1456. The Asynch flag 1450 indicates whether the proposed transfer may be performed using a synchronous or an asynchronous mode. The RDrive flag 1452 and the SDrive flag 1454 each respectively indicates whether the receiver 1406 is capable of transferring data with the receiver 1402 or the sender 1408 driving a synchronous mode transfer.

The range control field 1424 includes a byte of data such as the range control field 1424 illustrated in FIG. 52. In the illustrated embodiment, the range control field 1424 includes at least three fields: a BigExtent flag 1470, a start offset flag 1472, and a definite length flag 1474. The definite length flag 1474 indicates whether the transfer has a definite length. The definite length flag 1474 indicates whether the length field 1432 is present in the SendInit message 1420, and the BigExtent flag 1470 indicates a size for the length field 1432. For example, in some embodiments, a value of 1 in the BigExtent flag 1470 indicates that the length field 1432 is eight bytes. Otherwise, the length field 1432 is four bytes, when present. If the transfer has a definite length, the start offset flag 1472 indicates whether a start offset is present. If a start offset is present, the BigExtent flag 1470 indicates a length for the start offset field 1430. For example, in some embodiments, a value of 1 in the BigExtent flag 1470 indicates that the start offset field 1430 is eight bytes. Otherwise, the start offset field 1430 is four bytes, when present.

Returning to FIG. 50, the file designator length field 1426 includes two bytes that indicate a length of the file designator field 1434. The file designator field 1434 which is a variable length field dependent upon the file designator length field 1426. The max block size field 1428 proposes a maximum size of block that may be transferred in a single transfer.

The start offset field 1430, when present, has a length indicated by the BigExtent flag 1470. The value of the start offset field 1430 indicates a location within the file to be transferred from which the sender 1402 may start the transfer, essentially allowing large file transfers to be segmented into multiple bulk transfer sessions.

The length field 1432, when present, indicates a length of the file to be transferred if the definite length field 1474

indicates that the file has a definite length. In some embodiments, if the receiver **1402** receives a final block before the length is achieved, the receiver may consider the transfer failed and report an error as discussed below.

The file designator field **1434** is a variable length identifier chosen by the sender **1402** to identify the file to be sent. In some embodiments, the sender **1402** and the receiver **1406** may negotiate the identifier for the file prior to transmittal. In other embodiments, the receiver **1406** may use metadata along with the file designator field **1434** to determine whether to accept the transfer and how to handle the data. The length of the file designator field **1434** may be determined from the file designator length field **1426**. In some embodiments, the SendInit message **1420** may also include a metadata field **1480** of a variable length encoded in a TLV format. The metadata field **1480** enables the initiator to send additional information, such as application-specific information about the file to be transferred. In some embodiments, the metadata field **1480** may be used to avoid negotiating the file designator field **1434** prior to the bulk data transfer.

ii. SendAccept

A send accept message is transmitted from the responder to indicate the transfer mode chosen for the transfer. An embodiment of a SendAccept message **1500** is presented in FIG. **53**. The SendAccept message **1500** includes a transfer control field **1502** similar to the transfer control field **1422** of the SendInit message **1420**. However, in some embodiments, only the RDrive flag **1452** or the SDrive **1454** may have a nonzero value in the transfer control field **1502** to identify the sender **1402** or the receiver **1406** as the driver of a synchronous mode transfer. The SendAccept message **1500** also includes a max block size field **1504** that indicates a maximum block size for the transfer. The block size field **1504** may be equal to the value of the max block field **1428** of the SendInit message **1420**, but the value of the max block size field **1504** may be smaller than the value proposed in the max block field **1428**. Finally, the SendAccept message **1500** may include a metadata field **1506** that indicates information that the receiver **1506** may pass to the sender **1402** about the transfer.

iii. SendReject

When the receiver **1206** rejects a transfer after a SendInit message, the receiver **1206** may send a SendReject message that indicates that one or more issues exist regarding the bulk data transfer between the sender **1202** and the receiver **1206**. The send reject message may be formatted according to the status reporting format described above and illustrated in FIG. **54**. A send reject frame **1520** may include a status code field **1522** that includes two bytes that indicate a reason for rejecting the transfer. The status code field **1522** may be decoded using values similar to those enumerated as indicated in the Table 23 below.

TABLE 23

Example status codes for send reject message	
Status Code	Description
0x0020	Transfer method not supported
0x0021	File designator unknown
0x0022	Start offset not supported
0x0011	Length required
0x0012	Length too large
0x002F	Unknown error

In some embodiments, the send reject message **1520** may include a next status field **1524**. The next status field **1524**,

when present, may be formatted and encoded as discussed above in regard to the next status field **1188** of a status report frame. In certain embodiments, the send reject message **1520** may include an additional information field **1526**. The additional information field **1526**, when present, may store information about an additional status and may be encoded using the TLV format discussed above.

iv. ReceiveInit

A ReceiveInit message may be transmitted by the receiver **1206** as the initiator. The ReceiveInit message may be formatted and encoded similar to the SendInit message **1480** illustrated in FIG. **50**, but the BigExtent field **1470** may be referred to as a maximum length field that specifies the maximum file size that the receiver **1206** can handle.

v. ReceiveAccept

When the sender **1202** receives a ReceiveInit message, the sender **1202** may respond with a ReceiveAccept message. The ReceiveAccept message may be formatted and encoded as the ReceiveAccept message **1540** illustrated in FIG. **55**. The ReceiveAccept message **1540** may include four fields: a transfer control field **1542**, a range control field **1544**, a max block size field **1546**, and sometimes a length field **1548**. The ReceiveAccept message **1540** may be formatted similar to the SendAccept message **1502** of FIG. **53** with the second byte indicating the range control field **1544**. Furthermore, the range control field **1544** may be formatted and encoded using the same methods discussed above regarding the range control field **1424** of FIG. **52**.

vi. ReceiveReject

If the sender **1202** encounters an issue with transferring the file to the receiver **1206**, the sender **1202** may send a ReceiveReject message formatted and encoded similar to a SendReject message **48** using the status reporting format, both discussed above. However, the status code field **1522** may be encoded/decoded using values similar to those enumerated as indicated in the Table 24 below.

TABLE 24

Example status codes for receive reject message	
Status Code	Description
0x0020	Transfer method not supported
0x0021	File designator unknown
0x0022	Start offset not supported
0x0013	Length too short
0x002F	Unknown error

vii. BlockQuery

A BlockQuery message may be sent by a driving receiver **1202** in a synchronous mode bulk data transfer to request the next block of data. A BlockQuery message impliedly acknowledges receipt of a previous block of data if not explicit Acknowledgement has been sent. In embodiments using asynchronous transfers, a BlockQuery message may be omitted from the transmission process.

viii. Block

Blocks of data transmitted in a bulk data transfer may include any length greater than 0 and less than a max block size agreed upon by the sender **1202** and the receiver **1206**.

ix. BlockEOF

A final block in a data transfer may be presented as a Block end of file (BlockEOF). The BlockEOF may have a length between 0 and the max block size. If the receiver **1206** finds a discrepancy between a pre-negotiated file size (e.g., length

field **1432**) and the amount of data actually transferred, the receiver **1206** may send an Error message indicating the failure, as discussed below.

x. Ack

If the sender **1202** is driving a synchronous mode transfer, the sender **1202** may wait until receiving an acknowledgment (Ack) after sending a Block before sending the next Block. If the receiver is driving a synchronous mode transfer, the receiver **1206** may send either an explicit Ack or a Block-Query to acknowledge receipt of the previous block. Furthermore, in asynchronous mode bulk transfers, the Ack message may be omitted from the transmission process altogether.

xi. AckEOF

An acknowledgement of an end of file (AckEOF) may be sent in bulk transfers sent in synchronous mode or asynchronous mode. Using the AckEOF the receiver **1206** indicates that all data in the transfer has been received and signals the end of the bulk data transfer session.

xii. Error

In the occurrence of certain issues in the communication, the sender **1202** or the receiver **1206** may send an error message to prematurely end the bulk data transfer session. Error messages may be formatted and encoded according to the status reporting format discussed above. For example, an error message may be formatted similar to the SendReject frame **1520** of FIG. **54**. However, the status codes may be encoded/decoded with values including and/or similar to those enumerated in Table 25 below.

TABLE 25

Example status codes for an error message in a bulk data transfer profile	
Status code	Description
0x001F	Transfer failed unknown error
0x0011	Overflow error

The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

Efficient Communication Use Cases and Power Awareness

The efficient IPv6 802.15.4 network protocol and/or the efficient platform protocol discussed above may enable power-efficient operation in a home environment. As will be discussed below, in one example, such communication may include communicating an IPv6 packet to traverse a particular preferred network. Additionally or alternatively, properties of the manner of communication, such as the type of transport protocol—TCP or UDP—used to transport the message, may also be selectable. For example, to provide for greater reliability but less power savings, TCP may be selected, while to provide greater power savings but less reliability, UDP may be selected.

Smart Communication Using IPv6 Packet Header Fields

As indicated above, the fields available in an IPv6 packet header may be used in the system of this disclosure to convey information regarding a target node of a fabric **1000** that is targeted to receive a message. For instance, as seen in FIG. **56**,

a packet header **1600** of an IPv6 packet targeted to a particular node may include a MAC field **1602**, a subnet field **1604**, and a fabric ID field **1606**. The MAC field **1602** may fill a 64-bit area usually understood to represent an Extended Unique Identifier (EUI-64). The MAC field **1602** may include an indication of the MAC address of the target node. The subnet field **1604** and the fabric ID field **1606** may collectively represent an Extended Unique Local Address (EULA). In the EULA of these fields, the fabric ID field **1606** may indicate the particular fabric **1000** through which the IPv6 packet is to be sent, while the subnet field **1604** may identify a preferred network within the fabric **1000** over which the target node may preferably receive messages. In the example of FIG. **56**, the subnet field **1604** indicates that the target node may preferably receive messages via a particular WiFi network. It should be appreciated that the EULA formed by the fabric ID field **1606** and subnet field **1604** may be used when IPv6 packets are being sent entirely within one or more connected fabrics and/or services that serve those fabrics. When the IPv6 packets are to be sent from a node of a fabric **1000** to an external IPv6 Internet address, a different (e.g., more conventional) IPv6 packet header structure may be employed.

The EULA information of the subnet field **1604** and the fabric ID field **1606** can be used to efficiently communicate IPv6 packets through the fabric **1000** toward a target node. In an example shown in FIG. **57**, a message is sent through the network topology discussed above with reference to FIG. **11**. Here, the node **1026** is the sending node and the node **1036** is the target node. The node **1026** is operating on the 802.15.4 network **1022**, while the target node **1036** operates on both the 802.15.4 network **1022** and the WiFi network **1020**. The preferred network of the target node **1036** is represented in the example of FIG. **57** to be the WiFi network **1020**. As such, the IPv6 packets used to send the message from the sending node **1026** to the target node **1036** may generally have the characteristics shown in the IPv6 packet **1600** of FIG. **56**.

The various nodes **1026**, **1028**, **1030**, **1034**, and **1042** are shown in FIG. **57** to communicate the message from the sending node **1026** to the target node **1036**. When there is only one network over which to send the message, the message may be communicated through that network. This is the case with the nodes **1026**, **1028**, and **1030** in the example of FIG. **57**. When the message reaches a node that operates on more than one network, such as the node **1034**, however, that node may use the subnet field **1604** to determine which network to use to communicate the message further toward the target node **1036**.

A flowchart **1650** of FIG. **58** illustrates an example of a method for using the subnet field **1604** of a packet header **1600** to communicate the IPv6 packet toward a target node. In the method, a node that operates on two networks (e.g., node **1034**, which operates on both the WiFi network **1020** and the 802.15.4 network **1022**) may receive an IPv6 packet (block **1652**). The node may analyze the subnet field **1604** of the IPv6 packet header **1600** to determine which network is the most proper network to use to forward the IPv6 packet toward the target node. The subnet field **1604** may indicate, for example, that the message is to be received by the target node (e.g., the node **1036**) on the WiFi network **1020**. The receiving node (e.g., node **1034**) then may communicate the IPv6 packet toward the target node (e.g., node **1036**) over the network indicated by the subnet field **1604** (e.g., the WiFi network **1020**) (block **1654**).

In some examples, the network over which the IPv6 packet has been received may be different from the network indicated by the subnet field **1604**. In FIG. **57**, for example, the node **1034** receives the message over the 802.15.4 network

1022. When the subnet field **1604** indicates that the WiFi network **1020** is the preferred network to be used to send the IPv6 packet, however, the node **1034** may communicate the IPv6 packet over the WiFi network **1020** instead. In this way, the subnet field **1604** may enable a target node to have a preferred network over which to receive messages. In the example of FIG. **57**, the target node **1036** may be an always-on electronic device that may communicate more rapidly or more reliably over the WiFi network **1020** than the 802.15.4 network **1022**. In other examples, the target node **1036** may be a battery-powered sleepy device that would be better served to receive messages over the 802.15.4 network **1022**. Under such an example, even though the target node **1036** could receive messages via the WiFi network **1020**, by receiving the messages via the 802.15.4 network **1022** as may be indicated by a subnet field **1604**, the target node **1036** may conserve power. Thus, the EULA of the IPv6 packet header **1600** (e.g., the fabric ID field **1606** and the subnet field **1604**) may be used to promote efficient message transfer through a fabric.

Selection of the Transport Protocol or Preferred Target Network Based on the Desired Reliability of the Message

Judicious selection of the transport protocol (e.g., TCP or UDP) and/or a preferred target node network used to send the IPv6 packets may also lead to efficient network usage. Indeed, while TCP is more reliable than UDP, the reliability of TCP stems from its use of handshaking and acknowledgments when transmitting messages, many of which are absent in UDP. The additional reliability of TCP, however, may increase the cost of sending a message in terms of power consumed. Indeed, there is an additional cost in power due to the handshaking and acknowledgments of TCP. In addition, using TCP will cause dropped packets to be resent until they have been confirmedly received, consuming additional power at all devices that suffer dropped packets.

As such, it may be desirable to send messages by UDP unless there are reasons that reliability is preferred over power efficiency. For instance, as shown in a flowchart **1670** of FIG. **59**, one of the devices on a fabric **1000** may generate a message (block **1672**). The device may consider one or more reliability factors relating to a desired reliability of the message (block **1674**). This consideration of the one or more reliability factors may take place in the application layer **102** or the platform layer **100** of the OSI stack **90** running on the device. In either case, the reliability factor(s) that the device may consider may include (1) a type of the message generated at block **1672**, (2) a type of the network over which the message is going to be sent, (3) a distance over which the message may travel through the fabric, (4) a power sensitivity of the target node and/or the transmitting nodes that are going to be used to communicate the message to the target node, and/or (5) a target end node type (e.g., whether a device or a service). In some embodiments, only one factor may be considered. Moreover, the list of reliability factors discussed here is not intended to be exhaustive, but rather to provide examples for deciding whether reliability or power savings may be more desirable when sending a message.

A first factor that may affect the desired reliability of the transport protocol is the type of the message that is going to be sent. A very high reliability may be desired when the message is an alarm message, such as a message indicating that a hazard has been detected. A high reliability may be less valuable than power savings, however, when the message represents sensor data or certain device status data.

A second factor that may affect the desired reliability of the transport protocol is the type of network over which the message is to be sent. When the message will primarily

traverse an 802.15.4 network, for example, this may imply that power savings may be more beneficial than reliability. When the message will primarily or entirely traverse a WiFi network, however, this may imply that the power savings may be less valuable and reliability may be more valuable.

A third factor that may affect the desired reliability of the transport protocol is the distance over which the message may travel through the fabric **1000** to reach the target node. The distance may represent, for instance, the number of "hops" to reach the target node, the number of different types of networks that may be traversed to reach the target node, and/or an actual distance through the network.

A fourth factor that may affect the desired reliability of the transport protocol is the power sensitivity of the devices that may be used to communicate the message to the target node. When all or substantially all of such devices are always-on or are supplied by an external power source, higher reliability may be preferable to power savings. When one or many of the devices are low-power, sleepy, and/or battery powered devices, power savings may be preferable when the message is not especially urgent.

A fifth factor that may affect the desired reliability of the transport protocol is the type of the target end node of the message. In one example, when the target end node is a service, whether local or remote, a higher reliability may be desired. Thus, in this case, TCP may be preferred over UDP. In another example, a higher reliability may be preferred when the target end node is a remote service, but less reliability and greater power savings may be called for when the target end node is a local service. In other examples, the type of service may be considered. That is, for some services, reliability may be preferred over power savings, while for other services, power savings may be preferred over reliability. To provide just one example, to communicate with a service used to provide weather information, a relatively lower reliability may be desired as compared to power savings. On the other hand, to communicate with a service used to provide a software update, higher reliability may be preferred over power savings.

The device may consider one or more of these factors in any suitable way. In one example, the factors may be assigned a weight and reliability determination may be based on the total weighting of the factors. In other examples, certain factors may have a higher priority than other factors. In such an example, an urgent message may always be considered to have more desired reliability over power savings, while the desirability of reliability for non-urgent messages may depend on other factors. As such, when power savings is desired over reliability (decision block **1676**), the device may send the message via UDP (block **1678**) to save power despite lower reliability. When more reliability is desired over power savings (decision block **1676**), the device may send the message via TCP (block **1680**) to have increased reliability despite higher power consumption.

Although the above method has been discussed with reference to a selection of sending the message using TCP or UDP, it should be appreciated that the present communication system may efficiently adjust any number of properties of the manner of communication to balance desired reliability with power consumption. For example, in some embodiments, when a higher reliability is desired, a higher-power network (e.g., WiFi) may be preferred, while when a lower reliability and higher power savings is desired, a lower-power network (e.g., 802.15.4) may be preferred. The sending node may, for example, select a different preferred network to note in the subnet field **1604** of the IPv6 packet header **1600**, thereby

causing the message to be communicated, when possible, through that selected network.

Additional Use Cases

The fabric **1000** of connected devices discussed above may be used in a variety of manners. One example may involve using one device to invoke a method on another device. Another example may involve propagating a message, such as a hazard alarm, over various devices of the fabric. It should be understood that these use cases are intended to provide examples and are not intended to be exhaustive.

Invoking a Method from One Device on Another

In one case, a device in one area of the fabric **1000** may invoke a particular method on another compatible device. One example appears in a diagram **1700** of FIG. **60**. The diagram **1700** illustrates interactions between a first device **1702** and a second device **1704**, as mediated by a directory device (DDS) **1706**. The directory device (DDS) **1706** may issue a DDS service broadcast **1708** to the various devices on the fabric, including the first device **1702** and the second device **1704**. In response, the directory device (DDS) **1706** may receive a list of all methods and/or profiles the various devices of the fabric **1000** support.

When one of the devices of the fabric, such as the first device **1702** desires to perform a method (shown in FIG. **60** as a method **n**), the first device **1702** may query the directory device (DDS) **1706** with a corresponding query message **1710** (e.g., GetProperty (supports-n)). The directory device (DDS) **1706** may reply with the devices that support such a property—here, replying with a message **1712** indicating that the second device **1704** supports the desired method. Now in possession of this information, the first device **1702** may invoke the method in a message **1714** to the second device **1704**. The second device **1704** then may issue a reply **1716** with an appropriate response.

The method invoked by the first device **1702** on the second device **1704** may be any of a number of methods that may be useful to a home network. In one example, the first device **1702** may request environmental sensor data from the second device **1704**. The environmental sensor data may indicate motion, temperature, humidity, and so forth. The environmental sensor data may be used by the first device **1702** to determine occupancy for security, for example, or to determine various temperatures currently located around a house. In another example, the first device **1702** may request user interface input information from the second device **1704**. For instance, the first device **1702** may request an indication of recent thermostat temperature setpoints to ascertain information regarding the recent desired comfort settings of the occupants.

Propagating a Message to Various Devices of the Fabric

In some situations, it may be desirable to propagate a message to multiple devices of the fabric. For example, as shown in a diagram **1720** of FIG. **61**, several devices **1722**, **1724**, **1726**, and **1728** may be used to propagate a hazard alarm message. Indeed, the hazard alarm message may be propagated even though one or more of the various devices **1722**, **1724**, **1726**, and **1728** may be low-power, “sleepy” devices. In the example of FIG. **61**, the device **1722** is a hazard detector (e.g., a smoke detector) in the garage, the device **1724** is a hazard detector (e.g., a smoke detector) in the dining room, the device **1726** is a smart doorbell at the front door, and the device **1728** is a thermostat in the hallway.

The action of the diagram **1720** begins when an event **1730** (e.g., fire) is detected by the garage device **1722**. The garage device **1722** may propagate a network wake message **1732** to

the dining room device **1724**, which may issue a reply **1734** accordingly. The dining room device **1724** may temporarily wake up from its sleepy state to an awake, always-on state. The dining room device **1724** may also propagate a network wake message **1736** to the front door device **1726**, which may reply **1738** likewise while propagating another network wake message **1740** to the hallway device **1728**.

Having woken the devices of the fabric, the garage device **1722** may output an alarm **1744** associated with the event **1730** and may issue an alarm notification message **1746** to the dining room device **1724**. The alarm notification message **1746** may indicate the type of event and the originating device (e.g., event occurring in the garage), among other things. The dining room device **1724** may output a corresponding alarm **1748** and forward an alarm notification message to the front door device **1726**, which may itself begin to output an alarm **1752**. The front door device **1726** may also forward an alarm notification message to the hallway device **1728**.

The hallway device **1728** may display an interface message **1756** to enable a user to respond to the alarm. In the meantime, messages may continue to be propagated across the fabric. These include additional network wake and reply messages **1758**, **1760**, **1762**, **1764**, and **1766**, and additional alarm notification messages **1768**, **1770**, and **1772**. When a user provides user feedback **1774** on the hallway device **1728** requesting that the alarm be silenced (in the understanding, for example, that the alarm is false or due to non-hazardous conditions), the hallway device **1728** may respond by sending an alarm silence message **1776** that may be propagated over the fabric **1000** to all of the devices. The alarm silence message **1776** may reach the front door device **1726**, which may silence its alarm **1778** and issue a further alarm silence message **1780** to the dining room device **1724**. In response, the dining room device **1724** may silence its alarm **1782** and issue a further alarm silence message to the garage device **1722**, which may in turn silence its alarm **1786**.

After causing the devices **1726**, **1724**, and **1722** to silence their alarms, the hallway device **1728** may cause the devices **1726**, **1724**, and **1722** to reenter a sleepy, low-power state. Specifically, the hallway device **1728** may issue network sleep message **1790** to the front door device **1726**, which may enter a sleepy state after issuing a network sleep message **1792** to the dining room device **1724**. The dining room device **1724** may correspondingly enter a sleepy state after issuing a network sleep message **1794** to the garage device **1722**. Upon receipt of the network sleep message **1794**, the garage device **1722** may enter the low-power, sleepy state.

Joining or Creating a Fabric

The protocols discussed above can be used to join or create a fabric **1000** of devices in a home network or similar environment. For example, FIGS. **62-64** relate to a first method in which a new device joins an existing fabric **1000** through another device of the fabric **1000** that is connected to a service (e.g., via the Internet). FIGS. **65-67** relate to a second method in which a new device joins an existing fabric **1000** or creates a new fabric **1000** through a peer-to-peer connection with another device regardless of whether either device is connected to another service. The following examples relate to joining a fabric **1000** with a new device that may not have a user interface with a native display, and as such may involve assistance from a third-party client device (e.g., a mobile phone or tablet computer). In other embodiments, such as those in which the new device includes a user interface with a

61

native display, the activities described below as being carried out on a third-party client device may instead take place on the new device.

Joining or Creating a Fabric Using an Internet Connection to a Service

Turning first to a flowchart **1800** shown in FIGS. **62-64**, a user may join a new device to a fabric **1000** by opening the box in which the device has been sold (block **1802**) and obtaining instructions to install an application (block **1804**) on a third-party client device (e.g., a mobile phone or tablet computer). The application may be installed on the client device (block **1806**) and the user may log into a service account related to the fabric **1000** where the user may select the particular fabric **1000** the new device is to join (block **1808**). For instance, the user may install a Nest® application and may log into a Nest® service account associated with a Nest® Weave™ fabric. The application on the client device may obtain information associated with a service configuration of the fabric **1000** (block **1810**). The information associated with the service configuration of the fabric **1000** may include, for example:

- a service node identification (e.g., an EUI-64 or EULA);
- a set of certificates that may serve as trust anchors for the service (e.g., a fabric authentication token);
- a globally unique account identification associated with the user's account;
- a Domain Name Service (DNS) host name identifying the entry point for the service; and/or
- an opaque account pairing token that may be used by the new device to pair with the user's account.

The user may also elect, via the application on the client device, to add a new device to the fabric **1000** (block **1812**). Based on whether there is currently an existing fabric **1000** associated with the user or based on any other suitable criteria (decision block **1814**), the application may choose to create a new fabric **1000** (block **1816**) or to add the new device to an existing fabric **1000** (block **1818**).

When the application chooses to add the new device to an existing fabric **1000** (block **1818**), the application may determine whether the devices of the network are in an awake rather than sleepy state (decision block **1820**), waking the devices (block **1822**) if not awake. The user may select a particular existing device of the network to use in a joining process by, for example, pressing a button (block **1824**). The existing device may provide fabric joining information to the application on the client device (block **1826**). For instance, the application on the client device may establish a secure session with the existing device using a fabric **1000** authentication token. The application may use requests (e.g., GetNetworkConfiguration and/or aGetFabricConfiguration) to obtain from the existing device network configuration information and/or fabric **1000** configuration information. The application may save this information for later use.

The application may further instruct the user to wake the new device (block **1828**) by, for example, pressing a button on the new device (block **1830**). The method then may progress to block (A) **1832**, which continues on FIG. **63**. Here, the application on the client device may instruct the existing device to connect to the new device (block **1834**). For example, the application may establish a new secure session to the existing device using a fabric authentication token, and over this new session may send a request (e.g., ConnectOtherDevice) to the existing device. Meanwhile, the new device may have set up an 802.15.4 "joining network" specific to the purpose of joining with the existing device. Thus, the request of block **1834** may specify that the application wishes the existing device to connect to the new device via an

62

802.15.4 network connection (e.g., the 802.15.4 joining network created by the new device). The existing device then may perform a scan of nearby 802.15.4 networks looking for the network created by the new device. Once found, the existing device may leave the existing fabric, join the new 802.15.4 joining network, and probe the 802.15.4 joining network by attempting to connect to a rendezvous address (which may be previously specified by the software or firmware of the existing device or by the application on the client device). Once a connection to the new device is established, the existing device may respond to the request to connect to the new device (e.g., ConnectOtherDevice) from the application on the client device with a reply of success. From this point forward, messages provided to the new device from the application may be carried by proxy through the existing device via the 802.15.4 joining network. That is, the new device may be connected to the existing device via the 802.15.4 joining network, the existing device may be connected to the service node via WiFi (and/or an Internet connection), and the application on the client device may be connected to the service. In this way, the application may connect to the new device through the existing fabric, and the existing device may only use single WiFi connection and a single 802.15.4 connection (thereby reducing avoiding using in the existing device multiple receivers and transmitters per network type, which may reduce device cost and power consumption).

Alternatively, when a new fabric **1000** is to be created, the application on the client device may connect directly to the new device using a WiFi connection. Thus, the application on the client device may instruct the user to switch to a WiFi connection (block **1836**). The user may switch WiFi networks on their client device to establish a peer-to-peer WiFi connection with the new device (block **1838**). For example, the new device may have associated with it a unique WiFi SSID name on the back of the new device. The application on the client device may probe for the new device by repeatedly attempting to connect to a previously determined rendezvous address (e.g., as provided to the application by the configuration information from the service or as encoded in the application).

With either of these connections established, the application on the client device may detect the new device and display a serial number provided by the new device (block **1840**). At this time, the application may also validate that the new device has installed on it certain security features identifying the device as authentically validated and having proper permissions to join the fabric. These security features may be the same as or in addition to the DTLS security certificates discussed above.

Using either connection, the user may facilitate an authentication procedure when the application on the client device instructs the user to scan a QR code or other code associated with the new device (e.g., printed on the new device or on a card provided with the new device) (block **1842**). The user may enter the code by scanning or typing the code into the application (block **1844**). This code information may be provided to the new device, which may use the code to confirm that the application is being used authentically by a user in possession of the new device. The new device may, for example, validate the code using a built-in check digit. The new device may indicate when the code has been entered incorrectly with a corresponding reply. The application may establish a secure session with the new device using any suitable protocol, including the Weave PASE protocol, using the supplied pairing code as a password (block **1848**). Having established the secure connection to the new device, the application on the client device may issue a request to arm a

failsafe regimen on the new device (e.g., ArmConfiguration-Failsafe) (block **1850**). By arming the failsafe regimen, the new device may revert to certain original configurations if the joining process does not complete by some timeout value. The application may also determine whether the new device belongs to another existing fabric **1000** by issuing a suitable request (e.g., GetFabricState) (decision block **1852**). If so, the application may instruct the new device to leave the other existing fabric **1000** by issuing another request (e.g., LeaveFabric) (block **1854**).

In a case in which the new device is to form a new fabric **1000** with the existing device (decision block **1856**), the application may instruct the new device to enumerate a list of WiFi networks visible to the new device (e.g., via an EnumerateVisibleNetworks request) (block **1858**). Upon instruction from the application (block **1860**), the user then may select from among these networks or may enter the WiFi network that the new device is to join (block **1862**). The user may also enter an appropriate password to join the WiFi network (block **1864**). The method may further progress to block (B) **1866**, which continues on FIG. **64**. The application may send the WiFi network configuration information to the new device (e.g., via an AddNetwork request) (block **1868**), and the application may instruct the new device to test the connection (e.g., via a TestNetwork request) by attempting to reach the service on the Internet (block **1870**). The application may indicate to the user that the network connection is being confirmed (block **1872**) and the new device may subsequently confirm its connection to the application (block **1874**).

With the new device now connected to the Internet via the WiFi connection, if a new fabric **1000** is being created (block **1876**), the application may instruct the user to return to the fabric **1000** (e.g., the user's home) WiFi connection (block **1878**). The user may change the WiFi network being used by the client device to the WiFi connection used by the fabric **1000** (block **1880**).

Whether creating a new fabric **1000** or joining an existing one, the application may instruct the new device to do so at this point (block **1882**). That is, the application may instruct the new device to create a new fabric **1000** (e.g., via a CreateFabric request) or may instruct the new device to join the existing fabric **1000** (e.g., via a JoinExistingFabric request). In the case of joining an existing fabric, the application may inform the new device of the existing device (e.g., via a RegisterNewFabricMember request to the new device). In either case, the application may configure the new device to communicate with the service (e.g., the Nest® service) by sending a request (e.g., a RegisterService request) that contains service configuration information (e.g., Weave™ Service Configuration information).

Using the service configuration information, the new device may register with the service (block **1884**). For example, the new device may connect to the service using a service node ID and DNS name from the service configuration information. The new device may register with the service using a certificate installed on the new device and a private key. The new device may send a message (e.g., a PairDeviceToAccount message) to the service containing the service account identification associated with the fabric **1000** and an account pairing token obtained from the service configuration information. Using this information, the service may validate the account pairing token and may associate the new device with the user's service account associated with the fabric. At this point, the new device may be understood by the service to form a part of the fabric **1000** and may appear as an associated device when the user logs into the service. The service may respond to the message from the new device

(e.g., the PairDeviceToAccount message), may destroy its copy of the account pairing token, and may respond to the message previously sent to the application (e.g., the RegisterService request).

In response, to finalize the joining of the new device to the existing fabric **1000** or the new fabric, the application may cancel the joining failsafe mechanism by sending a corresponding message to the new device (e.g., a DisarmConfigurationFailsafe request) (block **1886**). The new device thereafter may receive this request to disarm the configuration failsafe (block **1888**). Pairing of the new device to the existing device in either a new fabric **1000** or an existing fabric **1000** may now be considered complete. The application on the client device thus may offer the user instructions for additional setup settings (block **1890**) that the user may select from (block **1892**). These may include, for example, continuing to pair additional devices or exiting setup. Joining or Creating a Fabric Without a WiFi Connection to the Internet

A new device may join or create a fabric **1000** without necessarily having access to a WiFi connection to a service or the Internet. For example, as shown in FIGS. **65-67**, such a connection may be formed using other network connection without facilitation by a service (e.g., over just an 802.15.4 network connection). This section describes the actions and events that may happen during the process of joining a new device in a device-to-device fabric. As used herein, a "device-to-device fabric" is a network of two or more fabric **1000** devices connected via a single network interface (e.g., via 802.15.4 interfaces only). Devices in a device-to-device fabric **1000** are not necessarily connected to a WiFi network and thus may not talk to an application (e.g., web or mobile) running on a client device (as in FIGS. **62-64**) or to a service on the Internet (e.g., the Nest® service).

In some cases, device-to-device fabrics may be easier to form than WiFi fabrics, involving user participation only in that the user may press buttons on two devices within a short period of time. The device-to-device joining process described by FIGS. **65-67** may support both the creation of a new device-to-device fabric **1000** using two independent devices, as well as the joining of a new independent device to an existing device-to-device fabric. Device-to-device joining can also be used to remove a device from an existing device-to-device fabric **1000** and join it to another device-to-device fabric. This latter scenario may become particularly useful when a user acquires a used device that wasn't properly severed from its old device-to-device fabric.

Note that the device-to-device joining process may not be used to join a new device into an existing WiFi fabric **1000** in some embodiments. For this, the user may follow the WiFi joining process discussed above with reference to FIGS. **62-64**. Also, the device-to-device joining process may not be used to join a device that is already a member of a WiFi fabric **1000** into a device-to-device fabric. Thus, in the case where a user acquires a used device that wasn't properly severed from its original WiFi fabric, the user may perform a factory reset on the device before proceeding with the device-to-device fabric **1000** joining process.

The device-to-device joining process may begin when, as shown by a flowchart **1900** of FIG. **65**, a first device (e.g., Device 1) of two devices that are to be joined is activated (block **1902**). For example, based on instructions in the sales box of the first device, a user may press a button on the first device. Here, if the user is adding a device to an existing fabric, the user may be instructed to press the button on the device to be added. If the user is creating a new fabric **1000** out of two independent devices, the user may select either

65

device as the first device. Also, if the first device is a member of a WiFi fabric, the first device may take no further action and the joining procedure stops. When the first device is a member of a WiFi fabric, the first device may be disassociated with the WiFi fabric **1000** before joining the device-to-device network (e.g., via a factory reset).

When not a member of an existing WiFi fabric, the first device (e.g., Device 1) may begin certain initialization procedures when activated as in block **1902**. For example, Device 1 may start a counter that increments with time (e.g., multiple times a second). This counter will later be used to determine which device is of two device has priority in establishing a fabric, if appropriate. Device 1 also may create an 802.15.4 wireless network, which may be called the 802.15.4 joining network (block **1904**). This 802.15.4 joining network may be a generally unique, unsecured network. For example, the 802.15.4 joining network may use a generally unique ELoWPAN **110** network name containing the following information: (a) a string identifying the network as a joining network, (b) the first device's node id, and (c) a flag indicating whether the device is part of a fabric. When the joining network is established, Device 1 may also assign itself two IPv6 addresses in the joining network (block **1906**). These may include, for example: (a) an IPv6 ULA or EULA with a distinct prefix, which may be called the rendezvous prefix, and an interface identifier derived from the device's MAC address, and (b) an IPv6 ULA or EULA with the rendezvous prefix and an interface identifier of 1, which may be called the rendezvous address.

Device 1 then may continuously scan for an 802.15.4 network created by another device (block **1908**). Indeed, in parallel to or after the acts of blocks **1902-1908**, a second device (Device 2) may perform the above acts itself (block **1910**). Either Device 1 or Device 2 may detect the other's joining network (block **1912**). Depending on certain characteristics of the device—Device 1 or Device 2—that is first to detect the other, the devices may perform an initiating device process (e.g., as shown in FIG. **66**) or a responding device process (e.g., as shown in FIG. **67**). That is, when one of the devices discovers the other's joining network, the device compares the information contained in the joining network name with its own information and may takes action as follows: (a) if the device is an independent device and the other device is a member of a fabric, the device may performs the acts shown in the initiating device process of FIG. **66**; or (b) if the device is a member of a fabric **1000** and the other device is an independent device, the device may perform the acts shown by the responding device process of FIG. **67**. If neither device is a member of a fabric, or if both devices are members of a fabric, the device that detects the other device's joining network may (a) compare its node id to the node id of the other device and (b) if the device's node id is less than the node id of the other device, the device may perform the acts of the acts shown in the initiating device process of FIG. **66**, if neither device is a member of a fabric, or if both devices are members of a fabric, the device that detects the other device's joining network may (a) compare its node id to the node id of the other device and (b) if the device's node id is greater than the node id of the other device, may perform the acts shown by the responding device process of FIG. **67**.

The device that performs the initiating device process of FIG. **66** may be either Device 1 or Device 2, as mentioned above. As such, the device that performs the initiating device process of FIG. **66** will now be referred to as the "initiating device." Likewise, the device that performs the responding device process of FIG. **67** may be the device not operating as the initiating device, and may be either Device 1 or Device 2,

66

as mentioned above. As such, the device that performs the responding device process of FIG. **67** will now be referred to as the "responding device."

As seen in a flowchart **1920**, the initiating device process of FIG. **66** may begin when the initiating device terminates its joining network and connects to the joining network created by the responding device (block **1922**). The initiating device may assign itself a IPv6 ULA or EULA with the rendezvous prefix and an interface identifier derived from its MAC address (block **1924**). The initiating device may send a Solicit Joining message to the responding device at its rendezvous address. The Solicit Joining message from the initiating device may include the following information: (a) a numeric discriminator value set to the value of the counter that was started when the device and woke up, and (b) a flag indicating whether the device is already a member of a fabric. The initiating device then may wait for a response message from the responding device, receiving either a Join Existing Fabric request or a Solicit Joining request (block **1928**).

When the initiating device receives a Join Existing Fabric request, the initiating device may leave its current fabric, if appropriate, and may reinitialize itself as an independent device, and may make itself part of the existing fabric **1000** with the responding device, using the information in the Join Existing Fabric request (block **1930**). The initiating device may send a Join Existing Fabric response to the responding device indicating it is now a member of the existing fabric **1000** (block **1932**).

When the initiating device receives a Solicit Joining request, the initiating device may respond in different manners depending on whether it is an independent device or a member of an existing fabric, but in either case may send fabric **1000** information in a Join Existing Fabric request (block **1934**). For example, when the initiating device is an independent device, the initiating device may create a new fabric **1000** by generating a new fabric id and corresponding fabric security information, may make itself part of the new fabric, and may send a Join Existing Fabric request to the responding device. The Join Existing Fabric request may contain the information for the new fabric. Otherwise, if the device is a member of a fabric, the device may send a Join Existing Fabric request to the responding device that contains the information for the existing fabric **1000** that the initiating device is a member of. The initiating device then may wait for, and receive, a Join Existing Fabric response from the responding device when the responding device joins the fabric **1000** of the initiating device.

The responding device process of FIG. **67** describes a manner in which the responding device may behave in relation to the initiating device. The responding device process of FIG. **67** is described by a flowchart **1950**. The flowchart **1950** begins when the responding device receives a Solicit Joining message from the initiating device (block **1952**).

If the responding device is an independent device and is not in an existing fabric **1000** (decision block **1954**), the responding device may create a new fabric **1000** by generating a new fabric id and corresponding fabric security information (block **1956**). The responding device may make itself part of the new fabric **1000** (block **1958**). The responding device then may send a Join Existing Fabric request to the initiating device that contains the information for the new fabric **1000** of the responding device (block **1960**). The responding device may wait for the Join Existing Fabric response from the initiating device.

Otherwise, upon receipt of the Solicit Joining message (block **1952**), if the responding device is in an existing fabric **1000** (decision block **1954**), the responding device may adopt

67

a different behavior. Specifically, if the responding device is in a fabric, the responding device may inspect the Solicit Joining message (block 1962). The responding device may inspect the discriminator value (the counter value of the initiating device) and the 'is member of fabric' flag in the Solicit Joining

Otherwise, if the Solicit Joining message indicates that the initiating device is not a member of a fabric 1000 or if the discriminator value is greater than or equal to the counter started by the responding device when it woke up (decision block 1964), the responding device may send a Join Existing Fabric request to the initiating device that contains the information for the fabric 1000 of the responding device (block 1974). The responding device may wait for the Join Existing Fabric response from the initiating device.

If the Solicit Joining message indicates that the initiating device is a member of a fabric 1000 or if the discriminator value is less than the counter started by the responding device when it woke up (decision block 1964), the responding device may leave its current fabric 1000 and reinitializes itself as an independent device (block 1966). The responding device may further send a Solicit Joining message to the initiating device (block 1968) and may wait for a Join Existing Fabric request from the initiating device. Upon receiving the Join Existing Fabric request from the initiating device (block 1970), the responding device may make itself part of the new fabric 1000 using the information in the Join Existing Fabric request (block 1972). The responding device may also send a Join Existing Fabric response indicating it is now a member of the existing fabric 1000 of the initiating device.

The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

What is claimed is:

1. An electronic device comprising:

a memory or storage device storing instructions to operate a network stack;

a processor configured to execute the instructions to operate the network stack; and

a network interface configured to join a network-connected fabric of devices and communicate a message to a target device of the fabric of devices using the network stack;

wherein the network stack comprises:

an application layer configured to provide an application payload comprising data to be transmitted in the message;

a platform layer configured to encapsulate the application payload in a general message format of the message;

a transport layer configured to selectably transport the message using either User Datagram Protocol (UDP) or Transmission Control Protocol (TCP); and

a network layer configured to communicate the message using Internet Protocol Version 6 (IPv6) via:

an 802.11 wireless network;

an 802.15.4 wireless network;

a powerline network;

a cellular network;

an Ethernet network; or

any combination thereof;

wherein the application layer, the platform layer, the transport layer, the network layer, or any combination

68

thereof, are configured to determine a property of a manner of communication of the message to the target device based at least in part on:

a type of the message;

the network over which the message is to be sent;

a distance over which the message may travel through the fabric;

power consumption behavior of the electronic device;

power consumption behavior of the target device;

power consumption behavior of an intervening device of the fabric of devices that is to communicate the message between the electronic device and the target device;

whether the target device comprises a service; or

any combination thereof; and

wherein varying the property of the manner of communication is configured to cause the electronic device, the target device, or the intervening device, or any combination thereof, to consume different amounts of power and cause the message to more reliably or less reliably reach the target device; and

wherein the processor is configured to determine whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on the network over which the message is to be sent, a distance over which the message may travel through the fabric, or whether the electronic device is powered by a power source external to the electronic device.

2. The electronic device of claim 1, wherein the property of the manner of communication comprises:

a determination to select Transmission Control Protocol (TCP) to transport the message;

a determination to select User Datagram Protocol (UDP) to transport the message;

a determination to communicate the message using a lower-power network;

a determination to communicate the message using a higher-power network;

a determination to select a preferred network of the target device as a higher-power network indicated in an Extended Unique Local Address (EULA) encoded in an IPv6 packet header of the message;

a determination to select a preferred network of the target device as a lower-power network indicated in the Extended Unique Local Address (EULA) encoded in the IPv6 packet header of the message; or

any combination thereof.

3. The electronic device of claim 1, wherein the application layer is configured to determine whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on an urgency of the message.

4. The electronic device of claim 3, wherein the message comprises an urgent message when the message communicates a device alarm and wherein the message comprises a non-urgent message when the message communicates an indication of a non-hazardous environmental condition without a device alarm.

5. The electronic device of claim 4, wherein the message is configured to be transported using TCP when the message comprises an urgent message, wherein the message is configured to be transported using UDP when the message comprises a non-urgent message.

6. The electronic device of claim 1, wherein the application layer is configured to determine whether to transport the

69

message using TCP or UDP depending on the network over which the message is to be sent.

7. The electronic device of claim 6, wherein the message is configured to be transported using TCP when the network over which the message is to be sent comprises a WiFi network, wherein the message is configured to be transported using UDP when the network over which the message is to be sent comprises an 802.15.4 wireless network.

8. The electronic device of claim 1, wherein the application layer is configured to determine whether to transport the message using TCP or UDP depending on a distance over which the message may travel through the fabric.

9. The electronic device of claim 8, wherein the message is configured to be transported using TCP when the distance over which the message may travel through the fabric network is greater than a threshold, wherein the message is configured to be transported using UDP when the distance over which the message may travel through the fabric network is less than a threshold.

10. The electronic device of claim 1, wherein the application layer is configured to determine whether to transport the message using TCP or UDP depending on whether the device is powered by a power source external to the device.

11. The electronic device of claim 10, wherein the message is configured to be transported using TCP when the device is powered by a power source external to the device, wherein the message is configured to be transported using UDP when the device is powered by a power source internal to the device.

12. The electronic device of claim 1, wherein the application layer is configured to determine whether to transport the message using TCP or UDP depending on whether the device is transmitting the message to the target device comprising a service.

13. A tangible non-transitory machine readable medium configured to store instructions thereon, wherein the instructions comprise:

- a network stack, utilized to join a network-connected fabric of devices and communicate a message to a target device of the fabric of devices, wherein the network stack comprises:
 - an application layer configured to provide an application payload comprising data to be transmitted in the message;
 - a platform layer configured to encapsulate the application payload in a general message format of the message;
 - a transport layer configured to selectably transport the message using either User Datagram Protocol (UDP) or Transmission Control Protocol (TCP); and
 - a network layer configured to communicate the message using Internet Protocol Version 6 (IPv6) via:
 - an 802.11 wireless network;
 - an 802.15.4 wireless network;
 - a powerline network;
 - a cellular network;
 - an Ethernet network; or
 - any combination thereof;
- wherein the application layer, the platform layer, the transport layer, the network layer, or any combination thereof, are configured to determine a property of a manner of communication of the message to the target device based at least in part on:
 - a type of the message;
 - the network over which the message is to be sent;
 - a distance over which the message may travel through the fabric;
 - power consumption behavior of the electronic device;

70

power consumption behavior of the target device;

power consumption behavior of an intervening device of the fabric of devices that is to communicate the message between the electronic device and the target device;

whether the target device comprises a service; or any combination thereof; and

wherein varying the property of the manner of communication is configured to cause the electronic device, the target device, or the intervening device, or any combination thereof, to consume different amounts of power and cause the message to more reliably or less reliably reach the target device; and

wherein the instructions are configured to determine whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on the network over which the message is to be sent, a distance over which the message may travel through the fabric, or whether the electronic device is powered by a power source external to the electronic device.

14. The tangible non-transitory machine readable medium of claim 13 wherein the property of the manner of communication comprises:

- a determination to select Transmission Control Protocol (TCP) to transport the message;
- a determination to select User Datagram Protocol (UDP) to transport the message;
- a determination to communicate the message using a lower-power network;
- a determination to communicate the message using a higher-power network;
- a determination to select a preferred network of the target device as a higher-power network indicated in an Extended Unique Local Address (EULA) encoded in an IPv6 packet header of the message;
- a determination to select a preferred network of the target device as a lower-power network indicated in the Extended Unique Local Address (EULA) encoded in an IPv6 packet header of the message; or
- any combination thereof.

15. The tangible non-transitory machine readable medium of claim 13, wherein the application layer is configured to determine whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on an urgency of the message.

16. The tangible non-transitory machine readable medium of claim 15, wherein the message comprises an urgent message when the message communicates a device alarm and wherein the message comprises a non-urgent message when the message communicates an indication of a non-hazardous environmental condition without a device alarm.

17. A method, comprising:

- storing instructions, at a memory or storage device of an electronic device, to operate a network stack;
- executing, via a processor of the electronic device, the instructions to operate the network stack;
- joining, via a network interface of the electronic device, a network-connected fabric of devices;
- communicating, via the network interface, a message to a target device of the fabric of devices using the network stack, wherein the network stack comprises:
 - an application layer configured to provide an application payload comprising data to be transmitted in the message;

71

a platform layer configured to encapsulate the application payload in a general message format of the message;

a transport layer configured to selectably transport the message using either User Datagram Protocol (UDP) or Transmission Control Protocol (TCP); and

a network layer configured to communicate the message using Internet Protocol Version 6 (IPv6) via:

- an 802.11 wireless network;
- an 802.15.4 wireless network;
- a powerline network;
- a cellular network;
- an Ethernet network; or
- any combination thereof; and

determining, via the application layer, the platform layer, the transport layer, the network layer, or any combination thereof, a property of a manner of communication of the message to the target device based at least in part on:

- a type of the message;
- the network over which the message is to be sent;
- a distance over which the message may travel through the fabric;
- power consumption behavior of the electronic device;
- power consumption behavior of the target device;
- power consumption behavior of an intervening device of the fabric of devices that is to communicate the message between the electronic device and the target device;
- whether the target device comprises a service; or
- any combination thereof;

wherein varying the property of the manner of communication is configured to cause the electronic device, the target device, or the intervening device, or any combination thereof,

72

to consume different amounts of power and cause the message to more reliably or less reliably reach the target device; and

determining whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on the network over which the message is to be sent, a distance over which the message may travel through the fabric, or whether the device is powered by a power source external to the device.

18. The method of claim 17, wherein determining the property of the manner of communication includes:

- a determination to select Transmission Control Protocol (TCP) to transport the message;

- a determination to select User Datagram Protocol (UDP) to transport the message;

- a determination to communicate the message using a lower-power network;

- a determination to communicate the message using a higher-power network;

- a determination to select a preferred network of the target device as a higher-power network indicated in an Extended Unique Local Address (EULA) encoded in an IPv6 packet header of the message;

- a determination to select a preferred network of the target device as a lower-power network indicated in the Extended Unique Local Address (EULA) encoded in the IPv6 packet header of the message; or

- any combination thereof.

19. The method of claim 17, comprising determining whether to transport the message using Transmission Control Protocol (TCP) or User Datagram Protocol (UDP) depending on an urgency of the message.

* * * * *