




(72) ELLIS, Frampton E., III, US

(71) ELLIS, Frampton E., III, US

(51) Int.Cl.⁶ G06F 11/30

(30) 1996/11/29 (60/031,855) US

(30) 1996/12/02 (60/032,207) US

(30) 1996/12/20 (60/033,871) US


(30) 1997/11/21 (60/066,313) US

(30) 1997/11/24 (60/066,415) US

(30) 1997/11/26 (08/980,058) US


(54) **ORDINATEURS DE RESEAU A COUVERTURE MONDIALE**

(54) **GLOBAL NETWORK COMPUTERS**



(57) Cette invention se rapporte de manière générale à au moins un réseau d'ordinateurs comportant des ordinateurs du type ordinateurs personnels ou serveurs de réseaux dotés de microprocesseurs reliés par des organes de transmission à large bande et comportant des organes matériels, logiciels, microprogrammés et autres tels qu'au moins une opération de traitement parallèle exécutée implique au moins deux ordinateurs du réseau. De manière plus spécifique, l'invention se rapporte à au moins un grand réseau composé de réseaux plus petits et d'un grand nombre d'ordinateurs reliés, tel que l'Internet, dans lequel au moins deux opérations de traitement parallèle distinctes impliquant au moins deux ensembles différents d'ordinateurs se produisent simultanément et dans lequel les liens entre les

(57) This invention relates to computer networks having computers like personal computers (1) or network servers (2) with microprocessors linked (5) by transmission means (4, 14) and having hardware, and other means such that at least one parallel processing operation occurs that involve at least two computers in the network. This invention also relates to large networks composed of smaller networks, like the Internet (3), wherein more than one separate parallel processing operation involving more than one set of computers occurs simultaneously and wherein ongoing processing linkages can be established between microprocessors of separate computers connected to the network. This invention further relates to business arrangements enabling the shared used of network microprocessors for



(21) (A1) **2,272,332**
(86) 1997/11/28
(87) 1998/06/18

traitements en cours peuvent être établis entre pratiquement tous les microprocesseurs des ordinateurs distincts reliés au réseau. De manière encore plus spécifique, cette invention se rapporte à des agencements commerciaux autorisant l'utilisation partagée de microprocesseurs de réseaux en vue d'un traitement parallèle ou autre, dans lesquels les propriétaires d'ordinateurs personnels apportent la puissance de traitement de microprocesseurs à un réseau, de préférence en vue d'un traitement parallèle, en échange d'un lien réseau avec d'autres ordinateurs personnels ou autres fournis par des fournisseurs de services réseaux, et notamment un lien avec d'autres microprocesseurs en vue d'un traitement parallèle ou autre. L'échange entre propriétaires et fournisseurs peut se faire sur la base de tout terme accepté par les deux parties, étant entendu que cet échange est conforme aux lois, règlements ou règles en vigueur, la rémunération de l'une des parties notamment se faisant au profit de l'autre partie sur la base d'une mesure périodique de l'utilisation nette ou de la fourniture de la puissance de traitement.

parallel and other processing, wherein personal computer owners provide microprocessor processing power to a network, in exchange for linkage to other computers, including linkage to other microprocessors; the basis of the exchange between owners and providers being whatever terms to which the parties agree.



CORRECTED
VERSION*


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 11/30		A3	(11) International Publication Number: WO 98/26366
			(43) International Publication Date: 18 June 1998 (18.06.98)
(21) International Application Number: PCT/US97/21812		(71)(72) Applicant and Inventor: ELLIS, Frampton, E., III [US/US]; Suite B2, 2895 South Abingdon Street, Arlington, VA 22206-1331 (US).	
(22) International Filing Date: 28 November 1997 (28.11.97)		(74) Agent: LAZAR, Dale, S.; Cushman Darby & Cushman, Intellectual Property Group, 1100 New York Avenue, N.W., Washington, D.C. 20005 (US).	
(30) Priority Data:		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DE (Utility model), DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
60/031,855 29 November 1996 (29.11.96) US 60/032,207 2 December 1996 (02.12.96) US 60/033,871 20 December 1996 (20.12.96) US Not furnished 21 November 1997 (21.11.97) US Not furnished 24 November 1997 (24.11.97) US Not furnished 26 November 1997 (26.11.97) US		Published <i>With international search report.</i>	
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Applications		(88) Date of publication of the international search report: 3 September 1998 (03.09.98)	
US 60/032,207 (CIP) Filed on 2 December 1996 (02.12.96) US 60/031,855 (CIP) Filed on 29 November 1996 (29.11.96) US 60/033,871 (CIP) Filed on 20 December 1996 (20.12.96) US 60/066,613 (CIP) Filed on 21 November 1997 (21.11.97) US 60/066,415 (CIP) Filed on 24 November 1997 (24.11.97) US 08/980,058 (CIP) Filed on 26 November 1997 (26.11.97)			

(54) Title: GLOBAL NETWORK COMPUTERS



(57) Abstract

This invention relates to computer networks having computers like personal computers (1) or network servers (2) with microprocessors linked (5) by transmission means (4, 14) and having hardware, and other means such that at least one parallel processing operation occurs that involve at least two computers in the network. This invention also relates to large networks composed of smaller networks, like the Internet (3), wherein more than one separate parallel processing operation involving more than one set of computers occurs simultaneously and wherein ongoing processing linkages can be established between microprocessors of separate computers connected to the network. This invention further relates to business arrangements enabling the shared used of network microprocessors for parallel and other processing, wherein personal computer owners provide microprocessor processing power to a network, in exchange for linkage to other computers, including linkage to other microprocessors; the basis of the exchange between owners and providers being whatever terms to which the parties agree.

WO 98/26366

PCT/US97/21812

1

GLOBAL NETWORK COMPUTERSBACKGROUND OF THE INVENTION

5 This invention generally relates to one or more
computer networks having computers like personal
computers or network computers such as servers with
microprocessors preferably linked by broadband
transmission means and having hardware, software,
firmware, and other means such that at least two parallel
10 processing operations occur that involve at least two
sets of computers in the network or in networks connected
together, a form of metacomputing. More particularly,
this invention relates to one or more large networks
composed of smaller networks and large numbers of
15 computers connected, like the Internet, wherein more than
one separate parallel or massively parallel processing
operation involving more than one different set of
computers occurs simultaneously. Even more particularly,
this invention relates to one or more such networks
20 wherein more than one (or a very large number of)
parallel or massively parallel microprocessing processing
operations occur separately or in an interrelated
fashion; and wherein ongoing network processing linkages
can be established between virtually any microprocessors
25 of separate computers connected to the network.

Still more particularly, this invention relates
generally to a network structure or architecture that
enables the shared use of network microprocessors for
parallel processing, including massive parallel
30 processing, and other shared processing such as
multitasking, wherein personal computer owners provide
microprocessor processing power to a network, preferably
for parallel or massively parallel processing or
multitasking, in exchange for network linkage to other
35 personal and other computers supplied by network
providers such as Internet Service Providers (ISP's),
including linkage to other microprocessors for parallel

WO 98/26366

PCT/US97/21812

2

or other processing such as multitasking. The financial basis of the shared use between owners and providers would be whatever terms to which the parties agree, subject to governing laws, regulations, or rules, including payment from either party to the other based on periodic measurement of net use or provision of processing power or preferably involving no payment, with the network system (software, hardware, etc) providing an essentially equivalent usage of computing resources by both users and providers (since any network computer operated by either entity can potentially be both a user and provider of computing resources alternately (or even simultaneously, assuming multitasking), with potentially an override option by a user (exercised on the basis, for example, of user profile or user's credit line or through relatively instant payment).

Finally, this invention relates to a network system architecture including hardware and software that will provide use of the Internet or its future equivalents or successors (and most other networks) without cost to most users of personal computers or most other computers, while also providing those users (and all other users, including of supercomputers) with computer processing performance that will at least double every 18 months through metacomputing means. This metacomputing performance increase provided by the new MetaInternet (or Metanet for short) will be in addition to all other performance increases, such as those already anticipated by Moore's Law.

By way of background, the computer industry has been governed over the last 30 years by Moore's Law, which holds that the circuitry of computer chips has been shrunk by substantially each year, yielding a new generation of chips every 18 months with twice as many transistors, so that microprocessor computing power is effectively doubled every year and a half.

The long term trend in computer chip miniaturization

WO 98/26366

PCT/US97/21812

3

is projected to continue unabated over the next few decades. For example, slightly more than a decade ago a 16 kilobit DRAM memory chip (storing 16,000 data bits) was typical; the current standard 16 megabit chip
5 (16,000,000 data bits) was introduced in 1993; and industry projections are for 16 gigabit memory chips (16,000,000,000 data bits) to be introduced in 2008 and 64 gigabit chips in 2011, with 16 terabit chips (16,000,000,000,000 data bits) conceivable by the mid-to-
10 late 2020's. This is a thousand-fold increase regularly every fifteen years. Hard drive speed and capacity are also growing at a spectacular rate.

Similarly regular and enormous improvements are anticipated to continue in microprocessor computing
15 speeds, whether measured in simple clock speed or MIPS (millions of instructions for second) or numbers of transistors per chip. For example, performance has improved by four or five times every three years since Intel launched its X86 family of microprocessors used in
20 the currently dominant "Wintel" standard personal computers. The initial Intel Pentium Pro microprocessor was introduced in 1995 and is a thousand times faster than the first IBM standard PC microprocessor, the Intel 8088, which was introduced in 1979. The fastest of
25 current microprocessors like Digital Equipment Corp.'s Alpha chip is faster than the processor in the original Cray Y-MP supercomputer.

Both microprocessors and software (and firmware and other components) are also evolving from 8 bit and 16 bit
30 systems into 32 bit systems that are becoming the standard today, with some 64 bit systems like the DEC Alpha already introduced and more coming, with future increases to 128 bit also likely.

A second major development trend in the past decade
35 or so has been the rise of parallel processing, a computer architecture utilizing more than one CPU microprocessor (often many more, even thousands of

WO 98/26366

PCT/US97/21812

4

relatively simple microprocessors, for massively parallel processing) linked together into a single computer with new operating systems having modifications that allow such an approach. The field of supercomputing has been
5 taken over by this approach, including designs utilizing many identical standard personal computer microprocessors.

Hardware, firmware, software and other components specific to parallel processing are in a relatively early
10 stage of development compared to that for single processor computing, and therefore much further design and development is expected in the future to better maximize the computing capacity made possible by parallel processing. One potential benefit that will likely be
15 available soon is system architecture that does not rely on the multiple microprocessors having to share memory, thereby allowing more independent operation of those microprocessors, each with their own discrete memory, like current personal computers, workstations and most
20 other computer systems architecture; for unconstrained operation, each individual microprocessor must have rapid access to sufficient memory.

Several models of personal computers are now available with more than one microprocessor. It seems
25 inevitable that in the future personal computers, broadly defined to include versions not currently in use, will also employ parallel computing utilizing multiple microprocessors or massively parallel computing with very large numbers of microprocessors. Future designs, such
30 Intel's Merced chip, will have a significant number of parallel processors on a single microprocessor chip.

A form of parallel processing is also being employed within microprocessor design itself. The current
generation of microprocessors such as the Intel Pentium
35 have more than one data path within the microprocessor in which data can be processed, with two to three paths being typical.

WO 98/26366

PCT/US97/21812

5

The third major development trend is the increasing size of bandwidth, which is a measure of communications power between computers connected by a network. Before now, the local area networks and telephone lines typically linking computers including personal computers have operated at speeds much lower than the processing speeds of a personal computer. For example, a typical Intel Pentium operates at 100 MIPS (millions of instructions per second), whereas a typical Ethernet connecting the PC's is 100 times slower at 10 megabits per second (Mbps) and telephone lines are very much slower, the highest typical speed now being about 28.8 kilobits.

Now, however, the situation is expected to change dramatically, with bandwidth being anticipated to expand from 5 to 100 times as fast as the rise of microprocessor speeds, due to the use of coaxial cable, wireless, and fiber optic cable. Telecommunication providers are now making available fiber connections supporting bandwidth of 40 gigabits.

Technical improvements are expected in the near term which will make it possible to carry over 2 gigahertz (billions of cycles per second) on each of 700 wavelength stream, adding up to more than 1,700 gigahertz on every single fiber thread. Experts believe that the bandwidth of optical fiber has been utilized one million times less fully than the bandwidth of coaxial or twisted pair copper lines. Within a decade, 10,000 wavelength streams per fiber are expected and 20 wavelengths on a single fiber is already commercially available.

Other network connection developments such as asynchronous transfer mode (ATM) and digital signal processors, which are improving their price/performance tenfold every two years, are also supporting the rapid increase in bandwidth. The increase in bandwidth reduces the need for switching and switching speed will be greatly enhanced when practical optical switches are

WO 98/26366

PCT/US97/21812

6

introduced in the fairly near future, potentially reducing costs substantially.

The result of this huge bandwidth increase will be extraordinary: within just a few years it will be technically possible to connect virtually any computer to a network at a speed that equals or exceeds the computer's own internal bus speed, even as that bus speed itself is increasing significantly. The bus of a computer is its internal network connecting its components such as microprocessor, random access memory (RAM), hard-drive, modem, floppy drive, and CD-ROM; for recent personal computers it has been only about 40 megabits per second, but is now up to a gigabit per second on Intel's Pentium PCI bus.

Despite these tremendous improvements anticipated in the future, the unfortunate present reality is that a typical personal computer (PC) is already so fast that its microprocessor is essentially idle during most of the time the PC is in actual use and that operating time itself is but a small fraction of those days the PC is even in any use at all. The reality is that nearly all PC's are essentially idle during roughly all of their useful life. A realistic estimate is that its microprocessor is in an idle state 99.9% of the time (disregarding current unnecessary microprocessor busywork like executing screen saver programs, which have been made essentially obsolete by power-saving CRT monitor technology, which is now standard in the PC industry).

Given the fact that the reliability of PC's is so exceptionally high now, with the mean time to failure of all components typically several hundred thousand hours or more, the huge idle time of PC's represents a total loss; given the high capital and operating costs of PC's, the economic loss is very high. PC idle time does not in effect store a PC, saving it for future use, since the principle limiting factor to continued use of today's PC's is obsolescence, not equipment failure from use.

Moreover, there is growing concern that Moore's Law, which as noted above holds that the constant miniaturization of circuits results in a doubling of computing power every 18 months, cannot continue to hold true much longer. Indeed, Moore's Law may now be nearing its limits for silicon-based devices, perhaps by as early as 2004, and no new technologies have yet emerged that currently seem with reasonable certainty to have the potential for development to a practical level by then.

10 SUMMARY OF THE INVENTION

However, the confluence of all three of the established major trends summarized above -- supercomputer-like personal computers, the spread of parallel processing using personal computer microprocessors (particularly massively parallel processing), and the enormous increase in network communications bandwidth -- will make possible in the near future a surprising solution to the hugely excessive idleness problem of personal computers (and to the problematic possible end of Moore's Law), with very high potential economic savings.

The solution is use those mostly idle PC's (or their equivalents or successors) to build a parallel or massively parallel processing computer utilizing a very large network like the Internet or, more specifically, like the World Wide Web (WWW), or their equivalents or eventual successors like the MetaInternet (and including Internet II, which is under development now and which will utilize much broader bandwidth and will coexist with the Internet, the structure of which is in ever constant hardware and software upgrade) with broad bandwidth connections. The prime characteristic of the Internet is of course the very large number of computers of all sorts already linked to it, with the future potential for effectively universal connection; it is a network of networks of computers that provides nearly unrestricted access (other than cost) worldwide. The soon-to-be

WO 98/26366

PCT/US97/21812

8

available very broad bandwidth of network communications can be used to link personal computers externally in a manner equivalent to the internal buses of the personal computers, so that no processing constraint will be
5 imposed on linked personal computers by data input or output, or throughput; the speed of the microprocessor itself will be the only processing constraint of the system.

This will make external parallel processing
10 possible, including massively parallel processing, in a manner paralleling more conventional internal parallel processing.

Optimally, the World Wide Web (or its equivalents or successors) will be transformed into a huge virtual
15 massively parallel processing computer or computers, with potential through its established hyperlinks connections to operate in a manner at least somewhat like a neural network or neural networks, since the speed of transmission in the linkages would be so great that any
20 linkage between two microprocessors would be virtually equivalent to direct, physically close connections between those microprocessors.

With further development, digital signal processor-type microprocessors or even analogue microprocessors may
25 be optimal for this approach. Networks with WWW-type hyperlinks incorporating digital signal processor-type microprocessor (or successors or equivalents) could operate separately from networks of conventional microprocessors (or successors or equivalents) or with
30 one or more connections between such differing networks or with relatively complete integration between such differing networks. Simultaneous operation across the same network connection structure should be possible.

Such broad bandwidth networks of computers will
35 enable every PC to be fully utilized or nearly so. Because of the extraordinary extent to which existing PC's are currently idle, at optimal performance this new

WO 98/26366

PCT/US97/21812

9

system will potentially result in a thousand-fold increase in computer power available to each and every PC user (and any other user); and, on demand, almost any desired level of increased power, limited mostly by the increased cost, which however would be relatively far less than possible from any other conceivable computer network configuration. This revolutionary increase is on top of the extremely rapid, but evolutionary increases already occurring in the computer/network industry discussed above.

The metacomputing hardware and software means of the MetaInternet will provide performance increases that will likely at least double every eighteen months based on the doubling of personal computers shared in a typical parallel processing operation by a standard PC user, starting first with at least 2 PC's, then about 4, about 8, about 16, about 32, about 64, about 128, about 256, and about 512. After about fifteen years, each standard PC user will likely be able to use about 1024 personal computers for parallel processing or any other shared computing use, while generally using the Internet or its successors like the MetaInternet for free. At the other end of the performance spectrum, supercomputers will experience a similar performance increase generally, but ultimately the performance increase is limited primarily by cost of adding temporary network linkages to available PC's, so there is definite potential for a quantum leap in supercomputer performance.

Network computer systems as described above offer almost limitless flexibility due to the abundant supply of heretofore idle connected microprocessors. This advantage would allow "tightly coupled" computing problems (which normally are difficult to process in parallel) to be solved without knowing in advance (as is now necessary in relatively massively parallel processing) how many processors are available, what they are and their connection characteristics. A minimum

number of equivalent processors (with equivalent other specs) can be easily found nearby in a massive network like the Internet and assigned within the network from those multitudes available nearby. Moreover, the number
5 of microprocessors used can be almost completely flexible, depending on the complexity of the problem, and limited only by cost. The current problem of time delay will be solved largely by the widespread introduction of broad bandwidth connections between computers processing
10 in parallel.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a meter means which measures flow of
15 computing during a shared operation such as parallel processing between a typical PC user and a network provider.

Figure 2 is a simplified diagram of a section of a computer network, such as the Internet, showing an
20 embodiment of another meter means which measures the flow of network resources, including shared processing, being provided to a typical PC user and a network provider.

Figure 3 is a simplified diagram of a section of a computer network, such as the Internet, showing an
25 embodiment of another meter means which, prior to execution, estimates the level of network resources, and their cost, of a shared processing operation requested by a typical PC user from a network provider.

Figure 4A-4C are simplified diagrams of a section of
30 a computer network, such as the Internet, showing in a sequence of steps an embodiment of a selection means whereby a shared processing request by a PC is matched with a standard preset number of other PC's to execute shared operation.

35 Figure 5 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a control means whereby the PC, when idled

by its user, is made available to the network for shared processing operations.

Figure 6 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a signal means whereby the PC, when idled by its user, signals its availability to the network for shared processing operations.

Figure 7 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a receiver and/or interrogator means whereby the network receives and/or queries the availability for shared processing status of a PC within the network.

Figure 8 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a selection and/or utilization means whereby the network locates available PC's in the network that are located closest to each other for shared processing.

Figure 9 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a system architecture for conducting a request imitated by a PC for a search using parallel processing means that utilizes a number of networked PC's.

Figures 10A-10I are simplified diagrams of a section of a computer network, such as the Internet, showing an embodiment of a system architecture utilizing a firewall to separate that part of a networked PC (including a system reduced in size to a microchip) that is accessible to the network for shared processing from a part that is kept accessible only to the PC user; also showing the alternating role that preferably each PC in the network can play as either a master or slave in a shared processing operation involving one or more slave PC's in the network; and showing a home or business network system.

Figure 11 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a system architecture for connecting clusters of PC's to each other by wireless means, to
5 create the closest possible (and therefore fastest) connections.

Figure 12 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a system architecture for connecting PC's
10 to a satellite by wireless means.

Figure 13 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a system architecture providing a cluster of networked PC's with complete interconnectivity by
15 wireless means.

Figure 14A is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a transponder means whereby a PC can identify one or more of the closest available PC's in a
20 network cluster to designate for shared processing by wireless means. Figure 14B shows clusters connected wirelessly; Figure 14C shows a wireless cluster with transponders and with a network wired connection to Internet; Figure 14D shows a network client/server wired
25 system with transponders.

Figure 15 is a simplified diagram of a section of a computer network, such as the Internet, showing an embodiment of a routing means whereby a PC request for shared processing can be routed within a network using
30 preferably broad bandwidth connection means to another area in a network with one or more idle PC's available.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The new network computer will utilize PC's as providers of computing power to the network, not just
35 users of network services. These connections between network and personal computer are enabled by a new form of computer/network financial structure that is rooted on

the fact that economic resources being provided the network by PC owners (or leaser) are similar in value to those being provided by the network provider providing connectivity.

5 Unlike existing one way functional relationships between network providers such as internet service providers (often currently utilizing telecommunications networks for connectivity) and PC users, wherein the network provider provides access to a network like the
10 Internet for a fee (much like cable TV services), this new relationship would recognize that the PC user is also providing the network access to the user's PC for parallel computing use, which has a similar value. The PC thus both provides and uses services on the network,
15 alternatively or potentially even virtually simultaneously, in a multitasking mode.

 This new network would operate with a structural relationship that would be roughly like that which presently exists between an electrical power utility and
20 a small independent power generator connected to the utility, wherein electrical power can flow in either direction depending on the operating decisions of both parties and at any particular point in time each party is in either a debt or credit position relative to the other
25 based on the net direction of that flow for a given period, and is billed accordingly. In the increasingly deregulated electrical power industry, electrical power (both its creation and transmission) is becoming a commodity bought and sold in a competitive marketplace
30 that crosses traditional borders. With the structural relationship proposed here for the new network, parallel free market structures should develop over time in a new computer power industry dominated by networks of personal computers in all their forms providing shared processing.

35 For this new network and its structural relationships, a network provider is defined in the broadest possible way as any entity (corporation or other

WO 98/26366

PCT/US97/21812

14

business, government, not-for-profit, cooperative, consortium, committee, association, community, or other organization or individual) that provides personal computer users (very broadly defined below) with initial and continuing connection hardware and/or software and/or firmware and/or other components and/or services to any network, such as the Internet and Internet II or WWW or their present or future equivalents, coexistors or successors, like the MetaInternet, including any of the current types of Internet access providers (ISP's) including telecommunication companies, television cable or broadcast companies, electrical power companies, satellite communications companies, or their present or future equivalents, coexistors or successors. The connection means used in the networks of the network providers, including between personal computers or equivalents or successors, would preferably be very broad bandwidth, by such means as fiber optic cable or wireless for example, but not excluding any other means, including television coaxial cable and telephone twisted pair, as well as associated gateways, bridges, routers, and switches with all associated hardware and/or software and/or firmware and/or other components and their present or future equivalents or successors. The computers used by the providers include any computers, including mainframes, minicomputers, servers, and personal computers, and associated their associated hardware and/or software and/or firmware and/or other components, and their present or future equivalents or successors.

Other levels of network control beyond the network provider will also exist to control any aspect of the network structure and function, any one of which levels may or may not control and interact directly with the PC user. For example, at least one level of network control like the World Wide Web Consortium (W3C) or Internet Society (ISOC) or other ad hoc industry consortia) would establish and ensure compliance with any prescribed

network standards and/or protocols and/or industry standard agreements for any hardware and/or software and/or firmware and/or other component connected to the network. Under the consensus control of these consortia/societies, other levels of network control would deal with administration and operation of the network. These other levels of network control might be constituted by any network entity, including those defined immediately above for network providers.

10 The principal defining characteristic of the network provided being communication connections (including hardware and/or software and/or firmware and/or other component) of any form, including electromagnetic (such as light and radio or microwaves) and electrochemical
15 (and not excluding biochemical or biological), between PC users, optimally connecting (either directly or indirectly) the largest number of users possible, like the Internet (and Internet II) and WWW and equivalents and successors, like the MetaInternet. Multiple levels
20 of such networks will likely coexist with different technical capabilities, like Internet and Internet II, but would have interconnection and therefore would communicate freely between levels, for such standard network functions as electronic mail.

25 And a personal computer (PC) user is defined in the broadest possible way as any individual or other entity using a personal computer, which is defined as any computer, digital or analog or neural, particularly including microprocessor-based personal computers having
30 one or more microprocessors (each including one or more parallel processors) in their general current form (hardware and/or software and/or firmware and/or any other component) and their present and future equivalents or successors, such as workstations, network computers,
35 handheld personal digital assistants, personal communicators such as telephones and pagers, wearable computers, digital signal processors, neural-based

computers (including PC's), entertainment devices such as televisions, video tape recorders, videocams, compact or digital video disk (CD or DVD) player/recorders, radios and cameras, other household electronic devices, business
5 electronic devices such as printers, copiers, fax machines, automobile or other transportation equipment devices, and other current or successor devices incorporating one or more microprocessors (or functional or structural equivalents), especially those used
10 directly by individuals, utilizing one or more microprocessors, made of inorganic compounds such as silicon and/or other inorganic or organic compounds; current and future forms of mainframe computers, minicomputers, microcomputers, and even supercomputers
15 are also be included. Such personal computers as defined above have owners or leasers, which may or may not be the same as the computer users. Continuous connection of computers to the network, such as the Internet, WWW, or equivalents or successors, is preferred.

20 Parallel processing is defined as one form of shared processing as involving two or more microprocessors involved in solving the same computational problem or other task. Massively parallel microprocessor processing involves large numbers of microprocessors. In today's
25 technology, massive parallel processing can probably be considered to be about 64 microprocessors (referred to in this context as nodes) and over 7,000 nodes have been successfully tested in an Intel supercomputer design using PC microprocessors (Pentium Pros). It is
30 anticipated that continued software improvements will make possible a much larger number of nodes, very possibly limited only by the number of microprocessors available for use on a given network, even an extraordinarily large one like the Internet or its
35 equivalents and/or successors, like the MetaInternet.

Broadband wavelength or broad bandwidth network transmission is defined here to mean a transmission speed

(usually measured in bits per second) that is at least high enough (or roughly at least equivalent to the internal clock speed of the microprocessor or microprocessors times the number of microprocessor channels equaling instructions per second or operations per second or calculations per second) so that the processing input and output of the microprocessor is substantially unrestricted, particularly including at peak processing levels, by the bandwidth of the network connections between microprocessors that are performing some form of parallel processing, particularly including massive parallel processing. Since this definition is dependent on microprocessor speed, it will increase as microprocessor speeds increase. A rough example might be a current 100 MIPS (millions instructions per second) microprocessor, for which a broad bandwidth connection would be greater than 100 megabits per second (Mbps); this is a rough approximation. However, a preferred connection means referenced above is fiber optic cable, which currently already provides multiple gigabit bandwidth on single fiber thread and will improve significantly in the future, so the use of fiber optic cable virtually assures broad bandwidth for data transmission that is far greater than microprocessor speed to provide data to be transmitted. The connection means to provide broad bandwidth transmission can be either wired or wireless, with wireless generally preferred for mobile personal computers (or equivalents or successors) and as otherwise indicated below. Wireless connection bandwidth is also increasing rapidly and can be considered to offer essentially the same benefit as fiber optic cable: data transmission speed that far exceeds data processing speed.

The financial basis of the shared use between owners/ leasers and providers would be whatever terms to which the parties agree, subject to governing laws, regulations, or rules, including payment from either

party to the other based on periodic measurement of net use or provision of processing power.

In one embodiment, as shown in Figure 1, in order for this network structure to function effectively, there would be a meter device 5 (comprised of hardware and/or software and/or firmware and/or other component) to measure the flow of computing power between PC 1 user and network 2 provider, which might provide connection to the Internet and/or World Wide Web and/or Internet II and/or any present or future equivalent or successor 3, like the MetaInternet. In one embodiment, the PC user should be measured by some net rating of the processing power being made available to the network, such as net score on one or more standard tests measuring speed or other performance characteristics of the overall system speed, such as PC Magazine's benchmark test program, ZD Winstone (potentially including hardware and/or software and/or firmware and/or other component testing) or specific individual scores for particularly important components like the microprocessor (such as MIPS or millions of instructions per second) that may be of application-specific importance, and by the elapsed time such resources were used by the network. In the simplest case, for example, such a meter need measure only the time the PC was made available to the network for processing 4, which can be used to compare with time the PC used the network (which is already normally measured by the provider, as discussed below) to arrive at a net cost; potential locations of such a meter include at a network computer such as a server, at the PC, and at some point on the connection between the two. Throughput of data in any standard terms is another potential measure.

In another embodiment, as shown in Figure 2, there also would be a meter device 7 (comprised of hardware and/or software and/or firmware and/or other component) that measures the amount of network resources 6 that are being used by each individual PC 1 user and their

associated cost. This would include, for example, time spent doing conventional downloading of data from sites in the network or broadcast from the network 6. Such metering devices currently exist to support billing by the hour of service or type of service is common in the public industry, by providers such as America Online, Compuserve, and Prodigy. The capability of such existing devices would be enhanced to include a measure of parallel processing resources that are allocated by the Internet Service Provider or equivalent to an individual PC user from other PC users 6, also measuring simply in time. The net difference in time 4 between the results of meter 5 and meter 7 for a given period would provide a reasonable billing basis.

Alternately, as shown in Figure 3, a meter 10 would also estimate to the individual PC user prospectively the amount of network resources needed to fulfill a processing request from the PC user to the network (provider or other level of network control) and associated projected cost, provide a means of approving the estimate by executing the request, and a realtime readout of the cost as it occurs (alternatively, this meter might be done only to alert 9 the PC user that a given processing request 8 falls outside normal, previously accepted parameters, such as level of cost). To take the example of an unusually deep search request, a priority or time limit and depth of search should optimally be criteria or limiting parameters that the user can determine or set with the device.

Preferably, the network would involve no payment between users and providers, with the network system (software, hardware, etc) providing an essentially equivalent usage of computing resources by both users and providers (since any network computer operated by either entity can potentially be both a user and provider of computing resources (even simultaneously, assuming multitasking), with potentially an override option by a

WO 98/26366

PCT/US97/21812

20

user (exercised on the basis, for example, of user profile or user's credit line or through relatively instant payment).

5 Preferably, as shown in Figure 4, the priority and extent of use of PC and other users can be controlled on a default-to-standard-of-class-usage basis by the network (provider or other) and overridden by the user decision on a basis prescribed by the specific network provider (or by another level of network control). One obvious
10 default basis would be to expend up to a PC's or other user's total credit balance with the provider described above and the network provider then to provide further prescribed service on an debt basis up to some set limit for the user; different users might have different limits
15 based on resources and/or credit history.

A specific category of PC user based, for example, on specific microprocessor hardware owned or leased, might have access to a set maximum number of parallel PC's or microprocessors, with smaller or basic users
20 generally having less access and vice versa. Specific categories of users might also have different priorities for the execution of their processing by the network. A very wide range of specific structural forms between user and provider are possible, both conventional and new,
25 based on unique features of the new network computer system of shared processing resources.

For example, in the simplest case, in an initial system embodiment, as shown in Fig. 4A, a standard PC 1 user request 11 for a use involving parallel processing
30 might be defaulted by system software 13, as shown in Fig. 4B, to the use of only one other essentially identical PC 1₂ microprocessor for parallel processing or multitasking, as shown in Figure 4C; larger standard numbers of PC microprocessors, such as about three PC's
35 at the next level, as shown in later Figure 10G (which could also illustrate a PC 1 user exercising an override option to use a level of services above the default

standard of one PC microprocessor, presumably at extra cost), for a total of about four, then about 8, about 16, about 32, about 64 and so on, or virtually any number in between, would be made available as the network system is
5 upgraded over time, as well as the addition of sophisticated override options. Eventually many more PC microprocessors would be made available to the standard PC user (virtually any number), preferably starting at about 128, then about 256, then about 512, then about
10 1024 and so on over time, as the network and all of its components are gradually upgraded to handle the increasing numbers. System scalability at even the standard user level is essentially unlimited over time.

Preferably, for most standard PC users (including
15 present and future equivalents and successors), connection to the Internet (or present or future equivalents or successors like the MetaInternet) would be at no cost to PC users, since in exchange for such Internet access the PC users would generally make their
20 PC, when idle, available to the network for shared processing. Preferably, then, competition between Internet Service Providers (including present and future equivalents and successors) for PC user customers would be over such factors as the convenience and quality of
25 the access service provided and of shared processing provided at no addition cost to standard PC users, or on such factors as the level of shared processing in terms, for example of number of slave PC's assigned on a standard basis to a master PC. The ISP's would also
30 compete for parallel processing operations, from inside or outside the ISP Networks, to conduct over their networks.

In addition, as shown in Figure 5, in another embodiment there would be a (hardware and/or software
35 and/or firmware and/or other) controlling device to control access to the user's PC by the network. In its simplest form, such as a manually activated

electromechanical switch, the PC user could set this controller device to make the PC available to the network when not in use by the PC user. Alternatively, the PC user could set the controller device to make the PC
5 available to the network whenever in an idle state, however momentary, by making use of multitasking hardware and/or software and/or firmware and/or other component (broadcast or "push" applications from the Internet or other network could still run in the desktop background).
10 Or, more simply, as shown in Figure 5A, whenever the state that all user applications are closed and the PC 1 is available to the network 14 (perhaps after a time delay set by the user, like that conventionally used on screensaver software) is detected by a software
15 controller device 12 installed in the PC, the device 12 would signal 15 the network computer such as a server 2 that the PC available to the network, which could then control the PC 1 for parallel processing or multitasking by another PC. Such shared processing can continue until
20 the device 12 detects the an application being opened 16 in the first PC (or at first use of keyboard, for quicker response, in a multitasking environment), when the device 12 would signal 17 the network computer such as a server 2 that the PC is no longer available to the network, as
25 shown in Figure 5B, so the network would then terminate its use of the first PC.

In a preferred embodiment, as shown in Figure 6, there would be a (hardware and/or software and/or firmware and/or other component) signaling device 18 for
30 the PC 1 to indicate or signal 15 to the network the user PC's availability 14 for network use (and whether full use or multitasking only) as well as its specific (hardware/software/firmware/other components) configuration 20 (from a status 19 provided by the PC) in
35 sufficient detail for the network or network computer such as a server 2 to utilize its capability effectively. In one embodiment, the transponder device would be

resident in the user PC and broadcast its idle state or other status (upon change or periodically, for example) or respond to a query signal from a network device.

Also, in another embodiment, as shown in Figure 7,
5 there would be a (hardware/software and/or firmware and/or other component) transponder device 21 resident in a part of the network (such as network computer, switch, router, or another PC, for examples) that receives 22 the PC device status broadcast and/or queries 26 the PC for
10 its status, as shown in Figure 7.

In one embodiment, as shown in Figure 8, the network would also have resident in a part of its hardware and/or software (and/or firmware and/or other components) a capacity such as to allow it to most effectively select
15 and utilize the available user PC's to perform parallel processing initiated by PC users or the network providers or others. To do so, the network should have the (hardware and/or software and/or firmware and/or other component) capability of locating each PC accurately at
20 the PC's position on the geographic grid lines/connection means 23 so that parallel processing occurs between PC's (PC 1 and PC 1₂) as close together as possible, which should not be difficult for PC's at fixed sites with a geographic location, customarily grouped together into
25 cells 24, as shown in Figure 8, but which requires an active system for any wireless microprocessor to measure its distance from its network relay site, as discussed below in Figure 14.

One of the primary capabilities of the Internet (or
30 Internet II or successor, like the MetaInternet) or WWW network computer would be to facilitate searches by the PC user or other user. As shown in Figure 9, searches are particularly suitable to multiple processing, since, for example, a typical search would be to find a specific
35 Internet or WWW site with specific information. Such site searches can be broken up geographically, with a different PC processor 1' allocated by the network

communicating through a wired means 99 as shown (or wireless connections) to search each area, the overall area being divided into eight separate parts, as shown, which would preferably be about equal, so that the total search would be about 1/8 as long as if one processor did it alone (assuming the PC 1 microprocessor provides control only and not parallel processing, which may be preferable in some case).

As a typical example, a single PC user might need 1,000 minutes of search time to find what is requested, whereas the network computer, using multiple PC processors, might be able to complete the search in 100 minutes using 10 processors, or 10 minutes using 100 processors or 1 minute using 1,000 processors (or even 1 second using 60,000 processors); assuming performance transparency, which should be achievable, at least over time. The network's external parallel processing would optimally be completely scalable, with virtually no theoretical limit.

The above examples also illustrates a tremendous potential benefit of network parallel processing. The same amount of network resources, 60,000 processor seconds, was expended in each of the equivalent examples. But by using relatively large multiples of processors, the network can provide the user with relatively immediate response with no difference in cost (or relatively little difference) -- a major benefit. In effect, each PC user linked to the network providing external parallel processing becomes, in effect, a virtual supercomputer! As discussed below, supercomputers would experience a similar quantum leap in performance by employing a thousand-fold (or more) increase in microprocessors above current levels.

Such power will likely be required for any effective searches in the World Wide Web (WWW). WWW is currently growing at a rate such that it is doubling every year, so that searching for information within the WWW will become

WO 98/26366

PCT/US97/21812

25

geometrically more difficult in future years,
particularly a decade hence, and it is already a very
significant difficulty to find WWW sites of relevance to
any given search and then to review and analyze the
5 contents of the site.

So the capability to search with massive parallel
processing will be required to be effective and will
dramatically enhance the capabilities of scientific,
technological and medical researchers.

10 Such enhanced capabilities for searching (and
analysis) will also fundamentally alter the relationship
of buyers and sellers of any items and/or services. For
the buyer, massive parallel network processing will make
it possible to find the best price, worldwide, for any
15 product or the most highly rated product or service (for
performance, reliability, etc.) within a category or the
best combination of price/performance or the highest
rated product for a given price point and so on. The
best price for the product can include best price for
20 shipping within specific delivery time parameters
acceptable to the buyer.

For the seller, such parallel processing will
drastically enhance the search, worldwide, for customers
potentially interested in a given product or service,
25 providing very specific targets for advertisement.
Sellers, even producers, will be able to know their
customers directly and interact with them directly for
feedback on specific products and services to better
assess customer satisfaction and survey for new product
30 development.

Similarly, the vastly increased capability provided
by the system's shared parallel processing will produce
major improvements in complex simulations like modeling
worldwide and local weather systems over time, as well as
35 design and testing of any structure or product, from
airliners and skyscrapers, to new drugs and to the use of
much more sophisticated artificial intelligence (AI) in

medical treatment and in sorting through and organizing the PC users voluminous input of electronic data from "push" technologies. Improvements in games would also be evident, especially in terms of realistic simulation and interactivity.

As is clear from the examples, the Internet or WWW network computer system like the MetaInternet would potentially put into the hands of the PC user an extraordinary new level of computer power vastly greater than the most powerful supercomputer existing today. The world's total of microchips is already about 350 billion, of which about 15 billion are microprocessors of some kind (most are fairly simple "appliance" type running wrist watches, Televisions, cameras, cars, telephones, etc). Assuming growth at its current rates, in a decade the Internet/Internet II/WWW could easily have a billion individual PC users, each providing a average total of at least 10 highly sophisticated microprocessors (assuming PC's with at least 4 microprocessors (or more, such as 16 microprocessors or 32, for example) and associated other handheld, home entertainment, and business devices with microprocessors or digital processing capability, like a digital signal processor or successor devices). That would be a global computer a decade from now made of at least 10 billion microprocessors, interconnected by electromagnetic wave means at speeds approaching the speed of light.

In addition, if the exceptionally numerous "appliance" microprocessors noted above, especially those that operate now intermittently like personal computers, are designed to the same basic consensus industry standard as parallel microprocessors for PC's (or equivalents or successors) or for PC "systems on a chip" discussed later in Figure 10A-H, and if also connected by broad bandwidth means such as fiber optic cable or equivalent wireless, then the number of parallel processors potentially available would increase roughly

about 10 times, for a net potential "standard" computing performance of up to 10,000 times current performance within fifteen years, exclusive of Moore's Law routine increases. Moreover, if all currently intermittently
5 operating microprocessors followed the same basic design standards, then although the cost per microprocessor would rise somewhat, especially initially, the net cost of computing for all users would fall drastically due to the general performance increase due to the use of
10 otherwise idle "appliance" microprocessors. Overall system costs will therefore compel such microprocessors, which are currently specialty devices, to become virtually all general microprocessors (like PC's), with software and firmware providing most of their
15 distinguishing functionality.

To put this in context, a typical supercomputer today utilizing the latest PC microprocessors has less than a hundred. Using network linkage to all external parallel processing, a peak maximum of perhaps 1 billion
20 microprocessors could be made available for a network supercomputer user, providing it with the power 10,000,000 times greater than would be available using today's internal parallel processing supercomputers (assuming the same microprocessor technology). Because
25 of it's virtually limitless scalability mentioned above, resources made available by the network to the supercomputer user or PC user would be capable of varying significantly during any computing function, so that peak computing loads would be met with effectively whatever
30 level of resources are necessary.

In summary, regarding monitoring the net provision of power between PC and network, Figures 1-9 show embodiments of a system for a network of computers, including personal computers, comprising: means for
35 network services including browsing functions, as well as shared computer processing such as parallel processing, to be provided to the personal computers within the

network; at least two personal computers; means for at least one of the personal computers, when idled by a personal user, to be made available temporarily to provide the shared computer processing services to the network; and means for monitoring on a net basis the provision of the services to each the personal computer or to the personal computer user. In addition, Figures 1-9 show embodiments including where the system is scalar in that the system imposes no limit to the number of the personal computers, including at least 1024 personal computers; the system is scalar in that the system imposes no limit to the number of personal computers participating in a single shared computer processing operation, including at least 256 personal computers; the network is connected to the Internet and its equivalents and successors, so that the personal computers include at least a million personal computers; the network is connected to the World Wide Web and its successors; the network includes at least one network server that participates in the shared computer processing.; the monitoring means includes a meter device to measure the flow of computing power between the personal computers and the network; the monitoring means includes a means by which the personal user of the personal computer is provided with a prospective estimate of cost for the network to execute an operation requested by the personal user prior to execution of the operation by the network; the system has a control means by which to permit and to deny access to the personal computers by the network for shared computer processing; access to the personal computers by the network is limited to those times when the personal computers are idle; and the personal computers having at least one microprocessor and communicating with the network through a connection means having a speed of data transmission that is at least greater than a peak data processing speed of the microprocessor.

Also, relative to maintaining a standard cost, Figures 1-9 show embodiments of a system for a network of computers, including personal computers, comprising: means for network services including browsing functions, as well as shared computer processing such as parallel processing, to be provided to the personal computers within the network; at least two personal computers; means for at least one of the personal computers, when idled by a personal user, to be made available temporarily to provide the shared computer processing services to the network; and means for maintaining a standard cost basis for the provision of the services to each personal computer or to the personal computer user. In addition, Figures 1-9 show embodiments including where the system is scalar in that the system imposes no limit to the number of personal computers, including at least 1,024 personal computers; the system is scalar in that the system imposes no limit to the number of the personal computers participating in a single shared computer processing operation, including at least 256 personal computers; the network is connected to the Internet and its equivalents and successors, so that the personal computers include at least a million personal computers; the standard cost is fixed; the fixed standard cost is zero; the means for maintaining a standard cost basis includes the use of making available a standard number of personal computers for shared processing by personal computers; the network is connected to the World Wide Web and its successors; the personal user can override the means for maintaining a standard cost basis so that the personal user can obtain additional network services; the system has a control means by which to permit and to deny access to the personal computers by the network for shared computer processing; the personal computers having at least one microprocessor and communicating with the network through a connection means having a speed of data transmission that is at least greater than a peak data

processing speed of the microprocessor.

Browsing functions generally include functions like those standard functions provided by current Internet browsers, such as Microsoft Explorer 3.0 or 4.0 and Netscape Navigator 3.0 or 4.0, including at least searching World Wide Web or Internet sites, exchanging E-Mail worldwide, and worldwide conferencing; an intranet network uses the same browser software, but might not include access to the Internet or WWW. Shared processing includes parallel processing and multitasking processing involving more than two personal computers, as defined above. The network system is entirely scalar, with any number of PC microprocessors potentially possible.

As shown in Figures 10A-10F, to deal with operational and security issues, it may be optimal for individual users to have one microprocessor or equivalent device that is designated, permanently or temporarily, to be a master 30 controlling device (comprised of hardware and/or software and/of firmware and/or other component) that remains inaccessible (preferably using a hardware and/or software and/or firmware and/or other component firewall 50) directly by the network but which controls the functions of the other, slave microprocessors 40 when the network is not utilizing them.

For example, as shown in Figures 10A, a typical PC 1 might have four or five microprocessors (even on a single microprocessor chip), with one master 30 and three or four slaves 40, depending on whether the master 30 is a controller exclusively (through different design of any component part), requiring four slave microprocessors 40 preferably; or the master microprocessor 30 has the same or equivalent microprocessing capability as a slave 40 and multiprocesses in parallel with the slave microprocessors 40, thereby requiring only three slave microprocessors 40, preferably. The number of PC slave microprocessors 40 can be increased to virtually any other number, such as at least about eight, about 16,

about 32, about 64, about 128, about 256, about 512, about 1024, and so on (these multiples are preferred; the PC master microprocessors 30 can also be increased. Also included is the preferred firewall 50 between master 30 and slave 40 microprocessors. As shown in preceding Figures 1-9, the PC 1 in Figure 10A is preferably connected to a network computer 2 and to the Internet or WWW or present or future equivalent or successor 3, like the MetaInternet.

Other typical PC hardware components such as hard drive 61, floppy diskette 62, CD-ROM 63, DVD 64, Flash memory 65, RAM 66, video or other display 67, graphics card 68, and sound card 69, together with the software and/or firmware stored on or for them, can be located on either side of the preferred firewall 50, but such devices as the display 67, graphics card 68 and sound card 69 and those devices that both read and write and have non-volatile memory (retain data without power and generally have to be written over to erase), such as hard drive 62, Flash memory 65, floppy drive 62, read/write CD-ROM 63 or DVD 64 are preferred to be located on the PC user side of the firewall 50, where the master microprocessor is also located, as shown in Figure 10A, for security reasons primarily. Alternately, any or these devices that are duplicative (or for other exceptional needs) like a second hard drive 61 can be located on the network side of the firewall 50. RAM 66 or equivalent memory, which typically is volatile (data is lost when power is interrupted), should generally be located on the network side of the firewall 50. However, at least a portion of RAM is can be kept on the Master 30 microprocessor side of the firewall 50, so that the PC user can use retain the ability to use a core of user PC 1 processing capability entirely separate from any network processing; if this capability is not desired, then the master 30 microprocessor can be moved to the network side of the firewall 50 and replaced with a

simpler controller on the PC 1 user side.

And the master microprocessor 30 might also control the use of several or all other processors 60 owned or leased by the PC user, such as home entertainment digital
5 signal processors 70, especially if the design standards of such microprocessors in the future conforms to the requirements of network parallel processing as described above. In this general approach, the PC master processor would use the slave microprocessors or, if idle (or
10 working on low priority, deferrable processing), make them available to the network provider or others to use. Preferably, wireless connections 100 would be extensively used in home or business network systems, including use of a master remote controller 31 without (or with)
15 microprocessing capability, with preferably broad bandwidth connections such as fiber optic cable connecting directly to at least one component such as a PC 1, shown in a slave configuration, of the home or business personal network system; that preferred
20 connection would link the home system to the network 2 such as the Internet 3, as shown in Figure 10I.

In the simplest configuration, as shown in Figure 10B, the PC 1 would have a single master microprocessor 30 and a single slave microprocessor 40, preferably
25 separated by a firewall 50, with both processors used in parallel or multitasking processing or with only the slave 40 so used, and preferably connected to a network computer 2 and Internet 3 (and successors like the MetaInternet). Virtually any number of slave
30 microprocessors 40 is possible. The other non-microprocessor components shown in Figure 10A above might also be included in this simple Figure 10B configuration.

Preferably, as shown in Figure 10C, microprocessors 80 are expected to integrate most or all of the other
35 necessary computer components (or their present or future equivalents or successors), like a PC's memory (RAM 66, graphics 82, sound 83, power management 84, network

communications 85, and video processing 86, possibly including modem 87, flash bios 88, and other components or present or future equivalents or successors) and internal bus, on a single chip 90 (silicon, plastic, or other), known in the industry as "system on a chip". Such a PC micro chip 90 would preferably have the same architecture as that of the PC 1 shown above in Figure 10A: namely, a master control and/or processing unit 93 and one or more slave processing units 94 (for parallel or multitasking processing by either the PC 1 or the Network 2), preferably separated by a firewall 50 and preferably connected to a network computer 3 and the Internet 3 and successors like the MetaInternet. In the simplest case, as shown in Figure 10D, the chip 90 would have a single master unit 93 and at least one slave unit 94 (with the master having a controlling function only or a processing function also), preferably separated by a firewall 50 and preferably connected to a network computer 3 and the Internet 3 (and successors like the MetaInternet).

As noted in the second paragraph of the introduction to the background of the invention, in the preferred network invention, any computer can potentially be both a user and provider, alternatively -- a dual mode. Consequently, any PC 1 within the network 2, preferably connected to the Internet 3 (and successors like the MetaInternet), can be temporarily a master PC 30 at one time initiating a parallel or multitasking processing request to the network 2 for execution by at least one slave PC 40, as shown in Figure 10E. At another time the same PC 1 can become a slave PC 40 that executes a parallel or multitasking processing request by another PC 1' that has temporarily assumed the function of master 30, as shown in Figure 10F. The simplest approach to achieving this alternation is for both master and slave versions of the parallel processing software to be loaded in each or every PC 1 that is to share in the parallel

WO 98/26366

PCT/US97/21812

34

processing, so each PC 1 has the necessary software means, together with minor operation modifications, such as a switching means by which a signal request for parallel processing initiated by one PC 1 user using
5 master software is transmitted to at least a second PC 1, triggering its slave software to respond to initiate parallel processing.

As shown in Figures 10G and 10H, which are parallel to Figures 10E and 10F, the number of PC slave processors
10 40 can be increased to any virtually other number, such as at least about 4; the processing system is completely scalar, so that further increases can occur to about eight, about 16, about 32, about 64, about 128, about 256, about 512, about 1024, and so on (these multiples
15 indicated are preferred); the PC master microprocessors 30 can also be increased.

In summary, relative to the use of master/slave computers, Figures 10A-10H show embodiments of a system for a network of computers, including personal computers,
20 comprising: at least two the personal computers; means for at least one the personal computer, when directed by its personal user, to function temporarily as a master personal computer to initiate and control the execution of a computer processing operation shared with at least
25 one other the personal computer in the network; means for at least one other the personal computer, when idled by its personal user, to be made available to function temporarily as at least one slave personal computer to participate in the execution of a shared computer
30 processing operation controlled by the master personal computer; and means for the personal computers to alternate as directed between functioning as a master and functioning as a slave in the shared computer processing operations. In addition, Figures 10A-10H show
35 embodiments including wherein the system is scalar in that the system imposes no limit to the number of personal computers; the system includes at least 256 said

personal computers; the system is scalar in that the system imposes no limit to the number of personal computers participating in a single shared computer processing operation, including at least 256 said personal computers; the system is scalar in that the system imposes no limit to the number of personal computers participating in a single shared computer processing operation, including at least 256 said personal computers; the network is connected to the Internet and its equivalents and successors, so that personal computers include at least a million personal computers; the shared computer processing is parallel processing; the network is connected to the World Wide Web and its successors; a means for network services, including browsing and broadcast functions, as well as shared computer processing such as parallel processing, are provided to said personal computers within said network; the network includes at least one network server that participates in the shared computer processing; the personal computers include a transponder means so that a master personal computer can determine the closest available slave personal computers; the closest available slave personal computer is compatible with the master personal computer to execute said shared computer processing operation; the personal computers having at least one microprocessor and communicating with the network through a connection means having a speed of data transmission that is at least greater than a peak data processing speed of the microprocessor.

30 The preferred use of the firewall 50, as described above in Figures 10A-10H, provides a solution to an important security problem by preferably completely isolating host PC's 1 that are providing slave microprocessors to the network for parallel or other shared processing functions from any capability to access or retain information about any element about that shared processing. In addition, of course, the firewall 50

WO 98/26366

PCT/US97/21812

36

provides security for the host PC against intrusion by outside hackers; by reducing the need for encryption and authentication, the use of firewalls 50 will provide a relative increase in computing speed and efficiency. In addition to computers such as personal computers, the firewall 50 described above could be used in any device with "appliance"-type microprocessors, such as telephones, televisions or cars, as discussed above.

In summary, regarding the use of firewalls, Figures 10A-10H show embodiments of a system architecture for computers, including personal computers, to function within a network of computers, comprising: a computer with at least two microprocessors and having a connection means with a network of computers; the architecture for the computers including a firewall means for personal computers to limit access by the network to only a portion of the hardware, software, firmware, and other components of the personal computers; the firewall means will not permit access by the network to at least a one microprocessor having a means to function as a master microprocessor to initiate and control the execution of a computer processing operation shared with at least one other microprocessor having a means to function as a slave microprocessor; and the firewall means permitting access by the network to the slave microprocessor. In addition, the system architecture explicitly includes embodiments of, for example, the computer is a personal computer; the personal computer is a microchip; the computer have a control means by which to permit and to deny access to the computer by the network for shared computer processing; the system is scalar in that the system imposes no limit to the number of personal computers, including at least 256 said personal computers; the network is connected to the Internet and its equivalents and successors, so that the personal computers include at least a million personal computers; the system is scalar in that the system

imposes no limit to the number of personal computers participating in a single shared computer processing operation, including at least 256 said personal computers; the personal computers having at least one
5 microprocessor and communicating with the network through a connection means having a speed of data transmission that is at least greater than a peak data processing speed of the microprocessor.

of the computer being a personal computer; the personal
10 computer being a microchip; the computer have a control means by which to permit and to deny access to the computer by the network for shared computer processing; and the network being connected to the Internet and its successors.

15 If the PC 1 microprocessors noted above are designed to the same basic consensus industry standard as parallel microprocessors for PC's (or equivalents or successors) as in Figures 10A-10B or for PC "systems on a chip" discussed in Figures 10C-10D, then although the cost per
20 microprocessor could rise somewhat, especially initially, the net cost of computing for all users would fall drastically almost instantly due to the general performance increase due to the use of otherwise idle "appliance" microprocessors. The potential very
25 substantial benefit to all users should provide a powerful force to reach consensus on important industry hardware, software, and other standards on a continuing basis for such basic parallel network processing designs. If such basic industry standards are adopted at the
30 outset and for the least number of shared microprocessors initially, and if design improvements incorporating greater complexity and more shared microprocessors are phased in gradually overtime on a step by step basis, then conversion to a MetaInternet architecture at all
35 component levels should be relatively easy and inexpensive (whereas an attempt at sudden, massive conversion would be hugely difficult and prohibitively

expensive). The scalability of the MetaInternet system architecture (both vertically and horizontally) as described herein would make this sensible approach possible.

5 By 1998, manufacturing technology improvements will allow 20 million transistors to fit on a single chip (with circuits as thin as .25 microns) and, in the next cycle, 50 million transistors using .18 micron circuits. Preferably, that entire computer on a chip would be
10 linked, preferably directly, by fiber optic or other broad bandwidth connection means so that the limiting factor on data throughput in the network system, or any part, is the speed of the linked microprocessors themselves.

15 For computers that are not reduced to a single chip, it is also preferred that the internal bus of any such PC's have a transmission speed that is at least high enough that the all processing operations of the PC microprocessor or microprocessors is unrestricted and
20 that the microprocessor chip or chips are directly linked by fiber optic or other broad bandwidth connection, as with the system chip described above.

The individual user PC's can be connected to the Internet (via an Intranet)/Internet II/WWW or successor,
25 like the MetaInternet (or other) network by any electromagnetic means, with the speed of fiber optic cable being preferred, but hybrid systems using fiber optic cable for trunk lines and coaxial cable to individual users may be more cost effective initially,
30 but much less preferred unless cable can be made (through hardware and/or software and/or firmware and/or other component means) to provide sufficiently broad bandwidth connections to provide unrestricted throughput by connected microprocessors. Given the speed and bandwidth
35 of transmission of fiber optic or equivalent connections, conventional network architecture and structures should be acceptable for good system performance, making

possible a virtual complete interconnection network between users.

However, the best speed for any parallel processing operation should be obtained, all other things being equal, by utilizing the available microprocessors that are physically the closest together. Consequently, as shown previously in Figure 8, the network needs have the means (through hardware and/or software and/or firmware and/or other component) to provide on a continually ongoing basis the capability for each PC to know the addresses of the nearest available PC's, perhaps sequentially, from closest to farthest, for the area or cell immediately proximate to that PC and then those cells of adjacent areas.

Network architecture that clusters PC's together should therefore be preferred and can be constructed by wired means. However, as shown in Figure 11, it would probably be optimal to construct local network clusters 101 (or cells) of personal computers 1' by wireless 100 means, since physical proximity of any PC 1 to its closest other PC 1' should be easier to access directly that way, as discussed further below. Besides, it is economically preferable for at least several network providers to serve any given geographic area to provide competitive service and prices.

Optimally, then, those wireless PC connections should be PC resident and capable of communicating by wireless or wired means with all available PC's in the cluster or cell geographic area, both proximal and potentially out to the practical limits of the wireless transmission.

As shown in Figure 12, wireless PC connections 100 can be made to existing non-PC network components, such as one or more satellites 110, or present or future equivalent or successor components and the wireless transmissions can be conventional radio waves, such as infrared or microwave, or any other part of the

electromagnetic wave spectrum.

Moreover, as shown in Figure 13, such a wireless or wired approach would also make it easily possible in the future to develop network clusters 101 of available PC's 1' with complete interconnectivity; i.e., each available PC 1 in the cluster 101 is directly connected (preferably wirelessly 100) to every other available PC 1 in the cluster 101, constantly adjusting to individual PC's becoming available or unavailable. Given the speed of some wired broad bandwidth connections, like fiber optic cable, such clusters 101 with complete interconnectivity is certainly a possible embodiment.

As shown in Figure 14A-14D, such wireless systems would optimally include a wireless device 120 comprised of hardware and/or software and/or firmware and/or other component, like the PC 1 availability device described above preferably resident in the PC, but also with a network-like capability of measuring the distance from each PC 1 in its cluster 101 by that PC's signal transmission by transponder or its functional equivalent and/or other means to the nearest other PC's 1' in the cluster 101. As shown in Figure 14A, this distance measurement could be accomplished in a conventional manner between transponder devices 120 connected to each PC in the cluster 101; for example, by measuring in effect the time delay from wireless transmission by the transponder device 120 of an interrogating signal 105 to request initiation of shared processing by a master PC 1 to the reception of a wireless transmission response 106 signaling availability to function as a slave PC from each of the idle PC's 1' in the cluster 101 that has received the interrogation signal 105. The first response signal 106' received by the master PC 1 would be from the closest available slave PC 1" (assuming the simplest shared processing case of one slave PC and one master PC), which would be selected for the shared processing operation by the requesting master PC 1, since

the closer the shared microprocessor, the faster the speed of the wireless connections 100 would be between sharing PC's (assuming equivalence of the connection means and other components among each of the PC's 1').

5 The interrogation signal 105 might specify other selection criteria also, for example, for the closest compatible (initially perhaps defined by a functional requirement of the system to be an identical microprocessor) slave PC 1", with the first response

10 signal 106' being selected as above.

This same transponder approach also can be used between PC's 1" connected by a wired 99 means, despite the fact that connection distances would generally be greater (since not line of sight, as is wireless), as

15 shown in Figure 14A, since the speed of transmission by the preferred broad bandwidth transmission means such as fiber optic cable is so high as to offset that greater distance. From a cost basis, this wired approach might be preferable for such PC's already connected by broad

20 bandwidth transmission means, since additional wireless components like hardware and software would not be necessary. In that case, the same transponder device 120 would preferably be operated in wired clusters 101 in generally the same manner as described above for PC's

25 connected in wireless clusters 101. Networks incorporating PC's 1 connected by both wireless and wired means are anticipated, like the home or business network mentioned in Figure 10I, with mobile PC's or other computing devices preferably using wireless connections.

30 Depending on distances between PC's and other factors, a local cluster 101 of a network 2 might connect wirelessly between PC's and with the network 2 through transponding means linked to wired broad bandwidth transmission means, as shown in Figure 14C.

35 As shown in Figure 14D, the same general transponder device means 120 can also be used in a wired 100 network system 2 employing network servers 98 operated, for

example, by an ISP, or in other network system architectures (including client/server or peer to peer) or topologies (including ring, bus, and star) well known in the art or their future equivalents or successors.

The Figure 14 approach to establishing local PC clusters 101 for parallel or other shared processing has major advantage in that it avoids using network computers such as servers (and, if wireless, other network components including even connection means), so that the entire local system of PC's within a cluster 101 would operate independently of network servers, routers, etc. Moreover, particularly if connected by wireless means, the size of the cluster 101 could be quite large, being limited generally by PC transmission power, PC reception sensitivity, and local conditions. Additionally, one cluster 101 could communicate by wireless 100 means with an adjacent or other clusters 101, as shown in Figure 14B, which could include those beyond its direct transmission range.

To improve response speed in shared processing involving a significant number of slave PC's 1, a virtual potential parallel processing network for PC's 1 in a cluster 101 would preferably be established before a processing request begins. This would be accomplished by the transponder device 120 in each idle PC 1, a potential slave, broadcasting by transponder 120 its available state when it becomes idle and/or periodically afterwards, so that each potential master PC 1 in the local cluster 101 would be able to maintain relatively constantly its own directory 121 of the idle PC's 1 closest to it that are available to function as slaves. The directory 121 would contain, for example, a list of about the standard use number of slave PC's 1 for the master PC (which initially would probably be just one other PC 1") or a higher number, preferably listed sequentially from the closest available PC to the

farthest. The directory of available slave PC's 1 would be preferably updated on a relatively up to date basis, either when a change occurs in the idle state of a potential slave PC in the directory 121 or periodically.

5 Such ad hoc clusters 101 should be more effective by being less arbitrary geographically, since each individual PC would be effectively in the center of its own ad hoc cluster. Scaling up or down the number of microprocessors required by each PC at any given time
10 would also be more seamless.

 The complete interconnection potentially provided optimally by such ad hoc wireless clusters is also remarkable because such clusters mimics the neural network structure of the animal brain, wherein each nerve
15 cell, called a neuron, interconnects in a very complicated way with the neurons around it. By way of comparison, the global network computer described above that is expected in a decade will have at least about 10 times as many PC 's as a human brain has neurons and they
20 will be connected by electromagnetic waves traveling at close to the speed of light, which is about 300,000 times faster than the transmission speed of human neurons (which, however, will be much closer together).

 An added note: in the next decade, as individual
25 PC's become much more sophisticated and more network oriented, compatibility issues may recede to unimportance, as all major types of PC's will be able to emulate each other and most software, particularly relative to parallel processing, will no longer be
30 hardware specific. Nearer term it will be important to set compatible hardware, software, firmware, and other component standards to achieve optimal performance by the components of the global network computer.

 Until that compatibility is designed into the
35 essential components of network system, the existing incompatibility of current components dramatically increase the difficulty involved in parallel processing

across large networks. Programming languages like Java is one approach that will provide a partial means for dealing with this interim problem. In addition, using similar configurations of existing standards, like using
5 PC's with a specific Intel Pentium chip with other identical or nearly identical components is probably the best way in the current technology to eliminate many of the serious existing problems that could easily be designed around in the future by adopting reasonable
10 consensus standards for system components. The potential gains to all parties with an interest far outweigh the potential costs.

The above described global network computer system has an added benefit of reducing the serious and growing
15 problem of nearly the immediate obsolescence of computer hardware, software, firmware, and other components. Since the preferred system above is the sum of its constituent parts used in parallel processing, each specific PC component becomes less critical. As long as
20 access to the network utilizing sufficient bandwidth is possible, then all other technical inadequacies of the user's own PC will be completely compensated for by the network's access to a multitude of technically able PC's, of which the user will have temporary use.

25 Although the global network computer will clearly cross the geographical boundaries of nations, its operation should not be unduly bounded by inconsistent or arbitrary laws within those states. There will be considerable pressure on all nations to conform to
30 reasonable system architecture and operational standards generally agreed upon, since the penalty of not participating in the global network computer is potentially so high as to not be politically possible anywhere.

35 As shown in Figure 15, because the largest number of user PC's will be completely idle, or nearly so, during the night, it would be optimal for the most complicated

large scale parallel processing, involving the largest numbers of processors with uninterrupted availability as close together as possible, to be routed by the network to geographic areas of the globe undergoing night and to keep them there even as the Earth rotates by shifting computing resources as the world turns. As shown in Figure 15, during the day, at least one parallel processing request by at least one PC 1 in a network 2 in the Earth's western hemisphere 131 are transmitted by very broad bandwidth connection wired 99 means such as fiber optic cable to the Earth's eastern hemisphere 132 for execution by at least one PC 1' of a network 2', which is idle during the night and the results are transmitted back by the same means to network 2 and the requesting at least one PC 1. Individual PC's within local networks like that operated by an ISP would likely be grouped into clusters or cells, as is typical in the practice of network industries. As is common in operating electrical power grids and telecommunications and computer networks, many such processing requests from many PC's and many networks could be so routed for remote processing, with the complexity of the system growing substantially over time in a natural progression.

This application encompasses all new apparatus and methods required to operate the above described network computer system or systems, including any associated computer or network hardware, software, or firmware (or other component), both apparatus and methods. Specifically included, but not limited to, are (in their present or future forms, equivalents, or successors): all enabling PC and network software and firmware operating systems, user interfaces and application programs; all enabling PC and network hardware design and system architecture, including all PC and other computers, network computers such as servers, microprocessors, nodes, gateways, bridges, routers, switches, and all other components; all enabling financial and legal

WO 98/26366

PCT/US97/21812

46

transactions, arrangements and entities for network providers, PC users, and/or others, including purchase and sale of any items or services on the network or any other interactions or transactions between any such
5 buyers and sellers; and all services by third parties, including to select, procure, set up, implement, integrate, operate and perform maintenance, for any or all parts of the foregoing for PC users, network providers, and/or others.

10 The foregoing embodiments meet the objectives of this invention as stated above. However, it will be clearly understood by those skilled in the art that the foregoing description has been made in terms of the preferred
15 embodiments and that various changes and modifications may be made without departing from the scope of the present invention, which is to be defined by the appended claims.

IN THE CLAIMS:

- 1 1. A system for a network of computers, including
2 personal computers, comprising:
3 means for network services including browsing
4 functions, as well as shared computer processing such as
5 parallel processing, to be provided to said personal
6 computers within said network;
7 at least two said personal computers;
8 means for at least one of said personal computers,
9 when idled by a personal user, to be made available
10 temporarily to provide said shared computer processing
11 services to said network; and
12 means for monitoring on a net basis the provision of
13 said services to each said personal computer or to said
14 user.
- 1 2. The system of claim 1, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers.
- 1 3. The system of claim 2, wherein said system
2 includes at least 1024 said personal computers.
- 1 4. The system of claim 1, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers participating in a single
4 shared computer processing operation.
- 1 5. The system of claim 4, wherein said system
2 includes at least 256 said personal computers.
- 1 6. The system of claim 1, wherein said network is
2 connected to the Internet and its equivalents and
3 successors, so that said personal computers include at
4 least a million personal computers.
- 1 7. The system of claim 1, wherein said network is

WO 98/26366

PCT/US97/21812

48

2 connected to the World Wide Web and its successors.

1 8. The system of claim 1, wherein said network
2 includes at least one network server that participates in
3 said shared computer processing.

1 9. The system of claim 1, wherein said monitoring
2 means includes a meter device to measure the flow of
3 computing power between said personal computers and said
4 network.

1 10. The system of claim 1, wherein said monitoring
2 means includes a means by which said personal user of
3 said personal computer is provided with a prospective
4 estimate of cost for said network to execute an operation
5 requested by said user prior to execution of said
6 operation by said network.

1 11. The system of claim 1, wherein said system has
2 a control means by which to permit and to deny access to
3 said personal computers by said network for shared
4 computer processing.

1 12. The system of claim 1, wherein access to said
2 personal computers by said network is limited to those
3 times when said personal computers are idle.

1 13. The system of claim 1, wherein said personal
2 computers having at least one microprocessor and
3 communicating with said network through a connection
4 means having a speed of data transmission that is at
5 least greater than a peak data processing speed of said
6 microprocessor.

1 14. A system for a network of computers, including
2 personal computers, comprising:
3 means for network services including browsing

WO 98/26366

PCT/US97/21812

49

4 functions, as well as shared computer processing such as
5 parallel processing, to be provided to said personal
6 computers within said network;
7 at least two said personal computers;
8 means for at least one of said personal computers,
9 when idled by a personal user, to be made available
10 temporarily to provide said shared computer processing
11 services to said network; and
12 means for maintaining a standard cost basis for the
13 provision of said services to each said personal computer
14 or to said user.

1 15. The system of claim 14, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers.

1 16. The system of claim 15, wherein said system
2 includes at least 1,024 said personal computers.

1 17. The system of claim 14, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers participating in a single
4 shared computer processing operation.

1 18. The system of claim 17, wherein said system
2 includes at least 256 said personal computers.

1 19. The system of claim 14, wherein said network is
2 connected to the Internet and its equivalents and
3 successors, so that said personal computers include at
4 least a million personal computers.

1 20. The system of claim 14, wherein the standard
2 cost is fixed.

1 21. The system of claim 14, wherein the fixed
2 standard cost is zero.

WO 98/26366

PCT/US97/21812

50

1 22. The system of claim 14, wherein said means for
2 maintaining a standard cost basis includes the use of
3 making available a standard number of said personal
4 computers for shared processing by said personal
5 computers.

1 23. The system of claim 14, wherein said network is
2 connected to the World Wide Web and its successors.

1 24. The system of claim 14, wherein said personal
2 user can override said means for maintaining a standard
3 cost basis so that said personal user can obtain
additional network services.

1 25. The system of claim 14, wherein said system has
2 a control means by which to permit and to deny access to
3 said personal computers by said network for shared
4 computer processing.

1 26. The system of claim 14, wherein said personal
2 computers having at least one microprocessor and
3 communicating with said network through a connection
4 means having a speed of data transmission that is at
5 least greater than a peak data processing speed of said
6 microprocessor.

1 27. A system for a network of computers, including
2 personal computers, comprising:

3 at least two said personal computers;

4 means for at least one said personal computer, when
5 directed by its personal user, to function temporarily as
6 a master personal computer to initiate and control the
7 execution of a computer processing operation shared with
8 at least one other said personal computer in said
9 network;

10 means for at least one other said personal computer,
11 when idled by its personal user, to be made available to

WO 98/26366

PCT/US97/21812

51

12 function temporarily as at least one slave personal
13 computer to participate in the execution of a shared
14 computer processing operation controlled by said master
15 personal computer; and
16 means for said personal computers to alternate as
17 directed between functioning as a master and functioning
18 as a slave in said shared computer processing operations.

1 28. The system of claim 27, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers.

1 29. The system of claim 28, wherein said system
2 includes at least 256 said personal computers.

1 30. The system of claim 27, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers participating in a single
4 shared computer processing operation.

1 31. The system of claim 30, wherein said system
2 includes at least 256 said personal computers.

1 32. The system of claim 27, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers participating in a single
4 shared computer processing operation.

1 33. The system of claim 27, wherein said system
2 includes at least 256 said personal computers.

1 34. The system of claim 27, wherein said network is
2 connected to the Internet and its equivalents and
3 successors, so that said personal computers include at
4 least a million personal computers.

1 35. The system of claim 27, wherein said shared

WO 98/26366

PCT/US97/21812

52

2 computer processing is parallel processing.

1 36. The system of claim 27, wherein said network is
2 connected to the World Wide Web and its successors.

1 37. The system on claim 27, wherein a means for
2 network services, including browsing and broadcast
3 functions, as well as shared computer processing such as
4 parallel processing, are provided to said personal
5 computers within said network.

1 38. The system of claim 27, wherein said network
2 includes at least one network server that participates in
3 said shared computer processing.

1 39. The system of claim 27, wherein said personal
2 computers include a transponder means so that a master
3 personal computer can determine the closest available
4 slave personal computers.

1 40. The system of claim 27, wherein said closest
2 available slave personal computer is compatible with said
3 master personal computer to execute said shared computer
4 processing operation.

1 41. The system of claim 27, wherein said personal
2 computers having at least one microprocessor and
3 communicating with said network through a connection
4 means having a speed of data transmission that is at
5 least greater than a peak data processing speed of said
6 microprocessor.

1 42. A system architecture for computers, including
2 personal computers, to function within a network of
3 computers, comprising:

4 a computer with at least two microprocessors and
5 having a connection means with a network of computers;

WO 98/26366

PCT/US97/21812

53

6 said architecture for said computers including a
7 firewall means for personal computers to limit access by
8 said network to only a portion of the hardware, software,
9 firmware, and other components of said personal
10 computers;

11 said firewall means will not permit access by said
12 network to at least a one said microprocessor having a
13 means to function as a master microprocessor to initiate
14 and control the execution of a computer processing
15 operation shared with said at least one other
16 microprocessor having a means to function as a slave
17 microprocessor; and

18 said firewall means permitting access by said
19 network to said slave microprocessor.

1 43. The system architecture of claim 42, wherein
2 said computer is a personal computer.

1 44. The system architecture of claim 43, wherein
2 said personal computer is a microchip.

1 45. The system architecture of claim 42, wherein
2 said computer have a control means by which to permit and
3 to deny access to said computer by the network for shared
4 computer processing.

1 46. The system of claim 43, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers.

1 47. The system of claim 46, wherein said system
2 includes at least 256 said personal computers.

1 48. The system of claim 43, wherein said network is
2 connected to the Internet and its equivalents and
3 successors, so that said personal computers include at
4 least a million personal computers.

WO 98/26366

PCT/US97/21812

54

1 49. The system of claim 43, wherein said system is
2 scalar in that said system imposes no limit to the number
3 of said personal computers participating in a single
4 shared computer processing operation.

1 50. The system of claim 49, wherein said system
2 includes at least 256 said personal computers.

1 51. The system of claim 43, wherein said personal
2 computers having at least one microprocessor and
3 communicating with said network through a connection
4 means having a speed of data transmission that is at
5 least greater than a peak data processing speed of said
6 microprocessor.




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 10G




FIG. 10H




FIG. 10I




FIG. 11

