




(86) Date de dépôt PCT/PCT Filing Date: 2009/06/04
 (87) Date publication PCT/PCT Publication Date: 2010/12/09
 (45) Date de délivrance/Issue Date: 2015/10/06
 (85) Entrée phase nationale/National Entry: 2011/12/20
 (86) N° demande PCT/PCT Application No.: CN 2009/072133
 (87) N° publication PCT/PCT Publication No.: 2010/139119

(51) Cl.Int./Int.Cl. *H04L 12/24* (2006.01)
 (72) Inventeurs/Inventors:
 YAN, JUN, CN;
 XIAO, XIN, CN;
 WU, QIUYOU, CN
 (73) Propriétaire/Owner:
 HUAWEI TECHNOLOGIES CO., LTD., CN
 (74) Agent: SMART & BIGGAR

(54) Titre : PROCEDE ET APPAREIL POUR OBTENIR UNE BOUCLE DE PROTECTION PARTAGEE D'UNE UNITE DE DONNEES DE CANAL OPTIQUE
 (54) Title: METHOD AND DEVICE FOR IMPLEMENTING OPTICAL CHANNEL DATA UNIT SHARED RING PROTECTION



(57) **Abrégé/Abstract:**

A method and a device for implementing an optical channel data unit (ODU) shared ring protection are disclosed by the present invention. The method includes: a first ODU of a first service transmitted in an optical line is set as a protection granularity, where the first ODU is an ODU_k that is directly multiplexed to the optical line; the first ODU is monitored for detecting errors/failures, and a monitoring result is obtained, wherein the monitoring result indicates whether an error/a failure has occurred or not; when the monitoring result indicates that a failure/an error has occurred, a cross-switching is performed on a second ODU of the first service, where the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than or equal to k. Through the embodiments of the present invention, a protection switching speed may be accelerated.

52663-23

Abstract

A method and a device for implementing an optical channel data unit (ODU) shared ring protection are disclosed by the present invention. The method includes: a first ODU of a first service transmitted in an optical line is set as a protection granularity, where
5 the first ODU is an ODU_k that is directly multiplexed to the optical line; the first ODU is monitored for detecting errors/failures, and a monitoring result is obtained, wherein the monitoring result indicates whether an error/a failure has occurred or not; when the monitoring result indicates that a failure/an error has occurred, a cross-switching is performed on a second ODU of the first service, where the second ODU is an ODU_m that is multiplexed
10 to the first ODU, and m is smaller than or equal to k. Through the embodiments of the present invention, a protection switching speed may be accelerated.

52663-23

METHOD AND DEVICE FOR IMPLEMENTING OPTICAL CHANNEL DATA UNIT SHARED RING PROTECTION

FIELD OF THE INVENTION

The present invention relates to the optical communication technology, and in
5 particularly to a method and a device for realizing an optical channel data unit (ODU)
shared protection ring (SPRing).

BACKGROUND OF THE INVENTION

With the rapid development of data services, a transport network for data services has
also been developed greatly. An optical transport network (OTN) is a kind of optical
10 transport technology. The OTN includes an optical channel (OCh), an optical multiplex
section (OMS), and an optical transport section (OTS). The OCh further includes three
sub-layers: an optical channel payload unit-k (OPUk), an optical channel data unit-k
(ODUk), and an optical channel transport unit-k (OTUk). Each sub-layer has a
corresponding overhead (OH) and function to support network management and monitoring.
15 k is an order, and represents a level, and different k values support different bit rates
correspondingly. In the OTN, different protection modes may be adopted to effectively
improve the survivability of services. In an existing synchronous digital hierarchy (SDH)
field, a multiplex section (MS) SPRing may be realized through VC cross. However, the
MS SPRing in the SDH field cannot be easily transplanted to the OTN. An OTN system has
20 multiple ODU levels numbered 0, 1, 2, 2e, 3, 4, and so on. Problems such as how to
monitor signal quality to trigger a switching, how to transfer APS information, and how to
coordinate protections of a multi-level ODUk are difficult to be solved. Currently, a scheme
of ODU SPRing exists in the OTN. In an implementation scheme of the existing ODU
SPRing, when the system has a multi-level ODU service, a switching is performed through
25 cross of each level of the ODUk, which may realize only protection for the current level of

52663-23

the ODU_k, that is, the current level of the ODU_k is regarded as a protection granularity. For example, the system has three levels of ODUs, which are respectively ODU₂, ODU₁, and ODU₀, and one ODU₂ may include 4 ODU₁s or 8 ODU₀s. A switching through cross of the ODU₁ is performed to realize protection of an ODU₁ level, and a switching is performed through cross of the ODU₀ so as to realize protection of an ODU₀ level. When multiple client services are multiplexed to the ODU₂, and the multiple client services all need protection, if the protection of the ODU₁ is adopted, 4 protection groups need to be created; and if the protection of the ODU₀ is adopted, 8 protection groups need to be created.

The prior art has the following disadvantages: if a low order (LO) ODU is taken as a protection granularity, the number of protection groups is larger, and required switching time is long, which may even exceed a threshold of the switching time (50 ms), and consequently, the switching cannot be performed smoothly.

SUMMARY OF THE INVENTION

The embodiments of the present invention provide a method and a device for realizing an ODU SPRing, so as to solve the problems in the prior art that the number of protection groups is larger and the switching time is long.

A method for realizing an ODU SPRing provided in an embodiment of the present invention includes:

taking a first ODU of a first service transmitted in an optical line as a protection granularity, where the first ODU is an ODU_k that is directly multiplexed to the optical line;

monitoring the first ODU, and obtaining a monitoring result; and

When the monitoring result indicates that a failure occurs, performing a switching through cross of a second ODU of the first service, where the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than or equal to k .

A device for realizing an ODU SPRing provided in an embodiment of the present invention includes:

52663-23

a first module, configured to take a first ODU of a first service transmitted in an optical line as a protection granularity, where the first ODU is an ODU_k that is directly multiplexed to the optical line;

5 a second module, configured to monitor the first ODU, and obtain a monitoring result; and

a third module, configured to perform a switching through cross of a second ODU of the first service when the monitoring result indicates that a failure occurs, where the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than or equal to k.

10 It can be known from the preceding technical solutions that, in the embodiments of the present invention, a first ODU SPRing is realized by the switching performed through cross of the second ODU, where the first ODU is taken as the protection granularity. Since an order of the first ODU is higher than that of the second ODU, multiple second ODUs may be multiplexed to one first ODU. Therefore, by taking the first ODU as the protection
15 granularity, the number of protection groups may be reduced, and a switching process maybe accelerated.

According to one aspect of the present invention, there is provided a method for implementing an optical channel data unit (ODU) shared ring protection, comprising:

20 setting a first ODU of a first service transmitted in an optical line as a protection granularity, wherein the first ODU is an ODU_k that is directly multiplexed to the optical line;

monitoring the first ODU for detecting errors/failures, and obtaining a monitoring result, wherein the monitoring result indicates whether an error/a failure has occurred or not; and

25 based on the monitoring result which indicates an error/a failure has occurred, performing cross-switching on a second ODU of the first service, wherein the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than k.

52663-23

According to another aspect of the present invention, there is provided a device for implementing an optical channel data unit (ODU) shared ring protection, comprising:

5 a first module, configured to set a first ODU of a first service transmitted in an optical line as a protection granularity, wherein the first ODU is an ODU_k that is directly multiplexed to the optical line;

a second module, configured to monitor the first ODU for detecting errors/failures, and obtain a monitoring result, wherein the monitoring result indicates whether an error/a failure has occurred or not; and

10 a third module, configured to perform cross-switching on a second ODU of the first service based on the monitoring result indicates that a failure/an error has occurred, wherein the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than k.

52663-23

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic flow chart of a method according to a first embodiment of the present invention;

FIG. 2 is a schematic structural diagram of an OUTk OH part adopted in the first
20 embodiment of the present invention;

FIG. 3 is a schematic flow chart of a method according to a second embodiment of the present invention;

FIG. 4 is a schematic structural diagram of a system corresponding to the second embodiment of the present invention;

25 FIG. 5 is a schematic flow chart of a method according to a third embodiment of the present invention;

FIG. 6 is a schematic structural diagram corresponding to the third embodiment of the

present invention;

FIG. 7 is a schematic flow chart of a method according to a fourth embodiment of the present invention;

FIG. 8 is a schematic structural diagram corresponding to the fourth embodiment of the present invention;

FIG. 9 is a schematic flow chart of a method according to a fifth embodiment of the present invention;

FIG. 10 is a schematic diagram of cross-ring protection corresponding to the fourth or fifth embodiment of the present invention;

FIG. 11 is a schematic flow chart of a method according to a sixth embodiment of the present invention;

FIG. 12 is a schematic structural diagram corresponding to the sixth embodiment of the present invention; and

FIG. 13 is a schematic structural diagram of a device according to a seventh embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

The technical solutions in the present invention are described in further detail in the following with reference to accompanying drawings and embodiments.

FIG. 1 is a schematic flow chart of a method according to a first embodiment of the present invention. The method includes:

Step 11: A monitoring endpoint takes a first ODU of a first service transmitted in an optical line as a protection granularity, where the first ODU is an ODU_k that is directly multiplexed to the optical line.

Step 12: The monitoring endpoint monitors the first ODU, and obtains a monitoring result.

Step 13: When the monitoring result indicates that a failure occurs, the monitoring endpoint performs a switching through cross of a second ODU of the first service, where

the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than or equal to k .

In this embodiment, a first ODU SPRing is realized by the switching performed through cross of the second ODU, where the first ODU is taken as the protection granularity. Since an order of the first ODU is higher than that of the second ODU, multiple second ODUs may be multiplexed to one first ODU. Therefore, by taking the first ODU as the protection granularity, the number of protection groups may be reduced, and a switching process may be accelerated.

When the first service includes two levels of ODUs, taking the first embodiment as an example, when m is smaller than k , in the embodiments described in the following, an ODU with a high level (for example, the ODU_k) is referred to as a high order (HO) ODU, and an ODU with a low level (for example, the ODU_m) is referred to as a low order (LO) ODU.

In order to better understand the embodiments of the present invention, a signal in an OTN that the embodiments of the present invention are based on is described first. The OTU_k is a frame with 4 rows and 4080 bytes, including an OPU_k payload part, an OTU_k forward error correction (FEC) part, and an OH part.

FIG. 2 is a schematic structural diagram of an OUT_k OH part adopted in the first embodiment of the present invention. Referring to FIG. 2, the OH part includes an OPU_k OH, an ODU_k OH, and an OTU_k OH. The OPU_k OH occupies bytes of the fifteenth and sixteenth columns in the first to fourth rows; the ODU_k OH occupies bytes of the first to fourteenth columns in the second to fourth rows; the OTU_k OH occupies bytes of the eighth to fourteenth columns in the first row; and a frame alignment OH occupies bytes of the first to seventh columns in the first row.

In the prior art, Tandem Connection Monitoring (TCM) is used for monitoring, and the TCM triggers a switching. However, since one level of the TCM is occupied in this mode, other protection modes that must use the TCM, such as Subnetwork Connection/Sublayer Monitoring (SNC/S), cannot adopt the level of the TCM within a range of this SPRing. In addition, in the prior art, an Automatic Protection Switching/Protection Communication

52663-23

Channel (APS/PCC) is divided by adopting a value of 6, 7, and 8 bit of a multiframe alignment signal (MFAS) and by binding with a monitoring mode, so that it is not easy to determine which one should be assigned to an ODUk SPRing for protection.

Therefore, in this embodiment of the present invention, protection groups
 5 may be monitored by monitoring a path monitoring (PM) of the HO ODU, and the PM of the HO ODU triggers the switching. An APS/PCC OH of the HO ODU serves as a channel for transferring APS information of the protection groups, and the APS/PCC may be divided through a field value of the MFAS. In this way, the TCM is not occupied, so that the protection mode in this embodiment of the present invention may co-exist with
 10 other protection modes. For example, the division is performed by using the sixth to eighth bits of the MFAS, and a value of "000" of the sixth to eighth bits indicates that an APS/PCC byte is used in a scheme adopted in this embodiment of the present invention that HO ODU protection is realized through cross of an LO ODU.

FIG. 3 is a schematic flow chart of a method according to a second
 15 embodiment of the present invention. The method includes:

Step 31: A monitoring endpoint takes an HO ODU of a first service transmitted in an optical line as a protection granularity for protection.

Step 32: The monitoring endpoint monitors a PM of an ODU OH part of the HO ODU, and obtains a monitoring result according to information carried in the PM.

20 Step 33: When the monitoring result indicates that a failure occurs, the monitoring endpoint performs a switching through cross corresponding to an LO ODU of the first service.

The mode adopted in this embodiment of the present invention that the PM of the HO ODU triggers the switching may support protection across a 3R node. FIG. 4
 25 is a schematic structural diagram of a system corresponding to the second embodiment of the present invention. The system includes five nodes A to E. A service enters a ring from the node A and leaves the ring from the node E, and signal quality among A to E needs to be monitored. The node A is used to bring in a client service, and it is assumed that the client service is an OTU1 service. At the node A, an ODU1 of client service data
 30 is multiplexed to an ODU2, and then transmitted through an optical line. Therefore, in

52663-23

this embodiment, an HO ODU is the ODU2, and an LO ODU is the ODU1. It is assumed that a 3R node is further included in this embodiment (an OTU OH part is terminated and regenerated at the 3R node), and a switching is triggered by monitoring a PM of the ODU2. It is analyzed in the following why the PM of the ODU2 needs to be used for triggering the switching. It is assumed
5 that a PM of the ODU1 is used for triggering the switching, however, because the ODU1 is generated outside the node A (because the ODU1 is multiplexed to the ODU2 at the node A, the ODU1 exists before the node A), the PM of the ODU1 is generated outside the node A accordingly, and the monitoring of the PM starts working at a PM generation point, if the PM of the ODU1 is adopted for monitoring, a monitoring range is not from the node A to the node E. It
10 is assumed that an SM of the OTU2 is used for triggering the switching, however, because this system has a 3R node, and the SM is terminated and regenerated at the 3R node, the monitoring range is between the 3R node and the node E, which also does not meet the requirement of this embodiment for monitoring the range from the node A to the node E. Since the PM of the ODU2 is terminated and regenerated at a place that a service enters or leaves the ring (for example, the
15 node A or the node E), it is appropriate to trigger the switching by using the PM of the ODU2.

In this embodiment, the PM is used for triggering the switching, and the TCM does not need to be occupied, so that other protection modes that must use the TCM (for example, an SNC/S) may also be adopted conveniently. In addition, an APS/PCC is divided by a value of 6, 7, and 8 bit of the MFAS, which is not limited to be bound with a monitoring mode. An OTN system may
20 include multiple hierarchies, and in order to remain that a first-level protection is realized through a second-level ODU, processes of de-multiplexing and multiplexing may be performed at a node where a hierarchy is added, so as to maintain the second-level ODU.

FIG. 5 is a schematic flow chart of a method according to a third embodiment of the present invention, and FIG. 6 is a schematic structural diagram corresponding to the third embodiment of
25 the present invention.

Referring to FIG. 6, it is assumed that the system has three hierarchies, HGFKJI are corresponding to an ODU1 ring, that is, the ODU1 ring includes two levels of ODUs: an

ODU0 and an ODU1, and the ODU0 is multiplexed to the ODU1. When protection of the ODU1 ring needs to be realized, a switching may be triggered by monitoring a PM of the ODU1, and the switching is performed through cross of the ODU0. It is assumed that a service needs to be multiplexed to an ODU2 at a node F, and nodes F, A, B, C, D, and E are
 5 corresponding to an ODU2 ring, that is, an HO ODU is the ODU2.

To maintain the simplicity of protection hierarchies, two levels of the ODUs may still be maintained when the system has multiple hierarchies. Referring to FIG. 5, this embodiment includes:

Step 51: A node where a hierarchy is added (a node F in this embodiment) performs
 10 de-multiplexing processing on an input second service, and obtains an ODU_i of the second service. The second service includes the ODU_i and an ODU_j, and the ODU_i is multiplexed to the ODU_j, where i is smaller than j. In this embodiment, the ODU_i is an ODU0, and the ODU_j is an ODU1.

Step 52: The node (F) where the hierarchy is added multiplexes the ODU_i (the ODU0)
 15 to an HO ODU of a first service (an ODU2 in this embodiment).

Step 53: In a ring (an ODU2 ring) corresponding to the first service, a switching is triggered by monitoring a PM of the HO ODU (the ODU2), and the switching is performed through cross of the ODU_i (the ODU0), so as to realize an ODU2 SPRing and protection of the first service.

20 In this embodiment, the de-multiplexing processing is performed first, so that the simplicity of the hierarchies of service data may be maintained, and an existing second-level ODU may be used simply to implement a scheme of an ODU SPRing.

Definitely, when the system has more hierarchies, a multi-layer ODU may also be maintained to realize multi-level protection.

25 FIG. 7 is a schematic flow chart of a method according to a fourth embodiment of the present invention, and FIG. 8 is a schematic structural diagram corresponding to the fourth embodiment of the present invention.

Referring to FIG. 8, it is assumed that a system has three hierarchies, nodes H, G, J, and I are corresponding to an ODU1 ring, that is, the ODU1 ring includes two levels of

ODUs: an ODU0 and an ODU1, and the ODU0 is multiplexed to the ODU1. When protection of the ODU1 ring needs to be realized, a switching may be triggered by monitoring a PM of the ODU1, and the switching is performed through cross of the ODU0. It is assumed that a service needs to be multiplexed to an ODU2 at a node A, and nodes A, B, C, D, E, and F are corresponding to an ODU2 ring. In addition, nodes K, L, M, and N form another ODU1 ring. In order to realize multi-level protection, the node A may directly multiplex the ODU1 that includes the ODU0. Referring to FIG. 7, this embodiment includes:

Step 71: A service entrance point (the node A in this embodiment) on a first service monitoring ring (the ODU2 ring in this embodiment) receives a second service. The second service includes an ODU_i and an ODU_j, and the ODU_i is multiplexed to the ODU_j, where *i* is smaller than *j*. In this embodiment, the ODU_i is the ODU0, and the ODU_j is the ODU1.

Step 72: The service entrance point (A) multiplexes the ODU_j to which the ODU_i is multiplexed (the ODU1 that includes the ODU0) to an HO ODU (the ODU2) of the first service.

Step 73: Multi-level protection is realized in a ring corresponding to the first service (the ODU2 ring).

The multi-level protection refers to that in the ODU2 ring, protection of the ODU2 may be realized, and protection of the ODU1 may also be realized.

The protection of the ODU2 may be realized in the following manner. The ODU2 is taken as a protection group, a switching is triggered by monitoring a PM of the ODU2, and then the switching may be performed through cross of the ODU1 that includes the ODU0, or the switching may be performed through cross of the ODU0.

The protection of the ODU1 may be realized in the following manner. The ODU1 is taken as a protection group, a switching is triggered by monitoring a PM of the ODU1, and then the switching is performed through cross of the ODU0.

In this embodiment, the multi-level protection is realized by directly multiplexing the ODU_j that includes the ODU_i to an ODU_k with a higher order, so that the protection is more comprehensive.

52663-23

FIG. 9 is a schematic flow chart of a method according to a fifth embodiment of the present invention, and in this embodiment, reference may also be made to the schematic structural diagram shown in FIG. 8. A difference from the fourth embodiment lies in that, in the fourth embodiment, the ODU1 of the second service is multiplexed to the ODU2 of the first service, while in this embodiment, an OTU1 of a second service (an OTU is a basic unit when being transmitted in an optical line, which includes an ODU, and when the ODU is needed in the preceding description, the ODU is extracted from the OTU) is multiplexed to an ODUflex as a whole, and then the ODUflex is multiplexed to an ODU2. Referring to FIG. 9, this embodiment includes:

10 Step 91: A service entrance point (a node A in this embodiment) on a first service monitoring ring (an ODU2 ring in this embodiment) receives a second service. The second service includes an ODU_i and an ODU_j, and the ODU_i is multiplexed to the ODU_j, where the ODU_j is included in an OTU_j. In this embodiment, the ODU_i is an ODU0, the ODU_j is an ODU1, and the OTU_j is an OTU1.

15 Step 92: The service entrance point (A) multiplexes the OTU_j (the OTU1) to an ODUflex.

Step 93: The service entrance point (A) multiplexes the ODUflex to an HO ODU of the first service (an ODU2 in this embodiment).

20 Step 94: Multi-level protection is realized in rings (an ODU2 ring and an ODU1 ring in this embodiment respectively) corresponding to the first service and the second service.

The multi-level protection refers to that in the ODU2 ring, protection of the ODU2 may be realized, and in the ODU1 ring, protection of the ODU1 may be realized.

25 The protection of the ODU2 may be realized in the following manner. The ODU2 is taken as a protection group, a switching is triggered by monitoring a PM of the ODU2, and then the switching is performed through cross of the ODUflex.

The protection of the ODU1 may be realized in the following manner. The ODU1 is taken as a protection group, a switching is triggered by monitoring a PM of the ODU1, and then the switching is performed through cross of the ODU0.

30 Definitely, it can be understood that in the fourth embodiment as shown in FIG. 7, the

ODU1 and the ODU2 also form a multi-level protection ring.

In this embodiment, the multi-level protection is realized by directly multiplexing the OTU as a whole to the ODUflex, and then multiplexing the ODUflex to the HO ODU, so that the protection is more comprehensive.

5 In a system that has multiple protection rings, the protection rings may be monitored respectively to realize cooperation among multiple levels. For example, referring to FIG. 8, it is assumed that a service of the nodes H to L needs to be monitored, when a problem occurs between the nodes A and B, the PM of the ODU2 on the ODU2 ring may discover the problem, and therefore, the protection of the ODU2 may be triggered to perform a
10 switching by monitoring the PM of the ODU2 on the ODU2 ring so as to realize the protection; when a problem occurs between the nodes K and L, the PM of the ODU1 on the ODU1 ring may discover the problem, and therefore, the protection of the ODU1 may be triggered to perform a switching by monitoring the PM of the ODU1 on the ODU1 ring so as to realize the protection.

15 FIG. 10 is a schematic diagram of cross-ring protection corresponding to the fourth or fifth embodiment of the present invention. Referring to FIG. 10, the cross-ring protection may be realized through the respective monitoring described in the preceding. It can be known from the preceding analysis that protection of an ODU1 SPRing in this embodiment may be realized by crossing an ODU2 ring.

20 In this embodiment, when the protection is multiple-level, the cross-ring protection may be realized by respectively monitoring different levels of monitoring rings.

When only a single-level ODU exists in a system, the ODU in this level may be considered as an HO ODU, and may also be considered as an LO ODU, and protection of the single-level ODU may also be realized by using the method described in the preceding.

25 FIG. 11 is a schematic flow chart of a method according to a sixth embodiment of the present invention; and FIG. 12 is a schematic structural diagram corresponding to the sixth embodiment of the present invention. This embodiment is directed to a scenario where only a single-level ODU exists in a system. Referring to FIG. 12, in this embodiment, it is assumed that only a service of an ODU2 exists in the system, and nodes A, B, C, D, E, and

F form an ODU2 ring.

Referring to FIG. 11, this embodiment includes:

Step 111: A monitoring endpoint takes an ODU (an ODU2 in this embodiment) of a single-level service transmitted in an optical line as an HO ODU and also as an LO ODU.

5 Step 112: The monitoring endpoint monitors an OH field of the ODU2, and obtains a monitoring result through the OH field.

Specifically, when a service brought in by a node is an OTU service (OTU2), a TCM6 field of the ODU2 needs to be monitored, and the monitoring result is carried by this field; and when the service brought in by the node is a non-OTU service (for example, an STM-64 service), a PM field of an ODU2 OH may be monitored to obtain a monitoring result. The reason of the preceding operation is that, when the service brought in by the node is the OTU service, it indicates that the OTU exists before the service is brought in, and a corresponding PM is generated before the service is brought in. In this way, if a switching is still triggered by using the PM, a monitoring range is not consistent with a range that needs to be monitored, which may cause a false switching.

10
15

Step 113: When the monitoring result indicates that a failure occurs, a switching is performed through cross of the ODU2 to realize protection of the ODU2.

In this embodiment, when a single-level ODU exists in the system, the protection is realized by taking the single-level ODU as an HO ODU and also as an LO ODU.

20 FIG. 13 is a schematic structural diagram of a device according to a seventh embodiment of the present invention. The device includes a first module 131, a second module 132, and a third module 133. The first module 131 is configured to take a first ODU of a first service transmitted in an optical line as a protection granularity, where the first ODU is an ODU_k that is directly multiplexed to the optical line. The second module 132 is configured to monitor the first ODU, and obtain a monitoring result. The third module 133 is configured to perform a switching through cross of a second ODU of the first service when the monitoring result indicates that a failure occurs, where the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than or equal to k.

25

This embodiment may further include a fourth module, connected to the first module,

and configured to receive a second service. The second service includes an ODU_j to which an ODU_i is multiplexed, where i is smaller than j . A service entrance point multiplexes the ODU_j to which the ODU_i is multiplexed to the ODU_k of the first service. At this time, the third module is specifically configured to perform a switching through cross of the ODU_j to realize protection of the ODU_k, or perform a switching through cross of the ODU_i to realize the protection of the ODU_k.

Alternatively, this embodiment may further include a fifth module, connected to the first module, and configured to receive the second service. The second service is an OTU_j that includes the ODU_j to which the ODU_i is multiplexed, where i is smaller than j . The service entrance point multiplexes the OTU_j to an ODUflex, and multiplexes the ODUflex to the ODU_k of the first service. At this time, the third module is specifically configured to perform a switching through cross of the ODUflex to realize the protection of the ODU_k.

This embodiment may further include a sixth module, connected to the first module, and configured to receive the second service, where the second service includes the ODU_j to which the ODU_i is multiplexed, and i is smaller than j ; perform de-multiplexing processing on the second service, and obtain the ODU_i from the second service; and multiplex the ODU_i to the ODU_k of the first service. At this time, the third module is specifically configured to perform a switching through cross of the ODU_i to realize the protection of the ODU_k.

The second module is specifically configured to monitor a PM of an ODU OH of the first ODU, and obtain a monitoring result according to information carried in the PM. The third module is specifically configured to perform a switching through cross of the second ODU according to switching request information carried in an APS/PCC in the ODU OH of the first ODU, where the APS/PCC is corresponding to different protection modes according to a value of 6, 7, and 8 bit in an MFAS in the OTU OH of the first service.

In this embodiment, a first ODU SPRing is realized by the switching performed through the cross of the second ODU, where the first ODU is taken as the protection granularity. Since an order of the first ODU is higher than that of the second ODU, multiple second ODUs may be multiplexed to one first ODU. Therefore, by taking the first ODU as

52663-23

the protection granularity, the number of protection groups may be reduced, and a switching process may be accelerated.

Persons of ordinary skill in the art may understand that all or a part of the steps of the preceding method embodiments may be implemented by a program instructing relevant
5 hardware. The program may be stored in a computer readable storage medium. When the program runs, the steps of the preceding method embodiments are performed. The storage medium includes any medium that is capable of storing program codes, such as an ROM, an RAM, a magnetic disk, or an optical disk.

Finally, it should be noted that the preceding embodiments are merely used for
10 describing the technical solutions of the present invention, but are not intended to limit the present invention. The scope of the claims should not be limited by the preferred embodiments set out above, but should be given the broadest interpretation consistent with the description as a whole.

52663-23

CLAIMS:

1. A method for implementing an optical channel data unit (ODU) shared ring protection, comprising:

5 setting a first ODU of a first service transmitted in an optical line as a protection granularity, wherein the first ODU is an ODU_k that is directly multiplexed to the optical line;

monitoring the first ODU for detecting errors/failures, and obtaining a monitoring result, wherein the monitoring result indicates whether an error/a failure has occurred or not; and

10 based on the monitoring result which indicates an error/a failure has occurred, performing cross-switching on a second ODU of the first service, wherein the second ODU is an ODU_m that is multiplexed to the first ODU, and m is smaller than k.

2. The method according to claim 1, wherein the monitoring and obtaining the monitoring step further comprises:

15 monitoring a path monitoring (PM) in an ODU overhead (OH) of the first ODU, and obtaining the monitoring result according to information carried by the PM.

3. The method according to claim 1, wherein the performing cross-switching step comprises:

20 performing the switching through the cross of the second ODU according to switching request information carried by an Automatic Protection Switching/Protection Communication Channel (APS/PCC) in an ODU OH of the first ODU.

4. The method according to claim 3, wherein the APS/PCC is corresponding to different protection modes according to a value of 6, 7, and 8 bit in a multiframe alignment signal (MFAS) in an optical channel transport unit (OTU) OH of the first service.

52663-23

5. The method according to claim 1, further comprising:

receiving, by a service entrance point in the optical line, a second service, wherein the second service comprises an ODU_j to which an ODU_i is multiplexed, and *i* is smaller than *j*;

5 performing de-multiplexing processing, by the service entrance point, on the second service, and obtaining the ODU_i from the second service; and

multiplexing, by the service entrance point, the ODU_i to the ODU_k of the first service,

wherein the performing cross-switching step comprises: performing

10 cross-switching on the ODU_i to implement protection for the ODU_k.

6. The method according to claim 1, further comprising:

receiving, by a service entrance point in the optical line, a second service, wherein the second service comprises an ODU_j to which an ODU_i is multiplexed, and *i* is smaller than *j*; and

15 multiplexing, by the service entrance point, the ODU_j to which the ODU_i is multiplexed to the ODU_k of the first service,

wherein the performing cross-switching step comprises: performing cross-switching on the ODU_j to implement protection of the ODU_k, or performing cross-switching on the ODU_i to implement protection for the ODU_k.

20 7. The method according to claim 6, further comprising:

setting the ODU_j as the protection granularity for protection, monitoring each ODU_j, and performing cross-switching on the ODU_i to implement protection for the ODU_j.

8. The method according to claim 1, further comprising:

52663-23

receiving, by a service entrance point in the optical line, a second service, wherein the second service is an OTU_j that comprises an ODU_j to which an ODU_i is multiplexed, and *i* is smaller than *j*; and

5 multiplexing, by the service entrance point, the OTU_j to an ODU_{flex}, and multiplexing the ODU_{flex} to the ODU_k of the first service,

wherein the performing cross-switching step comprises: performing cross-switching on the ODU_{flex} to implement protection for the ODU_k.

9. The method according to claim 6 or 8, wherein nodes passed through by the second service form a second service monitoring ring, and nodes passed through by the first service form a first service monitoring ring, the method further comprising:

10 monitoring a PM in an ODU OH of the ODU_j on the second service monitoring ring, and monitoring a PM in an ODU OH of the ODU_k on the first service monitoring ring, to implement cross-monitoring ring protection.

10. A device for implementing an optical channel data unit (ODU) shared ring protection, comprising:

a first module, configured to set a first ODU of a first service transmitted in an optical line as a protection granularity, wherein the first ODU is an ODU_k that is directly multiplexed to the optical line;

20 a second module, configured to monitor the first ODU for detecting errors/failures, and obtain a monitoring result, wherein the monitoring result indicates whether an error/a failure has occurred or not; and

a third module, configured to perform cross-switching on a second ODU of the first service based on the monitoring result indicates that a failure/an error has occurred, wherein the second ODU is an ODU_m that is multiplexed to the first ODU, and *m* is smaller than *k*.

52663-23

11. The device according to claim 10, further comprising:

a fourth module, connected to the first module, and configured to receive a second service, wherein the second service comprises an ODU_j to which an ODU_i is multiplexed, and i is smaller than j ; and the fourth module is further configured to multiplex
5 the ODU_j to which the ODU_i is multiplexed to the ODU_k of the first service; and

the third module is specifically configured to perform cross-switching on the ODU_j to implement protection for the ODU_k, or perform cross-switching on the ODU_i to implement protection for the ODU_k.

12. The device according to claim 10, further comprising:

10 a fifth module, connected to the first module, and configured to receive a second service, wherein the second service is an optical channel transport unit- j (OTU_j) that comprises an ODU_j to which an ODU_i is multiplexed, and i is smaller than j ; and the fifth module is further configured to multiplex the OTU_j to an ODUflex, and multiplexes the ODUflex to the ODU_k of the first service; and

15 the third module is specifically configured to perform cross-switching on the ODUflex to implement protection for the ODU_k.

13. The device according to claim 10, further comprising:

a sixth module, connected to the first module, and configured to receive a second service, wherein the second service comprises an ODU_j to which an ODU_i is
20 multiplexed, and i is smaller than j ; perform de-multiplexing processing on the second service, and obtain the ODU_i from the second service; and multiplex the ODU_i to the ODU_k of the first service; and

the third module is specifically configured to perform cross-switching on the ODU_i to realize protection of the ODU_k.

25 14. The device according to claim 10, wherein:

52663-23

the second module is specifically configured to monitor a path monitoring (PM) in an ODU overhead (OH) of the first ODU, and obtain a monitoring result according to information carried in the PM; and

5 the third module is specifically configured to perform cross-switching on of the second ODU according to switching request information carried in an Automatic Protection Switching/Protection Communication Channel (APS/PCC) in the ODU OH of the first ODU, wherein the APS/PCC is corresponding to different protection modes according to a value of 6, 7, and 8 bit in a multiframe alignment signal (MFAS) in an OTU OH of the first service.

1/7




FIG. 1

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	Frame alignment OH						OTUk OH						OPUk OH			
2	RES		TCM ACT	TCM6			TCM5		TCM4		FTFL					
3	TCM3		TCM2		TCM1		PM		EXP							
4	GCC1	GCC2	APS/PCC			RES										

FIG. 2

2/7




FIG. 3




FIG. 4

3/7




FIG. 5




FIG. 6

4/7




FIG. 7




FIG. 8

5/7




FIG. 9




FIG. 10

6/7




FIG. 11




FIG. 12




FIG. 13

Take a first ODU of a first service transmitted in an optical line as a protection granularity

11

Monitor the first ODU, and obtain a monitoring result

12

When the monitoring result indicates that a failure occurs, perform a switching through cross of a second ODU of the first service, where a level of the second ODU is smaller than or equal to that of the first ODU

13