

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199913247 B2
(10) Patent No. 762698

(54) Title
Method and apparatus for fixing a graft in a bone tunnel

(51)⁷ International Patent Classification(s)
A61B 017/56

(21) Application No: **199913247**

(22) Application Date: **1999.01.27**

(30) Priority Data

(31) Number	(32) Date	(33) Country
09/014937	1998.01.28	US

(43) Publication Date : **1999.08.19**

(43) Publication Journal Date : **1999.08.19**

(44) Accepted Journal Date : **2003.07.03**

(71) Applicant(s)
Ethicon, Inc.

(72) Inventor(s)
Gregory R. Whittaker; Joan M. Sullivan; Harold M. Martins; Ronald L. Taylor Jr.

(74) Agent/Attorney
FREEHILLS CARTER SMITH BEADLE,Level 43,101 Collins Street,MELBOURNE VIC 3000

(56) Related Art
US 5397356
US 5350380
US 5688284

ABSTRACT

A method for fixing a bone block (20) in a bone tunnel (16) comprising the steps of placing the bone block in the bone tunnel, advancing spaced-apart first (30) and second (34) metal wires through the bone, transversely of the bone tunnel, so as to
5 intersect the bone block and extend through the bone block, removing one of the wires and replacing the one removed wire with a first absorbable rod (40), and removing the other of the wires and replacing the other removed wire with a second absorbable rod (44), whereby to retain the bone block in the bone tunnel with the absorbable rods.

AUSTRALIA

Patents Act 1990

COMPLETE SPECIFICATION FOR A STANDARD PATENT

ORIGINAL

Name of Applicant:	ETHICON, INC.
Actual Inventors:	Gregory R. WHITTAKER, Joan M. SULLIVAN, Harold M. MARTINS and Ronald L. TAYLOR, Jr.
Address for service in Australia:	CARTER SMITH & BEADLE 2 Railway Parade Camberwell Victoria 3124 Australia
Invention Title:	METHOD AND APPARATUS FOR FIXING A GRAFT IN A BONE TUNNEL

The following statement is a full description of this invention, including the best method of performing it known to us

METHOD AND APPARATUS FOR FIXING

A GRAFT IN A BONE TUNNEL

Field Of The Invention

5 This invention relates to surgical methods and apparatus in general, and more particularly to methods and apparatus for fixing bone blocks in bone tunnels.

Background Of The Invention

10 The complete or partial detachment of ligaments, tendons and/or other soft tissues from their associated bones within the body are relatively commonplace injuries. Tissue detachment may occur as the result of an accident such as a fall, overexertion during a
15 work-related activity, during the course of an athletic event, or in any one of many other situations and/or activities. Such injuries are generally the result of excess stress being placed on the tissues.

20 In the case of a partial detachment, commonly referred to under the general term "sprain", the injury frequently heals itself, if given sufficient time, and if care is taken not to expose the injury to undue stress during the healing process. If, however, the

ligament or tendon is completely detached from its associated bone or bones, or if it is severed as the result of a traumatic injury, partial or permanent disability may result. Fortunately, a number of surgical procedures exist for re-attaching such detached tissues and/or completely replacing severely damaged tissues.

One such procedure involves the re-attachment of the detached tissue using "traditional" attachment devices such as staples, sutures and/or cancellous bone screws. Such traditional attachment devices have also been used to attach tendon or ligament grafts (often formed from autogenous tissue harvested from elsewhere in the body) to the desired bone or bones.

Another procedure is described in U.S. Patent No. 4,950,270, issued August 21, 1990 to Jerald A. Bowman et al. In this procedure, the damaged anterior cruciate ligament ("ACL") in a human knee, for example, is replaced by first forming bone tunnels through the tibia and femur at the points of normal attachment of the anterior cruciate ligament. Next, a ligament graft with a bone block on one of its ends is sized so as to

fit within the bone tunnels. Suture is then attached to the bone block and thereafter passed through the tibial and femoral bone tunnels. The bone block is then drawn through the tibial tunnel and up into the femoral tunnel using the suture. As this is done, the graft ligament extends back out of the femoral tunnel, across the interior of the knee joint, and then through the tibial tunnel. The free end of the graft ligament resides outside the tibia, at the anterior side of the tibia. Next, a bone screw is inserted between the bone block and the wall of femoral bone tunnel so as to securely lock the bone block in position by a tight interference fit. Finally, the free end of the graft ligament is securely attached to the tibia.

In U.S. Patent No. 5,147,362, issued September 15, 1992 to E. Marlowe Goble, there is disclosed a procedure wherein aligned femoral and tibial tunnels are formed in a human knee. A bone block with a graft ligament attached thereto is passed through the tunnels to a blind end of the femoral tunnel where the block is fixed in place by an anchor. The ligament extends out the tibial tunnel, and the end thereof is attached to

the tibial cortex by staples or the like.

Alternatively, the end of the ligament may be fixed in the tibial tunnel by an anchor or by an interference screw.

5 Various types of ligament and/or suture anchors, and anchors for attaching other objects to bone, are also well known in the art. A number of these devices are described in detail in U.S. Patents Nos. 4,898,156; 4,899,743; 4,968,315; 5,356,413; and 5,372,599, each of
10 which is presently owned by Mitek Surgical Products, Inc. of Westwood, Massachusetts, the assignee of this patent application.

15 One known method for anchoring bone blocks in bone tunnels is through "cross-pinning", in which a pin, screw or rod is driven into the bone transversely to the bone tunnel so as to intersect the bone block and thereby cross-pin the bone block in the bone tunnel.
20 In order to provide for proper cross-pinning of the bone block in the bone tunnel, a drill guide is generally used. The drill guide serves to ensure that the transverse passage is positioned in the bone so that it will intersect the appropriate tunnel section

and the bone block. Drill guides for use in effecting such transverse drilling are shown in U.S. Patents Nos. 4,901,711; 4,985,032; 5,152,764; 5,350,380; and 5,431,651.

5 Other patents in which cross-pinning is discussed include U.S. Patents Nos. 3,973,277; 5,004,474; 5,067,962; 5,266,075; 5,356,435; 5,376,119; 5,393,302; and 5,397,356.

10 In U.S. Patent No. 5,431,651, issued July 11, 1995 to E. Marlowe Goble, it is said that a cross-pin screw may be formed out of a material which may be absorbed by the body over time, thereby eliminating any need for the cross-pin screw to be removed in a subsequent surgical procedure.

15 However, such absorbable cross-pin screws as are presently known in the art lack sufficient strength to be passed directly into the bone and the bone block. Accordingly, to use absorbable cross-pin screws, one must first drill a hard metal drilling implement into the bone and bone block, remove the drilling implement, 20 and then replace the drilling implement with the absorbable cross-pin screw. However, removal of the

hard metal drilling implement often permits the bone block to shift in the tunnel, such that the subsequent insertion of the absorbable cross-pin screw becomes impossible.

5 Accordingly, there exists a need for a method and apparatus for fixing a bone block in a bone tunnel such that upon completion of the procedure, the bone block is cross-pinned in the bone tunnel by elements which are made of absorbable material.

10

Objects Of The Invention

 The object of the present invention is, therefore, to provide a method for fixing a bone block in a bone tunnel such that the bone block is retained in the
15 tunnel by cross-pins which are made of a material which is absorbable by the body.

 A further object of the present invention is to provide devices by which the aforementioned method may be realized.

Summary of the Invention

These and other objects of the present invention are addressed by the provision and use of the novel method for deploying an element in bone.

- 5 In accordance with the invention, there is provided a method for deploying an element in bone, the method comprising the steps of:

providing a trocar and trocar sleeve combination comprising a hollow sleeve having a distal end, a proximal end and a longitudinal length, wherein the
10 interior of the sleeve defines a substantially cylindrical longitudinal passageway between the proximal end and the distal end, and a pair of opposing grooves in the sidewall of the passageway,
15 the grooves extending respectively from the proximal end of the sleeve to opposing closed ends spaced from the distal end of the sleeve; and

 a trocar including a shaft having a transverse cross-section adapted to be slidably received in the
20 passageway, a pointed distal end adapted for drilling into bone and a pair of opposing projections adapted to be slidably received in the grooves when the shaft is located in the passageway such that the extension of the pointed end out of the distal end is limited
25 according to the longitudinal distance between the pointed end and the projections in relation to the longitudinal spacing of the closed groove ends from the distal end of the shaft;

 whereby when the trocar is inserted into the
30 passageway, the resulting trocar and trocar sleeve

combination may be rotated and drilled distally into bone as a unit and the trocar may be slidably, proximally removed from the sleeve;

drilling the trocar and trocar sleeve combination
5 into the bone;

removing the trocar from the trocar sleeve;

inserting the element into the bone through the passageway of the sleeve; and

removing the sleeve from the element and the
10 bone.

Brief Description of the Drawings

The above and other objects and features of the present invention will be more fully discussed in, or rendered obvious by, the following detailed
15 description of the preferred embodiments of the invention, which is to be considered together with the accompanying drawings wherein like members refer to like parts, and further wherein:

Fig. 1 is a diagrammatical sectional view of the
20 human knee joint, with appropriate bone tunnels formed therein and with a ligament bone block disposed in one of the tunnels;

Fig. 2 is similar to Fig. 1, but illustrative of a metal wire insertion phase of the inventive method;

25 Fig. 3 is similar to Fig. 2 but illustrative of completion of the metal wire insertion phase;

Fig. 4 is similar to Fig. 3, but illustrative of a first metal wire withdrawal phase;

Fig. 5 is similar to Fig. 4, but illustrative of a first absorbable rod insertion phase;

5 Fig. 6 is similar to Fig. 5, but illustrative of the first absorbable rod having been fully inserted;

Fig. 7 is similar to Fig. 6, but illustrative of a second metal wire withdrawal phase;

10 Fig. 8 is similar to Fig. 7, but illustrative of a second absorbable rod insertion phase;

Fig. 9 is similar to Fig. 8, but illustrative of the completion of the absorbable rod insertion phase of the inventive method;

15 Fig. 10 is a side elevational view of one form of rack assembly for cross-pinning a bone block in a bone tunnel, illustrative of an embodiment of the invention;

Fig. 11 is a bottom view of the rack assembly of Fig. 10;

20 Fig. 12 is a bottom view of a trocar sleeve guide member portion of the rack assembly of Figs. 10 and 11;

Fig. 13 is a side elevational view of the trocar sleeve guide member;

Fig. 14 is a front elevational view of the trocar sleeve guide member;

Fig. 15 is an interrupted side elevational view of a trocar portion of the rack assembly of Fig. 10;

5 Fig. 16 is an interrupted side elevational view, broken away and partly in section, of a trocar sleeve portion of the rack assembly of Fig. 10;

Fig. 17 is an end view of the trocar sleeve portion of Fig. 16;

10 Fig. 18 is a diagrammatical view of a human knee joint and illustrative of a step in a method in which the rack assembly of Fig. 10 is used;

Figs. 19-28 are diagrammatical views illustrating a series of steps in the use of the rack assembly of Fig. 10;

Fig. 29 is a side elevational view of another form of rack assembly illustrative of an alternative embodiment of the invention;

Fig. 30 is a bottom view of the rack assembly of Fig. 29;

Fig. 31 is a bottom view of a trocar sleeve guide member portion of the rack assembly of Fig. 29;

Fig. 32 is a side elevational view of the trocar sleeve guide member;

Fig. 33 is a front elevational view of the trocar sleeve guide member;

5 Fig. 34 is a view similar to that of Fig. 18;

Figs. 35-40 are diagrammatical views illustrating a series of steps in the use of the rack assembly of Fig. 29;

10 Fig. 41 is a side elevational view of a graft ligament, tendon or the like, wherein one end of the graft has been folded back upon itself and tack-stitched in place, and wherein a rod extending through the tissue is shown in phantom;

15 Fig. 42 is a side elevational view similar to Fig. 41, wherein the graft ligament, tendon or the like has been folded back upon itself, and wherein a rod extending between adjacent folds of the graft is shown in phantom;

20 Fig. 43 is a side elevational view similar to Fig. 42, wherein the folded tissue has been "whip stitched" together, and wherein a rod extending through the whip stitched tissue mass is shown in phantom;

Figs. 44-51 are illustrative sectional side elevational views showing the steps of advancing a trocar/trocar sleeve combination into a bone and through a bone tunnel therein, removing the trocar, inserting a rod into the sleeve and across the bone tunnel, removing the sleeve, and pulling an end of a tissue graft around the rod located across the bone tunnel;

Figs. 52 and 53 are illustrative side elevational views of representative bone blocks showing two possible examples of how a bone block may fracture during or after the placement of a cross-pin therethrough;

Fig. 54 is an illustrative sectional side elevational view of a bone block located in a partially closed ended bone tunnel and fixed in position by a rod extending across the bone tunnel between the bone block and the open end of the bone tunnel;

Fig. 55 is an illustrative side elevational view of an assembled trocar/trocar sleeve assembly for use in the present invention;

Figs. 56-63 are illustrative side sectional, elevational views showing the use of long trocars inserted through sleeves, originally placed with the combination depicted in Fig. 55, to penetrate the bone and a bone block for the emplacement of rods to hold the bone block in place within the bone tunnel;

Fig. 64 is a side elevational view of a stepped trocar formed in accordance with the present invention;

Fig. 65 is a side elevational, sectional view showing a trocar sleeve having an internal stop adapted to limit the travel of a stepped trocar, as depicted in Fig. 64, therethrough;

Fig. 66 is an exploded, side sectional, elevational view illustrating the use of a plunger and tapping device for driving a rod through a sleeve in bone and into a bone block located in a bone tunnel;

Fig. 67 is a side elevational view of another trocar/trocar sleeve combination formed in accordance with the present invention;

Fig. 68 is a side elevational view of still another trocar/trocar sleeve combination formed in accordance with the present invention;

Fig. 69 is an illustrative perspective view showing an apertured head substituted for the enlarged cannulated sleeve head depicted in Fig. 19; and

Figs. 70-74 are illustrative side elevational views showing the disposition of a rod across a reduced bone fracture using a trocar/trocar sleeve combination formed in accordance with the present invention.

Detailed Description Of The Preferred Embodiments

Referring first to Fig. 1, it will be seen that a human knee joint 10, including a femur 12 and tibia 14, has been provided with an appropriate femoral bone tunnel 16 and an appropriate tibial bone tunnel 18. Such tunnels may be provided in ways well known in the art. A bone block 20, having ligament material 22 attached thereto, has been positioned in femoral tunnel 16. Such bone block positioning may also be achieved in ways well known in the art.

Looking next at Fig. 2, in accordance with the present invention, a first metal wire 30, which may be of the type commonly referred to as a guidewire or a "K-wire", is advanced through skin 31 and a first

portion 32 of femur 12. First wire 30 is advanced transversely of femoral tunnel 16 so as to intersect and extend through bone block 20, as shown in Fig. 2. Thereafter, or simultaneously therewith, a second metal wire 34 is advanced through a second portion 36 of femur 12. Second wire 34 is also advanced transversely of femoral tunnel 16 so as to also intersect and extend through bone block 20 (Fig. 3). At this point, bone block 20 is securely held in femoral tunnel 16 by the two spaced-apart metal wires 30, 34.

Referring next to Fig. 4, it will be seen that one of the two wires 30, 34 is then removed, while the other of the two wires 30, 34 is left in place in femur 12 and bone block 20. By way of example but not limitation, wire 30 may be removed while wire 34 is left in place. A first absorbable rod 40 (Fig. 5) is then advanced through the bore 42 left by the removal of first wire 30, such that first absorbable rod 40 extends through femur 12 and bone block 20 (Fig. 6). At this point, bone block 20 is securely held in femoral tunnel 16 by both metal wire 34 and first absorbable rod 40.

Thereafter, the other of the two metal wires 30, 34 is withdrawn (e.g., in Fig. 7, metal wire 34 is removed), and a second absorbable rod 44 (Fig. 8) is advanced through the bore 46 left by the removal of metal wire 34, such that second absorbable rod 44 also extends through femur 12 and bone block 20 (Fig. 9).

It will be appreciated that, upon completion of the insertion of second absorbable rod 44 (Fig. 9), bone block 20 is retained in femoral tunnel 16 solely by the absorbable rods 40, 44.

The absorbable rods 40, 44 may be made out of a material such as polylactic acid (PLA), polyglycolic acid (PGA), polydioxanone (PDS), or out of some other such material which is formable into a relatively rigid and hard configuration, but which is absorbable by the body of the patient over time. If desired, the distal ends of absorbable rods 40, 44 can be pointed or rounded so as to facilitate their deployment into the body.

There is thus provided a method by which a bone block is fixed within a bone tunnel, such that the bone block is anchored in the tunnel by cross-pins which are

made out of a material which is absorbable by the body over time.

It will be understood that while the above method has been described and illustrated with respect to first and second wires replaced serially by first and second absorbable rods, the method may be exercised with any reasonable number of wires, exceeding one. In the latter instance, the method includes the steps of placing the bone block in the bone tunnel, and then advancing a plurality of metal wires through the bone, transversely of the tunnel, so as to intercept the bone block and extend therethrough. At least one of the wires is then removed while leaving at least one of the wires in place, and that at least one removed wire is then replaced by at least one absorbable rod. At least one further of the wires is then removed and that at least one removed wire is then replaced by at least one further absorbable rod. The last-mentioned step is then repeated until a selected number of the metal wires is each replaced with an absorbable rod, whereby to retain the bone block in the bone tunnel with absorbable rods.

It will also be understood that while Figs. 1-9 show metal wires 30, 34 and absorbable rods 40, 44 passing completely through bone block 20 during the cross-pinning procedure, it is also possible for metal wires 30, 34 and absorbable rods 40, 44 to pass only part way across bone block 20, if the same should be desired.

Furthermore, it will also be understood that while the above method has been described and illustrated with respect to metal wires 30, 34 being used to drill through femur 12 and bone block 20, other drilling implements (e.g., a twist drill or a spade drill) might also be used.

As noted above, various drill guides have been developed for forming transverse passages through the femur and bone block so as to cross-pin the bone block within the femoral tunnel. If desired, the inventive method of the present invention may be practiced using such known drill guides. Alternatively, the present invention may also be practiced using a novel rack assembly formed in accordance with the present invention.

More particularly, and looking now at Figs. 10-17,
a novel rack assembly 50 is disclosed for practicing
the present invention. Rack assembly 50 comprises an
L-shaped member 52 having a base portion 54 and an arm
5 portion 56. The arm portion 56 extends transversely,
and preferably is normal to, base portion 54.

Rack assembly 50 also includes a cannulated sleeve
58 which, at a first end 60 thereof, is provided with
an enlarged head portion 62, and which, at a second end
10 64 thereof, is releasably connectable to base portion
54 of L-shaped member 52. Sleeve 58 may be retained in
a bore 65 (Fig. 11) formed in base portion 54 by a set
screw 66.

A trocar sleeve guide member 70 is removably
15 connectable to arm portion 56 of L-shaped member 52.
Trocar sleeve guide member 70 is provided with bores 72
extending therethrough. Bores 72 extend substantially
normal to a longitudinal axis 68 (Fig. 10) of the
enlarged head portion 62 of cannulated sleeve 58. A
20 set screw 71 (Fig. 11) may be used to releasably retain
trocar sleeve guide member 70 in position on arm
portion 56. Alternatively, or in addition, arm portion

56 may be provided with stop means (not shown) for limiting the movement of the trocar sleeve guide member 70 along arm portion 56. Trocar sleeve guide member 70 is preferably formed in two halves releasably held together by a set screw 73 (Fig. 11), whereby trocar sleeve guide member 70 can be slidably mounted on, or detached from, trocar sleeves 74, 76 passing through bores 72, as will hereinafter be discussed.

First and second trocar sleeves 74, 76 are slidably received by bores 72, such that sleeves 74, 76 are axially and rotatably movable in bores 72. Referring to Figs. 16 and 17, it will be seen that trocar sleeve 74 is provided with a collar portion 78 having a slot 80 formed therein. Sleeve 76 is substantially identical to sleeve 74.

Rack assembly 50 also includes one or more trocars 82 (Figs. 10 and 15) for disposition in the sleeves 74, 76. Each trocar 82 is provided with a sharp end 84 (Fig. 15) for penetration of bone. A transversely-extending pin 86 is provided near (but spaced from) the opposite end of the trocar 82. Pin 86 is fixed in place and is receivable by the slots 80 of trocar

sleeves 74, 76 such that axial (in a distal direction) and rotational movement of trocar 82 causes similar movement of sleeves 74, 76.

5 The first and second absorbable rods 40, 44 are slidable through sleeves 74, 76, as will be further described hereinbelow.

Figs. 18-28 illustrate how rack assembly 50 may be used to practice the present invention.

10 Referring now to Fig. 18, there is shown a human knee joint 10 including femur 12 and tibia 14. An appropriate femoral tunnel 16 and an appropriate tibial tunnel 18 have been provided, as by means and methods well known in the art. A guidewire 90 extends through the bone tunnels 16, 18 as shown.

15 In accordance with the present invention, the rack assembly's cannulated sleeve 58 is fed over guidewire 90, through tibial tunnel 18 and into femoral tunnel 16, until the cannulated sleeve's head portion 62 engages an annular shoulder 92 in femoral tunnel 16 (Fig. 19). As this occurs, guidewire 90 extends through a bore 94 (Figs. 10 and 19) formed in base portion 54 of L-shaped member 52. The cannulated

20

sleeve's head portion 62 is preferably sized so as to form a snug fit in femoral tunnel 16. Cannulated sleeve 58 may be positioned in the bone tunnels 16, 18 and then connected to L-shaped member 52 or, more preferably, cannulated sleeve 58 may be first connected to L-shaped member 52 and then positioned in femur 12 and tibia 14. Trocar sleeve guide member 70, if not already positioned on arm portion 56, is then fixed to arm portion 56, as by set screw 71 (Fig. 11).

First trocar sleeve 74 is then inserted in a bore 72 of guide member 70 (Fig. 20), and trocar 82 is extended through sleeve 74 until pin 86 (Fig. 15) of trocar 82 is nested in slot 80 (Figs. 16 and 17) of sleeve 74, with the trocar's sharp end 84 extending beyond the distal end of sleeve 74 (Fig. 20).

Alternatively, trocar 82 may be mounted in first trocar sleeve 74 before first trocar sleeve 74 is mounted in a bore 72. The combination of trocar sleeve 74 and trocar 82 is then drilled, as a unit, into femur 12 toward, but short of, the enlarged head portion 62 of cannulated sleeve 58 (Fig. 20).

Trocar 82 may then be withdrawn from first trocar sleeve 74 and placed in second trocar sleeve 76 (Fig. 21). Alternatively, a second trocar 82 may be provided for second trocar sleeve 76. In either case, the combination of trocar sleeve 76 and trocar 82 is then drilled, as a unit, into femur 12 toward, but short of, head portion 62 of cannulated sleeve 58. The rack's L-shaped member 52 may then be removed from the surgical site. This may be accomplished by first loosening set screw 73 (Fig. 11) so as to separate trocar sleeve guide member 70 into its two halves, whereby trocar sleeves 74, 76 will be freed from guide member 70, and then sliding cannulated sleeve 58 downward along guidewire 90 until the cannulated sleeve emerges from bone tunnels 16, 18. This procedure will leave trocar sleeves 74, 76 lodged in femur 12 (Fig. 22).

Guidewire 90 is then used to pull a suture 96, which is attached to bone block 20, up through tibial tunnel 18 and into femoral tunnel 16, until bone block 20 engages the annular shoulder 92 in femoral tunnel 16 (Fig. 23). Guidewire 90 may be provided with an eyelet (not shown) adjacent to its proximal end so as to

facilitate this procedure. Bone block 20 can then be held in this position by maintaining tension on the portion of suture 96 emerging from the top of femur 12.

Trocar sleeve 76 and trocar 82 are then drilled
5 through bone block 20, as shown in Fig. 24. Trocar 82 may then be removed from sleeve 76, placed in sleeve 74, and sleeve 74 and trocar 82 drilled through bone block 20, as shown in Fig. 25. The trocar 82 (or
10 trocars 82 if more than one trocar is used) may then be withdrawn from the sleeve 74 (or sleeves 74, 76). The first absorbable rod 40 is then inserted, by sliding rod 40 through trocar sleeve 74 into a position
15 extending through bone block 20 (Fig. 26). Sleeve 74 may then be withdrawn from bone block 20 and femur 12, leaving first absorbable rod 40 in place in femur 12 and extending through bone block 20, as shown in Fig. 27.

Similarly, second absorbable rod 44 is then slid into place through sleeve 76. Sleeve 76 is then
20 removed, leaving second absorbable rod 44, along with first absorbable rod 40, extending through bone block

20 so as to lock bone block 20 in place in femoral tunnel 16, as shown in Fig. 28.

It should be appreciated that it is also possible to provide rack assembly 50 with a guide member 70 which is not formed in two separable halves. In this situation, when the rack's L-shaped member 52 is to be withdrawn from the surgical site (see Figs. 21 and 22), guide member 70 can simply be detached from L-shaped member 52 by unscrewing set screw 71. Guide member 70 can then be left mounted on the outboard portions of sleeves 74, 76 until sleeves 74, 76 are withdrawn from the surgical site, with guide member 70 being removed with the last of the sleeves 74, 76.

The present invention may also be practiced using the novel rack assembly 100 illustrated in Figs. 29-33. Rack assembly 100 comprises an L-shaped member 102 having a base portion 104 and an arm portion 106. Arm portion 106 extends transversely of, and preferably is normal to, base portion 104.

Rack assembly 100 also includes a cannulated sleeve 108 which, at a base end 110 thereof, is connected to base portion 104. Cannulated sleeve 108

may be retained in a bore 112 in base portion 104, as by screw threads or a set screw (not shown) or a press fit or the like. Cannulated sleeve 108 is provided with a slot 114 (Fig. 29) extending substantially throughout the length of sleeve 108. Base portion 104 of L-shaped member 102 is also provided with a slot 116 (Fig. 30) which is alignable with the sleeve's slot 114 so as to place the slots 114, 116 in communication with each other.

A trocar sleeve guide member 120 is removably connectable to arm portion 106 of L-shaped member 102. Trocar sleeve guide member 120 is provided with bores 122 extending therethrough. Bores 122 extend substantially normal to a hypothetical extension of the longitudinal axis 124 of cannulated sleeve 108. A set screw 126 (Fig. 30) may be used to releasably retain trocar sleeve guide member 120 in position on arm portion 106. To assist in positioning trocar sleeve guide member 120 on arm portion 106 of L-shaped member 102, arm portion 106 may be provided with a stop means (not shown) for limiting movement of member 120 on arm portion 106. Trocar sleeve guide member 120 is

preferably formed in two halves releasably held together by a set screw 127 (Fig. 30), whereby trocar sleeve guide member 120 can be slidably mounted on, or detachable from, trocar sleeves 128, 130 passing through bores 122, as will hereinafter be discussed.

First and second trocar sleeves 128, 130 are received by bores 122, such that sleeves 128, 130 are axially and rotatably movable in bores 122. The two trocar sleeves 128, 130 are substantially identical to the sleeve 74 shown in Figs. 16 and 17. Rack assembly 100 also includes one or more trocars 132 for disposition in sleeves 128, 130. The trocar 132 is substantially identical to the trocar 82 shown in Fig. 15. The aforementioned first and second absorbable rods 40, 44 are slidable through sleeves 128, 130.

Figs. 34-40 illustrate how rack assembly 100 may be used to practice the present invention.

Referring now to Fig. 34, it will be seen that bone tunnels 16 and 18 are formed in femur 12 and tibia 18, respectively, and a guidewire 90 extends through bone tunnels 16, 18. Guidewire 90 is then used to pull a suture 96, which is attached to bone block 20, up

through tibial tunnel 18 and into femoral tunnel 16,
such that bone block 20 is in engagement with annular
shoulder 92 (Fig. 35). Bone block 20 is kept in this
position by maintaining tension on the portion of
5 suture 96 emerging from the top of femur 12.

Suture 96 is then introduced into the rack
assembly's cannulated sleeve 108 and base portion 104
by way of slots 114, 116. Cannulated sleeve 108 is
then passed down the hole 133 (Figs. 35 and 36) left by
10 the removed guidewire 90 until the distal end of the
cannulated sleeve engages the top end of bone block 20
(Fig. 36). Next, first trocar sleeve 128 is extended
through a guide member bore 122 and a trocar 132 is
inserted into sleeve 128. Alternatively, a trocar 132
15 may be inserted into first trocar sleeve 128 before
first trocar sleeve 128 is inserted into a guide member
bore 122. The sleeve 128 and trocar 132 are then
drilled, as a unit, into femur 12. With bone block 20
held against shoulder 92 by pulling on suture 96, the
20 combination of sleeve 128 and trocar 132 is drilled
through bone block 20 (Fig. 36). In a similar manner,
sleeve 130 and trocar 132 (either the same trocar used

with sleeve 128 or another trocar) are then drilled through bone block 20, as shown in Fig. 37.

L-shaped member 102 and cannulated sleeve 108 are then removed from the surgical site. This may be accomplished by first loosening set screw 127 (Fig. 30) so as to separate trocar sleeve guide member 120 into its two halves, whereby trocar sleeves 128, 130 will be freed from guide member 120, and then sliding cannulated sleeve 108 upward and out of hole 133. Any trocars 132 are then removed, leaving the trocar sleeves 128, 130 extending into femur 12 and across bone block 20, as shown in Fig. 38.

Second absorbable rod 44 is then slid through sleeve 130 and sleeve 130 removed (Fig. 39), and first absorbable rod 40 is slid through sleeve 128 and sleeve 128 removed, leaving absorbable rods 40, 44 in place (Fig. 40) holding bone block 20 locked in femoral tunnel 16.

Suture 96 is then slipped through bone block 20 and removed, in the manner well known in the art.

It is to be understood that the present invention is by no means limited to the application thereof as

herein disclosed and/or as shown in the drawings. For example, for illustrative purposes, the inventive method and apparatus are described herein and illustrated with reference to the human knee joint. It is foreseen that the method and apparatus described herein will be particularly beneficial with respect to such operations. However, it will also be appreciated by those skilled in the art that the method and apparatus described herein find utility with respect to mammals generally, and with respect to other bones as, for example, in shoulder joints or the like.

By way of further example, trocars 82 and 132 and their associated sleeves 74, 76 and 128, 130, respectively, might be passed only part way through bone block 20, but not all the way through; or sleeves 74, 76 and/or sleeves 128, 130 might be stopped short of bone block 20 while trocars 82 and/or 132 penetrate into bone block 20.

Furthermore, trocars 82 and 132 are disclosed herein as being in the form of a hard rod with a sharp tip for penetrating bone. Thus, for example, trocars 82 and 132 might comprise guidewires or K-wires with a

pyramidal front point. Alternatively, however, the invention might also be practiced with trocars 82 and 132 comprising a twist drill, a spade drill and/or some other sort of drill.

5 Also it is contemplated that trocars 82 and/or 132 might be used with their associated rack assemblies 50 and 100, respectively, but without their associated sleeves 74, 76 and 128, 130, respectively. In this case, at least one trocar would always remain
10 positioned in bone block 20 until at least one absorbable rod 40, 44 was positioned in the bone block.

 It desired, it is also possible to practice the present invention using just one sleeve 74 and one trocar 82, or just one sleeve 76 and one trocar 82; and
15 it is possible to practice the invention using just one sleeve 128 and one trocar 132, or just one sleeve 130 and one trocar 132. In such a situation, the sleeve element would serve to retain the bone block in
20 position within the bone tunnel while the trocar is replaced by the rod which will ultimately hold the bone block to the bone.

It should also be appreciated that the present application will have utility with respect to setting cross-pins which may not necessarily be absorbable. In particular, the present invention will have utility
5 wherever cross-pinning needs to be achieved for cross-pins which cannot be passed directly through the bone and/or bone block, e.g., where the cross-pins may be too soft or too brittle or too fragile to pass directly through the bone and/or bone block, or where the cross-
10 pins may have a geometry which makes it difficult or impossible for them to be passed directly through the bone and/or bone block. By way of example, the present invention might be used to set cross-pins made out of plastic and/or ceramic materials, or the present
15 invention might be used to set cross-pins made out of metal.

In addition, numerous other alternatives are contemplated within the scope of the present invention in its broadest aspects.

20 More particularly, it will be understood by those skilled in the art that there are many instances wherein it is desired to locate a portion of a piece of

soft tissue, such as a ligament, tendon or the like, within a bone tunnel, without a bone block attached to it. This may occur, for example, where a prosthetic substitute for a ligament, tendon or the like is to be used to effect a repair, or in those instances wherein it is undesirable for one reason or another to harvest a repair graft from elsewhere in the patient's body along with a bone block naturally attached to one end of the graft.

In such cases, a portion of the piece of tissue alone may be cross-pinned in a bone tunnel by any of the methods discussed above. Specifically, as shown in Figs. 41 and 42, the portion 150 of the piece of tissue 152 to be cross-pinned in the bone tunnel is preferably folded back upon itself one or more times. When this is done, tacking stitches 154 may be used to hold the layers 156 of folded tissue together while the resulting mass 150 is inserted or pulled into the bone tunnel in a manner similar to the procedures used to locate a bone block in a bone tunnel discussed above. Thereafter, cross-pinning proceeds substantially as discussed above, such that the rods 158 ultimately

extend either through the tissue mass (see phantom lines in Fig. 41), or between the folded tissue layers (see phantom lines in Fig. 42), or both.

In this alternative, the chances of the rod and/or sleeve and/or trocar tearing laterally out of, or longitudinally along, the tissue 152 may be significant. This is particularly the case in those instances wherein the repair is to be subjected to substantial stress prior to complete healing.

Accordingly, it is often desirable to reinforce the portion 150 of the tissue 152 to be cross-pinned within the bone tunnel. This may be accomplished in numerous ways well known to those skilled in the art. One such alternative, representatively shown in Fig. 43, is to "whip stitch" the portion 150 of the tissue 152 which is to be cross-pinned within the bone tunnel. This creates a braid-enclosed, substantially solid mass 160 adapted to receive the rods 158, and adds the strength of the numerous passes of the cord-like material 162, extending through the tissue as used to form the "whip stitch", to alleviate the tear-out problem referred to above. In addition, "whip stitching" is well

understood by surgeons, and relatively easy to do.

Therefore, this alternative avoids certain complications which may arise during the harvesting of tissue grafts with bone blocks attached; avoids

5 trimming bone blocks to fit bone tunnels during surgical procedures; and provides a simple, fast and efficient way to cross-pin the tissue in a bone tunnel, with minimal added trauma to the patient.

10 As noted above, the foregoing procedures may also be used to secure artificial grafts in the bone tunnel, i.e., grafts comprising an artificial prosthetic device not harvested from the body. In such a case, it may or may not be desirable to fold the graft back upon itself one or more times, in the manner shown in Figs. 41-43, prior to cross-pinning.

15 Similarly, a portion 150 of a piece of tissue 152 may be fixed in a bone tunnel by positioning a bio-absorbable rod 163 diametrically across the bone tunnel 164, and thereafter pulling the portion 150 of the piece of tissue 152 into an open end of the bone tunnel, around the rod 163 and back out the same open end of the bone tunnel. More particularly, as best

seen in Figs. 44-51, it has been found that the positioning of a bio-absorbable rod 163 diametrically across bone tunnel 164 is best accomplished with a trocar/sleeve combination 171 such as that

5 illustratively shown in Figs. 15-17. This is because in any alternative wherein a means such as a sharpened k-wire, trocar or the like is used without an accompanying sleeve to form an opening through the bone 166, through the bone tunnel 164, and into the bone 166 on the opposite side of the bone tunnel 164, it is
10 difficult to remove the hole-forming device and to replace it with a rod 163. Typically, the rod 163 will pass through the opening 168 (Fig. 49) and through the bone tunnel 164 easily, however, it is often not as
15 easy to locate and engage opening 170 on the other side of bone tunnel 164 with the forward end of rod 163.

Accordingly, in the practice of this alternative, it is preferred that a trocar/sleeve combination 171 be drilled in the manner discussed in detail above into
20 bone 166, transversely to the longitudinal axis 172 (Fig. 44) of bone tunnel 164, diametrically through bone tunnel 164, and into bone 166 on the opposite side

of bone tunnel 164 (see Figs. 44 and 45). Thereafter,
the trocar 171a is removed from sleeve 171b, and a
bio-absorbable rod 163 is inserted into sleeve 171a so
as to occupy a position extending across bone tunnel
5 164 (see Figs. 46-48). Sleeve 171b is then removed
from bone 166 and rod 163, leaving rod 163 extending
from opening 168, diametrically across bone tunnel 164
and into opening 170 (see Fig. 49).

At this point in the procedure, or earlier if
10 desired, one end 175 of a length of cord-like material,
such as suture 173, is secured to an end 174 of piece
of tissue 152 (Fig. 50). The other end 176 of the
length of cord-like material 173 is then threaded into
an open end 178 of bone tunnel 164, and thence around
15 rod 163, and then back out open end 178 of bone tunnel
164 (see Fig. 50). Finally, the free end 176 of the
cord-like material 173 is pulled so as to draw portion
150 of piece of tissue 152 into open end 178 of bone
tunnel 164, around bio-absorbable rod 163, and back out
20 open end 178 of bone tunnel 164. Tissue portion 150
thus assumes a generally U-shape, having its closed end
slidably secured in bone tunnel 164 by bio-absorbable

rod 163, and its free ends extending outwardly from the same open end 178 of bone tunnel 164 (see Fig. 51).

As noted above, the foregoing procedure may also be used to secure articial grafts in the bone tunnel, i.e., grafts comprising an artificial prosthetic device not harvested from the body.

Still further, it has been found that, in practice, bone blocks are relatively hard. This is frequently the case where the bone block is formed out of cortical bone. In addition, it can also sometimes be relatively difficult to drill a trocar/sleeve combination through bone 166, particularly where bone 166 comprises a substantial layer of cortical bone. Consequently, it can be difficult to drill a trocar/sleeve combination (see, for example, Fig. 55) through the bone, and into and/or through the bone block. In addition, even if this drilling is successfully accomplished, the bone block may fracture, as shown, for example, in Figs. 52 and 53. In this respect it is noted that the possibility of bone block fracture may be reduced by reducing the diameter of the trocar/sleeve combination, and hence the resulting hole

through the bone block, but this may in turn lead to an increase in the possibility of rod breakage when a load is applied to the graft ligament.

Two alternatives have been developed to address these problems.

In the first of these alternatives, best seen in Fig. 54, the solution utilizes the facts that (1) a bone block is significantly stronger in compression than it is in tension, and (2) a larger diameter rod will provide a stronger bone block fixation in a bone tunnel if bone block fracture is not an issue. Specifically, the bone block 200 is located at substantially closed end 202 of substantially blind bone tunnel 204, with its associated tissue graft 206 extending outwardly from the open end 208 of the substantially blind bone tunnel 204. It will be understood that a guide hole 201 may extend through substantially closed end 202 of bone tunnel 204 so as to allow bone block 200 to be drawn into bone tunnel 204 by a cord-like element 203, or otherwise located in bone tunnel 204 as discussed hereinabove. A rod 208, as much as 30% larger in diameter than a rod suitable

for emplacement through bone block 200, is then located diametrically across bone tunnel 204 adjacent to proximal end 210 of bone block 200. In this case, rod 208 is positioned utilizing the same method as described above with regard to the threading of a portion of a piece of tissue over a rod extending diametrically through a bone tunnel (see Figs. 44-51). Also, the rod 208 may pass through the tissue graft 208, or not, as desired. The result is that bone block 200 is reliably fixed in bone tunnel 206 between substantially closed tunnel end 202 and rod 208.

The second of the above-mentioned alternatives proceeds from the premise that if the sleeve does not have to extend into or through the bone block, a significantly larger diameter rod may be used with a corresponding increase in the strength of the fixation of the bone block in the bone tunnel. This alternative is representatively shown in Figs. 56-63, which will be referred to specifically below.

In this case, the trocar/sleeve combinations 210 (see Figs. 15-17 and 55) are drilled through the skin and into the bone in the same manner as discussed in

detail above, and the bone block is located in the bone tunnel such that the various elements reside in a configuration generally as depicted in Fig. 22. At this point, the trocars are disengaged from the sleeves, the bone block is pulled up into the bone tunnel (Fig. 23), and rods are inserted through (i) the sleeves and (ii) the bone located between the distal ends of the sleeves and the bone tunnel, and then into the bone block.

The latter insertion step may be accomplished in any one of several different ways. For example, a second, longer trocar 212a, 212b may be inserted into each of the sleeves 214a, 214b and either drilled (Fig. 57) or tapped (Fig. 58) through the bone 216 located between the distal ends 218a, 218b of the sleeves 214a, 214b, and then into the bone tunnel 220 and into the bone block 222. Thereafter, one of the longer trocars 212 is removed (Fig. 59), and a metal, plastic, ceramic or bio-absorbable rod 224a is inserted into the bone and the bone block through the sleeve (Fig. 60). This is followed by the removal of the other longer trocar 212 (Fig. 61) and the insertion of another rod 224b

into the bone and bone block through the second sleeve (Fig. 62). Finally, the sleeves are removed from the patient (Fig. 63).

In the last discussed alternative, the longer
5 trocars 212a and 212b are commonly stepped, e.g., in
the manner shown in Fig. 24. More particularly, the
longer trocars 212a commonly include a distal portion
230 having a smaller transverse cross-sectional
diameter than their proximal portion 232, and define a
10 distally-facing radial shoulder 234 at the joiner of
their proximal and distal portions. In this way, the
extent of trocar penetration beyond the distal ends of
the sleeves is controlled by pre-selecting the axial
length of the distal portion of the longer trocars.
15 More specifically, the longer trocars are allowed to
penetrate beyond the distal ends of the sleeves only to
the point at which their distally-facing radial
shoulders engage either the bone at the distal ends of
the sleeves, or a radially-disposed, inward projection
20 236 formed on the sleeve side wall (Fig. 65).

Alternatively, rigid rods 224a, 224b may be driven
through the sleeves 214a, 214b, through the bone 216

located between the sleeves and the bone tunnel 220,
and then into the bone block 222 directly. This may be
accomplished by, preferably, pointing or rounding the
distal ends of the rods 224a, 224b, inserting the rods
5 into the sleeves 214a, 214b, and using a plunger shaft
238 and tapping means 240 to drive the rods into
position through the bone and into the bone block (Fig.
66).

It further has been found, that in the
10 interlocking trocar/sleeve assembly shown in Figs.
15-17 and 55, the radial shoulder 242 (Fig. 55), formed
by the distal end of the sleeve proximally of the
pointed distal end 224 of the trocar extending distally
thereof, can be a significant impediment to the passage
15 of the interlocked trocar/sleeve combination into bone.
Indeed, in practice, this shoulder, while normally only
about .005 to .010 inch in radial thickness, has been
noted to cause burning of the bone as the trocar/sleeve
combination is advanced through the bone toward the
20 bone tunnel. To correct this problem, the distal edge
242 of the sleeve could be bevelled at an angle
substantially equal to that of the adjacent trocar

point 244 (see Fig. 67). This is not preferred, however, in view of the variations in machining tolerance commonly acceptable in the art in the formation of bevelled edges and trocar points. In particular, the chance of an exact mating of the trocar point with a bevelled sleeve end is unlikely. Hence, the bone burning problem, and more generally the problem of the resistance to penetration of the trocar/sleeve combination into the bone, are still present in the embodiment shown in Fig. 67, albeit to a perhaps smaller degree than in the Fig. 55 embodiment.

To solve this basic problem, it has been found that the distal end 246 of the sleeve 248 should be slanted at an angle of approximately 15° proximally relative to a plane 250 located normal to the longitudinal axis 252 of the sleeve (see Fig. 68). In the resulting construction of the trocar/sleeve assembly, the trocar point 256 drills into the bone in the same manner as previously described, while the slanted distal end 246 of the sleeve 248 cuts into the sidewall of the hole formed by the trocar point, instead of rotating flat against the bone surrounding

the hole being formed by the trocar. As a practical matter, this alternative is deemed to be of significant importance, inasmuch as the ease of use of the methods and apparatus described herein affects their commercial utility. A bone drill which does not exhibit a tendency to bind, and/or to burn the bone during use, is significantly more desirable than a bone drill which does bind or burn the bone during use.

Accordingly it will be understood that, currently, one preferred method of practicing the present invention includes the following steps:

(1) drilling at least two trocar/sleeve assemblies, of the type depicted in Fig. 68, into the bone to a position similar to that shown in Fig. 22 (note: this may be accomplished by sequentially and separately mating a single trocar with each sleeve and drilling that assembly into the bone);

(2) removing the trocar(s) from the sleeves so as to leave the sleeves extending through the skin and into the bone, but not intersecting the bone tunnel;

(3) removing the rack assembly (see element 52 in Fig. 21) from the sleeves and the bone tunnel;

(4) locating a bone block in the bone tunnel in alignment with axial projections of the sleeves;

(5) using a first, elongated, stepped trocar (see Fig. 64) to drill through the bone between the distal end of the first sleeve and the bone tunnel, through the bone block, and a pre-selected distance into the bone on the opposite side of the bone tunnel;

(6) with the first, elongated stepped trocar extending through the bone and the bone block, using a second, elongated stepped trocar to drill through the bone between the distal end of the second sleeve and the bone tunnel, through the bone block, and a pre-selected distance into the bone on the opposite side of the bone tunnel;

(7) removing the second trocar from the bone, the bone block and the second sleeve;

(8) inserting a rigid rod (of bio-absorbable, or non-bio-absorbable, material) through the second sleeve to a position wherein it extends through the bone block and engages openings on opposite sides of the bone tunnel as formed by the second elongated stepped trocar;

(9) removing the first trocar from the bone, the bone block and the first sleeve;

(10) inserting another rigid rod (of bio-absorbable, or non-bio-absorbable, material) through the first sleeve to a position wherein it extends through the bone block and engages the openings on opposite sides of the bone tunnel as formed by the first elongated stepped trocar; and

(11) removing the first and second sleeves from the patient.

The last mentioned alternatives also provide advantageous settings for the use of certain modifications to the above-described cross-pinning apparatus. For example, in the embodiment of the rack assembly discussed above wherein the cannulated sleeve 58 has an enlarged head 62 adapted for location in a bone tunnel transversely of the trocar/sleeve assemblies which are being drilled into the surrounding bone (Figs. 19-21), a flattened head 258 (Fig. 69) defining a window 260 therethrough might be used in place of the enlarged head 62. In such a case, the flattened head 258 would extend substantially

diametrically across the bone tunnel 262 in a plane transverse to an axial projection of the trocar/sleeve assemblies 264 being drilled into the bone. Further, the window 260 would be so disposed that the

5 trocar/sleeve assemblies (or the trocars alone) could penetrate into the bone tunnel, through the window 260 in the head of the cannulated sleeve 266, and then into the bone on the opposite side of the bone tunnel.

More particularly, as shown in Fig. 69, this

10 embodiment of the present invention is useful in any situation in which it is desired to form diametrically opposed openings in the sidewall of a bone tunnel. Particular examples of such situations include those wherein the length of the sleeve and the length, and

15 rigidity, of the rods are such that they may be relied upon to ensure that a rod entering the bone tunnel from the drill means entry side thereof will be maintained in alignment with, and engage, the opening on the other side of the bone tunnel. Thus, those cases mentioned



20 above wherein a rigid rod is passed through an object in a bone tunnel may find this alternative beneficial.

Finally, it is to be understood that the interlocking trocar/sleeve assemblies discussed hereinabove have numerous other uses beyond the cross-pinning of objects in bone tunnels. One such illustrative use is in the placement of absorbable, or non-absorbable, pins across bone fractures so as to assist in maintaining broken bones in a desired healing relationship after fracture reduction procedures have been completed. As depicted in Figs. 70-74, this method follows the now well-understood steps of drilling a trocar/sleeve assembly into the desired position in bone, removing the trocar, inserting a rod into the sleeve, and then removing the sleeve from the bone and the rod.

Other illustrative uses of the devices and concepts of the present invention may include, among others, the removal of tissue from the interior of bones, and/or the delivery of other things into the interior of a bone, such as other devices or prostheses, drugs, bone graft material, substitute bone marrow, and so on.

Numerous further variations, alterations, modifications and other derivations of the present invention will occur and/or become obvious to those skilled in the art in view of the foregoing detailed description of the preferred embodiments of the present invention. Accordingly, it is to be understood that the foregoing specification and the appended drawings are intended to be illustrative only, and not as limiting of the invention.

10



THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method for deploying an element in bone, said method comprising the steps of:

providing a trocar and trocar sleeve combination
5 comprising a hollow sleeve having a distal end, a proximal end and a longitudinal length, wherein the interior of said sleeve defines a substantially cylindrical longitudinal passageway between said proximal end and said distal end, and a pair of
10 opposing grooves in the sidewall of said passageway, said grooves extending respectively from said proximal end of said sleeve to opposing closed ends spaced from said distal end of said sleeve; and

a trocar including a shaft having a transverse
15 cross-section adapted to be slidably received in said passageway, a pointed distal end adapted for drilling into bone and a pair of opposing projections adapted to be slidably received in said grooves when said shaft is located in said passageway such that the
20 extension of said pointed end out of said distal end is limited according to the longitudinal distance between said pointed end and said projections in relation to the longitudinal spacing of said closed groove ends from said distal end of said shaft;

25 whereby when said trocar is inserted into said passageway, the resulting trocar and trocar sleeve combination may be rotated and drilled distally into bone as a unit and said trocar may be slidably, proximally removed from said sleeve;

30 drilling said trocar and trocar sleeve

combination into the bone;

removing said trocar from said trocar sleeve;

inserting said element into said bone through said passageway of said sleeve; and

5 removing said sleeve from said element and said bone.

2. A method according to claim 1 further comprising the steps of:

providing a second trocar including a distal
10 portion having a first transverse cross-section and a proximal portion having a second transverse cross-section, said first transverse cross-section being smaller than said second transverse cross-section, and a distally facing shoulder at the joinder of said
15 first and second transverse cross-sections,

and after removing said trocar but before inserting said element, drilling said second trocar into said bone at the distal end of said sleeve a longitudinal length substantially equal to said
20 proximal portion of said trocar, such that said shoulder abuts said bone at said distal end of said sleeve.

3. A method according to claim 2 wherein the longitudinal passageway through said sleeve includes
25 internal stop means adapted to engage said trocar shoulder so as to further limit the longitudinal travel of said second trocar through said sleeve and into said bone at said distal end of said sleeve.

4. A method according to claim 2 wherein said

bone defines a bone tunnel, said trocar and trocar sleeve combination penetrates into said bone transversely of said bone tunnel but not into said bone tunnel, a bone block is located in said bone tunnel in axial alignment with said trocar and trocar sleeve combination, and said second trocar penetrates through the bone between the distal end of said sleeve and said bone tunnel and into said bone block, and said element comprises a rod.

10 5. The method of claim 2 wherein said element is selected from the group consisting of substantially rigid rods, medications, prosthetic materials and substitute tissue.

15 6. The method of claim 4 wherein said rods are formed of bio-absorbable material.

7. The method of claim 6 wherein said bioabsorbable material is selected from the group consisting of polylactic acid, polyglycolic acid and polydiaxanone.

20 8. The method of claim 4 wherein said rod is formed of a material selected from the group consisting of substantially rigid metals, plastics, and ceramics.

25 9. The method of claim 4 wherein said second trocar penetrates through said bone block and back into said bone.

10. The method of claim 4 wherein said second trocar does not penetrate all the way through said bone block.

11. The method of claim 4 wherein said bone comprises a reduced fracture, said element comprises a rigid rod, and said trocar and trocar sleeve combination extends across said reduced bone fracture.


- 5 12. A method for deploying an element in bone, substantially as hereinbefore described with reference to the accompanying drawings.

Dated: 8 May 2003

FREEHILLS CARTER SMITH BEADLE

Patent Attorneys for the Applicant:

ETHICON, INC.






FIG. 1




FIG. 2





FIG. 3






FIG. 5





FIG. 6

FIG. 8








FIG. 10



24 300 1347



11/48

FIG. 11

24 300 1047




FIG. 12




FIG. 13




FIG. 14

24 399 1047




FIG. 15




FIG. 16




FIG. 17

24 300 1047




FIG. 18

14/48




FIG. 19





FIG. 20

FIG. 21



17/48




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 26



23/48

FIG. 27




FIG. 28





FIG. 29

FIG. 30






FIG. 31




FIG. 32




FIG. 33




FIG. 35






FIG. 36

24 200 10747

FIG. 37




31/48



32/48

FIG. 38

FIG. 39



200 300 400 500




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45

36/48




FIG. 46




FIG. 47




FIG. 48






FIG. 49



38/48




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63

24 399 1347




FIG. 64







FIG. 65



24 389 1347




FIG. 69

46/48




FIG. 70




FIG. 71

24 300 13047




FIG. 72




FIG. 73

200 100 50




FIG. 74