



US009248309B2

(12) **United States Patent**  
**Pugh et al.**

(10) **Patent No.:** **US 9,248,309 B2**  
(45) **Date of Patent:** **Feb. 2, 2016**

(54) **LIGHT THERAPY SYSTEM INCLUDING SPECTACLE FRAMES AND CONTACT LENSES**

(58) **Field of Classification Search**  
CPC ..... A61N 5/06; A61N 2005/06  
See application file for complete search history.

(75) Inventors: **Randall B. Pugh**, Jacksonville, FL (US);  
**William Chester Neeley**, Melbourne, FL (US);  
**Robertson Towart**, Cove (GB);  
**Mario Jozef Joanna Peeters**, Meerhout (BE);  
**Wilhelmus Drinkenburg**, Molenschot (NL);  
**Aleksandar Miletic**, Moscow (RU)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,578,850	A *	5/1971	Grant	.....	351/159.02
5,137,018	A	8/1992	ChupriKov et al.		
5,757,458	A *	5/1998	Miller et al.	.....	351/159.02
6,235,046	B1 *	5/2001	Gerdt	.....	607/88
6,350,275	B1 *	2/2002	Vreman et al.	.....	607/88
2004/0225340	A1 *	11/2004	Evans	.....	607/88
2005/0237479	A1 *	10/2005	Rose	.....	351/123
2005/0240247	A1 *	10/2005	McIlroy et al.	.....	607/88
2011/0019148	A1	1/2011	Portney		

(73) Assignee: **Johnson & Johnson Vision Care, Inc.**, Jacksonville, FL (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 331 days.

FOREIGN PATENT DOCUMENTS

WO	WO 9747993	A1	12/1997
WO	WO 2006099413	A2	9/2006

(21) Appl. No.: **13/362,264**

OTHER PUBLICATIONS

(22) Filed: **Jan. 31, 2012**

International Search Report for PCT PCT/US2012/023672 Date of Mailing Jun. 1, 2012.

(65) **Prior Publication Data**

US 2012/0215291 A1 Aug. 23, 2012

\* cited by examiner

(51) **Int. Cl.**  
**A61N 5/06** (2006.01)  
**A61M 21/02** (2006.01)  
**G02C 7/04** (2006.01)  
**G02C 11/04** (2006.01)  
**A61M 21/00** (2006.01)

*Primary Examiner* — Lynsey Crandall

(52) **U.S. Cl.**  
CPC ..... **A61N 5/0618** (2013.01); **A61M 21/02** (2013.01); **G02C 7/04** (2013.01); **G02C 11/04** (2013.01); **A61M 2021/0044** (2013.01); **A61N 2005/063** (2013.01); **A61N 2005/0648** (2013.01)

(57) **ABSTRACT**

The present invention provides for eyeglasses used together with contact lenses to deliver light therapy to the wearer. The eyeglass lenses or frames feature an embedded light source in logical and electrical communication with power, sensors, processors, and other components contained within the eyeglasses. The eyeglass lenses or frames project light into complimentary contact lenses which refract, diffract or reflect light into the wearer's eyes.

**8 Claims, 11 Drawing Sheets**




FIG. 1







FIG. 2



**FIG. 3**





**FIG. 4**




FIG. 5




FIG. 6

FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



1

# LIGHT THERAPY SYSTEM INCLUDING SPECTACLE FRAMES AND CONTACT LENSES

## RELATED APPLICATIONS

This application claims priority to U.S. Provisional Patent Application Ser. No. 61/439,401 filed Feb. 4, 2011; the contents of which are relied upon and incorporated by reference.

## FIELD OF USE

This invention describes a light therapy delivery mechanism for treatment of seasonal affective disorder (SAD) and other purposes. More specifically, in some embodiments, the invention provides eyeglasses or contact lenses or both including features for intelligent delivery of light therapy.

## BACKGROUND

Seasonal affective disorder (SAD) is a well-established mood disorder wherein sufferers experience depressive symptoms in a certain season of the year, most frequently during winter months. Those affected by SAD often have normal mental health during most of the year. Symptoms of SAD may include, but are not limited to, excessive sleeping, lack of energy, craving carbohydrates, difficulty concentrating, and withdrawal from social activities. The symptoms result in feelings of depression, hopelessness, pessimism, and lack of pleasure.

Seasonal mood variations are believed to be related to changes in exposure to light. Geographic areas, such as the Arctic region, that experience fewer daylight hours, lower sunlight intensity, or significant periods of overcast skies exhibit a greater incidence of SAD. Variations in prevalence of SAD within the adult population are evident within the United States, ranging from low rates in Florida and other sunny states to notably higher rates in Alaska, New Hampshire and other northern or overcast areas.

Light therapy has been researched and established as a prominent and effective treatment for classic, or winter-based, seasonal affective disorder. Light therapy employs a device which emits significantly more lumens than a standard incandescent lamp. Common implementations include the preferred bright white full spectrum light at 10,000 lux, or optionally blue light at a wavelength of 480 nm at 2,500 lux, or green light at a wavelength of 500 nm at 350 lux. Light therapy normally requires a patient to sit with their eyes open at a prescribed distance from the light source for thirty to sixty minutes each day. This seasonal treatment is maintained for several weeks until the patient experiences frequent exposure to natural light. A majority of patients find the therapy inconvenient and a considerable percentage, in some studies up to 19%, therefore stop treatment. New methods and approaches are therefore desirable to deliver light therapy in a more convenient, continuous, and intelligent manner.

## SUMMARY

Accordingly, the present invention includes eyeglasses capable of delivering light therapy to the wearer. The eyeglass lenses or frames feature an embedded light source in logical and electrical communication with power, sensors, processors, and other components contained within the temple of the eyeglasses.

2

In addition, in some embodiments, eyeglass lenses or frames project light into complimentary contact lenses which refract or diffract the light into the wearer's eyes.

In still another aspect, in some embodiments, spectacle frames provide sensors and power which are in wireless communication with contact lenses containing a light source for the light therapy.

Finally, contact lenses may include embedded light sources as well as supporting electronics. Eyeglasses are not included in this embodiment.

## DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a back view of eyeglasses with light sources embedded in the lenses and with supporting electronics contained within the temple according to some embodiments of the present invention.

FIG. 2 illustrates a front view of eyeglasses with light sources embedded in the lenses according to some embodiments of the present invention.

FIG. 3 illustrates a close-up view of an eyeglass lens with embedded light sources according to some embodiments of the present invention.

FIG. 4 illustrates a close-up view of an eyeglass lens with embedded light sources mounted in spectacle frames according to some embodiments of the present invention.

FIG. 5 illustrates a portion of an eyeglass temple piece housing supporting electronics according to some embodiments of the present invention.

FIG. 6 illustrates a portion of an eyeglass temple piece opened to show supporting electronics according to some embodiments of the present invention.

FIG. 7 illustrates one side of supporting electronics from within an eyeglass temple piece according to some embodiments of the present invention.

FIG. 8 illustrates a second side of supporting electronics from within an eyeglass temple piece according to some embodiments of the present invention.

FIG. 9 illustrates a bottom view of eyeglasses with light sources embedded in the frame according to some embodiments of the present invention.

FIG. 10 illustrates a cross-section view of an eyeglass lens with embedded light sources directing light into a complimentary contact lens according to some embodiments of the present invention.

FIG. 11 illustrates a cross-section view of eyeglasses with supporting electronics in wireless communication with contact lenses containing light sources according to some embodiments of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

The present invention includes methods and apparatus for delivering light therapy using eyeglasses with embedded light sources. In addition, the present invention includes delivering light therapy using a combination of eyeglasses and complimentary contact lenses. The present invention also encompasses delivering light therapy using only contact lenses with embedded light sources.

In the following sections detailed descriptions of embodiments of the invention will be given. The description of both preferred and alternative embodiments are exemplary embodiments only, and it is understood that to those skilled in the art that variations, modifications and alterations may be apparent. It is therefore to be understood that said exemplary embodiments do not limit the scope of the underlying invention.

In this description and claims directed to the presented invention, various terms may be used for which the following definitions will apply:

Complimentary contact lens: as used herein refers to contact lenses and eyeglasses with special features used together to deliver light therapy.

Contact lens: refers to any ophthalmic device that resides in or on the eye. These devices can provide optical correction or may be cosmetic. For example, the term lens can refer to a contact lens, intraocular lens, overlay lens, ocular insert, optical insert or other similar device through which vision is corrected or modified, or through which eye physiology is cosmetically enhanced (e.g. iris color) without impeding vision. In some embodiments, the preferred lenses of the invention are soft contact lenses made from silicone elastomers or hydrogels, which include but are not limited to silicone hydrogels, and fluorohydrogels.

Intelligent light therapy: as used herein refers to a method of delivering light therapy whereby a processor evaluates various data and, based on data analysis, dynamically makes compensating adjustments to a programmed light therapy schedule. Adjusting light therapy based on the user's exposure to ambient light is one example of intelligent light therapy.

Light therapy: as used herein refers to exposure to specific wavelengths of light, controlled with various devices, and administered for a specified amount of time, at a specified intensity, and, in some cases, at a specified time of day.

Lux: as used herein refers to units of illumination in the International System of Units (SI). Lux provides a measure of luminous power per area. One lux is the amount of illumination provided when one lumen is evenly distributed over an area of one square meter. This is also equivalent to the illumination that would exist on a surface all points of which are one meter from a point source of one international candle. One lux is equal to 0.0929 foot-candle.

Optical Zone: as used herein refers to an area of an ophthalmic lens through which a wearer of the ophthalmic lens sees.

Programmed light therapy schedule: as used herein refers to a set of automated instructions that controls light therapy timing, duration and intensity based on variables such as dates, geographic region, and severity of a user's seasonal affective disorder symptoms. A programmed light therapy schedule may be set by an eye care professional, a medical doctor, or a user.

Seasonal Affective Disorder (SAD): as used herein refers to a mood disorder that occurs during seasons when exposure to sunlight is limited, characterized by symptoms of depression and relieved by the arrival of spring or by light therapy. A recurrent state of depression, usually experienced by people in winter, thought to be related to lack of sunlight.

Referring now to FIG. 1, a back view of spectacle frames **101** with light sources **102** embedded in lenses **103** is illustrated. Light sources **102** may also be mounted on the surface of lenses **103**. Light sources **102** may include light-emitting diodes (LEDs) or other lights which emit blue light at wavelengths of 450 to 500 nanometers, most preferably at 470 to 480 nanometers, and at 2,000 to 3,000 lux. Alternatively, LEDs or other lights may emit green light at wavelengths of 475 to 525 nanometers, most preferably at 490 to 510 nanometers, and at 300 to 400 lux. Additionally, the light source **102** may be secured in any other manner which allows

In another embodiment, a single light source may be piped to one or more locations within an eyeglass lens **103** or

eyeglass frame **101** to provide illumination. Light pipes may include, for example, fiber optic pathways.

An example of illuminated light sources is illustrated at **104**. A light source **102** provides illumination toward a wearer's eyes such that an illumination is not obvious to an observer.

In another embodiment, light sources **102** are positioned such that light is directed into a lens **103**. A lens **103** may include light scattering properties in areas where light is specifically directed or light scattering properties throughout a lens **103**. Light scattering areas may include diffractive properties, refractive properties, reflective properties or any combination of diffractive, refractive and reflective properties. Light scattering areas act to diffuse light, achieving presentation of a soft glow rather than a glaring ray before a user's eye. In some preferred embodiments, light scattering areas may form a ring within a perimeter area of an eyeglass lens **103** and may include an internal barrier between a light scattering area and an optical zone in a central portion of a lens **103**. An internal barrier prevents light intended for light therapy from being dispersed into an optical zone of a lens **103**, minimizing the effect of light therapy luminescence on normal vision. In still other embodiments, an entire lens **103** includes light scattering properties designed such that it disperses only light of wavelengths emitted by embedded light sources **102**. This embodiment supports maximum dispersion of light wavelengths intended for light therapy while not causing dispersion of light wavelengths that would affect normal vision. A lens **103** may include a coating which shields light therapy luminescence from being readily noticed by an observer while not diminishing a user's light therapy or vision.

In the present embodiment, light sources **102** are connected to one another via conductive paths **105**. Conductive paths **105** may be wires embedded within a lens **103**, or may be a conductive material, such as, for example, gold, copper, silver or other metal or conductive fiber applied to a surface of a lens **103** via pad printing, sputter coating, vapor deposition or other known method. Conductive paths **105** are in electrical and logical communication with supporting electronics contained within one or both temple pieces **109**. In some embodiments, supporting electronics are miniaturized such that they may be contained in other areas of eyeglasses, such as, for example, in areas near a hinge **107**, within a frame above a lens **108**, within a bridge **110**, within an earpiece **111**, or other area.

One or more light sensors **106** are used to detect ambient white light, blue light or green light. Light sensors **106** may be located within an eyeglass frame **101** near a hinge **107**, within a frame above a lens **108**, within a temple piece **109**, within a bridge **110**, or other appropriate area where a sensor **106** will not be obstructed, such as by hair. A light sensor **106** is in electrical and logical communication with supporting electronics contained within one or both temple pieces **109** or other area of eyeglasses.

In some embodiments, a user control element **112**, such as a switch or button, is provided to allow a user to adjust timing, duration and intensity of light therapy. One or more user control elements **112** may be present in temple pieces **109** or other areas of eyeglasses, such as, for example, in areas near a hinge **107**, within a frame above a lens **108**, within a bridge **110**, within an earpiece **111**, or other area. Some embodiments provide for a basic operational state, wherein light therapy is controlled manually by a user starting and stopping therapy at appropriate times.

According to the present embodiment, a programmed light therapy schedule may, for example, automatically adjust light

5

therapy timing, duration and intensity based on variables such as dates, geographic region, and severity of a user's seasonal affective disorder symptoms. A programmed light therapy schedule may be set by an eye care professional, a medical doctor, or a user. During programmed light therapy, it may be desirable for a user to adjust light intensity based on an activity, such as, for example, decreasing light intensity when reading, working on a computer, or driving. Conversely, it may be desirable to increase light intensity during work breaks, lunch break, or other less visually active times. In some embodiments, intelligent light therapy is delivered when a processor evaluates manual changes to a programmed light therapy schedule and provides compensating adjustments in duration and intensity of treatment. In still other embodiments, intelligent light therapy is achieved when data from light sensors **106** is analyzed by a processor and a programmed light therapy schedule is dynamically adjusted based on a wearer's exposure to ambient light.

In another embodiment of the present invention, a user may manually adjust light therapy based on the results of blood testing for melatonin levels. Melatonin produced by the pineal gland is inhibited by light and increases with darkness. Higher levels of melatonin promote sleepiness and lethargy, symptoms of seasonal affective disorder. Analysis of the level of melatonin in a patient's blood may be used as a guide to increase or decrease light therapy.

In still other embodiments, a user may manually adjust light therapy to intentionally alter their sleep cycle. The use of light therapy for sleep cycle alteration may be valuable for persons working night shifts, for persons travelling to significantly different time zones, for military personnel preparing for night operations, and other uses. Additionally, light therapy initiated by the user upon awakening may be used to treat circadian rhythm disorders such as delayed sleep phase syndrome (DSPS) and non-24-hour sleep-wake syndrome.

Referring now to FIG. 2, a front view of spectacle frames **201** with light sources **202** embedded in lenses **203** is illustrated. Light sources **202** are connected to one another via conductive paths **204**.

Referring now to FIG. 3, illustrated is a close-up view of a single eyeglass lens **301** with embedded light sources **302** connected via conductive paths **303**. While the embodiment described in this application shows eight light sources **302** per lens **301**, other embodiments may include fewer or more light sources **302** per lens **301** and may include light sources **302** in varying locations and patterns within a lens **301**. To provide a sense of scale, a lens **301** is shown placed over a standard U.S. quarter dollar coin **304**. Not shown in this diagram is a mechanism for providing electrical communication between the light sources **302** and supporting electronics. Electrical communication may be provided, for example, via a conductive contact between a source located in a temple of a pair of eyeglasses, via a conductive wire, a conductive ribbon wire, or via wireless modes, such as inductance. Inductance may be accomplished, for example, via an antenna located in the lens or the lens frame and a power source transmitting power from a temple piece or other proximate location to the antenna.

Referring now to FIG. 4, a close-up view of a single eyeglass lens **401** with embedded light sources **402** connected via conductive paths **403** is illustrated mounted into an eyeglass frame **404**.

Referring now to FIG. 5, illustrated is a close-up view of a portion of an eyeglass temple piece **501** which houses supporting electronics. The temple piece **501** is not fully closed as evidenced by a gap **502**. A USB connector **503** is used for electrical connection, such as, for example, charging batteries within a temple piece **501**. A USB connector **503** is also used

6

for logical communication, such as, for example, loading a user-specific programmed light therapy schedule or offloading usage and sensor data stored by supporting electronics. A hinge area **504** is visible, at which point a temple piece **501** connects to an eyeglass frame. For scale purposes, a temple piece **501** is shown adjacent to a standard U.S. quarter dollar coin **505**.

Referring now to FIG. 6, a close-up of an eyeglass temple piece **601** is now illustrated with a top half of a supporting electronics casing **602** removed. A circuit board containing supporting electronics **603** is displayed including batteries **604**, a processor **605** and a USB connector **606**. Wiring **607** provides logical and electrical communication between supporting electronics **603** and other components such as light sources and light sensors. A hinge area **608** is visible, where a temple piece **601** connects to an eyeglass frame. To provide a sense of scale, a temple piece **601** is shown adjacent to a standard U.S. quarter dollar coin **609**.

Referring now to FIG. 7, a top down view of a first side of a circuit board containing supporting electronics **701** is illustrated. The circuit board **701** is shown removed from a casing in which it was depicted in FIGS. 5 and 6. A circuit board **701** includes batteries **702**, a processor **703**, power terminals **704**, and a USB connector **705**. Wiring **706** attached to power terminals **704** provides logical and electrical communication between supporting electronics on a circuit board **701** and other components such as light sources and light sensors. A processor **703** may be used, for example, to run programmed light therapy schedules stored in memory, to analyze light sensor data and determine a unique light therapy schedule based on the wearer's exposure to ambient light, to evaluate manual changes to a programmed light therapy schedule and provide compensating adjustments, and to analyze light source and light sensor data to detect device failures. Power terminals **704** enable connection of wiring **706**, allowing logical and electrical communication between supporting electronics on a circuit board **701** and other components such as light sources and light sensors. To provide a sense of scale, a circuit board **701** is shown adjacent to a standard U.S. quarter dollar coin **707**.

Referring now to FIG. 8, illustrated is a top down view of a second side of a circuit board containing supporting electronics **801**. The circuit board **801** is shown removed from a casing in which it was depicted in FIGS. 5 and 6. A circuit board **801** includes memory **802**, capacitors **803**, and power terminals **804**. The USB connector of FIG. 7 (**705**) is seen in FIG. 8 at **805**. For scale, a circuit board **801** is shown adjacent to a standard U.S. quarter dollar coin **806**. Memory **802** may be used, by way of non-limiting example, to store pre-programmed light therapy schedules, to store data captured by light sensors, to store actual light therapy dates, times, durations and intensities, and to store data related to light source and light sensor operation in order to detect device failures.

Referring now to FIG. 9, illustrated is a bottom view of an eyeglass frame **901** with light sources **902** embedded in the eyeglass frame **901** above lenses **903**. Light sources **902** may be embedded within an eyeglass frame **901**, or may be mounted on a surface of an eyeglass frame **901**. Light sources **902** are connected to one another by conductive paths, not illustrated in FIG. 9. Conductive paths may be wires embedded within an eyeglass frame **901**, or may be a conductive material, such as, for example, gold, silver, copper or other metallic material or conductive fiber applied to the surface of an eyeglass frame **901** via pad printing, sputter coating, vapor deposition or other known method. Conductive paths allow light sources **902** to be in electrical and logical communication with supporting electronics housed within one or both

temple pieces **904**. In some embodiments, supporting electronics are miniaturized such that they may be contained in other eyeglass areas, such as, for example, in areas near a hinge **905**, within a frame above a lens **901**, within a bridge **906**, within an earpiece (not shown in FIG. 9), or other area. Light sources **902** are positioned so that light is directed onto lenses **903**. Lenses **903** may include light scattering properties in areas where light is specifically directed or light scattering properties throughout the lens. Light scattering areas may include diffractive properties, refractive properties, reflective properties or any combination of diffractive, refractive and reflective properties. Light scattering areas act to diffuse light, achieving presentation of a soft glow rather than a glaring ray before a user's eye. Lenses **903** may include a coating which shields light therapy illumination from being readily noticed by an observer while not affecting a user's light therapy or vision.

Referring now to FIG. 10, an embodiment including a complimentary contact lens is illustrated. A cross-section view **1000** includes an eyeglass lens **1001** with embedded light sources **1002** directing light **1003** into light scattering areas **1004** of a complimentary contact lens **1005**. A light scattering area **1004** results in light **1006** being dispersed across a cornea **1007** of an eye **1008**. A light scattering area **1004** may include diffractive properties, refractive properties, reflective properties or any combination of diffractive, refractive and reflective properties.

In some embodiments, a cross-section view **1000** may be a top-down view, wherein one or more embedded light sources **1002** are placed near the sides of an eyeglass lens **1001**. In other embodiments, a cross-section view **1000** may be a side view, such that one or more embedded light sources **1002** are placed near the top and bottom of an eyeglass lens **1001**. In still other embodiments, embedded light sources **1002** may be embedded in or mounted on an eyeglass frame rather than an eyeglass lens **1001**. Embedded light sources **1002** include light-emitting diodes (LEDs) or other light sources **1002** emitting light **1003** for light therapy. Light sources **1002** may include light-emitting diodes (LEDs) or other lights which emit blue light at wavelengths of 450 to 500 nanometers, most preferably at 470 to 480 nanometers, and at 2,000 to 3,000 lux. Alternatively, LEDs or other lights may emit green light at wavelengths of 475 to 525 nanometers, most preferably at 490 to 510 nanometers, and at 300 to 400 lux. Another embodiment includes a single light source from which light is piped to one or more locations within an eyeglass lens **1001** or eyeglass frame to provide illumination.

Supporting electronics, not shown, are contained in an eyeglass frame and include components such as, for example, light sensors, batteries, capacitors, memory, processors, and a USB connector. Supporting electronics are in logical and electrical communication with light sources **1002**. Electrical communication may be provided, for example, via a conductive contact between a source located in a temple of a pair of eyeglasses, via a conductive wire, a conductive ribbon wire, or via wireless modes, such as inductance. Inductance may be accomplished, for example, via an antenna located in the lens or the lens frame and a power source transmitting power from a temple piece or other proximate location to the antenna.

In some embodiments, light scattering areas **1004** of a complimentary contact lens **1005** form a ring within a perimeter area of a complimentary contact lens **1005** such that directed light **1003** need not strike a limited target area. The orientation of a complimentary contact lens **1005** on an eye **1008** relative to light sources **1002** within an eyeglass lens **1001** is therefore inconsequential when light **1003** is directed

toward a light scattering area **1004** continuously present around a perimeter area of a complimentary contact lens **1005**.

In some preferred embodiments, a complimentary contact lens **1005** may include an internal barrier between a light scattering area **1004** and an optical zone in a central portion of a lens. An internal barrier prevents light **1003** intended for light therapy from being dispersed into an optical zone of a complimentary contact lens **1005**. In this way, light **1003** intended for light therapy is only dispersed around a perimeter of a cornea **1007**, minimizing its effect on normal vision.

In still other embodiments, an entire complimentary contact lens **1005** includes light scattering properties such as diffraction, refraction and reflection. Light scattering properties are designed such that they disperse only light **1003** of wavelengths emitted by embedded light sources **1002**. This embodiment supports maximum dispersion of light **1003** wavelengths intended for light therapy within an eye **1008** while not causing dispersion of light wavelengths that would affect normal vision.

Referring now to FIG. 11, an embodiment is illustrated including an eyeglass frame and a complimentary contact lens. A cross-section view **1100** includes an eyeglass frame **1101** containing supporting electronics **1102**. Supporting electronics **1102** may include components such as, for example, light sensors, batteries, capacitors, memory, processors, and a USB connector. Supporting electronics **1102** are in wireless communication **1103** with a complimentary contact lens **1105** containing embedded light sources **1104** directing light **1106** onto a cornea **1107** of an eye **1108**. Supporting electronics **1102** may be placed in various locations embedded in or mounted on an eyeglass frame **1101**. In other embodiments, supporting electronics **1102** may be included in jewelry, hats, clothing, or other items worn by a user such that light sensors detect ambient light experienced by the user and supporting electronics **1102** are near a complimentary contact lens **1105** for purposes of wireless communication. Wireless modes of communication may include, for example, inductance. Inductance may be accomplished via an antenna located in a complimentary contact lens **1105** and a power source transmitting power from an eyeglass frame **1101**, jewelry, clothing, or other item proximate to the antenna.

In some embodiments of the present invention, a cross-section view **1100** may be a top-down view, wherein supporting electronics **1102** are placed near the sides of an eyeglass frame **1101**. In other embodiments, a cross-section view **1100** may be a side view, such that supporting electronics **1102** are placed near the top and bottom of a side of an eyeglass frame **1101**. A number of embedded light sources **1104** and an arrangement of embedded light sources **1104** around a perimeter of a complimentary contact lens **1105** may vary. Embedded light sources **1104** include light-emitting diodes (LEDs) or other light sources **1104** emitting light **1106** for light therapy. Light sources **1104** may include light-emitting diodes (LEDs) or other lights which emit blue light at wavelengths of 450 to 500 nanometers, most preferably at 470 to 480 nanometers, and at 2,000 to 3,000 lux. Alternatively, LEDs or other lights may emit green light at wavelengths of 475 to 525 nanometers, most preferably at 490 to 510 nanometers, and at 300 to 400 lux. Another embodiment includes a single light source from which light is piped to one or more locations within a complimentary contact lens **1105** to provide illumination.

In some embodiments, light sources **1104** may direct light **1106** into an interior portion of a complimentary contact lens **1105** in which the light sources **1104** are embedded. Light **1106** may be directed into a light scattering area, not depicted,

9

including diffractive properties, refractive properties, reflective properties, or any combination of diffractive, refractive and reflective properties. A light scattering area may form a ring within a perimeter area of a complimentary contact lens **1105**. Light **1106** striking a light scattering area causes a generally broad dispersion of light **1106** onto a cornea **1107** of an eye **1108**.

In some preferred embodiments, a complimentary contact lens **1105** may include an internal barrier between a light scattering area around a perimeter of a lens and an optical zone in a central portion of a lens. An internal barrier prevents light **1106** intended for light therapy from being dispersed into an optical zone of a complimentary contact lens **1105**. In this way, light **1106** intended for light therapy is only dispersed around a perimeter of a cornea **1107**, minimizing its effect on normal vision.

In still other embodiments, an entire complimentary contact lens **1105** includes light scattering properties such as diffraction, refraction or reflection. Light scattering properties are designed such that they disperse only light **1106** of wavelengths emitted by embedded light sources **1104**. This embodiment supports maximum dispersion of light **1106** wavelengths intended for light therapy within an eye **1108** while not causing dispersion of light wavelengths that would distort vision.

#### CONCLUSION

The present invention, as described above and as further defined by the claims below, provides methods and apparatus for delivering light therapy using eyeglasses with embedded light sources, using eyeglasses and complimentary contact lenses, or using contact lenses with embedded light sources.

What is claimed is:

1. A system for administering light therapy, the system comprising:
  - a spectacle frame sized for wearing on a human being and configured to secure one or more optical lenses;

10

a contact lens having an optic zone and a perimeter area, the contact lens includes light scattering areas in the perimeter area configured to diffuse light passing there-through; and

one or more light sources fixedly mounted to at least one of the spectacle frame or the one or more optical lenses, the one or more light sources configured to direct light onto the light scattering areas in the perimeter area of the contact lens.

2. The system for administering light therapy according to claim 1, wherein the one or more light sources comprises one or more light emitting diodes.

3. The system for administering light therapy according to claim 1, wherein the one or more light sources are configured to emit blue light at wavelengths of 470 to 480 nanometers at between 2000 and 3000 lux.

4. The system for administering light therapy according to claim 1, wherein the one or more light sources are configured to emit green light at wavelengths of 490 to 510 nanometers at between 300 to 400 lux.

5. The system for administering light therapy according to claim 1, further comprising one or more light sources mounted to the spectacle frame.

6. The system for administering light therapy according to claim 1, wherein the light scattering areas only disperse light of wavelengths emitted by the one or more light sources.

7. The system for administering light therapy according to claim 1, wherein the contact lens further comprises, an internal barrier for preventing light from the one or more light sources from being dispersed into the optical zone of the contact lens.

8. The system for administering light therapy according to claim 7, wherein light from the one or more light sources is dispersed by the contact lens into an area around the perimeter of a cornea.

\* \* \* \* \*