



US009068356B2

(12) **United States Patent**
Thiers et al.

(10) **Patent No.:** US 9,068,356 B2
(45) **Date of Patent:** *Jun. 30, 2015

(54) **FLOOR COVERING**(71) Applicant: **FLOORING INDUSTRIES LIMITED, SARL**, Bertrange (LU)(72) Inventors: **Bernard Thiers, Eine (BE); Mark Cappelle, Staden (BE)**(73) Assignee: **FLOORING INDUSTRIES LIMITED, SARL**, Bertrange (LU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/560,704**(22) Filed: **Dec. 4, 2014**(65) **Prior Publication Data**

US 2015/0082732 A1 Mar. 26, 2015

Related U.S. Application Data

(60) Continuation of application No. 14/320,887, filed on Jul. 1, 2014, now Pat. No. 8,904,729, which is a continuation of application No. 14/093,729, filed on Dec. 2, 2013, now Pat. No. 8,793,958, which is a (Continued)

(30) **Foreign Application Priority Data**

Jun. 20, 2000 (BE) 2000/0397

(51) **Int. Cl.****E04B 2/00** (2006.01)
E04F 15/02 (2006.01)(52) **U.S. Cl.**CPC **E04F 15/02038** (2013.01); **E04F 2201/023** (2013.01); **E04F 2201/0153** (2013.01); **E04F 15/02** (2013.01); **E04F 2201/0161** (2013.01); **E04F 2201/0115** (2013.01)(58) **Field of Classification Search**CPC E04F 15/02; E04F 15/02038; E04F 2201/0115; E04F 2201/026; E04F 2201/0161; E04F 2201/0153
USPC 52/592.1, 390, 392, 578, 586.1, 589.1, 52/591.1, 590.2, 590.1, 572, 570, 375, 52/588.1; 403/298, 375, 381

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

208,036 A 9/1878 Robley
213,740 A 4/1879 Conner

(Continued)

FOREIGN PATENT DOCUMENTS

AT 000 112 U2 2/1995
AU 13098/83 A 10/1983

(Continued)

OTHER PUBLICATIONS

"Key Contenders in the MDF Stakes", Wood Based Panels International, 3 pages, Sep. 1994.

(Continued)


Primary Examiner — Chi Q Nguyen

(74) Attorney, Agent, or Firm — Workman Nydegger

(57) **ABSTRACT**

Hard panels formed from a wood-based material and having a decorative layer for floor coverings are provided, at least on two opposite edges, with coupling devices made in one piece with the panels wherein similar panels may be coupled together to form a floor covering, wherein these coupling devices provide for an interlocking in a direction perpendicular to the plane of coupled panels, as well as in a direction perpendicular to the edges concerned and parallel to the plane of coupled panels. These coupling devices are constituted of a tongue and a groove. The top side of the tongue has a protrusion that cooperates with a meshing recess located in the lower side of the upper lip of the groove of the coupling devices, and a portion extending generally parallel with the plane of the panel to form a contact surface cooperating with the lower side of the upper lip of the groove.

30 Claims, 10 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/893,556, filed on May 14, 2013, now Pat. No. 8,631,625, which is a continuation of application No. 12/821,604, filed on Jun. 23, 2010, now Pat. No. 8,438,814, which is a continuation of application No. 11/979,317, filed on Nov. 1, 2007, now Pat. No. 7,779,597, which is a division of application No. 10/890,456, filed on Jul. 14, 2004, now Pat. No. 7,343,717, which is a division of application No. 09/878,206, filed on Jun. 12, 2001, now Pat. No. 6,772,568.

(56)

References Cited**U.S. PATENT DOCUMENTS**

308,313 A	11/1884	Gerike	2,004,193 A	6/1935	Cherry
662,458 A	11/1900	Nagel	2,015,813 A	10/1935	Nielsen
713,577 A	11/1902	Wickham	2,027,292 A	1/1936	Rockwell
714,987 A	12/1902	Wolfe	2,044,216 A	6/1936	Klages
752,694 A	2/1904	Lund	2,045,067 A	6/1936	Bruce
753,791 A	3/1904	Fulghum	2,049,571 A	8/1936	Schuck
769,355 A	9/1904	Platow	2,100,238 A	11/1937	Burgess
832,003 A	9/1906	Torrence	RE20,816 E	8/1938	Haase
877,639 A	1/1908	Galbraith	2,126,956 A	8/1938	Gilbert
890,436 A	6/1908	Momberg	2,138,085 A	11/1938	Birtles
898,381 A	9/1908	Mattison	2,141,708 A	12/1938	Elmendorf, III
1,078,776 A	11/1913	Dunton	2,142,305 A	1/1939	Davis
1,097,986 A	5/1914	Moritz	2,199,938 A	5/1940	Kloote
1,124,228 A	1/1915	Houston	2,222,137 A	11/1940	Bruce
1,137,197 A	4/1915	Ellis	2,226,540 A	12/1940	Boettcher
1,140,958 A	5/1915	Cowan	2,245,497 A	6/1941	Potchen
1,201,285 A	10/1916	Gray	2,253,943 A	8/1941	Rice
1,319,286 A	10/1919	Johnson et al.	2,261,897 A	11/1941	Adams
1,371,856 A	3/1921	Cade	2,263,930 A	11/1941	Pasquier
1,407,679 A	2/1922	Ruthrauff	2,266,464 A	12/1941	Kraft
1,411,415 A	4/1922	Cooley	2,276,071 A	3/1942	Scull
1,436,858 A	11/1922	Burhen	2,280,071 A	4/1942	Hamilton
1,454,250 A	5/1923	Parsons	2,282,559 A	5/1942	Byers
1,468,288 A	9/1923	Een	2,324,628 A	7/1943	Kahr
1,477,813 A	12/1923	Daniels et al.	2,398,632 A	4/1946	Frost et al.
1,510,924 A	10/1924	Daniels et al.	2,430,200 A	11/1947	Wilson
1,540,128 A	6/1925	Houston	2,441,364 A	5/1948	Maynard
1,575,821 A	3/1926	Daniels	2,491,498 A	12/1949	Kahr
1,602,256 A	10/1926	Sellin	2,644,552 A	7/1953	MacDonald
1,602,267 A	10/1926	Karwisch	2,729,584 A	1/1956	Foster
1,615,096 A	1/1927	Meyers	2,740,167 A	4/1956	Rowley
1,622,103 A	3/1927	Fulton	2,780,253 A	2/1957	Joa
1,622,104 A	3/1927	Fulton	2,805,852 A	9/1957	Malm
1,637,634 A	8/1927	Carter	2,808,624 A	10/1957	Sullivan
1,644,710 A	10/1927	Crooks	2,823,433 A	2/1958	Kendall
1,660,480 A	2/1928	Daniels	2,831,223 A	4/1958	De Shazor, Jr.
1,706,924 A	3/1929	Kane	2,839,790 A	6/1958	Collings
1,714,738 A	5/1929	Smith	2,863,185 A	12/1958	Riedi
1,718,702 A	6/1929	Pfiester	2,865,058 A	12/1958	Andersson et al.
1,734,826 A	11/1929	Pick	2,875,117 A	2/1959	Potchen et al.
1,764,331 A	6/1930	Moratz	2,878,530 A	3/1959	Lindstrom
1,776,188 A	9/1930	Langbaum	2,894,292 A	7/1959	Gramelspacher
1,778,069 A	10/1930	Fetz	2,914,815 A	12/1959	Alexander
1,787,027 A	12/1930	Wasleff	2,947,040 A	8/1960	Schultz
1,801,093 A	4/1931	Larkins	2,952,341 A	9/1960	Weiler
1,823,039 A	9/1931	Gruner	2,974,692 A	3/1961	Bolenbach
1,843,024 A	1/1932	Fetz	3,045,294 A	7/1962	Livezey, Jr.
1,854,396 A	4/1932	Davis	3,090,082 A	5/1963	Baumann
1,859,667 A	5/1932	Gruner	3,100,556 A	8/1963	De Ridder
1,864,774 A	6/1932	Storm	3,125,138 A	3/1964	Bolenbach
1,898,364 A	2/1933	Gynn	3,128,851 A	4/1964	Deridder et al.
1,906,411 A	5/1933	Potvin	3,141,392 A	7/1964	Schneider et al.
1,913,342 A	6/1933	Schaffert	3,162,906 A	12/1964	Dudley
1,929,871 A	10/1933	Jones	3,182,769 A	5/1965	Ridder
1,940,377 A	12/1933	Storm	3,199,258 A	8/1965	Jentoft et al.
1,953,306 A	4/1934	Moratz	3,200,553 A	8/1965	Frashour et al.
1,978,075 A	10/1934	Butterworth	3,203,149 A	8/1965	Soddy
1,986,739 A	1/1935	Mitte	3,204,380 A	9/1965	Smith et al.
1,988,201 A	1/1935	Hall	3,253,377 A	5/1966	Schakel
1,991,701 A	2/1935	Roman	3,267,630 A	8/1966	Omholt
			3,282,010 A	11/1966	King, Jr.
			3,301,147 A	1/1967	Clayton et al.
			3,310,919 A	3/1967	Bue et al.
			3,313,072 A	4/1967	Cue
			3,339,329 A	9/1967	Berg
			3,347,048 A	10/1967	Brown et al.
			3,363,381 A	1/1968	Forrest
			3,363,382 A	1/1968	Forrest
			3,373,071 A	3/1968	Fuerst
			3,377,931 A	4/1968	Hilton
			3,385,182 A	5/1968	Harvey
			3,387,422 A	6/1968	Wanzer
			3,397,496 A	8/1968	Sohns
			3,444,660 A	5/1969	Feichter et al.
			3,449,879 A	6/1969	Bloom
			3,460,304 A	8/1969	Braeuninger et al.
			3,474,584 A	10/1969	Lynch
			3,479,784 A	11/1969	Massagli
			3,481,810 A	12/1969	Waite

(56)

References Cited

U.S. PATENT DOCUMENTS

3,488,828 A	1/1970	Gallagher	4,501,102 A	2/1985	Knowles
3,526,420 A	9/1970	Brancaleone	4,503,115 A	3/1985	Hemels et al.
3,535,844 A	10/1970	Glaros	4,517,147 A	5/1985	Taylor et al.
3,538,665 A	11/1970	Gohner	4,538,392 A	9/1985	Hamar et al.
3,538,819 A	11/1970	Gould, Jr.	4,561,233 A	12/1985	Harter et al.
3,548,559 A	12/1970	Levine	4,599,124 A	7/1986	Kelly et al.
3,553,919 A	1/1971	Omholt	4,599,841 A	7/1986	Haid
3,555,761 A	1/1971	Rosebrough	4,599,842 A	7/1986	Counihan
3,555,762 A	1/1971	Costanzo, Jr.	4,612,745 A	9/1986	Hovde
3,572,224 A	3/1971	Perry	4,640,437 A	2/1987	Weingartner
3,579,941 A	5/1971	Tibbals	4,641,469 A	2/1987	Wood
3,619,964 A	11/1971	Passaro et al.	4,643,237 A	2/1987	Rosa
3,627,362 A	12/1971	Brenneman	4,646,494 A	3/1987	Saarinen et al.
3,640,191 A	2/1972	Hendrich	4,653,242 A	3/1987	Ezard
3,657,852 A	4/1972	Worthington et al.	4,703,597 A	11/1987	Eggemar
3,665,666 A	5/1972	Delcroix	4,715,162 A	12/1987	Brightwell
3,667,153 A	6/1972	Christiansen	4,724,187 A	2/1988	Ungar et al.
3,687,773 A	8/1972	Wangborg	4,738,071 A	4/1988	Ezard
3,694,983 A	10/1972	Couquet	4,757,658 A	7/1988	Kaempen
3,696,575 A	10/1972	Armstrong	4,769,963 A	9/1988	Meyerson
3,714,747 A	2/1973	Curran	4,806,435 A	2/1989	Athey
3,720,027 A	3/1973	Christensen	4,819,932 A	4/1989	Trotter, Jr.
3,731,445 A	5/1973	Hoffmann et al.	4,831,806 A	5/1989	Niese et al.
3,740,914 A	6/1973	Diez	4,845,907 A	7/1989	Meek
3,742,672 A	7/1973	Schaeufele	4,905,442 A	3/1990	Daniels
3,745,726 A	7/1973	Thom	4,906,484 A	3/1990	Lambuth et al.
3,758,650 A	9/1973	Hurst	4,952,775 A	8/1990	Yokoyama et al.
3,759,007 A	9/1973	Thiele	4,953,335 A	9/1990	Kawaguchi et al.
3,760,544 A	9/1973	Hawes et al.	4,988,131 A	1/1991	Wilson et al.
3,760,548 A	9/1973	Sauer et al.	4,998,395 A	3/1991	Bezner
3,761,338 A	9/1973	Ungar et al.	4,998,396 A	3/1991	Palmersten
3,768,846 A	10/1973	Hensley et al.	5,029,425 A	7/1991	Bogataj
3,778,958 A	12/1973	Fowler	5,050,362 A	9/1991	Tal et al.
3,780,469 A	12/1973	Hancovsky	5,074,089 A	12/1991	Kemmer et al.
3,786,608 A	1/1974	Boettcher	5,086,599 A	2/1992	Meyerson
3,798,111 A	3/1974	Lane et al.	5,092,095 A	3/1992	Zadok et al.
3,807,113 A	4/1974	Turner	5,109,898 A	5/1992	Schacht
3,859,000 A	1/1975	Webster	5,113,632 A	5/1992	Hanson
3,884,328 A	5/1975	Williams	5,117,603 A	6/1992	Weintraub
3,902,293 A	9/1975	Witt et al.	5,138,812 A	8/1992	Palmersten
3,908,053 A	9/1975	Hettich	5,148,850 A	9/1992	Urbanick
3,921,312 A	11/1975	Fuller	5,155,952 A	10/1992	Herwegh et al.
3,924,496 A	12/1975	DerMarderosian et al.	5,157,890 A	10/1992	Jines
3,936,551 A	2/1976	Elmendorf et al.	5,165,816 A	11/1992	Parasin
3,987,599 A	10/1976	Hines	5,179,812 A	1/1993	Hill
3,988,187 A	10/1976	Witt et al.	5,182,892 A	2/1993	Chase
4,021,087 A	5/1977	Ferguson	5,216,861 A	6/1993	Meyerson
4,037,377 A	7/1977	Howell et al.	5,244,303 A	9/1993	Hair
4,059,933 A	11/1977	Funk et al.	5,247,773 A	9/1993	Weir
4,065,902 A	1/1978	Lindal	5,253,464 A	10/1993	Nilsen
4,067,155 A	1/1978	Ruff et al.	5,259,162 A	11/1993	Nicholas
4,074,496 A	2/1978	Fischer	5,266,384 A	11/1993	O'Dell et al.
4,090,338 A	5/1978	Bourgade	5,271,564 A	12/1993	Smith
4,095,913 A	6/1978	Pettersson et al.	5,274,979 A	1/1994	Tsai
4,099,358 A	7/1978	Compaan	5,283,102 A	2/1994	Sweet et al.
4,100,710 A	7/1978	Kowallik	5,295,341 A	3/1994	Kajiwara
4,144,689 A	3/1979	Bains	5,343,665 A	9/1994	Palmersten
4,156,048 A	5/1979	Davis	5,344,700 A	9/1994	McGath et al.
4,164,832 A	8/1979	Van Zandt	5,348,778 A	9/1994	Knipp et al.
4,165,305 A	8/1979	Sundie et al.	5,349,796 A	9/1994	Meyerson
4,169,688 A	10/1979	Toshio	5,365,713 A	11/1994	Nicholas et al.
4,182,072 A	1/1980	Much	5,390,457 A	2/1995	Sjolander
4,186,539 A	2/1980	Harmon et al.	5,413,840 A	5/1995	Mizuno
4,242,390 A	12/1980	Nemeth	5,424,118 A	6/1995	McLaughlin
4,299,070 A	11/1981	Oltmanns et al.	5,433,806 A	7/1995	Pasquali et al.
4,316,351 A	2/1982	Ting	5,437,934 A	8/1995	Witt et al.
4,372,899 A	2/1983	Wiemann et al.	5,474,831 A	12/1995	Nystrom
4,376,593 A	3/1983	Schaefer	5,475,960 A	12/1995	Lindal
4,390,580 A	6/1983	Donovan et al.	5,497,589 A	3/1996	Porter
4,426,820 A	1/1984	Terbrack et al.	5,502,939 A	4/1996	Zadok et al.
4,449,346 A	5/1984	Tremblay	5,526,857 A	6/1996	Forman
4,455,803 A	6/1984	Kornberger	5,527,128 A	6/1996	Rope et al.
4,461,131 A	7/1984	Pressell	5,540,025 A	7/1996	Takehara et al.
4,471,012 A	9/1984	Maxwell	5,555,980 A	9/1996	Johnston et al.
4,489,115 A	12/1984	Layman et al.	5,566,519 A	10/1996	Almaraz-Miera
			5,570,554 A	11/1996	Searer
			5,618,602 A	4/1997	Nelson
			5,623,799 A	4/1997	Kowalski et al.
			5,630,304 A	5/1997	Austin

(56)

References Cited

U.S. PATENT DOCUMENTS

5,647,181 A	7/1997	Hunts	7,603,826 B1	10/2009	Moebus
5,671,575 A	9/1997	Wu	7,658,048 B2	2/2010	Moriau et al.
5,706,621 A	1/1998	Pervan	7,779,597 B2 *	8/2010	Thiers et al. 52/588.1
5,736,227 A	4/1998	Sweet et al.	8,006,458 B1	8/2011	Olofsson et al.
5,755,068 A	5/1998	Ormiston	8,215,076 B2	7/2012	Pervan et al.
5,768,850 A	6/1998	Chen	8,429,869 B2	4/2013	Pervan
5,791,114 A	8/1998	Mandel	8,438,814 B2 *	5/2013	Thiers et al. 52/591.1
5,797,237 A	8/1998	Finkell, Jr.	8,627,631 B2	1/2014	Thiers et al.
5,827,592 A	10/1998	Van Gulik et al.	8,631,625 B2 *	1/2014	Thiers et al. 52/591.1
5,860,267 A	1/1999	Pervan	8,793,958 B2 *	8/2014	Theirs et al. 52/591.1
D406,360 S	3/1999	Finkell, Jr.	8,904,729 B2 *	12/2014	Thiers et al. 52/591.1
5,894,701 A	4/1999	Delorme	2001/0029720 A1	10/2001	Pervan
5,904,019 A	5/1999	Kooij et al.	2001/0034992 A1	11/2001	Pletzer et al.
5,907,934 A	6/1999	Austin	2002/0020127 A1	2/2002	Thiers et al.
5,930,947 A	8/1999	Eckhoff	2002/0083673 A1	7/2002	Kettler et al.
5,935,668 A	8/1999	Smith	2002/0100242 A1	8/2002	Olofsson
5,937,612 A	8/1999	Winer et al.	2002/0108343 A1	8/2002	Knauseder
5,941,047 A	8/1999	Johansson	2002/0148551 A1	10/2002	Knauseder
5,950,389 A	9/1999	Porter	2002/0170258 A1	11/2002	Schwitte et al.
5,968,625 A	10/1999	Hudson	2002/0178681 A1	12/2002	Zancai et al.
5,971,655 A	10/1999	Shirakawa	2004/0035077 A1	2/2004	Martensson et al.
5,987,839 A	11/1999	Hamar et al.	2004/0139678 A1	7/2004	Pervan
5,987,845 A	11/1999	Laronde	2005/0005559 A1	1/2005	Ralf
5,996,301 A	12/1999	Conterno	2005/0028474 A1	2/2005	Kim
6,006,486 A	12/1999	Moriau et al.	2013/0104487 A1	5/2013	Moriau et al.
6,021,615 A	2/2000	Brown	2013/0247501 A1	9/2013	Thiers et al.
6,023,907 A	2/2000	Pervan	AU	752409 B2	9/2002
6,029,416 A	2/2000	Andersson	BE	417 526 A	9/1936
6,094,882 A	8/2000	Pervan	BE	556 860 A	5/1957
6,101,778 A	8/2000	Martensson	BE	557 844 A	6/1957
6,119,423 A	9/2000	Costantino	BE	765 817 A2	9/1971
6,134,854 A	10/2000	Stanchfield	CA	991 373 A1	6/1976
6,148,884 A	11/2000	Bolyard et al.	CA	1049736 A1	3/1979
6,156,402 A	12/2000	Smith	CA	1 169 106 A1	6/1984
6,158,915 A	12/2000	Kise	CA	2 162 836 A1	5/1997
6,182,410 B1	2/2001	Pervan	CA	2 226 286 A1	12/1997
6,182,413 B1	2/2001	Magnusson	CA	2 252 791 A1	5/1999
6,189,283 B1	2/2001	Bentley et al.	CA	2 289 309 A1	7/2000
6,205,639 B1	3/2001	Pervan	CH	200 949 A	11/1938
6,209,278 B1	4/2001	Tychsen	CH	211 877 A	10/1940
6,216,409 B1	4/2001	Roy et al.	CH	562 377 A5	5/1975
6,247,285 B1	6/2001	Moebus	CN	1054215 A	9/1991
6,271,156 B1	8/2001	Gleason et al.	CN	2091909 U	1/1992
6,314,701 B1	11/2001	Meyerson	CN	1115351 A	1/1996
6,324,803 B1	12/2001	Pervan	CN	1124941 A	6/1996
6,324,809 B1	12/2001	Nelson	CN	2242278 Y	12/1996
6,332,733 B1	12/2001	Hamberger et al.	DE	209979 C	11/1906
6,345,481 B1	2/2002	Nelson	DE	417526 C	8/1925
6,363,677 B1	4/2002	Chen et al.	DE	1 212 275 B	3/1966
6,385,936 B1	5/2002	Schneider	DE	1 985 418 U	5/1968
6,397,547 B1	6/2002	Martensson	DE	1 534 802 A1	4/1970
6,418,683 B1	7/2002	Martensson et al.	DE	7 102 476 U	1/1971
6,421,970 B1	7/2002	Martensson et al.	DE	1 658 875 B1	9/1971
6,423,257 B1	7/2002	Stobart et al.	DE	2 007 129 A1	9/1971
6,438,919 B1	8/2002	Knauseder	DE	1 534 278 A1	11/1971
6,446,405 B1	9/2002	Pervan	DE	2 139 283 A1	2/1972
6,497,079 B1	12/2002	Steinwender et al.	DE	2 101 782 A1	7/1972
6,505,452 B1	1/2003	Hannig et al.	DE	2 102 537 A1	8/1972
6,516,579 B1	2/2003	Pervan	DE	2 145 024 A1	3/1973
6,536,178 B1	3/2003	Palsson et al.	DE	2 205 232 A1	8/1973
6,591,568 B1	7/2003	Palsson	DE	2 238 660 A1	2/1974
6,601,359 B2	8/2003	Olofsson	DE	2 251 762 A1	5/1974
6,647,690 B1	11/2003	Martensson	DE	2 252 643 A1	5/1974
6,682,254 B1	1/2004	Olofsson et al.	DE	7 402 354 U	5/1974
6,685,391 B1	2/2004	Gideon	DE	2 502 992 A1	7/1976
6,711,869 B2	3/2004	Tychsen	DE	2 616 077 A1	10/1977
6,729,091 B1	5/2004	Martensson	DE	78 36 825 U1	6/1980
6,763,643 B1	7/2004	Martensson	DE	29 17 025 A1	11/1980
6,766,622 B1	7/2004	Thiers	DE	29 16 482 A1	12/1980
6,769,835 B2	8/2004	Stridsman	DE	29 27 425 A1	1/1981
6,772,568 B2 *	8/2004	Thiers et al. 52/592.1	DE	29 40 945 A1	4/1981
6,804,926 B1	10/2004	Eisermann	DE	79 11 924 U1	6/1981
6,823,638 B2	11/2004	Stanchfield	DE	79 28 703 U1	7/1981
7,343,717 B2 *	3/2008	Thiers et al. 52/592.1	DE	41 05 207 A1	8/1981
7,380,383 B2	6/2008	Olofsson et al.	DE	30 41 781 A1	6/1982
			DE	31 04 519 A1	9/1982

(56)	References Cited	FR	2 781 513 A1	1/2000
	FOREIGN PATENT DOCUMENTS	GB	356 270 A	9/1931
DE	31 17 605 A1 11/1982	GB	424 057 A	2/1935
DE	32 14 207 A1 11/1982	GB	448 329 A	6/1936
DE	32 46 376 A1 6/1984	GB	585 205 A	1/1947
DE	33 04 992 A1 8/1984	GB	589 635 A	6/1947
DE	33 06 609 A1 9/1984	GB	599 793 A	3/1948
DE	33 19 235 A1 11/1984	GB	636 423 A	4/1950
DE	33 43 601 A1 6/1985	GB	647 812 A	12/1950
DE	34 12 882 A1 10/1985	GB	812 671 A	4/1959
DE	86 04 004 U1 4/1986	GB	1 027 709 A	4/1966
DE	35 12 204 A1 10/1986	GB	1 039 949 A	8/1966
DE	33 43 601 C2 2/1987	GB	1 127 915 A	9/1968
DE	35 38 538 A1 5/1987	GB	1 212 983 A	11/1970
DE	35 44 845 A1 6/1987	GB	1 237 744 A	6/1971
DE	36 31 390 A1 12/1987	GB	1 275 511 A	5/1972
DE	37 41 041 A1 9/1988	GB	1 308 011 A	2/1973
DE	40 02 547 A1 8/1991	GB	1 430 423 A	3/1976
DE	39 32 980 A1 11/1991	GB	2 117 813 A	10/1983
DE	41 30 115 A1 3/1993	GB	2 126 106 A	3/1984
DE	93 00 306 U1 3/1993	GB	2 142 670 A	1/1985
DE	41 34 452 A1 4/1993	GB	2 167 465 A	5/1986
DE	42 15 273 A1 11/1993	GB	2 168 732 A	6/1986
DE	42 42 530 A1 6/1994	GB	2 221 740 A	2/1990
DE	43 13 037 C1 8/1994	GB	2 228 753 A	9/1990
DE	93 17 191 U1 3/1995	IT	2 243 381 A	10/1991
DE	44 02 352 A1 8/1995	JP	2 256 023 A	11/1992
DE	295 20 966 U1 8/1996	JP	444 123	1/1949
DE	197 09 641 A1 9/1998	JP	S54-65528 U	5/1979
DE	299 11 462 U1 11/1999	JP	S57-119056 A	7/1982
DE	299 22 649 U1 3/2000	JP	S59-41560 A	3/1984
DE	200 02 413 U1 4/2000	JP	S59-186336 U	12/1984
DE	200 00 484 U1 5/2000	JP	S62-37687 Y2	9/1987
DE	200 01 225 U1 7/2000	JP	H0-1178659 A	7/1989
DE	296 23 914 U1 7/2000	JP	H02-285145 A	11/1990
DE	200 05 877 U1 10/2000	JP	H03-169967 A	7/1991
DE	199 25 248 A1 12/2000	JP	H04-106264 A	4/1992
DE	200 18 760 U1 12/2000	JP	H04-191001 A	7/1992
DE	200 17 461 U1 2/2001	JP	H05-148984 A	6/1993
DE	100 08 108 C1 5/2001	JP	H05-154806 A	6/1993
DK	3726-84 A 8/1984	JP	H06-146553 A	5/1994
EP	0 085 196 A1 8/1983	JP	H06-200611 A	7/1994
EP	0 196 672 A2 10/1986	JP	H06-56310 U	8/1994
EP	0 220 389 A2 5/1987	JP	H06-315944 A	11/1994
EP	0 248 127 A1 12/1987	JP	H06-320510 A	11/1994
EP	0 279 278 A2 8/1988	JP	H07-76923 A	3/1995
EP	0 487 925 A1 6/1992	JP	H07-180333 A	7/1995
EP	0 562 402 A1 9/1993	JP	H07-189466 A	7/1995
EP	0 623 724 A1 11/1994	JP	H07-229276 A	8/1995
EP	0 652 332 A1 5/1995	JP	H07-279366 A	10/1995
EP	0 652 340 A1 5/1995	JP	H07-300979 A	11/1995
EP	0 690 185 A1 1/1996	JP	H07-310426 A	11/1995
EP	0 698 162 A1 2/1996	JP	96-1207 A	2/1996
EP	0 715 037 A1 6/1996	JP	H08-86078 A	4/1996
EP	0 855 482 A2 7/1998	JP	H08-109734 A	4/1996
EP	0 877 130 A2 11/1998	JP	H08-270193 A	10/1996
EP	0 903 451 A2 3/1999	JP	H09-38906 A	2/1997
EP	0 969 163 A2 1/2000	JP	H09-88315 A	3/1997
EP	0 969 164 A2 1/2000	KR	2002-021306 A	1/2002
EP	0 974 713 A1 1/2000	NL	95-33446 U	12/1995
EP	1 024 234 A2 8/2000	NL	7601773 A	8/1976
EP	0 813 641 B1 7/2001	SE	7708519 A	2/1978
EP	1 203 854 A2 5/2002	SE	372 051 B	12/1974
EP	0 958 441 B1 7/2003	SE	450 141 B	6/1987
EP	0 843 763 B2 11/2006	SE	462 809 B	9/1990
FR	1 215 852 A 4/1960	SE	501 014 C2	10/1994
FR	1 293 043 A 5/1962	SE	502 994 C2	3/1996
FR	2 209 024 A1 6/1974	SU	9500810-8	3/1996
FR	2 278 876 A1 2/1976	SU	363795 A1	12/1972
FR	2 445 874 A1 8/1980	SU	857393 A1	8/1981
FR	2 568 295 A1 1/1986	WO	84/02155 A1	6/1984
FR	2 630 149 A1 10/1989	WO	87/03839 A1	7/1987
FR	2 637 932 A1 4/1990	WO	92/17657 A1	10/1992
FR	2 675 174 A1 10/1992	WO	93/13280 A1	7/1993
FR	2 691 491 A1 11/1993	WO	93/19910 A1	10/1993
FR	2 697 275 A1 4/1994	WO	94/01628 A2	1/1994
FR	02 712 329 A1 5/1995	WO	94/04773 A1	3/1994
FR		WO	94/22678 A1	10/1994
FR		WO	94/26999 A1	11/1994

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	95/05274 A1	2/1995
WO	95/06176 A1	3/1995
WO	96/23942 A1	8/1996
WO	96/27719 A1	9/1996
WO	96/27721 A1	9/1996
WO	96/30177 A1	10/1996
WO	97/47834 A1	12/1997
WO	99/66151 A1	12/1999
WO	99/66152 A1	12/1999
WO	00/66856 A1	11/2000
WO	01/48332 A1	7/2001
WO	01/53628 A1	7/2001
WO	01/77461 A1	10/2001
ZA	9705060 A	4/1998

OTHER PUBLICATIONS

“Round the Twist” Wood Based Panels International, 1 page, Jul. 1992.

“The Uniloc System, A Revolution in Laminate Flooring”, Contract Flooring Journal, p. 27, Dec. 1996.

18th IUFRO World Congress Division 5, Forest Products, published by Yugoslav IUFRO World Congress Organizing Committee, 7 pages, Jan. 1986.

“Boden Wand Decke”, Das Profi-Magazin Fur Bodenbelage und Raumgestaltung, 3 pages, Jan. 1997.

Buteo Drawing, ALU Profil-Technik, 1985.

“Selbst Teppichboden, PVC und Parkett Verlegen”, Compact-Praxis, “do it yourself”, pp. 1-2, 84-87, Copyright 1985.

Daiken Design Execution Material 1995-1996, 7 Pages.

Daiken General Catalog 1995-1996, 6 Pages.

FAX Press Release Quick Step, Uniloc, Nov. 18, 1996, 3 pages.

Fibo-Trespo Alloc, “Der Laminatboden, Der Ohne Leim Verlegt Wird”, 31 pages, 1995.

Fibo-Trespo Alloc, Opplaering OG Autorisasjon, 29 pages, 1995.

Fibo-Trespo English, “Revolution at Floor Level”, 7 pages, Nov. 20, 1998.

Fibo-Trespo German, “Revolution at Floor Level”, 7 pages, Nov. 20, 1998.

Boehme, C., “Kriechverhalten UF-Verleimter MDF”, Holz als Rohwerkstoff 50 (1992) 158-162 Springer Verlag 1992, 5 pages.

Holz-Lexikon, Nachschlagewerk fur die holz-und Forstwirtschaft, 17 pages. Copyright 1962.

“Das Ziel: Holzfaserwerkstoffe mit hoher Fertigungstiefe”, Holz-Zentralblatt, Stuttgart Nr 7. 1 page, Jan. 15, 1993.

Knight, Edward H., Knights American Mechanical Dictionary Definition of Scarf, 6 pages, vol. III-Per-Zym, New York: Published by Hurd & Houghton, Cambridge: The Riverside Press, Copyright 1876.

Brochure; Kronospan MDF, 4 pages, 1993.

Lueger, Lexikon der Technik, “Hozwerkstoff”, 4 pages, Copyright 1961.

Depp, Hans-Joachim et al., “MDF—Mitteldichte Faserplatten”, Has-Joachin Deppe and Kurt Ernst, 14 pages, Copyright 1996.

MDF Guide d’Utilisation, Published by Euro MDF Board, Allemagne, France, 11 pages, Copyright Nov. 1993.

MDF Produktnorm EMB, Euro MDF Board, 11 pages, Copyright 1995.

MDF User’s Manual English, European Associate of Medium Density Fiberboard Manufacturers, 82 pages, Jan. 1993.

Mobil Symposium on Wood-Based Products, Sep. 8, 1995, Magdeburg, Germany.

Partial Translation of Snickeriarbete, 2nd Edition, Malmo 1952, Partial pp. 827 & 855, 1 page.

“Quick-Step Plaatsingssysteem Voor Laminaat”, Parketblad 1 page. Dec. 13, 1996.

Larsson, Knut et al., Traindustrins Handbook, Snickeriarbete, 2nd Edition, Malmo 1952, 6 pages.

Rhodes, G.T.A., et al., “MDF—A New Member of the Family of Wood-Based Panels”, 9 pages, European Plastic Laminates Forum, 19, 1995.

Topan Arbeitskreis MDF, German Extract, 17 pages, Copyright 1988.

Trabearbetning Partial Translation, Anders Gronlund, 1 page, Partial pp. 358 & 360, Copyright TrateknikCentrum, 1986.

Gronlund, Anders, “Trabearbetning”, TrateknikCentrum, 6 pages, Copyright 1986.

“Produktverbesserungen bei Witex Rechtfertigen Preisangepasung”, Unternehmen, Euwid Hz Nr 30 v 29, p. 10, 1996.

WKI Gutachterliche Stellungnahme Nr 642-96, 6 pages, dated Apr. 16, 1996.

* cited by examiner




FIG. 1





FIG. 2

FIG. 4
PRIOR ARTFIG. 5
PRIOR ART




FIG. 3




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 15






FIG. 19




FIG. 21




FIG. 20




FIG. 22




FIG. 23




FIG. 24




FIG. 26




FIG. 25

1
FLOOR COVERING

**CROSS-REFERENCE TO RELATED
APPLICATION**

This application is a continuation of application Ser. No. 14/320,887, filed Jul. 1, 2014, now U.S. Pat. No. 8,904,729, which is a continuation of application Ser. No. 14/093,729, filed Dec. 2, 2013, now U.S. Pat. No. 8,793,958, which is a continuation of application Ser. No. 13/893,556, filed May 14, 2013, now U.S. Pat. No. 8,631,625, which is a continuation of application Ser. No. 12/821,604, filed Jun. 23, 2010, now U.S. Pat. No. 8,438,814, which is a continuation of application Ser. No. 11/979,317 filed Nov. 1, 2007, now U.S. Pat. No. 7,779,597, which is a divisional of application Ser. No. 10/890,456 filed Jul. 14, 2004, now U.S. Pat. No. 7,343,717, which is a divisional of application Ser. No. 09/878,206 filed Jun. 12, 2001, now U.S. Pat. No. 6,772,568.

FIELD OF THE INVENTION

The present invention concerns panels for making a floor covering, in particular of the type consisting of hard panels.

In particular, it concerns laminate panels, also called laminate parquet.

BACKGROUND OF THE INVENTION

It is known that such laminate panels can be made of different layers. Usually, the panels are formed of boards having a wood basis, such as chipboard or fiberboard, in particular MDF (Medium Density Fiberboard) or HDF (High Density Fiberboard), upon which one or several layers, including a decorative layer, are provided at least on the top side. The decorative layer may be a printed paper layer, but in certain embodiments it may just as well be a layer of wood, in particular veneer. Such panels can also be made of other materials, for example merely synthetic material, or of a base plate on the basis of wood, such as chipboard, MDF or HDF and the like, upon which is provided, instead of a printed paper layer or veneer, another material such as cork, thin strips of wood and the like.

It is also known to couple these panels on their edges as they are laid to form a floor covering, either by means of a conventional tongue and groove joint, whereby they are possibly glued together, or by means of a glueless coupling which provides for a mutual interlocking of the panels both in the horizontal and vertical directions, for example as described in U.S. Pat. No. 6,006,486.

The present invention relates to hard panels for floor coverings, in particular laminate panels, which provides for new embodiments according to different aspects offering respective advantages.

BRIEF DESCRIPTION OF THE INVENTION

According to a first aspect, the invention provides for a floor covering panel comprising a hard panel, wherein the panel is provided, at least on two opposite edges, with coupling means made in one piece with the panel, so that several of such panels can be mutually coupled, whereby these coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled panels (vertically active), as well as in a direction perpendicular to the edges concerned and parallel to the plane of the coupled panels (horizontally active), whereby said coupling means comprise a tongue and a groove and whereby the lip which is situated on the bottom

2

side of the groove, hereafter called the lower lip, is longer than the lip on the top side, hereafter called the upper lip, wherein the edge which is provided with the tongue, is made flexible.

As the edge onto which the tongue is provided is elastically flexible, deflections arising during the coupling of the panels are accommodated by this edge, and the above-mentioned upper lip is safeguarded against large deflections, as a result of which the material cannot possibly split due to the bending of the lower lip.

10 The lower lip is preferably even made rigid, by making it sufficiently thick, so that any bending in this lip is entirely excluded.

According to a first possibility, the above-mentioned flexibility is obtained by making at least the tongue elastically flexible. According to a second possibility, which is preferably combined with the first one, and which contributes even more to the required flexibility being obtained, the tongue is situated on a part which is connected to the actual panel via a flexible zone in the shape of a local constriction.

15 20 Specific advantages of the embodiment according to the first aspect are further explained in the following detailed description.

The coupling means are preferably made such that they allow the panels to be coupled by pushing them laterally 25 towards one another.

According to a second aspect, the invention provides for hard panels for forming a floor covering, wherein the panels are provided with coupling means on at least two opposite edges, as a result of which several of such panels can be 30 mutually coupled to one another, wherein these coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned, and parallel to the plane of the floor panels, wherein said coupling means 35 comprise a tongue and a groove and whereby the lip situated on the bottom side of the groove, hereafter called the lower lip, is longer than the lip on the top side, hereafter called the upper lip, characterized in that the coupling means consist at least of first coupling parts, formed of contact surfaces working in conjunction with one another, on the top side of the tongue and the bottom side of the upper lip respectively; second coupling parts formed of contact surfaces, on the top 40 side of the lower lip and an opposite part of the other panel respectively; and third coupling parts providing for the horizontal interlocking in the plane of the coupled panels and which are situated on the lower lip, yet further than the free end of the upper lip, wherein these third coupling parts are situated between the first and second ones.

As a result, the vertical forces which are created when 45 50 walking over the floor covering are divided over two places, which results in a better distribution of the forces.

The third coupling parts preferably consist of an inwardly directed contact surface provided near the free end of the lower lip, on this lip, and a contact surface working in conjunction with it which is formed on the other similar panel to be coupled.

The second coupling parts preferably consist of a contact surface formed on the top side of the free end of the lower lip, as well as a contact surface working in conjunction with it on the bottom side of the other panel.

Moreover, a free space is preferably provided under the tongue extending from the tip of the tongue up to the third coupling parts. As a result, the tongue can be put more easily in the groove, without having to take very precise tolerances into account.

60 65 According to a third aspect, the invention provides for a floor covering hard panel, wherein the panel is provided with

coupling means on at least two opposite edges, so that several similar ones of such panels can be mutually coupled, wherein these coupling means provide for an interlocking in a direction perpendicular to the plane of coupled panels, as well as in a direction perpendicular to the edges concerned and parallel to the plane of coupled panels, said coupling means comprising a tongue and a groove and wherein the lip which is situated on the bottom side of the groove, hereafter called the lower lip, is longer than the lip on the top side, hereafter called the upper lip, further wherein that the coupling means consist at least of first coupling parts formed of contact surfaces working in conjunction with one another, on the top side of the tongue and the bottom side of the upper lip respectively; second coupling parts formed of contact surfaces, on the top side of the lower lip and an opposite part of the other coupled panel respectively; and third coupling parts which provide for the horizontal interlocking situated on the lower lip, yet further than the free end of the upper lip, whereby the second coupling parts are situated between the first and the third ones, and whereby these second coupling parts consist of contact surfaces working in conjunction with one another and defining a local contact zone situated in the middle or practically in the middle between the tip of the tongue and the third coupling parts.

By making use of such a local contact zone, there remains a space between this zone and the tip of the tongue, on the bottom side of the latter, which makes sure that there is freedom of movement for the tongue when the panels are joined.

According to a fourth aspect, the invention provides for a floor covering hard panel, wherein the panel is provided with coupling means on at least two opposite edges made in one piece with the panel, as a result of which several of such panels can be mutually coupled to one another, whereby these coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the coupled panels, wherein said coupling means comprise a tongue and a groove, further wherein the lip situated on the top side of the groove, hereafter called the upper lip, is longer than the lip situated on the bottom side of the groove, hereafter called the lower lip, and in that the above-mentioned coupling means contain coupling parts which provide for the interlocking in the horizontal direction in the plane of coupled panels, wherein these coupling parts consist at least of contact surfaces working in conjunction with one another, provided on the bottom side of the upper lip, outside the distal end of the lower lip, and on the opposite part of the edge of the other panel respectively.

As the interlocking takes place on the upper lip, it is easier to check the reliability of the interlocking while the floor is being laid than in the case where the interlocking takes place on the lower lip.

According to a fifth aspect, the invention provides for a floor covering panels comprising hard panels, whereby each panel is provided with coupling means on at least two opposite edges made in one piece with the panel, as a result of which several of such panels can be mutually coupled to one another, whereby these coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned, and parallel to the plane of the coupled panels, whereby said coupling means comprise a tongue and a groove, and wherein the lip situated on the top side of the groove, hereafter called the upper lip, is longer than the lip situated on the bottom side of the groove, hereafter called the lower lip, and in that the above-mentioned coupling

means contain coupling parts which provide for the interlocking in the horizontal direction, whereby these coupling parts make it possible for these panels to be mutually disconnected by turning them down toward their bottom sides and towards one another.

Thanks to the use of coupling means which make it possible for the panels to be disconnected by turning them downward, and preferably to be exclusively disconnectable by this movement, the panels fit particularly tight on the coupling means concerned, and are pushed even closer towards one another when being walked on.

The panels are hereby preferably rectangular, and they are provided with coupling means on two pairs of edges which make it possible for the panels to be disconnected by means of an upward rotation in order to be unlocked, whereas, on the other pair of edges, as mentioned above, they are provided with coupling means which only allow for a disconnection by turning the coupled panels with their bottom side towards one another. Also the opposite turning movements increase the guarantee that such a coupling remains always available.

It should be noted that in the case of longitudinal panels, the coupling means which allow for a disconnection by turning the panels upward are preferably provided on the longitudinal sides, whereas the coupling means which allow for a disconnection by turning the panels down, are preferably provided on the shortest sides.

According to a sixth aspect, the invention provides for floor covering panels wherein the panels are provided with coupling means on at least two opposite edges made in one piece with the panels, as a result of which several of such panels can be mutually coupled to one another, whereby these coupling means provide for an interlocking in a vertical direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned and parallel to the plane of the coupled panels, wherein said coupling means comprise a tongue and a groove, and further wherein the interlocking in the horizontal direction is at least provided by coupling parts in the shape of a local protrusion in the top side of the above-mentioned tongue, which meshes in a recess in the lip which borders the top side of the groove.

An advantage of this embodiment consists in that, since the protrusion is local, the recess can also have relatively small dimensions, and the upper lip is only weakened locally.

According to the sixth aspect, there is preferably no interlocking in the horizontal direction on the lower lip.

According to a seventh aspect, the invention provides for hard floor covering panels, wherein the panels are provided with coupling means on at least two opposite edges made in one piece with the panels, as a result of which several of such panels can be mutually coupled to one another, wherein these coupling means provide for an interlocking in a vertical direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned and parallel to the plane of the coupled panels, and whereby:

the above-mentioned coupling means comprise a tongue and a groove, wherein this groove is bordered by a lower lip on the bottom side of the groove and an upper lip on the top side of the groove hereafter called the lower lip and the upper lip respectively, and further wherein the distal end of the upper lip defines or intersects a vertical plane, hereafter called plane V1;

the lower lip is distally longer than the upper lip;
there is an interlocking part on the part of the lower lip which extends past the free end of the upper lip, with a contact surface which, when coupled, works in conjunction with a contact surface which is provided on the other

panel, whereby these contact surfaces form a contact zone when coupled, whose center defines or intersects a vertical plane, hereafter called plane V2; before the above-mentioned interlocking part, in the direction of the groove, there is formed a space in the lower lip which is open on the top side; in the coupled situation, there is a contact zone in the cross section in which the top side of the tongue makes contact with the bottom side of the upper lip, whereby the point of this contact zone which is situated most inwardly defines or intersects a first vertical plane, hereafter called plane V3, the most outwardly situated point of this contact zone defines or intersects a second vertical plane, hereafter called plane V4, and both planes V3 and V4 define a vertical plane situated right in between, hereafter called plane V5; the top side of the interlocking part defines a horizontal level, hereafter called level N1; the bottom side of the part upon which the tongue is provided and which extends from the tip of the tongue to the interlocking zone, defines a horizontal level, hereafter called level N2; the levels N1 and N2 define a horizontal level situated right in between, hereafter called level N3; the average height of the contact zones between the top side of the tongue and the bottom side of the upper lip define a horizontal level, hereafter called level N4; the distance between the planes V1 and V2 is at least half of the distance between the levels N3 and N4; wherein the floor covering further possesses at least in combination the following characteristics:

that the panels, and basically also the above-mentioned lips, are made of fiberboard of the type MDF or HDF; that the coupling means are made such that the panels can be assembled by pushing them towards one another; and that the above-mentioned space extends to beneath the upper lip, such that this space is in conformity with at least one of the following two characteristics:

- that the part of this space which is situated under the level N3 extends inwardly to at least past the plane V1;
- that the part of this space which is situated under the level N1 extends inwardly to at least past the plane V5.

When all the above-mentioned criteria are met, an embodiment is obtained according to the invention whereby the above-mentioned space is relatively large compared to the other parameters on the one hand, and, thanks to the specific application of the MDF or HDF material, the structure nevertheless remains sufficiently stable on the other hand. The relatively large space which is formed in the lower lip offers the advantage that the tongue can be located in the groove more easily, as well as the advantage that the tongue can be made relatively massive.

According to a particular embodiment, this floor covering panel is characterized in that the panel is rectangular and in that coupling means are formed on both pairs of edges which offer an interlocking in the horizontal and vertical directions, wherein these coupling means are formed as mentioned above on at least one pair of said edges, and whereby on at least two edges intersecting at right angles to one another, use is made of a groove which is bordered by an upper lip and a lower lip respectively, whereby the lower lip each time protrudes further than the upper lip, such that two such longer lips meet in at least one angle of the panel, whereby at least the above-mentioned space continues up to the end of the panel in said angle, in other words extends through the far end of the lip standing at right angles. As the above-mentioned space is made continuous, also a large flexibility can be guaranteed in

the angle concerned, as the interlocking parts of the longitudinally directed lower lip and the transversely directed lower lip are then disconnected by this continuous recess.

According to an eighth aspect, the invention provides for floor covering hard panels, whereby these panels are provided with coupling means on at least two opposite edges made in one piece with the panels, as a result of which several of such panels can be mutually coupled to one another, whereby these coupling means provide for an interlocking in a vertical direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned and parallel to the plane of the coupled panels, and whereby:

the above-mentioned coupling means comprise a tongue and a groove, wherein the groove is bordered by a lip on the bottom side and the top side of the groove, hereafter called the lower lip and the upper lip respectively;

the lower lip is longer than the upper lip;

there is an interlocking part on the part of the lower lip which extends past the free end of the upper lip, with a contact surface which, when coupled, works in conjunction with a contact surface which is provided on the other coupled panel; and

before the above-mentioned interlocking part, in the direction of the groove, is formed a space in the lower lip which is open on the top side;

wherein the coupling means are made such that the panels can be assembled by pushing them towards one another while in a generally common place, and in that in the bottom side of the part onto which the tongue is provided, and which extends from the tip of the tongue up to the interlocking zone, is provided a depression, such that this depression co-operates with the interlocking part in a position at which the tongue is situated in front of the groove. Thus is obtained that, while the tongue is being fit in, the interlocking part is located in the depression, so that the tongue is better positioned in front of the groove of the other panel.

Floor coverings consisting of hard panels known until now, and which allow for a glueless interlocking, do not enable temporary removal of individual panels from the middle of the floor covering after the floor covering has been entirely laid. This is disadvantageous in that it is difficult to replace damaged panels, as well as impossible to locally remove the floor covering, for example to work on or in the rough floor, to lay or remove cables under the floor covering, etc. With the known systems, the panels always need to be systematically removed from an edge of the floor covering.

According to a ninth aspect, the invention aims to provide floor covering hard panels, whereby it is possible to remove any coupled panel whatsoever from an existing floor covering made of coupled panels, and to put it back, without the floor covering having to be systematically broken up from an edge of the whole.

According to this ninth aspect, the invention to this end provides for a floor covering hard panel, wherein the panel is provided with coupling means on at least two opposite edges made in one piece with the panel, as a result of which several of such panels can be mutually coupled to one another, whereby these coupling means provide for an interlocking in a vertical direction perpendicular to the plane of the coupled panels, as well as in a horizontal direction perpendicular to the edges concerned and parallel to the plane of the coupled panels, whereby the above-mentioned coupling means are made such that two coupled panels, starting from a flat position, can be turned towards one another toward their bottom sides over at least a certain angle and this turning movement

makes it possible for said two panels to be removed from in between other adjacent coupled panels.

According to a first preferred embodiment, the coupling means are made such that the two coupled panels, when they are situated in a floor covering, may be lifted along their coupled edges, such that there is a disconnection on at least one of the opposite edges that is coupled with adjacent panels.

According to a second preferred embodiment, the coupling means are made such that the two coupled panels, when they are situated in a floor covering, may be lifted along their coupled edges, such that the coupling, in particular the vertical coupling, is interrupted along the edges concerned and a disconnection along the coupled edges becomes possible.

According to a particularly practical embodiment, the floor covering panel is characterized in that the coupling means mainly consist of a tongue and a groove, whereby the lip which is situated on the bottom side of the groove is longer than the lip on the top side of the groove, and the interlocking is obtained mainly in the horizontal direction thanks to an interlocking part on the lip situated on the bottom side of the groove and an interlocking part working in conjunction with it on the bottom side of the other coupled panel, whereby these coupling means make it possible for the panels to be assembled by means of a turning movement and whereby, in the coupled position, spaces are provided above the first-mentioned interlocking part as well as under the second-mentioned interlocking part which allow for a further turning movement.

The above-described aspects of the invention may occur independently or they can be mutually combined, in any possible combination, provided the embodiments as described according to the above-mentioned aspects do not have conflicting characteristics.

DESCRIPTION OF THE DRAWINGS

In order to better explain the characteristics of the invention, the following preferred embodiments are described as an example only without being limitative in any way, with reference to the accompanying drawings, in which:

FIG. 1 schematically represents a hard flooring panel;

FIG. 2 schematically represents a part of a floor covering made of hard panels shown in FIG. 1;

FIG. 3 represents an embodiment of coupling means of coupled panels according to the invention applied in a floor covering, seen from a section which corresponds for example to section III-III in FIG. 2;

FIG. 4 represents a section according to prior art viewed along line IV-IV in FIG. 2;

FIG. 5 represents a variant of FIG. 4;

FIGS. 6 to 8 represent the coupling means from FIG. 3 in different positions;

FIG. 9 represents a variant of the coupling means from FIG. 3;

FIG. 10 represents another variant;

FIGS. 11 to 13 represent the variant from FIG. 10 in different positions;

FIG. 14 represents another variant;

FIG. 15 represents yet another variant;

FIGS. 16 and 17 represent the coupling means of FIG. 15 in two other positions;

FIG. 18 represents an angular part of a panel according to the invention;

FIG. 19 represents a section of another embodiment according to the invention;

FIG. 20 represents a section of another embodiment of a floor covering made of panels according to the invention;

FIG. 21 represents the part indicated by F21 in FIG. 20 on a larger scale;

FIG. 22 represents how the panels of the floor covering from FIG. 20 can be disconnected and connected respectively;

FIG. 23 represents the part indicated by F23 in FIG. 22 on a larger scale;

FIG. 24 represents a view analogous to that in FIG. 21 for another variant;

FIG. 25 represents how the panels of FIG. 24 can be mutually disconnected and connected respectively;

FIG. 26 represents the part indicated by F26 in FIG. 25 on a larger scale.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

As represented in FIGS. 1 and 2, the invention concerns hard floor covering panels 2 from which a floor covering 1 may be formed by coupling of the panels.

As described in U.S. Pat. No. 6,006,486, it is known that such panels 2 can be connected without any glue being required by making use of coupling means which, when the panels 2 are rectangular, provide for an interlocking in a direction R1, perpendicular to the plane of the floor covering 1, at least on one pair of opposite edges 3-4, and preferably on both pairs of edges 3-4, 5-6 respectively, as well as in a direction R2 perpendicular to the edges 3-4 or 5-6 concerned, and parallel to the plane of the floor covering 1.

Coupling means can be used which allow for different coupling methods, but preferably coupling by rotating the panels relative to each other as well as by pushing the panels together while in a generally common plane. The latter makes

it possible for such panels 2 to be coupled to one another in a known manner by first rotating them into one another on their edges 3-4, as represented by means of the panel 2A in FIG. 2 with a movement of rotation W1, and by subsequently snapping them together on their edges 5-6 by means of a translation motion T1. According to a variant, the connection on the edges 3-4 of the panels 2 concerned, can also be realized by starting from a position as is schematically indicated by reference 2B, and coupling the panel 2 concerned by means of a translation T2.

Also, while a panel 2A is maintained in the rotated position, a following panel 2C can be coupled to the edges 5 and 6 concerned, either by means of a translation T3, or by means of a mutual rotation between the panels 2A and 2C, after which both panels 2A and 2C are then turned down so as to be locked to the preceding row of panels.

As mentioned in the introduction, the present invention provides different new embodiments of coupling means to mutually connect such panels 2.

FIG. 3 represents an embodiment according to a first aspect of the invention.

Also, in this embodiment, the floor covering 1 comprises hard panels 2 which are provided with coupling means 7 made in one piece with the panels 2 on at least two opposite edges, in this case 5-6, so that several of such panels 2 can be mutually connected to one another. These coupling means 7 provide for an interlocking in the direction R1, as well as R2.

Further, these coupling means 7 have a tongue 8 provided on the edge 5, and a groove 9 provided on the edge 6, in which the tongue 8 fits. The groove 9 is hereby bordered on the top side by means of a lip 10, hereafter called the upper lip. At the bottom, it is bordered by a lip 11, hereafter called the lower lip, which is longer than the upper lip 10, in other words,

which extends further than the distal end 12 of the lip 10 in the horizontal direction away from groove 9.

The interlocking in the direction R2 is obtained as the lower lip 11 forms an interlocking part 13 with an inwardly directed contact surface 14 which can co-operate with an opposite contact surface 15 formed on the edge 5 when being coupled.

According to the invention, the panel edge 5 which is provided with the tongue 8 is made elastically flexible, whereas the lip 11 is preferably made rigid, the latter by making it relatively thick, as is clearly visible in FIG. 3.

The panel edge 5 is made such that it can elastically bend in several places. Thus, for example, the tongue 8 is flexible, but even more important is that this tongue 8 is preferably situated on a part 16, as represented, which is connected to the actual panel 2 via a flexible zone 17 in the shape of a local constriction or reduced cross-section.

This flexible zone 17 is preferably situated on the place as indicated in FIG. 3, in other words seen as of the tongue 8, past the contact surface 15, and said flexible zone 17 has a thickness D1, according to the direction R1, which is smaller than half the thickness of the panels 2 and/or smaller than $\frac{2}{3}$ of the thickness D2 of the part 16 upon which the tongue 8 is situated.

If the panels 2 are made of fiberboard, of the type MDF or HDF, the thickness D1 is preferably even smaller than 3 mm, and better still smaller than 2 mm.

The flexible zone 17 is situated against the top side 18 of the panel 2 concerned, which is particularly useful when MDF or HDF board is used, as such materials have a larger density on the outer surfaces, and thus the thickness on these places can be maximally reduced so as to obtain an optimal flexibility.

Apart from the advantages already mentioned in the introduction, the invention according to the first aspect also offers the following advantageous characteristics:

As the contact surface 14 is situated relatively high, said contact surface 14 can be provided in a more vertical position, without much deviation from the tangential directions B1 and B2 represented in FIG. 3. Thus is obtained a solid interlocking.

As the flexibility of the connection is situated in the top side of the panel, this results in the interlocking being pulled even more tightly together when a tensile force is exerted on the panels.

In the design of FIG. 3 is created a stress concentration on the top side of the panel 2, right behind the tongue 8, which results in a bending. As a consequence, the stress concentration is transferred to the strongest place of the board. During the joining, it is practically impossible for forces to be created in the deepest point of a groove 9, so that it is almost excluded that splits are created at this deepest point.

According to a second aspect of the invention, which in the given example of FIG. 3 is combined with the above-mentioned first aspect, the coupling means 7 consist at least of first coupling parts formed of contact surfaces 19-20 working in conjunction with one another, on the top side of the tongue 8 and the bottom side of the upper lip 10 respectively; second coupling parts formed of contact surfaces 21-22, on the top side of the lower lip 11 and the opposite part 16 of the other panel 2 respectively; and third coupling parts which provide for the horizontal interlocking situated on the lower lip 11, but further than the free end 12 of the upper lip 10, formed of the above-mentioned contact surfaces 14 and 15. What is special here, is that the third coupling parts are situated between the first and the second ones.

The second coupling parts are preferably situated immediately next to the third coupling parts. The contact surface 21 is hereby formed of the top side of the above-mentioned interlocking part 13, whereas the contact surface 22 is situated precisely opposite to it.

According to the embodiment of FIG. 3, there is a free space 23 under the tongue 8 which extends from the tip 24 of the tongue 8 up to the third coupling parts, in other words the contact surface 14.

10 The coupling means 7 are mainly designed to be provided on one pair of edges 5-6, whereas coupling means 25 are preferably provided on the other edges 3-4, as represented in FIG. 4 or FIG. 5, which are described in U.S. Pat. No. 6,006,486 and which make it possible for the panels 2 concerned to be assembled along their top edges and, disassembled, respectively at least by means of a movement of relative rotation. In the case where the panels 2, as represented, are longitudinal, the coupling means 7 will preferably be provided on the short edges 5-6.

20 The above-described arrangement does not exclude, however, that the coupling means 7 may be provided on both pairs of edges 3-4 and 5-6, or on the longitudinal edges 3-4, whereas another connection is provided for on the short edges.

25 Nor is it excluded to provide the panels 2 on merely one pair of edges with coupling means, in this case the coupling means 7.

Further, the coupling means 7 are preferably made such that the panels 2 with their edges concerned, in this case the edges 5 and 6, can be connected to one another by pushing the panels 2 freely towards one another, as is represented step by step in FIGS. 6 to 8, and as will be further described into more detail. Moreover, the coupling means 7 are made such that the edges concerned, in this case the edges 5 and 6, can also be connected to one another by means of a movement of relative rotation, and disconnected, respectively, as is represented by means of a dot and dash line in FIG. 3.

30 The laying of the floor covering 1, with panels 2 containing coupling means 7, can then for example, yet not necessarily, be carried out as follows. In a situation as represented in FIG. 2, the panel 2A is first connected with its edge 3 to an edge 4 of already laid panels by presenting the panel 2A at an angle and by rotating the above-mentioned edges 3-4 into one another, so that a connection such as for example in FIG. 4, or, 35 as an alternative, FIG. 5, is created.

40 Then, the panel 2A can be connected to the preceding panel with a translation T1, whereby the situations as represented in FIGS. 6 to 8 are successively observed on the coupling means 7. It is clear that this is accompanied by an elastic bending in the tongue 8, and to a larger extent also in the flexible zone 17, whereby the part 16 with the contact surface 15 finally snaps down behind the contact surface 14.

45 FIG. 9 represents an embodiment which is realized according to the above-mentioned third aspect of the invention. The coupling means 26 used hereby represent first coupling parts analogous to the coupling means 7, formed by contact surfaces 19 and 20, and third coupling parts formed by contact surfaces 14 and 15. What is special in this example, is that the above-mentioned second coupling parts are situated between the first and third ones, and that the second coupling parts consist of contact surfaces 27-28 working in conjunction with one another and which define a local contact zone 29 which is situated in the middle or practically in the middle between the tip 24 of the tongue 8 and the third coupling parts, in other words the contact surface 14.

50 As represented in FIG. 9, a bulge or protrusion 30 can be provided in the lower lip 11 on the contact zone 29.

11

FIGS. 10 to 13 represent an embodiment for different positions with coupling means 31 which are in conformity with a fourth aspect of the invention. The upper lip 10 is hereby longer than the lower lip 11, and the coupling means which realize the interlocking in the horizontal direction consist of coupling parts formed of contact surfaces 32-33 working in conjunction with one another, which are provided on the bottom side of the upper lip 10, outside the distal end of the lower lip 11, and on the opposite part of the edge of the other panel 2 respectively. ¹⁰

The coupling means 31 are hereby made such that the connection can be realized by pushing the panels 2 towards one another with the edges 5-6 concerned, for example over a base, whereby they systematically fit into one another, as represented in FIGS. 10 to 12. ¹⁵

As shown in the figures, the tongue 8 has one end 24 which has been made thinner. There is also a free space 35 between the free end 36 of the lower lip 11 and the opposite part 37 under the tongue 8 of the other panel 2. ²⁰

The embodiment of FIGS. 10 to 13 also illustrates a fifth aspect of the invention, in other words that the edges, in this case the edges 5-6, are provided with coupling means 31 which make it possible for the panels 2 concerned to be mutually disconnected by rotating them towards their bottom sides 38 and towards one another, as is specifically shown in FIG. 13. The above-mentioned space 35 is helpful thereby. ²⁵

The embodiment of FIGS. 10 to 13 also corresponds to a sixth aspect of the invention, wherein the interlocking in the horizontal direction is formed of coupling parts in the shape of a local protrusion 39 in the top side 40 of the above-mentioned tongue 8, which meshes in a recess 41 in the upper lip 10. ³⁰

FIG. 14 represents a variant which also applies the above-mentioned characteristics of the sixth aspect of the invention. ³⁵

Other particularities of this embodiment, which must not all be combined according to variants which are not represented, consist in that the top side 40 of the tongue 8, with the exception of the local protrusion 39, is mainly parallel to the surface of the floor covering 1, and in that the bottom side 42 of the tongue 8 is mainly formed of a smoothly bent surface which reaches up to the top side 40 of the tongue 8. Also this embodiment makes it possible for the panels 2 to be assembled by means of a mainly horizontal movement as well as rotational movement about the coupled edge. ⁴⁰

As seen in FIG. 14, the groove 9 has an innermost point 9a. The recess 41 is located within the portion of the groove 9 which is located between the innermost point 9a of the groove and the distal end 36 of the lower lip 11. It will also be evident that the bottom side of the tongue 8 at least in the region of the tongue located directly underneath the protrusion 39 and underneath the portion of the top side of the tongue extending from the protrusion 41 to the distal end 8a of the tongue is free from horizontally active coupling parts. It will also be evident from FIG. 14 that the protrusion 41 is located at a distance proximally inwardly from an imaginary vertical transverse plane intersecting the distal tip 8a of the tongue 8. A portion 40a of the top side of the tongue 8 extends generally parallel with the plane of the floor panel and forms a contact surface cooperating with the lower side of the upper lip 10. ⁵⁰

FIG. 15 represents a connection with coupling means 43 realized according to a seventh aspect of the invention. It concerns a connection whereby:

the coupling means 43 comprise a tongue 8 and a groove 9, whereby this groove 9 is bordered on the bottom and top sides, respectively, by a lip, hereafter called the lower lip 11 and the upper lip 10, respectively, wherein the distal ⁶⁰

12

end 12 of the upper lip 10 defines (i.e., intersects) a vertical plane, hereafter called plane V1; the lower lip 11 is longer than the upper lip 10; ⁵

there is an interlocking part 13 on the part of the lower lip 11 which extends past the free end 12 of the upper lip 10, with a contact surface 14 which, when coupled, works in conjunction with a contact surface 15 which is provided on the other panel 2, whereby these contact surfaces 14-15 form a contact zone when coupled, whose center ¹⁰

M1 intersects a vertical plane, hereafter called plane V2; before the above-mentioned interlocking part 13, in the direction of the groove 9, is formed an open space 44 in the lower lip 11 which is open on the top side; in the coupled situation, there is a contact zone in the cross section in which the top side of the tongue 8 makes contact with the bottom side of the upper lip 10, whereby the point C3 of this contact zone which is situated most inwardly intersects a first vertical plane, hereafter called plane V3, the most outwardly situated point C4 of this contact zone intersects a second vertical plane, hereafter called plane V4, and both planes V3 and V4 define a vertical plane situated right in between, hereafter called plane V5; ¹⁵

the top side of the interlocking part 13 defines a horizontal level, hereafter called level N1;

the bottom side of the part 16 upon which the tongue 8 is provided and which extends from the tip 24 of the tongue 8 to the interlocking zone, defines a horizontal level, hereafter called level N2;

the levels N1 and N2 define a horizontal level situated right in between, hereafter called level N3;

the average height of the contact zone between the top side of the tongue 8 and the bottom side of the upper lip 10 define a horizontal level, hereafter called level N4;

the distance between the planes V1 and V2 is at least half of the distance between the levels N3 and N4.

This floor covering 1 is special in that it provides at least the combination of the following characteristics:

that the panels 2, and basically also the above-mentioned lips 10-11, are made of fiberboard of the type MDF or HDF;

that the coupling means 43 are made such that the panels 2 can be assembled by pushing them towards one another; and

that the above-mentioned space 44 extends to beneath the upper lip 10, such that this space 44 is in conformity with at least one of the following two characteristics:

that the part of this space 44 which is situated under the level N3 extends inwardly to at least past the plane V1; that the part of this space 44 which is situated under the level N1 extends inwardly to at least past the plane V5.

Thanks to this specific combination there is obtained a space 44 which acts as a depression in relation to the other dimensions extending over a relatively large distance in the direction R2, as a result of which the advantages mentioned in the introduction are obtained. In spite of the relatively large depression and, consequently, the fact that the lower lip 11 is relatively thin, the rigidity remains nevertheless sufficient thanks to the use of MDF or HDF as a base material, which has a layered fibrous structure.

The distance between the levels N1 and N2 is preferably smaller than $\frac{1}{3}$ of the distance between the levels N2 and N4. Thus, the obstruction formed by the interlocking part 13 while the panels are being pushed together, is restricted to a minimum, as a result of which the panels 2 can smoothly slide into one another.

13

Further, the intersection P4 between the plane V4 and the bottom side of the tongue **8** is situated beneath level N1, seen from a cross section, and better still beneath level N3. The tongue **8** thus obtains a relatively large thickness, which improves its rigidity. Further, it is even possible for the section P5 between the plane V5 and the bottom side of the tongue **8** to be situated beneath level N1, and better still beneath level N3.

In particular, the section P3 between the plane V3 and the bottom side of the tongue **8** could be situated beneath level N1, and better still beneath level N3.

According to a preferred characteristic of the invention, the part of the above-mentioned space **44** situated under the plane N3 would extend at least inwardly up to the vertical plane V6 which is determined by the tip **24** of the tongue **8**.

In the case where the panels **2** are rectangular and coupling means are formed on both pairs of edges **3-4** and **5-6** which provide for a vertical and a horizontal interlocking, whereby both edges **4** and **6** have a lower lip **11**, **11A** respectively, which is longer than the upper lip **10**, at least the above-mentioned space **44** is preferably made continuous up to the end of the panel **2**, as represented in FIG. 18, in the corner **45**, in other words it extends through the far end of the square lip **10A**, in particular the interlocking part **13A** thereof. As the space **44** is relatively large on the one hand, and this space **44** extends through the interlocking part **13A** on the other hand, and the interlocking parts **13** and **13A** are disconnected from one another, a particularly flexible angle is obtained, which makes it easier to assemble the panels.

FIG. 19 illustrates an eighth aspect of the invention, whereby a depression **46** is provided in the bottom side of the tongue **8**, such that in the mutual position of the two panels **2** as represented in FIG. 19, the tongue **8** is better positioned in front of the groove.

It should be noted that in all the above-mentioned embodiments, the contact surfaces providing for the horizontal interlocking are preferably directed slantly in relation to the plane of the floor covering **1**. This does not exclude, however, that according to a variant, one or both contact surfaces can also be directed perpendicular to the plane of the floor covering. The contact surfaces can also be bent as such, whereby the tangent line in the middle of the contact zone determines the above-mentioned gradient.

In the case where these contact surfaces, or their tangent line, are directed slantly, they preferably extend in a direction which is tangential or almost tangential to a circle, whose center is situated on a point of rotation around which the panels **2** can be turned apart. As indicated in FIG. 3, this means that the gradient or direction B1 of the contact surfaces deviates only little from the gradient of the tangent B2 onto the circle C.

In order to provide for a snap-in effect, the direction B1 pertaining to the contact surfaces preferably does deviate from the direction of the above-mentioned tangent B2 and is directed inwardly, such that a snap-in effect is created when the panels are rotated into one another, whereby the above-mentioned direction B1 deviates 30° at the most from the above-mentioned tangential direction B2.

What precedes can be applied in all the rotatable embodiments described above, also in the embodiments whereby the panels **2** are rotated apart by turning them down.

The coupling means which are realized according to one or several of the first eight aspects of the invention are all particularly suitable to be provided on edges **3-4** and/or **5-6**, whereby it must be possible to assemble the panels **2** by shifting them.

14

In the case where the panels **2** are rectangular, in other words square or longitudinal, they are preferably provided with coupling parts on all four edges **3-4** and **5-6** which allow for a vertical and a horizontal interlocking, whereby coupling means as described in one or several of the above-mentioned first eight aspects are then provided on at least two opposite edges **3-4** or **5-6**.

In the case where the panels **2** are rectangular, the new coupling means are preferably provided at least on the short edges **5-6**. Further, coupling means are then preferably provided on the long edges **3-4** which allow for an assembly, disassembly respectively by means of a movement of rotation, which can be of a known nature or which can also be made according to any of the above-mentioned eight aspects.

FIGS. 20 to 23 show an embodiment according to a ninth aspect of the invention. According to this ninth aspect, it concerns floor covering hard panels **2**, wherein these panels **2** are provided on at least two opposite edges, in the case of elongated panels **2** preferably on the longitudinal edges **3-4**, with coupling means **7** made in one piece with the panels **2**, so that several of such panels **2** can be mutually connected to one another to form floor covering **1**, whereby these coupling means **7** provide for an interlocking in a direction R1, perpendicular to the plane of the coupled panels, as well as in a direction R2 perpendicular to the edges **3-4** concerned and parallel to the plane of the coupled panels, whereby the above-mentioned coupling means **7** are made such that two connected panels **2** can be turned about their coupled edges towards one another toward their bottom side, starting from a flat position, over at least a certain angle on the one hand, whereby this turning movement makes it possible for the two above-mentioned panels **2** to be removed from between other adjacent panels **2D** and **2E**.

Moreover, according to the embodiment of FIGS. 20 to 23, the coupling means **7** are made such that, as represented in FIG. 22, they make it possible for the two panels **2** to be lifted along their coupled edges **3-4**, from a flat position, such that there is a disconnection on at least one of the opposite edges **40** which provide for the connection with the adjacent panels **2D** and **2E**. Thus, the panels **2** can be removed from an existing floor covering **1** by first lifting them as mentioned above and by subsequently turning the left panel **2** from FIG. 22 up, as represented by means of a dot and dash line, so that the left panel **2** of FIG. 22 can be removed. Next, also the right panel **2** can be removed. The initial lifting of the panels **2** can take place in any way whatsoever, for example by means of a suction cup or by sticking a hook or such through an opening made in the floor covering, for example a bore hole.

FIGS. 20 to 26 represent variants whereby the coupling means **7** are made such that they make it possible for the two panels **2** to be lifted, from a flat position, along their coupled edges **3-4**, such that the connection, in particular the vertical connection on the edges **3-4** concerned is undone. In this case, **55** it is not necessary to disconnect the panels **2D** and/or **2E** first in order to disconnect the two panels **2**.

Both in the embodiment of FIGS. 20 to 23 and in the one of FIGS. 24 to 26, the coupling means **7** mainly consist of a tongue **8** and a groove **9**, whereby the lip **11** which is situated **60** on the bottom side of the groove **9** is longer than the lip **10** on the top side, and the interlocking is mainly obtained in the horizontal direction by means of an interlocking part **13** on the lip **11** and an interlocking part **47** on the bottom side of the other panel **2** working in conjunction with it, whereby these **65** coupling means **7** make it possible for the panels **2** to be assembled by means of a turning movement, and whereby, in the coupled position, there are spaces **48-49** above the first-

15

mentioned interlocking part 13, as well as under the second-mentioned interlocking part 47, which allow for a further turning.

Practically, the above-mentioned interlocking parts 13-47 are positioned such that a lateral play S is created during the above-mentioned further turning, as is schematically represented in FIG. 21, so that a certain freedom of movement is obtained which is desirable in order to remove the panels 2 from between the fixed panels 2D and 2E.

In the embodiment of FIGS. 24 to 26, this lateral play S, as well as the design of the tongue 8 and the groove 9, are selected such that the right panel 2, in the situation of FIG. 26, comes loose so to say and can simply be removed from the left panel 2.

In particular, the distance Z1 between the tip of the tongue 8 and the interlocking part 47 situated on the same edge is smaller than or equal to the distance Z2 between the tip of the lip 10 bordering the top side of the groove 9 and the interlocking part 13 situated on the lip 11 bordering the bottom side of the groove 9.

It should be noted that in the embodiments of FIGS. 20 to 26, the tongue 8 is preferably made such that it can make a movement of rotation in the groove 9, as said tongue 8 is more or less round, as represented in FIGS. 20 to 23, or because it is relatively short, as represented in FIGS. 24 to 26.

As represented, coupling means are preferably provided both on the short edges and on the longitudinal edges which allow for an interlocking both in the vertical and in the horizontal direction, whereby they can all be made such that they allow for a connection and disconnection as described above with regard to FIGS. 20 to 26. It is also possible to apply the coupling means represented in these figures only on the longitudinal edges, whereas coupling means with another shape are applied on the short sides, for example as represented in FIG. 4.

The invention is by no means limited to the above-described embodiments represented in the accompanying drawings; on the contrary, such a floor covering can be made in different shapes and dimensions while still remaining within the scope of the invention.

The invention claimed is:

1. A floor panel, for forming a floor covering, wherein the floor panel is generally made of synthetic material;

wherein the floor panel comprises two pairs of opposite edges;

wherein the first pair of opposite edges comprises first coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said first coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein the second pair of opposite edges comprises second coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said second coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein said second coupling means are made in one piece with the floor panel;

wherein said second coupling means are configured for allowing assembly of two of such floor panels by means of a movement of rotation of one panel in respect to the other;

16

wherein said second coupling means comprise a tongue and a groove, said groove being bordered by an upper lip and a lower lip;

wherein said upper lip has a distal end and said lower lip extends beyond the distal end of the upper lip; wherein an interlocking part is situated on the lower lip, with a contact surface which, when coupled, works in conjunction with the contact surface which is provided on the other floor panel so as to provide said interlocking in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein the edge comprising said tongue comprises a lower surface being substantially horizontal;

wherein said lower surface is located distally from said contact surface working in conjunction with the contact surface of the interlocking part when coupled;

wherein said substantially horizontal lower surface in a distal direction connects to an upwardly inclined surface;

wherein the top side of said interlocking part defines a horizontal level;

wherein said second coupling means comprise coupling parts formed of contact surfaces working in conjunction with one another, on the top side of the tongue and the bottom side of the upper lip respectively, said contact surfaces defining a contact zone which is situated above said horizontal level;

wherein the distal end of the upper lip defines a vertical plane; and

wherein said vertical plane intersects the upper side of the lower lip at an intersection point which is situated beneath said horizontal level.

2. The floor panel of claim 1, wherein said lower surface comprises a contact surface working in conjunction with a contact surface situated on the upper side of the lower lip, when two of such floor panels are coupled.

3. The floor panel of claim 1, wherein said upwardly inclined surface borders the lower side of the tongue and extends up to the tip of the tongue.

4. The floor panel of claim 1, wherein said upwardly inclined surface is substantially flat.

5. The floor panel of claim 1, wherein said interlocking part is situated on a part of the lower lip which extends past the free end of the upper lip.

6. The floor panel of claim 1, wherein, in the coupled condition of two of such floor panels, a free space is formed underneath the substantially horizontal lower surface.

7. The floor panel of claim 1, wherein the distal end of the lower lip, in the coupled condition of two of such floor panels, in distal direction, is spaced from the other floor panel coupled thereto.

8. The floor panel of claim 1, wherein another free space is provided under the tip of the tongue.

9. The floor panel of claim 1, wherein said substantially horizontal lower surface is completely horizontal.

10. The floor panel of claim 1, wherein said substantially horizontal lower surface is slightly upwardly inclined in distal direction.

11. The floor panel of claim 1, wherein said substantially horizontal lower surface is directly located distally from said contact surface working in conjunction with the contact surface of the interlocking part when coupled.

12. The floor panel of claim 1, wherein, in coupled condition of two of such floor panels, said substantially horizontal lower surface cooperates with a substantially horizontal surface at the other floor panel.

17

13. The floor panel of claim 1, wherein the floor panel comprises a decorative layer;

wherein the floor panel is rectangular and has a longitudinal form, and has long and short edges;

wherein the first pair of opposite edges forms the short edges; and

wherein the second pair of opposite edges forms the long edges.

14. The floor panel of claim 1, wherein each of said coupling means are formed by coupling profiles.

15. A floor panel, for forming a floor covering, wherein the floor panel is generally made of synthetic material;

wherein the floor panel comprises two pairs of opposite edges;

wherein the first pair of opposite edges comprises first coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said first coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein the second pair of opposite edges comprises second coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said second coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein said second coupling means are made in one piece with the floor panel;

wherein said second coupling means are configured for allowing assembly of two of such floor panels by means of a movement of rotation of one panel in respect to the other;

wherein said second coupling means comprise a tongue and a groove, said groove being bordered by an upper lip and a lower lip;

wherein said upper lip has a distal end and said lower lip extends beyond the distal end of the upper lip;

wherein said second coupling means consist at least of first coupling parts formed of contact surfaces that in a coupled condition of two of such floor panels work in conjunction with one another, on the top side of the tongue and the bottom side of the upper lip respectively,

second coupling parts formed of contact surfaces, on the top side of the lower lip and an opposite part of the other coupled floor panel respectively, and third coupling parts which provide for the horizontal interlocking, comprising an interlocking part on the lower lip, said interlocking part having a contact surface which, when coupled, works in conjunction with the contact surface which is provided on the other floor panel;

wherein the top side of said interlocking part defines a horizontal level;

wherein the contact surfaces of the second coupling parts are situated beneath said horizontal level; and

wherein, in the coupled condition of two of such floor panels, a free space is situated above the upper side of the lower lip and between the second and third coupling parts.

16. The floor panel of claim 15, wherein the second coupling parts are situated between the first and third coupling parts.

17. The floor panel of claim 15, wherein the contact surfaces of the first coupling parts are substantially horizontal.

18

18. The floor panel of claim 15, wherein the contact surfaces of the second coupling parts are inclined with respect to the plane of the floor panel.

19. The floor panel of claim 15, wherein the contact surfaces of the first coupling parts are situated above said horizontal level.

20. The floor panel of claim 15, wherein the contact surfaces of the first coupling parts define a contact zone, whereby the point of this contact zone which is situated most inwardly defines or intersects a vertical plane;

and wherein the second coupling parts are configured such that in the coupled condition of two of such floor panels another free space exists under the tongue, said another free space extending as of the tip of the tongue up to at least said vertical plane.

21. The floor panel of claim 15, wherein the floor panel comprises a decorative layer.

22. The floor panel of claim 15, wherein the floor panel is rectangular and has a longitudinal form, and has long and short edges;

wherein the first pair of opposite edges forms the short edges; and wherein the second pair of opposite edges forms the long edges.

23. The floor panel of claim 15, wherein each of said coupling means are formed by coupling profiles.

24. A floor panel, for forming a floor covering, wherein the floor panel is generally made of synthetic material;

wherein the floor panel comprises two pairs of opposite edges;

wherein the first pair of opposite edges comprises first coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said first coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein the second pair of opposite edges comprises second coupling means, as a result of which several of such floor panels can be mutually coupled to one another, whereby said second coupling means provide for an interlocking in a direction perpendicular to the plane of the coupled floor panels, as well as in a direction perpendicular to the edges concerned, and parallel to the plane of the floor panel;

wherein said second coupling means are made in one piece with the floor panel;

wherein said second coupling means are configured for allowing assembly of two of such floor panels by means of a movement of rotation of one panel in respect to the other;

wherein said second coupling means comprise a tongue and a groove, said groove being bordered by an upper lip and a lower lip;

wherein said upper lip has a distal end and said lower lip extends beyond the distal end of the upper lip;

wherein said tongue is situated on a part which is connected to the floor panel via a zone in the shape of a local constriction or reduced cross-section, whereby said zone has a thickness which is smaller than half the thickness of the floor panel; and

wherein an interlocking part is situated on the lower lip, with a contact surface which, when coupled, works in conjunction with the contact surface which is provided on the other floor panel so as to provide said interlocking in a direction perpendicular to the edges concerned, and

parallel to the plane of the floor panel; wherein the top side of said interlocking part defines a horizontal level; wherein said second coupling means at least comprise coupling parts formed of contact surfaces working in conjunction with one another, on the top side of the tongue and the bottom side of the upper lip respectively, said contact surfaces defining a contact zone which is situated above said horizontal level; and wherein a space is provided under the tongue.

25. The floor panel of claim **24**, wherein the thickness of said zone is smaller than $\frac{2}{3}$ of the thickness of said part upon which the tongue is situated.

26. The floor panel of claim **24**, wherein said zone is situated past said contact surface of the interlocking part seen as of the tongue.

27. The floor panel of claim **24**, wherein the distal end of the lower lip, in the coupled condition of two of such floor panels, in distal direction, is spaced from the other floor panel coupled thereto.

28. The floor panel of claim **24**, wherein said zone is a flexible zone.

29. The floor panel of claim **24**, wherein the floor panel is rectangular and has a longitudinal form, and has long and short edges; wherein the first pair of opposite edges forms the short edges; and

wherein the second pair of opposite edges forms the long edges.

30. The floor panel of claim **24**, wherein each of said coupling means are formed by coupling profiles.

* * * * *

15

25

30