



US 20090018661A1

(19) **United States**
(12) **Patent Application Publication**
Kim et al.

(10) **Pub. No.: US 2009/0018661 A1**
(43) **Pub. Date: Jan. 15, 2009**

(54) **PROSTHETIC INTERVERTEBRAL DISCS**

Related U.S. Application Data

(75) Inventors: **Daniel H. Kim**, Mountain View, CA (US); **Thomas A. Afzal**, Menlo Park, CA (US); **Michael L. Reo**, Redwood City, CA (US); **Uriel Hiram Chee**, Santa Cruz, CA (US); **In Haeng Cho**, Seoul (KR); **Kunwoo Lee**, Seoul (KR); **Curtis W. Frank**, Cupertino, CA (US); **Sung Kyu Ha**, Kyunggi-do (KR)

(60) Division of application No. 10/903,276, filed on Jul. 30, 2004, which is a continuation-in-part of application No. 10/632,538, filed on Aug. 1, 2003, now Pat. No. 7,153,325.

Publication Classification

(51) **Int. Cl.**
A61F 2/44 (2006.01)
(52) **U.S. Cl.** **623/17.16**; 623/17.11; 623/17.15
(57) **ABSTRACT**


Correspondence Address:
Wheelock Chan LLP
P.O. Box 61168
Palo Alto, CA 94306 (US)

Prosthetic intervertebral discs and methods for using the same are described. The subject prosthetic discs include upper and lower endplates separated by a compressible core member. The prosthetic discs described herein include one-piece, two-piece, three-piece, and four-piece structures. The subject prosthetic discs exhibit stiffness in the vertical direction, torsional stiffness, bending stiffness in the saggital plane, and bending stiffness in the front plane, where the degree of these features can be controlled independently by adjusting the components of the discs. The interface mechanism between the endplates and the core members of several embodiments of the described prosthetic discs enables a very easy surgical operation for implantation.

(73) Assignee: **Spinal Kinetics, Inc.**, Sunnyvale, CA (US)

(21) Appl. No.: **11/968,185**

(22) Filed: **Jan. 1, 2008**






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 7

FIG. 8





FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D

FIG. 13E





FIG. 13F




FIG. 13G

FIG. 13H






FIG. 13I

FIG. 13J






FIG. 13K









FIG. 13L








FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24A




FIG. 24B




FIG. 24C




FIG. 25A




FIG. 25B




FIG. 25C




FIG. 26




FIG. 27




FIG. 28A




FIG. 28B






FIG. 28C






FIG. 31







FIG. 32






FIG. 36A

FIG. 36B




FIG. 37A

FIG. 37B








FIG. 38A

FIG. 38B






FIG. 43A




FIG. 43B




FIG. 44A




FIG. 44B




FIG. 45A




FIG. 45B




FIG. 46A




FIG. 46B




FIG. 47A




FIG. 47B




FIG. 48A




FIG. 48B




FIG. 49A






FIG. 49B






FIG. 51




FIG. 52A




FIG. 52B




FIG 53




FIG 54

PROSTHETIC INTERVERTEBRAL DISCS

RELATED APPLICATIONS

[0001] This application is a divisional of application Ser. No. 10/903,276, filed Jul. 30, 2004, which in turn, is a continuation-in-part of co-pending application Ser. No. 10/632,538, filed Aug. 1, 2003, which prior applications are incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] The intervertebral disc is an anatomically and functionally complex joint. The intervertebral disc is composed of three component structures: (1) the nucleus pulposus; (2) the annulus fibrosus; and (3) the vertebral endplates. The biomedical composition and anatomical arrangements within these component structures are related to the biomechanical function of the disc.

[0003] The spinal disc may be displaced or damaged due to trauma or a disease process. If displacement or damage occurs, the nucleus pulposus may herniate and protrude into the vertebral canal or intervertebral foramen. Such deformation is known as herniated or slipped disc. A herniated or slipped disc may press upon the spinal nerve that exits the vertebral canal through the partially obstructed foramen, causing pain or paralysis in the area of its distribution.

[0004] To alleviate this condition, it may be necessary to remove the involved disc surgically and fuse the two adjacent vertebra. In this procedure, a spacer is inserted in the place originally occupied by the disc and it is secured between the neighboring vertebrae by the screws and plates/rods attached to the vertebra. Despite the excellent short-term results of such a "spinal fusion" for traumatic and degenerative spinal disorders, long-term studies have shown that alteration of the biomechanical environment leads to degenerative changes at adjacent mobile segments. The adjacent discs have increased motion and stress due to the increased stiffness of the fused segment. In the long term, this change in the mechanics of the motion of the spine causes these adjacent discs to degenerate.

[0005] To circumvent this problem, an artificial intervertebral disc replacement has been proposed as an alternative approach to spinal fusion. Although various types of artificial intervertebral discs have been developed to restore the normal kinematics and load-sharing properties of the natural intervertebral disc, they can be grouped into two categories, i.e., ball and socket joint type discs and elastic rubber type discs.

[0006] Artificial discs of ball and socket type are usually composed of metal plates, one to be attached to the upper vertebra and the other to be attached to the lower vertebra, and a polyethylene core working as a ball. The metal plates have concave areas to house the polyethylene core. The ball and socket type allows free rotation between the vertebrae between which the disc is installed and thus has no load sharing capability against the bending. Artificial discs of this type have a very high stiffness in the vertical direction, they cannot replicate the normal compressive stiffness of the natural disc. Also, the lack of load bearing capability in these types of discs causes adjacent discs to take up the extra loads resulting in the eventual degeneration of the adjacent discs.

[0007] In elastic rubber type artificial discs, an elastomeric polymer is embedded between metal plates and these metal plates are fixed to the upper and the lower vertebrae. The elastomeric polymer is bonded to the metal plates by having the interface surface of the metal plates be rough and porous.

This type of disc can absorb a shock in the vertical direction and has a load bearing capability. However, this structure has a problem in the interface between the elastomeric polymer and the metal plates. Even though the interface surfaces of the metal plates are treated for better bonding, polymeric debris may nonetheless be generated after long term usage. Furthermore, the elastomer tends to rupture after a long usage because of its insufficient shear-fatigue strength.

[0008] Because of the above described disadvantages associated with either the ball/socket or elastic rubber type discs, there is a continued need for the development of new prosthetic devices.

RELEVANT LITERATURE

[0009] U.S. Pat. Nos. 3,867,728; 4,911,718; 5,039,549; 5,171,281; 5,221,431; 5,221,432; 5,370,697; 5,545,229; 5,674,296; 6,162,252; 6,264,695; 6,533,818; 6,582,466; 6,582,468; 6,626,943; 6,645,248. Also of interest are published U.S. Patent Application Nos. 2002/0107575, 2003/0040800, 2003/0045939, and 2003/0045940. See also Masahiko Takahata, Uasuo Shikinami, Akio Minami, "Bone Ingrowth Fixation of Artificial Intervertebral Disc Consisting of Bioceramic-Coated Three-dimensional Fabric," SPINE, Vol. 28, No. 7, pp. 637-44 (2003).

SUMMARY OF THE INVENTION

[0010] Prosthetic intervertebral discs and methods for using such discs are provided. The subject prosthetic discs include an upper endplate, a lower endplate, and a compressible core member disposed between the two endplates.

[0011] In one embodiment, the subject prosthetic discs are characterized by including top and bottom endplates separated by a fibrous compressible element that includes an annular region and a nuclear region. The two plates are held together by at least one fiber wound around at least one region of the top endplate and at least one region of the bottom endplate. The subject discs may be employed with separate vertebral body fixation elements, or they may include integrated vertebral body fixation elements. Also provided are kits and systems that include the subject prosthetic discs.

[0012] In other embodiments, the prosthetic disc comprises an integrated, single-piece structure. In another embodiment, the prosthetic disc comprises a two-piece structure including a lower endplate and a separable upper endplate assembly that incorporates the core member. The two-piece structure may be a constrained structure, wherein the upper endplate assembly is attached to the lower endplate in a manner that prevents relative rotation, or a partially or semi-constrained structure or an unconstrained structure, wherein the upper endplate assembly is attached to the lower endplate in a manner that allows relative rotation. In yet another, embodiment, the prosthetic disc comprises a three-piece structure including upper and lower endplates and a separable core member that is captured between the upper and lower endplates by a retaining mechanism. Finally, in yet another embodiment, the prosthetic disc comprises a four-piece structure including upper and lower endplates and two separable core assemblies which, together, form a core member.

[0013] Several optional core materials and structures may be incorporated in each of the prosthetic disc embodiments described herein. For example, the core member may be formed of a relatively compliant material, such as polyurethane or silicone, and is typically fabricated by injection

molding. In other examples, the core member may be formed by layers of fabric woven from fibers. In still further examples, the core member may comprise a combination of these materials, such as a fiber-reinforced polyurethane or silicone. As an additional option, one or more spring members may be placed between the upper and lower endplates in combination with the core member, such as in a coaxial relationship in which the core member has a generally cylindrical or toroidal shape and a spring is located at its center.

[0014] In the various embodiments, the disc structures are held together by at least one fiber wound around at least one region of the upper endplate and at least one region of the lower endplate. The fibers are generally high tenacity fibers with a high modulus of elasticity. The elastic properties of the fibers, as well as factors such as the number of fibers used, the thickness of the fibers, the number of layers of fiber windings, the tension applied to each layer, and the crossing pattern of the fiber windings enable the prosthetic disc structure to mimic the functional characteristics and biomechanics of a normal-functioning, natural disc.

[0015] Apparatus and methods for implanting prosthetic intervertebral discs are also provided. In a first embodiment, the apparatus includes three implantation tools used to prepare the two adjacent vertebral bodies for implantation and then to implant the prosthetic disc. A first tool, a spacer, is adapted to be inserted between and to separate the two adjacent vertebral bodies to create sufficient space for implanting the prosthetic disc. A second tool, a chisel, includes one or more wedge-shaped cutting blades located on its upper and/or lower surfaces that are adapted to create grooves in the inward facing surfaces of the two adjacent vertebral bodies. A third tool, a holder, includes an engagement mechanism adapted to hold the prosthetic disc in place while it is being implanted, and to release the disc once it has been implanted.

[0016] In another embodiment, the implantation apparatus includes a guide member that engages the lower endplate and that remains in place during a portion of the disc implantation process. A lower pusher member slidably engages the guide member and is used to advance the lower endplate into place between two adjacent vertebrae of a patient's spine. An upper pusher member is preferably coupled to the lower pusher member and is used to advance a first chisel into place opposed to the lower endplate between the two adjacent vertebrae. Once in place, an upward force is applied to the upper pusher member to cause the first chisel to engage the upper vertebral body and to create one or more grooves on its lower surface. A downward force is also applied to the lower pusher member to cause the lower endplate to engage the lower vertebral body and to become implanted. The upper pusher member and first chisel are then removed, as is the lower pusher member. Preferably, a second chisel is then advanced along the guide member and is used to provide additional preparation of the upper vertebral body. After the completion of the preparation by the first chisel and, preferably, the second chisel, the upper endplate and core members of the prosthetic disc are implanted using an upper endplate holder that is advanced along the guide member. After implantation, the upper endplate holder and guide member are removed.

[0017] Apparatus and methods for implanting prosthetic intervertebral discs using minimally invasive surgical procedures are also provided. In one embodiment, the apparatus includes a pair of cannulas that are inserted posteriorly, side-by-side, to gain access to the spinal column at the disc space. A pair of prosthetic discs are implanted by way of the cannu-

las to be located between two vertebral bodies in the spinal column. In another embodiment, a single, selectively expandable disc is employed. In an unexpanded state, the disc has a relatively small profile to facilitate delivery of it to the disc space. Once operatively positioned, it can then be selectively expanded to an appropriate size to adequately occupy the disc space. Implantation of the single disc involves use of a single cannula and an articulating chisel or a chisel otherwise configured to establish a curved or right angle disc delivery path so that the disc is substantially centrally positioned in the disc space. Preferably, the prosthetic discs have sizes and structures particularly adapted for implantation by the minimally invasive procedure.

[0018] Other and additional devices, apparatus, structures, and methods are described by reference to the drawings and detailed descriptions below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The Figures contained herein are not necessarily drawn to scale, with some components and features being exaggerated for clarity.

[0020] FIGS. 1A and 1B provide a three dimensional view of two different prosthetic discs according to the subject invention.

[0021] FIG. 2 provides a three-dimensional view of a fibrous compressible element that includes a polymeric nucleus and a fibrous annulus according to one embodiment of the subject invention.

[0022] FIGS. 3A to 3C provide different views of a fibrous component of the fibrous compressible elements according to an embodiment of the subject invention. FIG. 3C illustrates the manner in which the 2D fabrics in FIG. 3B are stitched together.

[0023] FIG. 4A provides a three-dimensional top view of a prosthetic disc according to an embodiment of the present invention in which the fixation elements are integral to the disc, while FIG. 4B shows the disc of FIG. 4A implanted with the use of bone screws.

[0024] FIGS. 5A and 5B show the mating interface between disc top endplate with an upper vertebral body fixation element according to an embodiment of the subject invention.

[0025] FIGS. 6A and 6B show the mating interface between disc top endplate with an upper vertebral body fixation element according to an alternative embodiment of the subject invention. The top endplate is clamped by a clamping element connected to the upper vertebral body fixation element through a spring.

[0026] FIG. 7 provides an exploded view of a disc system that includes both an intervertebral disc and vertebral body fixation elements, according to an embodiment of the present invention.

[0027] FIGS. 8 and 9 provide views of vertebral body fixation elements being held in an implantation device according to an embodiment of the subject invention.

[0028] FIG. 10 provides a view of disc implantation device and disc according to an embodiment of the subject invention.

[0029] FIG. 11 provides sequential views of a disc being replaced with a prosthetic disc according to a method of the subject invention.

[0030] FIG. 12 provides a cross-sectional view of a prosthetic disc having a one-piece structure.

[0031] FIG. 13A provides a three-dimensional view of a prosthetic disc having a one-piece structure including a single anchoring fin on each of the upper and lower endplates.

[0032] FIG. 13B provides a three-dimensional view of a prosthetic disc having a one-piece structure including three anchoring fins on each of the upper and lower endplates.

[0033] FIG. 13C provides a three-dimensional view of a prosthetic disc having a one-piece structure including a serrated surface on each of the upper and lower endplates.

[0034] FIG. 13D provides a three-dimensional view of a prosthetic disc having a one-piece structure including a superior dome.

[0035] FIG. 13E provides a three-dimensional view of the prosthetic disc having a one-piece structure of FIG. 13D, having no superior dome.

[0036] FIG. 13F provides a three-dimensional cross-sectional view of the prosthetic disc having a one-piece structure shown in FIG. 13D.

[0037] FIG. 13G provides a three-dimensional view of a prosthetic disc having a one-piece structure design without a gasket retaining ring.

[0038] FIG. 13H provides a three-dimensional cross-sectional view of the prosthetic disc having a one-piece structure shown in FIG. 2G.

[0039] FIG. 13I provides a cross-sectional view of an upper endplate of a prosthetic disc having a one-piece structure design without a gasket retaining ring.

[0040] FIG. 13J provides an inset view of a portion of the upper endplate shown in FIG. 2I.

[0041] FIG. 13K provides a cross-sectional illustration of a prosthetic disc having a one-piece structure design with a center spring.

[0042] FIG. 13L provides a three-dimensional cross-sectional illustration of the prosthetic disc having a one-piece structure shown in FIG. 13K.

[0043] FIGS. 14A and B provide illustrations of uni-directional and bi-directional fiber winding patterns.

[0044] FIGS. 15A-C provide illustrations of an annular capsule.

[0045] FIG. 16 provides a three-dimensional view of a prosthetic disc having a two-piece structure.

[0046] FIG. 17 provides a three-dimensional view of an outer lower endplate of the prosthetic disc shown in FIG. 16.

[0047] FIG. 18 provides a cross-sectional view of a prosthetic disc having a two-piece constrained structure.

[0048] FIG. 19 provides a three-dimensional view of a prosthetic disc having a two-piece unconstrained structure.

[0049] FIG. 20 provides a cross-sectional view of a prosthetic disc having a two-piece unconstrained structure.

[0050] FIG. 21 provides a three-dimensional view of a prosthetic disc having a three-piece structure.

[0051] FIG. 22 provides a three-dimensional view of a lower endplate of the prosthetic disc shown in FIG. 21.

[0052] FIG. 23 provides a cross-sectional view of a prosthetic disc having a three-piece structure.

[0053] FIG. 24A provides a three-dimensional view of a core assembly for a prosthetic disc having a three-piece structure.

[0054] FIG. 24B provides a three-dimensional view of another core assembly for a prosthetic disc having a three-piece structure.

[0055] FIG. 24C provides a three-dimensional view of another core assembly for a prosthetic disc having a three-piece structure.

[0056] FIG. 25A provides a cross-section view of a fiber reinforced core assembly.

[0057] FIG. 25B provides a cross-section view of another fiber reinforced core assembly.

[0058] FIG. 25C provides a cross-section view of another fiber reinforced core assembly.

[0059] FIG. 26 provides a three-dimensional view of a stacked fabric core assembly.

[0060] FIG. 27 provides a cross-sectional view of a stacked fabric core assembly.

[0061] FIG. 28A provides a three-dimensional view of a stacked fabric core assembly.

[0062] FIG. 28B provides a three-dimensional view of another stacked fabric core assembly.

[0063] FIG. 28C provides a three-dimensional view of another stacked fabric core assembly.

[0064] FIG. 29 provides a three-dimensional view of a prosthetic disc having a four-piece structure.

[0065] FIG. 30 provides a cross-sectional view of a prosthetic disc having a four-piece structure.

[0066] FIG. 31 provides an expanded view of a core assembly for a prosthetic disc having a four-piece structure.

[0067] FIG. 32 provides a three-dimensional view of a prosthetic disc having a four-piece structure.

[0068] FIG. 33 provides a cross-sectional view of a prosthetic disc having a four-piece structure.

[0069] FIG. 34 provides a three-dimensional view of a prosthetic disc having a four-piece structure.

[0070] FIG. 35 provides an expanded view of a core assembly for a prosthetic disc having a four-piece structure.

[0071] FIG. 36A provides a perspective view of a spacer.

[0072] FIG. 36B provides a perspective view of the head portion of the spacer shown in FIG. 36A.

[0073] FIG. 37A provides a perspective view of a double-sided chisel.

[0074] FIG. 37B provides a top view of the head portion of the double-sided chisel shown in FIG. 37A.

[0075] FIG. 38A provides a perspective view of a holder.

[0076] FIG. 38B provides a perspective view of the head portion of the holder shown in FIG. 38A.

[0077] FIG. 39 provides a perspective view of a guide member.

[0078] FIG. 40 provides a perspective view of a first chisel and lower endplate insert apparatus.

[0079] FIG. 41 provides a perspective view of an upper endplate holder.

[0080] FIG. 42 provides a perspective view of a second chisel.

[0081] FIG. 43A provides an illustration of a method step of advancing a first chisel and outer lower endplate.

[0082] FIG. 43B provides an illustration showing a pair of adjacent vertebrae during an implantation procedure.

[0083] FIG. 44A provides an illustration of a method step of providing a force separating a first chisel and an outer lower endplate.

[0084] FIG. 44B provides an illustration of a pair of adjacent vertebrae during the method step shown in FIG. 44A.

[0085] FIG. 45A provides an illustration of a guide member and outer lower endplate.

[0086] FIG. 45B provides an illustration of a pair of vertebrae with an outer lower endplate implanted onto the lower vertebra.

[0087] FIG. 46A provides an illustration of a method step of advancing a second chisel.

[0088] FIG. 46B provides an illustration of a pair of adjacent vertebrae during the method step shown in FIG. 46A.

[0089] FIG. 47A provides an illustration of a guide member and outer lower endplate.

[0090] FIG. 47B provides an illustration of a pair of vertebrae with an outer lower endplate implanted onto the lower vertebra.

[0091] FIG. 48A provides an illustration of a method step of advancing a prosthetic disc upper subassembly.

[0092] FIG. 48B provides an illustration of a pair of adjacent vertebrae during the method step shown in FIG. 48A.

[0093] FIG. 49A provides an illustration of a method step of withdrawing an upper endplate holder and guide member.

[0094] FIG. 49B provides an illustration of a pair of vertebrae with a prosthetic disc having been implanted therebetween.

[0095] FIG. 50A provides a three-dimensional view of a preferred prosthetic disc for use with a minimally invasive surgical procedure.

[0096] FIG. 50B provides a three-dimensional view of another preferred prosthetic disc for use with a minimally invasive surgical procedure.

[0097] FIG. 51 provides an illustration of a minimally invasive surgical procedure for implanting a pair of prosthetic discs.

[0098] FIG. 52A provides an illustration of an alternative minimally invasive surgical procedure for implanting a prosthetic disc.

[0099] FIG. 52B provides a schematic illustration of a dual prosthetic disc having a mechanism for separating the discs after implantation.

[0100] FIG. 53 provides a cross-sectional schematic illustration of an anti-creep compression member.

[0101] FIG. 54 provides a cross-sectional illustration of a mechanism for deploying and retracting fins and/or spikes located on prosthetic disc endplate.

DESCRIPTIONS OF THE PREFERRED EMBODIMENTS

[0102] Before the present invention is described, it is to be understood that this invention is not limited to particular embodiments described, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present invention will be limited only by the appended claims.

[0103] Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges is also encompassed within the invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the invention.

[0104] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present invention, the preferred

methods and materials are now described. All publications mentioned herein are incorporated herein by reference to disclose and describe the methods and/or materials in connection with which the publications are cited.

[0105] It must be noted that as used herein and in the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise.

[0106] The publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

[0107] As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present inventions.

[0108] Prosthetic intervertebral discs, methods of using such discs, apparatus for implanting such discs, and methods for implanting such discs are described herein. It is to be understood that the prosthetic intervertebral discs, implantation apparatus, and methods are not limited to the particular embodiments described, as these may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present inventions will be limited only by the appended claims.

[0109] The following description includes three Parts. Part A contains a description of a first set of embodiments of the subject prosthetic intervertebral discs, a review of representative methods for using the prosthetic discs, and a review of systems and kits that include the subject prosthetic discs. The embodiments described in Part A are those illustrated in FIGS. 1-11. Part B contains a description of a second set of embodiments of the subject prosthetic intervertebral discs, methods for using the discs, and apparatus and methods for implanting the discs. The embodiments described in Part B are those illustrated in FIGS. 12-54. Each of the descriptions contained in Parts A and B will be understood to be complete and comprehensive in its own right, as well as describing structures, features, and methods that are suitable for use with those described in the other Part. Part C includes additional information about the descriptions contained herein.

Part A

I. Prosthetic Intervertebral Disc

[0110] As summarized above, the subject invention is directed to a prosthetic intervertebral disc. By prosthetic intervertebral disc is meant an artificial or manmade device that is configured or shaped so that it can be employed as a replacement for an intervertebral disc in the spine of a vertebrate organism, e.g., a mammal, such as a human. The subject prosthetic intervertebral disc has dimensions that permit it to substantially occupy the space between two adjacent vertebral bodies that is present when the naturally occurring disc between the two adjacent bodies is removed, i.e., a void disc space. By substantially occupy is meant that it occupies at least about 75% by volume, such as at least about 80% by

volume or more. The subject discs may have a roughly bean shaped structure analogous to naturally occurring intervertebral body discs which they are designed to replace. In many embodiments the length of the disc ranges from about 15 mm to about 50 mm, such as from about 18 mm to about 46 mm, the width of the disc ranges from about 12 mm to about 30 mm, such as from about 14 mm to about 25 mm and the height of the disc ranges from about 3 mm to about 13 mm, such as from about 5 mm to about 12 mm.

[0111] The subject discs are characterized in that they include both an upper (or top) and lower (or bottom) endplate, where the upper and lower endplates are separated from each other by a fibrous compressible element, where the combination structure of the endplates and fibrous compressible element provides a prosthetic disc that functionally closely mimics real disc. A feature of the subject prosthetic discs is that the top and bottom endplates are held together by at least one fiber, e.g., of the fibrous compressible element, wound around at least one portion of each of the top and bottom endplates. As such, the two endplates (or planar substrates) are held to each other by one or more fibers that are wrapped around at least one domain/portion/area of the upper endplate and lower endplate such that the plates are joined to each other.

[0112] Two different representative intervertebral discs are shown in FIGS. 1A and 1B. As can be seen in FIGS. 1A and 1B, prosthetic discs 10 each include a top endplate 11 and a lower endplate 12. Top and bottom endplates 11 and 12 are planar substrates, where these plates typically have a length from about 12 mm to about 45 mm, such as from about 13 mm to about 44 mm, a width of from about 11 mm to about 28 mm, such as from about 12 mm to about 25 mm and a thickness of from about 0.5 mm to about 4 mm, such as from about 1 mm to about 3 mm. The top and bottom endplates are fabricated from a physiologically acceptable material that provides for the requisite mechanical properties, where representative materials from which the endplates may be fabricated are known to those of skill in the art and include, but are not limited to: titanium, titanium alloys, stainless steel, cobalt/chromium, etc.; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMW-PE), polyether ether ketone (PEEK), etc.; ceramics; graphite; etc. As shown in FIGS. 1A and 1B, separating the top and bottom endplates is a fibrous compressible element 17. The thickness of the fibrous compressible element may vary, but ranges in many embodiments from about 2 mm to about 10 mm, including from about 3 mm to about 8 mm.

[0113] The disc is further characterized in that it includes an annular region 13 (i.e., annulus), which is the region, domain or area that extends around the periphery of the disc, and a nuclear region (i.e., nucleus) 14, which is the region, domain or area in the center of the disc and surrounded by the annulus.

[0114] While in the broadest sense the plates may include a single region around which a fiber is wound in order to hold the plates together, in many embodiments the plates have a plurality of such regions. As shown in FIGS. 1A and 1B, endplates 11 and 12 include a plurality of slots 15 through which fibers, e.g., of the fibrous compressible element, may be passed through or wound, as shown. In many embodiments, the number of different slots present in the periphery of the device ranges from about 4 to about 36, such as from about 5 to about 25. As shown in FIGS. 1A and 1B, at least one fiber 16 of the fibrous compressible element is wrapped

around a region of the top and bottom plates, e.g., by being passed through slots in the top and bottom plates, in order to hold the plates together.

[0115] The fibrous compressible elements, 17, are typically made up of one or more fibers, where the fibers are generally high tenacity fibers with a high modulus of elasticity. By high tenacity fibers is meant fibers that can withstand a longitudinal stress without tearing asunder of at least about 50 MPa, such as at least about 250 MPa. As the fibers have a high modulus of elasticity, their modulus of elasticity is typically at least about 100 MPa, usually at least about 500 MPa. The fibers are generally elongate fibers having a diameter that ranges from about 3 mm to about 8 mm, such as about 4 mm to about 7 mm, where the length of each individual fiber making up the fibrous component may range from about 1 m to about 20 m, such as from about 2 m to about 15 m.

[0116] The fibers making up the fibrous compressible elements may be fabricated from any suitable material, where representative materials of interest include, but are not limited to: polyester (e.g., Dacron), polyethylene, polyaramid, carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinyl polymer, polyphosphazene, polysiloxane, and the like.

[0117] The fibrous compressible elements made up of one or more fibers wound around one or more regions of the top or bottom plates may make up a variety of different configurations. For example, the fibers may be wound in a pattern that has an oblique orientation to simulate the annulus of intact disc, where a representative oblique fiber configuration or orientation is shown in FIG. 1A. The number of layers of fiber winding may be varied to achieve similar mechanical properties to an intact disk. Where desired, compliancy of the structure may be reduced by including a horizontal winding configuration, as shown in FIG. 1B.

[0118] In certain embodiments, the fibrous compressible element 20 has a fibrous component 21 limited to the annular region of the disc 22, e.g., to the region along the periphery of the disc. FIG. 2 provides a representation of this embodiment, where the fibrous component is limited solely to the annular region of the disc and includes both oblique and horizontal windings. Also shown is a separate polymeric component 23 present in the nucleus. The fiber windings of the various layers of fiber may be at varying angles from each other where the particular angle for each layer may be selected to provide a configuration that best mimics the natural disc. Additionally, the tension placed on the fibers of each layer may be the same or varied.

[0119] In yet other embodiments the fibrous component of the fibrous compressible element may extend beyond the annular region of the disc into at least about a portion, if not all, of the nucleus. FIG. 3A provides a view of a fibrous component 30 that occupies both the annular and nuclear regions of the disc, where the annular region of the disc is made up of fiber windings that are both oblique and horizontal, as described above, while the nucleus of the disc is occupied by fibers woven into a three-dimensional network that occupies the nuclear space. Instead of a three-dimensional network structure, one may have multiple two dimensional layers' of interwoven fibers stacked on top of each other, as shown in FIG. 3B, where the multiple stacked layers may be stitched to each other, as shown in FIG. 3C. By adjusting one or more parameters of the fibrous component, such as the density of the fibers, number of layers, frequency of stitching,

the wrapping angle of each fiber layer, and the like, the mechanical properties of the fibrous component can be tailored as desired, e.g., to mimic the mechanical properties of a natural intervertebral disc. Also shown in FIGS. 3B and 3C is the outline of a polymeric component 32 in which the fibrous component 30 is embedded.

[0120] In certain embodiments, the fibrous compressible element further includes one or more polymeric components. The polymeric component(s), when present, may be fabricated from a variety of different physiologically acceptable materials. Representative materials of interest include, but are not limited to: elastomeric materials, such as polysiloxane, polyurethane, poly(ethylene propylene) copolymer, polyvinylchloride, poly(tetrafluoro ethylene) and copolymers, hydrogels, and the like.

[0121] The polymeric component may be limited to particular domains, e.g., the annular and/or nucleus domains, or extend throughout the entire region of the fibrous compressible elements positioned between the two endplates. As such, in certain embodiments the polymeric component is one that is limited to the nuclear region of the disc, as shown in FIG. 2. In FIG. 2, fibrous compressible element 20 includes a distinct fibrous component 21 that is located in the annular region of the disc 22, while polymeric component 23 is located in the nuclear region of the disc. In other embodiments, the polymeric component is located in both the annular and nuclear regions. In yet other embodiments, the polymeric component may be located solely in the annular region.

[0122] Depending on the desired configuration and mechanical properties, the polymeric component may be integrated with the fibrous component, such that at least a portion of the fibers of the fibrous component is embedded in, e.g., complexed with, at least a portion of the polymeric component. In other words, at least a portion of the fibrous component is impregnated with at least a portion of the polymeric component. For example, as shown in FIG. 3B, stacked two-dimensional layers of the fibrous component 30 are present inside the polymeric component 32, such that the fibrous component is impregnated with the polymeric component.

[0123] In those configurations where the fibrous and polymeric components are present in a combined format, e.g., as shown in FIG. 3B, the fibers of the fibrous component may be treated to provide for improved bonding with the polymeric component. Representative fiber treatments of interest include, but are not limited to: corona discharge, O₂ plasma treatment, oxidation by strong acid (HNO₃, H₂SO₄). In addition, surface coupling agents may be employed, and/or a monomer mixture of the polymer may be polymerized in presence of the surface-modified fiber to produce the composite fiber/polymeric structure.

[0124] As indicated above, the devices may include one or more different polymeric components. In those embodiments where two or more different polymeric components are present, any two given polymeric components are considered different if they differ from each other in terms of at least one aspect, e.g., composition, cross-linking density, and the like. As such, the two or more different polymeric components may be fabricated from the same polymeric molecules, but differ from each other in terms of one or more of: cross-linking density; fillers; etc. For example, the same polymeric material may be present in both the annulus and nucleus of the disc, but the crosslink density of the annulus polymeric component may be higher than that of the nuclear region. In yet

other embodiments, polymeric materials that differ from each other with respect to the polymeric molecules from which they are made may be employed.

[0125] By selecting particular fibrous component and polymeric component materials and configurations, e.g., from the different representative formats described above, a disc with desired functional characteristics, e.g., that mimics the functional characteristics of the naturally occurring disc, may be produced.

[0126] Representative particular combinations of interest include, but are not limited to, the following:

[0127] 1. Biocompatible polyurethane, such as Ethicon Biomer, reinforced with Dacron poly(ethylene terephthalate) fiber, or Spectra polyethylene fiber, or Kevlar polyaramide fiber, or carbon fiber.

[0128] 2. Biocompatible polysiloxane modified styrene-ethylene butylene block copolymer sold under C-Flex tradename reinforced with Dacron poly(ethylene terephthalate) fiber, or Spectra polyethylene fiber, or Kevlar polyaramide fiber, or carbon fiber.

[0129] 3. Biocompatible Silastic silicone rubber, reinforced with Dacron poly(ethylene terephthalate) fiber, or Spectra polyethylene fiber, or Kevlar polyaramide fiber, or carbon fiber.

[0130] In using the subject discs, the prosthetic disc is fixed to the vertebral bodies between which it is placed. More specifically, the upper and lower plates of the subject discs are fixed to the vertebral body to which they are adjacent. As such, the subject discs are employed with vertebral body fixation elements during use. In certain embodiments, the vertebral body fixation elements are integral to the disc structure, while in other embodiments the vertebral body fixation elements are separate from the disc structure.

[0131] A representative embodiment of those devices where the vertebral body fixation elements are integral with the disc structure is depicted in FIGS. 4A and 4B. FIG. 4A shows device 40 made up of top and bottom endplates 41 and 42. Integrated with top and bottom endplates 41 and 42 are vertebral body fixation elements 43 and 44. The vertebral body fixation elements include holes through which bone screws may be passed for fixation of the disc to upper and lower vertebral bodies 47 and 48 upon implantation, as represented in FIG. 4B.

[0132] In an alternative embodiment, the disc does not include integrated vertebral body fixation elements, but is designed to mate with separate vertebral body fixation elements, e.g., as depicted in FIG. 7. In other words, the disc is structured to interface with separate vertebral body fixation elements during use. Any convenient separate vertebral body fixation element may be employed in such embodiments, so long as it stably positions the prosthetic disc between two adjacent vertebral bodies.

[0133] One representative non-integrated vertebral body fixation element according to this embodiment is shown in FIGS. 5A and 5B. FIG. 5A provides a representation of the upper plate 50 of a prosthetic disc mated with a vertebral body fixation element 51, as the structures would appear upon implantation. Vertebral body fixation element 51 is a horseshoe shaped structure having spikes 55 at locations corresponding to the cortical bone of vertebrae and porous coating to enhance bone fixation. The fixation element 51 also has gear teeth 52 such that corresponding gear teeth 53 of the disc upperplate 50 can slide through the gear contact resulting in the right location of prosthetic disc with respect to the fixation

element. The gear teeth have a shape such that only inward movement of the upper plate upon implantation is possible. Also present are slots **56** in the spiked fixation elements next to the gear teeth that provide for the elastic deformation of the whole teeth area upon implantation and desirable clearance between mating gear teeth of the disc and fixation element so that incoming gear teeth of the disc can easily slide into the fixation element.

[0134] In the embodiment shown in FIG. **5A**, as the disc is pushed into the fixation element, the protruded rail **57** on the disc slides along the corresponding concave rail-way **58** on the fixation element until the protruded rail on the most front side is pushed into the corresponding concave rail-way on the fixation element, as shown in FIG. **5B**. This rail interface is devised to prevent the upward/downward movement of the top disc endplate and the bottom disc endplate with respect to the corresponding fixation element. This interface between the fixation elements and the top and bottom endplates of the disc enables an easy surgical operation. Specifically, the fixation elements are transferred together to the disc replacement area (disc void space) with an instrument and pushed in the opposite directions toward the vertebrae until they are fixed to the vertebrae, and then the prosthetic disc is transferred by the instrument between the fixation elements and simply pushed inward until the stoppers mate the corresponding stoppers. The prosthetic disc can also be easily removed after long-term use. For its removal, the gear teeth on the fixation element are pushed to reduce the gap of the slot so that the gear engagement between the disc endplate and the fixation element is released.

[0135] An alternative embodiment is depicted in FIGS. **6A** and **6B**. In the embodiment shown in FIGS. **6A** and **6B**, the fixation element **61** and the endplate **62** have a different mating interface from that depicted in FIGS. **5A** and **5B**. As shown in FIGS. **6A** and **6B**, the gear teeth in the endplate are brought in contact with the corresponding gear teeth of the clamping element **63** that is attached to the fixation element **61** through a spring **64**. In this mechanism, the slots next to the gear teeth shown in the embodiment depicted in FIGS. **5A** and **5B** are replaced by a spring attached to the fixation element and this spring deformation provides the necessary recess of the clamping element as the disc endplate is pushed in upon implantation. The gear teeth contact between the endplate and the clamping element allows one way sliding. The disc endplates and the fixation elements have the rail interface as in FIGS. **5A** and **5B** to prevent the vertical movement.

II. Systems

[0136] Also provided are systems that include at least one component of the subject prosthetic discs, as described above. The systems of the subject invention typically include all of the elements that may be necessary and/or desired in order to replace an intervertebral disc with a prosthetic disc as described above. As such, at a minimum the subject systems include a prosthetic disc according to the present invention, as described above. In addition, the systems in certain embodiments include a vertebral body fixation element, or components thereof, e.g., the fixation elements shown in FIGS. **5A** to **6B**, bone screws for securing integrated fixation elements as shown in FIGS. **4A** and **4B**, and the like. The subject systems may also include special delivery devices, e.g., as described in greater detail below.

[0137] One specific representative system of particular interest is depicted in FIG. **7**. The system **70** of FIG. **7** is

depicted as an exploded view, and includes upper and lower fixation elements **71A** and **71B**, and disc **74** made up of top and bottom endplates **72A** and **72B**, as well as the fibrous compressible element **75**, made up of both a fibrous component **73** and polymeric component **76** of the prosthetic disc.

III. Methods of Use

[0138] Also provided are methods of using the subject prosthetic intervertebral discs and systems thereof. The subject prosthetic intervertebral discs and systems thereof find use in the replacement of damaged or dysfunctional intervertebral discs in vertebrate organisms. Generally the vertebrate organisms are "mammals" or "mammalian," where these terms are used broadly to describe organisms which are within the class mammalia, including the orders carnivore (e.g., dogs and cats), rodentia (e.g., mice, guinea pigs, and rats), lagomorpha (e.g. rabbits) and primates (e.g., humans, chimpanzees, and monkeys). In many embodiments, the subjects will be humans.

[0139] In general, the devices are employed by first removing the to be replaced disc from the subject or patient according to standard protocols to produce a disc void space. Next, the subject prosthetic disc is implanted or positioned in the disc void space, resulting in replacement of the removed disc with the prosthetic disc. This implantation step may include a vertebral body fixation element implantation substep, a post implantation vertebral body securing step, or other variations, depending on the particular configuration of the prosthetic device being employed. In addition, the implantation step described above may include use of one or more implantation devices (or disc delivery devices) for implanting the system components to the site of implantation.

[0140] A representative implantation protocol for implanting the device depicted in FIG. **7** is now provided. First, the spine of a subject is exposed via a retroperitoneal approach after sterile preparation. The intervertebral disc in trauma condition is removed, and the cartilage endplates above and below the disc are also removed to the bony end plates to obtain the bleeding surface for the bone growth into porous cavities in the spiked fixation elements **71A** and **72A**. The gap resulting from these removals is measured and the proper artificial disk assembly is chosen according to the measurement.

[0141] The spiked fixation element plates are loaded onto a delivery instrument **80** as shown in FIGS. **8** and **9** such that relative location and orientation between the upper spiked fixation element plate and the lower spiked fixation element plate are kept at a desired configuration. This configuration can be realized by providing appropriate mating features on the instrument and the corresponding mating features on the spiked plates. One of the possible mating features would be the pocket of the instrument and the corresponding external faces of the spiked plates as shown in FIG. **8**. The pocket has the same internal face as the external face of spiked plates but with a slightly smaller size such that the spiked plate fits tightly into the pocket of the instrument. The instrument together with the spiked fixation plates is delivered to the area where the disc was removed and the spiked plates are pushed against the vertebra using the distracting motion of the instrument as shown in FIG. **9**.

[0142] Once the spiked fixation plates are firmly fixed to the vertebra, the prosthetic disc **75** is held by a different tool and inserted into the implanted spiked fixation plates such that its gear teeth go through the matching gear teeth on the spiked

fixation plates. FIG. 10 shows the tool holding the disc. The grippers in FIG. 10 hold the fiber area of the disc when it is in grasp position. The disc accommodating the grippers has the circular concave area in contact with the disc and is pushed into the spiked fixation plates through this contact. When the disc is inserted all the way into the spiked plates, the protruded rails on the disc at its most front side are in contact with the female railway of the spiked fixation plates and the disc is secured between the spiked fixation plates and therefore the vertebra.

[0143] The above-described protocol is depicted in FIG. 11.

[0144] The above specifically reviewed protocol is merely representative of the protocols that may be employed for implanting devices according to the subject invention.

IV. Kits

[0145] Also provided are kits for use in practicing the subject methods, where the kits typically include one or more of the above prosthetic intervertebral disc devices (e.g., a plurality of such devices in different sizes), and/or components of the subject systems, e.g., fixation elements or components thereof, delivery devices, etc. as described above. The kit may further include other components, e.g., site preparation components, etc., which may find use in practicing the subject methods.

[0146] In addition to above-mentioned components, the subject kits typically further include instructions for using the components of the kit to practice the subject methods. The instructions for practicing the subject methods are generally recorded on a suitable recording medium. For example, the instructions may be printed on a substrate, such as paper or plastic, etc. As such, the instructions may be present in the kits as a package insert, in the labeling of the container of the kit or components thereof (i.e., associated with the packaging or sub-packaging) etc. In other embodiments, the instructions are present as an electronic storage data file present on a suitable computer readable storage medium, e.g. CD-ROM, diskette, etc. In yet other embodiments, the actual instructions are not present in the kit, but means for obtaining the instructions from a remote source, e.g. via the internet, are provided. An example of this embodiment is a kit that includes a web address where the instructions can be viewed and/or from which the instructions can be downloaded. As with the instructions, this means for obtaining the instructions is recorded on a suitable substrate.

[0147] It is evident from the above discussion and results that the subject invention provides a significantly improved prosthetic intervertebral disc. Significantly, the subject discs closely imitate the mechanical properties of the fully functional natural discs that they are designed to replace. The subject discs exhibit stiffness in the vertical direction, torsional stiffness, bending stiffness in saggital plane, and bending stiffness in front plane, where the degree of these features can be controlled independently by adjusting the components of the discs, e.g., number of layers of fiber winding, pattern of fiber winding, distribution of impregnated polymer, and the types of impregnated polymers, etc. The fiber reinforced structure of the subject discs prevents the fatigue failure on the inside polymer and the surface treatment on the fiber of certain embodiments eliminates the debris problem, both of which are major disadvantages experienced with certain "rubber-type" artificial disks. The interface mechanism between the fixation plates and the disc plates of certain

embodiments of the subject invention, e.g., as shown in FIG. 7, enables a very easy surgical operation. The surgeon simply needs to push the disc inward after fixing the spiked fixation plates onto the vertebrae. Such embodiments also enable easy removal of the disc in case the surgery brings about an ill effect. The gear teeth on the fixation elements are easily pushed from outside such that the gear engagement between the disc endplates and the fixation elements is released and the disc endplates are pulled out from the spiked plates. In view of the above and other benefits and features provided by the subject invention, it is clear that the subject invention represents a significant contribution to the art.

Part B

[0148] With reference to the embodiments illustrated in FIGS. 12-54, the subject prosthetic discs include upper and lower endplates separated by a core member. In one embodiment, the prosthetic disc comprises an integrated, single-piece structure. In another embodiment, the prosthetic disc comprises a two-piece structure including a lower endplate, and an upper endplate and the core member. The core may be assembled or integrated with either or the two endplates. The two-piece structure may be a constrained structure, wherein the upper endplate assembly is attached to the lower endplate in a manner that prevents relative rotation. Alternatively, the structure may be a semi-constrained or an unconstrained structure, wherein the upper endplate assembly is attached to the lower endplate in a manner that allows relative rotation. In yet another embodiment, the prosthetic disc comprises a three-piece structure including upper and lower endplates and a separable core member that is captured between the upper and lower endplates by a retaining mechanism. Finally, in yet another embodiment, the prosthetic disc comprises a four-piece structure including upper and lower endplates and two separable core assemblies which, together, form a core member. Those of ordinary skill in the art will recognize that five-piece, six-piece, or other multi-piece structures may be constructed by further division of the core member and/or the upper and lower endplates, or by the provision of additional components to the structure.

[0149] The implantation apparatus and methods are adapted to implant the prosthetic discs between two adjacent vertebral bodies of a patient. In a first embodiment, the apparatus includes three implantation tools used to prepare the two adjacent vertebral bodies for implantation and then to implant the prosthetic disc. A first tool, a spacer, is adapted to be inserted between and to separate the two adjacent vertebral bodies to create sufficient space for implanting the prosthetic disc. A second tool, a chisel, includes one or more wedge-shaped cutting blades located on its upper and/or lower surfaces that are adapted to create grooves in the inward facing surfaces of the two adjacent vertebral bodies. A third tool, a holder, includes an engagement mechanism adapted to hold the prosthetic disc in place while it is being implanted, and to release the disc once it has been implanted.

[0150] In another embodiment, the implantation apparatus includes a guide member that engages the lower endplate and that remains in place during a portion of the disc implantation process. A lower pusher member slidably engages the guide member and is used to advance the lower endplate into place between two adjacent vertebral bodies of a patient's spine. An upper pusher member is preferably coupled to the lower pusher member and is used to advance a first chisel into place opposed to the lower endplate between the two adjacent ver-

tebral bodies. Once in place, an upward force is applied to the upper pusher member to cause the first chisel to engage the upper vertebral body and to chisel one or more grooves into its lower surface. A downward force is also applied to the lower pusher member to cause the lower endplate to engage the lower vertebral body and to become implanted. The upper pusher member and first chisel are then removed, as is the lower pusher member. Preferably, a second chisel is then advanced along the guide member and is used to provide additional preparation of the upper vertebral body. After the completion of the preparation by the first chisel and, preferably, the second chisel, the upper endplate and core members of the prosthetic disc are implanted using an upper endplate holder that is advanced along the guide member. After implantation, the upper endplate holder and guide member are removed.

[0151] As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present inventions.

I. Prosthetic Intervertebral Discs

[0152] The prosthetic intervertebral discs are preferably artificial or manmade devices that are configured or shaped so that they can be employed as replacements for an intervertebral disc in the spine of a vertebrate organism, e.g., a mammal, such as a human. The subject prosthetic intervertebral discs have dimensions that permit them to substantially occupy the space between two adjacent vertebral bodies that is present when the naturally occurring disc between the two adjacent bodies is removed, i.e., a disc void space. By substantially occupy is meant that the prosthetic disc occupies a sufficient volume in the space between two adjacent vertebral bodies that the disc is able to perform some or all of the functions performed by the natural disc for which it serves as a replacement. In certain embodiments, subject prosthetic discs may have a roughly bean shaped structure analogous to naturally occurring intervertebral body discs. In many embodiments, the length of the prosthetic discs range from about 15 mm to about 50 mm, preferably from about 18 mm to about 46 mm, the width of the prosthetic discs range from about 12 mm to about 30 mm, preferably from about 14 mm to about 25 mm, and the height of the prosthetic discs range from about 3 mm to about 15 mm, preferably from about 5 mm to about 14 mm.

[0153] The prosthetic discs include upper and lower endplates separated by a core member. The resulting structure provides a prosthetic disc that functionally closely mimics a natural disc.

A. One-Piece Structure

[0154] Representative prosthetic intervertebral discs **100** having one-piece structures are shown in FIGS. **12** through **15**. The prosthetic disc includes an upper endplate **110**, a lower endplate **120**, and a core member **130** retained between the upper endplate **110** and the lower endplate **120**. One or more fibers **140** are wound around the upper and lower endplates to attach the endplates to one another. (For clarity, the fibers **140** are not shown in all of the Figures. Nevertheless, fibers **140**, as shown, for example, in FIG. **12**, are present in

and perform similar functions in each of the embodiments described herein.) The fibers **140** preferably are not tightly wound, thereby allowing a degree of axial rotation, bending, flexion, and extension by and between the endplates. The core member **130** may be provided in an uncompressed or a pre-compressed state. An annular capsule **150** is optionally provided in the space between the upper and lower endplates, surrounding the core member **130** and the fibers **140**. The upper endplate **110** and lower endplate **120** are generally flat, planar members, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the upper endplate **110** and lower endplate **120** include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. Optionally, the endplates may be coated with hydroxyapatite, titanium plasma spray, or other coatings to enhance bony ingrowth.

[0155] As noted above, the upper and lower endplates typically have a length of from about 12 mm to about 45 mm, preferably from about 13 mm to about 44 mm, a width of from about 11 mm to about 28 mm, preferably from about 12 mm to about 25 mm, and a thickness of from about 0.5 mm to about 4 mm, preferably from about 1 mm to about 3 mm. The sizes of the upper and lower endplates are selected primarily based upon the size of the void between adjacent vertebral bodies to be occupied by the prosthetic disc. Accordingly, while endplate lengths and widths outside of the ranges listed above are possible, they are not typical.

[0156] The upper surface of the upper endplate **110** and the lower surface of the lower endplate **120** are preferably each provided with a mechanism for securing the endplate to the respective opposed surfaces of the upper and lower vertebral bodies between which the prosthetic disc is to be installed. For example, in FIG. **12**, the upper endplate **110** includes a plurality of anchoring fins **111a-b**. The anchoring fins **111a-b** are intended to engage mating grooves that are formed on the surfaces of the upper and lower vertebral bodies to thereby secure the endplate to its respective vertebral body. The anchoring fins **111a-b** extend generally perpendicularly from the generally planar external surface of the upper endplate **110**, i.e., upward from the upper side of the endplate as shown in FIG. **12**. In the FIG. **12** embodiment, the upper endplate **110** includes three anchoring fins **111a-c**, although only two are shown in the cross-sectional view. A first of the anchoring fins, **111a**, is disposed near an external edge of the external surface of the upper endplate and has a length that approximates the width of the upper endplate **110**. A second of the anchoring fins, **111b**, is disposed at the center of external surface of the upper endplate and has a relatively shorter length, substantially less than the width of the upper endplate **110**. Each of the anchoring fins **111a-b** has a plurality of serrations **112** located on the top edge of the anchoring fin. The serrations **112** are intended to enhance the ability of the anchoring fin to engage the vertebral body and to thereby secure the upper endplate **110** to the spine.

[0157] Similarly, the lower surface of the lower endplate **120** includes a plurality of anchoring fins **121a-b**. The anchoring fins **121a-b** on the lower surface of the lower endplate **120** are identical in structure and function to the anchoring fins **111a-b** on the upper surface of the upper endplate **110**, with

the exception of their location on the prosthetic disc. The anchoring fins **121a-b** on the lower endplate **120** are intended to engage mating grooves formed on the lower vertebral body, whereas the anchoring fins **111a-b** on the upper endplate **110** are intended to engage mating grooves on the upper vertebral body. Thus, the prosthetic disc **100** is held in place between the adjacent vertebral bodies.

[0158] The anchoring fins **111**, **121** may optionally be provided with one or more holes or slots **115**, **125**. The holes or slots help to promote bony ingrowths that bond the prosthetic disc **100** to the vertebral bodies.

[0159] Turning to FIGS. **13A-C**, there are shown several alternative mechanisms for securing the endplates to the respective opposed surfaces of the upper and lower vertebral bodies between which the prosthetic disc is to be installed. In FIG. **13A**, each of the upper endplate **110** and lower endplate **120** is provided with a single anchoring fin **111**, **121**. The anchoring fins **111**, **121** are located along a center line of the respective endplates, and each is provided with a plurality of serrations **112**, **122** on its upper edge. The single anchoring fins **111**, **121** are intended to engage grooves formed on the opposed surface of the upper and lower vertebral bodies, as described above. In FIG. **13B**, each of the upper endplate **110** and lower endplate **120** is provided with three anchoring fins **111a-c**, **121a-c**. The FIG. **13B** prosthetic disc is the same as the prosthetic disc shown in FIG. **1**, but it is shown in perspective rather than cross-section. Thus, the structure and function of the anchoring fins **111a-c** and **121a-c** are as described above in relation to FIG. **12**. Finally, in FIG. **13C**, each of the upper endplate **110** and lower endplate **120** is provided with a plurality of serrations **113**, **123** over a portion of the exposed external surface of the respective endplate. The serrations **113**, **123** are intended to engage the opposed surfaces of the adjacent vertebral bodies to thereby secure the endplates in place between the vertebral bodies. The serrations **113**, **123** may be provided over the entire external surface of each of the upper and lower endplates, or they may be provided over only a portion of those surfaces. For example, in FIG. **13C**, the serrations **113** on the upper surface of the upper endplate **110** are provided over three major areas, a first area **113a** near a first edge of the upper endplate **110**, a second area **113b** near the center of the upper endplate **110**, and a third area near a second edge of the endplate **113c**.

[0160] Turning to FIG. **54**, in an optional embodiment, the anchoring fins **111** are selectively retractable and extendable by providing a deployment mechanism **160** that is associated with the upper endplate **110**. A similar mechanism may be used on the lower endplate **120**. The deployment mechanism includes a slider **161** that slides within a channel **162** formed in the upper endplate **110**. The channel **162** includes a threaded region **163**, and the slider **161** includes matching threads **164**, thereby providing a mechanism for advancing the slider **161** within the channel **162**. As the slider **161** is advanced within the channel **162**, a tapered region **165** engages the bottom surface of a deployable fin **166**. Further advancement of the slider **161** causes the deployable fin **166** to be raised upward within a slot **167** on the upper surface of the upper endplate **110**. Reversing the deployment mechanism **160** causes the fin **166** to retract. The deployment mechanism **160** may also be used in conjunction with spikes, serrations, or other anchoring devices. In an alternative embodiment, the threaded slider **161** of the deployment

mechanism may be replaced with a dowel pin that is advanced to deploy the fin **166**. Other advancement mechanisms are also possible.

[0161] Returning to FIG. **12**, the upper endplate **110** contains a plurality of slots **114** through which the fibers **140** may be passed through or wound, as shown. The actual number of slots **114** contained on the endplate is variable. Increasing the number of slots will result in an increase in the circumferential density of the fibers holding the endplates together. In addition, the shape of the slots may be selected so as to provide a variable width along the length of the slot. For example, the width of the slots may taper from a wider inner end to a narrow outer end, or visa versa. Additionally, the fibers may be wound multiple times within the same slot, thereby increasing the radial density of the fibers. In each case, this improves the wear resistance and increases the torsional and flexural stiffness of the prosthetic disc, thereby further approximating natural disc stiffness. In addition, the fibers **140** may be passed through or wound on each slot, or only on selected slots, as needed. Two exemplary winding patterns are shown in FIGS. **14A** and **14B**. In FIG. **14A**, the fibers **140** are wound in a uni-directional manner, which closely mimics natural annular fibers found in a natural disc. In FIG. **14B**, the fibers **140** are wound bi-directionally. Other winding patterns, either single or multi-directional, are also possible.

[0162] As described above, the purpose of the fibers **140** is to hold the upper endplate **110** and lower endplate **120** together and to limit the range-of-motion to mimic the range-of-motion of a natural disc. Accordingly, the fibers preferably comprise high tenacity fibers with a high modulus of elasticity, for example, at least about 100 MPa, and preferably at least about 500 MPa. By high tenacity fibers is meant fibers that can withstand a longitudinal stress of at least 50 MPa, and preferably at least 250 MPa, without tearing. The fibers **140** are generally elongate fibers having a diameter that ranges from about 100 μm to about 500 μm , and preferably about 200 μm to about 400 μm . Optionally, the fibers may be injection molded with an elastomer to encapsulate the fibers, thereby providing protection from tissue ingrowth and improving torsional and flexural stiffness, or the fibers may be coated with one or more other materials to improve fiber stiffness and wear. Additionally, the core may be injected with a wetting agent such as saline to wet the fibers and facilitate the mimicking of the viscoelastic properties of a natural disc.

[0163] The fibers **140** may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron®), polyethylene, polyaramid, poly-paraphenylene terephthalamide (e.g., Kevlar®), carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like.

[0164] The fibers **140** may be terminated on an endplate by tying a knot in the fiber on the superior surface of an endplate. Alternatively, the fibers **140** may be terminated on an endplate by slipping the terminal end of the fiber into a slot on an edge of an endplate, similar to the manner in which thread is retained on a thread spool. The slot may hold the fiber with a crimp of the slot structure itself, or by an additional retainer such as a ferrule crimp. As a further alternative, tab-like crimps may be machined into or welded onto the endplate structure to secure the terminal end of the fiber. The fiber may then be closed within the crimp to secure it. As a still further

alternative, a polymer may be used to secure the fiber to the endplate by welding. The polymer would preferably be of the same material as the fiber (e.g., PE, PET, or the other materials listed above). Still further, the fiber may be retained on the endplates by crimping a cross-member to the fiber creating a T-joint, or by crimping a ball to the fiber to create a ball joint.

[0165] The core member 130 is intended to provide support to and to maintain the relative spacing between the upper endplate 110 and lower endplate 120. The core member 130 is made of a relatively compliant material, for example, polyurethane or silicone, and is typically fabricated by injection molding. A preferred construction for the core member includes a nucleus formed of a hydrogel and an elastomer reinforced fiber annulus. For example, the nucleus, the central portion of the core member 130, may comprise a hydrogel material such as a water absorbing polyurethane, polyvinyl alcohol (PVA), polyethylene oxide (PEO), polyvinylpyrrolidone (PVP), polyacrylamide, silicone, or PEO based polyurethane. The annulus may comprise an elastomer, such as silicone, polyurethane or polyester (e.g., Hytrel®), reinforced with a fiber, such as polyethylene (e.g., ultra high molecular weight polyethylene, UHMWPE), polyethylene terephthalate, or poly-paraphenylene terephthalamide (e.g., Kevlar®).

[0166] The shape of the core member 130 is typically generally cylindrical or bean-shaped, although the shape (as well as the materials making up the core member and the core member size) may be varied to obtain desired physical or performance properties. For example, the core member 130 shape, size, and materials will directly affect the degree of flexion, extension, lateral bending, and axial rotation of the prosthetic disc.

[0167] The annular capsule 150 is preferably made of polyurethane or silicone and may be fabricated by injection molding, two-part component mixing, or dipping the endplate-core-fiber assembly into a polymer solution. A preferred annular capsule 150 is shown in FIGS. 15A-C. As shown, the annular capsule is generally cylindrical, having an upper circular edge 153, a lower circular edge 154, and a generally cylindrical body 155. In the embodiment shown in the Figures, the body 155 has two bellows 156a-b formed therein. Alternative embodiments have no bellows, one bellow, or three or more bellows. A function of the annular capsule is to act as a barrier that keeps the disc materials (e.g., fiber strands) within the body of the disc, and that keeps natural in-growth outside the disc.

[0168] Additional examples of the one-piece structure embodiment of the prosthetic disc are illustrated in FIGS. 13D-F. Each of these embodiments includes an upper endplate 110, lower endplate 120, and a core member 130, as described above. The upper endplate 110 includes an outer portion 110a and an inner portion 110b, and the lower endplate also includes an outer portion 120a and an inner portion 120b. The inner and outer portions of each of the endplates are bonded to each other by methods known to those of skill in the art. Each of the endplates 110, 120 also includes anchoring fins 111a-c, 121a-c on the upper surface of the upper endplate 110 and the lower surface of the lower endplate 120, as also described above. Additionally, with reference to FIG. 13D, a superior dome 116 is provided on the upper surface of the upper endplate 110. The superior dome 116 is a generally convex portion that extends upward from the upper surface of the upper endplate 110. The superior dome 116 is optional,

and functions by filling space between the upper endplate 110 and the vertebral body upon implantation to help approximate the upper endplate 110 to the natural anatomy. The size and shape of the superior dome 116 may be varied according to need. As shown in FIG. 13D, the superior dome 116 is generally convex and has a maximum height (distance above the generally flat upper surface portion of the upper endplate) of approximately one-half the height of the anchoring fin 111b. The superior dome 116 may be centered in the middle of the upper endplate 110, as shown in FIG. 2D, or it may be shifted to one side or another, depending on need.

[0169] With particular reference to FIG. 13F, a polymer film 170 is sandwiched between the outer portion 10a and inner portion 10b of the upper endplate 110, and another polymer film 170 is sandwiched between the outer portion 120a and inner portion 120b of the lower endplate 120. The polymer films 170 are adapted to tightly adhere, either mechanically or chemically, to the fibers 140 wound through the slots 114, 124 formed in the upper endplate 110 and lower endplate 120.

[0170] FIGS. 13D-F provide additional detail concerning the annular capsule 150. As shown there, the annular capsule 150 seals the interior space between the upper and lower endplates. The annular capsule 150 is retained on the disc by a pair of retaining rings 151 that engage a mating pair of external facing grooves 152 on the upper and lower endplates. (See FIG. 13F). Although the retaining rings may be of any suitable cross-section (e.g., round, triangular, square, etc.), the examples shown in FIG. 13F have a rectangular cross-section. The rectangular shape is believed to provide relatively better gasket retention and is more easily manufactured.

[0171] FIGS. 13G and 13H illustrate still further examples of the one-piece structure embodiment of the prosthetic disc. In the examples shown there, the upper endplate 110 includes an outer portion 110a and an inner portion 110b. Similarly, the lower endplate 120 includes an outer portion 120a and an inner portion 120b. The two portions 110a-b, 120a-b of each of the upper and lower endplates mate together to form the integrated upper endplate 110 and lower endplate 120. Preferably, the two portions 110a-b, 120a-b of the upper and lower endplates 110, 120 are joined together by welding, e.g., laser welding or some similar process. An advantage that may be obtained with this structure is the ability to retain the annular capsule 150 (not shown in FIGS. 13G-H) without the need for a separate retaining ring. For example, the upper edge of the annular capsule may be captured and retained between the outer portion 110a and inner portion 110b of the upper endplate 110 when they are attached to one another. Similarly, the lower edge of the annular capsule may be captured and retained between the outer portion 120a and inner portion 120b of the lower endplate 120 when those components are attached to one another. In this manner, the annular capsule is held in place between the upper and lower endplates by the compression forces retaining the upper and lower edges of the annular capsule.

[0172] An optional structure for retaining the annular capsule 150 is illustrated in FIGS. 13I-J. There, an upper endplate 110 is shown including an outer portion 110a and an inner portion 110b. The upper surface of the inner portion 110b of the upper endplate 110 is provided with an annular groove 117 that extends about the periphery of the inner portion 110b. The annular groove 117 cooperates with the bottom surface of the outer portion 110a of the upper endplate 110 to

create an annular space **118**. A similar structure, not shown in the drawings, may be provided on the lower endplate **120**. The annular capsule **150** (not shown in FIGS. **13I-J**) may advantageously be formed having a bead, i.e., a ball-like termination about its upper and lower edge, (also not shown in the drawings), that occupies the annular space **118** formed on the upper and lower endplates **110**, **120**. The cooperation of the annular space **118** with the bead formed on the annular capsule **150** creates a stronger and more secure retaining force for retaining the upper and lower edge of the annular capsule **150** by the upper and lower endplates **110**, **120**. Alternatively, the annular capsule may be retained by adhesives with or without the endplate compression already described.

[0173] Another optional feature of the present invention is the placement of the fibers in a state of tensile fatigue upon fabrication so as to minimize long-term wear. For example, in the embodiment of FIGS. **13I-J**, a material **131** such as a metal plate or a polymer film may be positioned within space **119** of upper portion **110a** of the endplate and between the fibers **127** and the surface of the endplate. The material may initially be in a form, e.g., gel or emulsion, so as to coat and impregnate the fibers. With such material, the fibers are caused to impinge upon the endplate thereby reducing their susceptibility to movement during use of the disc. As an additional optional feature, each of the endplates may be made up of two plates that are selectively rotationally displaceable relative to each other. In this structure, a slight rotation of one of the plates relative to the other has the effect of changing the size and/or shape of the slots formed on the combined endplate. Thus, the user is able to select a desired set of dimensions of the slots.

[0174] FIGS. **13K-L** illustrate another optional feature that may be incorporated in the one-piece structure embodiment of the prosthetic disc. In the examples shown there, a spring **180** is located coaxially with the core member **130** between the upper endplate **110** and lower endplate **120**. In this example, the core member **130** is in the form of a toroid, thus having a space at its center. The spring **180** is placed in the space at the center of the core member **130**, with each being retained between the upper endplate **110** and lower endplate **120**. The spring **180** provides a force biasing the two endplates apart, and having performance characteristics and properties that are different from those provided by the core member **130**. Those characteristics may be varied by, for example, selecting a spring **180** having different dimensions, materials, or a different spring constant. In this way, the spring **180** provides an additional mechanism by which the performance of the prosthetic disc may be varied in order to approximate that of a natural disc.

[0175] Turning to FIGS. **50A-B**, additional examples of the one-piece structure embodiment of the prosthetic discs are shown. The discs illustrated in FIGS. **50A-B** are particularly adapted in size and shape for implantation by minimally invasive surgical procedures, as described below. Aside from their size and shape, the structures of the examples shown in FIGS. **50A-B** are similar to those described above, including an upper endplate **110**, lower endplate **120**, a core member **130**, and an annular capsule **150**. Each of the upper and lower endplates **110**, **120** is provided with an anchoring fin **111**, **121** extending from its surface over most of the length of the endplate. Although not shown in the drawings, these examples also preferably include fibers **140** wound between and connecting the upper endplate **110** to the lower endplate **120**.

[0176] In the example shown in FIG. **50A**, a single elongated core member is provided, whereas the example structure shown in FIG. **50B** has a dual core including two generally cylindrical core members **130a**, **130b**. It is believed that the dual core structure (FIG. **50B**) better simulates the performance characteristics of a natural disc. In addition, the dual core structure is believed to provide less stress on the fibers **140** relative to the single core structure (FIG. **50A**). Each of the exemplary prosthetic discs shown in FIGS. **50A-B** has a greater length than width. Exemplary shapes to provide these relative dimensions include rectangular, oval, bullet-shaped, or others. This shape facilitates implantation of the discs by the minimally invasive procedures described below.

[0177] The one-piece structure embodiment of the prosthetic disc is implanted by a surgical procedure. After removing the natural disc, grooves are formed in the superior and inferior vertebrae between which the prosthetic disc is to be implanted. The prosthetic disc is then inserted into the void, while aligning the anchoring fins **111**, **121** with the grooves formed on the vertebral bodies. The anchoring fins cause the prosthetic disc to be secured in place between the adjacent vertebral bodies. The prosthetic disc has several advantages over prior art artificial discs, as well as over alternative treatment procedures such as spinal fusion. For example, the prosthetic discs described herein provide compressive compliance similar to that of a natural spinal disc. In addition, the motions in flexion, extension, lateral bending, and axial rotation are also restricted in a manner near or identical to those associated with a natural disc.

B. Two-Piece Structure

[0178] Representative prosthetic intervertebral discs **200** having two-piece structures are shown in FIGS. **16** through **20**. The components and features included in the two-piece prosthetic discs are very similar to those of the one-piece disc described above. A primary difference between the devices is that the two-piece prosthetic disc contains two separable components, whereas the one-piece prosthetic disc contains a single, integrated structure. In particular, and as described more fully below, the lower endplate of the two-piece prosthetic disc is separated into an inner lower endplate **220a**, and an outer lower endplate **220b** (see FIGS. **16-20**), whereas there is only a single lower endplate **120** in the one-piece disc (see FIGS. **12** and **13A-C**).

[0179] Turning to FIGS. **16-20**, the two-piece prosthetic disc includes two primary, separable components: the outer lower endplate **220b**, and an upper subassembly **205**. In a first embodiment of the two-piece prosthetic disc, shown in FIGS. **16-18**, the upper subassembly **205** is constrained, i.e., it cannot freely rotate in relation to the outer lower endplate **220b**. In a second embodiment of the two-piece prosthetic disc, shown in FIGS. **19-20**, the upper subassembly **205** is unconstrained, i.e., it can substantially freely rotate in relation to the outer lower endplate **220b**.

[0180] The upper subassembly includes the inner lower endplate **220a**, an upper endplate **210**, and a core member **230** retained between the upper endplate **210** and the inner lower endplate **220a**. One or more fibers **240** are wound around the upper and inner lower endplates to attach the endplates to one another. The fibers **240** preferably are not tightly wound, thereby allowing a degree of axial rotation, bending, flexion, and extension by and between the endplates. The core member **230** is preferably pre-compressed. An annular capsule **250**

is optionally provided in the space between the upper and inner lower endplates, surrounding the core member **230** and the fibers **240**. Alternatively, an outer ring or gasket (not shown in the drawings) may optionally be provided in place of the annular capsule **250**.

[0181] The upper endplate **210** and outer lower endplate **220b** are generally flat, planar members, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the upper endplate **210** and outer lower endplate **220b** include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. Optionally, the endplates may be coated with hydroxyapatite, titanium plasma spray, or other coatings to enhance bony ingrowth.

[0182] As noted above, the upper and outer lower endplates typically have a length of from about 12 mm to about 45 mm, preferably from about 13 mm to about 44 mm, a width of from about 11 mm to about 28 mm, preferably from about 12 mm to about 25 mm, and a thickness of from about 0.5 mm to about 4 mm, preferably from about 1 mm to about 3 mm. The sizes of the upper and outer lower endplates are selected primarily based upon the size of the void between adjacent vertebral bodies to be occupied by the prosthetic disc. Accordingly, while endplate lengths and widths outside of the ranges listed above are possible, they are not typical.

[0183] The upper surface of the upper endplate **210** and the lower surface of the outer lower endplate **220b** are preferably each provided with a mechanism for securing the endplate to the respective opposed surfaces of the upper and lower vertebral bodies between which the prosthetic disc is to be implanted. For example, as shown in FIGS. **16** and **18-20**, the upper endplate **210** includes a plurality of anchoring fins **211a-c**. The anchoring fins **211a-c** are intended to engage mating grooves that are formed on the surfaces of the upper and lower vertebral bodies to thereby secure the endplate to its respective vertebral body. The anchoring fins **211a-c** extend generally perpendicular from the generally planar external surface of the upper endplate **210**, i.e., upward from the upper side of the endplate as shown in FIG. **16**. In the FIG. **16** embodiment, the upper endplate **210** includes three anchoring fins **211a-c**. The first and third of the anchoring fins, **211a** and **211c**, are disposed near the external edges of the external surface of the upper endplate **210** and have lengths that approximate the width of the upper endplate **210**. The second of the anchoring fins, **211b**, is disposed at the center of external surface of the upper endplate and has a relatively shorter length, substantially less than the width of the upper endplate **210**. Each of the anchoring fins **211a-c** has a plurality of serrations **212** located on the top edge of the anchoring fin. The serrations **212** are intended to enhance the ability of the anchoring fin to engage the vertebral body and to thereby secure the upper endplate **210** to the vertebral body.

[0184] The lower surface of the outer lower endplate **220b** includes a plurality of anchoring spikes **221**. The anchoring spikes **221** on the lower surface of the outer lower endplate **220b** are intended to engage the surface of the lower vertebral body, while the anchoring fins **211a-c** on the upper endplate **210** are intended to engage mating grooves on the upper

vertebral body. Thus, the prosthetic disc **200** is held in place between the adjacent vertebral bodies.

[0185] Alternatively, the upper endplate **210** and outer lower endplate **220b** of the two-piece prosthetic disc may employ one of the alternative securing mechanisms shown in FIGS. **13A-C**. As described above, in FIG. **13A**, each of the upper endplate **110** and lower endplate **120** is provided with a single anchoring fin **111**, **121**. The anchoring fins **111**, **121** are located along a center line of the respective endplates, and each is provided with a plurality of serrations **112**, **122** on its upper edge. The single anchoring fins **111**, **121** are intended to engage grooves formed on the opposed surface of the upper and lower vertebral bodies, as described above. In FIG. **13B**, each of the upper endplate **110** and lower endplate **120** is provided with three anchoring fins **111a-c**, **121a-c**. The FIG. **13B** prosthetic disc is the same as the prosthetic disc shown in FIG. **12**, but it is shown in perspective rather than cross-section. Thus, the structure and function of the anchoring fins **111a-c** and **121a-c** are as described above in relation to FIG. **12**. Finally, in FIG. **13C**, each of the upper endplate **110** and lower endplate **120** is provided with a plurality of serrations **113**, **123** over a portion of the exposed external surface of the respective endplate. The serrations **113**, **123** are intended to engage the opposed surfaces of the adjacent vertebral bodies to thereby secure the endplates in place between the vertebral bodies. The serrations **113**, **123** may be provided over the entire external surface of each of the upper and lower endplates, or they may be provided over only a portion of those surfaces. For example, in FIG. **13C**, the serrations **113** on the upper surface of the upper endplate **110** are provided over three major areas, a first area **113a** near a first edge of the upper endplate **110**, a second area **113b** near the center of the upper endplate **110**, and a third area near a second edge of the endplate **113c**.

[0186] Turning to FIG. **54**, in an optional embodiment, the anchoring fins **111** are selectively retractable and extendable by providing a deployment mechanism **160** that is associated with the upper endplate **110**. A similar mechanism may be used on the lower endplate **120**. The deployment mechanism includes a slider **161** that slides within a channel **162** formed in the upper endplate **110**. The channel **162** includes a threaded region **163**, and the slider **161** includes matching threads **164**, thereby providing a mechanism for advancing the slider **161** within the channel **162**. As the slider **161** is advanced within the channel **162**, a tapered region **165** engages the bottom surface of a deployable fin **166**. Further advancement of the slider **161** causes the deployable fin **166** to be raised upward within a slot **167** on the upper surface of the upper endplate **110**. Reversing the deployment mechanism **160** causes the fin **166** to retract. The deployment mechanism **160** may also be used in conjunction with spikes, serrations, or other anchoring devices. In an alternative embodiment, the threaded slider **161** of the deployment mechanism may be replaced with a dowel pin that is advanced to deploy the fin **166**. Other advancement mechanisms are also possible.

[0187] Returning to FIG. **18**, the upper endplate **210** contains a plurality of slots **214** through which the fibers **240** may be passed through or wound, as shown. The actual number of slots **214** contained on the endplate is variable. Increasing the number of slots will result in an increase in the circumferential density of the fibers holding the endplates together. Additionally, the fibers may be wound multiple times within the same slot, thereby increasing the radial density of the fibers.

In each case, this improves the wear resistance and increases the torsional and flexural stiffness of the prosthetic disc, thereby further approximating natural disc stiffness. In addition, the fibers **240** may be passed through or wound on each slot, or only on selected slots, as needed.

[0188] As described above, the purpose of the fibers **240** is to hold the upper endplate **210** and lower endplate **220** together and to limit the range-of-motion to mimic the range-of-motion of a natural disc. Accordingly, the fibers preferably comprise high tenacity fibers with a high modulus of elasticity, for example, at least about 100 MPa, and preferably at least about 500 MPa. By high tenacity fibers is meant fibers that can withstand a longitudinal stress of at least 50 MPa, and preferably at least 250 MPa, without tearing. The fibers **240** are generally elongate fibers having a diameter that ranges from about 100 μm to about 500 μm , and preferably about 200 μm to about 400 μm . Optionally, the fibers may be injection molded with an elastomer to encapsulate the fibers, thereby providing protection from tissue ingrowth and improving torsional and flexural stiffness.

[0189] The fibers **240** may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron®), polyethylene, polyaramid, poly-paraphenylene terephthalamide (e.g., Kevlar®), carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like.

[0190] The fibers **240** may be terminated on an endplate by tying a knot in the fiber on the superior surface of an endplate. Alternatively, the fibers **240** may be terminated on an endplate by slipping the terminal end of the fiber into a slot on an edge of an endplate, similar to the manner in which thread is retained on a thread spool. The slot may hold the fiber with a crimp of the slot structure itself, or by an additional retainer such as a ferrule crimp. As a further alternative, tab-like crimps may be machined into or welded onto the endplate structure to secure the terminal end of the fiber. The fiber may then be closed within the crimp to secure it. As a still further alternative, a polymer may be used to secure the fiber to the endplate by welding. The polymer would preferably be of the same material as the fiber (e.g., PE, PET, or the other materials listed above). Still further, the fiber may be retained on the endplates by crimping a cross-member to the fiber creating a T-joint, or by crimping a ball to the fiber to create a ball joint.

[0191] The core member **230** is intended to provide support to and to maintain the relative spacing between the upper endplate **210** and inner lower endplate **220a**. The core member **230** is made of a relatively compliant material, for example, polyurethane or silicone, and is typically fabricated by injection molding. A preferred construction for the core member **230** includes a nucleus formed of a hydrogel and an elastomer reinforced fiber annulus. For example, the nucleus, the central portion of the core member **230**, may comprise a hydrogel material such as tecophilic water absorbing polyurethane, polyvinyl alcohol (PVA), polyethylene oxide (PEO), polyvinylpyrrolidone (PVP), polyacrylamide, silicone, or PEO based polyurethane. The annulus may comprise an elastomer, such as silicone, polyurethane or polyester (e.g., Hytrel®), reinforced with a fiber, such as polyethylene, polyethylene terephthalate, or poly-paraphenylene terephthalamide (e.g., Kevlar®).

[0192] The shape of the core member **230** is typically generally cylindrical or bean-shaped, although the shape (as well as the materials making up the core member and the core member size) may be varied to obtain desired physical or performance properties. For example, the core member **230** shape, size, and materials will directly affect the degree of flexion, extension, lateral bending, and axial rotation of the prosthetic disc.

[0193] The annular capsule **250** is preferably made of polyurethane or silicone and may be fabricated by injection molding, two-part component mixing, or dipping the endplate-core-fiber assembly into a polymer solution. Alternatively, an outer ring or gasket (not shown in the drawings) may optionally be provided in place of the annular capsule **250**.

[0194] The upper subassembly **205** is configured to be selectively attached to the outer lower endplate **220b**. As shown, for example, in FIGS. 3 and 6, the edges **225** of the inner lower endplate **220a** have a size and shape adapted to engage slots **226** formed on the upper surface of the outer lower endplate **220b**. Accordingly, the upper subassembly **205** will slide onto the outer lower endplate **220b**, with the inner lower endplate edges **225** engaging the outer lower endplate slots **226**.

[0195] At this point, the differences between the constrained, semi-constrained and unconstrained embodiments of the two-piece prosthetic disc will be described. Turning first to the constrained embodiment shown in FIGS. 16-18, once the upper subassembly **205** is fully advanced onto the outer lower endplate **220b**—i.e., once the leading edge **225** of the inner lower endplate **220a** engages the back portion of the slot **226** of the outer lower endplate **220b**—a tab **261** on the bottom surface of the inner lower endplate **220a** engages a notch **262** on the top surface of the outer lower endplate **220b** (see FIG. 18), thereby locking the upper subassembly **205** to the outer lower endplate **220b**. The tab **261** and notch **262** are squared surfaces, thereby preventing relative rotation between the inner lower endplate **220a** and outer lower endplate **220b**. Additionally, the edges **225** of the inner lower endplate **220a** and the mating slots **226** of the outer lower endplate **220b** include mating straight portions **227** and **228**, respectively, which also tend to inhibit rotation of the inner lower endplate **220a** relative to the outer lower endplate **220b**.

[0196] Turning next to the unconstrained embodiment shown in FIGS. 19-20, the outer lower endplate **220b** is provided with a raised lip **271**. The raised lip **271** is slightly downwardly displaceable, i.e., the raised lip **271** will deflect downwardly when force is applied to it. Accordingly, when the upper subassembly is being attached to the outer lower endplate **220b**, the raised lip will displace downwardly to allow the edges **225** of the inner lower endplate **220a** to engage the slots **226** of the outer lower endplate **220b**. Once the upper subassembly **205** is fully advanced onto the outer lower endplate **220b**—i.e., once the leading edge **225** of the inner lower endplate **220a** engages the back portion of the slot **226** of the outer lower endplate **220b**—the raised lip **271** snaps back into place, as shown in FIG. 20, thereby locking the upper subassembly **205** to the outer lower endplate **220b**. Notably, the raised lip **271** and inner lower endplate **220a** include rounded surfaces, thereby allowing relative rotation between the inner lower endplate **220a** and outer lower endplate **220b**. Additionally, the edges **225** of the inner lower endplate **220a** and the mating slots **226** of the outer lower endplate **220b** do not include the mating straight portions **227**, **228** of the constrained embodiment. Thus, in the uncon-

strained embodiment of the two-piece prosthetic disc, as shown in FIGS. 19 and 20, the upper subassembly 205 is capable of substantially free rotation relative to the outer lower endplate 220b.

[0197] The two-piece structure embodiment of the prosthetic disc is implanted by a surgical procedure. After removing the natural disc, the outer lower endplate 220b is placed onto and anchored into the inferior vertebral body within the void between the two adjacent vertebral bodies previously occupied by the natural disc. Next, grooves are formed in the superior vertebral body. The upper subassembly 205 of the prosthetic disc is then inserted into the void, while aligning the anchoring fins 211 with the grooves formed on the superior vertebral body, and while sliding the inner lower endplate 220a into the outer lower endplate 220b in a manner that the edges 225 of the inner endplate 220a engage the slots 226 of the outer endplate 220b. The anchoring fins cause the prosthetic disc to be secured in place between the adjacent vertebral bodies.

[0198] The two-piece prosthetic disc has several advantages over prior art artificial discs, as well as over alternative treatment procedures such as spinal fusion. For example, the two-piece prosthetic discs described herein provide compressive compliance similar to that of a natural spinal disc. In addition, the motions in flexion, extension, lateral bending, and axial rotation are also restricted in a manner near or identical to those associated with a natural disc.

C. Three-Piece Structure

[0199] A representative prosthetic intervertebral disc 300 having a three-piece structure is shown in FIGS. 21 through 23. The prosthetic disc includes an upper endplate 310, a lower endplate 320, and a core assembly 330 retained between the upper endplate 310 and the lower endplate 320.

[0200] The upper endplate 310 and lower endplate 320 are generally flat, planar members, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the upper endplate 310 and lower endplate 320 include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. Optionally, the endplates may be coated with hydroxyapatite, titanium plasma spray, or other coatings to enhance bony ingrowth.

[0201] As noted above, the upper and lower endplates typically have a length of from about 12 mm to about 45 mm, preferably from about 13 mm to about 44 mm, a width of from about 11 mm to about 28 mm, preferably from about 12 mm to about 25 mm, and a thickness of from about 0.5 mm to about 4 mm, preferably from about 1 mm to about 3 mm. The sizes of the upper and lower endplates are selected primarily based upon the size of the void between adjacent vertebral bodies to be occupied by the prosthetic disc. Accordingly, while endplate lengths and widths outside of the ranges listed above are possible, they are not typical. The upper surface of the upper endplate 310 and the lower surface of the lower endplate 320 are preferably each provided with a mechanism for securing the endplate to the respective opposed surfaces of the upper and lower vertebral bodies between which the prosthetic disc is to be implanted. For example, in FIGS. 21 and

23, the upper endplate 310 includes an anchoring fin 311. The anchoring fin 311 is intended to engage a mating groove that is formed on the surface of the upper vertebral body to thereby secure the endplate to the vertebral body. The anchoring fin 311 extends generally perpendicularly from the generally planar external surface of the upper endplate 310, i.e., upward from the upper side of the endplate as shown in FIGS. 21 and 23. As shown in the Figures, the anchoring fin 311 is disposed at the center of external surface of the upper endplate 310 and has a length that is slightly shorter than the width of the upper endplate 310. Although not shown in the Figures, the anchoring fin 311 may be provided with a plurality of serrations located on the top edge of the anchoring fin. The serrations are intended to enhance the ability of the anchoring fin to engage the vertebral body and to thereby secure the upper endplate 310 to the spine.

[0202] Similarly, the lower surface of the lower endplate 320 includes an anchoring fin 321. The anchoring fin 321 on the lower surface of the lower endplate 320 is identical in structure and function to the anchoring fin 311 on the upper surface of the upper endplate 310, with the exception of its location on the prosthetic disc. The anchoring fin 321 on the lower endplate 320 is intended to engage a mating groove formed on the lower vertebral body, whereas the anchoring fin 311 on the upper endplate 310 is intended to engage a mating groove on the upper vertebral body. Thus, the prosthetic disc 300 is held in place between the adjacent vertebral bodies.

[0203] Alternatively, the upper endplate 310 and lower endplate 320 of the three-piece prosthetic disc may employ one of the alternative securing mechanisms shown in FIGS. 13A-C. As described above in relation to the one-piece prosthetic device shown in FIG. 13A, each of the upper endplate 110 and lower endplate 120 is provided with a single anchoring fin 111, 121. The anchoring fins 111, 121 are located along a center line of the respective endplates, and each is provided with a plurality of serrations 112, 122 on its upper edge. The single anchoring fins 111, 121 are intended to engage grooves formed on the opposed surface of the upper and lower vertebral bodies, as described above. In FIG. 13B, each of the upper endplate 110 and lower endplate 120 is provided with three anchoring fins 111a-c, 121a-c. The FIG. 13B prosthetic disc is the same as the prosthetic disc shown in FIG. 12, but it is shown in perspective rather than cross-section. Thus, the structure and function of the anchoring fins 111a-c and 121a-c are as described above in relation to FIG. 12. Finally, in FIG. 13C, each of the upper endplate 110 and lower endplate 120 is provided with a plurality of serrations 113, 123 over a portion of the exposed external surface of the respective endplate. The serrations 113, 123 are intended to engage the opposed surfaces of the adjacent vertebral bodies to thereby secure the endplates in place between the vertebral bodies. The serrations 113, 123 may be provided over the entire external surface of each of the upper and lower endplates, or they may be provided over only a portion of those surfaces. For example, in FIG. 13C, the serrations 113 on the upper surface of the upper endplate 110 are provided over three major areas, a first area 113a near a first edge of the upper endplate 110, a second area 113b near the center of the upper endplate 110, and a third area near a second edge of the endplate 113c.

[0204] Turning to FIG. 54, in an optional embodiment, the anchoring fins 111 are selectively retractable and extendable by providing a deployment mechanism 160 that is associated with the upper endplate 110. A similar mechanism may be

used on the lower endplate 120. The deployment mechanism includes a slider 161 that slides within a channel 162 formed in the upper endplate 110. The channel 162 includes a threaded region 163, and the slider 161 includes matching threads 164, thereby providing a mechanism for advancing the slider 161 within the channel 162. As the slider 161 is advanced within the channel 162, a tapered region 165 engages the bottom surface of a deployable fin 166. Further advancement of the slider 161 causes the deployable fin 166 to be raised upward within a slot 167 on the upper surface of the upper endplate 110. Reversing the deployment mechanism 160 causes the fin 166 to retract. The deployment mechanism 160 may also be used in conjunction with spikes, serrations, or other anchoring devices. In an alternative embodiment, the threaded slider 161 of the deployment mechanism may be replaced with a dowel pin that is advanced to deploy the fin 166. Other advancement mechanisms are also possible.

[0205] The core assembly 330 is intended to provide support to and to maintain the relative spacing between the upper endplate 310 and lower endplate 320. The core assembly 330 provides compressive compliance to the three-piece prosthetic disc, as well as providing limited translation, flexion, extension, and lateral bending by and between the upper endplate 310 and lower endplate 320. The core assembly 330 further provides substantially unlimited rotation by and between the upper endplate 310 and the lower endplate 320.

[0206] The core assembly 330 includes a top cap 331, a bottom cap 332, a sidewall 333, and a core center 334 held by and retained between the top cap 331, bottom cap 332, and sidewall 333. The top cap 331 and bottom cap 332 are generally planar, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the top cap 331 and bottom cap 332 include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. The core center 334 is made of a relatively compliant material, for example, polyurethane or silicone, and is typically fabricated by injection molding. The shape of the core center 334 is typically generally cylindrical or bean-shaped, although the shape (as well as the materials making up the core center and the core member size) may be varied to obtain desired physical or performance properties. For example, the core member 334 shape, size, and materials will directly affect the degree of flexion, extension, lateral bending, and axial rotation of the prosthetic disc.

[0207] The top cap 331 and bottom cap 332 each preferably includes a generally concave indentation 336 formed at a center point of the cap. The indentations 336 are intended to cooperate with a pair of retainers formed on the internal surfaces of the endplates to retain the core assembly 330 in place between the retainers, as described more fully below.

[0208] The top cap 331 and bottom cap 332 preferably contain a plurality of slots 335 spaced radially about the surface of each of the caps. One or more fibers 340 are wound around the top cap 331 and bottom cap 332 through the slots 335 to attach the endplates to one another. The fibers 340 preferably are not tightly wound, thereby allowing a degree of axial rotation, bending, flexion, and extension by and between the top cap 331 and bottom cap 332. The core center

334 is preferably pre-compressed. The actual number of slots 335 contained on each of the top cap 331 and bottom cap 332 is variable. Increasing the number of slots will result in an increase in the circumferential density of the fibers holding the endplates together. Additionally, the fibers may be wound multiple times within the same slot, thereby increasing the radial density of the fibers. In each case, this improves the wear resistance and increases the torsional and flexural stiffness of the prosthetic disc, thereby further approximating natural disc stiffness. In addition, the fibers 340 may be passed through or wound on each slot, or only on selected slots, as needed.

[0209] The purpose of the fibers 340 is to hold the top cap 331 and bottom cap 332 together and to limit the range-of-motion to mimic the range-of-motion of a natural disc. Accordingly, the fibers preferably comprise high tenacity fibers with a high modulus of elasticity, for example, at least about 100 MPa, and preferably at least about 500 MPa. By high tenacity fibers is meant fibers that can withstand a longitudinal stress of at least 50 MPa, and preferably at least 250 MPa, without tearing. The fibers 140 are generally elongate fibers having a diameter that ranges from about 100 μm to about 500 μm , and preferably about 200 μm to about 400 μm . Optionally, the fibers may be injection molded with an elastomer to encapsulate the fibers, thereby providing protection from tissue ingrowth and improving torsional and flexural stiffness.

[0210] The fibers 340 may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron®), polyethylene, polyaramid, poly-paraphenylene terephthalamide (e.g., Kevlar®), carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like.

[0211] The fibers 340 may be terminated on an endplate by tying a knot in the fiber on the superior surface of an endplate. Alternatively, the fibers 340 may be terminated on an endplate by slipping the terminal end of the fiber into a slot on an edge of an endplate, similar to the manner in which thread is retained on a thread spool. The slot may hold the fiber with a crimp of the slot structure itself, or by an additional retainer such as a ferrule crimp. As a further alternative, tab-like crimps may be machined into or welded onto the endplate structure to secure the terminal end of the fiber. The fiber may then be closed within the crimp to secure it. As a still further alternative, a polymer may be used to secure the fiber to the endplate by welding. The polymer would preferably be of the same material as the fiber (e.g., PE, PET, or the other materials listed above). Still further, the fiber may be retained on the endplates by crimping a cross-member to the fiber creating a T-joint, or by crimping a ball to the fiber to create a ball joint.

[0212] The sidewall 333 is preferably made of polyurethane or silicone and may be fabricated by injection molding, two-part component mixing, or dipping the core assembly into a polymer solution. Alternatively, an outer ring or gasket (not shown in the drawings) may optionally be provided in place of the sidewall 333.

[0213] As noted above, the core assembly 330 is selectively retained between the upper endplate 310 and the lower endplate 320. A preferred mechanism for retaining the core assembly 330 between the two endplates is illustrated in FIGS. 21 through 23. For example, the upper endplate 310 is

provided with a retainer **313** formed on the interior surface of the upper endplate **310**. The retainer **313** is a convex body formed at the center of the internal surface of the upper endplate **310** that extends into the space between the upper endplate **310** and lower endplate **320** when the endplates are implanted into the patient. A similar retainer **323** is formed on the opposed internal surface of the lower endplate **320**. Each of the retainers **313**, **323** is preferably of generally semi-spherical shape, and each is preferably formed from the same material used to fabricate the upper and lower endplates **310**, **320**.

[0214] As shown, for example, in FIG. 23, the retainers **313**, **323** formed on the internal surfaces of the endplates cooperate with the indentations **336** formed on the external surfaces of the top cap **331** and bottom **332** of the core assembly **330** to hold the core assembly in place between the endplates. The amount of retaining force holding the core assembly **330** in place will depend on several factors, including the materials used to form the endplates and the core assembly, the size and shape of the core assembly, the distance separating the two endplates, the size and shape of each of the retainers and indentations, and other factors. Any one or all of these factors may be varied to obtain desired results. Typically, the retaining force will be sufficient to hold the core assembly in place, while still allowing each of the endplates to rotate substantially freely relative to the core assembly.

[0215] Turning to FIGS. 24A-C, three embodiments of the core assembly **330** are illustrated. In a first embodiment, shown in FIG. 24A, the core assembly **330** is provided with a through hole **337**, i.e., the central portion of the core assembly **330** is hollow. In this embodiment, although there are no indentations **336**, the through hole **337** creates a shoulder **338** on each of the top cap **331** and bottom cap **332**. The shoulders **338** have a size selected to suitably engage the retainers **313**, **323** formed on the endplates. In a second embodiment, the core assembly **330** is provided with indentations **336** and the core center **334** extends throughout the internal volume of the core assembly. Finally, in a third embodiment, the core assembly **330** is provided with indentations **336**, but the core center **334** occupies only a central portion of the internal volume of the core assembly **330**.

[0216] Turning to FIGS. 25A-C, the core assembly may optionally include a plurality of reinforcing fibers **360** distributed throughout the body of the core assembly. The fibers **360** may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron), polyethylene, polyaramid, carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like. The reinforcing fibers **360** provide additional strength to the core assembly. The fiber reinforcement is made by injecting core center material around the fibers formed in the shape of the core center. Exemplary core shapes are shown in FIGS. 25A-C, and include a core assembly **330** having a through hole **337** (FIG. 25A), a core assembly **330** having indentations **336** on each of the top and bottom surfaces (FIG. 25B), and a core assembly **330** having a toroidal shape (FIG. 25C).

[0217] The fibers **360** may be terminated on an endplate by tying a knot in the fiber on the superior surface of an endplate. Alternatively, the fibers **360** may be terminated on an endplate by slipping the terminal end of the fiber into a slot on an edge of an endplate, similar to the manner in which thread is

retained on a thread spool. The slot may hold the fiber with a crimp of the slot structure itself, or by an additional retainer such as a ferrule crimp. As a further alternative, tab-like crimps may be machined into or welded onto the endplate structure to secure the terminal end of the fiber. The fiber may then be closed within the crimp to secure it. As a still further alternative, a polymer may be used to secure the fiber to the endplate by welding. The polymer would preferably be of the same material as the fiber (e.g., PE, PET, or the other materials listed above). Still further, the fiber may be retained on the endplates by crimping a cross-member to the fiber creating a T-joint, or by crimping a ball to the fiber to create a ball joint.

[0218] Turning next to FIGS. 26, 27, and 28A-C, the core assembly may optionally be formed of stacks of reinforcing fabric having no silicone, polyurethane, or other polymeric component. As shown in FIG. 26, woven fibers **370** are formed into sheets of fabric that are compressed into a stack to form a core body. The woven fibers **370** may be formed of materials such as polyester (e.g., Dacron), polyethylene, polyaramid, carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like. FIG. 27 is a cross-sectional view of a woven fiber core body. FIG. 28A illustrates a woven fiber core body **330** having a through hole **337** similar to the structure described previously. Similarly, FIG. 28B illustrates a woven fiber core body **330** having indentations **336** on its upper and lower surfaces. Finally, FIG. 28C illustrates a woven fiber core body **330** having a toroidal shape.

[0219] The three-piece structure embodiment of the prosthetic disc is implanted by a surgical procedure. After removing the natural disc, grooves are formed in the superior and inferior vertebrae between which the prosthetic disc is to be implanted. The upper endplate **310** and lower endplate **320** are then each implanted into the void, while aligning the anchoring fins **311** **321** with the grooves formed on the vertebral bodies. The anchoring fins cause the prosthetic disc to be secured in place between the adjacent vertebral bodies. After the upper endplate **310** and lower endplate **320** are implanted, the core assembly **330** is engaged between the endplates to complete the implantation.

[0220] The three-piece prosthetic disc has several advantages over prior art artificial discs, as well as over alternative treatment procedures such as spinal fusion. For example, the prosthetic discs described herein provide compressive compliance similar to that of a natural spinal disc. In addition, the motions in flexion, extension, lateral bending, and axial rotation are also restricted in a manner near or identical to those associated with a natural disc.

D. Four-Piece Structure

[0221] Representative prosthetic intervertebral discs **400** having four-piece structures are shown in FIGS. 29 through 35. The prosthetic discs include an upper endplate **410**, a lower endplate **420**, and a two-piece core assembly **430** retained between the upper endplate **410** and the lower endplate **420**.

[0222] The upper endplate **410** and lower endplate **420** are generally flat, planar members, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the upper endplate **410** and lower endplate **420** include tita-

nium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. Optionally, the endplates may be coated with hydroxyapatite, titanium plasma spray, or other coatings to enhance bony ingrowth.

[0223] As noted above, the upper and lower endplates typically have a length of from about 12 mm to about 45 mm, preferably from about 13 mm to about 44 mm, a width of from about 11 mm to about 28 mm, preferably from about 12 mm to about 25 mm, and a thickness of from about 0.5 mm to about 4 mm, preferably from about 1 mm to about 3 mm. The sizes of the upper and lower endplates are selected primarily based upon the size of the void between adjacent vertebral bodies to be occupied by the prosthetic disc. Accordingly, while endplate lengths and widths outside of the ranges listed above are possible, they are not typical

[0224] The upper surface of the upper endplate 410 and the lower surface of the lower endplate 420 are preferably each provided with a mechanism for securing the endplate to the respective opposed surfaces of the upper and lower vertebral bodies between which the prosthetic disc is to be implanted. For example, as shown in FIGS. 30 and 32, the upper endplate 410 includes an anchoring fin 411. The anchoring fin 411 is intended to engage a mating groove that is formed on the surface of the upper vertebral body to thereby secure the endplate to the vertebral body. The anchoring fin 411 extends generally perpendicularly from the generally planar external surface of the upper endplate 410, i.e., upward from the upper side of the endplate as shown in FIGS. 30 and 32. As shown in the Figures, the anchoring fin 411 is disposed at the center of external surface of the upper endplate 410 and has a length that is slightly less than the width of the upper endplate 410. Although not shown in the Figures, the anchoring fin 411 may be provided with a plurality of serrations located on its top edge. The serrations are intended to enhance the ability of the anchoring fin to engage the vertebral body and to thereby secure the upper endplate 410 to the spine.

[0225] Similarly, the lower surface of the lower endplate 420 includes an anchoring fin 421. The anchoring fin 421 on the lower surface of the lower endplate 420 is identical in structure and function to the anchoring fin 411 on the upper surface of the upper endplate 410, with the exception of its location on the prosthetic disc. The anchoring fin 421 on the lower endplate 420 is intended to engage a mating groove formed on the lower vertebral body, whereas the anchoring fin 411 on the upper endplate 410 is intended to engage a mating groove on the upper vertebral body. Thus, the prosthetic disc 400 is held in place between the adjacent vertebral bodies.

[0226] Alternatively, the upper endplate 410 and lower endplate 420 of the three-piece prosthetic disc may employ one of the alternative securing mechanisms shown in FIGS. 13A-C. As described above in relation to the one-piece prosthetic device shown in FIG. 13A, each of the upper endplate 110 and lower endplate 120 is provided with a single anchoring fin 111, 121. The anchoring fins 111, 121 are located along a centerline of the respective endplates, and each is provided with a plurality of serrations 112, 122 on its upper edge. The single anchoring fins 111, 121 are intended to engage grooves formed on the opposed surface of the upper and lower vertebral bodies, as described above. In FIG. 13B, each of the

upper endplate 110 and lower endplate 120 is provided with three anchoring fins 111a-c, 121a-c. The FIG. 13B prosthetic disc is the same as the prosthetic disc shown in FIG. 12, but it is shown in perspective rather than cross-section. Thus, the structure and function of the anchoring fins 111a-c and 121a-c are as described above in relation to FIG. 12. Finally, in FIG. 13C, each of the upper endplate 110 and lower endplate 120 is provided with a plurality of serrations 113, 123 over a portion of the exposed external surface of the respective endplate. The serrations 113, 123 are intended to engage the opposed surfaces of the adjacent vertebral bodies to thereby secure the endplates in place between the vertebral bodies. The serrations 113, 123 may be provided over the entire external surface of each of the upper and lower endplates, or they may be provided over only a portion of those surfaces. For example, in FIG. 13C, the serrations 113 on the upper surface of the upper endplate 110 are provided over three major areas, a first area 113a near a first edge of the upper endplate 110, a second area 113b near the center of the upper endplate 110, and a third area near a second edge of the endplate 113c.

[0227] Turning to FIG. 54, in an optional embodiment, the anchoring fins 111 are selectively retractable and extendable by providing a deployment mechanism 160 that is associated with the upper endplate 110. A similar mechanism may be used on the lower endplate 120. The deployment mechanism includes a slider 161 that slides within a channel 162 formed in the upper endplate 110. The channel 162 includes a threaded region 163, and the slider 161 includes matching threads 164, thereby providing a mechanism for advancing the slider 161 within the channel 162. As the slider 161 is advanced within the channel 162, a tapered region 165 engages the bottom surface of a deployable fin 166. Further advancement of the slider 161 causes the deployable fin 166 to be raised upward within a slot 167 on the upper surface of the upper endplate 110. Reversing the deployment mechanism 160 causes the fin 166 to retract. The deployment mechanism 160 may also be used in conjunction with spikes, serrations, or other anchoring devices. In an alternative embodiment, the threaded slider 161 of the deployment mechanism may be replaced with a dowel pin that is advanced to deploy the fin 166. Other advancement mechanisms are also possible.

[0228] FIG. 29 illustrates yet another alternative mechanism for securing the upper and lower endplates to the vertebral bodies. As shown in the Figure, the upper endplate 410 may be provided with a plurality of anchoring spikes 419 spaced over the external surface of the endplate. The anchoring spikes 419 are adapted to engage the internal surface of the vertebral body. Although not shown in FIG. 29, the external surface of the lower endplate 420 may optionally be provided with similar anchoring spikes to secure the lower endplate to the internal surface of the inferior vertebral body.

[0229] The core assembly 430 is intended to provide support to and to maintain the relative spacing between the upper endplate 410 and lower endplate 420. The core assembly 430 provides compressive compliance to the four-piece prosthetic disc, as well as providing limited translation, flexion, extension, and lateral bending by and between the upper endplate 410 and lower endplate 420. The core assembly 430 further provides substantially unlimited rotation by and between the upper endplate 410 and the lower endplate 420.

[0230] The core assembly 430 includes an upper core member 430a and a lower core member 430b, 430c. Two embodi-

ments of the core assembly **430** of the four-piece prosthetic disc are shown in FIGS. **29** through **35**. In the first embodiment, shown in FIGS. **29** through **32**, both the upper core member **430a** and the lower core member **430b** include a core structure having top and bottom caps, slots, fibers, a core center, and an annular capsule. In the second embodiment, shown in FIGS. **33** through **35**, the upper core member **430a** is identical to that of the first embodiment, but the lower core member **430c** is, instead, a solid structure. These structures are described more fully below.

[0231] The upper core member **430a** includes a top cap **431a**, a bottom cap **432a**, a sidewall **433a**, and a core center **434a** held by and retained between the top cap **431a**, bottom cap **432a**, and sidewall **433a**. The top cap **431a** and bottom cap **432a** are generally planar, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the top cap **431a** and bottom cap **432a** include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. The core center **434a** is made of a relatively compliant material, for example, polyurethane or silicone, and is typically fabricated by injection molding. The shape of the core center **434a** is typically generally cylindrical or bean-shaped, although the shape (as well as the materials making up the core center and the core member size) may be varied to obtain desired physical or performance properties. For example, the core member **434a** shape, size, and materials will directly affect the degree of flexion, extension, lateral bending, and axial rotation of the prosthetic disc.

[0232] The bottom cap **432a** preferably includes a generally convex retainer **437a** formed at a center point of the bottom cap **432a**. The retainer **437a** is intended to cooperate with an indentation **436b**, **436c** formed on the upper surface of the lower core member **430b**, **430c** to create an engagement between the upper core member **430a** and the lower core member **430b**, **430c**, as described more fully below.

[0233] The top cap **431a** and bottom cap **432a** preferably contain a plurality of slots **435a** spaced radially about the surface of each of the caps. One or more fibers **440** are wound around the top cap **431a** and bottom cap **432a** through the slots **435a** to attach the top and bottom caps to one another. The fibers **440** preferably are not tightly wound, thereby allowing a degree of axial rotation, bending, flexion, and extension by and between the top cap **431a** and bottom cap **432a**. The core center **434a** is preferably pre-compressed. The actual number of slots **435a** contained on each of the top cap **431a** and bottom cap **432a** is variable. Increasing the number of slots will result in an increase in the circumferential density of the fibers holding the endplates together. Additionally, the fibers may be wound multiple times within the same slot, thereby increasing the radial density of the fibers. In each case, this improves the wear resistance and increases the torsional and flexural stiffness of the prosthetic disc, thereby further approximating natural disc stiffness. In addition, the fibers **440** may be passed through or wound on each slot, or only on selected slots, as needed.

[0234] The purpose of the fibers **440** is to hold the top cap **431a** and bottom cap **432a** together and to limit the range-of-motion to mimic the range-of-motion of a natural disc.

Accordingly, the fibers preferably comprise high tenacity fibers with a high modulus of elasticity, for example, at least about 100 MPa, and preferably at least about 500 MPa. By high tenacity fibers is meant fibers that can withstand a longitudinal stress of at least 50 MPa, and preferably at least 250 MPa, without tearing. The fibers **440** are generally elongate fibers having a diameter that ranges from about 100 μm to about 500 μm , and preferably about 200 μm to about 400 μm . Optionally, the fibers may be injection molded with an elastomer to encapsulate the fibers, thereby providing protection from tissue ingrowth and improving torsional and flexural stiffness.

[0235] The fibers **440** may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron®), polyethylene, polyaramid, poly-paraphenylene terephthalamide (e.g., Kevlar®), carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinyl polymer, polyphosphazene, polysiloxane, and the like.

[0236] The fibers **440** may be terminated on an endplate by tying a knot in the fiber on the superior surface of an endplate. Alternatively, the fibers **440** may be terminated on an endplate by slipping the terminal end of the fiber into a slot on an edge of an endplate, similar to the manner in which thread is retained on a thread spool. The slot may hold the fiber with a crimp of the slot structure itself, or by an additional retainer such as a ferrule crimp. As a further alternative, tab-like crimps may be machined into or welded onto the endplate structure to secure the terminal end of the fiber. The fiber may then be closed within the crimp to secure it. As a still further alternative, a polymer may be used to secure the fiber to the endplate by welding. The polymer would preferably be of the same material as the fiber (e.g., PE, PET, or the other materials listed above). Still further, the fiber may be retained on the endplates by crimping a cross-member to the fiber creating a T-joint, or by crimping a ball to the fiber to create a ball joint.

[0237] The sidewall **433a** is preferably made of polyurethane or silicone and may be fabricated by injection molding, two-part component mixing, or dipping the core assembly into a polymer solution. Alternatively, an outer ring or gasket (not shown in the drawings) may optionally be provided in place of the sidewall **433a**.

[0238] As shown, for example, in FIGS. **29** through **35**, the top cap **431a** of the upper core member **430a** includes an edge member **438a** that is adapted to engage a groove **416** formed on the perimeter of the internal surface of the upper endplate **410** to provide an engagement mechanism for attaching the upper core member **430a** to the upper endplate **410**. For example, the upper core member **430a** is slid into the upper endplate **410**, as shown by the arrows in FIG. **29**. After the upper endplate **430a** is fully advanced, i.e., once the leading edge of the edge member **438a** contacts the interior of the groove **416** on the upper endplate **410**, a tab **461a** on the upper surface of the top cap **431a** engages a slot **462a** on the lower surface of the upper endplate **410** (see FIGS. **30** and **33**), thereby locking the upper core member **430a** in place within the upper endplate **410**.

[0239] Turning to the first embodiment of the lower core member **430b**, shown in FIGS. **29** through **32**, the lower core member **430b** includes a top cap **431b**, a bottom cap **432b**, a sidewall **433b**, and a core center **434b** held by and retained between the top cap **431b**, bottom cap **432b**, and sidewall

433b. The top cap **431b** and bottom cap **432b** are generally planar, and are fabricated from a physiologically acceptable material that provides substantial rigidity. Examples of materials suitable for use in fabricating the top cap **431b** and bottom cap **432b** include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others. The core center **434b** is made of a relatively compliant material, for example, polyurethane or silicone, and is typically fabricated by injection molding. The shape of the core center **434b** is typically generally cylindrical or bean-shaped, although the shape (as well as the materials making up the core center and the core member size) may be varied to obtain desired physical or performance properties. For example, the core member **434b** shape, size, and materials will directly affect the degree of flexion, extension, lateral bending, and axial rotation of the prosthetic disc.

[0240] The top cap **431b** preferably includes a generally concave indentation **436b** formed at a center-point of the top cap **431b**. The indentation **436b** is intended to cooperate with the retainer **437a** formed on the lower surface of the upper core member **430a** to create an engagement between the upper core member **430a** and the lower core member **430b**, as described more fully below.

[0241] The top cap **431b** and bottom cap **432b** preferably contain a plurality of slots **435b** spaced radially about the surface of each of the caps. One or more fibers **440** are wound around the top cap **431b** and bottom cap **432b** through the slots **435b** to attach the top and bottom caps to one another. The fibers **440** preferably are not tightly wound, thereby allowing a degree of axial rotation, bending, flexion, and extension by and between the top cap **431b** and bottom cap **432b**. The core center **434b** is preferably pre-compressed. The actual number of slots **435b** contained on each of the top cap **431b** and bottom cap **432b** is variable. In addition, the fibers **440** may be passed through or wound on each slot, or only on selected slots, as needed.

[0242] The purpose of the fibers **440** is to hold the top cap **431b** and bottom cap **432b** together. Accordingly, the fibers preferably comprise high tenacity fibers with a high modulus of elasticity, for example, at least about 100 MPa, and preferably at least about 500 MPa. By high tenacity fibers is meant fibers that can withstand a longitudinal stress of at least 50 MPa, and preferably at least 250 MPa, without tearing. The fibers **440** are generally elongate fibers having a diameter that ranges from about 100 μm to about 500 μm , and preferably about 200 μm to about 400 μm .

[0243] The fibers **440** may be fabricated from any suitable material. Examples of suitable materials include polyester (e.g., Dacron), polyethylene, polyaramid, carbon or glass fibers, polyethylene terephthalate, acrylic polymers, methacrylic polymers, polyurethane, polyurea, polyolefin, halogenated polyolefin, polysaccharide, vinylic polymer, polyphosphazene, polysiloxane, and the like.

[0244] The sidewall **433b** is preferably made of polyurethane or silicone and may be fabricated by injection molding, two-part component mixing, or dipping the core assembly into a polymer solution. Alternatively, an outer ring or gasket (not shown in the drawings) may optionally be provided in place of the sidewall **433b**.

[0245] As shown, for example, in FIGS. 29 through 32, the bottom cap **432b** of the lower core member **430b** includes an edge member **438b** that is adapted to engage a groove **426** formed on the perimeter of the internal surface of the lower endplate **420** to provide an engagement mechanism for attaching the lower core member **430b** to the lower endplate **420**. For example, the lower core member **430b** is slid into the lower endplate **420**, as shown by the arrow in FIG. 16. After the lower endplate **430b** is fully advanced, i.e., once the leading edge of the edge member **438b** contacts the interior of the groove **426** on the lower endplate **420**, a tab **461b** on the lower surface of the bottom cap **432b** engages a slot **462b** on the upper surface of the lower endplate **420** (see FIG. 30), thereby locking the lower core member **430b** in place within the lower endplate **420**.

[0246] Turning to the second embodiment of the lower core member **430c**, shown in FIGS. 33 through 35, the lower core member **430c** is formed of a solid structure having none of the top and bottom caps, sidewall, core center, or fibers that are included in the first embodiment of the lower core member **430b**. The second embodiment of the lower core member **430c** has an identical external shape and size to that of the first embodiment of the lower core member **430b**, including having an edge member **438c** that engages the groove **426** on the internal surface of the lower endplate **420**. A tab **461c** is configured to selectively engage the notch **462c** formed on the upper internal surface of the lower endplate **420**. An indentation **436c** is formed on the central upper surface of the lower core member **430c**, and is adapted to engage the retainer **437a** formed on the upper core member **430a**.

[0247] Examples of materials suitable for use in fabricating the second embodiment of the lower core member **430c** include titanium, titanium alloys, stainless steel, cobalt/chromium, etc., which are manufactured by machining or metal injection molding; plastics such as polyethylene with ultra high molar mass (molecular weight) (UHMWPE), polyether ether ketone (PEEK), etc., which are manufactured by injection molding or compression molding; ceramics; graphite; and others.

[0248] The four-piece structure embodiment of the prosthetic disc is implanted by a surgical procedure. After removing the natural disc, grooves are formed in the superior and inferior vertebrae between which the prosthetic disc is to be implanted (only in the situation where the endplates are provided with anchoring fins). The upper endplate **410** and lower endplate **420** are then each implanted into the void, while aligning the anchoring fins **411**, **421** with the grooves formed on the vertebral bodies. The anchoring fins cause the prosthetic disc to be secured in place between the adjacent vertebral bodies. After the upper endplate **410** and lower endplate **420** are put in position, the core assembly **430** is engaged between the endplates to complete the implantation.

[0249] The four-piece prosthetic disc has several advantages over prior art artificial discs, as well as over alternative treatment procedures such as spinal fusion. For example, the prosthetic discs described herein provide compressive compliance similar to that of a natural spinal disc. In addition, the motions in flexion, extension, lateral bending, and axial rotation are also restricted in a manner near or identical to those associated with a natural disc.

E. Fabric Tubes

[0250] The one-piece, two-piece, three-piece, and four-piece structures of the prosthetic discs described above include upper and lower endplates that are attached to each other by fibers wound around the endplates. In an alternative embodiment, the fiber component is provided in a fabric cylinder or tubing of woven or knitted form, rather than as individual fibers. The fabric tubing extends between and structurally connects the upper and lower endplates.

[0251] In a first example, a single fabric tube may be provided in place of the wound fibers. The fabric tube may be attached at its upper edge to the upper endplate, and at its lower edge to the lower endplate. For example, through-holes may be provided in each of the endplates to allow the fabric tubing (or individually woven fibers) to pass through and to be secured by knots or crimping on the external surfaces of the endplates. Alternatively, the fabric tube may be attached to each endplate by a peripheral metal or plastic ring that is fixed to the interior surfaces of the endplates.

[0252] In another example, two or more tubes of fabric may be provided between and interconnecting the upper and lower endplates. The two or more fabric tubes may be attached to the endplates by through-holes, as described above, or by press-fit, adhesion, weld, or injection molding integration to a progressively smaller metal or plastic ring with tubing circumferentially affixed to it. This structure creates an assembly of two or more concentric layers of fabric tubing. Alternatively, the concentric tubes may be terminated by collecting each tubing end together and crimping or sewing them together, then fixing the collected ends to the upper and lower endplates. As a still further alternative, an injection molded lid may be fabricated in a manner in which the lid captures the terminal ends of each of the fabric tubes during the injection molding process.

[0253] In a particularly preferred embodiment, multiple concentric fabric tubes are provided. Each of the fabric tubes may be formed from a fabric of material different from the other tubes (e.g. PET, PE, PTFE, Polyamide, etc.), or from a fabric having different material properties. This provides the ability to construct prosthetic discs having a range of performance characteristics.

[0254] As an alternative, the tubing may be comprised of a fiber reinforced elastomeric material rather than a fabric alone. For example, a polyurethane, PDMS, polyester, or other elastomer may be integrated with a fabric or with indi-

vidual fibers to create a tubing that attaches and interconnects the upper and lower endplates.

F. Anti-Creep Compression Member

[0255] Turning to FIG. 53, an optional anti-creep compression member 135 is shown. The anti-creep member 135 is intended to prevent “creeping” of the core due to vertical compression and lateral expansion of the core, which occurs due to extended from wear. The anti-creep member 135 is preferably used in connection with a toroidal shaped core member 130, 230, 330, 430 of any of the one-, two-, three-, or four-piece structures of the prosthetic disc. The anti-creep element 135 includes a post 136 extending downward from the upper endplate 110, 210, 310, 410 and a mating receptacle or cup 137 extending upward from the lower endplate 120, 220, 320, 420. Alternatively, the post 136 may extend upward from the lower endplate and the receptacle 137 may extend downward from the upper endplate. A spring 138 is located within the receptacle 138. The post 136 is slightly conical in shape, and the receptacle 137 has a slightly larger diameter than the post 136 in order to receive the post 136 within the receptacle 137. The slightly conical shapes of the post 136 and cup 137 are preferred in order to accommodate lateral bending (side-to-side), flexion (forward), and extension (backward) of the upper and lower endplates relative to one another. The spring is pre-loaded to provide a force biasing the two endplates apart.

G. Advantages of the Present Prosthetic Intervertebral Discs

[0256] It is evident from the above discussion and results that the present invention provides significantly improved prosthetic intervertebral discs. Significantly, the subject discs closely imitate the mechanical properties of the fully functional natural discs that they are intended to replace.

[0257] More specifically, the modes of spinal motion may be characterized as compression, shock absorption (i.e., very rapid-compressive loading and unloading), flexion (forward) and extension (backward), lateral bending (side-to-side), torsion (twisting), and translation and subluxation (motion of axis). The prosthetic discs described herein semi-constrain each mode of motion, rather than completely constrain or allow a mode to be unconstrained. In this manner, the present prosthetic discs closely mimic the performance of natural discs. The tables below provide data that illustrates this performance.

TABLE 1

One-Piece Structure Lumbar Prosthetic Disc Compared to Natural Human Disc and Ball & Socket Design Prosthetic Disc Compressive Mode of Motion				
Properties	Human Spine	Ball & Socket Design	Prosthetic Disc Core Only	Prosthetic Disc Core & Fiber
Stiffness (N/mm)	≈1288	Very large	800-1600	850-1650
ROM (mm)	0.50	≈0	0.61	0.50
Ult. Load (N)	3952	>5900	>5900	>5900

TABLE 2

One-Piece Structure Cervical Prosthetic Disc Compared to Natural Human Disc and Ball & Socket Design Prosthetic Disc Compressive Mode of Motion				
Properties	Human Spine	Ball & Socket Design	Prosthetic Disc Core Only	Prosthetic Disc Core & Fiber
Stiffness (N/mm)	≈737	Very large	100-950	150-1000
ROM (mm)	0.70 +/- 0.03	≈0	≈0.87	≈0.60
Ult. Load (N)	≈1600	>5900	>9000	>9000

[0258] The subject discs exhibit stiffness in the axial direction, torsional stiffness, bending stiffness in the sagittal plane, and bending stiffness in the front plane, where the degree of these features can be controlled independently by adjusting the components of the discs. The interface mechanism between the endplates and the core members of several embodiments of the described prosthetic discs enables a very easy surgical operation. In view of the above and other benefits and features provided by the subject inventions, it is clear that the subject inventions represent a significant contribution to the art.

II. Implantation Apparatus and Methods

A. Conventional (Non-Minimally Invasive Method)

[0259] The prosthetic intervertebral discs may be implanted into a patient's spine using the apparatus and methods described herein. This description will focus on use of apparatus to implant one- and two-piece prosthetic discs, although the apparatus may also be used to implant other embodiments of the prosthetic disc with little or no modification, as will be appreciated by a person of skill in the art. In addition, and as described below, the method may incorporate less than all of the apparatus components described below.

[0260] The prosthetic discs are implanted surgically between two adjacent vertebrae, an upper vertebra and a lower vertebra, in a patient's spinal column. The vertebrae to be treated are exposed using conventional surgical procedures. After exposure, the natural vertebral disc is removed, leaving a void space between the two adjacent vertebrae. The prosthetic intervertebral disc is then implanted using the apparatus and methods described below.

1. Implantation Tools

[0261] In a first embodiment, and in reference to FIGS. 36-38, the implantation tools include a spacer 810, a two-sided chisel 830, and a holder 850.

[0262] Turning first to FIGS. 36A-B, the spacer 810 includes a proximal handle 812, a shaft 814, and a head portion 816. The handle 812 is adapted to be easily grasped by the user during the implantation procedure. The shaft 814 is preferably cylindrical and smaller in cross-section than the handle. The head portion 816 has a size and shape adapted to perform its function of being inserted between and separating two adjacent vertebral bodies. In the embodiment shown in the Figures, the head portion 816 has a generally trapezoidal shape when viewed from above or below, with a leading edge 817 being generally parallel to, but having a shorter length than the trailing edge 818. Other shapes may be used. The head portion has a thickness "h". The thickness "h" may be varied according to need, i.e., the thickness "h" will impact

the ability of the user to insert the head portion 816 between the two vertebral bodies, and also the amount by which the head portion 816 will be able to separate the two bodies. Thus, a spacer 810 with a head portion 816 of relatively large or small thickness "h" may be used depending on the need. The edges 819 of the head portion 816 are generally rounded to allow the head portion 816 to be more easily inserted between the two vertebral bodies.

[0263] Turning next to FIGS. 37A-B, the two-sided chisel 830 includes a handle 832, a shaft 834, and a head portion 836. The handle 832 is adapted to be easily grasped by the user during the implantation procedure. The shaft 834 is preferably cylindrical and smaller in cross-section than the handle. The head portion 836 has a size and shape adapted to perform its function of being inserted between and creating grooves on the two adjacent vertebral bodies. In the embodiment shown in the Figures, the head portion 836 has a generally trapezoidal shape when viewed from above or below, with a leading edge 837 being generally parallel to, but having a shorter length than the trailing edge 838. Other shapes may be used. The head portion has a thickness "h". The thickness "h" may be varied according to need, i.e., the thickness "h" will impact the ability of the user to be able to insert the head portion 836 between the two vertebral bodies and to cut grooves on the two bodies. Thus, a chisel 830 with a head portion 836 of relatively large or small thickness "h" may be used depending on the need.

[0264] The chisel 830 includes a plurality of wedge-shaped blades 839 formed on the upper and lower surfaces of the head portion 836. The blades 839 of the chisel 830 are adapted to create grooves in the lower surface of the upper vertebra and on the upper surface of the lower vertebra being treated. In the embodiment shown in the Figures, the chisel 830 includes three blades 839 on each of the upper and lower surfaces. More or fewer blades may be provided. Optimally, the number, shape, and orientation of the blades 839 on the surfaces of the chisel 830 are selected to match those of the anchoring fins provided on the surfaces of the prosthetic disc to be implanted.

[0265] Turning next to FIGS. 38A-B, the holder 850 includes a handle 852, a shaft 854, and a head portion 856. The handle 852 is adapted to be easily grasped by the user during the implantation procedure. The shaft 854 is preferably cylindrical and smaller in cross-section than the handle. The head portion 856 has a size and shape adapted to perform its function of retaining the prosthetic disc on an end thereof in order to implant the disc between the two adjacent vertebral bodies.

[0266] The head portion 856 of the holder 850 includes a proximal body portion 857 and two arms 858a-b extending distally from the body portion 857. The body portion 857 has

a generally square shape, and its distal end includes a slightly concave section **859** at its center that provides a space for receiving a portion of the prosthetic disc. Each of the arms **858a-b** also includes a slightly recessed portion **860a-b** that is adapted to engage the side surfaces of the prosthetic disc in order to facilitate holding the disc in place during the implantation procedure. The body portion also includes engagement pins **861** on its distal surface, which engagement pins **861** are adapted to engage mating holes provided on the prosthetic disc.

[0267] In an alternative embodiment, and in reference to FIGS. 39-42, the implantation tools include a guide **500**, a lower pusher **520** connected to a first chisel **540**, an upper endplate holder **560**, and a second chisel **580**.

[0268] Turning first to FIG. 39, the guide **500** serves the purposes of, first, positioning and retaining the lower endplate **220b** in place on the lower of the two adjacent vertebrae being treated, and, second, guiding one or more of the other implantation tools to their proper locations for performing their functions. In the preferred embodiment, the guide **500** comprises a generally flat, elongated member **501** having a first end **502**, a second end **503**, and a pair of raised sides **504**, **505**. Each of the raised sides **504**, **505** includes an inwardly facing portion **504a**, **505a** that extends back over the elongated member **501** on a plane slightly above that of the elongated member. Each of the inwardly facing portions **504a**, **505a** of the pair of raised sides **504**, **505** thereby forms a groove **506**, **507** that extends along the length of the guide **500**. As described below, the grooves **506**, **507** may be used to guide one or more of the other implantation tools in cooperation with a flange provided on those other tools.

[0269] Extending from the first end **502** of the guide **500** are a pair of lower endplate rods **508**, **509**. Each of the lower endplate rods **508**, **509** is a generally cylindrical rod that extends outward from the first end **502** of the guide **500** in the plane of the elongate member **501** or parallel to that plane. The sizes of the lower endplate rods **508**, **509**—e.g., lengths, cylindrical diameters—are not critical, provided that the rods are of sufficient size to be capable of performing the function of engaging and retaining the lower endplate **220b**, as described more fully below.

[0270] Turning to FIG. 40, in the preferred embodiment, a spacer tool **570** includes a combination of a lower pusher **520** and a first chisel **540** attached to a base member **530**. The lower pusher **520** includes a pair of lower pusher rods **521a**, **521b**. Each of the lower pusher rods **521a**, **521b** is connected at a first end to the base **530**. At a second end, a cross-member **522** extends between and connects to each of the pair of lower pusher rods **521a**, **521b**. The two lower pusher rods **521a**, **521b** are thus held in a generally parallel relation to one another and extend outward from the base **530**. At the end opposite the base **530**, each of the lower pusher rods **521a**, **521b** is attached to a lower endplate insert **523**. The lower endplate insert **523** includes a flange **524** along its edge that is adapted to engage the matching slot **226** found on an outer lower endplate **220b** of a two-piece prosthetic disc, such as those described herein.

[0271] In the preferred embodiment, each of the lower pusher rods **521a**, **521b** and the cross-member **522** are generally cylindrical rods. The cross-sectional shape and size of the rods are not critical, such that the lower pusher rods **521a**, **521b** are capable of advancing the lower endplate during the implantation procedure, as described more fully below.

[0272] In the preferred embodiment illustrated in FIG. 40, the base **530** includes a block-shaped bottom portion **531**. The bottom portion **531** of the base **530** is the portion of the base to which the pusher rods **521a**, **521b** of the lower pusher **520** are attached. The bottom portion **531** shown in FIG. 40 has a generally block-shaped body, although the size and shape of the bottom portion **531** are not critical.

[0273] Extending upward from the top surface of the bottom portion are two flanges, a tall flange **532** and a short flange **533**. A pivot pin **534** is located at the upper end of the tall flange **532**. The pivot pin **534** extends through a hole in the upper end of the tall flange **532**, and is able to rotate around its pivot axis. A pair of upper pusher rods **541a**, **541b** are attached to the pivot pin **534**, with one of the two upper pusher rods **541a** attached to a first end of the pivot pin **534**, and the other upper pusher rod **541b** attached to the opposite end of the pivot pin **534**. At the end of the upper pusher rods **541a**, **541b** opposite the pivot pin **534**, the upper pusher rods **541a**, **541b** are attached to a first chisel **540**. In addition, a cross-member **542** attaches to and interconnects the pair of upper pusher rods **541a**, **541b** near the end to which the first chisel **540** is attached.

[0274] A ratchet key **535** extends through a hole in the short flange **533**. The ratchet key **535** is able to rotate around its longitudinal axis within the hole in the short flange. The ratchet key **535** includes a grasping portion **536** extending from one side of the short flange **533**, and a gear portion (not shown in the Figures) extending from the opposite side of the short flange **533**. An elongated guide rail **537** extends beneath the gear portion of the ratchet key **535** and generally between the pair of upper pusher rods **541a**, **541b** and the pair of lower pusher rods **521a**, **521b**. The guide rail **537** includes a plurality of teeth **538** formed on its upper side, which teeth are adapted to engage the gear portion of the ratchet key **535**. Thus, by rotating the ratchet key **535**, a user is able to advance or withdraw the guide rail **537**.

[0275] A separator **515** is attached to an end of the guide rail **537**. The separator **515** is a generally flat member that is disposed generally transversely to the guide rail **537**. A pair of upper grooves **516a**, **516b** are formed on the top edge of the separator **515**. The upper grooves **516a**, **516b** have a size and are located so as to slidably engage the upper pusher rods **541a**, **541b**. Similarly, a pair of lower grooves **517a**, **517b** are formed on the bottom edge of the separator **515**. The lower grooves **517a**, **517b** have a size and are located so as to slidably engage the lower pusher rods **521a**, **521b**. Thus, as shown in FIG. 40, the separator is able to be advanced or withdrawn along the lengths of the upper pusher rods **541a**, **541b** and lower pusher rods **521a**, **521b** by turning the ratchet key **535**. Turning the ratchet key **535** causes the gear portion of the ratchet key **535** to engage the teeth **538** on the guide rail **537**. With reference to the perspective illustrated in FIG. 40, rotating the ratchet key clockwise will cause the guide rail **537** and the separator **515** to withdraw, i.e., to draw nearer to the base **530**. Alternatively, rotating the ratchet key **535** counter-clockwise will cause the guide rail **537** and the separator to advance, i.e., to move away from the base **530**.

[0276] As best seen in the illustration in FIG. 40, the separator **515** has a partial height, h , that is defined as the distance between the bottom edge of the upper grooves **516a**, **516b** and the top edge of the lower grooves **517a**, **517b**. The partial height h of the separator **515** is less than the distance separating the upper pusher rods **541a**, **541b** and lower pusher rods **521a**, **521b** at the point that they attach to the base **530**. The

partial height *h* of the separator is greater than the height of the prosthetic disc or, stated otherwise, the partial height *h* of the spacer is greater than the post-operative distance separating the two adjacent vertebrae being treated. Thus, as explained more fully below, the separator **515** has a partial height *h* that is suitable for expanding the distance separating the first chisel **540** and the lower endplate insert **523** as the separator **515** is advanced during the implantation procedure.

[0277] The first chisel **540** is attached to the ends of each of the upper pusher rods **541a**, **541b** opposite the tall flange **532**. The first chisel **540** includes a generally flat plate portion **543** and one or more wedge-shaped blades **544** extending upward from the flat plate portion **543**. The blades **544** of the first chisel are adapted to create grooves in the lower surface of the upper vertebra being treated. The flat plate portion **543** of the first chisel is preferably relatively thin in relation to the height of the prosthetic disc, thereby allowing the first chisel to be inserted between the two adjacent vertebrae after the natural disc has been removed.

[0278] Turning to FIG. **41**, the upper endplate holder **560** includes a pusher block **561** attached to the end of a push rod **563**. The pusher block **561** has a generally flat front surface **562** that is adapted to engage the trailing surface of the upper endplate of the prosthetic disc, as described more fully below. In addition, the upper endplate holder **560** includes a pair of outer engagement pins **564** extending outward from the front surface **562**, and a center engagement pin **565** also extending outward from the front surface. The outer engagement pins **564** and center engagement pin **565** are each generally cylindrical in shape, and relatively short in length relative to the size of the push rod **563**. The engagement pins **564**, **565** are intended to engage and retain the upper endplate of the prosthetic disc during the implantation procedure, as explained more fully below.

[0279] Turning to FIG. **42**, the second chisel **580** includes a generally flat plate portion **583** attached to the end of a push rod **582**. One or more wedge-shaped blades **584** attach to and extend upward from the top surface of the flat plate portion **583**. Similar to the blade **544** of the first chisel **540**, the blades **584** of the second chisel are adapted to create grooves in the lower surface of the upper vertebra being treated. The flat plate portion **583** of the second chisel is preferably thicker than the flat plate portion **543** of the first chisel **540**, and is generally about the same thickness as the height of the prosthetic disc. A flange **585** extends outward from the bottom of the second chisel **580**. The flange **585** has a size and is oriented such that it will engage the grooves **506**, **507** on the guide member **500** during the implantation procedure.

2. Implantation Procedures

a. First Embodiment

[0280] A preferred implantation procedure utilizes the spacer **810**, chisel **830**, and holder **850** shown in FIGS. **36-38**. As discussed above, the procedure described herein is in relation to implantation of a one-piece prosthetic disc. This description is intended to illustrate the apparatus and methods described herein, however, and is not intended to be limiting.

[0281] A first step of the procedure is to expose the two adjacent vertebrae to be treated by conventional surgical procedures and to remove the natural disc. Once the natural disc has been removed, the spacer **810** is advanced and its head portion **816** is placed between the two adjacent vertebrae in

order to separate them. After the vertebrae are adequately separated, the spacer **810** is withdrawn.

[0282] The two-sided chisel **830** is then advanced and its head portion **836** is placed between the vertebral bodies. Because of the size of the head portion **836** relative to the axial space between the vertebrae, the wedge-shaped blades **839** engage the inward-facing surfaces of the vertebrae, creating grooves on those surfaces simultaneously. After the grooves are formed as needed, the two-sided chisel is withdrawn.

[0283] A prosthetic disc is then installed on the distal end of the holder **850**. Optimally, the arms **858a-b** of the holder **850** engage the side surfaces of the prosthetic disc, and the proximal side of the disc butts up against the distal face of the body portion **857** of the holder **850**. In this position, the holder is able to retain the prosthetic disc and hold it in place. The prosthetic disc is then advanced by the holder into the disc space between the two vertebrae. Optimally, the anchoring fins on the external surfaces of the prosthetic disc are aligned with the grooves formed in the upper and lower vertebrae as the disc is implanted. Once the disc has been satisfactorily located, the holder **850** is withdrawn, leaving the disc in place.

b. Second Embodiment

[0284] An alternative implantation procedure is illustrated in FIGS. **43** through **49**. The preferred procedure utilizes the implantation tools described above in relation to FIGS. **39-42**. As discussed above, the procedure described herein is in relation to implantation of a two-piece prosthetic disc. This description is intended to illustrate the apparatus and methods described herein, however, and is not intended to be limiting.

[0285] Turning first to FIGS. **43A-B**, after the two adjacent vertebrae to be treated are exposed by conventional surgical procedures and the natural disc is removed, the guide member **500**, lower pusher **520**, and upper pusher rods **541a**, **541b** are advanced in the direction of arrow "A" toward the void space between the two adjacent vertebrae **601**, **602** until the outer lower endplate **220b** and first chisel **540** are located between the two adjacent vertebrae **601**, **602** (see FIG. **43B**).

[0286] At this point in the procedure, the distance "d" between the vertebrae **601**, **602** is insufficient to accommodate the prosthetic disc. Accordingly, as shown in FIGS. **44A-B**, a force is applied to separate the first chisel **540** and the outer lower endplate **220b**, e.g., as represented by arrows "B" in FIGS. **44A-B**. The separating force is applied by advancing the separator **515** away from the base member in the apparatus shown in FIG. **40** by the method described above. The upward force by the first chisel **540** causes the wedge-shaped blades **544** of the first chisel to embed in the lower surface of the upper vertebra **601**, creating grooves in that surface. Similarly, the downward force by the lower endplate insert **523** and outer lower endplate **220b** cause the anchor fins **221** on the lower surface of the outer lower endplate **220b** to embed in the upper surface of the lower vertebra **602**. Thus, by advancing the separator **515** between the upper pusher rods **541a**, **541b** and lower pusher rods **521a**, **521b**, the user is able to implant the outer lower endplate **220b** onto the lower vertebra **602** and to create a set of grooves in the upper vertebra **601** that will accommodate the anchoring fins **211** on the upper endplate of the prosthetic disc.

[0287] After the separating forces are applied as described above, the first chisel apparatus is withdrawn, as shown in FIGS. **45A-B**. More particularly, the lower pusher **520** is withdrawn, thereby withdrawing the lower endplate insert **523** from the outer lower endplate **220b**, leaving the outer

lower endplate **220b** implanted onto the lower vertebra **602**. Also, the upper pusher rods **541a**, **541b** are withdrawn, thereby withdrawing the first chisel **540**, leaving one or more grooves formed on the upper vertebra **601** (see FIG. **45B**). The guide member **500** remains in place to facilitate additional procedures described below.

[0288] After the first chisel apparatus is withdrawn, the second chisel **580** is advanced into the space between the two vertebrae **601**, **602**, as shown in FIGS. **46A-B**. Preferably, the second chisel is advanced (see arrows "A") into the void space by advancing the push rod **583**. Upon entry into the void space, the wedge-shaped blades **584** on the top surface of the second chisel engage the grooves formed in the lower surface of the upper vertebra **601** by the first chisel **540**. Advantageously, the flange **585** on the bottom surface of the second chisel **580** engages and rides in the grooves **506**, **507** on the guide member **500** as the second chisel is being advanced, thereby guiding the second chisel **580** into place.

[0289] As noted above, the second chisel **580** preferably has a thickness that is similar to the height of the upper endplate assembly of the two-piece prosthetic disc. Thus, advancing the second chisel **580** into the void space between the two adjacent vertebrae **601**, **602** ensures that the void space is adequately prepared for implanting the remaining portion of the prosthetic disc. In addition, if the second chisel **580** has a snug fit within the void space, this will further confirm that a prosthetic disc of the appropriate size and shape is being used.

[0290] After the second chisel **580** has been advanced and engages the lower surface of the upper vertebra **601**, it is withdrawn, once again leaving behind the outer lower endplate **220b** implanted onto the lower vertebra **601** and the guide member **500** engaged with the outer lower endplate **220b**. (See FIGS. **47A-B**).

[0291] Once the pair of vertebrae **601**, **602** have been adequately prepared for implantation of the remaining portions of the prosthetic disc, the upper subassembly **205** of the prosthetic disc is implanted using the upper endplate holder **560**. (See FIGS. **48A-B**). The upper endplate holder **560** is advanced in the direction "A" by the push rod **563** until the upper subassembly **205** engages the outer lower endplate **220b** and is locked in place by the tab **261** and notch (not shown). At this point, the anchoring fins **211** on the upper subassembly engage the grooves formed on the lower surface of the upper vertebra **601**, thereby helping to retain the prosthetic disc in place between the two adjacent vertebrae **601**, **602**. Turning to FIGS. **49A-B**, the upper endplate holder **560** and the guide member **500** are then withdrawn, leaving the prosthetic disc in place. FIG. **49A** provides additional detail showing the manner by which the engagement pins **564**, **565** of the upper endplate holder engages a set of mating holes **206** formed in the trailing edge of the upper subassembly **205**. Similarly, FIG. **49A** shows the manner by which the lower endplate rods **508**, **509** engage the mating holes **215** formed on the trailing edge of the outer lower endplate **220b**.

[0292] In an alternative method particularly adapted for implanting the one-piece structure prosthetic discs **100** described herein, implantation of the prosthetic disc is achieved without using the guide member **500**, through use of only the second chisel **580**, the spacer tool **570**, and a modified upper endplate holder **560'**. The spacer tool **570** is used, as described above, to separate the adjacent vertebral bodies to provide space for the prosthetic disc. The second chisel **580** is also used in the manner described above to provide grooves

on the internal surface of the vertebral bodies to accommodate the fins on the prosthetic disc. The modified upper endplate holder **560'** has a similar structure to the endplate holder **560** shown in FIG. **41**, but is provided with an additional set of engagement pins **564'**, **565'** for engaging mating holes provided on the lower endplate **120** of the one-piece prosthetic disc **100**. The modified upper endplate holder **560'** is used to advance the prosthetic disc **100** into place between the adjacent vertebrae, then is withdrawn.

B. Minimally Invasive Implantation

[0293] A minimally invasive surgical implantation method is illustrated in FIG. **51**. The minimally invasive surgical implantation method may be performed using a posterior approach, rather than the anterior approach used for conventional lumbar disc replacement surgery.

[0294] Turning to FIG. **51**, the a pair of cannulas **700** are inserted posteriorly to provide access to the spinal column. More particularly, a small incision is made and a pair of access windows are created through the lamina **610** of one of the vertebrae on each side of the vertebral canal to access the natural vertebral disc to be replaced. The spinal cord **605** and nerve roots **606** are avoided or mobilized to provide access. Once access is obtained, each of the cannulas **700** is inserted. The cannulas **700** may be used to remove the natural disc by conventional means. Alternatively, the natural disc may have already been removed by other means prior to insertion of the cannulas.

[0295] Once the natural disc has been removed and the cannulas **700** located in place, a pair of prosthetic discs are implanted between adjacent vertebral bodies. In the preferred embodiment, the prosthetic discs have a shape and size adapted for the minimally invasive procedure, such as the elongated one-piece prosthetic discs **100** described above in relation to FIGS. **50A-B**. A prosthetic disc **100** is guided through each of the two cannulas **700** (see arrows "C" in FIG. **51**) such that each of the prosthetic discs is implanted between the two adjacent vertebral bodies. In the preferred method, the two prosthetic discs **100** are located side by side and spaced slightly apart between the two vertebrae. Optionally, prior to implantation, grooves are created on the internal surfaces of one or both of the vertebral bodies in order to engage anchoring fins located on the prosthetic discs **100**. The grooves may be created using a chisel tool adapted for use with the minimally invasive procedure.

[0296] Optionally, a third prosthetic disc may be implanted using the methods described above. The third prosthetic disc is preferably implanted at a center point, between the two prosthetic discs **100** shown in FIG. **51**. The third disc would be implanted prior to the two discs shown in the Figure. Preferably, the disc would be implanted by way of either one of the cannulas, then rotated by 90.degree. to its final load bearing position between the other two prosthetic discs. The first two prosthetic discs **100** would then be implanted using the method described above.

[0297] An alternative minimally invasive implantation method and apparatus is illustrated schematically in FIGS. **52A-B**. In this alternative implantation method, a single cannula **700** is used. The cannula is inserted on one side of the vertebral canal in the manner described above. Once the cannula is inserted, a chisel is used to create a groove **701** having a 90.degree. bend on the interior surfaces of the two

adjacent vertebral bodies. Thus, the terminal portion of the groove **702** is perpendicular to the axis defined by the insertion cannula **700**.

[0298] Turning to FIG. **52B**, a dual prosthetic disc **710** structure is shown. The dual disc **710** includes a pair of one-piece structure prosthetic discs **100a-b** identical in structure to those described above in relation to FIGS. **50A-B**. The two prosthetic discs **100a-b** of the dual disc **710** are joined by a separating mechanism **711**. The separating mechanism **711** is accessed remotely by the surgeon after the dual disc **710** has been implanted into a patient's spinal column, and is adapted to drive the two prosthetic discs **100a-b** apart once they are implanted. The separating mechanism **711** may be a screw device such as a worm screw, a ratcheting mechanism, a spring, or any other mechanism suitable for providing the capability of applying a separating force between the two prosthetic discs **100a-b** of the dual disc **710**. Preferably, an anchoring fin **111** is provided on only one of the prosthetic discs **100a**. Thus, when the dual disc **710** is implanted, the anchoring fin **111** of the first prosthetic disc **100a** will retain the first disc **100a** in place while the ratcheting mechanism **711** causes the second disc **100b** to be separated spatially from the first disc **100a**, as shown by the arrow "D".

[0299] The subject devices and systems may be provided in the form of a kit for performing the methods of the present invention. The kits may include instructions for using the various devices and systems.

Part C

I. Information Concerning the Descriptions Contained Herein

[0300] It is to be understood that the inventions that are the subject of this patent application are not limited to the particular embodiments described, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present invention will be limited only by the appended claims.

[0301] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which these inventions belong. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present inventions, the preferred methods and materials are herein described.

[0302] All patents, patent applications, and other publications mentioned herein are hereby incorporated herein by reference in their entireties. The patents, applications, and publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

[0303] As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present inventions.

[0304] The preceding merely illustrates the principles of the invention. It will be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally intended to aid the reader in understanding the principles of the invention and the concepts contributed by the inventors to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the invention as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents and equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure. The scope of the present invention, therefore, is not intended to be limited to the exemplary embodiments shown and described herein. Rather, the scope and spirit of present invention is embodied by the appended claims.

We claim as our invention:

1. A prosthetic intervertebral disc comprising: a first endplate, a second endplate having a slot on its internal periphery, a core member fixedly attached on a first side to said first endplate and having a flange on a second side opposite said first side, said flange adapted to engage the slot on said second endplate to thereby attach said core member to said second endplate.

2. The prosthetic intervertebral disc of claim **1** further comprising a fixation member for securing said first endplate to a vertebral body.

3. The prosthetic intervertebral disc of claim **1** further comprising a fixation member for securing said second endplate to a vertebral body.

4. The prosthetic intervertebral disc of claim **2** wherein said fixation member comprises at least one anchoring fin.

5. The prosthetic intervertebral disc of claim **3** wherein said fixation member comprises at least one anchoring fin.

6. The prosthetic intervertebral disc of claim **2** wherein said fixation member comprises at least one anchoring spike.

7. The prosthetic intervertebral disc of claim **3** wherein said fixation member comprises at least one anchoring spike.

8. The prosthetic intervertebral disc of claim **2** wherein said fixation member comprises a plurality of serrations formed on an external surface of at least one of said first and said second endplates.

9. The prosthetic intervertebral disc of claim **3** wherein said fixation member comprises a plurality of serrations formed on an external surface of at least one of said first and said second endplates.

10. The prosthetic intervertebral disc of claim **1** wherein said flange of said core member and said slot of said second endplate cooperate to selectively attach said second endplate to said core member while allowing the flange to slide relatively freely within the confines of said slot.

11. The prosthetic intervertebral disc of claim **10** wherein said flange is formed on an inner second endplate attached to said core member.

12. The prosthetic intervertebral disc of claim **10** further comprising a retaining lip formed on said second endplate and adapted to retain said core member on said second end-

plate in a manner that allows the flange to slide relatively freely within the confines of the slot.

13. The prosthetic intervertebral disc of claim **11** further comprising a plurality of fibers connecting said first endplate to said inner second endplate.

14. The prosthetic intervertebral disc of claim **1** further comprising a center core retained within said core member, wherein said center core comprises one of either polyurethane or silicone.

* * * * *