



US 20100292800A1

(19) **United States**

(12) **Patent Application Publication**
Zubok

(10) **Pub. No.: US 2010/0292800 A1**

(43) **Pub. Date: Nov. 18, 2010**

(54) **INTERVERTEBRAL DISC IMPLANTS AND TOOLING**

Related U.S. Application Data

(60) Provisional application No. 60/846,196, filed on Sep. 21, 2006.

(75) Inventor: **Rafail Zubok**, Midland Park, NJ (US)

Publication Classification

(51) **Int. Cl.**
A61F 2/44 (2006.01)

(52) **U.S. Cl.** 623/17.16

Correspondence Address:
**LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK
600 SOUTH AVENUE WEST
WESTFIELD, NJ 07090 (US)**

(57) **ABSTRACT**

A kit for preparing an intervertebral disc space for receiving an implant (100) includes a plurality of trials (152) having different sizes. Each trial (152) includes a body (154) insertible into an intervertebral disc space, the body (154) having a leading end (162), a trailing end (164), a top surface (156) and a bottom surface (160), the top surface of the body having a first groove (176) formed therein. Each implant also includes a flange (166) secured to the trailing end (164) of the body (154), the flange (166) having a first channel (180) aligned with the first groove (176), wherein each of the different sized trials has a different flange thickness. The flange thickness controls advancement of a cutting tool such as a chisel (192) into the first groove at the top surface of the trial body, which controls the depth of the cut into vertebral bone.

(73) Assignee: **SPINECORE, INC.**, Summit, NJ (US)

(21) Appl. No.: **12/442,181**

(22) PCT Filed: **Sep. 21, 2007**

(86) PCT No.: **PCT/US2007/020562**

§ 371 (c)(1),
(2), (4) Date: **Aug. 5, 2010**




FIG. 1A















FIG. 1B










FIG. 5B




FIG. 5C





FIG. 5D







FIG. 6A

FIG. 6B




FIG. 6E




FIG. 6C




FIG. 6D

FIG. 7A

210




FIG. 7B

210




FIG. 7C

210




FIG. 8A




FIG. 8B




FIG. 8D




FIG. 8E




FIG. 8F





FIG. 8C










FIG. 11B




FIG. 11C





FIG. 11A







FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B





FIG. 18C



INTERVERTEBRAL DISC IMPLANTS AND TOOLING

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of the filing date of U.S. Provisional Patent Application No. 60/846,196 filed Sep. 21, 2006, the disclosure of which is hereby incorporated herein by reference.

[0002] The present application is related to U.S. patent application Ser. No. 11/439,808, filed May 24, 2006, which claims the benefit of U.S. Provisional Patent Application No. 60/790,415, filed Apr. 7, 2006, which claims the benefit of U.S. Provisional Patent Application No. 60/721,053, filed Sep. 27, 2005, which claims the benefit of U.S. Provisional Patent Application No. 60/701,306, filed Jul. 21, 2005, which claims the benefit of U.S. Provisional Patent Application No. 60/685,295, filed May 27, 2005, the disclosures of which are hereby incorporated by reference herein.

[0003] The present application also relates to U.S. Pat. No. 6,908,484, entitled "Cervical Disc Replacement" and filed on Mar. 6, 2003; U.S. Pat. No. 6,994,728, entitled "Cervical Disc Replacement Method" and filed on Feb. 11, 2004; United States Patent Application Publication No. 2004/0176851, entitled "Cervical Disc Replacement" and filed on Feb. 11, 2004; U.S. Pat. No. 6,994,729, entitled "Cervical Disc Replacement" and filed on Feb. 11, 2004; U.S. Pat. No. 6,997,955, entitled "Cervical Disc Replacement" and filed on Feb. 11, 2004; U.S. Pat. No. 6,972,037, entitled "Cervical Disc Replacement" and filed on Feb. 11, 2004; U.S. Pat. No. 6,972,038, entitled "Cervical Disc Replacement" and filed on Feb. 11, 2004; U.S. Pat. No. 6,997,954, entitled "Cervical Disc Replacement Method" and filed on Feb. 11, 2004; United States Patent Application Publication No. 2005/0240272, entitled "Cervical Disc Replacement" and filed on May 9, 2005; United States Patent Application Publication No. 2005/0240271, entitled "Cervical Disc Replacement" and filed on May 9, 2005; United States Patent Application Publication No. 2005/0240270, entitled "Cervical Disc Replacement" and filed on May 9, 2005; U.S. Pat. No. 6,896,676, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Oct. 17, 2003; United States Patent Application Publication No. 2004/0176773, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176843, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176778, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176777, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176852, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176774, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0176772, entitled "Instrumentation And Methods For Use In Implant-

ing A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2004/0220590, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 18, 2004; United States Patent Application Publication No. 2005/0071013, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Nov. 19, 2004; and United States Patent Application Publication No. 2004/0193272, entitled "Instrumentation And Methods For Use In Implanting A Cervical Disc Replacement Device" and filed on Feb. 19, 2004, the disclosures of which are hereby incorporated by reference herein.

[0004] The present application also relates to U.S. Pat. No. 6,607,559, entitled "Trial Intervertebral Distraction Spacers" and filed on Jul. 16, 2001; U.S. patent application Ser. No. 10/436,039, entitled "Trial Intervertebral Spacers" and filed May 12, 2003; U.S. patent Ser. No. 10/128,619, entitled "Intervertebral Spacer Having A Flexible Wire Mesh Vertebral Body Contact Element" and filed Apr. 23, 2002; U.S. patent application Ser. No. 11/073,987, entitled "Intervertebral Spacer Having A Flexible Wire Mesh Vertebral Body Contact Element"; U.S. patent application Ser. No. 10/140,153, entitled "Artificial Intervertebral Disc Having A Flexible Wire Mesh Vertebral Body Contact Element" and filed May 7, 2002; U.S. patent application Ser. No. 10/151,280, entitled "Tension Bearing Artificial Disc Providing A Centroid Of Motion Centrally Located Within An Intervertebral Space" and filed May 20, 2002; U.S. patent application Ser. No. 10/175,417, entitled "Artificial Intervertebral Disc Utilizing A Ball Joint Coupling" and filed Jun. 19, 2002; U.S. patent application Ser. No. 10/256,160, entitled "Artificial Intervertebral Disc" and filed Sep. 26, 2002; U.S. patent application Ser. No. 10/294,983, entitled "Artificial Intervertebral Disc Having A Captured Ball And Socket Joint With A Solid Ball And Retaining Cap" and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/294,982, entitled "Artificial Intervertebral Disc" and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/294,981, entitled "Artificial Intervertebral Disc Having A Captured Ball And Socket Joint With A Solid Ball And Compression Locking Post" and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/642,523, entitled "Axially Compressible Artificial Intervertebral Disc Having Limited Rotation Using A Captured Ball and Socket" and filed Aug. 15, 2003; U.S. patent application Ser. No. 10/642,522, entitled "Artificial Intervertebral Disc Having A Circumferentially Buried Wire Mesh Endplate Attachment Device and filed Aug. 15, 2003; U.S. patent application Ser. No. 11/073,987, entitled "Intervertebral Spacer Device Having A Circumferentially Buried Wire Mesh Endplate Attachment Device" and filed Aug. 15, 2003; U.S. patent application Ser. No. 10/642,526, entitled "Circumferentially Buried Wired Mesh Endplate Attachment Device For Use With An Orthopedic Device" and filed Aug. 15, 2003; U.S. patent application Ser. No. 10/294,984, entitled "Artificial Intervertebral Disc Having Limited Rotation Using A Captured Ball And Socket Joint With A Retaining Cap And A Solid Ball Having A Protrusion" and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/294,985, entitled "Artificial Intervertebral Disc Having Limited Rotation Using A Captured Ball and Socket Joint With A Compression" and filed Ser. No. 10/294,985; U.S. patent application Ser. No. 10/294,980, entitled "Artificial Intervertebral Disc Having Limited Rotation Using A Captured Ball And Socket Joint With A Solid Ball, A Retain-

ing Cap, And An Interference Pin” and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/294,986, entitled “Artificial Intervertebral Disc Having Limited Rotation. Using A Captured Ball and Socket Joint With A Solid Ball, A Compression Locking Post, And An Interference Pin” and filed Nov. 14, 2002; U.S. patent application Ser. No. 10/282,356, entitled “Artificial Intervertebral Disc” and filed Sep. 26, 2002; U.S. patent application Ser. No. 10/784,646, entitled “Artificial Intervertebral Disc Having A Controllably Separable Distal End” and filed Feb. 23, 2004; U.S. patent application Ser. No. 10/309,585, entitled “Static Trials And Related Instruments and Methods For Use In Implanting An Artificial Intervertebral Disc” and filed Dec. 4, 2002; U.S. patent application Ser. No. 10/784,637, entitled “Instrumentation For Properly Seating An Artificial Disc In An Intervertebral Space” and filed Feb. 23, 2004; U.S. patent application Ser. No. 10/783,153, entitled “Parallel Distractor And Related Methods For Use In Implanting An Artificial Intervertebral Disc” and filed Feb. 20, 2004, the disclosures of which are hereby incorporated by reference herein.

BACKGROUND OF THE INVENTION

[0005] The present invention is directed to a spinal joint replacement implant and more particularly to a cervical intervertebral disc implant having saddle shaped articulating surfaces and to tooling and methods of inserting the cervical intervertebral disc implant.

[0006] As is well known to those skilled in the art, the structure of the intervertebral disc disposed between the cervical bones in the human spine comprises a peripheral fibrous shroud (the annulus) which circumscribes a spheroid of flexibly deformable material (the nucleus). The nucleus comprises a hydrophilic, elastomeric cartilaginous substance that cushions and supports the separation between the bones while also permitting articulation of the two vertebral bones relative to one another to the extent such articulation is allowed by the other soft tissue and bony structures surrounding the disc. The additional bony structures that define pathways of motion in various modes include the posterior joints (the facets) and the lateral intervertebral joints (the unco-vertebral joints). Soft tissue components, such as ligaments and tendons, constrain the overall segmental motion as well.

[0007] Traumatic, genetic, and long term wearing phenomena contribute to the degeneration of the nucleus in the human spine. This degeneration of this critical disc material, from the hydrated, elastomeric material that supports the separation and flexibility of the vertebral bones, to a flattened and inflexible state, has profound effects on the mobility (instability and limited ranges of appropriate motion) of the segment, and can cause significant pain to the individual suffering from the condition. Although the specific causes of pain in patients suffering from degenerative disc disease of the cervical spine have not been definitively established, it has been recognized that pain may be the result of neurological implications (nerve fibers being compressed) and/or the subsequent degeneration of the surrounding tissues (the arthritic degeneration of the facet joints) as a result of their being overloaded.

[0008] Traditionally, the treatment of choice for physicians caring for patients who suffer from significant degeneration of the cervical intervertebral disc is to remove some, or all, of the damaged disc. In instances in which a sufficient portion of the intervertebral disc material is removed, or in which much

of the necessary spacing between the vertebrae has been lost (significant subsidence), restoration of the intervertebral separation is required.

[0009] Unfortunately, until the advent of spine arthroplasty devices, the only methods known to surgeons to maintain the necessary disc height necessitated the immobilization of the segment. Immobilization is generally achieved by attaching metal plates to the anterior or posterior elements of the cervical spine, and the insertion of some osteoconductive material (autograft, allograft, or other porous material) between the adjacent vertebrae of the segment. This immobilization and insertion of osteoconductive material has been utilized in pursuit of a fusion of the bones, which is a procedure carried out on tens of thousands of pain suffering patients per year.

[0010] This sacrifice of mobility at the immobilized, or fused, segment, however, is not without consequences. It was traditionally held that the patient's surrounding joint segments would accommodate any additional articulation demanded of them during normal motion by virtue of the fused segment's immobility. While this is true over the short-term (provided only one, or at most two, segments have been fused), the effects of this increased range of articulation demanded of these adjacent segments has recently become a concern. Specifically, an increase in the frequency of returning patients who suffer from degeneration at adjacent levels has been reported.

[0011] Whether this increase in adjacent level deterioration is truly associated with rigid fusion, or if it is simply a matter of the individual patient's predisposition to degeneration is unknown. Either way, however, it is clear that a progressive fusion of a long sequence of vertebrae is undesirable from the perspective of the patient's quality of life as well as from the perspective of pushing a patient to undergo multiple operative procedures.

[0012] While spine arthroplasty has been developing in theory over the past several decades, and has even seen a number of early attempts in the lumbar spine show promising results, it is only recently that arthroplasty of the spine has become a truly realizable promise. The field of spine arthroplasty has several classes of devices. The most popular among these are: (a) the nucleus replacements, which are characterized by a flexible container filled with an elastomeric material that can mimic the healthy nucleus; and (b) the total disc replacements, which are designed with rigid baseplates that house a mechanical articulating structure that attempts to mimic and promote the healthy segmental motion.

[0013] Among these solutions, the total disc replacements have begun to be regarded as the most probable long-term treatments for patients having moderate to severe lumbar disc degeneration. In the cervical spine, it is likely that these mechanical solutions will also become the treatment of choice. At present, there are two devices being tested clinically in humans for the indication of cervical disc degeneration. The first of these is the Bryan disc, disclosed in part in U.S. Pat. No. 6,001,130. The Bryan disc is comprised of a resilient nucleus body disposed in between concave-convex upper and lower elements that retain the nucleus between adjacent vertebral bodies in the spine. The concave-convex elements are L-shaped supports that have anterior wings that accept bone screws for securing to the adjacent vertebral bodies.

[0014] The second of these devices being clinically tested is the Bristol disc, disclosed substantially in U.S. Pat. No. 6,113,637. The Bristol disc is comprised of two L-shaped elements,

with corresponding ones of the legs of each element being interposed between the vertebrae and in opposition to one another. The other of the two legs are disposed outside of the intervertebral space and include screw holes through which the elements may be secured to the corresponding vertebra; the superior element being secured to the upper vertebral body and the inferior element being attached to the lower vertebral body. The opposing portions of each of the elements comprise the articulating surfaces that include an elliptical channel formed in the lower element and a convex hemispherical structure disposed in the channel.

[0015] As is evident from the above descriptions, the centers of rotation for both of these devices, which are being clinically tested in human subjects, is disposed at some point in the disc space. More particularly with respect to the Bryan disc, the center of rotation is maintained at a central portion of the nucleus, and hence in the center of the disc space. The Bristol disc, as a function of its elongated channel (its elongated axis being oriented along the anterior to posterior direction), has a moving center of rotation which is at all times maintained within the disc space at the rotational center of the hemispherical ball (near the top of the upper element).

[0016] Thus, there remains a need for improved intervertebral discs, as well as new and improved methods for safely and efficiently implanting intervertebral discs.

SUMMARY OF THE INVENTION

[0017] Disclosed herein are intervertebral discs or implants, surgical instruments and procedures in accordance with certain preferred embodiments of the present invention. It is contemplated, however, that the implants, instruments and procedures may be slightly modified, and/or used in whole or in part and with or without other instruments or procedures, and still fall within the scope of the present invention. Although the present invention may discuss a series of steps in a procedure, the steps can be accomplished in a different order, or be used individually, or in subgroupings of any order, or in conjunction with other methods, without deviating from the scope of the invention.

[0018] In certain preferred embodiments of the present invention, an intervertebral disc implant includes a top element **102** and a bottom element **104**. The top and bottom elements preferably have opposing articulating surfaces that engage one another. The intervertebral disc implant is adapted to be inserted into a disc space between adjacent vertebrae. In certain preferred embodiments, two or more disc implants can be stacked over one another in two or more successive disc spaces. In still other preferred embodiments, the disc implants are cervical implants.

[0019] The top element of the implant preferably includes a first bone engaging surface having a protrusion and a second articulating surface. The top element desirably includes a posterior end, an anterior end and an opening at the anterior end that is adapted to receive a prong or post of an insertion instrument. The top element desirably includes opposing lateral sides that extend between the posterior end and the anterior end of the top element. In certain preferred embodiments, the intervertebral disc implant may be at least partially coated with an osteoconductive material to facilitate long-term fixation to endplates of vertebral bodies.

[0020] The articulating surface of the top element preferably defines a convex curve or surface extending between the sides. The articulating surface also defines a concave curve or surface extending between the posterior and anterior ends of

the top element. In certain preferred embodiments, the articulating surface defines a toroidal saddle-shaped surface.

[0021] The protrusions on the top element preferably include teeth **122**, which desirably have sloping surfaces. Each of the sloping surfaces preferably has a low point nearer to the posterior end of the top element and a high point nearer to the anterior end of the top element. The sloping surfaces preferably facilitate insertion of the posterior end of the top element into a disc space while making it more difficult for the top element to be removed or discharged from the disc space in a posterior to anterior direction.

[0022] The intervertebral disc implant preferably includes the bottom element having a first bone engaging surface and a second articulating surface that is designed to engage the articulating surface of the top element when the top and bottom elements contact one another. The bottom element includes a posterior end, an anterior end, and lateral sides extending between the posterior end and the anterior end. The first bone engaging surface of the second element includes first and second protrusions, with each protrusion preferably including teeth. The teeth desirably include sloping surfaces having a low point nearer to the posterior end of the bottom element and a high point nearer to the anterior end of the bottom element. The sloping surfaces on the teeth of the bottom element preferably facilitate insertion of the bottom element into a disc space. The teeth have vertical surfaces, however, that hinder or prevent dislodgement of the implant from the disc space. In certain preferred embodiments, the teeth on the top and bottom elements may have the same structure, or one or more features of the teeth described above.

[0023] The bottom element desirably has two openings provided at the anterior end thereof. The two openings are preferably adapted to receive the prongs or pins of an insertion instrument, as will be described in more detail below. In certain preferred embodiments, the bottom element may be at least partially coated with an osteoconductive material to facilitate long-term fixation to a vertebral endplate.

[0024] The articulating surface of the bottom element preferably defines a convex curve or surface extending between the posterior end and the anterior end of the bottom element. The articulating surface preferably defines a concave curve or surface extending between the lateral sides of the bottom element. As will be described in more detail herein, the articulating surface preferably defines a toroidal saddle-shaped surface that engages the articulating surface of the top element when the top and bottom elements are in contact with one another.

[0025] When the top element is assembled with the bottom element, the opposing articulating surfaces are adapted to engage one another. When the top and bottom elements are assembled together, the projection on the top element is offset from the two projections on the bottom element. In prior art devices, it has been observed that stacking two implants in successive disc spaces may result in cracking of vertebral bone between the implants because the apexes on the teeth of the two implants are in alignment. The present invention seeks to avoid this cracking problem by offsetting the projection on the top element from the projections on the bottom element. Although the present invention is not limited by any particular theory of operation, it is believed that providing projections that are offset from one another enables two or more intervertebral disc implants to be inserted into two or

more successive disc spaces, while minimizing the likelihood of cracking the vertebral bodies between the disc spaces.

[0026] Prior to insertion into an intervertebral space, the articulating surface of the top element opposes the articulating surface of the bottom element. In preferred embodiments, the articulating surface of the top element defines a toroidal saddle-shaped surface including a concave surface extending between proximal and anterior ends thereof and a convex surface extending between the sides of the top element. The articulating surface of the bottom element also preferably includes a toroidal saddle-shaped surface having a convex surface extending between the posterior and anterior ends and a concave surface extending between the sides of the bottom element. The articulating surfaces may be similar to the articulating surfaces disclosed in commonly assigned U.S. Pat. No. 6,997,955, the disclosure of which is hereby incorporated by reference herein.

[0027] In other preferred embodiments of the present invention, a kit for preparing an intervertebral disc space for receiving an implant includes a plurality of trials having different sizes. Each trial preferably includes a body insertible into an intervertebral disc space, the body having a leading end, a trailing end, a top surface with a first groove formed therein and a bottom surface with a second groove formed therein. The grooves preferably extend between the leading and trailing ends of the body. Each trial also desirably includes a flange secured to the trailing end of the body, the flange having a first channel aligned with the first groove and a second channel aligned with the second groove, wherein each of the different sized trials has a different flange thickness. Although the present invention is not limited by any particular theory of operation, it is believed that changing the flange thickness will limit the depth to which bone cutting instruments such as a chisel may be advanced into vertebral bone. Thus, in certain preferred embodiments, a smaller sized trial will have a thicker flange and a larger sized trial will have a thinner flange.

[0028] In certain preferred embodiments, the top surface of the body desirably tapers toward the bottom surface of the body between the trailing end and the leading end of the body. In other words, the leading end of the body has a taper which facilitates insertion into a disc space.

[0029] The trial desirably includes a third groove formed in the bottom surface of the body, wherein the first groove is offset from the second and third grooves, and the second and third grooves are spaced from one another. The flange preferably includes a third channel aligned with the third groove in the body.

[0030] In preferred embodiments, the first channel has an upper end having a first width and a lower end having a second width that is less than the first width. The first groove in the body preferably has a width that is substantially the same as the first width of the first channel. The second channel desirably has a lower end having a first width and an upper end having a second width that is less than the first width of the second channel. The second groove in the body desirably has a width that is substantially the same as the first width of said second channel.

[0031] In another preferred embodiment of the present invention, an inserter head for an intervertebral disc implant includes a body having a leading end with a concave surface, whereby the concave surface has an upper end and a lower end. The inserted head preferably includes a first pin projecting from the concave surface adjacent the upper end of the

concave surface, and a pair of second pins spaced from one another and projecting from the concave surface adjacent the lower end of the concave surface. The first pin may be resilient. The inserter head desirably includes a wedge projecting from the concave surface and being disposed between the first pin and the pair of second pins.

[0032] The inserter head desirably includes a first flange projecting upwardly from the body and a second flange projecting downwardly from the body. The first and second flanges are desirably adapted for engaging vertebral bone for limiting advancement of the inserter head into an intervertebral disc space. The inserter head may desirably include a stem projecting from a trailing end of the inserter head for coupling the inserter head to a handle.

[0033] In further preferred embodiments of the present invention, a combination inserter head and intervertebral disc implant includes the intervertebral disc implant having a top element with a posterior end, an anterior end, an opening in the anterior end, a bone engaging surface and an articulating surface. The intervertebral disc implant preferably has a bottom element with a posterior end, an anterior end, a pair of spaced openings in the anterior end, a bone engaging surface and an articulating surface that opposes the articulating surface of the top element.

[0034] In the combination, the inserter head preferably includes a body having a leading end with a concave surface, the concave surface having an upper end and a lower end. The inserter head desirably has a first pin, such as a resilient pin, projecting from the concave surface adjacent the upper end of the concave surface, a pair of second pins spaced from one another and projecting from the concave surface adjacent the lower end of the concave surface, and a wedge projecting from the concave surface and being disposed between the first pin and the pair of second pins. The first pin is disposed in the opening of the top element of the implant and the pair of second pins are disposed in the pair of openings in the bottom element of the implant.

[0035] As noted above, the first pin is preferably resilient for urging the top element of the implant against the wedge of the inserter head. The pair of spaced second pins on the inserter head are desirably spaced from one another by a first distance and the pair of openings in the lower element of the implant are spaced from one another by a second distance that is different than the first distance. In certain preferred embodiments, the first distance is greater than the second distance. In other preferred embodiments, however, the first distance is less than the second distance. The different distances preferably form a friction lock between the pair of pins and the pair of openings in the bottom element.

[0036] In still other preferred embodiments of the present invention, a kit for stabilizing a spinal segment includes a plurality of two-part intervertebral disc implants having different sizes and a plurality of inserter heads having different sizes, whereby each of the inserter heads is adapted for holding together one of the two-part intervertebral disc implants as a single implantable unit.

[0037] The inserter head may have indicia corresponding to the size of the intervertebral disc implant held by the inserter head. The indicia may include a color, code and/or text indicating the size of the intervertebral disc implant held by the inserter head.

[0038] Each intervertebral disc implant preferably has a top element including a bone engaging surface, an articulating surface and an opening at an anterior end thereof, and a

bottom element including a bone engaging surface, an articulating surface and a pair of openings adjacent the anterior end thereof, whereby the inserter head includes pins insertible into the openings at the anterior end for holding the articulating surfaces of the top and bottom elements in contact with one another.

[0039] In certain preferred embodiments, the intervertebral disc implant, or the instruments, may alternatively or additionally incorporate any or all of the features discussed previously, disclosed herein, or discussed in U.S. patents and/or patent applications incorporated by reference herein. Preferably, the configuration of the bearing surfaces of the intervertebral disc implant in this preferred embodiment may be substantially similar to those of the other bearing surface configurations discussed previously, disclosed herein, or incorporated by reference herein.

[0040] It should be noted that features and methods and functionalities of the present invention, including but not limited to features and methods and functionalities for engaging one tool (or parts thereof) with one or more other tools (or parts thereof) or with the implants (or parts thereof), and vice-versa; for addressing, avoiding, manipulating, or engaging the patient's anatomy; for aligning one or more tools with anatomic or non-anatomic reference points; and for aligning the tools and implants with one another and/or a treatment space; are not and should not be limited to those embodied in and achieved by the structures and methods of the specific embodiments described and shown, but rather the structures and methods of the specific embodiments described and shown are merely examples of structures and methods that can achieve certain features and methods and functionalities of the present invention.

[0041] Another aspect of the present invention includes a method of performing spinal surgery including the steps of inserting a trial in an intervertebral disc space between two adjacent vertebrae, cutting a portion of at least one vertebrae while the trial is in the intervertebral disc space, removing the trial, and inserting a two-part intervertebral disc implant in the intervertebral disc space. The method may further include the step of attaching the two-part intervertebral disc implant to an inserter head having a size corresponding to the implant.

[0042] These and other preferred embodiments of the present invention will be described in more detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0043] FIG. 1A shows a side elevational view of an intervertebral disc implant having a top element and a bottom element, in accordance with certain preferred embodiments of the present invention.

[0044] FIG. 1B shows a perspective view of the intervertebral disc implant shown in FIG. 1A.

[0045] FIGS. 2A-2G show the top element of the intervertebral disc implant shown in FIGS. 1A and 1B.

[0046] FIGS. 3A-3G show the bottom element of the intervertebral disc implant shown in FIGS. 1A and 1B.

[0047] FIGS. 4A-4C show a combination trial and chisel guide used for preparing an intervertebral disc space for receiving the intervertebral disc implant shown in FIGS. 1A and 1B, in accordance with certain preferred embodiments of the present invention.

[0048] FIGS. 5A-5D show a chisel used with the combination trial and chisel guide of FIGS. 4A-4C, in accordance with certain preferred embodiments of the present invention.

[0049] FIGS. 6A-6E show the chisel of FIGS. 5A-5D assembled with the combination trial and chisel guide of FIGS. 4A-4C.

[0050] FIGS. 7A-7C show an inserter head for inserting the intervertebral disc implant of FIGS. 1A-1B into an intervertebral disc space, in accordance with certain preferred embodiments of the present invention.

[0051] FIGS. 8A-8F show the inserter head of FIGS. 7A-7C coupled with the intervertebral disc implant of FIGS. 1A-1B.

[0052] FIGS. 9A-9D show a handle attachable to the combination trial and chisel guide of FIGS. 4A-4C and the inserter head of FIGS. 7A-7C, in accordance with certain preferred embodiments of the present invention.

[0053] FIG. 10 shows a pusher rod, in accordance with certain preferred embodiments of the present invention.

[0054] FIGS. 11A-11C show the handle of FIGS. 9A-9C attached to the inserter head of FIGS. 7A-7C.

[0055] FIGS. 12A-12C show the pusher rod of FIG. 10 coupled with the handle of FIGS. 9A-9C.

[0056] FIG. 13 shows a combination trial and chisel guide, in accordance with one preferred embodiment of the present invention.

[0057] FIG. 14 shows a combination trial and chisel guide, in accordance with another preferred embodiment of the present invention.

[0058] FIG. 15 shows a combination trial and chisel guide, in accordance with still another preferred embodiment of the present invention.

[0059] FIG. 16 shows a combination trial and chisel guide, in accordance with yet a further preferred embodiment of the present invention.

[0060] FIGS. 17A-17C show respective top plan, side elevational and cross-sectional views of an intervertebral disc implant coupled with an inserter head, in accordance with certain preferred embodiments of the present invention.

[0061] FIGS. 18A-18C show respective top plan, side elevational and cross-sectional views of an intervertebral disc implant coupled with an inserter head, in accordance with further preferred embodiments of the present invention.

DETAILED DESCRIPTION

[0062] Referring to FIGS. 1A and 1B, in certain preferred embodiments of the present invention, an intervertebral disc implant **100** includes a top element **102** and a bottom element **104**. As will be described in more detail below, the top and bottom elements **102**, **104** have opposing articulating surfaces that engage one another. The intervertebral disc implant is adapted to be inserted into a disc space between adjacent vertebrae. In certain preferred embodiments, two or more disc implants can be stacked over one another in two or more successive disc spaces. In still other preferred embodiments, the disc implants are cervical implants.

[0063] Referring to FIGS. 2A-2E, the top element **102** includes a first bone engaging surface **106** having a protrusion **108** and a second articulating surface **110**. Referring to FIGS. 2E-2G, the top element **102** has a posterior end **112** and an anterior end **114**. As shown in FIGS. 2A-2B and 2D, the top element **102** has an opening **116** at the anterior end **114** thereof that is adapted to receive a prong or post of an insertion instrument, as will be described in more detail below. Referring to FIGS. 2C-2D and 2F-2G, the top element **102** has opposing lateral sides **118**, **120** that extend between the posterior end **112** and the anterior end **114** of the top element.

In certain preferred embodiments, the intervertebral disc implant may be at least partially coated with an osteoconductive material to facilitate long-term fixation to endplates of vertebral bodies.

[0064] Referring to FIGS. 2C and 2D, the articulating surface 110 preferably defines a convex curve or surface extending between the sides 118, 120 of the top element 102. Referring to FIGS. 2A and 2E, the articulating surface 110 also defines a concave curve or surface extending between the posterior and anterior ends 112, 114 of the top element 102. In certain preferred embodiments, the articulating surface 110 defines a toroidal saddle-shaped surface.

[0065] As shown in FIGS. 2A-2E and 2G, the protrusion 108 preferably includes teeth 122. Referring to FIG. 2E, the teeth 122 desirably have sloping surfaces 124, each sloping surface preferably having a low point nearer to the posterior end 112 of the top element 102 and a high point nearer to the anterior end 114 of the top element 102. Referring to FIGS. 2E and 2G, the sloping surfaces 124 preferably facilitate insertion of the posterior end 112 of the top element 102 into a disc space while making it more difficult for the top element to be removed or discharged from the disc space. Thus, referring to FIG. 2G, the sloping surfaces 124 of the teeth 122 facilitate insertion of the implant in a direction indicated by arrow D₁, while the vertical surfaces 126 (FIG. 2E) of the teeth 122 hinder or prevent dislodgement of the implant in the direction indicated by arrow D₂.

[0066] Referring to FIGS. 3A-3E, the intervertebral disc implant preferably includes the bottom element 104 having a first bone engaging surface 128 and a second articulating surface 130 that is designed to engage the articulating surface 110 of the top element 102 (FIG. 2A) when the top and bottom elements contact one another. The bottom element 104 includes a posterior end 132, an anterior end 134, and lateral sides 136, 138 extending between the posterior end and the anterior end. Referring to FIGS. 3C-3D and 3G, the first bone engaging surface 128 of the second element includes first and second protrusions 140A, 140B, with each protrusion 140A, 140B preferably including teeth 144. Referring to FIGS. 3E and 3G, the teeth include sloping surfaces 146 having a low point nearer to the posterior end 132 of the bottom element 104 and a high point nearer to the anterior end 134 of the bottom element 104. Referring to FIG. 3G, similar to the sloping surfaces 146 of the teeth of the top element 102 described above, the sloping surfaces 146 on the teeth 144 facilitate insertion of the bottom element 104 in the direction indicated by arrow D₃. The teeth 144 have vertical surfaces 147, however, that hinder or prevent dislodgement of the implant in the direction indicated by arrow D₄.

[0067] Referring to FIGS. 3A-3B, 3D and 3F, the bottom element 108 has two openings 150A, 150B provided at the anterior end 134 thereof. The openings 150A, 150B are preferably adapted to receive the prongs of an insertion instrument, as will be described in more detail below. In certain preferred embodiments, the bottom element 104 may be at least partially coated with an osteoconductive material to facilitate long-term fixation to a vertebral endplate.

[0068] Referring to FIGS. 3A and 3E, the articulating surface 130 preferably defines a convex curve or surface extending between the posterior end 132 and the anterior end 134 of the bottom element 104. Referring to FIGS. 3C and 3D, the articulating surface 130 preferably defines a concave curve or surface extending between the lateral sides 136, 138 of the bottom element 104. As will be described in more detail

herein, the articulating surface 130 preferably defines a toroidal saddle-shaped surface that engages the articulating surface 110 of the top element 102 (FIG. 2A) when the top end bottom elements are in contact with one another.

[0069] FIGS. 1A and 1B show the top element 102 of FIG. 2A being assembled with the bottom element 104 of FIG. 3A. The opposing articulating surfaces 110, 130 of the respective top element 102 and the bottom element 104 are adapted to engage one another. The teeth 122 on the top element 102 slope downwardly toward the posterior end 112 of the top element. Similarly, the teeth 144 on the bottom element 104 slope downwardly toward the posterior end 132 of the bottom element.

[0070] Referring to FIG. 1B, when the top and bottom elements 102, 104 are assembled together, the projection 108 on the top element 102 is offset from the two projections 140A, 140B on the bottom element 104. In prior art devices, it has been observed that stacking two implants in successive disc spaces may result in cracking of vertebral bone between the implants because the apexes on the teeth of the two implants are in alignment. The present invention seeks to avoid this cracking problem by offsetting the projection 108 on the top element 102 from the projections 140A, 140B on the bottom element 104. Although the present invention is not limited by any particular theory of operation, it is believed that providing projections 108, 140 that are offset from one another enables two or more intervertebral disc implants to be inserted into two or more successive disc spaces, while minimizing the likelihood of cracking the vertebral bodies between the disc spaces.

[0071] Referring to FIGS. 1A-1B, in preferred embodiments of the present invention, prior to insertion into an intervertebral space, the articulating surface 110 of the top element 102 opposes the articulating surface 130 of the bottom element 104. In preferred embodiments, the articulating surface 110 of the top element 102 defines a toroidal saddle-shaped surface including a concave surface extending between proximal and anterior ends 112, 114 thereof and a convex surface extending between the sides 118, 120 of the top element 102. The articulating surface 130 of the bottom element 104 also preferably includes a toroidal saddle-shaped surface having a convex surface extending between the posterior and anterior ends 132, 134 and a concave surface extending between the sides 136, 138 of the bottom element 104.

[0072] The articulating surfaces may be similar to the articulating surfaces disclosed in commonly assigned U.S. Pat. No. 6,997,955, the disclosure of which is hereby incorporated by reference herein. In certain preferred embodiments of the present invention, the longitudinally inwardly directed articulation surface of the top element 102 forms a constant radii saddle-shaped articulation surface. More particularly, the saddle surface is defined by a concave arc that is swept perpendicular to and along a convex arc. The articulation surface has a cross-section in one plane that forms a concave arc, and a cross-section in another plane (perpendicular to that plane) that forms a convex arc. The concave arc has a respective constant radius of curvature about an axis perpendicular to the one plane. The convex arc has a respective constant radius of curvature about an axis perpendicular to the other plane.

[0073] In a preferred embodiment, the concave arc has a constant radius of curvature A about an axis perpendicular to the anterior-posterior plane, and the convex arc has a constant

radius of curvature B about an axis perpendicular to the lateral plane. Preferably, radius A is less than radius B.

[0074] The longitudinally inwardly directed articulation surface of the bottom element **104** also preferably forms a constant radii saddle-shaped articulation surface. More particularly, the saddle-shaped surface is defined by a convex arc that is swept perpendicular to and along a concave arc. The articulation surface has a cross-section in one plane that forms a convex arc, and a cross-section in another plane (perpendicular to that plane) that forms a concave arc. The convex arc has a respective constant radius of curvature about an axis perpendicular to the one plane. The concave arc has a respective constant radius of curvature about an axis perpendicular to the other plane.

[0075] In a preferred embodiment, the convex arc has a constant radius of curvature C about an axis perpendicular to the anterior-posterior plane, and the concave arc has a constant radius of curvature D about an axis perpendicular to the lateral plane. Preferably, radius C is less than radius D.

[0076] The constant radii saddle shaped articulation surfaces of the top and bottom elements are configured and sized to be nestable against one another and articulatable against one another, to enable adjacent vertebral bones (against which the top and bottom elements are respectively disposed in the intervertebral space) to articulate in flexion, extension, and lateral bending. More particularly, the intervertebral disc of the present invention is assembled by disposing the top and bottom elements so that the vertebral body contact surfaces are directed away from one another, and the articulation surfaces are nested against one another such that the concave arcs accommodate the convex arcs.

[0077] Accordingly, movement of the adjacent vertebral bones relative to one another is permitted by the movement of the top and bottom elements relative to one another. In flexion and extension, the concave arcs of the top element **102** ride on the convex arcs of the bottom element **104** about a center of rotation below the articulation surfaces. In lateral bending, the concave arcs of the bottom element **104** ride on the convex arcs of the top element **102** about a center of rotation above the articulation surfaces. During these articulations, the elements are maintained at constant relative distraction positions, i.e., the elements do not move in directions that are directed away from one another (for example, do not move in opposing axial directions from one another (e.g., along a longitudinal axis of the spine)). Accordingly, in certain preferred embodiments, the present invention provides a pair of articulation surfaces that have a center of rotation above the surfaces in one mode of motion (e.g., lateral bending), and a center of rotation below the surfaces in another (e.g., flexion/extension), consistent in these regards with the motion of a natural intervertebral joint, such as a cervical joint. Preferably, the articulation surfaces are sized and configured so that the respective ranges of angles through which flexion/extension and lateral bending can be experienced are equal to or greater than the respective normal physiologic ranges for such movements in the cervical spine.

[0078] It is preferable that, in addition to the flexion, extension, and lateral bending motions described above, the adjacent vertebral bones be permitted by the intervertebral disc implant to axially rotate relative to one another (e.g., about the longitudinal axis of the spinal column) through a small range of angles without moving in opposite (or otherwise directed away from one another) directions (e.g., along the longitudinal axis) within that range, and then to engage in such oppo-

site (or otherwise directed away from one another) movement once that range is exceeded. Preferably, the articulation surfaces are accordingly configured and sized to permit such movements. Because of the differing radii of the opposing articulation surfaces, the top and bottom elements are able to axially rotate relative to one another about the longitudinal axis of the spinal column through a range of angles without causing the vertebral body contact surfaces to move away from one another along the longitudinal axis. Once the axial rotation exceeds that range, however, the articulation surfaces interfere with one another as the concave arcs move toward positions in which they would be parallel to one another, and the distance between the vertebral body contact surfaces increases with continued axial rotation as the concave arcs ride up against their oppositely directed slopes. Thus, the articulation surfaces are configurable according to the present invention to permit normal physiologic axial rotational motion of the adjacent vertebral bones about the longitudinal axis through a range of angles without abnormal immediate axially opposite (or otherwise directed away from one another) movement, and to permit such axially opposite (or otherwise directed away from one another) movement when under normal physiologic conditions it should occur, that is, outside that range of angles.

[0079] The articulation surfaces preferably maintain contact over a range of normal physiologic articulating movement between the adjacent vertebral bones. That is, through flexion, extension, lateral bending, and axial rotation, the articulation surfaces are in contact with one another. Preferably, the surface area dimensions of the articulation surfaces are selected in view of the selected radii of curvature to prevent the edges of the saddle surfaces (particularly the edges of the concave arcs) from hitting any surrounding anatomic structures, or other portions of the opposing upper or lower element, before the limit of the normal physiologic range of an attempted articulation is reached.

[0080] Referring to FIGS. 1A and 1B, the intervertebral disc implant **100** includes the top element **102** and the bottom element **104**. The articulating surface of the top element **102** preferably engages the articulating surface of the bottom element **104**. The articulating surface of the top element **102** defines a convex surface extending between lateral sides **118**, **120** thereof and the articulating surface of the bottom element **104** defines a concave surface extending between the lateral sides **136**, **138** thereof. After the opposing articulating surfaces are in contact with one another, the protrusion **108** on the top element **102** is offset from the protrusion **140A**, **140B** on the bottom element **104**. The offset protrusions preferably permit stacking of two intervertebral disc implants in two successive disc spaces, while minimizing the likelihood of cracking the vertebral bone between the adjacent disc spaces. In other preferred embodiments, the offset protrusions enable three or more intervertebral discs to be stacked atop one another over three or more successive disc spaces.

[0081] Referring to FIG. 1B, the articulating surface **110** of the top element **102** defines a concave surface extending between posterior **112** and anterior **114** ends thereof. The articulating surface **130** of the bottom element **104** defines a convex surface extending between the posterior **132** and anterior **134** ends thereof. The teeth **122** on the protrusion **108** of the top element **102** include sloping surfaces **124** that slope downwardly toward the posterior end **112** of the top element **102**. The teeth **144** on the protrusions **140A**, **140B** of the bottom element **104** have sloping surfaces **146** that slope

downwardly toward the posterior end **132** of the bottom element **104**. As a result, the sloping surfaces **124**, **146** of the respective teeth **122**, **144** slope in the same direction, i.e., toward the posterior ends of the top and bottom elements **102**, **104**. The respective sloping surfaces **124**, **146** facilitate insertion of the implant **100** into a disc space. The vertical surfaces **126**, **147** on the respective teeth **122**, **144**, however, hinder or prevent expulsion or migration of the implant **100** from the disc space after it has been inserted.

[0082] FIGS. 4A-4C show a combination trial and chisel guide **152**, in accordance with certain preferred embodiments of the present invention. Referring to FIG. 4B, the trial **152** includes a body **154** having a top surface **156** with a leading end **158** that is sloped and a bottom surface **160**. The trial body **154** also includes a leading end **162** designed for insertion into a disc space and a trailing end **164**. The trial includes a flange **166** connected with the trailing end **164** of the body **154**. The flange **166** includes an upper flange **168** that projects above top surface **156** of the body **154** and a bottom flange section **170** that projects below the bottom surface **160** of the body **154**. The trailing end **164** of the body **154** includes a stem **172** projecting therefrom. The stem **172** includes a tapered section **174** that engages an end of a handle, as will be described in more detail below.

[0083] Referring to FIG. 4A, the body **154** preferably includes a groove **176** formed in the top surface **156** thereof. The groove **176** extends from the leading end **162** of the body toward the flange **166** at the trailing end of the body. The groove **176** guides advancement of a cutting blade on a chisel for forming an opening in an end plate of a vertebral body to accept the protrusion **108** of the top element **102**, as will be described in more detail below. In certain preferred embodiments of the present invention, it is contemplated that a chisel, broach or other cutting instrument may be used for forming the openings. A chisel typically has cutting edges along its axis. A chisel typically has just a single cutting edge. As used herein, the term chisel is deemed to cover both a chisel and a broach, or any other cutting tool that may be used to cut bone. The bottom surface of the body **154** preferably includes a pair of grooves (FIG. 6B) that are offset from the single groove **176** provided in the top surface **156** of the body **154**. The two grooves at the bottom of the body guide advancement of respective cutting blades on a chisel for forming openings in a second vertebral body that opposes the first vertebral body to accept protrusions **140A** and **140B** of the bottom element **104**. Thus, the trial and chisel guide can be used for forming openings in opposing vertebrae.

[0084] FIG. 4C shows a rear elevational view of the trial and chisel guide shown in FIGS. 4A and 4B. The upper flange portion **168** includes openings **178A**, **178B** that are adapted to receive anchoring elements such as pins or screws for temporarily securing the flange to bone. The upper flange portion **168** also includes a channel **180** having a wider upper end **182** and a narrower lower end **184**. The lower flange portion **170** includes a pair of channels **186A**, **186B**. The first channel **186A** in the lower flange portion **170** has a wider section **188A** that becomes narrower at an upper end **190A** thereof. The lower flange section **170** also includes the second channel **186B** having a lower end **188B** that is wider in an upper end **190B** that is narrower. The cutting blades on the chisel pass through the wider upper ends **182**, **188A** and **188B** of the channels. The cutting blades of the chisel are too wide to pass through the narrow sections **184**, **190A** and **190B** of the

channels. The narrow sections **184**, **190A** and **190B** of the channels provide a relief for cut bone chips and particles to escape.

[0085] As shown in FIG. 4C, the channel **180** in the upper flange part **168** is offset from the two channels **186A**, **186B** in the lower flange portion **170**. The respective channels **180**, **186A**, **186B** are aligned with the respective grooves formed in the upper and lower surfaces of the body of the trial **154**.

[0086] Referring to FIGS. 4A and 4B, in certain preferred embodiments of the present invention, a plurality of trial and chisel guides having different sizes are provided in a kit. The different sized trials are used to determine the correct size for an intervertebral disc implant to be placed in a disc space. Each of the trial and chisel guides may have a body having a different size. The differently sized bodies of the trials may have a different width, height and/or, depth. In addition, the thickness of the flange **166** for the trial may vary. Although the present invention is not limited by any particular theory of operation, it is believed that the thickness of the flange will control how far the cutting blades on a chisel may advance into the grooves on a trial body for controlling the depth of cutting into the vertebral bodies.

[0087] FIGS. 5A-5C show a chisel **192** used for forming openings in opposing vertebral bodies that accept the protrusions of the top element **102** and the bottom element **104**, in accordance with certain preferred embodiments of the present invention. Referring to FIGS. 5B and 5C, the chisel **192** includes a leading end **194** and a trailing end **196**. The chisel includes a handle **198** extending between the leading and trailing ends and a striking surface **200** provided at the trailing end. As will be described in more detail below, after the chisel is assembled with the trial, a hammer, mallet or other similar instrument may be struck against the striking surface **200** for advancing the chisel through the grooves in the body of the trial and into vertebral bone.

[0088] Referring to FIG. 5A, the leading end **194** of the chisel **192** includes a first cutting blade **202** adapted to form an opening in a first vertebral body and second cutting blades **204A**, **204B** for forming openings in a second vertebral body. Referring to FIG. 5B, the chisel includes a notch **206** provided near the leading end thereof that is adapted to accommodate the base **173** of the stem **172** (FIG. 4A) of the trial. When the chisel **192** is assembled with the trial **154** (FIG. 4A), the first cutting blade slides in the groove provided in the upper surface of the trial and the second cutting blades **204** slide in the grooves provided in the bottom surface of the trial. Referring to FIGS. 5C and 5D, the first cutting blade **202** of the chisel is offset from the pair of second cutting blades **204A**, **204B**.

[0089] FIGS. 6A-6E show the chisel **192** of FIG. 5A being assembled with the trial **154** of FIG. 4A. As shown in FIG. 6A, the first cutting blade **202** slides through channel **180** and groove **176** for cutting a first keel opening in an end face of a first vertebral body. Referring to FIGS. 6A and 6B, the pair of second cutting blades **204A**, **204B** pass through channels **186A**, **186B** of lower flange portion **170** and through grooves (not shown) provided in the bottom surface **160** of the trial.

[0090] FIG. 6D shows the pair of second cutting blades **204A**, **204B** extended over the bottom surface of the trial and first cutting blade **202** extending over the top surface of the trial.

[0091] In one preferred embodiment of the present invention, a surgeon selects one of the combination trial and chisel guides from a kit. After the trial and chisel guide is attached to a distal end of a handle (FIGS. 9A and 9B), the surgeon inserts

the body of the trial into the disc space and observes and senses whether the selected trial is the correct size. If the trial is not the correct size, then the surgeon will select a trial having a different size and insert that trial into the disc space. The surgeon will continue to evaluate trials having different sizes until a correctly sized trial has been identified. At that point, the surgeon will note the size of the trial and will use the size information for selecting an appropriately sized chisel and intervertebral disc implant.

[0092] The surgeon will then use the correctly sized trial to form the openings in the opposing faces of the vertebral bodies. While maintaining the body of the trial in the disc space, the surgeon will secure the flange 166 to bone by passing pins or screws through the openings 178A, 178B in the flange (FIG. 4C). The chisel 192 shown in FIGS. 5A-5D will then be assembled with the trial so that the cutting blades are advanceable in the grooves in the body of the trial. A mallet or hammer may be used for driving the cutting blades into the vertebral bodies for forming the above-discussed openings for accepting the protrusions of the top and bottom portions, 102 and 104, respectively.

[0093] In certain preferred embodiments, a plurality of combination trial and chisel guides of different sizes are provided. The bodies of the trial and chisel guides may have different sizes, heights, lengths and/or widths. The flanges provided at the trailing ends of the bodies may also have different thicknesses. In further preferred embodiments, a plurality of chisels are provided, each chisel being size specific to the trial selected. Thus, the prongs of a first chisel may be longer than the prongs of a second chisel so that the respective chisels cut channels in bone having different lengths.

[0094] FIGS. 7A-7C show an inserter head 210 used for inserting an intervertebral disc implant into a disc space, in accordance with certain preferred embodiments of the present invention. Referring to FIG. 7A, the inserter head 210 preferably includes a body 212 having a concave surface 214 at a leading end thereof. Referring to FIGS. 7A and 7B, the body 212 preferably includes a top flange 216 projecting from an upper end thereof and a bottom flange 218 projecting from a lower end thereof. The flanges 216, 218 limit advancement of the inserter head 210 into an intervertebral disc space. The body 212 includes a wedge 220 having a sloping surface. In addition, the leading end of the body 212 includes a first pin 222 adapted to engage the opening in the top element of the intervertebral disc implant (FIG. 1A). The first pin 222 is preferably resilient. When the first pin 222 is inserted into the opening 116 in the top element 102 of the implant (FIG. 2B), the resilient pin 222 presses the articulating surface 110 of the top element against the sloping surface 220 of the wedge 220.

[0095] The leading end of the body of the inserted head also preferably includes a pair of second pins 224A, 224B that are adapted to engage the pair of openings 150A, 150B in the bottom element 104 of the intervertebral disc implant (FIG. 3D). The distance between the second pins 224A, 224B preferably defines a distance that is different than the distance between the openings 150A, 150B in the bottom element on the implant. In one preferred embodiment, the distance between the pins is slightly wider than the distance between the openings 150A, 150B. In another preferred embodiment, the distance between the pins is slightly narrower than the distance between the openings 150A, 150B. These differences preferably form a friction lock between the second pins 224A, 224B and the openings 150A, 150B (FIG. 3D) in the

bottom element. The inserter head preferably has a tapered stem 225 at a trailing end thereof that is adapted to be received in a tapered opening at a leading end of a handle, as will be described in more detail below.

[0096] Referring to FIGS. 8A-8C, the inserter head 210 is adapted to secure the top and bottom elements of the intervertebral disc implant 100. Referring to FIGS. 8D and 8E, the bottom pins 224 of the inserter head 210 slide into the openings 150 in the bottom element 104 of the implant. Referring to FIGS. 8D and 8F, the first resilient pin 222 on the inserted head 210 slides into the opening 116 in the top element 102 of the implant. The first resilient pin urges the articulating surface of the top element against the wedge for securing the top element to the inserted head.

[0097] FIGS. 9A-9D show a handle 230 having a leading end 232, a trailing end 234 and a shaft 236 that extends between the leading and trailing ends. The leading end 232 of the shaft 236 includes a slot 238 formed therein that enables the leading end of the shaft to flex outwardly. Referring to FIG. 9B, the leading end 232 of the shaft 236 also includes a notch 240 that is adapted to slide over the flanges 216, 218 of the inserter head 210 (FIG. 7B) when the handle is assemble with the inserter head. Referring to FIG. 9D, the handle 230 has an opening 239 at the leading end that is tapered. The tapered opening 239 of the handle preferably accommodates the tapered stem 225 of the inserter head 210 (FIG. 7B). The tapered opening 239 of the handle 230 may also accommodate tapered stems on the plurality of combination trial and chisel guides (FIG. 4A). Referring to FIGS. 9A-9C, the trailing end 234 of the handle 230 includes a striking surface 240 that may be struck with a hammer or mallet for advancing the leading end 232 of the handle 230 toward an intervertebral disc space. The shaft 236 preferably has an opening that extends along the length thereof from the leading end 232 to the trailing end 234.

[0098] In certain preferred embodiments of the present invention, a pusher rod 244 includes a shaft 246 having a leading end 248 and a trailing end 250. The trailing end 250 of the shaft 246 includes a radially extending flange 252 having a striking surface 254. The shaft 246 preferably slides within the opening of the handle 230 (FIG. 9A).

[0099] FIGS. 11A-11C show the leading end of the handle 230 of FIGS. 9A-9C secured to the inserter head 210 of FIG. 8A. In turn, the inserter head 210 is holding the top and bottom elements 102, 104 of the intervertebral disc implant. The notches 240 at the leading end of the shaft 236 accommodate the flanges 216, 218 on the inserter head 210.

[0100] In certain preferred embodiments of the present invention, the handle 230 is used to insert the implant 100 into a prepared disc space. The correct size of the implant to be inserted into the disc space was preferably previously determined using the combination trial and chisel guide shown and described above in FIGS. 4A-4C. Referring to FIGS. 12A-12C, in order to disengage the implant 100 from the inserter head 210, the shaft 246 of the pusher rod 244 is advanced into the elongated opening extending through the handle 230 and advanced until the leading end of the pusher rod engages the intervertebral disc implant 100. The pusher rod 244 is further advanced for disengaging the implant 100 from the inserter head 210.

[0101] Referring to FIGS. 13 and 14, in accordance with certain preferred embodiments of the present invention, a surgical kit includes a plurality of trial and chisel guides 152. The trial and chisel guides 152A, 152B have respective bod-

ies **154A**, **154B** having the same sizes (i.e. same length, width and height). In the particular embodiment shown in FIGS. **13-14**, however, the first trial and chisel guide **152A** (FIG. **13**) has a flange **166A** having a first thickness T_1 and the second trial and chisel guide **152B** (FIG. **14**) has a flange **166B** having a second thickness T_2 . The flange thickness T_2 of the second trial and chisel guide **152B** is preferably greater than the thickness T_1 of the first trial and chisel guide **152A**. As shown in FIGS. **13** and **14**, the flange thickness controls how far the cutting blades **202**, **204A**, **204B** of the chisel **192** may advance toward the leading ends **162A**, **162B** of the respective trial and chisel guides **152A**, **152B**. When the same sized chisel **192** having cutting blades of the same length is used, the different flange thicknesses will control the depth of the channels cut into the vertebral bone. In preferred embodiments, the kit may include a plurality of trial and chisel guides having flanges having different thicknesses. In still other preferred embodiments, a surgical kit may have a plurality of trial and chisel guides having a plurality of different sized bodies and/or a plurality of flanges having different thicknesses and/or a plurality of chisels having cutting blades of different lengths.

[0102] Referring to FIGS. **15** and **16**, in accordance with certain preferred embodiments of the present invention, a surgical kit includes a plurality of trial and chisel guides **252A** and **252B**. At least some of the trial and chisel guides **252** in the kit preferably have different sizes. Although only two trial and chisel guides are shown, the kit may include many more trial and chisel guides. In the particular embodiment shown in FIGS. **15-16**, a first trial and chisel guide **252A** (FIG. **15**) has a smaller body **254A** and a second trial and chisel guide **252B** (FIG. **16**) has a larger body **254B**. The respective bodies may differ in size by length and/or width and/or thickness. Even though the trial and chisel guides have bodies with different sizes, both guides have flanges **266A**, **266B** having the same thickness T_3 . In order to control the depth of the cut into the vertebral bone, chisels having cutting blades having different lengths, widths and/or heights may be provided. In FIG. **15**, a first chisel **292A** having cutting blades having a length L_1 is coupled with trial and chisel guide **252A**. In FIG. **16**, a second chisel **292B** having cutting blades having a length L_2 is used. Even though the flange thickness T_3 of the respective trial and chisel guides **252A**, **252B** are the same, the second chisel **292B** is able to cut further into bone due to the longer cutting blades **302B**, **304A** and **304B** on the second chisel. In other preferred embodiments, a plurality of chisels having different cutting blade lengths may be used. In still other preferred embodiments, as noted above, a plurality of chisels having cutting blades having different lengths, widths and/or heights may be provided.

[0103] As noted above, in certain preferred embodiments, a plurality of disc implants having different sizes may be provided. The particular size selected for insertion into the disc space is related to the size of the intervertebral space. Each disc implant may be coupled with an inserter head having a size that matches the size of the disc implant. Thus, a plurality of inserter heads having different sizes may be provided, whereby each inserter head is sized to be coupled with an intervertebral disc implant having a particular size.

[0104] In FIGS. **17A-17C**, a first disc implant **110A** is coupled with a first inserter head **210A**. In FIGS. **18A-18C**, a second disc implant **110B**, which is larger than the first disc implant **100A**, is coupled with a second inserter head **210B**

that is larger than the first inserter head **210A**. Other sized disc implants and inserter heads may also be provided.

[0105] In still other preferred embodiments of the present invention, a surgical kit may include chisels having different sizes such as cutting blades having different lengths, widths and/or heights that may be used for forming channels in bone having different lengths, widths and/or heights. The particular chisel selected may relate to the size of the implant being used. In certain preferred embodiments, the differently sized implants have differently sized bone engaging elements (e.g. teeth or bone engaging projections), thereby requiring differently sized trial and chisel guides and/or chisels for preparing the disc spaces.

[0106] In certain preferred embodiments, a plurality of inserter heads, each holding a different sized implant, are provided. After the surgeon has determined the correct size needed for the implant, the surgeon will select the appropriate inserter head that holds the correctly sized implant. The surgeon will then attach the inserter head to the leading end of the handle for inserting the implant into the prepared disc space. The handle and the attached inserter head are then removed, leaving the implant in the disc space. The inserter head may then be removed from the handle using the pusher rod.

[0107] Prior to implanting the intervertebral disc implant, a review of X-rays, MRI or CT-myelogram is preferably conducted to assess the level to be treated for osteophytes and to compare the intervertebral disc height with the adjacent levels. The patient may be positioned in the supine position to provide for an anterior surgical approach to the cervical spine. Steps should preferably be taken to stabilize the patient's spine in a neutral position and to prevent rotation during the procedure. In certain preferred embodiments, it may be preferable to place a towel or bean bag underneath the patient's shoulders. Tape, a halter or skeletal traction may be used to prevent rotation.

[0108] In certain preferred embodiments, a transverse skin incision may be made at the appropriate level to expose the targeted spinal segment including the discs above and below the target spinal segment. Care should be taken to avoid prolonged retraction pressure on vital structures, such as the esophagus.

[0109] Another step in the intervertebral disc implantation procedure may involve identifying and marking a midline on the target segment of the spine. In certain preferred embodiments, a template is utilized to mark the midline. The size and dimensions of the template may vary. The exact template size selected may be based upon initial estimation of the appropriate implant size from pre-operative X-rays and/or MRI/CT. In still other preferred embodiments, fluoroscopy may be used to verify the midline and lateral margins of the disc space. In addition, the spinous processes are preferably centered.

[0110] A tool such as a scalpel or an electrocautery tool is preferably utilized to score the midline points on the anterior surfaces of the superior and inferior vertebral bodies. Care is preferably taken to ensure that the midline is well defined for all subsequent endplate preparation and implant insertion steps. A cutting tool such, as a scalpel may be used to dissect a window in the annulus of the targeted disc. The size of the window dissected in the annulus preferably approximates the width of an intervertebral disc implant to be inserted therein. In certain preferred embodiments, radiographic imaging such as fluoroscopy may be used to identify osteophytes that extend anteriorly. Any osteophytes that extend anteriorly are

preferably resected back to the vertebral body so that the surfaces of the superior and inferior vertebral bodies are flattened. Moreover, techniques such as radiographic imaging may be used to identify any osteophytes extending downwardly or upwardly into the anterior region of the disc space. Such osteophytes should be resected to the endplates.

[0111] After the targeted spinal segment has been distracted, the discectomy procedure is completed. In preferred embodiments, the posterior and lateral margins of the disc space are cleared of any extraneous matter. The clearing of the lateral and posterior margins preferably extends to the unciniate processes and all the way back to the nerve root and canal. In certain preferred embodiments, lateral fluoroscopy is utilized to check the anterior aspects of the vertebral body for osteophytes. A cutting tool, such as a burr, may be used to further prepare the endplates of the opposing superior and inferior vertebral bodies. The cutting tool may be utilized to smooth out the curvatures of the endplates. After the discectomy has been completed, the endplates of the adjacent vertebral bodies are preferably parallel to one another and relatively uniform, thereby preventing undersizing of the implant.

[0112] In certain preferred embodiments, the decompression of the targeted disc space may be completed by removing any posterior osteophytes or soft tissue material that may inhibit the full distraction of the posterior portion of the targeted disc space. In certain preferred embodiments, it may be necessary to remove the posterior longitudinal ligament (PLL) to achieve optimal restoration of the disc height, decompression and release for post-operative motion. In addition, the posteriolateral corners of the endplates may be resected as needed to provide neural decompression. In certain instances, it may be necessary to remove the posteriolateral uncovertebral joints. The lateral uncovertebral joints are preferably not removed unless they are causing nerve root compression. In addition, in certain preferred embodiments it may be necessary to perform a foraminotomy if there are symptoms of neural/foraminal stenosis.

[0113] In certain preferred embodiments, an appropriately sized intervertebral disc implant is selected and inserted into a targeted disc space. In certain preferred embodiments, the intervertebral disc implant is provided as a single unit with the top and bottom elements of the implant being held together by an implant dispenser (not shown). In preferred embodiments, the dispenser is color coded to correspond to the height of the implant. In addition, the dispenser is preferably marked with the height of the implant and the width of the top and bottom elements. The outer surface of the implant may also be marked with the height and width of the implant, as well as the inferior/superior orientation. In particular preferred embodiments, the anterior face of the implant is marked with the height and width of the implant.

[0114] In preferred embodiments, prior to insertion of the intervertebral disc implant, the size label on the implant is inspected and the size label on the dispenser is also inspected to ensure that the correctly sized implant was selected and that the top element of the implant is oriented for proper insertion. In preferred embodiments, an implant is selected having a height and baseplate dimensions that match the corresponding trial that restored the desired height of the disc space without over-tensioning the annulus or damaging the facets.

[0115] After an appropriately sized intervertebral disc implant has been selected, an inserter head, such as the inserter head shown and described above in FIGS. 7A-7C, is

selected. The selected inserter head preferably has a height and/or dimensions that match the particular dimensions of the selected implant and selected implant dispenser. Thus, a plurality of insert heads having different sizes may be provided and the inserter heads may also be color coded to correspond to the height of the implant and the particular dimensions of the implant dispenser. The inserter head may be a single use component that is discarded after the implantation procedure.

[0116] In certain preferred embodiments, the implant is attached to the inserter head by first matching the superior and inferior labels on the implant dispenser with the inserter head. The pins on the inserter head are then slid into the openings at the anterior ends of the top and bottom elements. The implant is preferably secured to the inserter head when the pins are seated in the openings of the top and bottom elements. Once the implant has been secured to the inserter head, the implant dispenser may be decoupled from the implant. Once secured thereto, the posterior ends of the top and bottom elements of the implant preferably extend beyond the ends of the pins of the inserter head. The implant dispenser may then be detached from engagement with the implant.

[0117] In certain preferred embodiments, the intervertebral disc implant is inserted into a prepared disc space. The inserter head is properly oriented with the disc space. In preferred embodiments, the inserter head includes at least one label or marking that is oriented relative to the superior or inferior vertebral bodies. Preferably, a superior label of the inserter head is oriented on top and an inferior label is oriented on the bottom. As the intervertebral disc is advanced toward the disc space, the implant protrusions/teeth are preferably aligned with the openings previously formed in the endplates. In certain preferred embodiments, fluoroscopy is utilized to check the angle of insertion of the implant. In certain preferred embodiments, the inserter head is preferably advanced toward the disc space until the upper and lower flanges of the inserter head come into contact with the anterior surfaces of the adjacent vertebral bodies.

[0118] In certain preferred embodiments, insertion is completed when the implant is fully disengaged from the inserter head and the top and bottom elements of the implant are positioned between the superior and inferior vertebral bodies. The anterior/posterior positioning of the implant is preferably confirmed to be satisfactory using fluoroscopy. If more posterior positioning of either the top element or the bottom element of the intervertebral disc implant is required, a tamp may be utilized for adjusting the position of the implant. In preferred embodiments, the tamp may be impacted to adjust the anterior/posterior depth of the top and bottom elements of the implant.

[0119] An intraoperative lateral and anterior/posterior image of the implant may be obtained to observe its final position. If the implant is not properly positioned, it may be removed such as by using an extractor. Once it has been confirmed that the intervertebral disc is properly positioned within the disc space, a standard surgical closure procedure for anterior spinal surgery may be performed. Prior to discharge from the hospital, a lateral and anterior/posterior X-ray with the patient in the standing and/or sitting position is preferred.

[0120] Following surgery, in certain preferred embodiments, a goal of post-operative rehabilitation is to return the patient to normal activity as soon as possible without jeopardizing soft and hard tissue healing. Preferably, the patient should wear a soft collar for approximately 1-2 weeks to

support healing of the incision. The patient's rehabilitation program may be modified under the direction of a surgeon to take into consideration the patient's age, stage of healing, general health, physical condition, life-style, and activity goals. Adherence to a recommended rehabilitation program is highly desirable.

[0121] Disclosed herein are implants, surgical instruments and procedures in accordance with certain preferred embodiments of the present invention. It is contemplated, however, that the implants, instruments and procedures may be slightly modified, and/or used in whole or in part and with or without other instruments and procedures, and still fall within the scope of the present invention. Although the present, invention may discuss a series of steps in a procedure, the steps may be accomplished in a different order, or may be used individually, or in conjunction with other methods, without deviating from the scope of the present invention.

[0122] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

INDUSTRIAL APPLICABILITY

[0123] The present invention enjoys wide industrial applicability including, but not limited to, providing implants and instruments useful in spinal surgery.

1. A kit for preparing an intervertebral disc space for receiving an implant comprising:

a plurality of trials having different sizes, each said trial comprising:

a body insertible into an intervertebral disc space, said body having a leading end, a trailing end, a top surface and a bottom surface, said top surface of said body having a first groove formed therein; and

a flange secured to said trailing end of said body, said flange having a first channel aligned with said first groove, wherein each of said different sized trials has a different flange thickness.

2. The kit as claimed in claim 1, wherein said first groove extends between said leading and trailing ends of said body.

3. The kit as claimed in claim 1, wherein said top surface of said body tapers toward said bottom surface of said body between said trailing end and said leading end of said body.

4. The kit as claimed in claim 1, further comprising second and third grooves formed in said bottom surface of each said body, wherein said first groove is offset from said second and third grooves.

5. The kit as claimed in claim 4, wherein said second and third grooves are spaced from one another.

6. The kit as claimed in claim 4, wherein said flange includes a second channel aligned with said second groove in said body and a third channel aligned with said third groove in said body.

7. The kit as claimed in claim 1, wherein said first channel has an upper end having a first width and a lower end having a second width that is less than the first width.

8. The kit as claimed in claim 7, wherein said first channel has a width that is substantially the same as the first width of said first channel.

9. The kit as claimed in claim 6, wherein said second channel has a lower end having a first width and an upper end having a second width that is less than the first width of said second channel, and wherein said third channel has a lower end having a first width and an upper end having a second width that is less than the first width of said third channel.

10. The kit as claimed in claim 9, wherein said second groove has a width that is substantially the same as the first width of said second channel and said second groove has a width that is substantially the same as the first width of said third channel.

11. An inserter head for an intervertebral disc implant comprising:

a body having a leading end with a concave surface;

said concave surface having an upper end and a lower end;

a first pin projecting from said concave surface adjacent said upper end of said concave surface;

a pair of second pins spaced from one another and projecting from said concave surface adjacent said lower end of said concave surface;

a wedge projecting from said concave surface and being disposed between said first pin and said pair of second pins.

12. The inserter head as claimed in claim 11, wherein said first pin is resilient.

13. The inserter head as claimed in claim 11, further comprising:

a first flange projecting upwardly from said body; and

a second flange projecting downwardly from said body, wherein said first and second flanges are adapted for engaging vertebral bone for limiting advancement of said inserter head into an intervertebral disc space.

14. The inserter head as claimed in claim 11, further comprising a stem projecting from a trailing end of said inserter head for coupling said inserter head to a handle.

15. A combination inserter head and intervertebral disc implant comprising:

an intervertebral disc implant having a top element with a posterior end, an anterior end, an opening in the anterior end, a bone engaging surface and an articulating surface;

said intervertebral disc implant having a bottom element with a posterior end, an anterior end, a pair of spaced openings in the anterior end, a bone engaging surface and an articulating surface that opposes the articulating surface of the top element;

said inserter head including a body having a leading end with a concave surface, said concave surface having an upper end and a lower end;

said inserter head having a first pin projecting from said concave surface adjacent said upper end of said concave surface, a pair of second pins spaced from one another and projecting from said concave surface adjacent said lower end of said concave surface, and a wedge projecting from said concave surface and being disposed between said first pin and said pair of second pins, wherein said first pin is disposed in said opening of said top element of said implant and said pair of second pins are disposed in said pair of openings in said bottom element of said implant.

16. The combination as claimed in claim 15, wherein said first pin is resilient and urges said top element of said implant against said wedge of said inserter head.

17. The combination as claimed in claim 15, wherein said pair of spaced second pins on said inserter head are spaced

from one another by a first distance, and said, pair of openings in said lower element of said implant are spaced from one another by a second distance that is different than the first distance for forming a friction lock between said pair of second pins and said bottom element.

18. The combination as claimed in claim **17**, wherein the first distance is greater than the second distance.

19. The combination as claimed in claim **17**, wherein the first distance is less than the second distance.

20. A kit comprising:

a plurality of two-part intervertebral disc implants having different sizes; and

a plurality of inserter heads having different sizes, each said inserter head being adapted for holding together one of said two-part intervertebral disc implants as a single implantable unit, wherein each said inserter head has indicia corresponding to the size of said intervertebral disc implant held by said inserter head.

21. The kit as claimed in claim **20**, wherein said indicia includes a color code.

22. The kit as claimed in claim **20**, wherein said indicia includes text indicating the size of said intervertebral disc implant held by said inserter head.

23. The kit as claimed in claim **20**, wherein each said intervertebral disc implant has a top element including a bone engaging surface, an articulating surface and an opening at an anterior end thereof, and a bottom element including a bone engaging surface, an articulating surface and a pair of openings at an anterior end thereof, wherein said inserter head includes pins insertible into the openings at said anterior ends for holding said articulating surfaces of said top and bottom elements in contact with one another.

24. A method of performing spinal surgery comprising the steps:

inserting a trial in an intervertebral disc space between two adjacent vertebrae;

cutting a portion of at least one vertebrae while the trial is in the intervertebral disc space;

removing the trial; and

inserting a two-part intervertebral disc implant in the intervertebral disc space.

25. The method of claim **24**, further comprising the step of attaching the two-part intervertebral disc implant to an inserter head having a size corresponding to the implant.

* * * * *