



US009687660B2

(12) **United States Patent**
Janzig et al.

(10) **Patent No.:** **US 9,687,660 B2**
(45) **Date of Patent:** ***Jun. 27, 2017**

(54) **ELECTRICAL CONTACT FOR
IMPLANTABLE MEDICAL DEVICE**

H01R 43/02 (2013.01); *H01R 43/16*
(2013.01); *H01R 2107/00* (2013.01); *Y10T*
29/4921 (2015.01)

(71) Applicant: **Medtronic, Inc.**, Minneapolis, MN
(US)

(58) **Field of Classification Search**
CPC A61N 1/3752; A61N 1/375; A61N 1/3754;
A61N 1/3756; H01R 13/11; H01R 24/58;
H01R 2201/12; H01R 9/2491
See application file for complete search history.

(72) Inventors: **Darren A. Janzig**, Center City, MN
(US); **Chris J. Paidosh**, St. Anthony,
MN (US); **Paulette C. Olson**, Eagan,
MN (US); **Gerald G. Lindner**, Lino
Lakes, MN (US)

(56) **References Cited**

(73) Assignee: **MEDTRONIC, INC.**, Minneapolis,
MN (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

4,898,173 A 2/1990 Daglow et al.
4,995,389 A 2/1991 Harris
(Continued)

This patent is subject to a terminal dis-
claimer.

Primary Examiner — Tammie K Heller
(74) *Attorney, Agent, or Firm* — Mueting, Raasch &
Gebhardt, P.A.

(21) Appl. No.: **14/790,171**

(57) **ABSTRACT**

(22) Filed: **Jul. 2, 2015**

(65) **Prior Publication Data**

US 2015/0375002 A1 Dec. 31, 2015

Related U.S. Application Data


(63) Continuation of application No. 12/555,431, filed on
Sep. 8, 2009, now Pat. No. 9,095,728.
(Continued)

A one-piece electrical contact ring for use in a lead recep-
tacle of an implantable medical device includes (i) a tubular
body defining a cavity extending through the body and (ii)
a plurality of resiliently deflectable elements extending from
the tubular body into the cavity. The deflectable elements
have a lead contacting portion configured to contact the lead
when received by the cavity. The lead contacting portions of
the deflectable elements in a relaxed state are located in a
plane that intersects the tubular body and are configured to
deflect along the plane towards the tubular body as the lead
is inserted in the contact ring. The contact ring may further
include a plurality of stops, each configured to (i) engage a
stop portion of the elements when the elements are suffi-
ciently outwardly deflected and (ii) inhibit further outward
deflection of the elements when the stops engage the stop
portions.

(51) **Int. Cl.**
A61N 1/375 (2006.01)
H01R 13/11 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A61N 1/3752* (2013.01); *H01R 13/111*
(2013.01); *H01R 13/42* (2013.01); *H01R*
13/5202 (2013.01); *H01R 24/58* (2013.01);

14 Claims, 13 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/094,499, filed on Sep. 5, 2008.

(51) **Int. Cl.**

H01R 24/58 (2011.01)
H01R 13/42 (2006.01)
H01R 13/52 (2006.01)
H01R 43/02 (2006.01)
H01R 43/16 (2006.01)
H01R 107/00 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,730,628	A	3/1998	Hawkins
7,167,749	B2	1/2007	Biggs et al.
7,402,083	B2	7/2008	Kast et al.
7,711,428	B2	5/2010	Janzig et al.
2004/0167582	A1	8/2004	Tvaska et al.
2005/0027327	A1	2/2005	Ries et al.
2005/0107859	A1	5/2005	Daglow et al.
2006/0004419	A1	1/2006	Olbertz
2006/0047322	A1	3/2006	Naviaux
2006/0095086	A1	5/2006	Balsells




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 9




FIG. 10




FIG . 11A




FIG . 11B




FIG . 11C




FIG . 11D




FIG . 12

1

**ELECTRICAL CONTACT FOR
IMPLANTABLE MEDICAL DEVICE****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation patent application of U.S. patent application Ser. No. 12/555,431, filed on Sep. 8, 2009, now U.S. Pat. No. 9,095,728, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/094,499 filed Sep. 5, 2008, which applications are hereby incorporated herein by reference in their entirety to the extent that they do not conflict with the present disclosure.

FIELD

This application relates to medical devices, more particularly to implantable medical devices operably couplable to leads or lead extensions and to electrical contact assemblies for operably coupling the leads to the devices.

BACKGROUND

Implantable electrical signal generators, such as pacemakers, defibrillators, neurostimulators, and the like, have been used to treat a variety of diseases. Such devices generate electrical signals that are transferred to a patient's tissue through electrodes disposed on a distal end portion of a lead. The proximal end portion of a lead typically contains a number of connector rings corresponding to the number of electrodes. Conductors run within and along the lead body and electrically couple the connectors to the electrodes. The proximal end portion of the lead is inserted into lead receptacle of a signal generator such that electrical contact is made between discrete contacts in the receptacle and the connector rings of the lead. The contacts of the receptacle typically include a garter spring within a ferrule. The ferrule is typically electrically coupled to a feedthrough that provides electrical coupling with electronics of the device. The garter spring contacts a contact ring of a lead, electrically coupling the lead to the device electronics via the ferrule and feedthrough. While such lead receptacle contacts have been proven to perform very well over time, garter rings are difficult to manufacture and must provide two contacts for proper electrical connection: one contact with the lead connector ring, and the other with the ferrule. Further, because of the spring configuration, the spring contacts the lead connector ring and the ferrule at multiple points, with each separate contact resulting in increased electrical resistance. Such resistance could result in undesirably large power consumption.

BRIEF SUMMARY

One-piece conductive contacts that may be used in lead receptacles of implantable medical devices are described herein. For example, a one-piece electrical contact ring for use in a lead receptacle of an implantable medical device includes a tubular body defining a cavity extending through the body. The cavity is configured to receive a lead. The one-piece contact ring further includes a plurality of resiliently deflectable elements extending from the tubular body into the cavity. The deflectable elements have a lead contacting portion configured to contact the lead when the lead is received by the cavity. The lead contacting portions of the deflectable elements in a relaxed state are located in a plane that intersects the tubular body and are configured to deflect

2

along the plane towards the tubular body as the lead is inserted in the contact ring. In various embodiments, the contact ring further includes a plurality of stops, each configured to (i) engage a stop portion of the elements when the elements are sufficiently outwardly deflected and (ii) inhibit further outward deflection of the elements when the stops engage the stop portions.

By employing a one-piece contact ring for a lead receptacle of an implantable medical device, the complexity of assembly of the device is reduced. Further, the number of electrical contacts required to electrically couple the lead to electronics of the device is reduced; i.e., by eliminating the garter spring one less contact is needed with the one-piece contact rings described herein, which may reduce electrical resistance and power consumption. The number of points of contact between the ring contact and lead may also be reduced relative to a garter spring, further reducing potential sources for electrical resistance. In addition, contact rings described herein may be made according to a number of readily available manufacturing techniques. Many of the rings described herein should be readily scalable. These and other advantages will be readily understood from the following detailed descriptions when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of an exploded view of a representative implantable active electrical device and associated lead and extension.

FIG. 2 is a schematic diagram of a perspective view of a representative lead.

FIG. 3 is a schematic diagram of a perspective view of a representative lead.

FIG. 4 is a schematic diagram of a representative spinal cord stimulation (SCS) system implanted in a patient.

FIG. 5A is a schematic diagram of a side view of an active implantable medical device with representative internal components shown in dashed lines.

FIG. 5B is a schematic diagram of a front view of the device depicted in FIG. 5A viewed along line 5b of FIG. 5A.

FIG. 5C is a schematic diagram of a top view of the device depicted in FIG. 5A viewed along line 5c of FIG. 5A.

FIG. 5D is a schematic diagram of a cut away top view of the device depicted in FIG. 5A.

FIG. 5E is a schematic cut away side view of an alternative embodiment of the device depicted in FIG. 5A with representative internal components shown in dashed lines.

FIGS. 6-7 are schematic diagrams of perspective views of embodiments of electrical contact rings.

FIGS. 8A-D and 8F are schematic drawings of front or perspective views of representative embodiments electrical contact rings according to various embodiments.

FIG. 8E is a schematic drawing of a cut away perspective view of a portion of the contact ring depicted in FIG. 8F.

FIGS. 9-10 are schematic drawings of perspective views of sections of embodiments of contact rings having a flange for mating with a seal.

FIGS. 11A-D are schematic drawings of perspective views depicting removal of portions of a solid tubular material to generate a one-piece contact ring.

FIG. 12 is a schematic drawing of subunits of an electrical contact ring disposed about a mandrel.

The drawings are not necessarily to scale. Like numbers used in the figures refer to like components, steps and the like. However, it will be understood that the use of a number to refer to a component in a given figure is not intended to

limit the component in another figure labeled with the same number. In addition, the use of different numbers to refer to components is not intended to indicate that the different numbered components cannot be the same or similar.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings that form a part hereof, and in which are shown by way of illustration several specific embodiments of devices, systems and methods. It is to be understood that other embodiments are contemplated and may be made without departing from the scope or spirit of the present invention. The following detailed description, therefore, is not to be taken in a limiting sense.

All scientific and technical terms used herein have meanings commonly used in the art unless otherwise specified. The definitions provided herein are to facilitate understanding of certain terms used frequently herein and are not meant to limit the scope of the present disclosure.

As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” encompass embodiments having plural referents, unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

As used herein, “active implantable electrical device” or the like refers to a device that is capable of generating, sending or receiving an electrical signal via a medical lead.

As used herein, “tubular” means having the shape and configuration of a tube. “Tube”, as used herein means a hollow object having a body and a cavity extending through the body. A tube may take any suitable shape, such as a cylinder, a cuboid, or the like.

The present disclosure relates to contact rings for lead receptacles of implantable medical devices. The electrical contact rings described herein are one-piece. Such one-piece contacts may result in improved reliability due to decreased number of required contacts, simplified assembly, and ease of manufacturability.

Referring to FIG. 1, a schematic of an exploded view of a representative implantable medical device system 100 in which such one-piece contact rings may be employed is shown. The system 100 includes an implantable active electrical device 10, and a lead 20 operably coupleable to active electrical device 10. Active electrical device 10 may be any electrical signal generator or receiver useful for delivering therapy to a patient or for patient diagnostics. For example, active electrical device 10 may be a hearing implant; a cochlear implant; a sensing or monitoring device; a signal generator such as a cardiac pacemaker or defibrillator, a neurostimulator (such as a spinal cord stimulator, a brain or deep brain stimulator, a peripheral nerve stimulator, a vagal nerve stimulator, an occipital nerve stimulator, a subcutaneous stimulator, etc.), a gastric stimulator; or the like. As shown in FIG. 1, the system 100 may include a lead extension 30 or other adaptor to couple lead 20 to active electrical device 10. While not shown, it will be understood that more than one lead 20 may be operably coupled to one active electrical device 10 or one extension 30 or that more than one extension 30 may be operably coupled to one active electrical device 10. It will also be understood that lead 20 may be coupled to active electrical device 10 without extension 30 or adaptor.

Active electrical device 10 may include a connector header 40 for connecting to lead 20 or extension 30 or other

adaptor to couple lead 20 to active electrical device 10. In the embodiment depicted in FIG. 1, the connector header 40 is configured to receive a proximal connector portion 50 of a lead extension 30. The extension 30 includes a distal connector 60 configured to receive proximal end of lead 20. Distal connector 60 has internal electrical contacts 70 configured to electrically couple extension 30 to lead 20 via electrical contacts 80 disposed on the proximal end portion of lead 20. Electrodes 90 are disposed on distal end portion of lead 20 and are electrically coupled to electrical contacts 80, typically through conductors (not shown) within the body of the lead 20. Lead 20 may include any number of electrodes 90, e.g. one, two, three, four, five, six, seven, eight, sixteen, thirty-two, or sixty-four. Typically, each electrode 90 is electrically coupled to a discrete electrical contact 80.

FIGS. 2 and 3 are schematic perspective views of representative leads 20. Leads 20, as shown in FIGS. 2 and 3, contain four exposed electrical contacts 80 and four electrodes 90. However, it will be understood that a lead 20 may include any number of contacts 80 or electrodes 90, such as 1, 2, 3, 4, 8, 16, 32, or 64. The contacts 80 are typically electrically coupled to the electrode 90 via conductors (not shown) running within the lead body. Typically each contact 80 is operably coupled to a discrete contact in an active electrical medical device such that a discrete electrical signal may be applied to each electrode 90 or electrode pair. The lead contacts 80 may be electrically coupled to the device via direct insertion into a receptacle of the device or via an extension or adaptor (see, e.g., FIG. 1). The lead 20 shown in FIG. 3 is a paddle-type lead. However, it will be understood that any lead configuration may be employed in accordance with the teachings provided herein.

By way of example and referring to FIG. 4, a spinal cord stimulation (SCS) system, is shown implanted in a patient 6. For SCS, an electrical signal generator 10 is typically placed in a medically appropriate location of the patient 6, such as in the abdominal or pectoral region, and distal portion of lead 20 containing electrodes 90 is placed at a desired location along spinal cord 8. The proximal portion of lead 20 is connected to distal connector 60 of lead extension 30, which is connected to device 10. Such a system, or any system including an electrical signal generator 10 as described herein, may also include an external programmer (not shown), such as a physician programmer or a patient programmer, for telemetric communication with the electrical signal generator 10. Electrical signal generator 10 is capable of generating electrical signals that may be applied to tissue of patient 6 via electrodes 90 for therapeutic or diagnostic purposes. Electrical signal generator 10 contains a power source and electronics for sending electrical signals to the spinal cord 8 via electrodes 90 to provide a desired therapeutic effect. It will be appreciated that other systems employing active electrical devices and therapeutic uses thereof are contemplated.

For the purposes of the remainder of this disclosure, “lead” and “lead extension” are used interchangeably.

Referring now to FIG. 5A, a schematic side view of a representative active implantable electrical device 10 is shown, with selected internal components shown in dashed lines. The device 10 includes a header 40 having a lead receptacle 42 extending therein. The lead receptacle 42 is configured to receive a proximal portion of a lead, extension or adaptor. The receptacle 42 includes one or more electrically conductive portions (not shown) configured to electrically couple with proximal contacts 80 of a lead 20 (see, e.g., FIGS. 2-3) or lead extension. The conductive portions are

5

electrically coupled to electronics **15** disposed within hermetically sealed device housing **11**. Hermetically sealed electrical feedthroughs **18** may be used to couple conductive portions of the receptacle **42** to the electronics **15**. In the depicted embodiment, the electronics **15** are operably coupled to a power source **12**, such as a battery, capacitor, or the like. The header **40** may be attached to hermetically sealed housing **11** of device **10** by, for example, fasteners, adhesives, welds, or the like.

In some embodiments (not shown), the lead receptacle **42** extends within hermetically sealed housing **11**. In such embodiments, device **10** may not include a header **40** and feedthroughs **18**. Any suitable hermetically sealed receptacle may be employed in such embodiments, such as those described in U.S. patent application Ser. No. 11/733,247, filed on Apr. 10, 2007, entitled "Hermetic. Lead Connector Assembly", which application is hereby incorporated herein by reference in its entirety to the extent that it does not conflict with the disclosure presented herein.

Referring now to FIG. **5B**, a schematic front view of the header **40** along line **5b** in FIG. **5A** is shown. An opening **110** of the lead receptacle is formed in housing **15**. In FIG. **5C**, a top view of the header **40** along line **5c** in FIG. **5A** is shown. The housing **45** of header **40** defines an opening **120** for receiving a set screw for assisting in retaining a lead in the receptacle.

In FIGS. **5D-E**, schematics of a cut away top view (**5E**) and a cut away side view (**5F**) of an embodiment of a header **40** of FIG. **5A** are shown. In the depicted embodiment, exterior portions of the lead receptacle are shown. In FIG. **5E**, dashed lines represent bores **210**, **220** formed in set screw block **200**. The receptacle includes alternating conductive **150** and insulating **160** sections. The conductive sections **150** are positioned such that when a lead is inserted into the receptacle, a contact on proximal portion may be electrically coupled with a conductive section **150**. The conductive sections **150** of the receptacle are electrically coupled to feedthroughs **18** that couple the conductive sections **150** to electronics of the device. Set screw block **200** of the receptacle may be fixed relative to housing **45**. The lead receptacle may include an end cap **170**. End cap **170** may fit snugly against housing **45** or other feature such that an axially compressive force is applied to the receptacle.

Set screw block **200** defines a lead receiving bore **220** and a second bore **210** configured to receive a set screw. The second bore **210** is generally perpendicular to and intersects with the lead receiving bore **220**. In the depicted embodiment, set screw block **200** is conductive and is electrically coupled to a feedthrough **18** that serves to electrically couple the block **200** to electronics of the device.

While the lead receptacle depicted in FIGS. **5C-E**, include a set screw block, it will be understood that any mechanism for retaining a lead other than a set screw may be employed. It will also be understood that the lead receptacles described herein are applicable to devices having headers that are not fully enclosed by a housing. Such headers are well known and are typically open-faced. Lead receptacles are typically sealed to such header housings with medical adhesive and are back-filled with medical polymeric material, such as silicone, to provide a seal between the electrically conductive portions of the lead receptacle and tissue or fluid of a patient when implanted.

Referring now to FIGS. **6-7**, representative embodiments of one-piece electrical connector contact rings **300** that may serve as conductive portions **150** (see, e.g., FIGS. **5D-E**) of a lead receptacle are shown. The depicted contact rings **300** include a tubular body **310** defining a cavity **320** extending

6

through the body **310**. The cavity **320** is configured to receive a lead. The contact ring **300** includes a plurality resiliently deflectable elements **330**. The deflectable elements **330** have lead contacting portions **335** configured to contact a contact of a lead when the lead is inserted into the cavity **320**. The lead contacting portions **335** of the deflectable elements **330**, in a relaxed state, are located in a plane **900** that intersects the tubular body **310**. The lead contacting portions **335** are configured to deflect along the plane **900** towards the tubular body **320** as the lead is inserted in the cavity **320**. As shown in FIG. **7**, the plane **900** may be orthogonal to the central axis **910** of the cavity **320**. The dashed lines on the tubular body **310** and contacting portions **335** of the deflectable elements **330** shown in FIGS. **6-7** depict the location of intersection of the plane **900**.

Referring now to FIGS. **8A-F**, representative embodiments of one-piece electrical connector contact rings **300** are shown. The contact rings **300** depicted in FIG. **8A** are configured to operate in a manner similar to the ring described with regards to FIG. **6** or FIG. **7**. That is, the rings **300** include tubular bodies **310** defining a cavity **310**, a plurality of resiliently deflectable members **320** extending from the tubular body and having lead contacting portions **335**, where the lead contacting portions **335** lie in a plane that intersects the tubular body **310** and where the contacting portions **335** are configured to deflect along the plane towards the tubular body **310** when the lead is inserted into the cavity **320**. In the embodiments depicted in FIGS. **8A-F**, the deflectable members **330** extend into the cavity **320** in a non-radial manner (in a direction not along a radius). As a lead is inserted into the cavity **320** of contact **300**, elements **330** deflect outwardly (relative to axial center of contact **300**) in a non-radial manner in the depicted embodiments. While portions of the elements **330**, such as lead contacting portion **335**, may deflect outwardly in a radial manner, the overall element **310** is configured to deflect non-radially when a lead is inserted. That is, the sum total of vectors of deflection along the length of an element **330** is non-radial. As used herein, "non-radial" with regard to outward deflection means deflection in a direction other than along a line defined by a radius.

As shown in FIG. **8F**, the lead contacting portions **335** of deflectable elements **300**, in a relaxed state, are located along a circumference of an imaginary circle **400** concentric with the tubular body **310**. The imaginary circle **400** has a diameter that is smaller than the outer diameter of the portion of the lead that the lead contact portions **335** are configured to contact. As the lead is inserted, the elements **330** deflect outwardly (relative to axial center of contact ring **300**) to accommodate insertion of the lead. The resilient nature of the deflectable elements **330** biases the contacting portions **335** toward the circumference of the imaginary circle **400**, forcing the contacting portions **335** against the inserted lead. Of course, if the contact of the lead, with which the lead contacting portions **335** are configured to contact, have an exterior shape different from a cylinder (e.g., cuboid), the lead contacting portions **335** may be configured to located along an imaginary shape (e.g., rectangle) similar in shape to the contact of the lead.

In the representative embodiments shown in FIGS. **8A-F**, contact rings **300** include stops **340** configured to engage a stop portions **332** of elements **330** when the elements are sufficiently outwardly deflected. The stops **340** and stop portions **332** of elements **330** cooperate to inhibit outward deflection of the elements **330** when the stops **340** engage the stop portions **332**. The cooperation of the stops **340** and the stop portions **332** inhibits damage to the elements **332**;

e.g. when a lead is placed into cavity **320** at an undesirable or unintended angle. In various embodiments, tubular body portion **310** of contact ring **300** forms stops **340** (see, e.g., FIGS. **8A** and **8B**). In numerous embodiments, deflectable elements **330** form stops **340** (see, e.g., FIGS. **8C-D**). Any portion of the connector ring **300** that a deflectable element **330** contacts when outwardly deflected serves as a stop **340** provided that further outward deflection is inhibited or prevented. The portion of the element that contacts the stop **340** is the stop portion **332** of the element. As shown in, for example, the embodiments depicted in FIG. **8A** the stop region **332** of the deflectable element **330** is a concave portion of the element **330**. In the embodiment depicted in FIG. **8B**, the deflectable elements **330** include a proximal portion **337** continuous with the tubular body **310** and a distal portion **339** extending inwardly from the tubular body **310**. In the embodiment depicted in FIG. **8B**, distal portion **339** includes the lead contacting portion **335** and forms the stop region **332**. In the embodiment depicted in FIG. **8B**, the stop region **332** includes a bulge of increased thickness relative to a region of the element **330** proximal to the stop region **332**.

The deflecting elements **330** shown in FIGS. **8A** and **8C-F** are arcuate or substantially arcuate. The deflected elements may be generally linear, e.g. as shown in FIG. **8B**. However, it will be understood that deflecting elements **330** may be of any suitable shape.

Referring now to FIG. **8E-F**, by way of example, the deflectable elements may have a tapered region **334** in proximity to, adjacent to, or leading to, lead contacting portion **335**. The tapered region **334** may serve as a ramp to facilitate insertion of the lead into the cavity of the connector ring. The tapered portion **334** preferably begins at a point on the elements proximal to where contact with the lead is expected. For example, the proximal beginning point of the tapered region **334** may begin on element **330** at a location along the circumference of an imaginary circle **410** coaxial with the tubular body portion **310** of the ring **300**. The imaginary circle **410** has a diameter that is greater than the diameter of the portion of the lead that contacts the elements **330** as the lead is inserted into the contact ring **300**. In the depicted embodiment, the distal ending point of the taper **334** is at the lead contact region **335** of the deflectable element **330**, which lead contacting region **334** is disposed in the interior on the contact ring **300**.

As the lead is inserted into the cavity in a direction from the proximal face **350** to the distal face of the connector, the lead can contact the tapered portion **334** causing the element **330** to deflect outwardly. Element **334** is torsionally biased towards a state where lead contacting portion **335** is located along a circumference of an imaginary circle **400** concentric with the tubular body **310**. As described above with regard to FIG. **8F**, the imaginary circle **400** has a diameter that is smaller than the outer diameter of the portion of the lead that the lead contact portions **335** are configured to contact.

The contact rings described herein may be formed from any suitable conductive material or materials. For example, the contact rings may be formed from platinum, platinum iridium, titanium, tantalum, palladium or alloys thereof; nickel-cobalt-molybdenum alloys (such as MP35N); or the like; or combinations thereof. It will be understood that the material selected may vary on the ultimate design configuration. Generally, the elastic modulus or modulus of resiliency will be taken into account along with the design configuration, such as position and shape of stops and stop regions of the deflectable elements and the shape of the deflectable element, to minimize the stress and potential

failure of the proximal portion of the deflectable element associated with insertion of a lead at an unintended angle.

In various embodiments, the contact rings are made of a core material having suitable modulus properties such as platinum, platinum iridium, titanium, tantalum, palladium or alloys thereof, or nickel-cobalt-molybdenum alloys. The core material may be plated, coated, clad, or the like with a softer material that is highly conductive, such as gold or the like. In some embodiments, a core of a less noble metal is plated, coated, clad, or the like with platinum, platinum iridium, titanium, tantalum, palladium or alloys thereof, or nickel-cobalt-molybdenum alloys.

In various embodiments, the contact rings are monolithic (formed from a single material without joints). Such monolithic contact rings (which can be of any suitable size, e.g. as described above) may improve the electrical properties of the contact ring relative to other contact rings, which employ a variety of materials or which require welding or other coupling between parts. By employing the same seamless material throughout, electrical resistance due to flow of electrons between the junctions of differing materials can be reduced, which can advantageously reduce the power requirement of devices employing the contact rings.

Contact rings **300** as described herein may be of any suitable size for use in implantable medical devices. For example, the contact rings **300** may have a thickness (axial length) between about 0.10 inches (2.5 millimeters) and about 0.01 inches (0.25 millimeters). In some embodiments, the contact rings **300** have a thickness of between about 0.75 inches (2 millimeters) and about 0.025 inches (0.6 millimeters); e.g., about 0.05 inches (1.2 millimeters). In numerous embodiments, contact rings **300** have a thickness that is approximately the same as the thickness of a ring contact of a lead to which the contact ring **300** is to be electrically coupled. The contact rings **300** may be of any suitable inner and outer diameter. For example, the contact rings **300** may have an outer diameter of between about 0.200 inches (5 millimeters) and 0.05 inches (1.2 millimeters). In some embodiments, the contact rings **300** have an outer diameter of about 0.1 inches (2.5 millimeters) or about 0.11 inches (2.8 millimeters). Generally, the inner diameter of the contact rings **300** (or the diameter formed by lead contacting portions **335** of the deflectable elements **330**) is suitable for insertion of a lead. The deflectable elements **330** of the contact rings **300** may have any suitable length and thickness, which may vary depending on the material from which they are formed. The length will vary depending on the outer diameter of the ring and desired inner diameter formed from lead contacting portions **335** of the deflectable elements **330**. In various embodiments, the deflectable elements **330** may have a thickness of between about 0.01 inches (0.25 millimeters) and about 0.001 inches (0.025 millimeters). In some embodiments, the deflectable elements **330** may have a thickness of between about 0.006 inches (0.15 millimeters) and about 0.002 inches (0.05 millimeters). The thickness of the deflectable elements **330** may be substantially the same along the length of the element or may vary along the length of the element. In some embodiments, the element **330** is thicker at the base and thinner at the lead contacting portion **335**.

It will be understood that a contact ring **300** may include any suitable number of deflectable elements **330**. For example, a contact ring may have between 1 and 100 or more deflectable elements. In some embodiments, the contact ring has between 3 and 6 or between 4 and 5 deflectable elements. All other thing being equal, the smaller the number of deflectable elements, the less force required to insert

a lead through the cavity of the contact ring. However, if the insertion force is too low, the quality of electrical contact between the lead and the contacting portions of the deflectable elements may be poor. That is, greater resilient force pressing against the lead may lead to better quality and more reliable electrical contact, but may also result in greater insertion force. The number of deflectable elements included in a ring contact may be varied to achieve a desirable balance between quality and reliability of electrical contact and insertion force.

In addition, it may be desirable to decrease the number of contact points between the lead and the contact ring, as each point of contact may incrementally increase electrical resistance. Thus, in some embodiments, the lowest number of deflectable element that can provide high quality and reliable electrical contact with the lead is employed.

In some embodiments (not shown), at least a portion of the region between tubular body **310** and the lead contacting portions **335** of the deflectable elements **330** is backfilled with an elastomeric material, such as silicone. Such backfilling may increase the structural integrity and resilience of the elements **330**, serving to reduce breakage.

Referring now to FIGS. **9-10** in which schematic perspective views of sections of contact rings **300** are shown (shown without deflectable elements for purposes of convenience), the tubular body **310** of the contact ring **300** may form a flange **390** or rim configured to cooperate with an insulating seal when the contacts are used to form a lead receptacle (see e.g., FIGS. **5D-E**). The contact ring **300** may have one flange region **390** (FIG. **9**) or two flange regions **390** (FIG. **10**) on opposing sides of the tubular body, allowing for sealing engagement with an insulating element on opposing sides of contact ring **300**.

Contact rings **300** as described herein may be formed by any suitable process. For example, various components may be molded (e.g., microinjection molding), machined, or otherwise formed. In various embodiments, contact rings are formed by removing a solid portion of a cylinder to form the ring contact.

Referring now to FIGS. **11A-D**, perspective views of representative cylinders **500** (FIG. **7A-C**) that may serve as starting material for a contact ring **300** (FIG. **7D**) by removal of a portion of the cylinder **500** (dashed lines in FIGS. **11B-C** represent material to be removed). Any suitable method may be used to remove appropriate portion(s) of the cylinder **500**. For example, electrical discharge machining, laser cutting, water jet cutting, photo-etching, or the like may be used to remove appropriate portion(s) of the cylinder **500**. One example of electrical discharge machining that may be employed is wire electrical discharge machining; e.g., with a 0.004 inch wire. As shown in FIGS. **11A-B**, the cylinder starting material may include a central cavity **510**. It may be desirable for the diameter of the central cavity **510** to be the same as the diameter of the imaginary tube (see dashed line **400** in, e.g., FIG. **6F**) along whose circumference the lead contacting portions of the deflectable elements lie in a relaxed state. Alternatively, the starting cylinder **500** may be solid throughout as shown in FIG. **11C**.

Referring now to FIG. **12**, a plurality of thin subunits **700'**, **700"**, **700'''** may be axially aligned in a stacked manner and bonded to form a one-piece contact ring **300** (see, e.g., FIG. **11D**). In the depicted embodiment, each subunit **700** includes a thinner version of all of the components of the connector ring. For example, each subunit includes a tubular body defining a cavity extending through the subunit body, a plurality of non-radially, outwardly deflectable subunit elements extending inwardly from the subunit tubular body,

a plurality of subunit stops (see e.g., FIGS. **8A-F** and associated text for a detailed description of such parts). The subunits **700'**, **700"**, **700'''** may be axially aligned by placing the subunits **700'**, **700"**, **700'''** about a mandrel **800**. The subunits are brought into contact and the subunit tubular bodies, deflectable elements, and stops are aligned. Then adjacent stacked subunits are bonded to each other to form the one-piece electrical ring contact that may be used in an implantable medical device. Any suitable method for bonding, such as welding, may be employed.

The rings and cylinders depicted in FIGS. **11-12** are shown for the purposes of illustration only. It will be understood that rings having non-radially outwardly deflecting elements, such as those shown in FIGS. **8A-F** may be made in a manner as described with regard to FIGS. **11-12**.

The rings and cylinders depicted in the figures are shown for the purposes of illustration. It will be understood that the rings may take any suitable shape including cuboid or the like.

Thus, embodiments of the ELECTRICAL CONTACT FOR IMPLANTABLE MEDICAL DEVICE are disclosed. One skilled in the art will appreciate that the present invention can be practiced with embodiments other than those disclosed. The disclosed embodiments are presented for purposes of illustration and not limitation, and the present invention is limited only by the claims that follow.

What is claimed is:

1. An electrical contact ring for electrically coupling a medical lead with electronics of an implantable medical device, comprising:
 - a tubular body defining a cavity extending through the body, the cavity configured to receive the lead; and
 - a plurality of resiliently deflectable elements extending from the tubular body into the cavity, each of the plurality of deflectable elements having a lead contacting portion configured to contact the lead when the lead is received by the cavity,
 wherein each of the plurality of deflectable elements, along its entire length, in a relaxed state extends from the tubular body to the lead contacting portion along a plane that intersects the tubular body.
2. The electrical contact ring of claim **1**, wherein the lead contacting portions of the deflectable elements, in a relaxed state, are located along a circumference of an imaginary circle, the circumference of the imaginary circle having a diameter smaller than an outer diameter of a portion of the lead that the lead contacting portions are configured to contact.
3. The electrical contact ring of claim **1**, wherein the lead contacting portion is formed from a material comprising a metal selected from the group consisting of platinum, platinum iridium, titanium, tantalum, palladium, or alloys thereof, and a nickel-cobalt-molybdenum alloy.
4. The electrical contact ring of claim **1**, wherein the deflectable elements are arcuate.
5. The electrical contact ring of claim **1**, wherein the deflectable elements comprise a tapered region in proximity to the lead contacting portion to facilitate insertion of the lead into the cavity.
6. The electrical contact ring of claim **1**, wherein the plurality of deflectable elements consists of between 3 and 6 deflectable elements.
7. The electrical contact ring of claim **1**, wherein the plurality of deflectable elements consists of 4 or 5 deflectable elements.
8. The electrical contact ring of claim **1**, wherein the tubular body comprises a flange for interacting with a seal.

9. A lead receptacle comprising:

a first electrical contact ring according to claim **1**; and
an insulating ring axially aligned with the first contact
ring.

10. The lead receptacle of claim **9**, further comprising: 5

a second electrical contact ring,
wherein the first and second contact rings and the insu-
lating ring are axially aligned and wherein the insulat-
ing ring is disposed between the first and second
contact rings. 10

11. An implantable medical device comprising:

a lead receptacle according to claim **10**;
a hermetically sealed housing; and
electronics disposed in the housing,
wherein the first electrical contact ring is electrically 15
coupled to the electronics.

12. A header for an implantable medical device, compris-
ing a lead receptacle according to claim **10**.

13. The header of claim **12**, further comprising:

a set screw block defining a lead receiving bore and a 20
second bore extending generally perpendicular to and
intersecting with the lead receiving bore,
wherein the lead receiving bore is axially aligned with the
first contact ring, and wherein the second bore is
configured to receive a set screw. 25

14. An implantable medical device, comprising:

a header according to claim **12**;
a hermetically sealed housing;
electronics disposed in the housing;
a hermetic feedthrough extending through the housing 30
and electrically coupling the first contact ring of the
header to the electronics.

* * * * *