

**(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. AU 2017314341 B2

(54) Title
User identity verification method, apparatus and system

(51) International Patent Classification(s)
H04L 29/06 (2006.01)

(21) Application No: **2017314341** (22) Date of Filing: **2017.08.11**

(87) WIPO No: **WO18/036389**

(30) Priority Data

(31) Number **201610717080.1** (32) Date **2016.08.24** (33) Country **CN**

(43) Publication Date: **2018.03.01**
(44) Accepted Journal Date: **2020.05.07**

(71) Applicant(s)
Alibaba Group Holding Limited

(72) Inventor(s)
He, Le;Tuo, Yukun;Li, Liang;Huang, Mian;Chen, Jidong;Yang, Wenbo

(74) Agent / Attorney
Cotters Patent & Trade Mark Attorneys, GPO Box 469, Sydney, NSW, 2001, AU

(56) Related Art
CN 105825102 A
US 20140358954 A1

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织

国际局

(43) 国际公布日

2018年3月1日 (01.03.2018)



WIPO | PCT



(10) 国际公布号

WO 2018/036389 A1

(51) 国际专利分类号:

H04L 29/06 (2006.01)

(21) 国际申请号:

PCT/CN2017/096987

(22) 国际申请日: 2017年8月11日 (11.08.2017)

(25) 申请语言:

中文

(26) 公布语言:

中文

(30) 优先权:

201610717080.1 2016年8月24日 (24.08.2016) CN

(71) 申请人: 阿里巴巴集团控股有限公司(ALIBABA GROUP HOLDING LIMITED) [—/CN]; 开曼群岛

大开曼资本大厦一座四层 847号邮箱,
Grand Cayman (KY)。

(72) 发明人: 何乐(HE, Le); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集

团法务部, Zhejiang 311121 (CN)。 度宇鲲(TUO, Yukun); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集团法务部, Zhejiang 311121 (CN)。 李亮(LI, Liang); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集团法务部, Zhejiang 311121 (CN)。 黄冕(HUANG, Mian); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集团法务部, Zhejiang 311121 (CN)。 陈继东(CHEN, Jidong); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集团法务部, Zhejiang 311121 (CN)。 杨文波(YANG, Wenbo); 中国浙江省杭州市余杭区文一西路969号3号楼5楼阿里巴巴集团法务部, Zhejiang 311121 (CN)。

(74) 代理人: 北京三友知识产权代理有限公司(BEIJING SANYOU INTELLECTUAL PROPERTY AGENCY LTD.); 中国北京市金

(54) Title: USER IDENTITY VERIFICATION METHOD, APPARATUS AND SYSTEM

(54) 发明名称: 用户核身方法、装置及系统




图 1

101 RECEIVING A HUMAN FACE IMAGE CORRESPONDING TO AN IDENTITY VERIFICATION OBJECT AND AN EYEPRINT PAIR IMAGE CORRESPONDING TO THE NUMBER OF EYEPRINT ACQUISITION STEPS, WHICH ARE SENT BY A CLIENT

102 COMPARING THE HUMAN FACE IMAGE WITH A PRE-SET HUMAN FACE IMAGE, AND COMPARING THE EYEPRINT PAIR IMAGE WITH A PRE-SET EYEPRINT TEMPLATE

103 IF COMPARISON RESULTS OF THE HUMAN FACE IMAGE AND THE EYEPRINT PAIR IMAGE BOTH SATISFY A PRE-SET CONDITION, SENDING IDENTITY VERIFICATION SUCCESS INFORMATION TO THE CLIENT

WO 2018/036389 A1

(57) Abstract: Disclosed are a user identity verification method, apparatus and system, relating to the technical field of information. The present invention is primarily used for solving the problems of relatively low accuracy and reliability in an existing user identity verification method. The method comprises: firstly receiving a human face image corresponding to an identity verification object and an eyeprint pair image corresponding to the number of eyeprint acquisition steps, which are sent by a client; then comparing the human face image with a pre-set human face image, and comparing the eyeprint pair image with a pre-set eyeprint template; and if comparison results of the human face image and the eyeprint pair image both satisfy a pre-set condition, sending identity verification success information to the client.

[见续页]



融街 35 号 国 际 企 业 大 厦 A 座 16 层,
Beijing 100033 (CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW。

(84) 指定国(除另有指明, 要求每一种可提供的地区保护): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚 (AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG)。

本国际公布:

- 包括国际检索报告(条约第21条(3))。

(57) 摘要: 本发明公开了一种用户核身方法、装置及系统, 涉及信息技术领域。本发明主要用于解决现有用户核身方法的精确度和可靠性较低的问题。所述方法包括: 首先接收客户端发送的核身对象对应的人脸图像和与眼纹采集步数对应的眼纹对图像, 然后将所述人脸图像与预置人脸图像进行比对, 并且将所述眼纹对图像与预置眼纹模板进行比对, 若所述人脸图像和所述眼纹对图像的比对结果均符合预设条件, 则向所述客户端发送核身成功信息。

User Identity Verification Method, Apparatus and System

This application claims priority to the Chinese patent application No. 201610717080.1 filed on August 24, 2016, and entitled "User Identity Verification Method, Apparatus and System", which is incorporated herein by reference in its entirety.

Technical field

This invention relates to the field of information technology, particularly to a user identity verification method, apparatus, and system.

Background

With the continuous development of information technologies and the Internet, a variety of applications have emerged. Of these, more and more financial institutions are providing users with apps to manage associated financial transactions. To ensure the security of user information, it is necessary to perform identity verification of the users managing financial transactions through apps, that is, performing user security verification operations such as identity authentication and name authentication.

Today, user identity verification is normally performed by employing a method of combining facial image recognition with live facial image verification, i.e.: issuing facial movement parameters to the user when verifying a collected facial image, requiring the user to complete live movement verification according to these movement parameters. However, now it is possible to synthesize rather lifelike 3D facial images and simulate user movements and expressions, resulting in low precision and reliability for existing user identity verification methods, and making it unlikely to ensure the security of the apps used by users.

Summary

In view of this, the embodiments of this invention provide a user identity verification method, apparatus, and system, with the main objective being to solve the problems of low precision and reliability in the user identity verification methods of current technologies.

To achieve this objective, this invention provides the following technical solutions:

In a first aspect, the present disclosure provides a user identity verification method, comprising:

sending a facial quality score threshold and a number of eye-print collection steps corresponding to an identity verification mode to a client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of

eye-print collection steps;

receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from the client, wherein the facial image meets the facial quality score threshold and a number of the one or more eye-print pair images corresponds to the number of eye-print collection steps;

comparing the facial image to a preset facial image, and comparing the one or more eye-print pair images to preset eye-print templates corresponding to the identity verification object; and

when comparison results for the facial image and the one or more eye-print pair images meet preset conditions, sending successful identity verification information to the client.

In a second aspect, the present disclosure provides a user identity verification method, comprising:

receiving a facial quality score threshold and a number of eye-print collection steps corresponding to a current mode;

obtaining a facial image and one or more eye-print pair images corresponding to an identity verification object, the facial image being obtained based on the facial quality score threshold and a number of the one or more eye-print pair images corresponding to the number of eye-print collection steps; and

sending the obtained facial image and the one or more eye-print pair images to a server to perform identity verification of the identity verification object.

In a third aspect, the present disclosure provides a non-transitory computer-readable storage medium for user identity verification, storing instructions executable by one or more processors causing the one or more processors to perform operations comprising:

sending a facial quality score threshold and a number of eye-print collection steps corresponding to an identity verification mode to a client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps;

receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from the client, wherein the facial image meets the facial quality score threshold and a number of the one or more eye-print pair images corresponds to the number of eye-print collection steps;

comparing the facial image to a preset facial image, and comparing the one or more eye-print pair images to preset eye-print templates; and

when comparison results for the facial image and the one or more eye-print pair images meet preset conditions, sending successful identity verification information to the client.

In a further aspect, an embodiment of this invention provides a user identity verification method, comprising:

receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to a number of eye-print collection steps;

comparing the facial image to a preset facial image, and comparing the eye-print pair images to preset eye-print templates;

sending successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

In a further aspect, an embodiment of this invention provides another user identity verification method, comprising:

collecting a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps;

sending the facial image and eye-print pair images to the server, causing the server to perform identity verification of the identity verification object.

In a further aspect, an embodiment of this invention provides a server, comprising:

a receiving unit, configured to receive a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to the number of eye-print collection steps;

a comparison unit, configured to compare the facial image to a preset facial image, and compare the eye-print pair images to preset eye-print templates;

a sending unit, configured to send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

In a further aspect, an embodiment of this invention provides a client, comprising: a collection unit, configured to collect a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps; a sending unit, configured to send the facial image and eye-print pair images to the server, causing the server to perform identity verification of the identity verification object.

In a further aspect, an embodiment of this invention provides a user identity verification system, comprising:

a server, when receiving a user identity verification request, configured to send, to a client, a facial quality score threshold and a number of eye-print collection steps corresponding to the current mode;

a client, configured to obtain a facial image based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collections steps;

the server is also configured to receive a facial image sent by a client and eye-print pair images corresponding to a number of eye-print collection steps; compare the facial image to a preset facial image, and compare the eye-print pair images to preset eye-print templates; and send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

The technical solutions provided by the embodiments of this invention possess at least the following advantages:

The user identity verification method, apparatus, and system provided by the embodiments of this invention comprise first receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to a number of eye-print collection steps, when a user identity verification request is received; then comparing the facial image to a preset facial image, comparing the eye-print pair images to preset eye-print templates; and sending successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, the embodiments of this invention use multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and ensuring the security of apps used by the user.

The preceding explanation is merely a summary of the technical solutions of this invention. To enable a clearer understanding of the technical measures of this invention, to enable implementation in accordance with the content of this description, and to make the preceding and other objectives, features, and advantages of this invention clearer and more easily understood, specific implementation manners of this invention are presented below.

Brief Description of the Drawings

By reading the following detailed description of preferred implementation manners, a variety of other advantages and benefits will become clear to persons having ordinary skill in the art. The drawings are merely used to illustrate the objectives of preferred implementation manners and are not to be taken as limitations of this invention. The same reference symbols used in all drawings represent the same components. In the drawings:

FIG. 1 presents a flow diagram of a user identity verification method provided by an embodiment of this invention;

FIG. 2 presents a flow diagram of another user identity verification method provided by an embodiment of this invention;

FIG. 3 presents a flow diagram of another user identity verification method provided by an embodiment of this invention;

FIG. 4 presents a flow diagram of another user identity verification method provided by an embodiment of this invention;

FIG. 5 presents a schematic diagram of a server provided by an embodiment of this invention;

FIG. 6 presents a schematic diagram of another server provided by an embodiment of this invention;

FIG. 7 presents a schematic diagram of a client provided by an embodiment of this invention;

FIG. 8 presents a schematic diagram of another client provided by an embodiment of this invention;

FIG. 9 presents a diagram of a user identity verification system provided by an embodiment of this invention;

FIG. 10 presents a flow diagram of a user identity verification scenario presented by an embodiment of this invention.

Detailed Description

Referencing the drawings, a more detailed description of the exemplary embodiments of this disclosure is given below. Even though the drawings present exemplary embodiments of this disclosure, it should be understood that this disclosure may be achieved in other forms and should not be limited by the embodiments described here. Rather, these embodiments are provided to enable a more thorough understanding of this disclosure and to transmit the scope of this disclosure in its entirety to persons skilled in the art.

An embodiment of this invention provides a user identity verification method, as shown in FIG. 1, the method comprising:

101. Receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to a number of eye-print collection steps.

Here, because a larger number of eye-print collection steps results in a longer period of time in eye-print collection, when a number of the eye-print templates of the identity verification object is ample, a smaller number of eye-print collection steps may be used; when the number of the eye-print templates of the identity verification object is smaller, to collect eye-print pair images for the accumulation of eye-print templates for the identity verification object, a larger number of eye-print collection steps may be used. For this embodiment, it is possible to further boost the precision of user identity verification by configuring different numbers of eye-print collection steps based on different circumstances. The server can use communication means such as mobile cellular networks and WIFI networks to perform data transmission with the client. No limitations are placed on this by the embodiments of this invention.

102. Comparing the facial image to a preset facial image, and comparing the eye-print pair images to preset eye-print templates.

Here, the preset facial image may be a photograph of the user that has been registered with a public security network or a facial photograph that has been verified by a user identity verification. No limitations are placed on this by the embodiments of this invention. The preset eye-print templates may be multiple sets of eye-print pair images that have been verified by a security verification. The comparison operation may be determining whether the degree of matching between images meets preset requirements. No limitations are placed on this by the embodiments of this invention.

103. Sending successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

Here, the preset conditions may be facial comparison score thresholds and eye-print match score thresholds. No limitations are placed on this by the embodiments of this invention. For this embodiment, when both the facial image and eye-print pair images comparison results meet preset conditions, a successful identity verification is determined, thus performing the user identity verification through multiple dimensions such as facial images and eye-print pair images, and thereby making it possible to boost the precision of the user identity verification method.

An embodiment of this invention provides a user identity verification method. When a user identity verification request is received, first a facial image and one or more eye-print pair images corresponding to an identity verification object are received, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then the facial image is compared to a preset facial image, and the eye-print pair images are compared to preset eye-print templates. Successful identity verification information is sent to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions. Compared to the method of combining facial image recognition with live facial image verification commonly used today when performing user identity verification, the embodiments of this invention use multidimensional verification modes such as facial image verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and ensuring the security of apps when used by the user.

Furthermore, an embodiment of this invention provides another user identity verification method, as shown in FIG. 2. The method comprises:

201. Obtaining a number of eye-print templates corresponding to the identity verification object from a preset storage location, when a user identity verification request is received.

Here, eye-print templates corresponding to different identity verification objects are stored in the preset storage location. When a user needs to perform security verification such as login identity validation or payment identity validation, a user identity verification request is sent to a client.

Following step 201, the embodiments of this invention may also comprise: if the number of eye-print templates is less than a preset threshold, determining the current mode as an eye-print enrollment mode; sending a facial quality score threshold and the number of eye-print collection steps corresponding to the eye-print enrollment mode to the client, to make the client obtain a facial image based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps; and storing the eye-print pair images in the preset storage location as the eye-print templates corresponding to the preset identity verification object.

It should be noted that when the number of eye-print templates is less than the preset threshold, it means that the number of eye-print templates at that time is rather low, and it is not possible to ensure the precision of an eye-print verification. At that time, the current mode is determined as eye-print enrollment mode. This can enable the client to input in real time an eligible eye-print as the eye-print templates of the identity verification object, thus achieving the accumulation of eye-print templates. When the number of eye-print templates reaches the preset threshold, the identity verification mode is switched on, thus making it possible to further boost the precision and reliability of the user identity verification.

202. Determining that the current mode as identity verification mode if the number of eye-print templates is greater than or equal to a preset threshold.

Here, the current mode may comprise eye-print collection mode, identity verification mode, etc. The current mode is associated with the number of eye-print templates corresponding to the user that are stored in the preset storage location. No limitations are placed on this by the embodiments of this invention. It should be noted that for eye-print collection mode, the collected eye-print image quality requirements are quite high, to facilitate the server's accumulation of eye-print templates; for identity verification modes, average eye-print image quality is sufficient, because the server can perform eye-print comparisons using previously accumulated eye-print templates. For the facial quality score threshold used to indicate the quality of the facial image collected by the client, a higher facial quality score threshold requires a higher quality in the facial image collected by the client. The number of eye-print collection steps is used to indicate the number of eye-print pairs collected at one time by the client. For example, when the number of eye-print collection steps is 5, the client needs to collect 5 pairs of eye-prints.

It should be noted that, because a larger number of eye-print collection steps results in a

longer period of time in eye-print collection, there will be different numbers of eye-print collection steps configured for different modes. For example, for identity verification mode, because there are an ample number of eye-print templates under this mode, a smaller number of eye-print collection steps may be configured; for eye-print collection mode, because the main objective of this mode is to collect eye-print pair images for the accumulation of eye-print templates, a larger number of eye-print collection steps may be configured. For this embodiment, it is possible to further boost the precision of user identity verification by configuring different numbers of eye-print collection steps based on different modes.

203. Sending a facial quality score threshold and the number of eye-print collection steps corresponding to identity validation mode to a client.

Furthermore, the client is caused to obtain a facial image based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps. Here, the client may be configured on a mobile device with a webcam and microphone. These mobile devices include but are not limited to smartphones and tablet PCs. The client can use the webcam to collect relevant images.

204. Receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to the number of eye-print collection steps.

Here, the server can use communication means such as mobile cellular networks and WIFI networks to perform data transmission. No limitations are placed on this by the embodiments of this invention.

205. Comparing the facial image to a preset facial image, and comparing the eye-print pair images to preset eye-print templates.

Here, the preset facial image may be a photograph of the user that has been registered with a public security network or a facial photograph that has been verified by a user identity verification. No limitations are placed on this by the embodiments of this invention. The preset eye-print templates may be multiple sets of eye-print pair images that have been verified by a security verification.

For this embodiment, if the current mode is determined as the identity verification mode, comparing the facial image to a preset facial image may comprise: using the facial image and the preset facial image as input to a preset facial algorithm, and obtaining a facial comparison score corresponding to the identity verification object. Comparing the eye-print pair images to preset eye-print templates comprises: using the eye-print pair images and the eye-print templates corresponding to the identity verification object as input to a preset eye-print algorithm, and

obtaining multiple eye-print liveness scores corresponding to the number of eye-print collection steps and an eye-print match score.

Here, the preset facial algorithm and the preset eye-print algorithm may be convolutional neural network algorithms, multi-layer neural network algorithms, etc. No limitations are placed on this by the embodiments of this invention. The facial comparison score is used to reflect the degree to which the facial image of the identity verification object matches the preset facial image. A higher facial comparison score means a higher match between the facial image of the identity verification object and the preset facial image. The eye-print liveness score is used to reflect the fidelity of the currently collected eye-print pair images of the identity verification object. A higher eye-print liveness score means higher fidelity of the eye-print pair image. The eye-print match score is used to reflect the degree to which the eye-print pair images of the identity verification object match the preset eye-print templates. A higher eye-print match score means a higher match between the eye-print pair images of the identity verification object and the preset eye-print templates.

206. Sending successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

For this embodiment, step 206 may comprise: sending successful identity verification information to the client if the facial comparison score, multiple eye-print liveness scores, and the eye-print match score are greater than respective preset thresholds. In this embodiment, when the facial comparison score, multiple eye-print liveness scores, and eye-print match score all are greater than the preset thresholds, identity verification is determined as successful, thus making it possible to boost the precision and reliability of the user identity verification method.

207. When user identity verification is determined as successful, updating the eye-print templates corresponding to the identity verification object that are stored in the preset storage location based on the eye-print pair images collected by the client.

For this embodiment, when user identity verification is determined as successful, it indicates that the eye-print pair images collected by the client at this time are true and reliable, and the eye-print templates corresponding to the identity verification object stored in the preset storage location are updated based on the eye-print pair images collected by the client. This can further ensure the accuracy of the eye-print templates corresponding to the identity verification object that are stored in the preset storage location, thereby further boosting the precision of the user identity verification method.

For this embodiment, a specific application scenario flow may be, but is not limited to that, as shown in FIG. 10, first, the server may use a configured decision module, FEARbitrator, to obtain

an eye-print template number of 10, corresponding to the identity verification object. This is greater than the preset template number threshold of 9, so the current mode is determined as identity verification mode: Verify. Next, a facial quality score threshold QT and the number of eye-print collection steps 1 corresponding to the identity verification mode Verify is sent to the client. At this time, the client collects a facial image and one eye-print pair. Then, after determining that the quality of the collected facial image is greater than or equal to QT, preprocessing such as optimization and compression is performed on the collected facial image and eye-print pair image, then the preprocessed facial image and eye-print pair image are sent to the server. At this time, the server uses a preset facial algorithm to compare the facial image to a verified preset facial image and obtains a facial image comparison score FX; and uses a preset eye-print algorithm to compare the collected eye-print pair to preset eye-print templates and obtains an eye-print liveness score LK and eye-print match score MX. If FX is greater than or equal to the preset facial comparison score threshold FT, LK is greater than or equal to the preset eye-print liveness score threshold LT, and MX is greater than or equal to the preset eye-print match score threshold, at this point, successful identity verification information is sent to the client, and the preset eye-print templates are updated based on the collected eye-print pair image. If the number of eye-print templates corresponding to the identity verification object is less than 9, the client is instructed to conduct eye-print pair images collection until the number of eye-print templates corresponding to the identity verification object is greater than or equal to 9, and the mode is switched to identity verification mode.

In another user identity verification method provided by an embodiment of this invention, when a user identity verification request is received, first a facial image and one or more eye-print pair images corresponding to an identity verification object are received, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then the facial image is compared to a preset facial image, and the eye-print pair images are compared to preset eye-print templates. If the comparison results for the facial image and the eye-print pair images meet preset conditions, successful identity verification information will be sent to the client. Compared to the method of combining facial image recognition with live facial image verification commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, an embodiment of this invention provides a user identity verification method, as shown in FIG. 3. The method comprises:

301. Collecting a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps.

Here, the executing entity of this embodiment may be a client. The client may be configured on a mobile device with a webcam and microphone. These mobile devices include but are not limited to smartphones and tablet PCs. When the client receives a user request such as account login or payment, a facial image and one or more eye-print pair images corresponding to an identity verification object are collected, for a server to perform security verification such as identity validation or payment identity validation for the user. The one or more eye-print pair images corresponding to the number of eye-print collection steps.

302. Sending the facial image and the number of eye-print pair images to the server.

Furthermore, it causes the server to perform identity verification of the identity verification object.

For this embodiment, before step 302, the method may also comprise: the client performing preprocessing of the collected facial image and eye-print pair images, wherein the preprocessing may comprise: image optimization, image segmentation, image compression, facial image quality calculation, and eye-print liveness calculation. No limitations are placed on this by the embodiments of this invention. By performing preprocessing of the collected facial image and eye-print pair images, it is possible to ensure the true accuracy of the image used by the server for identity verification, thereby ensuring the precision of user identity verification.

An embodiment of this invention provides another user identity verification method. First, a facial image corresponding to the identity verification object and a number of eye-print pair images corresponding to a number of eye-print collection steps are collected, then the facial image and the eye-print pair images are sent to the server, causing the server to perform identity verification of the identity verification object. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, an embodiment of this invention provides another user identity verification method, as shown in FIG. 4. The method comprises:

401. Sending a user identity verification request to a server.

Here, the executing entity of this embodiment may be a client. The client may be configured

on a mobile device with a webcam and microphone. These mobile devices include but are not limited to smartphones and tablet PCs. When the user requests the performance of an operation such as account login or payment, a user identity verification request is sent to a server, causing the server to perform security verification of the user, such as identity validation and payment identity validation. The user identity verification request may include identification information of the user, to enable the server to extract information such as the user's preset facial image or preset eye-print templates, etc. from a database to perform subsequent user identity verification.

402. Receiving a facial quality score threshold and the number of eye-print collection steps corresponding to the current mode and sent by the server.

Here, the client can use communication means such as mobile cellular networks and WIFI networks to perform data transmission with the server. No limitations are placed on this by the embodiments of this invention. The relevant portions of step 101 may be referenced for an explanation of the identity verification mode, facial quality score threshold, and the number of eye-print collection steps. Further details will not be given here.

403. Obtaining a facial image based on the facial quality score threshold and obtaining a number of eye-print pair images corresponding to the number of eye-print collections steps.

For example, a client may use a preset webcam to obtain a facial image and eye-print pair images of the current identity verification object. No limitations are placed on this by the embodiments of this invention.

404. Determining whether the image quality of the currently obtained facial image is greater than or equal to the facial quality score threshold, and determining whether the eye-print pair images meet preset eye-print liveness conditions.

Here, the preset eye-print liveness conditions are used to reflect the authenticity of the eye-print pair image. For this embodiment, before sending the facial image and the eye-print pair images to the server, by determining whether the image quality of the currently obtained facial image is greater than or equal to the facial quality score threshold, and by determining whether the eye-print pair images meet preset eye-print liveness conditions, it is possible to ensure the true accuracy of the image sent to the server for identity verification, thereby ensuring the precision of user identity verification.

405. Sending the facial image and the eye-print pair images to the server if the image quality of the currently obtained facial image is greater than or equal to the facial quality score threshold and the eye-print pair images meet preset eye-print liveness conditions.

Furthermore, it causes the server to perform identity verification of the user. For this embodiment, after determining that the quality of the collected facial image and eye-print pair

images meets requirements, these images are sent to the server. Thus it is possible to ensure the true accuracy of the images sent to the server for identity verification, thereby ensuring the precision of user identity verification.

An embodiment of this invention provides another user identity verification method. First, a facial image and one or more eye-print pair images corresponding to an identity verification object from are collected, the one or more eye-print pair images corresponding to a number of eye-print collection steps are collected, then the facial image and the eye-print pair images are sent to the server, causing the server to perform identity verification of the identity verification object. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, as an implementation of the method shown in FIG. 1, an embodiment of this invention provides a server, as shown in FIG. 5. The server may comprise: a receiving unit 51, comparison unit 52, and sending unit 53.

The receiving unit 51 is configured to receive a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print pair images corresponding to a number of eye-print collection steps;

the comparison unit 52 is configured to compare the facial image to a preset facial image, and compare the eye-print pair images to a preset eye-print template;

the sending unit 53 is configured to send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

It should be noted that this apparatus embodiment corresponds to the aforementioned method embodiment. For ease of reading, this apparatus embodiment will not go over each detail given in the aforementioned method embodiment, but it should be clear that the apparatus of this embodiment is capable of correspondingly achieving everything in the aforementioned method embodiment.

An embodiment of this invention provides a server. When a user identity verification request is received, first, a facial image and one or more eye-print pair images corresponding to an identity verification object from a client are received, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then the facial image is compared to a

preset facial image, and the eye-print pair images are compared to preset eye-print templates. Successful identity verification information is sent to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method and making it possible to ensure security when a user uses an application.

Furthermore, as an implementation of the method shown in FIG. 2, an embodiment of this invention provides another server, as shown in FIG. 6. The server may comprise: a receiving unit 61, comparison unit 62, sending unit 63, acquisition unit 64, determination unit 65, storing unit 66, and update unit 67.

The receiving unit 61 is configured to receive a facial image and one or more eye-print pair images corresponding to an identity verification object from a client, the one or more eye-print images corresponding to a number of eye-print collection steps;

the comparison unit 62 is configured to compare the facial image to a preset facial image, and compare the eye-print pair images to preset eye-print templates;

the sending unit 63 is configured to send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

Furthermore, the server also comprises:

the acquisition unit 64, when receiving a user identity verification request, configured to obtain a number of eye-print templates corresponding to the identity verification object from a preset storage location, where the eye-print templates corresponding to different identity verification objects are stored;

the determination unit 65, configured to determine that the current mode is identity verification mode if the number of eye-print templates is greater than or equal to a preset threshold.

The sending unit 63 is also configured to send a facial quality score threshold and the number of eye-print collection steps corresponding to identity verification mode to a client, causing the client to obtain a facial image based on the facial quality score threshold and obtain one or more eye-print pair images corresponding to the number of eye-print collection steps.

Furthermore, the server also comprises: the storing unit 66.

The determination unit 65 is also configured to determine that the current mode is an eye-

print enrollment mode if the number of eye-print templates is less than the preset threshold;

the sending unit 63 is also configured to send a facial quality score and the number of eye-print collection steps corresponding to the eye-print enrollment mode to the client, causing the client to obtain a facial image based on the facial quality score threshold and obtain one or more eye-print pair images corresponding to the number of eye-print collection steps;

the storing unit 66 is configured to store the eye-print pair images in the preset storage location as the eye-print template corresponding to the preset identity verification object.

Furthermore, the comparison unit 62 is configured to use the facial image and the preset facial image as input to a preset facial algorithm, and obtain a facial comparison score corresponding to the identity verification object;

the eye-print pair images and the eye-print template corresponding to the identity verification object are used as input to an eye-print algorithm to obtain multiple eye-print liveness scores corresponding to the number of eye-print collection steps and an eye-print match score.

Furthermore, the sending unit 63 is configured to send successful identity verification information to the client if the facial comparison score, multiple eye-print liveness scores, and the eye-print match score are greater than respective preset thresholds.

Furthermore, the server also comprises:

the updating unit 67, when user identity verification is determined as successful, based on the eye-print pair images collected by the client, configured to update the eye-print templates corresponding to the identity verification object that is stored in the preset storage location.

It should be noted that this apparatus embodiment corresponds to the aforementioned method embodiment. For ease of reading, this apparatus embodiment will not go over each detail given in the aforementioned method embodiment, but it should be clear that the apparatus of this embodiment is capable of correspondingly achieving everything in the aforementioned method embodiment.

An embodiment of this invention provides another server. When a user identity verification request is received, first a facial image and one or more eye-print pair images corresponding to an identity verification object from a client are received, the one or more eye-print pair images corresponding to the number of eye-print collections steps, the facial image is compared to a preset facial image, and the eye-print pair images are compared to preset eye-print templates. Successful identity verification information is sent to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions. Compared to the method of combining facial image recognition with live facial image verification commonly used today when performing user identity verification, the embodiments of this invention use multidimensional verification modes

such as facial image verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, as an implementation of the method shown in FIG. 3, an embodiment of this invention provides a client, as shown in FIG. 7. The client may comprise: a collection unit 71 and sending unit 72.

The collection unit 71 is configured to collect a facial image corresponding to the identity verification object and one or more eye-print pair images corresponding to a number of eye-print collection steps;

the sending unit 72 is configured to send the facial image and the eye-print pair images to the server, causing the server to perform identity verification of the identity verification object.

It should be noted that this apparatus embodiment corresponds to the aforementioned method embodiment. For ease of reading, this apparatus embodiment will not go over each detail given in the aforementioned method embodiment, but it should be clear that the apparatus of this embodiment is capable of correspondingly achieving everything in the aforementioned method embodiment.

An embodiment of this invention provides a client which first collects a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then sends the facial image and the eye-print pair images to the server, causing the server to perform identity verification of the identity verification object. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, as an implementation of the method shown in FIG. 4, an embodiment of this invention provides another client, as shown in FIG. 8. The client may comprise: a collection unit 81, sending unit 82, receiving unit 83, and determination unit 84.

The collection unit 81 is configured to collect a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps;

the sending unit 82 is configured to send the facial image and the eye-print pair images to

the server, causing the server to perform identity verification of the identity verification object.

Furthermore, the client also comprises: the receiving unit 83;

the sending unit 82 is configured to send a user identity verification request to a server;

the receiving unit 83 is configured to receive a facial quality score threshold and the number of eye-print collection steps corresponding to the current mode and sent by the server;

the collection unit 81 is configured to obtain a facial image corresponding to the identity verification object based on the facial quality score threshold and to obtain one or more eye-print pair images corresponding to the number of eye-print collection steps.

Furthermore, the client also comprises: the determination unit 84;

the determination unit 84 is configured to determine whether the image quality of the currently obtained facial image is greater than or equal to the facial quality score threshold;

if so, the sending unit is configured to send the facial image to the server.

The determination unit 84 is also configured to determine whether the eye-print pair images meet preset eye-print liveness conditions;

the sending unit 81 is also configured to send the eye-print pair images to the server if conditions are met.

It should be noted that this apparatus embodiment corresponds to the aforementioned method embodiment. For ease of reading, this apparatus embodiment will not go over each detail given in the aforementioned method embodiment, but it should be clear that the apparatus of this embodiment is capable of correspondingly achieving everything in the aforementioned method embodiment.

Another client provided by an embodiment of this invention first collects a facial image and one or more eye-print pair images corresponding to an identity verification object, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then sends the facial image and the eye-print pair images to the server, causing the server to perform identity verification of the identity verification object. Compared to the method of combining facial image recognition with live facial image verification, commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

Furthermore, as an implementation of the methods shown in FIG. 1 and FIG. 3, an embodiment of this invention provides a user identity verification system, as shown in FIG. 9. The user identity verification system comprises: a server 91 and a client 92.

The server 91 is configured to send a facial quality score threshold and the number of eye-print collection steps corresponding to the current mode to a client when a user identity verification request is received;

The client 92 is configured to obtain a facial image based on the facial quality score threshold and obtain one or more eye-print pair images corresponding to the number of eye-print collections steps;

the server 91 is also configured to receive a facial image sent by a client and one or more eye-print pair images corresponding to a number of eye-print collection steps; compare the facial image to a preset facial image, and compare the eye-print pair images to preset eye-print templates; and send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

It should be noted that this apparatus embodiment corresponds to the aforementioned method embodiment. For ease of reading, this apparatus embodiment will not go over each detail given in the aforementioned method embodiment, but it should be clear that the apparatus of this embodiment is capable of correspondingly achieving everything in the aforementioned method embodiment.

In a user identity verification system provided by an embodiment of this invention, when a user identity verification request is received, first a facial image and one or more eye-print pair images corresponding to an identity verification object from a client are received, the one or more eye-print pair images corresponding to a number of eye-print collection steps, then the facial image is compared to a preset facial image, and the eye-print pair images are compared to preset eye-print templates, and successful identity verification information is sent to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions. Compared to the method of combining facial image recognition with live facial image verification commonly used today when performing user identity verification, this embodiment uses multidimensional verification modes such as facial verification combined with eye-print image verification and live eye-print image verification to perform user identity verification, thereby boosting the precision and reliability of the user identity verification method, and it can ensure the security of apps used by the user.

The user identity verification apparatus comprises a processor and a memory. The aforementioned virtual elements are all stored in the memory as program units, and the processor executes these program units that are stored in the memory to perform corresponding functions.

The processor contains a kernel. The kernel retrieves the corresponding program units from the memory. There may be one or more kernels. By adjusting kernel parameters, it is possible to

solve the existing problem of low precision in user identity verification methods.

The memory could comprise the forms of volatile memory on computer-readable media, random access memory (RAM), and/or non-volatile RAM, such as read-only memory (ROM) or flash RAM. The memory comprises at least one storage chip.

This application also provides a computer program product. When it is executed on a data processing device, it is suitable for executing and initializing program code with the following method steps. As an example:

a server is configured to send a facial quality score threshold and number of eye-print collection steps corresponding to the current mode to a client when a user identity verification request is received;

a client is configured to obtain a facial image based on the facial quality score threshold and obtain one or more eye-print pair images corresponding to the number of eye-print collections steps; and

the server is also configured to receive a facial image sent by a client and one or more eye-print pair images corresponding to the number of eye-print collection steps; compare the facial image to a preset facial image, and compare the eye-print pair images to preset eye-print templates; and send successful identity verification information to the client if the comparison results for the facial image and the eye-print pair images meet preset conditions.

A person skilled in the art should understand that the embodiments of this application can be provided as methods, systems, or computer program products. Therefore, this application may employ a purely hardware embodiment form, purely software embodiment form, or an embodiment form that combines software and hardware. Also, this application may employ the form of computer program products achieved through one or more computer storage media (including but not limited to magnetic disc memory, CD-ROM, and optical memory) comprising computer-executable program code.

This application is described by referencing flow diagrams and/or block diagrams based on the user identity verification method, apparatus, system, and computer program product of this embodiment. It should be understood that computer program instructions can be used to achieve every flow and/or block in the flow diagrams and/or block diagrams, as well as combinations of flows and/or blocks in the flow diagrams and/or block diagrams. These computer program instructions can be provided to the processor of a general-purpose computer, special-purpose computer, embedded processing machine, or other programmable data processing device to produce a machine, causing the instructions executed by the processor of a computer or other programmable data processing device to produce a device used to achieve the specified functions of

one or more flows in a flow diagram and/or one or more blocks in a block diagram.

These computer program instructions can also be stored in computer-readable memory that can cause a computer or other programmable data processing device to operate in a given mode, causing the instructions stored in this computer-readable memory to generate a product comprising an instruction apparatus. This instruction apparatus achieves the functions specified in one or more flows of a flow chart and/or one or more blocks of a block diagram.

These computer program instructions can also be loaded onto a computer or other programmable data processing device, enabling the execution of a series of operation steps on the computer or other programmable device to produce computer processing. Thus, the instructions executed on the computer or other programmable device provide steps for achieving the specified functions of one or more flows in a flow chart and/or one or more blocks in a block diagram.

In one typical configuration, the computation equipment comprises one or more processors (CPUs), input/output interfaces, network interfaces, and internal memory.

The memory could comprise the forms of volatile memory on computer-readable media, random access memory (RAM), and/or non-volatile RAM, such as read-only memory (ROM) or flash RAM. Memory is an example of computer-readable media.

Computer-readable media include permanent, nonpermanent, mobile, and immobile media, which can achieve information storage through any method or technology. The information may be computer-readable instructions, data structures, program modules, or other data. Examples of computer storage media include, but are not limited to, Phase-change RAM (PRAM), Static RAM (SRAM), Dynamic RAM (DRAM), other types of Random Access Memory (RAM), Read-Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), flash memory or other internal memory technologies, Compact Disk Read-Only Memory (CD-ROM), Digital Versatile Discs (DVD) or other optical memories, cassettes, magnetic tape and disk memories or other magnetic memory devices, or any other non-transmission media, which can be used for storing information that can be accessed by a computation device. According to the definitions herein, computer-readable media exclude transitory computer-readable media (transitory media), such as modulated data signals and carriers.

The preceding are merely embodiments of this application. They are not used to limit this application. For persons skilled in the art, this application could have various modifications and changes. All revisions, equivalent substitutions, and improvements made within the spirit and principles of this application shall fall within the scope of the claims of this application.

The claims defining the invention are as follows:

1. A user identity verification method, comprising:

 sending a facial quality score threshold and a number of eye-print collection steps corresponding to an identity verification mode to a client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps;

 receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from the client, wherein the facial image meets the facial quality score threshold and a number of the one or more eye-print pair images corresponds to the number of eye-print collection steps;

 comparing the facial image to a preset facial image, and comparing the one or more eye-print pair images to preset eye-print templates corresponding to the identity verification object; and

 when comparison results for the facial image and the one or more eye-print pair images meet preset conditions, sending successful identity verification information to the client.

2. The method according to claim 1, wherein before sending the facial quality score threshold and the number of eye-print collection steps, the method further comprises:

 receiving a user identity verification request;

 obtaining a number of preset eye-print templates corresponding to the identity verification object from a preset storage location, wherein the preset storage location stores eye-print templates corresponding to different identity verification objects; and

 when the number of eye-print templates corresponding to the identity verification object is no less than a present threshold, determining a current mode as the identity verification mode.

3. The method according to claim 2, wherein after obtaining a number of eye-print templates corresponding to the identity verification object, the method further comprises:

 when the number of eye-print templates is less than the preset threshold, determining the current mode as an eye-print enrollment mode;

 sending a facial quality score threshold and a number of eye-print collection steps corresponding to the eye-print enrollment mode to the client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps; and

 storing the one or more eye-print pair images in the preset storage location as the eye-print templates corresponding to the identity verification object.

4. The method according to either one of claim 1 and claim 2, wherein comparing the facial image to the preset facial image comprises:

using the facial image and the preset facial image as input to a preset facial algorithm; and
obtaining a facial comparison score corresponding to the identity verification object from the preset facial algorithm.

5. The method according to claim 4, wherein comparing the one or more eye-print pair images to the preset eye-print templates comprises:

using the one or more eye-print pair images and the eye-print templates corresponding to the identity verification object as input to a preset eye-print algorithm; and
obtaining multiple eye-print liveness scores and an eye-print match score from the preset eye-print algorithm, the number of the multiple eye-print liveness scores corresponding to the number of eye-print collection steps.

6. The method according to claim 5, wherein the preset conditions include:

the facial comparison score, the multiple eye-print liveness scores, and the eye-print match score are greater than respective preset threshold scores.

7. The method according to any one of the preceding claims 4 to 6, further comprising:

when the comparison results for the facial image and the one or more eye-print pair images meet the preset conditions, updating the eye-print templates corresponding to the identity verification object.

8. A user identity verification method, comprising:

receiving a facial quality score threshold and a number of eye-print collection steps corresponding to a current mode;

obtaining a facial image and one or more eye-print pair images corresponding to an identity verification object, the facial image being obtained based on the facial quality score threshold and a number of the one or more eye-print pair images corresponding to the number of eye-print collection steps; and

sending the obtained facial image and the one or more eye-print pair images to a server to perform identity verification of the identity verification object.

9. The user identity verification method according to claim 8, wherein sending the obtained facial image to a server comprises:

determining an image quality of the obtained facial image is no less than the facial quality score threshold; and
sending the obtained facial image to the server.

10. The user identity verification method according to claim 8, wherein before sending the obtained one or more eye-print pair images to the server, the method further comprises:

determining the one or more eye-print pair images meet preset eye-print liveness conditions.

11. A non-transitory computer-readable storage medium for user identity verification, storing instructions executable by one or more processors causing the one or more processors to perform operations comprising:

sending a facial quality score threshold and a number of eye-print collection steps corresponding to an identity verification mode to a client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps;

receiving a facial image and one or more eye-print pair images corresponding to an identity verification object from the client, wherein the facial image meets the facial quality score threshold and a number of the one or more eye-print pair images corresponds to the number of eye-print collection steps;

comparing the facial image to a preset facial image, and comparing the one or more eye-print pair images to preset eye-print templates; and

when comparison results for the facial image and the one or more eye-print pair images meet preset conditions, sending successful identity verification information to the client.

12. The non-transitory computer-readable storage medium according to claim 11, wherein before sending the facial quality score threshold and the number of eye-print collection steps, the operations further comprise:

receiving a user identity verification request;

obtaining a number of preset eye-print templates corresponding to the identity verification object from a preset storage location, wherein the preset storage location stores eye-print templates corresponding to different identity verification objects; and

when the number of eye-print templates corresponding to the identity verification object is no less than a preset threshold, determining a current mode as the identity verification mode.

13. The non-transitory computer-readable storage medium according to claim 12, wherein after obtaining the number of eye-print templates corresponding to the identity verification object, the operations further comprise:

when the number of eye-print templates corresponding to the identity verification object is less than the preset threshold, determining the current mode as an eye-print enrollment mode;

sending a facial quality score threshold and a number of eye-print collection steps corresponding to the eye-print enrollment mode to the client to obtain facial images based on the facial quality score threshold and obtain eye-print pair images corresponding to the number of eye-print collection steps; and

storing the obtained eye-print pair images in the preset storage location as the eye-print templates corresponding to the identity verification object.

14. The non-transitory computer-readable storage medium according to any one of the preceding claims 11 to 13, wherein comparing the facial image to the preset facial image comprises:

using the facial image and the preset facial image as input to a preset facial algorithm; and

obtaining a facial comparison score corresponding to the identity verification object from the preset facial algorithm.

15. The non-transitory computer-readable storage medium according to claim 14, wherein comparing the one or more eye-print pair images to the preset eye-print templates comprises:

using the one or more eye-print pair images and the eye-print templates corresponding to the identity verification object as input to a preset eye-print algorithm; and

obtaining multiple eye-print liveness scores and an eye-print match score from the preset eye-print algorithm, the number of the multiple eye-print liveness scores corresponding to the number of eye-print collection steps.

16. The non-transitory computer-readable storage medium according to claim 15, wherein the preset conditions include:

the facial comparison score, the multiple eye-print liveness scores, and the eye-print match score are greater than respective preset threshold scores.

17. The non-transitory computer-readable storage medium according to any one of the preceding claims 14 to 16, wherein the operations further comprise:

when the comparison results for the facial image and the one or more eye-print pair images meet the preset conditions, updating the eye-print templates corresponding to the identity verification object.

Alibaba Group Holding Limited

By Patent Attorneys for the Applicant



Patent & Trade Mark Attorneys




FIG. 1



FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10