



US011591032B1

(12) **United States Patent**
Willison et al.

(10) **Patent No.:** **US 11,591,032 B1**

(45) **Date of Patent:** **Feb. 28, 2023**

(54) **LAND VEHICLES INCORPORATING BRAKE SYSTEMS AND METHODS THEREFOR**

2123/00; B60T 1/005; B60R 7/08; B60P 3/007

See application file for complete search history.

(71) Applicant: **Workhorse Group Inc.**, Loveland, OH (US)

(56) **References Cited**

(72) Inventors: **Robert Willison**, Lebanon, OH (US);
Donald L. Wires, Loveland, OH (US);
Gary Cain, Loveland, OH (US)

U.S. PATENT DOCUMENTS

1,251,749 A	1/1918	Cilley
1,728,889 A	9/1929	Kemble
2,172,831 A	9/1939	Philip
2,728,420 A	12/1955	Wright et al.
2,973,220 A	2/1961	White
3,066,621 A	12/1962	Dean et al.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/546,500**

CN	103359174 A	10/2013
CN	110884568 A	3/2020

(22) Filed: **Dec. 9, 2021**

(Continued)

(51) **Int. Cl.**

B60T 1/00	(2006.01)
B62D 63/04	(2006.01)
B60T 1/06	(2006.01)
F16D 55/22	(2006.01)
F16D 63/00	(2006.01)
B60K 7/00	(2006.01)
B62D 33/06	(2006.01)
F16D 65/18	(2006.01)
F16D 121/04	(2012.01)
F16D 121/18	(2012.01)

OTHER PUBLICATIONS

Machine translation of DE 10 2019 109 465 (no date).*

(Continued)

Primary Examiner — Nicholas J Lane

(74) *Attorney, Agent, or Firm* — Taft Stettinius & Hollister LLP

(52) **U.S. Cl.**

CPC **B62D 63/04** (2013.01); **B60K 7/0007** (2013.01); **B60T 1/005** (2013.01); **B60T 1/065** (2013.01); **B62D 33/06** (2013.01); **F16D 55/22** (2013.01); **F16D 63/006** (2013.01); **F16D 65/183** (2013.01); **B60K 2007/0092** (2013.01); **F16D 2121/04** (2013.01); **F16D 2121/18** (2013.01)


(57) **ABSTRACT**

Land vehicles and methods of operating land vehicles are disclosed. A land vehicle includes a frame structure, a plurality of wheels, and a brake system. The frame structure includes a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction. The plurality of wheels are supported by the frame structure. Each of plurality of wheels is sized to permit direct integration of an electric motor therein.

(58) **Field of Classification Search**

CPC F16D 63/006; F16D 2055/0091; F16D 2055/005; F16D 2055/0083; F16D

20 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,696,732 A 10/1972 Rodgers
 4,159,832 A * 7/1979 Inbody F16D 55/22
 4,270,622 A 6/1981 Travis
 4,676,545 A 6/1987 Bonfilio et al.
 4,934,733 A 6/1990 Smith et al.
 5,168,963 A 12/1992 Poncini
 5,363,939 A 11/1994 Catlin
 5,628,438 A 5/1997 Legrow
 5,690,378 A 11/1997 Romesburg
 5,829,542 A 11/1998 Lutz
 6,893,046 B2 5/2005 Ledesma et al.
 6,926,351 B2 8/2005 Telehowski et al.
 6,954,152 B1 10/2005 Matthews
 7,651,153 B2 1/2010 Martin et al.
 8,641,133 B1 2/2014 Scaringe et al.
 8,714,592 B1 5/2014 Thoreson et al.
 9,103,535 B1 8/2015 Strobel et al.
 9,168,818 B2 10/2015 Hirai et al.
 9,550,414 B2 * 1/2017 Kudo B60B 27/0015
 10,801,169 B2 10/2020 Roy et al.
 10,967,904 B2 4/2021 Penz et al.
 2004/0118643 A1 * 6/2004 Booher F16D 55/22
 188/73.1
 2006/0158024 A1 7/2006 Wendl
 2006/0273571 A1 12/2006 Matsumoto et al.
 2007/0257570 A1 * 11/2007 Walter B60K 7/0007
 310/67 R
 2008/0003321 A1 1/2008 Kerr et al.
 2009/0032321 A1 2/2009 Marsh et al.
 2010/0025132 A1 2/2010 Hill et al.
 2010/0101900 A1 * 4/2010 Usui F16D 65/18
 188/156
 2010/0108417 A1 5/2010 Gilmore
 2010/0263954 A1 10/2010 Constans
 2011/0017527 A1 * 1/2011 Oriet et al. B60S 13/00
 2013/0153343 A1 * 6/2013 Neudeck B60T 1/065
 188/71.1
 2013/0341971 A1 12/2013 Masini et al.
 2014/0054916 A1 2/2014 Knudtson et al.
 2014/0083606 A1 3/2014 Masini et al.
 2014/0159468 A1 * 6/2014 Heinen B60L 15/2009
 301/6.5
 2014/0182954 A1 7/2014 Weber
 2014/0203624 A1 * 7/2014 Hilton B60T 13/585
 303/3
 2015/0027795 A1 1/2015 Hirai et al.
 2015/0291017 A1 * 10/2015 LaBiche B60J 7/1204
 296/100.1
 2015/0367721 A1 * 12/2015 Shiraki F16D 55/02
 301/6.5
 2017/0050514 A1 2/2017 Li
 2017/0113716 A1 4/2017 Gong et al.
 2017/0225715 A1 8/2017 Kobayashi et al.
 2017/0305253 A1 10/2017 Perlo et al.
 2018/0037151 A1 2/2018 Bauer et al.
 2018/0043895 A1 * 2/2018 Shami F16H 63/486
 2018/0108891 A1 4/2018 Fees et al.
 2018/0290627 A1 10/2018 Hariri et al.
 2018/0337377 A1 11/2018 Stephens et al.
 2018/0345777 A1 12/2018 Bimschein et al.
 2019/0054895 A1 * 2/2019 Hall B60R 25/09
 2019/0056005 A1 * 2/2019 Hall B60T 1/06
 2019/0168678 A1 * 6/2019 Magnuson B60R 7/08
 2019/0389444 A1 * 12/2019 Kistner B60T 13/74
 2020/0062183 A1 2/2020 Smith et al.
 2020/0369334 A1 11/2020 Lee
 2021/0171120 A1 6/2021 Kim et al.
 2021/0206432 A1 * 7/2021 Willison B29C 70/28

FOREIGN PATENT DOCUMENTS

DE 19626901 A1 1/1998
 DE 102012101483 A1 6/2013
 DE 102015200737 B4 * 6/2020 B60T 1/005
 DE 102015200737 B4 6/2020
 DE 102019109465 A1 * 10/2020 F16D 63/006
 DE 102019109465 A1 10/2020
 EP 1538072 A1 6/2005
 EP 2552763 A2 2/2013
 EP 3174680 A2 6/2017
 EP 3689717 A1 8/2020
 FR 2698601 A1 6/1994
 GB 2479898 A * 11/2011 B60T 1/06
 WO 2016016662 A2 2/2016

OTHER PUBLICATIONS

Machine translation of DE 10 2015 200 737 (no date).
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2021/012327; dated Mar. 9, 2021; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2021/012327; dated Mar. 9, 2021; 8 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2021/012330; dated Mar. 9, 2021; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2021/012330; dated Mar. 9, 2021; 9 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2021/012332; dated Mar. 24, 2021; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2021/012332; dated Mar. 24, 2021; 7 pages.
 Supplementary European Search Report; European Patent Office; European Application No. 21710384.5; dated Oct. 21, 2021; 12 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2022/014847; dated Mar. 8, 2022; 3 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2022/014847; dated Mar. 8, 2022; 6 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2022/014844; dated Mar. 16, 2022; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2022/014844; dated Mar. 16, 2022; 7 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2022/014852; dated Apr. 18, 2022; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2022/014852; dated Apr. 18, 2022; 7 pages.
 International Search Report; International Searching Authority; International Patent Application No. PCT/US2022/014851; dated Apr. 25, 2022; 2 pages.
 Written Opinion of the International Searching Authority; International Searching Authority; International Patent Application No. PCT/US2022/014851; dated Apr. 25, 2022; 7 pages.
 Extended European Search Report; European Patent Office; European Patent Application No. 22153661.8; dated Jul. 6, 2022; 11 pages.
 Partial European Search Report (R. 64 EPC); European Patent Office; European Patent Application No. 22153665.9; dated Aug. 18, 2022; 16 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

1

LAND VEHICLES INCORPORATING BRAKE SYSTEMS AND METHODS THEREFOR

TECHNICAL FIELD

The present disclosure generally relates to land vehicles incorporating electric motors and brake systems, and, more particularly, to utility and delivery vehicles incorporating electric motors and brake systems.

BACKGROUND

Powertrain devices and/or systems that include one or more gas-powered motors may suffer from a variety of drawbacks, particularly when incorporated into, or designed for use with, land vehicles such as utility and delivery vehicles, for example. In addition, brake systems for land vehicles may have various shortcomings. For those reasons, among others, powertrain devices and/or brake systems that avoid the limitations of conventional components remain an area of interest.

SUMMARY

The present disclosure may comprise one or more of the following features and combinations thereof.

According to one aspect of the present disclosure, a land vehicle may include a frame structure, a plurality of wheels supported by the frame structure, and a brake system coupled to each one of the plurality of wheels. The frame structure may include a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction. Each of the plurality of wheels may be sized to permit direct integration of an electric motor therein. The brake system may include a disc having a plurality of notches defined between circumferentially adjacent teeth of the disc, a first braking device configured to contact an outer face of the disc to resist rotation of one of the plurality of wheels, a second braking device that is circumferentially spaced from the first braking device about the disc and configured to contact the outer face of the disc to resist rotation of the one of the plurality of wheels, and a third braking device configured to contact one or more teeth of the disc to resist rotation of the one of the plurality of wheels.

In some embodiments, the first braking device may include only one caliper and at least piston at least partially housed by the only one caliper. The at least one piston may include six pistons. Additionally, in some embodiments, at least one piston may include only one piston.

In some embodiments, the second braking device may be an electronic parking brake mechanism. The third braking device may be a parking pawl mechanism operated independently from the electronic parking brake mechanism. The parking pawl mechanism may include a receptacle sized to receive a drive to permit manual release of the parking pawl mechanism in use of the land vehicle.

In some embodiments, the operator may include a steering wheel, an operator seat, and a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays. The operator cabin may include a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction, and the rack may be movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery

2

position, in which the rack is disposed close to the operator seat. The land vehicle may have a gross vehicular weight rating (GVWR) of between 10,001 pounds and 14,000 pounds.

In some embodiments, the land vehicle may include a plurality of electric motors, and each of the plurality of electric motors may be integrated directly into one of the plurality of wheels. Each of the plurality of electric motors may be coupled to one of the plurality of wheels without any transmission gearing interposed therebetween, and the land vehicle may not include an internal combustion engine.

According to another aspect of the present disclosure, a land vehicle may include a frame structure, a plurality of wheels supported by the frame structure, and a brake system coupled to each one of the plurality of wheels. The frame structure may include a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction. The brake system may include a disc having a plurality of notches defined between circumferentially adjacent teeth of the disc, a first braking device configured to contact an outer face of the disc to resist rotation of one of the plurality of wheels, and a second braking device configured to contact one or more teeth of the disc to resist rotation of the one of the plurality of wheels.

In some embodiments, the first braking device may be an electronic parking brake mechanism. The second braking device may be a parking pawl mechanism operated independently from the electronic parking brake mechanism. The land vehicle may include a third braking device circumferentially spaced from the first braking device about the disc that is configured to contact the outer face of the disc to resist rotation of the one of the plurality of wheels, and the third braking device may include only one caliper and a plurality of pistons at least partially housed by the only one caliper. Additionally, in some embodiments, the third braking device may include only one caliper and only one piston at least partially housed by the caliper.

In some embodiments, the operator cabin may include a steering wheel, an operator seat, and a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays. The operator cabin may include a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction, and the rack may be movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery position, in which the rack is disposed close to the operator seat. The land vehicle may have a gross vehicular weight rating (GVWR) of between 10,001 pounds and 14,000 pounds. The land vehicle may include a plurality of electric motors, each of the plurality of electric motors may be integrated directly into one of the plurality of wheels, each of the plurality of electric motors may be coupled to one of the plurality of wheels without any transmission gearing interposed therebetween, and the land vehicle may not include an internal combustion engine.

According to yet another aspect of the present disclosure, a method of operating a land vehicle that includes a frame structure having a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction, a plurality of wheels supported by the frame structure, and a brake system coupled to each one of the plurality of wheels may include operating the land vehicle in a park operating range and operating the brake systems when the land vehicle is in the

park operating range. Operating the brake systems when the land vehicle is in the park operating range may include selectively activating an electronic parking brake mechanisms of each brake system and selectively activating a parking pawl mechanisms of each brake system.

In some embodiments, operating the brake systems when the land vehicle is in the park operating range may include activating the parking brake mechanism of each brake system and the parking pawl mechanism of each brake system contemporaneously. Additionally, in some embodiments, the method may include selectively releasing the parking pawl mechanism of each brake system manually subsequent to activation of the parking pawl mechanism of each brake system.

According to yet another aspect of the present disclosure still, a land vehicle may include a frame structure, a plurality of wheels supported by the frame structure, a plurality of electric motors to generate rotational power that are supported by the plurality of wheels, and a power cell assembly to supply electrical power to the plurality of electric motors that is supported by the frame structure. The frame structure may include a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction. The plurality of wheels may include a pair of front wheels and a pair of rear wheels positioned rearward of the pair of front wheels in the longitudinal direction. The plurality of electric motors may include a first electric motor integrated directly into one of the pair of front wheels, a second electric motor integrated directly into the other of the pair of front wheels, a third electric motor integrated directly into one of the pair of rear wheels, and a fourth electric motor integrated directly into the other of the pair of rear wheels. The power cell assembly may be at least partially housed by a carrier positioned between the pair of front wheels and the pair of rear wheels in the longitudinal direction.

In some embodiments, the operator cabin may include a steering wheel, an operator seat, and a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays. The operator cabin may include a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction, and the rack may be movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery position, in which the rack is disposed close to the operator seat. The land vehicle may have a gross vehicular weight rating (GVWR) of between 10,001 pounds and 14,000 pounds.

In some embodiments, each of the plurality of electric motors may be configured to generate about 100 horsepower (hp). The power cell assembly may include a modular system having one or more battery pack modules each configured to supply electrical power to the plurality of electric motors in use of the vehicle, and in use of the vehicle, battery pack modules may be added to, or removed from, the modular system depending on a particular delivery mission of the vehicle.

In some embodiments, each of the plurality of electric motors may be coupled to one of the plurality of wheels without any transmission gearing interposed therebetween. The land vehicle may not include an internal combustion engine.

In some embodiments, the power cell assembly may include a bottom tray, a casing supported by the bottom tray that houses a plurality of cooling plates to dissipate heat

generated by the power cell assembly in use thereof, an intermediate tray at least partially positioned in the casing, a plurality of power cells at least partially positioned in the intermediate tray, and a top cover that cooperates with the bottom tray, the casing, and the intermediate tray to at least partially enclose the plurality of power cells. The frame structure may include a pair of rails that each extends from a first end arranged forward of the pair of front wheels in the longitudinal direction to a second end arranged rearward of the pair of rear wheels in the longitudinal direction, the pair of rails may be spaced apart a first distance from one another in the location of the carrier, the pair of rails may be spaced apart a second distance from one another in a location forward of the carrier that is less than the first distance, and the pair of rails may be spaced apart a third distance from one another in a location rearward of the carrier that is less than the first distance and greater than the second distance.

According to a further aspect of the present disclosure, a land vehicle may include a frame structure, a plurality of wheels supported by the frame structure, a plurality of electric motors to generate rotational power that are supported by the plurality of wheels, and a power cell assembly to supply electrical power to the plurality of motors that is supported by the frame structure. The frame structure may include a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction. The plurality of wheels may include a pair of front wheels and a pair of rear wheels positioned rearward of the pair of front wheels in the longitudinal direction. Each of the plurality of electric motors may be integrated directly into one of the plurality of wheels. The power cell assembly may be at least partially housed by a carrier positioned between the pair of front wheels and the pair of rear wheels in the longitudinal direction. The frame structure may include a pair of rails that each extends from a first end arranged forward of the pair of front wheels in the longitudinal direction to a second end arranged rearward of the pair of rear wheels in the longitudinal direction. The pair of rails may be spaced apart a first distance from one another in the location of the carrier. The pair of rails may be spaced apart a second distance from one another in a location forward of the carrier that is less than the first distance. The pair of rails may be spaced apart a third distance from one another in a location rearward of the carrier that is less than the first distance and greater than the second distance.

In some embodiments, the operator cabin may include a steering wheel, an operator seat, and a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays. The operator cabin may include a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction, and the rack may be movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery position, in which the rack is disposed close to the operator seat.

In some embodiments, each of the plurality of electric motors may be coupled to one of the plurality of wheels without any transmission gearing interposed therebetween. The plurality of electric motors may include a first electric motor integrated directly into one of the pair of front wheels, a second electric motor integrated directly into the other of the pair of front wheels, a third electric motor integrated

5

directly into one of the pair of rear wheels, and a fourth electric motor integrated directly into the other of the pair of rear wheels.

In some embodiments, the power cell assembly may include a bottom tray, a casing supported by the bottom tray that houses a plurality of cooling plates to dissipate heat generated by the power cell assembly in use thereof, an intermediate tray at least partially positioned in the casing, a plurality of power cells at least partially positioned in the intermediate tray, and a top cover that cooperates with the bottom tray, the casing, and the intermediate tray to at least partially enclose the plurality of power cells. The land vehicle may include a second power cell assembly to supply electrical power to the plurality of electric motors that is supported by the frame structure, and the second power cell assembly may be at least partially housed by a second carrier that extends from a first end arranged forward of the pair of rear wheels in the longitudinal direction to a second end arranged rearward of the pair of rear wheels in the longitudinal direction.

According to a further aspect of the present disclosure still, a method of operating a land vehicle that includes a frame structure having a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction, a plurality of wheels supported by the frame structure, and a plurality of electric motors each integrated directly into one of the plurality of wheels may include operating the plurality of electric motors independently of one another to drive rotation of the plurality of wheels independently of one another and steering the plurality of wheels to adjust an orientation of the land vehicle.

In some embodiments, steering the plurality of wheels to adjust an orientation of the land vehicle may include turning the land vehicle 360 degrees in a circular path. Turning the land vehicle 360 degrees in a circular path may include turning the land vehicle without shifting the land vehicle to a reverse operating range.

These and other features of the present disclosure will become more apparent from the following description of the illustrative embodiments.

BRIEF DESCRIPTION OF THE FIGURES

The invention described herein is illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. For example, the dimensions of some elements may be exaggerated relative to other elements for clarity. Further, where considered appropriate, reference labels have been repeated among the figures to indicate corresponding or analogous elements.

FIG. 1 is a front perspective view of an electric vehicle; FIG. 2 is a bottom perspective view of the electric vehicle of FIG. 1 according to one embodiment of the present disclosure;

FIG. 3 is a bottom perspective view of the electric vehicle of FIG. 1 according to another embodiment of the present disclosure;

FIG. 4 is a sectional view of the electric vehicle of FIG. 1 taken about line 4-4 showing a rack in a stowed position in which the rack is disposed distant from an operator seat;

FIG. 5 is a sectional view similar to FIG. 4 showing the rack in a delivery position in which the rack is disposed close to the operator seat;

6

FIG. 6 is a bottom perspective view of the electric vehicle of FIG. 1 showing a power cell assembly supported by a frame structure;

FIG. 7 is a side perspective view of the electric vehicle of FIG. 1 showing an electric motor integrated directly into a wheel;

FIG. 8 is a front perspective view of the electric vehicle of FIG. 1 showing a plurality of electric motors supported by the frame structure with certain features omitted for the sake of simplicity;

FIG. 9 is a detail view of a portion of the electric vehicle of FIG. 8 with certain features omitted for the sake of simplicity;

FIG. 10 is an exploded assembly view of at least one power cell assembly that may be included in the electric vehicle of FIG. 1;

FIG. 11 is a side perspective view of at least one brake assembly coupled to a wheel according to one embodiment of the present disclosure;

FIG. 12 is a detail view of a first braking device that may be included in the at least one brake assembly of FIG. 11;

FIG. 13 is a side perspective view of a brake system coupled to a wheel according to another embodiment of the present disclosure;

FIG. 14 is a detail view of several braking devices of the brake system of FIG. 13;

FIG. 15 is a detail view of a portion of one of the several braking devices of FIG. 14;

FIG. 16 is a diagrammatic view of a control system that may be included in the electric vehicle of FIG. 1;

FIG. 17 is a simplified flowchart of a method of operating the electric vehicle of FIG. 1 according to one embodiment of the present disclosure;

FIG. 18 is a simplified flowchart of a method of operating the electric vehicle of FIG. 1 according to another embodiment of the present disclosure;

FIG. 19 is a bottom perspective view of a carriage configured to hold one or more battery pack modules; and

FIG. 20 is a perspective view of a modular system including one or more battery pack modules that may be secured by the carriage of FIG. 19.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and will be described herein in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives consistent with the present disclosure and the appended claims.

References in the specification to “one embodiment,” “an embodiment,” “an illustrative embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may or may not necessarily include that particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. Additionally, it should be appreciated that items included in a list in

the form of “at least one A, B, and C” can mean (A); (B); (C); (A and B); (A and C); (B and C); or (A, B, and C). Similarly, items listed in the form of “at least one of A, B, or C” can mean (A); (B); (C); (A and B); (A and C); (B and C); or (A, B, and C).

In the drawings, some structural or method features, such as those representing devices, modules, instructions blocks and data elements, may be shown in specific arrangements and/or orderings for ease of description. However, it should be appreciated that such specific arrangements and/or orderings may not be required. Rather, in some embodiments, such features may be arranged in a different manner and/or order than shown in the illustrative figures. Additionally, the inclusion of a structural or method feature in a particular figure is not meant to imply that such feature is required in all embodiments and, in some embodiments, may not be included or may be combined with other features.

In some embodiments, schematic elements used to represent blocks of a method may be manually performed by a user. In other embodiments, implementation of those schematic elements may be automated using any suitable form of machine-readable instruction, such as software or firmware applications, programs, functions, modules, routines, processes, procedures, plug-ins, applets, widgets, code fragments and/or others, for example, and each such instruction may be implemented using any suitable programming language, library, application programming interface (API), and/or other software development tools. For instance, in some embodiments, the schematic elements may be implemented using Java, C++, and/or other programming languages. Similarly, schematic elements used to represent data or information may be implemented using any suitable electronic arrangement or structure, such as a register, data store, table, record, array, index, hash, map, tree, list, graph, file (of any file type), folder, directory, database, and/or others, for example.

Further, in the drawings, where connecting elements, such as solid or dashed lines or arrows, are used to illustrate a connection, relationship, or association between or among two or more other schematic elements, the absence of any such connection elements is not meant to imply that no connection, relationship, or association can exist. In other words, some connections, relationships, or associations between elements may not be shown in the drawings so as not to obscure the disclosure. In addition, for ease of illustration, a single connecting element may be used to represent multiple connections, relationships, or associations between elements. For example, where a connecting element represents a communication of signals, data or instructions, it should be understood by those skilled in the art that such element may represent one or multiple signal paths (e.g., a bus), as may be needed, to effect the communication.

Referring now to FIG. 1, an illustrative land vehicle **100** is embodied as, or otherwise includes, an electric delivery vehicle **102**, such as an electric delivery truck adapted for any use as a delivery vehicle, for example. In some embodiments, the electric delivery vehicle **102** is adapted for use as a mail delivery vehicle that may be employed by the United States Postal Service. Of course, in other embodiments, the electric delivery vehicle **102** may be configured for use in a variety of other suitable applications. Furthermore, in other embodiments, the land vehicle **100** may be embodied as, or otherwise include, an electric utility van.

In some embodiments, the illustrative electric delivery vehicle **102** is a postal delivery truck. Additionally, in some embodiments, the illustrative delivery vehicle **102** is a

non-postal delivery truck. In embodiments in which the delivery vehicle **102** is a non-postal delivery truck, the vehicle **102** may be employed in a variety of applications, such as the applications mentioned below, for example.

The illustrative land vehicle **100** may include one or more of the features of the electric vehicle described in co-pending U.S. patent application Ser. No. 17/546,555, such as a roof cap **104**, one or more rain gutter(s) **106**, one or more blind spot camera system(s) **108**, one or more opera window(s) **110**, and one or more opera window mirror(s) **112**, just to name a few. Additionally, the illustrative land vehicle **100** may include one or more features of the electric vehicle described in co-pending U.S. patent application Ser. No. 17/546,641, such as an impact management system **114**, for example. The disclosures of those applications are incorporated herein by reference in their entireties.

In some embodiments, the illustrative land vehicle **100** may include a monocoque, such as one of the monocoques described in U.S. patent application Ser. No. 17/142,766. Furthermore, in some embodiments, a monocoque of the illustrative land vehicle **100** may be formed using a modular mold system, such as one of the modular mold systems described in U.S. patent application Ser. No. 17/142,766. Further still, in some embodiments, a monocoque of the illustrative land vehicle **100** may be formed according to the methods described in U.S. patent application Ser. No. 17/142,785. The disclosures of those applications are incorporated herein by reference in their entireties.

It should be appreciated that the land vehicle **100** may be employed in a variety of applications. In some embodiments, the land vehicle **100** may be embodied as, or otherwise included in, a fire and emergency vehicle, a refuse vehicle, a coach vehicle, a recreational vehicle or motorhome, a municipal and/or service vehicle, an agricultural vehicle, a mining vehicle, a specialty vehicle, an energy vehicle, a defense vehicle, a port service vehicle, a construction vehicle, and a transit and/or bus vehicle, just to name a few. Additionally, in some embodiments, the vehicle **100** may be adapted for use with, or otherwise incorporated into, tractors, front end loaders, scraper systems, cutters and shredders, hay and forage equipment, planting equipment, seeding equipment, sprayers and applicators, tillage equipment, utility vehicles, mowers, dump trucks, backhoes, track loaders, crawler loaders, dozers, excavators, motor graders, skid steers, tractor loaders, wheel loaders, rakes, aerators, skidders, bunchers, forwarders, harvesters, swing machines, knuckleboom loaders, diesel engines, axles, planetary gear drives, pump drives, transmissions, generators, and marine engines, among other suitable equipment.

The illustrative land vehicle **100** includes a frame structure **200** (see FIG. 2) and wheels **212** supported by the frame structure **200**. The frame structure **200** includes, or otherwise at least partially defines, a front cage **204** that at least partially defines an operator cabin **206** and a rear compartment **208** positioned rearward of the front cage **204** in a longitudinal direction **210**. The wheels **212** includes a pair of front wheels **214**, **216** and a pair of wheels **218**, **220** positioned rearward of the wheels **214**, **216** in the longitudinal direction **210**. As will be evident from the discussion that follows, each of the wheels **212** is sized to permit direct integration of an electric motor **800** therein. However, as mentioned above, in other embodiments, the land vehicle **100** may include a monocoque. In one example, the monocoque may be provided in place of the frame structure **200**. In another example, the monocoque may be provided in addition to the frame structure **200**. In yet another example, the frame structure **200** may serve as an reinforcement

structure which is disposed internally in the monocoque, and the monocoque may be disposed externally to the frame structure **200**.

In the illustrative embodiment, the land vehicle **100** includes electric motors **800** (see FIG. 8) supported by the wheels **212** that are configured to generate rotational power in use of the vehicle **100**. More specifically, the illustrative vehicle **100** includes an electric motor **802** integrated directly into the wheel **214**, an electric motor **804** integrated directly into the wheel **216**, an electric motor **806** integrated directly into the wheel **218**, and an electric motor **808** integrated directly into the wheel **220**. As discussed below, each of the motors **802**, **804**, **806**, **808** is illustratively embodied as, or otherwise includes, a hub motor or wheel hub motor.

The illustrative land vehicle **100** includes a power cell assembly **1000** (see FIG. 10) supported by the frame structure **200** that is configured to supply electrical power to the electric motors **800** in use of the vehicle **100**. As best seen in FIGS. 2 and 3, the power cell assembly **1000** is at least partially housed by a carrier **222** included in, or otherwise defined by, the frame structure **200**. In the illustrative embodiment, the carrier **222** is positioned between the front wheels **214**, **216** and the rear wheels **218**, **220** in the longitudinal direction **210**. In some embodiments, positioning of the power cell assembly **1000** approximately midway between the front wheels **214**, **216** and the rear wheels **218**, **220** in the direction **210** may facilitate routing of electrical power to, and distribution of electrical power between, the electric motors **800** integrated directly into the wheels **212**.

The illustrative land vehicle **100** includes a brake system **1300** (see FIG. 13) coupled to each one of the wheels **212**. In some embodiments, the brake system **1300** includes a disc **1302**, a braking device **1310**, a braking device **1330**, and a braking device **1350**. The illustrative disc **1302** includes notches **1304** defined between circumferentially adjacent teeth **1306** of the disc **1302**. The illustrative braking device **1310** is configured to contact an outer face **1308** of the disc **1302** to resist rotation of one of the wheels **212** in use of the vehicle **100**. The illustrative braking device **1330** is circumferentially spaced from the braking device **1310** about the disc **1302** and configured to contact the outer face **1308** thereof to resist rotation of one of the wheels **212** in use of the vehicle **100**. The illustrative braking device **1350** is configured to contact one or more teeth **1306** of the disc **1302** to resist rotation of one of the wheels **212** in use of the vehicle **100**.

Referring now to FIG. 2, the illustrative frame structure **200** includes a pair of substantially identical rails **230**, **240** arranged to extend in the longitudinal direction **210** substantially over an entire length **L** of the vehicle **100**. The rail **230** extends from an end **232** arranged forward of the wheels **214**, **216** in the longitudinal direction **210** to an opposite end **234** arranged rearward of the wheels **218**, **220** in the direction **210**. The rail **240** extends from an end **242** arranged forward of the wheels **214**, **216** in the direction **210** to an opposite end **244** arranged rearward of the wheels **218**, **220** in the direction **210**.

In the illustrative embodiment, as shown in FIGS. 2 and 8, the rails **230**, **240** are laterally spaced apart from one another by a distance **D1** in the location of the carrier **222**. In a location **224** forward of the carrier **222** in the direction **210**, the rails **230**, **240** are laterally spaced apart from one another by a distance **D2**. In a location **226** rearward of the carrier **222** in the direction **210**, the rails **230**, **240** are laterally spaced apart from one another by a distance **D3**.

The illustrative distance **D1** is greater than the distance **D2** and the distance **D3**. The illustrative distance **D3** is greater than the distance **D2**.

Referring now to FIG. 3, in some embodiments, in addition to the power cell assembly **1000**, the land vehicle **100** includes a power cell assembly **300**. The power cell assembly **300** may be substantially identical to the power cell assembly **1000**. Like the power cell assembly **1000**, the illustrative power cell assembly **300** is supported by the frame structure **200** and configured to supply electrical power to the electric motors **800**. In the illustrative embodiment, the power cell assembly **300** is at least partially housed by a carrier **322** of the frame structure **200**. The carrier **322** is illustratively arranged rearward of the carrier **222** in the longitudinal direction **210**. Additionally, the carrier **322** extends from an end **324** located forward of the wheels **218**, **220** in the direction **210** to an opposite end **326** located rearward of the wheels **218**, **220** in the direction **210**.

In the illustrative embodiment, in the location of the carrier **322**, the rails **230**, **240** are laterally spaced apart from one another by a distance **D4**. The distance **D4** is illustratively smaller than the distance **D1**. The distance **D4** is illustratively greater than the distance **D2** and the distance **D3**. In some embodiments, however, the distance **D4** may be substantially equal to the distance **D3**.

Referring now to FIGS. 4 and 5, in the illustrative embodiment, a number of features are included in the operator cabin **206** of the land vehicle **100**. Those features are described in greater detail in co-pending U.S. application Ser. No. 17/546,555. Among other things, the illustrative operator cabin **206** includes, or otherwise houses, a steering wheel **400**, an operator seat **410**, and a rack **420** including trays **422**.

The illustrative cabin **206** includes a right-hand drive configuration **402** in which the steering wheel **400** and the operator seat **410** are arranged on a right side **404** of the cabin **206**. It should be appreciated that the configuration **402** may facilitate curbside delivery from a driver seated in the operator seat **410** to a curbside mailbox, at least in some embodiments. In any case, in the illustrative right-hand configuration **402** of the operator cabin **206**, the rack **420** is mounted on a left side **406** of the cabin **206** opposite the steering wheel **400** and the operator seat **410**. As such, the rack **420** occupies a space that might otherwise be occupied by a passenger or driver seat in other configurations.

The illustrative operator cabin **206** includes, or otherwise houses, a pair of tracks **430**, **432** that are affixed to a floor **408** of the cabin **206**. The tracks **430**, **432** are spaced apart from one another in the longitudinal direction **210** and arranged on the left side **406** of the cabin **206**. In the illustrative embodiment, the rack **420** is movable in the operator cabin **206** along the tracks **430**, **432** in a lateral direction **412** perpendicular to the longitudinal direction **210**.

In the illustrative embodiment, the rack **420** is movable in the operator cabin **206** along the tracks **430**, **432** in a lateral direction **412** between a stowed position **440** and a delivery position **500**. In the stowed position **440** of the rack **420**, the rack **420** is disposed distant from the operator seat **410**. It should be appreciated that when the rack **420** is disposed in the stowed position **440**, items (e.g., mail parcels, articles, etc.) held by the trays **422** of the rack **420** may be located sufficiently far from the operator such that the operator may be required to leave the seat **410** to access the items. In the delivery position **500** of the rack **420**, the rack **420** is disposed close to the operator seat **410**. As a result, when the rack **420** is disposed in the delivery position **500**, items held

by the trays **422** of the rack **420** may be accessed by the operator without leaving the seat **410**, at least in some embodiments.

It should be appreciated that in the United States, trucks are often classified according to their gross vehicular weight rating (GVWR) which may correspond to particular truck classifications and duty classifications given in Table 1 below. In some embodiments, the vehicle **100** has a GVWR (i.e., accounting for the weight of the truck when empty and the payload carrying capacity of the truck when full) of between 6,000 pounds and 19,800 pounds. Additionally, in some embodiments, the vehicle **100** has a GVWR of between 10,001 pounds and 14,000 pounds such that the vehicle **100** is embodied as, or otherwise includes, a Class 3 electric delivery truck. In one particular example, in some embodiments, the vehicle **100** has a 1000 cubic foot capacity and weighs roughly 6,500 pounds when empty and has a 6,000 pound payload capacity such that the vehicle **100** has a GVWR of about 12,500 pounds. Of course, it should be appreciated that in other embodiments, the vehicle **100** may be embodied as, or otherwise include, a Class 3 vehicle, a Class 4 vehicle, or a Class 5 vehicle.

TABLE 1

US Truck Class	Duty Classification	Weight Limit
Class 1	Light Truck	0-6,000 Pounds
Class 2a	Light Truck	6,001-8,500 Pounds
Class 2b	Light/Medium Truck	8,501-10,000 Pounds
Class 3	Medium Truck	10,001-14,000 Pounds
Class 4	Medium Truck	14,001-16,000 Pounds
Class 5	Medium Truck	16,001-19,500 Pounds
Class 6	Medium Truck	19,501-26,000 Pounds
Class 7	Heavy Truck	26,001-33,000 Pounds
Class 8	Heavy Truck	33,001 Pounds+

It should be appreciated that in some embodiments, the illustrative cabin **206** may include a left-hand drive configuration in which the steering wheel **400** and the operator seat **410** are arranged on the left side **406** of the cabin **206**. In such a left-hand drive configuration, the rack **420** may be mounted on the right side **404** of the cabin **206** opposite the steering wheel **400** and the operator seat **410**. As such, the rack **420** may occupy a space that might otherwise be occupied by a passenger or driver seat in other configurations. Furthermore, in such a left-hand drive configuration, the tracks **430**, **432** may be arranged on the right side **404** of the cabin **206**.

In some embodiments, the vehicle **100** is embodied as, or otherwise includes, any one of a Class 3 through Class 5 electric delivery truck having a right-hand drive configuration. Additionally, in some embodiments, the vehicle **100** is embodied as, or otherwise includes, any one of a Class 3 through Class 5 electric delivery truck having a left-hand drive configuration. Further, in some embodiments still, the vehicle **100** is embodied as, or otherwise includes, any one of a Class 3 through Class 5 electric delivery truck having another suitable drive configuration, such as a configuration in which the steering wheel **400** and the operator seat **410** are centrally located in the cabin **206** in the lateral direction **412**, for example.

Referring now to FIG. 6, the illustrative power cell assembly **1000** includes a connection panel **600**. The connection panel **600** is illustratively arranged at, and accessible from, a forward-most point **602** of the power cell assembly **1000**. Such positioning may facilitate coupling between the electric motors **802**, **804** integrated into the respective

wheels **214**, **216** and the power cell assembly **1000** via the connection panel **600**, among other things.

In the illustrative embodiment, the connection panel **600** includes a master disconnect switch **604**, quick disconnects **606**, a connector **608**, and quick disconnects **610**. The master disconnect switch **604** is configured to selectively disconnect the power cell assembly **1000** from one or more loads (e.g., the motors **800**) or accessories to prevent electrical power from being supplied to the one or more loads or accessories. The quick disconnects **606** are each configured to enable electrical signal transmission at high-voltage ratings between components of the vehicle **100** (e.g., between the power cell assembly **1000** and the motors **800** and/or between the power cell assembly **1000** and a high voltage junction box). In the illustrative embodiment, the connection panel **600** includes three quick disconnects **606**, although it should be appreciated that the connection panel **600** may include another suitable number of quick disconnects **606** in other embodiments. The connector **608** is configured to enable electrical signal transmission at low-voltage ratings between components of the vehicle **100** (e.g., between the power cell assembly **1000** and other low-voltage components). The quick disconnects **610** are configured for connection to one or more fluid hoses to permit delivery of cooling fluid from a fluid source to the power cell assembly **1000** in use of the vehicle **100**.

Referring now to FIG. 7, one of the electric motors **800** (i.e., the motor **802**) is shown in greater detail. The illustrative motor **802** is embodied as, or otherwise includes, any device that is capable of being driven by electrical energy supplied by the power cell assembly **1000** to produce rotational power. As indicated above, the illustrative motor **802** is directly integrated into the wheel **214** so that rotational power produced by the motor **802** is provided directly to the wheel **214** in use of the vehicle **100**. At least in some embodiments, the motor **802** is directly integrated into the wheel **214** such that the motor **802** and the wheel **214** are concentrically mounted about an axis **700**. In such embodiments, the axis **700** may define, or otherwise coincide with, a rotational axis of the wheel **214**.

In the illustrative embodiment, each of the electric motors **800** is coupled to one of the wheels **212** without any transmission gearing interposed therebetween. Even more, at least in some embodiments, the illustrative land vehicle **100** entirely omits one or more transmissions. Consequently, in such embodiments, the land vehicle **100** is free from components that may be present in conventional transmissions, such as torque converters, rotating torque-transmitting mechanisms or clutches, stationary torque-transmitting mechanisms or brakes, transmission gearing, pressure control valves, shift control valves, regulator valves, check valves, and various components of electro-hydraulic control systems. As a result, the powertrain and/or drivetrain of the vehicle **100** may include significantly fewer parts than other configurations, thereby facilitating maintenance, reliability, and reduced design complexity, among other things.

In the illustrative embodiment, the electric motors **800** of the land vehicle **100** are the only components of the vehicle **100** capable of generating rotational power to drive the wheels **212**. The illustrative land vehicle **100** therefore does not include an internal combustion engine. As such, the land vehicle **100** is free from a number of components that may be utilized in conventional configurations to transmit rotational power from one or more internal combustion engines to one or more wheels, such as driveshafts, differentials, and axles, just to name a few. In that additional respect, the powertrain and/or drivetrain of the vehicle **100** may include

13

significantly fewer parts than other configurations, which may facilitate maintenance, reliability, and reduced design complexity as mentioned above.

Referring now to FIG. 8, the wheels **214**, **216**, **218**, **220** with the respective electric motors **802**, **804**, **806**, **808** integrated directly therein are shown mounted to, and supported by, the frame structure **200**. The power cell assembly **1000** is shown mounted to the carrier **222** so that the power cell assembly **1000** is supported by the frame structure **200**. Certain elements (e.g., a body and a roof at least partially defining the front cage **204** and the rear compartment **208**) of the land vehicle **100** are omitted for the sake of simplicity.

In the illustrative embodiment, each of the electric motors **802**, **804**, **806**, **808** is configured to generate about 100 horsepower (hp) in use of the land vehicle **100**. In some embodiments, each of the motors **802**, **804**, **806**, **808** may be embodied as, or otherwise include, a brushed DC motor, a brushless DC motor, a switched reluctance motor, a universal AC/DC motor, an induction motor, a torque motor, a synchronous motor, a doubly-fed electric machine, an ironless or coreless rotor motor, a pancake or axial rotor motor, a servo motor, a stepper motor, a linear motor, or the like. Of course, it should be appreciated that in other embodiments, each of the motors **802**, **804**, **806**, **808** may be embodied as, or otherwise include, another suitable device capable of converting electrical energy supplied by the power cell assembly **1000** to rotational power to drive the wheels **212**. In some embodiments, each of the electric motors **802**, **804**, **806**, **808** is configured to generate a sufficient amount of rotational power and/or motive force to drive movement of one or more of the wheels **212** over an estimated service life of the vehicle **100**, which may encompass a significant number of missions and/or delivery trips. In such embodiments, each of the motors **802**, **804**, **806**, **808** may be configured to generate less than 100 horsepower in use of the vehicle **100** or greater than 100 horsepower in use of the vehicle **100**, whatever the case may be.

The illustrative power cell assembly **1000** includes one or more power cells **1050** (see FIG. 10) capable of supplying electrical power to the electric motors **802**, **804**, **806**, **808** in use of the land vehicle **100**. In the illustrative embodiment, the power cell(s) **1050** are configured to supply electrical power to the motors **800** at a rate of about 80 kilowatt-hour (kWh). In some embodiments, each of the one or more power cells **1050** may be embodied as, or otherwise include, a deep-cycle rechargeable battery. Additionally, in some embodiments, each of the one or more power cells **1050** may be embodied as, or otherwise include, a lithium-ion battery or lithium-polymer battery. In some embodiments still, each of the one or more power cells **1050** may be embodied as, or otherwise include, a lead-acid battery, a nickel-cadmium battery, a nickel-metal hydride battery, a zinc-air battery, or a sodium nickel chloride battery. However, in other embodiments, each of the power cell(s) **1050** may be embodied as, or otherwise include, another suitable device capable of supplying electrical power to the motors **800** to drive the wheels **212**. In some embodiments, each of the one or more power cells **1050** is configured to supply electrical power to the electric motors **802**, **804**, **806**, **808** at a sufficient rate to drive movement of one or more of the wheels **212** over an estimated service life of the vehicle **100**, which may encompass a significant number of delivery missions and/or delivery trips. In such embodiments, each of the one or more power cells **1050** may be configured to supply electrical power to the motors **802**, **804**, **806**, **808** at a rate less than 80 kWh in use of the vehicle **100** or greater than 80 kWh in use of the vehicle **100**, whatever the case may be.

14

Referring now to FIG. 9, the front wheels **214**, **216** with the respective electric motors **802**, **804** integrated directly therein are depicted without a number of the features (e.g., the frame structure **200**, the power cell assembly **1000**, the rear wheels **218**, **220**, and the electric motors **806**, **808**) shown in FIG. 8. A number of components that may be included in a steering system **900** of the land vehicle **100** are shown in FIG. 9. Additionally, a number of components that may be included in a suspension system **950** of the land vehicle **100** are shown in FIG. 9.

The illustrative steering system **900** of the land vehicle **100** is configured to steer the wheels **214**, **216** based on electrical signals provided by a component (e.g., the controller **1602**) of a control system **1600** (see FIG. 16) of the vehicle **100**. In the illustrative embodiment, the steering system **900** includes a lever **902** coupled to the wheel **214**, a pin **904** coupled to the lever **902**, a tie rod **906** coupled to the pin **904**, an electric steering rack **908** coupled to the tie rod **906**, a tie rod **910** coupled to the electric steering rack **908**, a pin **912** coupled to the tie rod **910**, and a lever **914** coupled to the pin **912** and the wheel **216**. Of course, it should be appreciated that in other embodiments, the steering system **900** may include additional and/or alternative components.

The illustrative lever **902** receives the pin **904** such that a head **905** of the pin **904** extends outwardly from, and is not surrounded by, the lever **902**. The head **905** of the pin **904** is received by a circular loop **907** of the tie rod **906**. The tie rods **906**, **910** are coupled to the electric steering rack **908** opposite one another. A circular loop (not shown) of the tie rod **910** receives a head (not shown) of the pin **912**. The lever **914** receives the pin **912** such that the head of the pin **912** extends outwardly from, and is not surrounded by, the lever **914**.

In some embodiments, the electric steering rack **908** may include, or otherwise be coupled to, one or more devices capable of causing selective extension or retraction of part(s) of the steering rack **908** based on electrical signals provided by a component of the control system **1600**. In one example, the steering rack **908** may include, or otherwise be coupled to, one or more electrically-powered actuators capable of driving steering of the wheels **214**, **216** through the tie rods **906**, **910**, the pins **904**, **912**, and the levers **902**, **914**. Of course, to do so, it should be appreciated that length(s) of the one or more actuators may be varied based on the selective extension or retraction thereof. As such, it should be appreciated that the one or more actuators of the steering rack **908**, the tie rods **906**, **910**, the pins **904**, **912**, and the levers **902**, **914** may cooperate to steer the wheels **214**, **216** jointly and substantially in concert with one another, at least in some embodiments.

Although not depicted in FIG. 9, it should be appreciated that the steering system **900** may include a set of components substantially identical to those discussed above to effect steering of the rear wheels **218**, **220**, at least in some embodiments. That is, the steering system **900** may include, among other things, levers, pins, tie rods, and an electric steering rack including one or more actuators that cooperatively drive steering of the wheels **218**, **220**. Of course, those components of the steering system **900** may cooperate to steer the wheels **218**, **220** jointly and substantially in concert with another, at least in some embodiments. In some embodiments, under control by the control system **1600**, the steering system **900** may steer the front wheels **214**, **216** and the rear wheels **218**, **220** independently of one another. In other embodiments, under control by the control system

15

1600, the steering system 900 may steer the front wheels 214, 216 and the rear wheels 218, 220 substantially in concert with one another.

The illustrative suspension system 950 is configured to couple the frame structure 200 to the wheels 212 to permit some degree of relative movement between the frame structure 200 and the wheels 212 in use of the land vehicle 100. It should be appreciated that in some instances, one or more components of the steering system 900 may contribute to, or otherwise permit, some degree of relative movement between the frame structure 200 and the wheels 212. In that sense, the steering system 900 and the suspension system 950 may cooperate to permit movement between the frame structure 200 and the wheels 212 in use of the vehicle 100, at least in some embodiments.

It should be apparent that only a portion of the illustrative suspension system 950 of the land vehicle 100 that is associated with the front wheels 214, 216 is depicted in FIG. 9. Although the rear wheels 218, 220 are not shown in the figure, the description of the suspension system 950 with respect to the front wheels 214, 216 is largely intended to apply to the rear wheels 218, 220. Regardless, in the illustrative embodiment, the suspension system 950 includes a strut 952 coupled to the wheel 214, a spring 954 at least partially surrounding the strut 952, an attachment structure 956 that couples the wheel 214 to the frame structure 200, a strut 972 coupled to the wheel 216, a spring 974 at least partially surrounding the strut 972, and an attachment structure 976 that couples the wheel 216 to the frame structure 200.

The illustrative strut 952 may be coupled to the wheel 214 at one end thereof and coupled to a stationary structure of the land vehicle 100 (e.g., a portion of the frame structure 200 or a body partially defining the front cage 204 and the rear compartment 208) at an opposite end thereof. In some embodiments, the strut 952 may be adapted to resist longitudinal compression in use of the vehicle 100. In other embodiments, however, the strut 952 may be placed in tension in use of the vehicle 100. In any case, the spring 954 receives the strut 952 such that the spring 954 may be positioned between the strut 952 and the stationary structure mentioned above. In some embodiments, the strut 952 and the spring 954 may cooperatively dampen forces applied at the wheel 214 in use of the vehicle 100 such that lower magnitude forces are reacted to the stationary structure and/or the frame structure 200 to improve ride quality and reduce vibration.

The illustrative attachment structure 956 includes an arm 958, grooved links 964, 966 pivotally coupled to the arm 958, and a mount bracket 968 affixed to the arm 958. The arm 958 is coupled to the wheel 214 at an end 960 thereof and to the mount bracket 968 at an opposite end 962 thereof. The illustrative arm 958 extends between the ends 960, 962 such that the arm 958 generally defines a J-shape. The grooved links 964, 966 each generally define a V-shape and are configured to contact and/or couple to the frame structure 200, at least in some embodiments. The mount bracket 968 is also configured to contact and/or couple to the frame structure 200. In some embodiments, the grooved links 964, 966 and the mount bracket 968 may interface with the rail 230 of the frame structure 200 at a location arranged forward of the carrier 222 in the longitudinal direction 210.

The illustrative strut 972 may be coupled to the wheel 216 at one end thereof and coupled to a stationary structure of the land vehicle 100 (e.g., a portion of the frame structure 200 or a body partially defining the front cage 204 and the rear compartment 208) at an opposite end thereof. In some

16

embodiments, the strut 972 may be adapted to resist longitudinal compression in use of the vehicle 100. In other embodiments, however, the strut 972 may be placed in tension in use of the vehicle 100. In any case, the spring 974 receives the strut 972 such that the spring 974 may be positioned between the strut 972 and the stationary structure mentioned above. In some embodiments, the strut 972 and the spring 974 may cooperatively dampen forces applied at the wheel 216 in use of the vehicle 100 such that lower magnitude forces are reacted to the stationary structure and/or the frame structure 200 to improve ride quality and reduce vibration.

The illustrative attachment structure 976 includes an arm 978, grooved links 984, 986 pivotally coupled to the arm 978, and a mount bracket 988 affixed to the arm 978. The arm 978 is coupled to the wheel 216 at an end 980 thereof and to the mount bracket 988 at an opposite end 982 thereof. The illustrative arm 978 extends between the ends 980, 982 such that the arm 978 generally defines a J-shape. The grooved links 984, 986 each generally define a V-shape and are configured to contact and/or couple to the frame structure 200, at least in some embodiments. The mount bracket 988 is also configured to contact and/or couple to the frame structure 200. In some embodiments, the grooved links 984, 986 and the mount bracket 988 may interface with the rail 240 of the frame structure 200 at a location arranged forward of the carrier 222 in the longitudinal direction 210.

Of course, it should be appreciated that in some embodiments, the suspension system 950 may include additional and/or alternative components. For example, the suspension system 950 may include one or more shock absorbers, springs, linkages, axles, rods, dampers, torsion bars, beams, or the like. Furthermore, in some embodiments, it should be appreciated that the suspension system 950 may include a first set of components for the front wheels 214, 216 and a second set of components for the rear wheels 218, 220, and that the first and second sets of components may not be identical.

Referring now to FIG. 10, the illustrative power cell assembly 1000 includes a bottom tray 1010, a casing 1020 supported by the bottom tray 1010, an intermediate tray 1040 at least partially positioned in the casing 1020, the power cells 1050, and a top cover 1060. When the power cell assembly 1000 is assembled and held by the carrier 222, the casing 1020, the intermediate tray 1040, and the power cells 1050 are arranged between the bottom tray 1010 and the top cover 1060. Additionally, when the power cell assembly 1000 is assembled and held by the carrier 222, the bottom tray 1010 defines the lowest point of the assembly 1000 (i.e., in a vertical direction) relative to a surface underlying the vehicle 100 and the top cover 1060 defines the highest point of the assembly 1000 relative to the surface.

In the illustrative embodiment, the casing 1020 is formed to include the connection panel 600. The illustrative casing 1020 houses cooling plates 1030 in an interior cavity 1022 thereof. Each of the cooling plates 1030 is embodied as, or otherwise includes, any device or collection of devices capable of dissipating heat generated by the power cells 1050 to cool the assembly 1000 in use of the vehicle 100. In some embodiments, each of the cooling plates 1030 may be embodied as, or otherwise include, a liquid cold plate or the like. Furthermore, in some embodiments, each of the cooling plates 1030 may be utilized in conjunction with one or more heat exchangers to transfer heat from heated liquid (i.e., liquid that receives heat from the power cells 1050) to a fluid medium (e.g., air). Further still, in some embodiments, one or more fans may be utilized in conjunction with

the cooling plates **1030** and the one or more heat exchangers to effect heat transfer from the power cells **1050** to a fluid medium to cool the assembly in use of the vehicle **100**.

In the illustrative embodiment, the power cells **1050** are at least partially positioned in an interior space **1042** defined by the intermediate tray **1040**. When the power cell assembly **1000** is assembled, the power cells **1050** are at least partially positioned in the intermediate tray **1040** and the intermediate tray **1040** is at least partially positioned in the casing **1020**. Accordingly, when the power cell assembly **1000** is assembled, the top cover **1060** cooperates with the bottom tray **1010**, the casing **1020**, and the intermediate tray **1040** to at least partially enclose the power cells **1050**.

In some embodiments, each of the power cells **1050** may be included in a battery pack module (e.g., one of the battery pack modules **2010**). Additionally, in some embodiments, the power cell assembly **1000** may include n battery pack modules, where n is an integer equal to or greater than one. It should be appreciated that a greater number of battery pack modules included in the power cell assembly **1000** provides increased power capacity during operation of the illustrative vehicle **100**. Therefore, when the vehicle **100** requires additional power capacity to complete one or more extended routes, additional battery pack modules may provide sufficient power as the vehicle **100** travels the extended route(s). However, when the vehicle **100** completes one or more routes of decreased duration, the vehicle **100** may not require the power provided by the power capacity of the additional battery pack modules.

Often times, the vehicle **100** may execute delivery routes of different durations. For example, the vehicle **100** may execute delivery routes of increased duration during the holiday season as the amount of stops per delivery route is significantly increased due to the significant increase in packages that are required to be delivered during the holiday season. In such an example, the duration of the delivery routes executed by the vehicle **100** may be significantly increased in order for the increased amount of packages to be delivered in a timely manner. However, during other times of the year that are outside of the holiday season, the duration of the delivery routes executed by the vehicle **100** may be significantly decreased from the duration of the delivery routes executed during the holiday season due to a significant decrease in the amount of packages that are required to be delivered.

Delivery routes of increased duration require that the vehicle **100** have an increased power capacity in order for the vehicle **100** to have sufficient power to complete the delivery routes of increased duration. In doing so, the vehicle **100** may require that the power cell assembly **1000** include increased battery pack modules in order to have the increased power capacity such that the vehicle **100** has sufficient power to complete the delivery routes of increased duration. Although the increased battery pack modules increase the weight of the vehicle **100**, increased weight may be necessary to have the power capacity to execute the routes of increased duration.

Rather than having different power cell assemblies with different quantities of battery pack modules to be used for the execution of different duration of routes, the power cell assembly **1000** may be modular such that different quantities of battery pack modules may be added or removed from the power cell assembly **1000** to customize the power capacity of the vehicle **100** to the duration of the route(s) expected to be executed. In doing so, battery pack modules may be added to the power cell assembly **1000** when the vehicle **100** is executing routes of increased duration. Conversely, bat-

tery pack modules may be removed from the power cell assembly **1000** when the vehicle **100** is executing routes of decreased duration to avoid unnecessarily increasing the weight of the vehicle **100**. Further discussion of a modular system (e.g., the modular system **2000**) including various quantities of battery pack modules (e.g., modules **2010**) is provided below with reference to FIGS. **19** and **20**.

Referring now to FIGS. **11** and **12**, according to one embodiment of the present disclosure, the land vehicle **100** includes at least one brake assembly **1100**. The brake assembly **1100** is illustratively coupled to one of the wheels **212**. It should be appreciated that in some embodiments, the brake assembly **1100** is coupled to each one of the wheels **212** such that the land vehicle **100** includes a total of four brake assemblies **1100**. In other embodiments, as described in greater detail below with reference to FIG. **13**, the land vehicle **100** may include a brake system **1300** coupled to each one of the wheels **212** that includes multiple braking devices.

In the illustrative embodiment, the brake assembly **1100** includes a disc or rotor **1102** configured for rotation about a rotational axis **1104**. The illustrative disc **1102** is coupled to the wheel **212** for common rotation therewith about the axis **1104**, at least in some embodiments. Additionally, in some embodiments, the disc **1102** may be integrally formed with the wheel **212**. At an inner diameter **1106** thereof, the disc **1102** is formed to include notches **1108** that are defined between circumferentially adjacent teeth **1109** of the disc **1102**.

The illustrative brake assembly **1100** includes a braking device **1210** configured to contact an outer face **1112** of the disc **1102** to resist rotation of the wheel **212** about the axis **1104** in use of the land vehicle **100**. In the illustrative embodiment, the braking device **1210** is embodied as, or otherwise includes, a disc brake assembly. The braking device **1210** includes a caliper **1220**, one or more pistons **1230**, and brake pads **1250**. In addition, the braking device **1210** may include a number of components not depicted in the Figures, such as one or more seals, dust boots, bleeder devices, anti-rattle clips, brake shoes, linings, locating pins, mounting pins, bearings, retainers, caps, anchor plates, mounting plates, spindles, or the like.

The illustrative caliper **1220** of the braking device **1210** is embodied as, or otherwise includes, a housing **1222** of the braking device **1210** that at least partially houses a number of components of the braking device **1210**, such as the pistons **1230**, for example. In the illustrative embodiment, the braking device **1210** includes only one caliper **1220**. Furthermore, in the illustrative embodiment, the braking device **1210** includes six pistons **1232**, **1234**, **1236**, **1238**, **1240**, **1242** that are at least partially housed by the only one caliper **1220**. However, in other embodiments, it should be appreciated that the braking device **1210** may include only one piston. The illustrative braking device **1210** also includes a pair of brake pads **1252**, **1254** that are configured to contact opposite sides (i.e., outer and inner sides) of the disc **1102** to resist rotation of the wheel **212** about the axis **1104** in use of the vehicle **100**.

The caliper **1220** of the braking device **1210** may have a variety of constructions. In the illustrative example, the caliper **1220** has a two-piece construction in which parts **1224**, **1226** are secured to one another in close proximity to an end **1228** of the caliper **1220** by fasteners **1212**. In the illustrative example, the parts **1224**, **1226** are spaced apart from one another in close proximity to an end **1229** that is arranged opposite the end **1228**. The brake pads **1252**, **1254** are coupled to inner sides of the parts **1224**, **1226** and

19

arranged in confronting relation with one another to permit contact between the brake pads **1252**, **1254** and the disc **1102** when the disc **1102** is positioned between the pads **1252**, **1254** adjacent the end **1229**. In the illustrative example, a sensor **1260** is coupled to the part **1224** of the caliper **1220** at an outer periphery thereof. The sensor **1260** is configured to provide a signal indicative of wear or degradation of the brake pads **1252**, **1254** in use of the vehicle **100**, at least in some embodiments. In other examples, however, the caliper **1220** may have another suitable construction and be formed from another suitable number of parts.

In some embodiments, the wheel **212** illustratively depicted in FIG. **11** is supported for rotation about the rotational axis **1104** by a bearing **1120**. In such embodiments, a braking sensor **1122** is integrated into the bearing **1120**. The illustrative braking sensor **1122** is configured to provide a signal to the control system **1600** indicative of a rotational speed of the wheel **212** in use of the vehicle **100**, at least in some embodiments. The signal provided by the braking sensor **1122** may be utilized to control one or more components of an anti-lock brake system (not shown) included in the vehicle **100**.

In some embodiments, fluid connections **1124** are located radially between the rotational axis **1104** and the inner diameter **1106** of the disc **1102**. The fluid connections **1124** may be utilized to circulate cooling fluid delivered from a cooling fluid source (not shown) through the wheel **212** to cool the wheel **212** in use of the vehicle **100**, at least in some embodiments. Each of the fluid connections **1124** may be embodied as, or otherwise include, a projection **1126** that extends outwardly away from an interior **1128** of the wheel **212** and parallel to the rotational axis **1104** such that the fluid connections **1124** are not generally not recessed. In some embodiments, a connector **1130** is located in the interior **1128** of the wheel **212** adjacent the fluid connections **1124**. The connector **1130** may be configured to interface with a single low voltage cable **1132** that is at least partially positioned in the interior **1128**.

Referring now to FIG. **13**, as mentioned above, the illustrative brake system **1300** includes, among other things, a disc **1302**, a braking device **1310**, a braking device **1330**, and a braking device **1350**. It should be appreciated that any one of the braking devices **1310**, **1330**, **1350** may be activated to resist rotation of the wheel **212** in use of the vehicle **100** and thereby provide redundant braking means. Additionally, it should be appreciated that the multiple braking devices **1310**, **1330**, **1350** may be activated in combination with one another to cooperatively resist rotation of the wheel **212** in use of the vehicle **100**. In any case, in some embodiments, the brake system **1300** may be coupled to the wheel **212** in lieu of the brake assembly **1100**. Furthermore, in some embodiments, the brake system **1300** may be coupled to each one of the front wheels **214**, **216** and the rear wheels **218**, **220** such that the vehicle **100** includes four total brake systems **1300**.

In the illustrative embodiment, the disc or rotor **1302** of the brake system **1300** is configured for rotation about a rotational axis **1303**. The illustrative disc **1302** is coupled to the wheel **212** for common rotation therewith about the axis **1303**, at least in some embodiments. Additionally, in some embodiments, the disc **1302** may be integrally formed with the wheel **212**. At an inner diameter **1305** thereof, the disc **1302** is formed to include the notches **1304** that are defined between circumferentially adjacent teeth **1306** of the disc **1302**.

The illustrative braking device **1310** is configured to contact the outer face **1308** of the disc **1302** to resist rotation

20

of the wheel **212** about the axis **1303** in use of the land vehicle **100**. In the illustrative embodiment, the braking device **1310** is embodied as, or otherwise includes, a disc brake assembly. The braking device **1310** includes a caliper **1312**, one or more pistons **1314**, and brake pads **1324**. In addition, the braking device **1310** may include a number of components not depicted in the Figures, such as one or more seals, dust boots, bleeder devices, anti-rattle clips, brake shoes, linings, locating pins, mounting pins, bearings, retainers, caps, anchor plates, mounting plates, spindles, or the like.

The illustrative caliper **1312** of the braking device **1310** is embodied as, or otherwise includes, a housing **1313** of the braking device **1310** that at least partially houses a number of components of the braking device **1310**, such as the piston(s) **1314**, for example. In the illustrative embodiment, the braking device **1310** includes only one caliper **1312**. Furthermore, in the illustrative embodiment, the braking device **1310** includes six pistons (only pistons **1316**, **1318**, **1320** are shown in FIG. **13**) that are at least partially housed by the only one caliper **1312**. However, in some embodiments, the braking device **1310** may include only one piston (e.g., one piston **1314**). The illustrative braking device **1310** also includes a pair of brake pads (only brake pad **1324** is shown) that are configured to contact opposite sides (i.e., outer and inner sides) of the disc **1302** to resist rotation of the wheel **212** about the axis **1303** in use of the vehicle **100**.

The caliper **1312** of the braking device **1310** may have a variety of constructions. In the illustrative example, the caliper **1312** has a two-piece construction in which two parts (only part **1326** is shown in FIG. **13**) are secured to one another in close proximity to an end **1328** of the caliper **1312** by fasteners **1327**. In the illustrative example, the parts of the caliper **1312** are spaced apart from one another in close proximity to an end **1329** that is arranged opposite the end **1328**. The brake pads are coupled to inner sides of the parts and arranged in confronting relation with one another to permit contact between the brake pads and the disc **1302** when the disc **1302** is positioned between the pads adjacent the end **1329**. In the illustrative example, a sensor **1380** is coupled to the part **1326** of the caliper **1312** at an outer periphery thereof. The sensor **1380** is configured to provide a signal indicative of wear or degradation of the brake pads in use of the vehicle **100**, at least in some embodiments. In other examples, however, the caliper **1312** may have another suitable construction and be formed from another suitable number of parts.

In some embodiments, the wheel **212** illustratively depicted in FIG. **13** is supported for rotation about the rotational axis **1303** by a bearing **1360**. In such embodiments, a braking sensor **1362** is integrated into the bearing **1360**. The illustrative braking sensor **1362** is configured to provide a signal to the control system **1600** indicative of a rotational speed of the wheel **212** in use of the vehicle **100**, at least in some embodiments. The signal provided by the braking sensor **1362** may be utilized to control one or more components of an anti-lock brake system (not shown) included in the vehicle **100**.

In some embodiments, fluid connections **1364** are located radially between the rotational axis **1303** and the inner diameter **1305** of the disc **1302**. The fluid connections **1364** may be utilized to circulate cooling fluid delivered from a cooling fluid source (not shown) through the wheel **212** to cool the wheel **212** in use of the vehicle **100**, at least in some embodiments. Each of the fluid connections **1364** may be embodied as, or otherwise include, a projection **1366** that extends outwardly away from an interior **1368** of the wheel

212 and parallel to the rotational axis **1303** such that the fluid connections **1364** are not generally not recessed. In some embodiments, a connector **1370** is located in the interior **1368** of the wheel **212** adjacent the fluid connections **1364**. The connector **1370** may be configured to interface with a single low voltage cable **1372** that is at least partially positioned in the interior **1368**.

Referring now to FIG. **14**, the braking devices **1330**, **1350** are shown in greater detail with other elements (e.g., the wheel **212**, the disc **1302**, the braking device **1310**) omitted for the sake of simplicity. In the illustrative embodiment, the braking device **1330** is an electronic parking brake mechanism. Additionally, in the illustrative embodiment, the braking device **1350** is a parking pawl mechanism. It should be appreciated that in use of the vehicle **100**, the braking devices **1330**, **1350** may be operated by the control system **1600** independently of one another, as further discussed below.

As mentioned above, the illustrative electronic parking brake mechanism **1330** is configured to contact the outer face **1308** of the disc **1302** to resist rotation of the wheel **212** about the axis **1303** in use of the vehicle **100**. As best seen in FIG. **13**, the parking brake mechanism **1330** is circumferentially spaced from the braking device **1310** about the disc **1302** and the axis **1303**. More specifically, the parking brake mechanism **1330** and the braking device **1310** are circumferentially spaced about 180 degrees from one another about the disc **1302** and the axis **1303**. In the illustrative arrangement, among other components, the fluid connections **1364** and the connector **1370** are circumferentially located between the parking brake mechanism **1330** and the braking device **1310**.

At least in some embodiments, the illustrative parking brake mechanism **1330** includes a number of features similar to corresponding features of the braking device **1310**. In such embodiments, the parking brake mechanism **1330** includes a housing **1432**, one or more actuators or pistons **1438** at least partially housed by the housing **1432**, and brake pads **1440**, **1442** supported by the housing **1432** that are configured to contact opposite sides (i.e., outer and inner sides) of the disc **1302** to resist rotation of the wheel **212** about the axis **1303** in use of the vehicle **100**. In addition, the parking brake mechanism **1330** may include a number of components not depicted in the Figures, such as one or more seals, dust boots, bleeder devices, anti-rattle clips, brake shoes, linings, locating pins, mounting pins, bearings, retainers, caps, anchor plates, mounting plates, spindles, or the like.

The housing **1432** of the parking brake mechanism **1330** may have a variety of constructions. In some embodiments, the housing **1432** of the parking brake mechanism **1330** may have a two-piece construction. In the illustrative example, the illustrative housing **1432** includes two parts **1434**, **1436** that are secured to one another in close proximity to an end **1438** of the housing **1432**. In the illustrative example, the parts **1434**, **1436** of the housing **1432** are spaced apart from one another in close proximity to an end **1439** that is arranged opposite the end **1438**. The brake pads **1440**, **1442** are coupled to inner sides of the parts **1434**, **1436** and arranged in confronting relation with one another to permit contact between the brake pads **1440**, **1442** and the disc **1302** when the disc **1302** is positioned between the pads adjacent the end **1439**. In the illustrative embodiment, a sensor **1444** is coupled to the half **1434** of the housing **1432** at an outer periphery thereof. The sensor **1444** is configured to provide a signal indicative of wear or degradation of the brake pads **1440**, **1442** in use of the vehicle **100**, at least in

some embodiments. Of course, it should be appreciated that in other embodiments, the housing **1432** may have another suitable construction and be formed from another suitable number of parts.

As mentioned above, the illustrative parking pawl mechanism **1350** is configured to contact one or more teeth **1306** of the disc **1302** to resist rotation of the wheel **212** in use of the vehicle **100**. Unlike some conventional devices, the illustrative parking pawl mechanism **1350** is not fitted to, and does not interact with, a transmission of the vehicle **100**, since the vehicle **100** omits one or more transmissions as indicated above. Thus, unlike some conventional devices, the illustrative parking pawl mechanism **1350** does not lock an output shaft of a transmission to prevent rotation of the wheel **212**.

In the illustrative embodiment, the parking pawl mechanism **1350** includes a pawl or pin **1452** at least partially housed by a housing **1456**. The pawl **1452** may be sized to contact one or more of the teeth **1306** in use of the mechanism **1350**. Additionally, in some embodiments, the parking pawl mechanism **1350** may include one or more actuators **1454** at least partially housed by the housing **1456**. The one or more actuators **1454** are configured to drive movement (e.g., extension) of the pawl **1452** relative to the housing **1456** to contact one or more of the teeth **1306** and thereby resist rotation of the wheel **212**, at least in some embodiments. Additionally, in such embodiments, the one or more actuators **1454** are configured to drive movement (i.e., retraction) of the pawl **1452** relative to the housing **1456** to release the pawl **1452** and thereby permit rotation of the wheel **212**.

Referring now to FIG. **15**, the illustrative parking pawl mechanism **1350** includes a receptacle **1500** disposed at an end **1502** of the mechanism **1350**. The receptacle **1500** is sized to receive a drive or release (e.g., a square drive or release) to permit manual release of the parking pawl mechanism **1350** in use of the vehicle **100**. Of course, it should be appreciated that manual release of the mechanism **1350** may be desirable in the event that automatic release of the pawl **1452** is not attainable. Furthermore, it should be appreciated that although the receptacle **1500** is depicted in FIG. **15** as having a square shape, in other embodiments, the receptacle **1500** may take the shape of other suitable geometric forms. In such embodiments, the shape and size of the receptacle **1500** may be dependent upon the shape and size of the corresponding drive or release.

Referring now to FIG. **16**, the illustrative control system **1600** is utilized to control operation of various components and/or systems of the land vehicle **100**. The control system **1600** illustratively includes a controller **1602** having a processor **1604** and a memory device **1606** coupled to the processor **1604**. In the illustrative embodiment, the controller **1602** is communicatively coupled to (i) the one or suspension systems **950**, (ii) the one or more power cell assemblies **1000**, (iii) the brake systems **1300**, (iv) the electric motors **800**, (v) a dashboard **1636**, and (vi) the one or more steering systems **900**.

The processor **1604** may be embodied as, or otherwise include, any type of processor, controller, or other compute circuit capable of performing various tasks such as compute functions and/or controlling the functions of the land vehicle **100** and subcomponents or subsystems thereof. For example, the processor **1604** may be embodied as a single or multi-core processor(s), a microcontroller, or other processor or processing/controlling circuit. In some embodiments, the processor **1604** may be embodied as, include, or be coupled to an FPGA, an application specific integrated

circuit (ASIC), reconfigurable hardware or hardware circuitry, or other specialized hardware to facilitate performance of the functions described herein. Additionally, in some embodiments, the processor **1604** may be embodied as, or otherwise include, a high-power processor, an accelerator co-processor, or a storage controller. In some embodiments still, the processor **1604** may include more than one processor, controller, or compute circuit.

The memory device **1606** may be embodied as any type of volatile (e.g., dynamic random access memory (DRAM), etc.) or non-volatile memory capable of storing data therein. Volatile memory may be embodied as a storage medium that requires power to maintain the state of data stored by the medium. Non-limiting examples of volatile memory may include various types of random access memory (RAM), such as dynamic random access memory (DRAM) or static random access memory (SRAM). One particular type of DRAM that may be used in a memory module is synchronous dynamic random access memory (SDRAM). In particular embodiments, DRAM of a memory component may comply with a standard promulgated by JEDEC, such as JESD79F for DDR SDRAM, JESD79-2F for DDR2 SDRAM, JESD79-3F for DDR3 SDRAM, JESD79-4A for DDR4 SDRAM, JESD209 for Low Power DDR (LPDDR), JESD209-2 for LPDDR2, JESD209-3 for LPDDR3, and JESD209-4 for LPDDR4 (these standards are available at www.jedec.org). Such standards (and similar standards) may be referred to as DDR-based standards and communication interfaces of the storage devices that implement such standards may be referred to as DDR-based interfaces.

In some embodiments, the memory device **1606** may be embodied as a block addressable memory, such as those based on NAND or NOR technologies. The memory device **1606** may also include future generation nonvolatile devices, such as a three dimensional crosspoint memory device (e.g., Intel 3D XPoint™ memory), or other byte addressable write-in-place nonvolatile memory devices. In some embodiments, the memory device **1606** may be embodied as, or may otherwise include, chalcogenide glass, multi-threshold level NAND flash memory, NOR flash memory, single or multi-level Phase Change Memory (PCM), a resistive memory, nanowire memory, ferroelectric transistor random access memory (FeTRAM), anti-ferroelectric memory, magnetoresistive random access memory (MRAM) memory that incorporates memristor technology, resistive memory including the metal oxide base, the oxygen vacancy base and the conductive bridge Random Access Memory (CB-RAM), or spin transfer torque (STT)-MRAM, a spintronic magnetic junction memory based device, a magnetic tunneling junction (MTJ) based device, a DW (Domain Wall) and SOT (Spin Orbit Transfer) based device, a thyristor based memory device, or a combination of any of the above, or other memory. The memory device may refer to the die itself and/or to a packaged memory product. In some embodiments, 3D crosspoint memory (e.g., Intel 3D XPoint™ memory) may comprise a transistor-less stackable cross point architecture in which memory cells sit at the intersection of word lines and bit lines and are individually addressable and in which bit storage is based on a change in bulk resistance.

In the illustrative embodiment, the controller **1602** is communicatively coupled to one or more suspension system devices **1608** of the suspension systems **950**. The suspension system devices **1608** are illustratively embodied as, or otherwise include, any devices of the suspension systems **950** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the

controller **1602** to facilitate operation and control of the suspension systems **950**. In some embodiments, the suspension system devices **1608** include one or more sensors, switches, actuators, and/or solenoids, among other features. Of course, it should be appreciated that in other embodiments, the suspension system devices **1608** may include other suitable components.

In the illustrative embodiment, the controller **1602** is communicatively coupled to one or more power cell devices **1610** of the power cell assembly **1000**. The power cell devices **1610** are illustratively embodied as, or otherwise include, any devices of the power cell assembly **1000** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the power cell assembly **1000**. In some embodiments, the power cell devices **1610** include one or more sensors, switches, actuators, and/or solenoids, among other things. Of course, it should be appreciated that in other embodiments, the power cell devices **1610** may include other suitable components.

In the illustrative embodiment of FIG. 16, the controller **1602** is depicted as being communicatively coupled to the electric or hub motors **800**, which include the motors **802**, **804**, **806**, **808** as discussed above. It should be appreciated that each of the motors **802**, **804**, **806**, **808** may be communicatively coupled to the controller **1602** to permit independent operation and control thereof by the controller **1602**, at least in some embodiments. In such embodiments, it should further be appreciated that various electrical devices (e.g., sensors, switches, actuators, solenoids, etc.) of each of the motors **802**, **804**, **806**, **808** are also communicatively coupled to the controller **1602**.

In the illustrative embodiment, the controller **1602** is communicatively coupled to a first brake system **1300** (e.g., the brake system **1300** coupled to the front wheel **214**) of the land vehicle **100**. More specifically, the controller **1602** is communicatively coupled to one or more disc brake assembly devices **1612**, one or more parking brake devices **1614**, and one or more parking pawl devices **1616** of the first brake system **1300**. The one or more disc brake assembly devices **1612** are included in, or otherwise associated with, the braking device **1310** of the brake system **1300**. The one or more disc brake assembly devices **1612** are illustratively embodied as, or otherwise include, any devices of the braking device **1310** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1310**. The one or more parking brake devices **1614** are included in, or otherwise associated with, the braking device **1330** of the brake system **1300**. The one or more parking brakes devices **1614** are illustratively embodied as, or otherwise include, any devices of the braking device **1330** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1330**. The one or more parking pawl devices **1616** are included in, or otherwise associated with, the braking device **1350** of the brake system **1300**. The one or more parking pawl devices **1616** are illustratively embodied as, or otherwise include, any devices of the braking device **1350** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1350**. In some embodiments, each of the devices **1612**, **1614**, **1616** may include one or more sensors, switches, actuators, and/or solenoids, among other things. Of course, it should be appreciated that in other

25

embodiments, each of the devices **1612**, **1614**, **1616** may include other suitable components.

In the illustrative embodiment, the controller **1602** is communicatively coupled to a second brake system **1300** (e.g., the brake system **1300** coupled to the front wheel **216**) of the land vehicle **100**. More specifically, the controller **1602** is communicatively coupled to one or more disc brake assembly devices **1618**, one or more parking brake devices **1620**, and one or more parking pawl devices **1622** of the second brake system **1300**. The one or more disc brake assembly devices **1618** are included in, or otherwise associated with, the braking device **1310** of the brake system **1300**. The one or more disc brake assembly devices **1618** are illustratively embodied as, or otherwise include, any devices of the braking device **1310** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1310**. The one or more parking brake devices **1620** are included in, or otherwise associated with, the braking device **1330** of the brake system **1300**. The one or more parking brakes devices **1620** are illustratively embodied as, or otherwise include, any devices of the braking device **1330** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1330**. The one or more parking pawl devices **1622** are included in, or otherwise associated with, the braking device **1350** of the brake system **1300**. The one or more parking pawl devices **1622** are illustratively embodied as, or otherwise include, any devices of the braking device **1350** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1350**. In some embodiments, each of the devices **1618**, **1620**, **1622** may include one or more sensors, switches, actuators, and/or solenoids, among other things. Of course, it should be appreciated that in other embodiments, each of the devices **1618**, **1620**, **1622** may include other suitable components.

In the illustrative embodiment, the controller **1602** is communicatively coupled to a third brake system **1300** (e.g., the brake system **1300** coupled to the rear wheel **218**) of the land vehicle **100**. More specifically, the controller **1602** is communicatively coupled to one or more disc brake assembly devices **1624**, one or more parking brake devices **1626**, and one or more parking pawl devices **1628** of the third brake system **1300**. The one or more disc brake assembly devices **1624** are included in, or otherwise associated with, the braking device **1310** of the brake system **1300**. The one or more disc brake assembly devices **1624** are illustratively embodied as, or otherwise include, any devices of the braking device **1310** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1310**. The one or more parking brake devices **1626** are included in, or otherwise associated with, the braking device **1330** of the brake system **1300**. The one or more parking brakes devices **1626** are illustratively embodied as, or otherwise include, any devices of the braking device **1330** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1330**. The one or more parking pawl devices **1628** are included in, or otherwise associated with, the braking device **1350** of the brake system **1300**. The one or more parking pawl devices **1628** are illustratively embodied as, or otherwise include, any devices of the

26

braking device **1350** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1350**. In some embodiments, each of the devices **1624**, **1626**, and **1628** may include one or more sensors, switches, actuators, and/or solenoids, among other things. Of course, it should be appreciated that in other embodiments, each of the devices **1624**, **1626**, and **1628** may include other suitable components.

In the illustrative embodiment, the controller **1602** is communicatively coupled to a fourth brake system **1300** (e.g., the brake system **1300** coupled to the rear wheel **220**) of the land vehicle **100**. More specifically, the controller **1602** is communicatively coupled to one or more disc brake assembly devices **1630**, one or more parking brake devices **1632**, and one or more parking pawl devices **1634** of the fourth brake system **1300**. The one or more disc brake assembly devices **1630** are included in, or otherwise associated with, the braking device **1310** of the brake system **1300**. The one or more disc brake assembly devices **1630** are illustratively embodied as, or otherwise include, any devices of the braking device **1310** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1310**. The one or more parking brake devices **1632** are included in, or otherwise associated with, the braking device **1330** of the brake system **1300**. The one or more parking brakes devices **1632** are illustratively embodied as, or otherwise include, any devices of the braking device **1330** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1330**. The one or more parking pawl devices **1634** are included in, or otherwise associated with, the braking device **1350** of the brake system **1300**. The one or more parking pawl devices **1634** are illustratively embodied as, or otherwise include, any devices of the braking device **1350** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the braking device **1350**. In some embodiments, each of the devices **1630**, **1632**, and **1634** may include one or more sensors, switches, actuators, and/or solenoids, among other things. Of course, it should be appreciated that in other embodiments, each of the devices **1630**, **1632**, and **1634** may include other suitable components.

The illustrative controller **1602** is communicatively coupled to the dashboard **1636** as indicated above. The dashboard **1636** includes a user interface **1638** and a display **1640** coupled to the user interface **1638**. The user interface **1638** is configured to provide various inputs to the control system **1600** based on various actions, which may include actions performed by an operator. The display **1640** is configured to output or display various indications, messages, and/or prompts to an operator, which may be generated by the control system **1600**. It should be appreciated that in some embodiments, the user interface **1638** and the display **1640** are positioned in the operator cabin **206**.

In the illustrative embodiment, the controller **1602** is communicatively coupled to one or more steering system devices **1642** of the steering systems **900**. The steering system devices **1642** are illustratively embodied as, or otherwise include, any devices of the steering systems **900** that are capable of providing electrical signals to the controller **1602** and/or receiving electrical signals from the controller **1602** to facilitate operation and control of the

steering systems **900**. In some embodiments, the steering system devices **1642** include one or more sensors, switches, actuators, and/or solenoids, among other features. Of course, it should be appreciated that in other embodiments, the suspension system devices **1642** may include other suitable components.

Referring now to FIG. 17, an illustrative method **1700** of operating the land vehicle **100** may be embodied as, or otherwise include, a set of instructions that are executable by the control system **1600** to control operation of the vehicle **100**. The method **1700** corresponds to, or is otherwise associated with, performance of the blocks described below in the illustrative sequence of FIG. 17. It should be appreciated, however, that the method **1700** may be performed in one or more sequences different from the illustrative sequence. Furthermore, in some embodiments, it should be appreciated that one or more blocks of the illustrative method **1700** may be performed manually by a user or operator of the vehicle **100**.

The illustrative method **1700** begins with block **1702**. In block **1702**, the controller **1602** (or an operator) operates, or directs operation of, the hub motors **800** independently of one another to permit independent rotation of the wheels **212**. It should be appreciated that in some embodiments, performance of block **1702** includes, or is otherwise associated with, driving rotation of the front wheels **214**, **216** and the rear wheels **218**, **220** independently via the hub motors **800** in one or more four-wheel drive mode(s) of the vehicle **100**. In some embodiments, to perform block **1702**, the controller **1602** (or an operator) performs block **1703**. In block **1703**, the controller **1602** (or an operator) selectively transitions between a two-wheel drive operational mode and a four-wheel drive operational mode of the vehicle **100**. In one example, the two-wheel drive operational mode may be a mode in which rotation of only the front wheels **214**, **216** is driven by the hub motors **800**. In another example, the two-wheel drive operational mode may be a mode in which rotation of only the rear wheels **218**, **220** is driven by the hub motors **800**. In some embodiments, the selective transition between the two-wheel drive operational mode and the four-wheel drive operational mode in block **1703** may be dependent upon the terrain or the grade of the surface underlying the vehicle **100**. Regardless, following completion of blocks **1702** and **1703**, the method **1700** subsequently proceeds to block **1704**.

In block **1704** of the illustrative method **1700**, the controller **1602** (or an operator) steers the wheels **212** to adjust an orientation of the vehicle **100**. To do so, in block **1706**, the controller **1602** (or an operator) turns the vehicle **100** 360 degrees in a circular path. To perform block **1706**, in the illustrative embodiment, the controller **1602** (or an operator) performs block **1708**. In block **1708**, the controller **1602** (or an operator) turns the vehicle **100** 360 degrees in the circular path without shifting the land vehicle (e.g., using a shift selector disposed in the operator cabin **206**) to a reverse operating range.

Referring now to FIG. 18, an illustrative method **1800** of operating the land vehicle **100** may be embodied as, or otherwise include, a set of instructions that are executable by the control system **1600** to control operation of the vehicle **100**. The method **1800** corresponds to, or is otherwise associated with, performance of the blocks described below in the illustrative sequence of FIG. 18. It should be appreciated, however, that the method **1800** may be performed in one or more sequences different from the illustrative sequence. Furthermore, in some embodiments, it should be

appreciated that one or more blocks of the illustrative method **1800** may be performed manually by a user or operator of the vehicle **100**.

The illustrative method **1800** begins with block **1802**. In block **1802**, the controller **1602** (or an operator) operates, or directs operation of, the land vehicle **100** in a park operating range. From block **1802**, the method **1800** subsequently proceeds to block **1804**.

In block **1804** of the illustrative method **1800**, the controller **1602** (or an operator) operates the brake systems **1300** of the vehicle **100** when the vehicle **100** is in the park operating range. To do so, in the illustrative embodiment, the controller **1602** (or an operator) performs at least one or both of blocks **1806** and **1808**. In block **1806**, the controller **1602** (or an operator) selectively activates or engages one or more parking brake mechanisms **1330** and one or more parking pawl mechanisms **1350**. In block **1808**, the controller **1602** (or an operator) activates or engages the one or more parking brake mechanisms **1330** and the one or more parking pawl mechanisms **1350** contemporaneously. In any case, from block **1804**, the method **1800** subsequently proceeds to block **1810**.

In block **1810** of the illustrative method **1800**, the controller **1602** (or an operator) releases, or directs the release of, one or more parking pawl mechanisms **1350** manually subsequent to activation of the one or more mechanisms **1350**.

Referring now to FIG. 19, an illustrative carriage **1900** may be supported by, coupled to, or integrally formed with, the frame structure **200** of the vehicle **100**. In some embodiments, the carriage **1900** may be integrated into, or otherwise form a portion of, the carrier **222**. Furthermore, in some embodiments, the carriage **1900** may be supported by the rails **230**, **240** such that the carriage **1900** extends longitudinally along the rails **230**, **240** and laterally between the rails **230**, **240**.

The carriage **1900** illustratively includes a plurality of compartments **1902**, **1904**, **1906**, **1908**, **1910**, **1912**. Although six compartments are depicted in FIG. 19, it should be appreciated that the number of compartments may vary depending on the number of battery pack modules **2010** (see FIG. 20) included in a modular system **2000** of the vehicle **100**. In any case, each of the compartments **1902**, **1904**, **1906**, **1908**, **1910**, **1912** is configured to receive and secure a battery pack module, which may be used to power one or more of the electric motors **800** in use of the vehicle **100**, among other things.

Referring now to FIG. 20, in some embodiments, the vehicle **100** may include the modular system **2000** that has, among other things, the battery pack modules **2010**. Each of the battery pack modules **2010** illustratively includes one or more power cells, such as the power cells **1050** described below with reference to FIG. 10, for example. In some embodiments, each of the battery pack modules **2010** may be included in, or otherwise form a portion of, each of the power cell assemblies **300**, **1000** discussed above. Additionally, in some embodiments, each of the power cell assemblies **300**, **1000** may include one or more battery pack modules **2010**.

In the illustrative embodiment, one or more battery pack modules may be added and integrated into the modular system **2000** or removed from the modular system **2000**. Addition or removal of the one or more battery pack modules may be dependent upon a variety of factors. In one example, addition of one or more battery pack modules into the system **2000** may be desirable to provide one or more auxiliary or supplemental power sources for particular appli-

29

cation(s) of the vehicle **100**, such as during time periods in which heavy usage of the vehicle **100** is expected, for instance. Of course, to hold any additional battery pack modules, the carriage **1900** may be formed to include additional compartments. In another example, one or more battery pack modules may be removed from the system **2000** to, among other things, reduce the weight of the vehicle **100**, which may be desirable during time periods in which light usage of the vehicle **100** is expected (e.g., during holidays), for instance. In those situations, one or more compartments may be removed from the carriage **1900**, as the case may be. It should be appreciated that the number of battery pack modules provided in the modular system **2000** may be dictated by the particular implementation of the vehicle **100**.

While the disclosure has been illustrated and described in detail in the foregoing drawings and description, the same is to be considered as exemplary and not restrictive in character, it being understood that only illustrative embodiments thereof have been shown and described and that all changes and modifications that come within the spirit of the disclosure are desired to be protected.

What is claimed is:

1. A land vehicle comprising:

- a frame structure including a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction;
- a plurality of wheels supported by the frame structure, wherein each of the plurality of wheels is sized to permit direct integration of an electric motor therein; and
- a brake system coupled to each one of the plurality of wheels, wherein each brake system includes
 - a disc having a plurality of notches defined between circumferentially adjacent teeth of the disc,
 - a first braking device configured to contact an outer face of the disc to resist rotation of one of the plurality of wheels,
 - a second braking device circumferentially spaced from the first braking device about the disc that is configured to contact the outer face of the disc to resist rotation of the one of the plurality of wheels, and
 - a third braking device configured to contact one or more teeth of the disc to resist rotation of the one of the plurality of wheels,

wherein:

- the disc includes an outer annular surface that extends circumferentially to at least partially define an outer diameter of the disc,
- the teeth are disposed at an inner diameter of the disc,
- the first braking device is configured to contact the outer face of the disc without enclosing the outer annular surface,
- the second braking device is configured to contact the outer face of the disc without enclosing the outer annular surface,
- the first braking device includes a first housing,
- the second braking device includes a second housing,
- the second housing has a different configuration from the first housing, and
- the first housing defines a unitary structure that surrounds an open cavity extending axially all the way through the first housing.

2. The land vehicle of claim 1, wherein the first braking device includes only one caliper and at least one piston at least partially housed by the only one caliper.

30

3. The land vehicle of claim 2, wherein the at least one piston includes six pistons.

4. The land vehicle of claim 1, wherein the second braking device is an electronic parking brake mechanism.

5. The land vehicle of claim 4, wherein the third braking device is a parking pawl mechanism operated independently from the electronic parking brake mechanism.

6. The land vehicle of claim 5, wherein the parking pawl mechanism includes a receptacle sized to receive a drive to permit manual release of the parking pawl mechanism in use of the land vehicle.

7. The land vehicle of claim 1, wherein the operator cabin comprises:

- a steering wheel;
- an operator seat; and
- a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays.

8. The land vehicle of claim 7, wherein:

the operator cabin comprises a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction;

the rack is movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery position, in which the rack is disposed close to the operator seat; and

the land vehicle has a gross vehicular weight rating (GVWR) of between 10,001 pounds and 14,000 pounds.

9. The land vehicle of claim 1, further comprising a plurality of electric motors, wherein each of the plurality of electric motors is integrated directly into one of the plurality of wheels.

10. The land vehicle of claim 9, wherein:

- each of the plurality of electric motors is coupled to one of the plurality of wheels without any transmission gearing interposed therebetween; and
- the land vehicle does not include an internal combustion engine.

11. A land vehicle comprising:

- a frame structure including a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction;
- a plurality of wheels supported by the frame structure; and
- a brake system coupled to each one of the plurality of wheels, wherein each brake system includes
 - a disc having a plurality of notches defined between circumferentially adjacent teeth of the disc,
 - a first braking device configured to contact an outer face of the disc to resist rotation of one of the plurality of wheels, and
 - a second braking device configured to contact one or more teeth of the disc to resist rotation of the one of the plurality of wheels,

wherein:

- the disc includes an outer annular surface that extends circumferentially to at least partially define an outer diameter of the disc,
- the teeth are disposed at an inner diameter of the disc,
- the first braking device is configured to contact the outer face of the disc without enclosing the outer annular surface,

31

the first braking device includes a housing having an open cavity extending axially therethrough that is at least partially arranged radially inward of the inner diameter of the disc,

the open cavity extends axially all the way through the housing of the first braking device, and

the housing of the first braking device defines a unitary structure that surrounds the open cavity.

12. The land vehicle of claim **11**, wherein the first braking device is an electronic parking brake mechanism.

13. The land vehicle of claim **12**, wherein the second braking device is a parking pawl mechanism operated independently from the electronic parking brake mechanism.

14. The land vehicle of claim **13**, further comprising a third braking device circumferentially spaced from the first braking device about the disc that is configured to contact the outer face of the disc to resist rotation of the one of the plurality of wheels, wherein the third braking device includes only one caliper and a plurality of pistons at least partially housed by the only one caliper.

15. The land vehicle of claim **11**, wherein the operator cabin comprises:

a steering wheel;

an operator seat; and

a rack arranged in the operator cabin opposite the steering wheel and the operator seat that includes a plurality of trays.

16. The land vehicle of claim **15**, wherein:

the operator cabin comprises a pair of tracks affixed to a floor of the operator cabin and spaced apart from one another in the longitudinal direction;

the rack is movable along the pair of tracks in a lateral direction perpendicular to the longitudinal direction between a stowed position, in which the rack is disposed distant from the operator seat, and a delivery position, in which the rack is disposed close to the operator seat; and

the land vehicle has a gross vehicular weight rating (GVWR) of between 10,001 pounds and 14,000 pounds.

17. The land vehicle of claim **16**, further comprising a plurality of electric motors, wherein:

each of the plurality of electric motors is integrated directly into one of the plurality of wheels;

each of the plurality of electric motors is coupled to one of the plurality of wheels without any transmission gearing interposed therebetween; and

the land vehicle does not include an internal combustion engine.

32

18. A method of operating a land vehicle that includes (i) a frame structure having a front cage that at least partially defines an operator cabin and a rear compartment positioned rearward of the front cage in a longitudinal direction, (ii) a plurality of wheels supported by the frame structure, and (iii) a brake system coupled to each one of the plurality of wheels, the method comprising:

operating the land vehicle in a park operating range; and operating the brake systems when the land vehicle is in

the park operating range, wherein operating the brake systems when the land vehicle is in the park operating range comprises selectively activating one or more electronic parking brake mechanisms of each brake system and selectively activating one or more parking pawl mechanisms of each brake system,

wherein selectively activating one or more electronic parking brake mechanisms of each brake system comprises contacting an outer face of a disc with a first braking device to resist rotation of a wheel coupled to the disc,

wherein contacting the outer face of the disc with the first braking device comprises contacting the outer face of the disc without enclosing an outer annular surface of the disc that extends circumferentially to at least partially define an outer diameter of the disc,

wherein the first braking device includes a housing having an open cavity extending axially therethrough that extends radially inward beyond an inner diameter of the disc,

wherein the housing includes a first exterior face and a second exterior face arranged opposite the first exterior face,

wherein the open cavity extends axially through at least one of the first and second exterior faces to define at least one opening in the at least one of the first and second exterior faces, and

wherein the housing defines a unitary structure that surrounds the open cavity.

19. The method of claim **18**, wherein operating the brake systems when the land vehicle is in the park operating range comprises activating the one or more parking brake mechanisms of each brake system and the one or more parking pawl mechanisms of each brake system contemporaneously.

20. The method of claim **18**, further comprising selectively releasing the one or more parking pawl mechanisms of each brake system manually subsequent to activation of the one or more parking pawl mechanisms of each brake system.

* * * * *