



(51) International Patent Classification:

G06Q 10/08 (2012.01) G06Q 10/10 (2012.01)

G06Q 10/06 (2012.01) G06Q 30/06 (2012.01)

(21) International Application Number:

PCT/IB2020/052166

(22) International Filing Date:

11 March 2020 (11.03.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/351,937 13 March 2019 (13.03.2019) US

(71) Applicant: COUPANG CORP. [KR/KR]; 570 Songpa-daero, Songpa-gu, Seoul 05510 (KR).

(72) Inventors: MA, Ke; 570 Songpa-daero, Songpa-gu, Seoul 05510 (KR). GU, Bin; 570 Songpa-daero, Songpa-gu,

Seoul 05510 (KR). WANG, Nan; 570 Songpa-daero, Songpa-gu, Seoul 05510 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

(54) Title: GENETIC ALGORITHM-BASED SYSTEMS AND METHODS FOR SIMULATING OUTBOUND FLOW




FIG. 3

(57) Abstract: The embodiments of the present disclosure provide systems and methods for optimizing allocation of products, comprising receiving an initial set of solutions comprising an initial distribution of a plurality of stock keeping unit (SKUs) among a plurality of fulfillment centers (FCs), and running a simulation of each solution of the initial set of solutions. Participation ratios may be calculated for each solution, and a score for each solution may be determined based on the calculated participation ratio. At least one solution with a highest determined score may be selected to feed a simulation algorithm to generate one or more additional solutions. Based on a best-performing solution, an allocation of the plurality of SKUs among the plurality of FCs may be modified. The best-performing solution may have the highest determined score among all solutions generated.



EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *in black and white; the international application as filed
contained color or greyscale and is available for download
from PATENTSCOPE*

**GENETIC ALGORITHM-BASED SYSTEMS AND METHODS FOR SIMULATING
OUTBOUND FLOW**

Technical Field

[001] The present disclosure generally relates to computerized systems and methods for simulating outbound flow and optimizing allocation of products. In particular, embodiments of the present disclosure relate to inventive and unconventional systems related to simulating outbound flow and optimizing allocation of products based on genetic algorithms.

Background

[002] Typically, when customer orders are made, the orders must be transferred to one or more fulfillment centers. However, customer orders are made by many different customers located at many different regions, and as such, the orders are bound for many different destinations. Therefore, the orders must be properly sorted such that they are routed to an appropriate fulfillment center and, ultimately, correctly routed to their destination.

[003] Systems and methods for optimizing shipping practices and identifying shipping routes for outbound products already exist. For example, US 2010/0274609 A1 describes a method of simulating shipments according to shipping routes. In order to determine the optimal routing plan, an alternative routing module can modify package routing data according to a user input. That is, the user may manually change data associated with the original package routing data and view the effects of each routing change. This process is repeated until the optimal routing plan is determined.

[004] However, these conventional systems and methods for optimizing outbound flow of products is difficult, time-consuming, and inaccurate mainly because they require manual modification and repeated testing of individual combinations of parameters. Especially for entities with multiple fulfillment centers

throughout the region, it is significantly challenging and time-consuming to replicate outbound flow of products at all levels of processes, including the level at which customer orders are initially received, the level at which inbound/stowing/inventory estimates are determined, and the level at which logic to assign orders to various fulfillment centers is determined. In addition, because conventional systems and methods require manual modification and repeated testing after each modification, simulation can only be done on a larger scale, rather than on a granular scale. For example, simulation can only be done on a product type by product type basis, rather than on a stocking keeping unit (SKU) by SKU basis.

[005] Therefore, there is a need for improved systems and methods for simulating outbound flow and optimizing allocation of products. In particular, there is a need for improved systems and methods for optimizing simulation of outbound flow of products that obviate the need for manual modification of parameters and repeated testing after each manual modification.

Summary

[006] One aspect of the present disclosure is directed to a computer-implemented system for optimizing allocation of products. The system may comprise a memory storing instructions and at least one processor configured to execute the instructions. The at least one processor may be configured to execute the instructions to receive an initial set of solutions, comprising an initial distribution of a plurality of stock keeping unit (SKUs) among a plurality of fulfillment centers (FCs). The at least one processor may run a simulation of each solution of the initial set of solutions, and calculate a participation ratio for each solution of the initial set of solutions. The at least one processor may further determine a score for each solution of the initial set of solutions based on the calculated participation ratio. The at least

one processor may select at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions. Based on a best-performing solution, the at least one processor may modify an allocation of the plurality of SKUs among the plurality of FCs. The best-performing solution may have the highest determined score among all solutions generated. Each of the plurality of SKUs may be indicative of at least one of a manufacturer, material, size, color, packaging, type, or weight of the product.

[007] In some aspects, the best-performing solution may raise the participation ratio for at least one FC by 2%. In other aspects, the simulation algorithm may comprise at least one constraint. The at least one constraint may comprise at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs. In some embodiments, the initial distribution of the plurality of SKUs among the plurality of FCs may be randomly generated. In some embodiments, the participation ratio for each of the solutions may be indicative of a percentage of FCs that contributed to a total output of products from a network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). In other embodiments, selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions may comprise changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions.

[008] In yet another embodiment, the at least one processor may be configured to execute the instructions to simulate customer demand at each of the plurality of FCs and allocate the plurality of SKUs among the plurality of FCs based on the simulated customer demand. The at least one processor may be further

configured to execute the instructions to cache at least a portion of the simulation algorithm. The cached portion of the simulation algorithm may comprise at least one constraint that remains substantially constant with each run of the simulation algorithm.

[009] Another aspect of the present disclosure is directed to a computer-implemented method for optimizing allocation of products. The method may comprise receiving an initial set of solutions, comprising an initial distribution of a plurality of stock keeping unit (SKUs) among a plurality of fulfillment centers (FCs). The method may further comprise running a simulation of each solution of the initial set of solutions, and calculating a participation ratio for each solution of the initial set of solutions. The method may further comprise determining a score for each solution of the initial set of solutions based on the calculated participation ratio, and selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions. The method may further comprise modifying an allocation of the plurality of SKUs among the plurality of FCs based on a best-performing solution. The best-performing solution may have the highest determined score among all solutions generated.

[0010] In some aspects, the best-performing simulation may raise the participation ratio for at least one FC by 2%. In other aspects, the simulation algorithm may comprise at least one constraint. The at least one constraint may comprise at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs. The initial distribution of the plurality of SKUs among the plurality of FCs may be randomly generated. In some embodiments, the participation ratio for each of the solutions may be indicative of a percentage of FCs that contributed to a total output of

products from a network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). In other embodiments, selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions may comprise changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions.

[0011] In yet another embodiment, the method may further comprise simulating customer demand at each of the plurality of FCs and allocating the plurality of SKUs among the plurality of FCs based on the simulated customer demand. The method may further comprise caching at least a portion of the simulation algorithm. The cached portion of the simulation algorithm may comprise at least one constraint that remains substantially constant with each run of the simulation algorithm.

[0012] Yet another aspect of the present disclosure is directed to a computer-implemented system for optimizing allocation of products. The system may comprise a memory storing instructions and at least one processor configured to execute the instructions. The at least one processor may be configured to execute the instructions to receive an initial set of solutions, comprising an initial distribution of a plurality of stock keeping unit (SKUs) among a plurality of fulfillment centers (FCs). The at least one processor may run a simulation of each solution of the initial set of solutions, and calculate a participation ratio for each solution of the initial set of solutions. The at least one processor may further determine a score for each solution of the initial set of solutions based on the calculated participation ratio. The at least one processor may select at least one solution with a highest determined score to feed the simulation algorithm to generate one or more additional solutions. In some

aspects, the simulation algorithm may comprise at least one constraint. The at least one constraint may comprise at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs. In other aspects, at least one constraint that remains substantially constant with each run of the simulation algorithm may be cached. In other embodiments, selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions may comprise changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions.

[0013] In some aspects, the at least one processor may simulate customer demand at each of the plurality of FCs. Based at least on the simulated customer demand and on a best-performing solution, the at least one processor may modify an allocation of the plurality of SKUs among the plurality of FCs. In some embodiments, modifying an allocation of the plurality of SKUs among the plurality of FCs comprises modifying data associated with the allocation. The best-performing solution may raise the participation ratio for at least one FC by 2%.

[0014] Other systems, methods, and computer-readable media are also discussed herein.

Brief Description of the Drawings

[0015] FIG. 1A is a schematic block diagram illustrating an exemplary embodiment of a network comprising computerized systems for communications enabling shipping, transportation, and logistics operations, consistent with the disclosed embodiments.

[0016] FIG. 1B depicts a sample Search Result Page (SRP) that includes one or more search results satisfying a search request along with interactive user interface elements, consistent with the disclosed embodiments.

[0017] FIG. 1C depicts a sample Single Display Page (SDP) that includes a product and information about the product along with interactive user interface elements, consistent with the disclosed embodiments.

[0018] FIG. 1D depicts a sample Cart page that includes items in a virtual shopping cart along with interactive user interface elements, consistent with the disclosed embodiments.

[0019] FIG. 1E depicts a sample Order page that includes items from the virtual shopping cart along with information regarding purchase and shipping, along with interactive user interface elements, consistent with the disclosed embodiments.

[0020] FIG. 2 is a diagrammatic illustration of an exemplary fulfillment center configured to utilize disclosed computerized systems, consistent with the disclosed embodiments.

[0021] FIG. 3 is a schematic block diagram illustrating an exemplary embodiment of a system comprising an optimization system for simulating and optimizing outbound flow of products.

[0022] FIG. 4 is a flowchart illustrating an exemplary embodiment of a method for simulating and optimizing outbound flow of products.

[0023] FIG. 5 is another flowchart illustrating an exemplary embodiment of a method for simulating and optimizing outbound flow of products.

[0024] FIG. 6 is a diagram of an exemplary summary page that includes results of a generated simulation.

Detailed Description

[0025] The following detailed description refers to the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the following description to refer to the same or similar parts. While several illustrative embodiments are described herein, modifications, adaptations and other implementations are possible. For example, substitutions, additions, or modifications may be made to the components and steps illustrated in the drawings, and the illustrative methods described herein may be modified by substituting, reordering, removing, or adding steps to the disclosed methods. Accordingly, the following detailed description is not limited to the disclosed embodiments and examples. Instead, the proper scope of the invention is defined by the appended claims.

[0026] Embodiments of the present disclosure are directed to systems and methods configured for simulating outbound flow and optimizing allocation of products, using genetic algorithms.

[0027] Referring to FIG. 1A, a schematic block diagram 100 illustrating an exemplary embodiment of a system comprising computerized systems for communications enabling shipping, transportation, and logistics operations is shown. As illustrated in FIG. 1A, system 100 may include a variety of systems, each of which may be connected to one another via one or more networks. The systems may also be connected to one another via a direct connection, for example, using a cable. The depicted systems include a shipment authority technology (SAT) system 101, an external front end system 103, an internal front end system 105, a transportation system 107, mobile devices 107A, 107B, and 107C, seller portal 109, shipment and order tracking (SOT) system 111, fulfillment optimization (FO) system 113, fulfillment

messaging gateway (FMG) 115, supply chain management (SCM) system 117, workforce management system 119, mobile devices 119A, 119B, and 119C (depicted as being inside of fulfillment center (FC) 200), 3rd party fulfillment systems 121A, 121B, and 121C, fulfillment center authorization system (FC Auth) 123, and labor management system (LMS) 125.

[0028] SAT system 101, in some embodiments, may be implemented as a computer system that monitors order status and delivery status. For example, SAT system 101 may determine whether an order is past its Promised Delivery Date (PDD) and may take appropriate action, including initiating a new order, reshipping the items in the non-delivered order, canceling the non-delivered order, initiating contact with the ordering customer, or the like. SAT system 101 may also monitor other data, including output (such as a number of packages shipped during a particular time period) and input (such as the number of empty cardboard boxes received for use in shipping). SAT system 101 may also act as a gateway between different devices in system 100, enabling communication (e.g., using store-and-forward or other techniques) between devices such as external front end system 103 and FO system 113.

[0029] External front end system 103, in some embodiments, may be implemented as a computer system that enables external users to interact with one or more systems in system 100. For example, in embodiments where system 100 enables the presentation of systems to enable users to place an order for an item, external front end system 103 may be implemented as a web server that receives search requests, presents item pages, and solicits payment information. For example, external front end system 103 may be implemented as a computer or computers running software such as the Apache HTTP Server, Microsoft Internet

Information Services (IIS), NGINX, or the like. In other embodiments, external front end system 103 may run custom web server software designed to receive and process requests from external devices (e.g., mobile device 102A or computer 102B), acquire information from databases and other data stores based on those requests, and provide responses to the received requests based on acquired information.

[0030] In some embodiments, external front end system 103 may include one or more of a web caching system, a database, a search system, or a payment system. In one aspect, external front end system 103 may comprise one or more of these systems, while in another aspect, external front end system 103 may comprise interfaces (e.g., server-to-server, database-to-database, or other network connections) connected to one or more of these systems.

[0031] An illustrative set of steps, illustrated by FIGS. 1B, 1C, 1D, and 1E, will help to describe some operations of external front end system 103. External front end system 103 may receive information from systems or devices in system 100 for presentation and/or display. For example, external front end system 103 may host or provide one or more web pages, including a Search Result Page (SRP) (e.g., FIG. 1B), a Single Detail Page (SDP) (e.g., FIG. 1C), a Cart page (e.g., FIG. 1D), or an Order page (e.g., FIG. 1E). A user device (e.g., using mobile device 102A or computer 102B) may navigate to external front end system 103 and request a search by entering information into a search box. External front end system 103 may request information from one or more systems in system 100. For example, external front end system 103 may request information from FO System 113 that satisfies the search request. External front end system 103 may also request and receive (from FO System 113) a Promised Delivery Date or “PDD” for each product included in the search results. The PDD, in some embodiments, may represent an estimate of when

a package containing the product will arrive at the user's desired location or a date by which the product is promised to be delivered at the user's desired location if ordered within a particular period of time, for example, by the end of the day (11:59 PM). (PDD is discussed further below with respect to FO System 113.)

[0032] External front end system 103 may prepare an SRP (e.g., FIG. 1B) based on the information. The SRP may include information that satisfies the search request. For example, this may include pictures of products that satisfy the search request. The SRP may also include respective prices for each product, or information relating to enhanced delivery options for each product, PDD, weight, size, offers, discounts, or the like. External front end system 103 may send the SRP to the requesting user device (e.g., via a network).

[0033] A user device may then select a product from the SRP, e.g., by clicking or tapping a user interface, or using another input device, to select a product represented on the SRP. The user device may formulate a request for information on the selected product and send it to external front end system 103. In response, external front end system 103 may request information related to the selected product. For example, the information may include additional information beyond that presented for a product on the respective SRP. This could include, for example, shelf life, country of origin, weight, size, number of items in package, handling instructions, or other information about the product. The information could also include recommendations for similar products (based on, for example, big data and/or machine learning analysis of customers who bought this product and at least one other product), answers to frequently asked questions, reviews from customers, manufacturer information, pictures, or the like.

[0034] External front end system 103 may prepare an SDP (Single Detail Page) (e.g., FIG. 1C) based on the received product information. The SDP may also include other interactive elements such as a “Buy Now” button, a “Add to Cart” button, a quantity field, a picture of the item, or the like. The SDP may further include a list of sellers that offer the product. The list may be ordered based on the price each seller offers such that the seller that offers to sell the product at the lowest price may be listed at the top. The list may also be ordered based on the seller ranking such that the highest ranked seller may be listed at the top. The seller ranking may be formulated based on multiple factors, including, for example, the seller’s past track record of meeting a promised PDD. External front end system 103 may deliver the SDP to the requesting user device (e.g., via a network).

[0035] The requesting user device may receive the SDP which lists the product information. Upon receiving the SDP, the user device may then interact with the SDP. For example, a user of the requesting user device may click or otherwise interact with a “Place in Cart” button on the SDP. This adds the product to a shopping cart associated with the user. The user device may transmit this request to add the product to the shopping cart to external front end system 103.

[0036] External front end system 103 may generate a Cart page (e.g., FIG. 1D). The Cart page, in some embodiments, lists the products that the user has added to a virtual “shopping cart.” A user device may request the Cart page by clicking on or otherwise interacting with an icon on the SRP, SDP, or other pages. The Cart page may, in some embodiments, list all products that the user has added to the shopping cart, as well as information about the products in the cart such as a quantity of each product, a price for each product per item, a price for each product based on an associated quantity, information regarding PDD, a delivery method, a

shipping cost, user interface elements for modifying the products in the shopping cart (e.g., deletion or modification of a quantity), options for ordering other product or setting up periodic delivery of products, options for setting up interest payments, user interface elements for proceeding to purchase, or the like. A user at a user device may click on or otherwise interact with a user interface element (e.g., a button that reads “Buy Now”) to initiate the purchase of the product in the shopping cart. Upon doing so, the user device may transmit this request to initiate the purchase to external front end system 103.

[0037] External front end system 103 may generate an Order page (e.g., FIG. 1E) in response to receiving the request to initiate a purchase. The Order page, in some embodiments, re-lists the items from the shopping cart and requests input of payment and shipping information. For example, the Order page may include a section requesting information about the purchaser of the items in the shopping cart (e.g., name, address, e-mail address, phone number), information about the recipient (e.g., name, address, phone number, delivery information), shipping information (e.g., speed/method of delivery and/or pickup), payment information (e.g., credit card, bank transfer, check, stored credit), user interface elements to request a cash receipt (e.g., for tax purposes), or the like. External front end system 103 may send the Order page to the user device.

[0038] The user device may enter information on the Order page and click or otherwise interact with a user interface element that sends the information to external front end system 103. From there, external front end system 103 may send the information to different systems in system 100 to enable the creation and processing of a new order with the products in the shopping cart.

[0039] In some embodiments, external front end system 103 may be further configured to enable sellers to transmit and receive information relating to orders.

[0040] Internal front end system 105, in some embodiments, may be implemented as a computer system that enables internal users (e.g., employees of an organization that owns, operates, or leases system 100) to interact with one or more systems in system 100. For example, in embodiments where network 101 enables the presentation of systems to enable users to place an order for an item, internal front end system 105 may be implemented as a web server that enables internal users to view diagnostic and statistical information about orders, modify item information, or review statistics relating to orders. For example, internal front end system 105 may be implemented as a computer or computers running software such as the Apache HTTP Server, Microsoft Internet Information Services (IIS), NGINX, or the like. In other embodiments, internal front end system 105 may run custom web server software designed to receive and process requests from systems or devices depicted in system 100 (as well as other devices not depicted), acquire information from databases and other data stores based on those requests, and provide responses to the received requests based on acquired information.

[0041] In some embodiments, internal front end system 105 may include one or more of a web caching system, a database, a search system, a payment system, an analytics system, an order monitoring system, or the like. In one aspect, internal front end system 105 may comprise one or more of these systems, while in another aspect, internal front end system 105 may comprise interfaces (e.g., server-to-server, database-to-database, or other network connections) connected to one or more of these systems.

[0042] Transportation system 107, in some embodiments, may be implemented as a computer system that enables communication between systems or devices in system 100 and mobile devices 107A-107C. Transportation system 107, in some embodiments, may receive information from one or more mobile devices 107A-107C (e.g., mobile phones, smart phones, PDAs, or the like). For example, in some embodiments, mobile devices 107A-107C may comprise devices operated by delivery workers. The delivery workers, who may be permanent, temporary, or shift employees, may utilize mobile devices 107A-107C to effect delivery of packages containing the products ordered by users. For example, to deliver a package, the delivery worker may receive a notification on a mobile device indicating which package to deliver and where to deliver it. Upon arriving at the delivery location, the delivery worker may locate the package (e.g., in the back of a truck or in a crate of packages), scan or otherwise capture data associated with an identifier on the package (e.g., a barcode, an image, a text string, an RFID tag, or the like) using the mobile device, and deliver the package (e.g., by leaving it at a front door, leaving it with a security guard, handing it to the recipient, or the like). In some embodiments, the delivery worker may capture photo(s) of the package and/or may obtain a signature using the mobile device. The mobile device may send information to transportation system 107 including information about the delivery, including, for example, time, date, GPS location, photo(s), an identifier associated with the delivery worker, an identifier associated with the mobile device, or the like. Transportation system 107 may store this information in a database (not pictured) for access by other systems in system 100. Transportation system 107 may, in some embodiments, use this information to prepare and send tracking data to other systems indicating the location of a particular package.

[0043] In some embodiments, certain users may use one kind of mobile device (e.g., permanent workers may use a specialized PDA with custom hardware such as a barcode scanner, stylus, and other devices) while other users may use other kinds of mobile devices (e.g., temporary or shift workers may utilize off-the-shelf mobile phones and/or smartphones).

[0044] In some embodiments, transportation system 107 may associate a user with each device. For example, transportation system 107 may store an association between a user (represented by, e.g., a user identifier, an employee identifier, or a phone number) and a mobile device (represented by, e.g., an International Mobile Equipment Identity (IMEI), an International Mobile Subscription Identifier (IMSI), a phone number, a Universal Unique Identifier (UUID), or a Globally Unique Identifier (GUID)). Transportation system 107 may use this association in conjunction with data received on deliveries to analyze data stored in the database in order to determine, among other things, a location of the worker, an efficiency of the worker, or a speed of the worker.

[0045] Seller portal 109, in some embodiments, may be implemented as a computer system that enables sellers or other external entities to electronically communicate with one or more systems in system 100. For example, a seller may utilize a computer system (not pictured) to upload or provide product information, order information, contact information, or the like, for products that the seller wishes to sell through system 100 using seller portal 109.

[0046] Shipment and order tracking system 111, in some embodiments, may be implemented as a computer system that receives, stores, and forwards information regarding the location of packages containing products ordered by customers (e.g., by a user using devices 102A-102B). In some embodiments,

shipment and order tracking system 111 may request or store information from web servers (not pictured) operated by shipping companies that deliver packages containing products ordered by customers.

[0047] In some embodiments, shipment and order tracking system 111 may request and store information from systems depicted in system 100. For example, shipment and order tracking system 111 may request information from transportation system 107. As discussed above, transportation system 107 may receive information from one or more mobile devices 107A-107C (e.g., mobile phones, smart phones, PDAs, or the like) that are associated with one or more of a user (e.g., a delivery worker) or a vehicle (e.g., a delivery truck). In some embodiments, shipment and order tracking system 111 may also request information from workforce management system (WMS) 119 to determine the location of individual products inside of a fulfillment center (e.g., fulfillment center 200). Shipment and order tracking system 111 may request data from one or more of transportation system 107 or WMS 119, process it, and present it to a device (e.g., user devices 102A and 102B) upon request.

[0048] Fulfillment optimization (FO) system 113, in some embodiments, may be implemented as a computer system that stores information for customer orders from other systems (e.g., external front end system 103 and/or shipment and order tracking system 111). FO system 113 may also store information describing where particular items are held or stored. For example, certain items may be stored only in one fulfillment center, while certain other items may be stored in multiple fulfillment centers. In still other embodiments, certain fulfillment centers may be designed to store only a particular set of items (e.g., fresh produce or frozen products). FO

system 113 stores this information as well as associated information (e.g., quantity, size, date of receipt, expiration date, etc.).

[0049] FO system 113 may also calculate a corresponding PDD (promised delivery date) for each product. The PDD, in some embodiments, may be based on one or more factors. For example, FO system 113 may calculate a PDD for a product based on a past demand for a product (e.g., how many times that product was ordered during a period of time), an expected demand for a product (e.g., how many customers are forecast to order the product during an upcoming period of time), a network-wide past demand indicating how many products were ordered during a period of time, a network-wide expected demand indicating how many products are expected to be ordered during an upcoming period of time, one or more counts of the product stored in each fulfillment center 200, which fulfillment center stores each product, expected or current orders for that product, or the like.

[0050] In some embodiments, FO system 113 may determine a PDD for each product on a periodic basis (e.g., hourly) and store it in a database for retrieval or sending to other systems (e.g., external front end system 103, SAT system 101, shipment and order tracking system 111). In other embodiments, FO system 113 may receive electronic requests from one or more systems (e.g., external front end system 103, SAT system 101, shipment and order tracking system 111) and calculate the PDD on demand.

[0051] Fulfilment messaging gateway (FMG) 115, in some embodiments, may be implemented as a computer system that receives a request or response in one format or protocol from one or more systems in system 100, such as FO system 113, converts it to another format or protocol, and forward it in the converted format or

protocol to other systems, such as WMS 119 or 3rd party fulfillment systems 121A, 121B, or 121C, and vice versa.

[0052] Supply chain management (SCM) system 117, in some embodiments, may be implemented as a computer system that performs forecasting functions. For example, SCM system 117 may forecast a level of demand for a particular product based on, for example, based on a past demand for products, an expected demand for a product, a network-wide past demand, a network-wide expected demand, a count products stored in each fulfillment center 200, expected or current orders for each product, or the like. In response to this forecasted level and the amount of each product across all fulfillment centers, SCM system 117 may generate one or more purchase orders to purchase and stock a sufficient quantity to satisfy the forecasted demand for a particular product.

[0053] Workforce management system (WMS) 119, in some embodiments, may be implemented as a computer system that monitors workflow. For example, WMS 119 may receive event data from individual devices (e.g., devices 107A-107C or 119A-119C) indicating discrete events. For example, WMS 119 may receive event data indicating the use of one of these devices to scan a package. As discussed below with respect to fulfillment center 200 and FIG. 2, during the fulfillment process, a package identifier (e.g., a barcode or RFID tag data) may be scanned or read by machines at particular stages (e.g., automated or handheld barcode scanners, RFID readers, high-speed cameras, devices such as tablet 119A, mobile device/PDA 119B, computer 119C, or the like). WMS 119 may store each event indicating a scan or a read of a package identifier in a corresponding database (not pictured) along with the package identifier, a time, date, location, user identifier, or other information,

and may provide this information to other systems (e.g., shipment and order tracking system 111).

[0054] WMS 119, in some embodiments, may store information associating one or more devices (e.g., devices 107A-107C or 119A-119C) with one or more users associated with system 100. For example, in some situations, a user (such as a part- or full-time employee) may be associated with a mobile device in that the user owns the mobile device (e.g., the mobile device is a smartphone). In other situations, a user may be associated with a mobile device in that the user is temporarily in custody of the mobile device (e.g., the user checked the mobile device out at the start of the day, will use it during the day, and will return it at the end of the day).

[0055] WMS 119, in some embodiments, may maintain a work log for each user associated with system 100. For example, WMS 119 may store information associated with each employee, including any assigned processes (e.g., unloading trucks, picking items from a pick zone, rebin wall work, packing items), a user identifier, a location (e.g., a floor or zone in a fulfillment center 200), a number of units moved through the system by the employee (e.g., number of items picked, number of items packed), an identifier associated with a device (e.g., devices 119A-119C), or the like. In some embodiments, WMS 119 may receive check-in and check-out information from a timekeeping system, such as a timekeeping system operated on a device 119A-119C.

[0056] 3rd party fulfillment (3PL) systems 121A-121C, in some embodiments, represent computer systems associated with third-party providers of logistics and products. For example, while some products are stored in fulfillment center 200 (as discussed below with respect to FIG. 2), other products may be stored off-site, may be produced on demand, or may be otherwise unavailable for storage in fulfillment

center 200. 3PL systems 121A-121C may be configured to receive orders from FO system 113 (e.g., through FMG 115) and may provide products and/or services (e.g., delivery or installation) to customers directly. In some embodiments, one or more of 3PL systems 121A-121C may be part of system 100, while in other embodiments, one or more of 3PL systems 121A-121C may be outside of system 100 (e.g., owned or operated by a third-party provider).

[0057] Fulfillment Center Auth system (FC Auth) 123, in some embodiments, may be implemented as a computer system with a variety of functions. For example, in some embodiments, FC Auth 123 may act as a single-sign on (SSO) service for one or more other systems in system 100. For example, FC Auth 123 may enable a user to log in via internal front end system 105, determine that the user has similar privileges to access resources at shipment and order tracking system 111, and enable the user to access those privileges without requiring a second log in process. FC Auth 123, in other embodiments, may enable users (e.g., employees) to associate themselves with a particular task. For example, some employees may not have an electronic device (such as devices 119A-119C) and may instead move from task to task, and zone to zone, within a fulfillment center 200, during the course of a day. FC Auth 123 may be configured to enable those employees to indicate what task they are performing and what zone they are in at different times of day.

[0058] Labor management system (LMS) 125, in some embodiments, may be implemented as a computer system that stores attendance and overtime information for employees (including full-time and part-time employees). For example, LMS 125 may receive information from FC Auth 123, WMA 119, devices 119A-119C, transportation system 107, and/or devices 107A-107C.

[0059] The particular configuration depicted in FIG. 1A is an example only. For example, while FIG. 1A depicts FC Auth system 123 connected to FO system 113, not all embodiments require this particular configuration. Indeed, in some embodiments, the systems in system 100 may be connected to one another through one or more public or private networks, including the Internet, an Intranet, a WAN (Wide-Area Network), a MAN (Metropolitan-Area Network), a wireless network compliant with the IEEE 802.11a/b/g/n Standards, a leased line, or the like. In some embodiments, one or more of the systems in system 100 may be implemented as one or more virtual servers implemented at a data center, server farm, or the like.

[0060] FIG. 2 depicts a fulfillment center 200. Fulfillment center 200 is an example of a physical location that stores items for shipping to customers when ordered. Fulfillment center (FC) 200 may be divided into multiple zones, each of which are depicted in FIG. 2. These “zones,” in some embodiments, may be thought of as virtual divisions between different stages of a process of receiving items, storing the items, retrieving the items, and shipping the items. So while the “zones” are depicted in FIG. 2, other divisions of zones are possible, and the zones in FIG. 2 may be omitted, duplicated, or modified in some embodiments.

[0061] Inbound zone 203 represents an area of FC 200 where items are received from sellers who wish to sell products using system 100 from FIG. 1A. For example, a seller may deliver items 202A and 202B using truck 201. Item 202A may represent a single item large enough to occupy its own shipping pallet, while item 202B may represent a set of items that are stacked together on the same pallet to save space.

[0062] A worker will receive the items in inbound zone 203 and may optionally check the items for damage and correctness using a computer system (not pictured).

For example, the worker may use a computer system to compare the quantity of items 202A and 202B to an ordered quantity of items. If the quantity does not match, that worker may refuse one or more of items 202A or 202B. If the quantity does match, the worker may move those items (using, e.g., a dolly, a handtruck, a forklift, or manually) to buffer zone 205. Buffer zone 205 may be a temporary storage area for items that are not currently needed in the picking zone, for example, because there is a high enough quantity of that item in the picking zone to satisfy forecasted demand. In some embodiments, forklifts 206 operate to move items around buffer zone 205 and between inbound zone 203 and drop zone 207. If there is a need for items 202A or 202B in the picking zone (e.g., because of forecasted demand), a forklift may move items 202A or 202B to drop zone 207.

[0063] Drop zone 207 may be an area of FC 200 that stores items before they are moved to picking zone 209. A worker assigned to the picking task (a “picker”) may approach items 202A and 202B in the picking zone, scan a barcode for the picking zone, and scan barcodes associated with items 202A and 202B using a mobile device (e.g., device 119B). The picker may then take the item to picking zone 209 (e.g., by placing it on a cart or carrying it).

[0064] Picking zone 209 may be an area of FC 200 where items 208 are stored on storage units 210. In some embodiments, storage units 210 may comprise one or more of physical shelving, bookshelves, boxes, totes, refrigerators, freezers, cold stores, or the like. In some embodiments, picking zone 209 may be organized into multiple floors. In some embodiments, workers or machines may move items into picking zone 209 in multiple ways, including, for example, a forklift, an elevator, a conveyor belt, a cart, a handtruck, a dolly, an automated robot or device, or

manually. For example, a picker may place items 202A and 202B on a handtruck or cart in drop zone 207 and walk items 202A and 202B to picking zone 209.

[0065] A picker may receive an instruction to place (or “stow”) the items in particular spots in picking zone 209, such as a particular space on a storage unit 210. For example, a picker may scan item 202A using a mobile device (e.g., device 119B). The device may indicate where the picker should stow item 202A, for example, using a system that indicate an aisle, shelf, and location. The device may then prompt the picker to scan a barcode at that location before stowing item 202A in that location. The device may send (e.g., via a wireless network) data to a computer system such as WMS 119 in FIG. 1A indicating that item 202A has been stowed at the location by the user using device 119B.

[0066] Once a user places an order, a picker may receive an instruction on device 119B to retrieve one or more items 208 from storage unit 210. The picker may retrieve item 208, scan a barcode on item 208, and place it on transport mechanism 214. While transport mechanism 214 is represented as a slide, in some embodiments, transport mechanism may be implemented as one or more of a conveyor belt, an elevator, a cart, a forklift, a handtruck, a dolly, a cart, or the like. Item 208 may then arrive at packing zone 211.

[0067] Packing zone 211 may be an area of FC 200 where items are received from picking zone 209 and packed into boxes or bags for eventual shipping to customers. In packing zone 211, a worker assigned to receiving items (a “rebin worker”) will receive item 208 from picking zone 209 and determine what order it corresponds to. For example, the rebin worker may use a device, such as computer 119C, to scan a barcode on item 208. Computer 119C may indicate visually which order item 208 is associated with. This may include, for example, a space or “cell” on

a wall 216 that corresponds to an order. Once the order is complete (e.g., because the cell contains all items for the order), the rebin worker may indicate to a packing worker (or “packer”) that the order is complete. The packer may retrieve the items from the cell and place them in a box or bag for shipping. The packer may then send the box or bag to a hub zone 213, e.g., via forklift, cart, dolly, handtruck, conveyor belt, manually, or otherwise.

[0068] Hub zone 213 may be an area of FC 200 that receives all boxes or bags (“packages”) from packing zone 211. Workers and/or machines in hub zone 213 may retrieve package 218 and determine which portion of a delivery area each package is intended to go to, and route the package to an appropriate camp zone 215. For example, if the delivery area has two smaller sub-areas, packages will go to one of two camp zones 215. In some embodiments, a worker or machine may scan a package (e.g., using one of devices 119A-119C) to determine its eventual destination. Routing the package to camp zone 215 may comprise, for example, determining a portion of a geographical area that the package is destined for (e.g., based on a postal code) and determining a camp zone 215 associated with the portion of the geographical area.

[0069] Camp zone 215, in some embodiments, may comprise one or more buildings, one or more physical spaces, or one or more areas, where packages are received from hub zone 213 for sorting into routes and/or sub-routes. In some embodiments, camp zone 215 is physically separate from FC 200 while in other embodiments camp zone 215 may form a part of FC 200.

[0070] Workers and/or machines in camp zone 215 may determine which route and/or sub-route a package 220 should be associated with, for example, based on a comparison of the destination to an existing route and/or sub-route, a

calculation of workload for each route and/or sub-route, the time of day, a shipping method, the cost to ship the package 220, a PDD associated with the items in package 220, or the like. In some embodiments, a worker or machine may scan a package (e.g., using one of devices 119A-119C) to determine its eventual destination. Once package 220 is assigned to a particular route and/or sub-route, a worker and/or machine may move package 220 to be shipped. In exemplary FIG. 2, camp zone 215 includes a truck 222, a car 226, and delivery workers 224A and 224B. In some embodiments, truck 222 may be driven by delivery worker 224A, where delivery worker 224A is a full-time employee that delivers packages for FC 200 and truck 222 is owned, leased, or operated by the same company that owns, leases, or operates FC 200. In some embodiments, car 226 may be driven by delivery worker 224B, where delivery worker 224B is a “flex” or occasional worker that is delivering on an as-needed basis (e.g., seasonally). Car 226 may be owned, leased, or operated by delivery worker 224B.

[0071] Referring to FIG. 3, a schematic block diagram 300 illustrating an exemplary embodiment of a system comprising an optimization system 301 for simulating outbound flow. Optimization system 301 may be associated with one or more systems in system 100 of FIG. 1A. For example, optimization system 301 may be implemented as part of SCM system 117. Optimization system 301, in some embodiments, may be implemented as a computer system that stores information for each FC 200 as well as information for customer orders from other systems (e.g., external front end system 103, shipment and order tracking system 111, and/or FO system 113). For example, optimization system 301 may include one or more processors 305, which may store information describing a distribution of SKUs among FCs. One or more processors 305 of optimization system 301, thus, may

store a list of SKUs that are stored in each FC. One or more processors 305 may also store information describing constraints associated with each of the FCs. For example, certain FCs may have constraints, including maximum capacity, compatibility with certain items due to size, refrigeration needs, weight, or other item requirements, costs of transfer, building restrictions, and/or any combination thereof. By way of example, certain items may be stored only in one fulfillment center, while certain other items may be stored in multiple fulfillment centers. In still other embodiments, certain fulfillment centers may be designed to store only a particular set of items (e.g., fresh produce or frozen products). One or more processors 305 may store or retrieve this information as well as associated information (e.g., quantity, size, date of receipt, expiration date, etc.) for each FC.

[0072] In other embodiments, each of the aforementioned information associated with each FC 200 may be stored in a database 304. As such, optimization system 301 may retrieve information from the database 304 over network 302. Database 304 may include one or more memory devices that store information and are accessed through network 302. By way of example, database 304 may include Oracle™ databases, Sybase™ databases, or other relational databases or non-relational databases, such as Hadoop sequence files, HBase, or Cassandra. While database 304 is illustrated as being included in the system 300, it may alternatively be located remotely from system 300. In other embodiments, database 304 may be incorporated into optimization system 301. Database 304 may include computing components (e.g., database management system, database server, etc.) configured to receive and process requests for data stored in memory devices of database 304 and to provide data from database 304.

[0073] System 300 may also comprise a network 302 and a server 303.

Optimization system 301, server 303, and database 304 may be connected and be able to communicate with each other via network 302. Network 302 may be one or more of a wireless network, a wired network or any combination of wireless network and wired network. For example, network 302 may include one or more of a fiber optics network, a passive optical network, a cable network, an Internet network, a satellite network, a wireless LAN, a Global System for Mobile Communication ("GSM"), a Personal Communication Service ("PCS"), a Personal Area Network ("PAN"), D-AMPS, Wi-Fi, Fixed Wireless Data, IEEE 802.11b, 802.15.1, 802.11n and 802.11g or any other wired or wireless network for transmitting and receiving data.

[0074] In addition, network 302 may include, but not be limited to, telephone lines, fiber optics, IEEE Ethernet 902.3, a wide area network ("WAN"), a local area network ("LAN"), or a global network such as the Internet. Also network 302 may support an Internet network, a wireless communication network, a cellular network, or the like, or any combination thereof. Network 302 may further include one network, or any number of the exemplary types of networks mentioned above, operating as a stand-alone network or in cooperation with each other. Network 302 may utilize one or more protocols of one or more network elements to which they are communicatively coupled. Network 302 may translate to or from other protocols to one or more protocols of network devices. Although network 302 is depicted as a single network, it should be appreciated that according to one or more embodiments, network 302 may comprise a plurality of interconnected networks, such as, for example, the Internet, a service provider's network, a cable television network, corporate networks, and home networks.

[0075] Server 303 may be a web server. Server 303, for example, may include hardware (e.g., one or more computers) and/or software (e.g., one or more applications) that deliver web content that can be accessed by, for example a user through a network (e.g., network 302), such as the Internet. Server 303 may use, for example, a hypertext transfer protocol (HTTP or sHTTP) to communicate with a user. The web pages delivered to the user may include, for example, HTML documents, which may include images, style sheets, and scripts in addition to text content.

[0076] A user program such as, for example, a web browser, web crawler, or native mobile application, may initiate communication by making a request for a specific resource using HTTP and server 303 may respond with the content of that resource or an error message if unable to do so. Server 303 also may enable or facilitate receiving content from the user so the user may be able to, for example, submit web forms, including uploading of files. Server 303 may also support server-side scripting using, for example, Active Server Pages (ASP), PHP, or other scripting languages. Accordingly, the behavior of server 303 can be scripted in separate files, while the actual server software remains unchanged.

[0077] In other embodiments, server 303 may be an application server, which may include hardware and/or software that is dedicated to the efficient execution of procedures (e.g., programs, routines, scripts) for supporting its applied applications. Server 303 may comprise one or more application server frameworks, including, for example, Java application servers (e.g., Java platform, Enterprise Edition (Java EE), the .NET framework from Microsoft®, PHP application servers, and the like). The various application server frameworks may contain a comprehensive service layer model. Server 303 may act as a set of components accessible to, for example, an entity implementing system 100, through an API defined by the platform itself.

[0078] As discussed in detail below, one or more processors 305 of optimization system 301 may implement genetic algorithms to generate one or more simulations of outbound flow of products to one or more FCs. For example, based on information associated with each FC stored in database 304, one or more processors 305 may optimize outbound flow of products, e.g., SKUs, among one or more FCs. In some embodiments, one or more processors 305 may optimize outbound flow through SKU mapping. SKU mapping is the allocation of SKUs to FCs, and outbound network optimization may be achieved through SKU mapping. One or more processors 305 may generate a simulation, via SKU mapping, and each simulation may comprise different distribution of SKUs among FCs. Each simulation may be randomly generated. Accordingly, one or more processors 305 may find an optimal simulation by generating one or more simulations and selecting the optimal simulation that improves most upon the output rate of one or more FCs across a statewide, regional, or nationwide network. Determining an optimal simulation that improves upon the output rate may be crucial in optimizing outbound flow of products. For example, while it may be easier to place one of each item in each FC, this may not be optimal because the FC will run out of items quickly if customer demand for a particular item increases rapidly. Likewise, if all of one item is placed in a single FC, this may not be optimal because customers from various locations may want the item. Then, because the item will only be available in a single FC, costs to transfer the item from one FC to another FC may increase, and thus, the system will lose efficiency. Accordingly, the computerized embodiments directed to optimizing outbound flow of products provide novel and crucial systems for determining an optimal distribution of SKUs among FCs.

[0079] In yet another embodiment, one or more processors 305 may be able to implement one or more constraints, such as business constraints, to genetic algorithms. Constraints may include, for example, maximum capacity of each FC, item compatibility associated with each FC, costs associated with FC, or any other characteristics associated with each FC. Maximum capacity of each FC may include information associated with how many SKUs can be held at each FC. Item compatibility associated with each FC may include information associated with certain items that cannot be held at certain FCs due to size of the items, weight of the items, need for refrigeration, or other requirements associated with the items/SKUs. There may also be building restrictions associated with each FC that allow certain items to be held and prevent certain items to be held at each FC. Costs associated with each FC may include FC-to-FC transfer costs, cross-cluster shipment costs (e.g., shipping costs incurred from shipping items from multiple FCs), shipping costs incurred from cross-stocking items between FCs, unit per parcel (UPP) costs associated with having all SKUs in one FC, or any combination thereof.

[0080] In other embodiments, one or more processors 305 may cache one or more portions of the genetic algorithm in order to increase efficiency. For example, one or more portions of the genetic algorithm may be cached to obviate the need to re-run all portions of the algorithm each time a simulation is generated. One or more processors 305 may determine which portion(s) of the genetic algorithm may be cached based on whether there will be significant changes in each iteration. For example, some parameters may remain consistent each time a simulation is generated, while other parameters may change. The parameters that remain consistent each time will not need to be re-run each time a simulation is generated. Therefore, one or more processors 305 may cache these consistent parameters. For

example, maximum capacity at each FC may not change each time a simulation is generated, and thus, may be cached. On the other hand, parameters that may vary per simulation may include, for example, customer order profiles, customer interest in each SKU across regions, or stowing models. Customer order profiles may refer to behavior of customer orders across a statewide, regional, or nationwide network. For example, customer order profiles may refer to ordering patterns of customer orders across a statewide, regional, or nationwide network. Customer interest in each SKU may refer to the amount of customer demand for each item across a statewide, regional, or nationwide network. Stowing models may refer to models indicating where a particular item is placed, such as a particular spot in picking zone 209 or a particular space on a storage unit 210 in each FC. Stowing models may vary for each FC. By caching one or more portions of the genetic algorithm, one or more processors 305 may increase efficiency and reduce processing capacity.

[0081] In some embodiments, another constraint added to the simulation algorithm may comprise customer demand at each of the FCs. One or more processors 305 may be able to determine customer demand at each of the FCs by looking at order histories at each of the FCs. In other embodiments, one or more processors 305 may simulate customer demand at each of the FCs. For example, based on at least the order histories at each FC, one or more processors 305 may predict and/or simulate customer demand at each FC. Based on at least the simulated customer demand at each of the FCs, one or more processors 305 may allocate the SKUs among the FCs in order to optimize SKU allocation, SKU mapping, and outbound flow of products.

[0082] FIG. 4 is a flow chart illustrating an exemplary method 400 for simulating and optimizing outbound flow of products. This exemplary method is

provided by way of example. Method 400 shown in FIG. 4 can be executed or otherwise performed by one or more combinations of various systems. Method 400 as described below may be carried out by the optimization system 301, as shown in FIG. 3, by way of example, and various elements of that system are referenced in explaining the method of FIG. 4. Each block shown in FIG. 4 represents one or more processes, methods, or subroutines in the exemplary method 400. Referring to FIG. 4, exemplary method 400 may begin at block 401.

[0083] At block 401, one or more processors 305 may receive an initial set of solutions, comprising an initial distribution of SKUs among FCs. In some embodiments, each set of solutions may comprise a list of one or more SKUs to be stored in each FC. The one or more SKUs may be specific to each corresponding item, and thus, may be indicative of a manufacturer, material, color, packaging type, weight, or any other characteristic associated with each corresponding item. Each set of solutions may also comprise a number of total output in each FC based on the list of one or more SKUs to be stored in the corresponding FC. In some aspects, the distribution of SKUs among FCs in each set of solutions may be randomly generated. For example, whenever one or more processors 305 generate a set of solutions, one or more SKUs may be randomly distributed among the one or more FCs. Each time one or more processors 305 generate a set of solutions, each set of solutions may comprise a different distribution of SKUs among the FCs. In other aspects, a set of solutions may be received from another system or data store. For example, a set of solutions may be based on current distribution of SKUs.

[0084] As discussed above, each set of solutions may also take into consideration one or more constraints associated with each FC. For example, one or more processors 305 may apply one or more constraints (e.g., maximum capacity of

each FC, item compatibility associated with each FC, costs associated with FC, or any other characteristics associated with each FC) when generating a set of solutions. As such, the set of solutions (e.g., distribution of SKUs among FCs) may be randomly generated while also taking into consideration various constraints related to each FC.

[0085] Once the initial set of solutions is received, method 400 may proceed to block 402. At block 402, one or more processors 305 may run a simulation of each solution in the initial set of solutions. For example, one or more processors 305 may simulate the outbound flow of products based on the initial distribution of SKUs among FCs in the initial set of solutions. One or more processors 305 may run a simulation of each solution in the initial set of solutions, in order to determine how well the initial distribution of SKUs among FCs performs. In some embodiments, one or more processors 305 may obtain output data by running a simulation of each solution in the initial set of solutions. The output data may comprise the total output at each FC in each set of solutions.

[0086] Once a simulation for each solution in the initial set of solutions is run, method 400 may proceed to block 403. At block 403, one or more processors 305 may evaluate the fitness of the initial set of solutions received. For example, one or more processors 305 may evaluate whether the initial set of solutions for placement of SKUs among FCs is optimal. If one or more processors 305 determines that the solutions in the initial simulation are optimal, method 400 may proceed to block 403A. At block 403A, one or more processors 305 may determine that the termination condition has been reached because the initial set of solutions is optimal. If one or more processors 305 determine that the initial set of solutions is optimal and the termination condition has been reached at block 403A, then method 400 may

proceed to block 407, at which one or more processors 305 may terminate method 400. As will be discussed in detail below, evaluating the fitness of the initial set of solutions may comprise, for example, calculating total output at each FC, calculating a participation ratio of each FC for each solution, or determining a score for each solution based on the participation ratio. A total output at each FC may comprise a total output of items/products from each FC. A participation ratio of an FC may indicate a percentage of the total output of a network of FCs. For example, such a network of FCs may be statewide, regionwide, or nationwide.

[0087] If one or more processors 305 determine that the initial simulation is not yet optimal and the termination condition has not been reached at block 403A, then method 400 may continue to block 404. For example, if the participation ratio at one or more FCs increases by a predetermined threshold, then one or more processors 305 may determine that the initial set of solutions is optimal. The predetermined threshold may be between 0.5% and 10%. By way of example, if there is a 2% increase in participation ratio of one or more FCs, the one or more processors 305 may determine that the initial set of solutions is optimal. However, if the participation ratio at one or more FCs does not increase by a predetermined threshold, one or more processors 305 may determine that the simulation is not optimal, and thus, method 400 may continue to block 404.

[0088] At block 404, one or more processors 305 may select one or more solutions from the initial set of solutions to feed a simulation algorithm (e.g., a genetic algorithm) to generate one or more additional solutions. The one or more solutions selected and fed to the simulation algorithm may remain constant in the one or more additional solutions generated.

[0089] Once the one or more new, additional solutions are generated, method 400 may continue to block 405. At block 405, one or more processors 305 may again evaluate the fitness of the one or more new solutions. Similar to block 403, one or more processors 305 may evaluate the fitness of the one or more new simulations by evaluating whether the one or more new solutions for placement of SKUs among FCs is optimal. For example, evaluating the fitness of the one or more new solutions may comprise, for example, calculating total output at each FC, calculating a participation ratio of each FC, or determining a score for each solution based on the participation ratio calculated for each solution.

[0090] After evaluating the fitness of the one or more new solutions, method 400 may continue to block 406. At block 406, one or more processors 305 may determine whether a termination condition has been reached. In some embodiments, the termination condition may be reached if one or more processors 305 determine that a participation ratio at one or more FCs has increased by a predetermined threshold. For example, as discussed above, if one or more processors 305 determine that a participation ratio at one or more FCs has increased between 0.5% and 10%, then one or more processors 305 may determine that the simulation is optimal and that the termination condition has been reached. In other embodiments, if there is a 2% increase in participation ratio of one or more FCs, the one or more processors 305 may determine that the termination condition has been reached.

[0091] If one or more processors 305 determine that the termination condition has been reached, method 400 may proceed to block 407. At block 407, one or more processors 305 may terminate the optimization. For example, one or more processors 305 may stop running the simulation algorithm. However, if one or more processors 305 determine that the termination condition has not been reached,

method 400 may return to block 404, at which one or more processors 305 may add the one or more new solutions generated to the initial set of solutions received to form a new set of solutions. Then, one or more processors 305 may again select one or more solutions from the new set of solutions and feed the simulation algorithm with the selected one or more solutions from the new set of solutions to generate one or more additional solutions. One or more processors 305 may repeat this process until the termination condition has been reached. For example, one or more processors 305 may repeat the process until an increase in participation ratio at one or more FCs reaches a predetermined threshold, such as a 2% increase.

[0092] FIG. 5 is a flow chart illustrating method 400 (in FIG. 4) for simulating and optimizing outbound flow of products in further detail. This exemplary method is provided by way of example. Method 500 shown in FIG. 5 can be executed or otherwise performed by one or more combinations of various systems. Method 500 as described below may be carried out by the optimization system 301, as shown in FIG. 3, by way of example, and various elements of that system are referenced in explaining the method of FIG. 5. Each block shown in FIG. 5 represents one or more processes, methods, or subroutines in the exemplary method 500. Referring to FIG. 5, exemplary method 500 may begin at block 501.

[0093] At block 501, similar to block 401 in FIG. 4, one or more processors 305 may receive an initial set of solutions comprising an initial distribution of SKUs among FCs. In some embodiments, the initial set of solutions may comprise a list of one or more SKUs to be stored in each FC. The one or more SKUs may be specific to each corresponding item, and thus, may be indicative of a manufacturer, material, color, packaging type, weight, or any other characteristic associated with each corresponding item. In some aspects, each set of solutions may be randomly

generated. For example, whenever one or more processors 305 generate a set of solutions, one or more SKUs may be randomly distributed among the one or more FCs. Each time one or more processors 305 generate a set of solutions, each simulation may comprise a different distribution of SKUs among the FCs. For example, each set of solutions may comprise a different distribution of SKUs among FCs.

[0094] As discussed above, each set of solutions may also take into consideration one or more constraints associated with each FC. For example, one or more processors 305 may apply one or more constraints (e.g., maximum capacity of each FC, item compatibility associated with each FC, costs associated with FC, or any other characteristics associated with each FC) when generating each set of solutions. As such, the set of solutions (e.g., distribution of SKUs among FCs) may be randomly generated while also taking into consideration various constraints related to each FC.

[0095] Once the initial set of solutions is received, method 500 may proceed to block 502. At block 502, one or more processors 305 may run a simulation of each solution in the initial set of solutions. For example, one or more processors 305 may simulate the outbound flow of products based on the initial distribution of SKUs among FCs in the initial set of solutions. One or more processors 305 may run a simulation of each solution in the initial set of solutions, in order to determine how well the initial distribution of SKUs among FCs performs. In some embodiments, one or more processors 305 may obtain output data by running a simulation of each solution in the initial set of solutions. The output data may comprise the total output at each FC in each set of solutions. For example, the output data may comprise a

number of total output in each FC based on the list of one or more SKUs to be stored in the corresponding FCs.

[0096] Once a simulation for each solution in the initial set of solutions is run, method 500 may proceed to block 503. At block 503, one or more processors 305 may calculate a participation ratio for each solution in the initial set of solutions. In order to calculate the participation ratio of each solution, one or more processors 305 may determine the total output of items/products from each FC, as well as the total output of items/products of the network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). A participation ratio of an FC may indicate a percentage of the total output of a network of FCs (e.g., statewide, regionwide, or nationwide). .

[0097] Once the participation ratio for each solution has been calculated, method 500 may proceed to block 504. At block 504, based on the calculated participation ratios, one or more processors 305 may determine a score for each solution in the initial set of solutions. The score may be indicative of the increase in participation ratio for each solution and each FC. For example, one or more processors 305 may determine a difference between the initial output at each FC (e.g., in the initial simulation) and the new output (e.g., in the new simulation), as well as a difference between the initial participation ratio (e.g., in the initial simulation) and the new participation ratio (e.g., in the new simulation). Based on the difference between the calculated participation ratios, one or more processors 305 may determine whether there was an increase or a decrease in the participation ratio of each FC. Based on the difference in the participation ratios, one or more processors 305 may assign a score to each solution. The assigned score may be indicative of how much the new solution was able to increase or decrease the participation ratio

for each FC (e.g., contribution of each FC to the total output of the network of FCs). A participation ratio of an FC may indicate a percentage of the total output of a network of FCs (statewide, regionwide, or nationwide).

[0098] Once the scores are determined, method 500 may proceed to block 505. At block 505, one or more processors 305 may select at least one solution with the highest determined score. For example, one or more processors 305 may select at least one solution in the initial set of solutions with the highest determined score. In some embodiments, one or more processors 305 may select between 1 and 10 solutions in the initial set of solutions. The selected solution(s) may comprise solution(s) that best improved the corresponding FC's contribution to the overall output of the network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). In some embodiments, one or more processors 305 may use an algorithm to determine the solution(s) to be selected as input to generate one or more additional solutions. For example, the algorithm may determine a probability of each solution to be selected. By way of example, based on the algorithm, solution(s) with the highest determined score may have a higher probability to be selected than other solution(s) in the set of solutions with a lower determined score. Accordingly, solution(s) with the highest determined score may have higher probability to be selected as input to generate one or more additional solutions. The algorithm used to determine the probability of each solution to be selected may be as follows:

$$P_i = \frac{S_i}{\sum S_i}$$

where S_i is the score of solution i , and P_i is the probability of solution i being selected.

[0099] Method 500 may proceed to block 506, at which one or more processors 305 may feed the selected solution(s) with the highest determined score

into a simulation algorithm (e.g., a genetic algorithm). At block 507, one or more processors 305 may generate one or more additional solutions. For example, one or more processors 305 may add the selected solution(s) (in block 506) to the initial set of solutions received (in block 501) to generate a new set of solutions. In some embodiments, the selected solution(s) with the highest determined score may remain constant in the new set of solutions generated, while one or more other solutions in the new set of solutions may again be randomly generated while taking one or more constraints at the FCs into consideration. Accordingly, one or more processors 305 may select between 1 and 10 solutions with the highest determined scores and feed them into the simulation algorithm to generate one or more additional solutions. By feeding a number of solutions to the simulation algorithm, the process cuts down on processor load and increases the efficiency, compared to systems that would generation a larger number of possible solutions (e.g., all possible combinations of SKUs) each time.

[00100] The solutions that are fed into the simulation algorithm may remain constant in the additional solutions generated. For example, the selected solutions fed into the simulation algorithm may comprise a particular distribution of SKUs among corresponding FCs. The distribution of SKUs among the FCs in the selected solutions may remain unchanged in the additional solutions generated.

[00101] Once the one or more additional solutions are generated at block 507, method 500 may continue to block 508. Similar to block 502, at block 508, one or more processors 305 may run a simulation of the one or more additional solutions generated (in block 507). For example, one or more processors 305 may run a simulation of the one or more additional solutions, in order to determine how well the distribution of SKUs among FCs in the one or more additional solutions

performs. In some embodiments, one or more processors 305 may obtain output data by running a simulation of each of the one or more additional solutions. The output data may comprise the total output at each FC in each of the one or more additional solutions. For example, the output data may comprise a number of total output in each FC based on the list of one or more SKUs to be stored in the corresponding FCs.

[00102] Once a simulation of the one or more additional solutions is run, method 500 may continue to blocks 509 and 510. Similar to block 503, at block 509, one or more processors 305 may calculate the participation ratio for each of the one or more additional solutions. Similar to block 504, at block 510, one or more processors 305 may determine a score for each of the one or more additional solutions based on the participation ratio.

[00103] After evaluating the fitness of the one or more additional solutions (as discussed above with respect to, for example, block 403 in Fig. 4), method 500 may continue to block 511. At block 511, one or more processors 305 may determine whether a termination condition has been reached. In some embodiments, the termination condition may be reached if one or more processors 305 determine that a participation ratio at one or more FCs has increased by a predetermined threshold. For example, as discussed above, if one or more processors 305 determine that a participation ratio at one or more FCs has increased between 0.5% and 10%, then one or more processors 305 may determine that the simulation is optimal and that the termination condition has been reached. In other embodiments, if there is a 2% increase in participation ratio of one or more FCs, the one or more processors 305 may determine that the termination condition has been reached.

[00104] If one or more processors 305 determine that the termination condition has been reached, method 500 may proceed to block 512. At block 512, one or more processors 305 may select the best-performing solution with the highest score and terminate the optimization process. For example, one or more processors 305 may select a solution that has the highest determined score (e.g., highest increase in participation ratio). The selected solution may be the best-performing solution.

[00105] On the other hand, if in block 511, one or more processors 305 determine that the termination condition has not been reached, method 500 may proceed to block 511A. At block 511A, one or more processors 305 may add the one or more additional solutions generated (in block 507) to the initial set of solutions received (in block 501) to generate a new set of solutions. Then, method 500 may return to block 505 with the new set of solutions, at which one or more processors 305 may select at least one solution from the new set of solutions with the highest determined scores.

[00106] Once the at least one solution is selected, method 500 may proceed to block 506 again, at which one or more processors feed the selected solution(s) from the new set of solutions into the simulation algorithm to generate one or more additional solutions at block 507. In some embodiments, the selected solution(s) from the new set of solutions may be one or more of the additional solutions generated (at block 507) and/or they may be one or more of the solutions in the initial set of solutions received (at block 501). One or more processors 305 may repeat the process at blocks 505-511A until the termination condition has been reached. For example, one or more processors 305 may repeat the process until an

increase in participation ratio at one or more FCs reaches a predetermined threshold, such as a 2% increase.

[00107] In other embodiments, one or more processors 305 may repeat the process until the number of times the process has been repeated exceeds a predetermined threshold. Accordingly, one or more processors 305 may terminate the simulation process after the process has been repeated a predetermined number of times. For example, if the number of times one or more processors 305 has repeated the process, e.g., generated additional simulations, exceeds a predetermined threshold, one or more processors 305 may terminate method 500, even if the termination condition has not been reached. In some embodiments, one or more processors 305 may proceed to block 511A and return to blocks 505-507 to generate one or more additional solutions about 10 times, 9 times, 7 times, 5 times, or 3 times before terminating method 500.

[00108] If the one or more processors 305 determine that the termination condition has been reached at block 511 and the one or more processors 305 select the best-performing solution at block 512, method 500 may proceed to block 513. At block 513, one or more processors 305 may allocate the SKUs among the FCs based on the best-performing solution. As discussed previously, one or more processors 305 may allocate the SKUs among FCs according to the distribution simulated in the best-performing solution. By allocating the SKUs among FCs in accordance with the best-performing solution, one or more processors 305 may optimize outbound flow of products.

[00109] Referring now to FIG. 6, a diagram of an exemplary summary page that includes results of a generated simulation is shown. As discussed above, one or more processors 305 may generate a simulation, comprising a set of

solutions for each FC. One or more processors 305 may transmit the results of a generated simulation to one or more systems in system 100. For example, one or more processors 305 may transmit the results of a generated simulation to internal front end system 105 to display the results. An exemplary summary page 600 of an exemplary simulation is shown in FIG. 6. As seen in FIG. 6, one or more processors 305 may determine the total output at each FC in the initial simulation (e.g., "Before Output") as well as the total output at each FC in the new simulation (e.g., "After Output"). In some embodiments, one or more processors 305 may further determine a difference between the total output in the initial simulation and the total output in the new simulation (e.g., "Variance"). By calculating the difference, one or more processors 305 may determine whether the new simulation has improved upon each FC's initial total output, as well as each FC's initial contribution to the overall output of the network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). In some aspects, one or more processors 305 may calculate the variance in percentage.

[00110] As discussed above, one or more processors 305 may further calculate the participation ratio of each FC in the initial simulation and in the new simulation. The participation ratio may be indicative of each FC's contribution to the total output of a network of FCs (e.g., a nationwide network, a regionwide network, or a statewide network). A participation ratio of an FC may indicate a percentage of the total output of a network of FCs (statewide, regionwide, or nationwide). In some embodiments, one or more processors 305 may determine a difference between the participation ratio of each FC in the initial simulation (e.g., "Before Participation Ratio") and in the new simulation (e.g., "After Participation Ratio"). Based on the difference between the participation ratios of each FC, one or more processors 305

may determine a score for each solution associated with each FC. By way of example, the solution that raised the participation ratio of a particular FC by the greatest number may be given a maximum score. Likewise, the solution that decreased the participation ratio of a particular FC by the greatest number may be given a minimum score. For example, a solution that raises the participation ratio of an FC by about 2% may be given a maximum score.

[00111] In other embodiments, one or more processors 305 may determine a score for each solution based at least on the variance. Because variance is correlated with the change in each FC's participation ratio, one or more processors 305 may give a maximum score to a solution that returned the highest variance and a minimum score to a solution that returned the lowest variance. As discussed above, one or more processors 305 may select one or more solutions with the highest scores and feed those solutions to a simulation algorithm to generate additional simulations. In some embodiments, one or more processors 305 may select two solutions with the top two highest scores, or three solutions with the top three highest scores. The solutions that are selected and fed into the simulation algorithm may be referred to as the "best-performing simulation."

[00112] While the present disclosure has been shown and described with reference to particular embodiments thereof, it will be understood that the present disclosure can be practiced, without modification, in other environments. The foregoing description has been presented for purposes of illustration. It is not exhaustive and is not limited to the precise forms or embodiments disclosed. Modifications and adaptations will be apparent to those skilled in the art from consideration of the specification and practice of the disclosed embodiments. Additionally, although aspects of the disclosed embodiments are described as being

stored in memory, one skilled in the art will appreciate that these aspects can also be stored on other types of computer readable media, such as secondary storage devices, for example, hard disks or CD ROM, or other forms of RAM or ROM, USB media, DVD, Blu-ray, or other optical drive media.

[00113] Computer programs based on the written description and disclosed methods are within the skill of an experienced developer. Various programs or program modules can be created using any of the techniques known to one skilled in the art or can be designed in connection with existing software. For example, program sections or program modules can be designed in or by means of .Net Framework, .Net Compact Framework (and related languages, such as Visual Basic, C, etc.), Java, C++, Objective-C, HTML, HTML/AJAX combinations, XML, or HTML with included Java applets.

[00114] Moreover, while illustrative embodiments have been described herein, the scope of any and all embodiments having equivalent elements, modifications, omissions, combinations (e.g., of aspects across various embodiments), adaptations and/or alterations as would be appreciated by those skilled in the art based on the present disclosure. The limitations in the claims are to be interpreted broadly based on the language employed in the claims and not limited to examples described in the present specification or during the prosecution of the application. The examples are to be construed as non-exclusive. Furthermore, the steps of the disclosed methods may be modified in any manner, including by reordering steps and/or inserting or deleting steps. It is intended, therefore, that the specification and examples be considered as illustrative only, with a true scope and spirit being indicated by the following claims and their full scope of equivalents.

CLAIMS

What is claimed is:

1. A computer-implemented system for optimizing allocation of products, the system comprising:
a memory storing instructions; and
at least one processor configured to execute the instructions to:
receive an initial set of solutions, the initial set of solutions comprising
an initial distribution of the plurality of stock keeping units
(SKUs) among the plurality of fulfillment centers (FCs);
run a simulation of each solution of the initial set of solutions;
calculate a participation ratio for each solution of the initial set of
solutions;
determine a score for each solution of the initial set of solutions based
on the calculated participation ratio;
select at least one solution with a highest determined score to feed a
simulation algorithm to generate one or more additional
solutions; and
modify an allocation of the plurality of SKUs among the plurality of FCs
based on a best-performing solution, wherein the best-
performing solution has the highest determined score among all
solutions generated.
2. The system of claim 1, wherein each of the plurality of SKUs is indicative of at least one of a manufacturer, material, size, color, packaging, type, or weight of a product.

3. The system of claim 1, wherein the best-performing solution raises the participation ratio for at least one FC by 2%.
4. The system of claim 1, wherein the simulation algorithm comprises at least one constraint, the constraint comprising at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs.
5. The system of claim 1, wherein selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions comprises changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions.
6. The system of claim 1, wherein the initial distribution of the plurality of SKUs among the plurality of FCs is randomly generated.
7. The system of claim 1, wherein the participation ratio for each of the solutions is indicative of a percentage of FCs that contributed to a total output of products from a network of FCs.
8. The system of claim 1, wherein the at least one processor is further configured to execute the instructions to:
simulate customer demand at each of the plurality of FCs; and

allocate the plurality of SKUs among the plurality of FCs based on the simulated customer demand.

9. The system of claim 1, wherein the at least one processor is further configured to execute the instructions to cache at least a portion of the simulation algorithm.
10. The system of claim 9, wherein the cached portion of the simulation algorithm comprises at least one constraint that remains substantially constant with each run of the simulation algorithm.
11. A computer-implemented method for optimizing allocation of products, the method comprising:
 - receiving an initial set of solutions, the initial set of solutions comprising an initial distribution of the plurality of stock keeping units (SKUs) among the plurality of fulfillment centers (FCs);
 - running a simulation of each solution of the initial set of solutions;
 - calculating a participation ratio for each solution of the initial set of solutions;
 - determining a score for each solution of the initial set of solutions based on the calculated participation ratio;
 - selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions; and
 - modifying an allocation of the plurality of SKUs among the plurality of FCs based on a best-performing solutions, wherein the best-performing

solutions has the highest determined score among all solutions generated.

12. The method of claim 11, wherein the participation ratio for each of the solutions is indicative of a percentage of FCs that contributed to a total output of products from a network of FCs.
13. The method of claim 11, wherein the best-performing solution raises the participation ratio for at least one FC by 2%.
14. The method of claim 11, wherein the simulation algorithm comprises at least one constraint, the constraint comprising at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs.
15. The method of claim 11, wherein selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions comprises changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions.
16. The method of claim 15, wherein the initial distribution of the plurality of SKUs among the plurality of FCs is randomly generated.
17. The method of claim 11, further comprising:

simulating customer demand at each of the plurality of FCs; and
allocating the plurality of SKUs among the plurality of FCs based on the
simulated customer demand.

18. The method of claim 11, further comprising caching at least a portion of the simulation algorithm.
19. The method of claim 18, wherein the cached portion of the simulation algorithm comprises at least one constraint that remains substantially constant with each run of the simulation algorithm.
20. A computer-implemented system for optimizing allocation of products, the system comprising:
a memory storing instructions; and
at least one processor configured to execute the instructions to:
receive an initial set of solutions, the initial set of solutions comprising
an initial distribution of the plurality of stock keeping units
(SKUs) among the plurality of fulfillment centers (FCs) that is
randomly generated;
run a simulation of each solution of the initial set of solutions;
calculate a participation ratio for each solution of the initial set of
solutions;
determine a score for each solution of the initial set of solutions based
on the calculated participation ratio;

select at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions, wherein:


the simulation algorithm comprises at least one constraint, the constraint comprising at least one of customer demand at each of the FCs, maximum capacities of the FCs, compatibility with FCs, or transfer costs between FCs;

at least one constraint that remains substantially constant with each run of the simulation algorithm is cached; and

selecting at least one solution with a highest determined score to feed a simulation algorithm to generate one or more additional solutions comprises changing, via the simulation algorithm, at least one parameter associated with the at least one solution selected to generate the one or more additional solutions;

simulate customer demand at each of the plurality of FCs; and

modify an allocation of the plurality of SKUs among the plurality of FCs based at least on the simulated customer demand and on a best-performing solution, wherein the best-performing solution raises the participation ratio for at least one FC by 2%.



[login](#) [Sign Up](#) [Service center](#)

Category

Cheese

?

[My Orders](#) [Shopping Cart](#)

all '**Cheese**' (65,586)

filter

☐ Fast Delivery

☐ Imported Product

category

All

Food

Silverware

Kitchen utensils

Home electronics digital

Household goods

[View more](#)

brands

Local Milk

Daily dairy

Cattle and trees

[View more](#)

scope

All stars

4 or more

3 or more

2 or more

1 or more

Gift Cards

65,586 results for 'Cheese'

Related searches: [Sliced cheese](#) [baby cheese](#) [cheddar cheese](#) [string cheese](#) [butter](#) [pizza cheese](#) [cream cheese](#) [cheese stick](#) [cubed cheese](#) [parmesan cheese](#)

6 per page




 CHEDDAR	 LOCAL FARM MILK	
FREE Shipping Sliced cheese, 18g, 100 pieces (88 won per 10 g) Morning (Thursday) (1294)	Mozzarella cheese, 1kg, 2 pieces  (103 won per 10 g) Tomorrow (Wed) (285)	100 grams of cheddar sliced cheese, 18 grams, 100 pieces (73 won per 10 g) Morning (Thursday) (862)
 REAL GRATED PARMESAN		 Cheese Heads String
Grated Parmesan Cheese, 85g, 1 piece  (389 won per 10g) Tomorrow (Wed) (839)	Mozzarella cheese, 1 kg, 1 (85 won per 10g) Morning (Thursday) (379)	FREE Shipping 1.36 kg of string cheese Morning (Thursday) (337)

FIG. 1B

[Favorites](#)
[Application](#)

[login](#)
[Sign Up](#)
[Service center](#)

[My Account](#)
[Shopping Cart](#)

[Shipments](#)
[Fast Shipments](#)
[Christmas](#)
[Gold deals](#)
[Regular delivery](#)
[Events / Coupons](#)
[Planned Exhibition](#)

[Gift Cards](#)

[Home](#) > [Food](#) > [Daily products / ice cream](#) > [Cheese](#) > [Fresh cheese](#) > [Mozzarella](#)

mozzarella cheese

285 Reviews 20,000 won

FREE Shipping
Tomorrow (Wed) 11/28 Arrival Guarantee

Weight per piece x Quantity : **1kg x 2 pieces**

1

Add to cart

Buy now

- Country of origin: See product description
- Shelf Life: 2019-11-04
- Total quantity: 2
- Cheese form: crushed (powder)
- Item Number: 23532 - 3432551

Products purchased by other customers

Rosé spaghetti sauce, 600g, 2...
6,500 won (54 won per 10g) (3,721)

Chunky Tomato Pasta...
3,800 won (86 won per 10g) (545)

Grated Parmesan cheese,
6,460 won (285 won per 10g) (1,330)

Bacon and Mushroom Cream Pasta Sauce
4,870 won (108 won per 10g) (3,193)

Chili sauce, 295ml, 1
2,370 won (80 won per 10ml) (2,552)

Hot sauce, **2,340 won** (66 won per 10ml) (245)

Product Details

Reviews (285)

Contact Us

Shipping & Returns

Required notation information

Type of food	Natural cheese / frozen products	Producers and Locations	Cheese Corp. / Republic of Korea
Date of manufacture, shelf life or quality maintenance	Shelf Life: Products manufactured on or after November 04, 2019 : Manufactured goods after May 19, 2018	Capacity (weight), quantity by packing unit	1kg, 2 pieces
Ingredients and	Content reference	nutrient	None

FIG. 1C

11/28/2018 Shopping Cart

General Purchasing (1)

Periodic Delivery (0)

☒ Select All
 Product Information
 Item Amount shipping fee

Rocket shipping products free shipping

☒

 Mozzarella cheese, 1kg, 2 pieces
 Tomorrow (Thursday) 11/29
 Arrival guarantee (order before 12 pm)
 

1▼

 free
 20,510 won

Even if you add other rocket shipping products, free shipping available
 shipping Free Order amount
 \$20.00


☒ Select All (1/1)
 Delete all
 sold out / discontinued products clear all
 interest payment

\$__00


Continue shopping

Buy now

Customers who bought this product also purchased


 Rosé spaghetti sauce,
 600g, 2 pieces
6,500 won
 (54 won per 10g)
 


 Napoli Chunky Tomato
 Pasta Sauce,
3,800 won
 (86 won per 10g)
 


 REAL
 GRATED
 PARMESAN
 Grated Parmesan
 cheese,
6,460 won
 (285 won per 10g)
 

1/5


 CARNIA
 CREAM
 Bacon and Mushroom Cream
 Pasta Sauce,
4,870 won
 (108 won per 10g)
 

FIG. 1D

Order / PaymentShopping Cart> **Order Payment**> Order Completion

Buyer Information
name
e-mail
Mobile Phone 0123456789
Number

Recipient information
name
Shipping address
Contact
Delivery Request Front door

Shipping 1 out of 1
Tomorrow (Thursday) 11/29 arrival guarantee
Mozzarella cheese, 1kg, 2 pieces 1 quantity / free shipping  Fast Delivery

Billing Information
Total product price \$20.00
discount coupon 0 No applicable discount coupons available.
shipping fee 0
MyCash 0
Total payment amount \$20.00 – MyCash to be credited \$0.40
Payment Method ☒ ☐ Rocket Transfer ☐ ☐ Rocket credit/check card ☐ Credit/Check Card
☐ Cellphone ☐ Bank transfer (virtual account)

Select bank

☐ I agree to use future payments with the selected payment method (Selection)

Cash receipts
☐ Apply for cash receipt

*A cash receipt will be issued for the amount of cash deposited at the time of settlement of cash.

I have confirmed the order above and agree to the payment.

FIG. 1E




FIG. 2




FIG. 3




FIG. 4




FIG. 5

600
5

Summary of Simulation Results

FC Name	Before Output	After Output	Variance	Variance %	Before Participation Ratio	After Participation Ratio
ABC	17521	17526	5	0.03	1.48	1.48
DEF1	41815	31363	-10452	-25.0	3.53	2.65
DEF2	170783	169693	-1090	-0.64	14.41	14.32
GHI	294000	294142	142	0.05	24.81	24.82
JKL3	6842	6843	1	0.01	0.58	0.58
MNO1	19244	19205	-39	-0.2	1.63	1.62
PQR4	304698	304574	-124	-0.04	25.71	25.7
PQR5	14335	14328	-7	-0.05	1.21	1.21
PQR7	6160	6164	4	0.06	0.52	0.52
STUV	50211	62143	11932	23.76	4.24	5.24
WXY1	71915	72343	428	0.6	6.07	6.1
ZAB1	32127	32116	-11	-0.03	2.71	2.71
CDE1	81924	81739	-185	-0.23	6.91	6.9
FG1	1358	1358	0	0.0	0.11	0.11
FG2	1160	1162	2	0.17	0.1	0.1
FG3	6089	5626	-463	-7.6	0.51	0.47
FG4	3236	3236	0	0.0	0.27	0.27
FG5	1658	1658	0	0.0	0.14	0.14
FG6	63	63	0	0.0	0.01	0.01
FG7	792	792	0	0.0	0.07	0.07
FG8	3577	3441	-136	-3.8	0.3	0.29

FIG. 6

A. CLASSIFICATION OF SUBJECT MATTER**G06Q 10/08(2012.01)i, G06Q 10/06(2012.01)i, G06Q 10/10(2012.01)i, G06Q 30/06(2012.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G06Q 10/08; G06F 15/02; G06F 17/60; G06F 19/00; G06K 7/10; G06Q 10/06; G06Q 30/02; G06Q 99/00; G06Q 10/10; G06Q 30/06

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: optimizing, allocation, product, solution, score, best

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2006-0143030 A1 (DAVID L. WERTHEIMER) 29 June 2006 See paragraphs [0016]-[0018], [0026]-[0032], [0042]-[0047] and claims 1-3, 7, 25-26.	1-20
Y	KR 10-2007-0067503 A (NONG SIM CO., LTD.) 28 June 2007 See claims 1-5 and figures 1-2.	1-20
Y	JP 2001-266048 A (HITACHI LTD.) 28 September 2001 See claims 1, 4 and figures 1, 4.	1-20
A	US 2019-0012634 A1 (WALMART APOLLO, LLC) 10 January 2019 See paragraphs [0018]-[0033], claims 1-2 and figure 1.	1-20
A	US 2017-0200104 A1 (ORACLE INTERNATIONAL CORPORATION) 13 July 2017 See claims 1-3, 6 and figures 1-3.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"D" document cited by the applicant in the international application

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

30 June 2020 (30.06.2020)

Date of mailing of the international search report

30 June 2020 (30.06.2020)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsu-ro, Seo-gu, Daejeon, 35208, Republic of Korea



Facsimile No. +82-42-481-8578

Authorized officer

KANG, Min Jeong



Telephone No. +82-42-481-8131

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/IB2020/052166

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2006-0143030 A1	29/06/2006	US 7930050 B2	19/04/2011
KR 10-2007-0067503 A	28/06/2007	KR 10-0782921 B1	07/12/2007
JP 2001-266048 A	28/09/2001	None	
US 2019-0012634 A1	10/01/2019	US 10074070 B2	11/09/2018
		US 2016-0092831 A1	31/03/2016
US 2017-0200104 A1	13/07/2017	CN 108369710 A	03/08/2018
		JP 2019-505914 A	28/02/2019
		JP 6679734 B2	15/04/2020
		US 10528903 B2	07/01/2020
		US 2017-0200180 A1	13/07/2017
		WO 2017-120395 A1	13/07/2017