

(12) **United States Patent**
An et al.

(10) **Patent No.:** **US 10,978,494 B2**
(45) **Date of Patent:** **Apr. 13, 2021**

(54) **DISPLAY INCLUDING PLURALITY OF WIRING LAYERS IN BENDING REGION**

(71) Applicant: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(72) Inventors: **Jungchul An**, Suwon-si (KR); **Suyeon Kim**, Suwon-si (KR); **Sangseol Lee**, Suwon-si (KR); **Kwangtai Kim**, Suwon-si (KR); **Hyungsup Byeon**, Suwon-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/269,981**

(22) Filed: **Feb. 7, 2019**

(65) **Prior Publication Data**
US 2019/0252412 A1 Aug. 15, 2019

(30) **Foreign Application Priority Data**
Feb. 9, 2018 (KR) 10-2018-0016140

(51) **Int. Cl.**
H01L 23/48 (2006.01)
H01L 21/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01L 27/124** (2013.01); **H01L 27/1218** (2013.01); **H01L 27/1244** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H01L 27/3276
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,274,559 B2 * 3/2016 Prushinskiy G06F 1/1652
345/55
9,276,055 B1 * 3/2016 Son H01L 27/3288
9,659,966 B2 * 5/2017 Kwak H01L 27/1218
(Continued)

FOREIGN PATENT DOCUMENTS

KR 10-0671660 B1 1/2007
KR 10-1740192 B1 5/2017
(Continued)

OTHER PUBLICATIONS

International Search Report dated May 7, 2019, issued in International Application No. PCT/KR2019/001558.

(Continued)



Primary Examiner — Calvin Lee

(74) *Attorney, Agent, or Firm* — Jefferson IP Law, LLP

(57) **ABSTRACT**

A display including a bending region is provided. The display includes a pixel layer including a plurality of pixel and a substrate disposed under the pixel layer and including a first area on which the pixel layer is disposed and a second area extending out of the pixel layer from the first area, at least a partial area of the second area being bendable, wherein the substrate includes: a wiring layer including at least one first wiring electrically connected with at least one pixel of the plurality of pixels and connected from the first area to the second area, and at least one second wiring disposed in the at least partial area and electrically connected with the at least one first wiring in the second area. Further, other embodiments may be possible.

18 Claims, 12 Drawing Sheets



- (51) **Int. Cl.**
H01L 27/12 (2006.01)
H01L 27/32 (2006.01)
H01L 51/00 (2006.01)

2014/0138637 A1 5/2014 Yang et al.
 2016/0079336 A1 3/2016 Youn et al.
 2017/0199619 A1 7/2017 Lee et al.
 2017/0262109 A1 9/2017 Choi et al.
 2017/0323934 A1 11/2017 Ki et al.
 2017/0345877 A1 11/2017 Hwang

- (52) **U.S. Cl.**
 CPC *H01L 27/323* (2013.01); *H01L 27/3276*
 (2013.01); *H01L 51/0097* (2013.01)

FOREIGN PATENT DOCUMENTS

- (58) **Field of Classification Search**
 USPC 438/461, 617; 257/676, 736, 786
 See application file for complete search history.

KR 10-2017-0083668 A 7/2017
 KR 10-2017-0106621 A 9/2017

- (56) **References Cited**

OTHER PUBLICATIONS

U.S. PATENT DOCUMENTS

9,818,974 B2* 11/2017 Kwon H01L 27/323
 9,977,466 B2* 5/2018 Kwon G06F 1/1652
 361/749

European Search report dated Feb. 23, 2021, issued in European
 Application No. 19751205.6-1230.

* cited by examiner




FIG. 1




FIG.2A




FIG.2B




FIG.2C




FIG.3A




FIG.3B




FIG.3C




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG. 10




FIG. 11

DISPLAY INCLUDING PLURALITY OF WIRING LAYERS IN BENDING REGION

CROSS-REFERENCE TO RELATED APPLICATION(S)

This application is based on and claims priority under 35 U.S.C. § 119(a) of a Korean patent application number 10-2018-0016140, filed on Feb. 9, 2018, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

The disclosure relates to a display. More particularly, the disclosure relates to a display including a bending region.

2. Description of Related Art

An electronic device may refer to a device that performs specific functions in accordance with programs installed therein, such as an electronic notepad, a mobile multimedia player, a mobile communication terminal, a tablet personal computer (PC), a video/sound device, a desktop/laptop computer, and an automobile navigation system, including home appliances. For example, electronic devices can output information stored therein using sound or images. As electronic devices have become highly integrated and high-speed and large-capacity wireless communication has become popular, recently it has become possible to integrate various functions into a single electronic device.

Portable electronic devices include a window and users can see images displayed on the display in the electronic devices through the window from the outside. The window may include a transparent area and a bezel area (e.g., a dead space) surrounding the transparent area. The bezel area is opaque, so it can hide wiring and components under the bezel area.

Portable electronic devices may be formed such that the transparent area of a window is large and the bezel area (e.g., dead space) is small so as to achieve a large screen. The bezel area, which is an area for arranging wiring connected to electrodes of a display or a touch panel in the electronic device, can hide the wiring and provide a gap that can mitigate electromagnetic interference among the wires. For example, the larger the bezel area, the larger the gaps between the wiring may be, that is, electromagnetic interference can be mitigated, or signals can be stably transmitted by sufficiently securing line width of the wirings. However, as the bezel area is increased, the area in which images can be output may be reduced.

The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

Wiring connected to a display or a touch panel may be arranged substantially on a substrate (e.g., a flexible printed circuit board) and may be connected to a driving circuit (e.g., a display driver integrated circuit (IC) (display driver integration (DDI))) or a touch sensor driver IC (T-IC) for driving the display or the touch panel. This substrate may be

disposed substantially to correspond to a bezel area and may be bent in a curved line shape or a curved surface shape to increase the ratio of the screen area or reduce the bezel area.

As the substrate is bent, the driving circuit can be disposed under the display, so the bezel area can be decreased. According to the substrate, the bending portion of the substrate formed in a curved line shape or a curved surface shape may be damaged by external force, so a crack may be generated in the wiring. Cracks may even be generated in the wiring by direct contact or friction between a window and the bending portion.

Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide a display in which a first wiring and a second wiring can be doubly configured in a bending region of a substrate.

Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

In accordance with an aspect of the disclosure, a display is provided. The display includes a pixel layer including a plurality of pixels, a substrate disposed under the pixel layer and including a first area on which the pixel layer is disposed, and a second area extending out of the pixel layer from the first area, at least a partial area of the second area being bendable, wherein the substrate includes: a wiring layer including at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed from the first area to the second area, and at least one second wiring disposed in the at least partial area and electrically connected with the at least one first wiring in the second area.

In accordance with another aspect of the disclosure, a display is provided. The display includes a display panel including a first area (e.g., an active area (AA)) including a plurality of pixels, and a second area including a bendable bending region, at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed on the first area and the bending region of the second area, and at least one second wiring electrically connected with the at least one first wiring in the second area, and disposed on the bending region of the second area.

In accordance with another aspect of the disclosure, a display is provided. The display includes a pixel layer including a plurality of pixel, and a substrate disposed under the pixel layer, including a first area in which the pixel layer is disposed, and a second area extending out of the pixel layer from the first area, and at least a partial area of the second area being bendable, wherein the substrate includes: at least one first wiring electrically connected with first pixels of the plurality of pixels, and disposed from the first area to the second area, and at least one second wiring electrically connected with second pixels different from first pixels electrically connected with the first wiring, and disposed from the first area to the second area.

In accordance with another aspect of the disclosure, a display is provided. The display includes a substrate including a first area and a second area extending from the first area, at least a partial area of the second area being bendable, at least one first wiring disposed from the first area to the second area, at least one second wiring disposed in the at least a partial area of the second area, and electrically connected with the at least one first wiring in the second area, and at least one wiring layer disposed between the at

3

least one first wiring, and the at least one second wiring and separating the at least one first wiring and the at least one second wiring.

In accordance with another aspect of the disclosure, a display is provided. The display includes a substrate including a first area, a second area extending from a first side of the first area, and a third area extending from a second side of the first area, at least a partial area of the second area being bendable, and at least a partial area of the third area being bendable, at least one first wiring disposed from the first side of the first area to the second area, at least one second wiring disposed in the at least a partial area of the second area, and electrically connected with the at least one first wiring in the second area, at least one third wiring disposed from the second side of the first area to the third area, and at least one fourth wiring disposed in the at least a partial area of the third area, and electrically connected with the at least third wiring in the third area.

According to various embodiments, since a first wiring and a second wiring are doubly separated in a bending region of a substrate, it is possible to mitigate interference between a window of an electronic device and the bending region. Further, two wirings that are arranged in parallel in the related art can be disposed to substantially overlap each other on different layers in various embodiments, so the width of the bending region can be reduced.

According to various embodiments, since a first wiring and a second wiring are doubly disposed in a bending region of a substrate, the same wiring can be doubly achieved. Accordingly, even if a crack is generated in at least one of the first wiring and the second wiring, the other wiring can be electrically connected with the display driver integration of an electronic device, so a poor wiring rate of a product can be reduced.

Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic diagram showing an electronic device in a network environment, the electronic device including a plurality of wiring layers on a bending region according to an embodiment of the disclosure;

FIG. 2A is a front view showing an electronic device according to an embodiment of the disclosure;

FIG. 2B is a rear view showing the electronic device according to an embodiment of the disclosure;

FIG. 2C is an exploded perspective view showing the electronic device according to an embodiment of the disclosure;

FIG. 3A is a cross-sectional view according to one of various embodiments and taken along line A-A' of FIG. 2A according to an embodiment of the disclosure;

FIG. 3B is an enlarged plan view showing the portion A in FIG. 3A according to an embodiment of the disclosure;

FIG. 3C is a cross-sectional view showing a display including a thin film transistor (TFT) layer according to one of various embodiments and taken along line A-A' of FIG. 2A according to an embodiment of the disclosure;

4

FIG. 4 is a plan view showing a display according to an embodiment of the disclosure;

FIG. 5 is a lateral cross-sectional view showing a state before a display according to other various embodiments is bent according to an embodiment of the disclosure;

FIG. 6 is a lateral cross-sectional view showing a state before a TFT layer according to other various embodiments is bent according to an embodiment of the disclosure;

FIG. 7 is a lateral cross-sectional view showing another embodiment of a wiring layer of a display according to an embodiment of the disclosure;

FIG. 8 is a lateral cross-sectional view showing a display according to an embodiment of the disclosure;

FIG. 9 is a lateral cross-sectional view showing a display according to an embodiment of the disclosure;

FIG. 10 is a front view showing the pattern of a second wiring of a display according to an embodiment of the disclosure; and

FIG. 11 is a front view showing another embodiment of the pattern of the second wiring of the display according to an embodiment of the disclosure.

Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

It is to be understood that the singular forms "a," "an," and "the" include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to "a component surface" includes reference to one or more of such surfaces.

The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smart phone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals

als may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st,” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., Play Store™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer’s server, a server of the application store, or a relay server.

According to various embodiments, each component (e.g., a module or a program) of the above-described com-

ponents may include a single entity or multiple entities. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments according to an embodiment of the disclosure.

Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input device **150**, a sound output device **155**, a display device **160**, an audio module **170**, a sensor module **176**, an interface **177**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the display device **160** or the camera module **180**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components may be implemented as single integrated circuitry. For example, the sensor module **176** (e.g., a fingerprint sensor, an iris sensor, or an illuminance sensor) may be implemented as embedded in the display device **160** (e.g., a display).

The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may load a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), and an auxiliary processor **123** (e.g., a graphics processing unit (GPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. Additionally or alternatively, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified

function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

The auxiliary processor **123** may control at least some of the functions or states related to at least one component (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an ISP or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**.

The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

The input device **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input device **150** may include, for example, a microphone, a mouse, a keyboard, or a digital pen (e.g., a stylus pen).

The sound output device **155** may output sound signals to the outside of the electronic device **101**. The sound output device **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record, and the receiver may be used for an incoming call. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

The display device **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display device **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display device **160** may include touch circuitry adapted to detect a touch, or sensor circuitry (e.g., a pressure sensor) adapted to measure the intensity of force incurred by the touch.

The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input device **150**, or output the sound via the sound output device **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, ISP, or flashes.

The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the AP) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a cellular network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such

as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas. In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** and **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, or client-server computing technology may be used, for example.

FIG. 2A is a perspective view showing the front surface of an electronic device (e.g., an electronic device **101** shown in FIG. 1) according to an embodiment of the disclosure.

FIG. 2B is a perspective view showing the rear surface of the electronic device shown in FIG. 2A according to an embodiment of the disclosure.

FIG. 2C is an expanded perspective view of the electronic device shown in FIG. 2A according to an embodiment of the disclosure.

Referring to FIGS. 2A and 2B, an electronic device **200** according to an embodiment may include a housing **210**

having a first surface (or a front surface) **210A**, a second surface (or a rear surface) **210B**, and a side **210C** surrounding the space between the first surface **210A** and the second surface **210B**. In another embodiment (not shown), the housing may refer to a structure forming some of the first surface **210A**, the second surface **210B**, and the side **210C** shown in FIG. 2A. According to an embodiment, the first surface **210A** may be at least partially substantially formed by a transparent front plate **202** (e.g., a glass plate or a polymer plate including various coating layers). The second surface **210B** may be formed by a substantially opaque rear plate **211**. The rear plate **211**, for example, may be made of coated or colored glass, ceramic, a polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination thereof. The side **210C** is combined with a front plate **202** and a rear plate **211** and may be formed by a lateral bezel structure **218** (or a "lateral member") including metal and/or a polymer. In an embodiment, the rear plate **211** and the lateral bezel structure **218** may be integrated and may include the same material (e.g., a metallic material such as aluminum).

According to an embodiment, the electronic device **200** may include at least one or more of a display **201**, a microphone hole **203** and/or speaker holes **207** and **214**, sensor modules **204** and **219**, camera modules **205**, **212**, and **213**, key input units **215**, **216**, and **217**, an indicator **206**, and connector holes **208** and **209**. In an embodiment, the electronic device **200** may not include at least one (e.g., the key input units **215**, **216**, and **217** or the indicator **206**) of the components or may further include other components.

The display **201**, for example, may be exposed through a large part of the front plate **202**. The display **201** may be combined with or disposed adjacent to a touch sensing circuit, a pressure sensor that can measure the intensity (pressure) of a touch, and/or a digitizer that detects a magnetic stylus pen.

A microphone for catching external sounds may be disposed in the microphone hole **203**, and in an embodiment, a plurality of microphones may be disposed therein to sense the direction of sounds. The speaker holes **207** and **214** may include an external speaker hole **207** and/or a receiver hole **214** for a telephone call. In an embodiment, the speaker holes **207** and **214** and the microphone hole **203** may be integrated into one hole or a speaker (e.g., **305** in FIGS. 3A through 3C) may be included without the speaker holes **207** and **214**.

The sensor modules **204** and **219** can generate electrical signals or data values corresponding to the internal operation state of the electronic device **200** or the external environmental state. The sensor modules **204** and **219**, for example, may include a first sensor module **204** (e.g., a proximity sensor) disposed on the first surface **210A** of the housing **210**, a second sensor module (not shown) (e.g., a fingerprint sensor), and/or a third sensor module **219** (e.g., a heart rate monitor (HRM) sensor) disposed on the second surface **210B** of the housing **210**. The fingerprint sensor may be disposed not only on the first surface **210A** (e.g., a home key button **215**), but also on the second surface **210B** of the housing **210**. The electronic device **200** may further include, for example, at least one of a gesture sensor, a gyro sensor, a barometer sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an IR sensor, a biosensor, a temperature sensor, a humidity sensor, and an illumination sensor, which are not shown in the figures.

The camera modules **205**, **212**, and **213** may include a first camera module **205** disposed on the first surface **210A** of the housing of the electronic device **200**, and a second camera

212 and/or a flash **213** disposed on the second surface **210B**. The camera modules **205** and **212** may include one or more lenses, an image sensor, and/or an ISP. The flash **213**, for example, may include a light emitting diode or a xenon lamp. In an embodiment, two or more lenses (a wide-angle lens and a telephoto lens) and image sensors may be disposed on one surface of the electronic device **200**.

The key input units **215**, **216**, and **217** may include a home key button **215** disposed on the first surface **210A** of the housing **210**, touch pads **216** disposed around the home key button **215**, and/or a side key button **217** disposed on the side **210C** of the housing **210**. In another embodiment, the electronic device **200** may not include some or all of the key input units **215**, **216**, and **217** described above and the not-included key input units **215**, **216**, and **217** may be implemented in other types such as a software key on the display **201**.

The indicator **206**, for example, may be disposed on the first surface **210A** of the housing **210**. The indicator **206**, for example, can provide state information of the electronic device **200** using an optical type and may include an LED.

The connector holes **208** and **209** may include a first connector hole **208** that can accommodate a connector (e.g., a USB connector) for transmitting and receiving power and/or data to and from external electronic devices and/or a second connector hole **209** (e.g., an earphone jack) that can accommodate a connector for transmitting and receiving audio signals to and from external electronic devices.

Referring to FIG. 2C, the electronic device **200** may include a lateral bezel structure **218**, an intermediate plate **280** (e.g., a bracket), a front plate **202**, a display **201**, a printed circuit board **240**, a battery **250**, a supporting member **260** (e.g., a rear case), an antenna **270**, and a rear plate **211**. In an embodiment, the electronic device **200** may not include at least one (e.g., the intermediate plate **280** or the supporting member **260**) of the components or may further include other components. At least one of the components of the electronic device **200** may be the same as or similar to at least one of the components of the electronic device **200** shown in FIG. 2A or FIG. 2B and a repeated description is omitted below.

The intermediate plate **280** is disposed in the electronic device **200** and may be connected with the lateral bezel structure **218** or may be integrated with the lateral bezel structure **218**. The intermediate plate **280**, for example, may be made of a metallic material and/or a non-metallic material (e.g., a polymer). The display **201** may be coupled to a surface of the intermediate plate **280** and the printed circuit board **240** may be coupled to the other surface of the intermediate plate **280**. A processor, a memory, and/or an interface may be mounted on the printed circuit board **240**. The processor, for example, may include one or more of a CPU, an AP, a graphic processor, an ISP, a sensor hub processor, and a communication processor.

The memory, for example, may include a volatile memory or a nonvolatile memory.

The interface may include a HDMI, a USB interface, an SD card interface, and/or an audio interface. The interface, for example, can electrically or physically connect the electronic device **200** to external electronic devices and may include an USB connector, an SD card/MMC connector, or an audio connector.

The battery **250**, which is a device for supplying power to one or more components of the electronic device **200**, for example, may include a primary battery that is not rechargeable, a secondary battery that is rechargeable, or a fuel cell. At least a portion of the battery **250**, for example, may be

disposed in substantially the same plane as the printed circuit board **240**. The battery **250** may be integrally disposed in the electronic device **200** and may be detachably attached to the electronic device **200**.

The antenna **270** may be disposed between the rear plate **211** and the battery **250**. The antenna **270**, for example, may include a near field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. The antenna **270**, for example, can perform near field communication with external devices or can wirelessly transmit and receive power for charging. In another embodiment, the antenna may be formed by a portion or a combination of the lateral bezel structure **218** and/or the supporting member **260**.

FIG. 3A is a cross-sectional view according one of various embodiments taken along line A-A' shown in FIG. 2A according to an embodiment of the disclosure.

FIG. 3B is an enlarged plan view of the portion A shown in FIG. 3A according to an embodiment of the disclosure.

Referring to FIGS. 3A and 3B, a display **300**, according to one of various embodiments, may include a display panel **301** and a touch sensor **302**. The display panel **301** may include a substrate **310**. For example, the display panel **301** may include an organic light emitting diode (OLED) element.

The substrate **310** may include any one or two or more combinations selected from polycarbonate (PC), polymethyl methacrylate (PMMA), polyimide (PI), polyethylene terephthalate (PET), polypropylene terephthalate (PPT), amorphous polyethylene terephthalate (APET), polyethylene naphthalate terephthalate (PEN), polyethylene terephthalate glycol (PETG), tri-acetyl-cellulose (TAC), cyclic olefin polymer (COP), cyclic olefin copolymer (COC), polydicyclopentadiene (DCPD), cyclopentadienyl anions (CPD), polyarylate (PAR), polyethersulfone (PES), poly ether imide (PEI), and modified epoxy resin or acrylic resin. According to an embodiment, the substrate **310** may be made of an inflexible material.

The display panel **301** may be disposed under the touch sensor **302**. The display panel **301** is not limited to an OLED and may be various display devices such as an LCD.

A display driver **380** (e.g., a display driver integration (DDI)) may be a display driving chip that controls a plurality of pixels **351**, **352**, **353** of the display **300** to provide various colors.

According to an embodiment, the display driver **380** may be disposed at least one of an end of the display panel **301** and a circuit board (e.g., an M-FPCB) (not shown) included in an electronic device (e.g., **200** in FIG. 2A). The display driver **380** will be described hereafter based on an embodiment in which the display driver **380** is disposed at an end of the display panel **301**.

The substrate **310** may be disposed under a pixel layer **350** including the plurality of pixels **351**, **352**, and **353**.

The plurality of pixels **351**, **352**, and **353** can generate light for outputting images. The plurality of pixels **351**, **352**, and **353** may be arranged on a first insulating layer **341** of a wiring layer **340**.

The substrate **310** includes a first area **311** on which the pixel layer **350** is disposed and a second area **312** extending out of the pixel layer **350** from the first area **311**. At least a partial area of the second area **312** may be bendable.

The substrate **310** may include at least one first wiring **320**, at least one second wiring **330**, or a wiring layer **340**.

13

The at least one first wiring 320 may be electrically connected with the plurality of pixels 351, 352 and 353 and may be disposed from the first area 311 to the second area 312.

The at least one second wiring 330 may be disposed on at least a partial area of the second area 312 and may be electrically connected with the at least one first wiring 320 in the second area 312.

The wiring layer 340 may be disposed between the at least one first wiring 320 and the at least one second wiring 330 to be able to separate the at least one first wiring 320 from the at least one second wiring 330. For example, as shown in FIG. 3A, the first wiring 320 may be disposed on the bottom surface of a first insulating layer 341 and a second insulating layer 342, and the second wiring 330 may be disposed on the top surface of the second insulating layer 342.

According to an embodiment, the substrate 310 may include first and second substrates 310a and 310b. The first substrate 310a may be disposed in the first area 311, the second substrate 310b may be bent at a side of the first area 311 such that a portion of the second substrate 310b (e.g., the portion on which the display driver 380 is mounted) is disposed on the rear surface of the first substrate 310a. The first substrate 310a may be disposed under a plurality of pixels 351, 352 and 353. The second substrate 310b may be bent in at least a partial area of the second area 312. For example, the second substrate 310b may extend and bend from the first substrate 310a.

The at least one first wiring 320 may be disposed on the first and second areas 311 and 312. The at least one first wiring 320 electrically connected with the plurality of pixels 351, 352 and 353. The at least one second wiring 330 electrically connected with the at least one first wiring 320 may be disposed on at least a partial area of the second area 312.

The first wiring 320 and second wiring 330 may be disposed on different surfaces of the second insulating layer 342. For example, the first wiring 320 may be disposed on a first surface of the of the second insulating layer 342 and the second wiring 330 may be disposed on a second surface opposite to the first surface of the second insulating layer 342.

The wiring layer 340 may include a first insulating layer 341 and a second insulating layer 342. The first insulating layer 341 may be disposed on the first area 311. The second insulating layer 342 may be disposed on the second area 312. The second insulating layer 342 may separate the first wiring 320 and the second wiring 330 in at least bending regions of the second area 312.

The first insulating layer 341 or the second insulating layer 342 may include at least one of a thin film encapsulation (TFE) layer, a pixel define layer (PDL), and a thin film transistor (TFT) Passivation layer. A TFE layer is exemplified but the first insulating layer 341 or the second insulating layer 342 are not limited thereto. For example, various configurations may be applied to the first insulating layer 341 and the second insulating layer 342 as long as they can provide electrical insulation.

According to an embodiment, at least a portion of the second substrate 310b may be formed in a chip on plastic (COP) structure, which is a bending structure. For example, the COP structure may be formed by further extending some plastic layers in the second substrate 310b, mounting a display driver 380 (e.g., a DDI), and then bending the second substrate 310b. The second substrate 310b can provide the area for mounting the display driver 380 by extending from the first substrate 310a and is deformed in a curved surface

14

shape, whereby the display driver 380 can be disposed on the rear surface of the first substrate 310a. The bent area of the second substrate 310b may have an elliptical or semi-circular cross-section. The display driver 380 for controlling the display panel 301 may be disposed at an end of the second substrate 310b. The display driver 380 may be electrically connected with the plurality of pixels 351, 352 and 353 disposed on the first substrate 310a through the at least one first wiring 320 and the at least one second wiring 330. For example, in an embodiment, the display driver 380 may be set to output display information by controlling the plurality of pixels 351, 352 and 353 disposed on the substrate 310.

According to an embodiment, the display 300 may further include at least one protective film 370. The at least one protective film 370 may be attached to the lower portion of the first substrate 310a or to an end of the second substrate 310b.

As described above, since the at least one first wiring 320 is disposed on the first substrate 310a and the second substrate 310b, the at least one first wiring 320 and the at least one second wiring 330 are separately and doubly disposed in the second area 312 (e.g., a bending region) of the second substrate 310b, it is possible to mitigate a problem (e.g., insulator cracks or breakage of wire) that may occur due to interference between the window (not shown) of an electronic device (e.g., 101 in FIG. 1) and the second area 312 (e.g., the bending region) of the second substrate 310b, and it is also possible to reduce the width of the second area 312 (e.g., the bending region) of the second substrate 310b.

Referring to FIG. 3A stated above, the first wiring 320 and the second wiring 330 may be separately disposed on the bottom and the top of the second insulating layer 342 on the second area 312 of the second substrate 310b. According to an embodiment, since the first wiring 320 and the second wiring 330 are disposed on the bottom and the top of the second insulating layer 342, respectively, the first wiring 320 and the second wiring 330 may face each other in the second area 312 with the second insulating layer 342 therebetween.

According to an embodiment, a width of at least a portion of the second wiring 330 may be greater than a width of at least a portion of the first wiring 320.

FIG. 3C is a cross-sectional view showing a display including a TFT layer, according to one of various embodiments, and taken along line A-A' of FIG. 2A according to an embodiment of the disclosure.

Referring to FIG. 3C, a display 300, according to one of various embodiments, may include a display panel 301, a touch sensor 302 and a TFT layer 303, the display panel 301 may include a substrate 310. For example, the display panel 301 may include an organic light emitting diode (OLED) element. At least one of the components of the display 300 including the TFT layer 303 may be the same as or similar to at least one of the components of the display 300 shown in FIG. 3A or FIG. 3B and a repeated description is omitted below.

The display driver 380 (e.g., a DDI) may be a display driving chip that controls the pixels 351, 352 and 353 of the display 300 to generate various colors.

The substrate 310 may be disposed under the pixel layer 350 including the plurality of pixels 351, 352 and 353 and may include a second area 312 extending out of the pixel layer 350 from a first area 311 on which the pixel layer 350 is disposed, and at least a partial area of the second area 312 may be bendable.

The display 300 may include at least one first wiring 320, at least one second wiring 330, and a wiring layer 340.

The at least one first wiring 320 may be electrically connected with the plurality of pixels 351, 352 and 353 and may be disposed from the first area 311 to the second area 312.

The at least one second wiring 330 may be disposed on at least a partial area of the second area 312 and may be electrically connected with the at least one first wiring 320 in the second area 312.

The wiring layer 340 may be disposed between the at least one first wiring 320 and the at least one second wiring 330 to be able to separate the at least one first wiring 320 and the at least one second wiring 330. For example, as shown in FIG. 3C, the at least one first wiring 320 may be disposed on the bottom surface of a first insulating layer 341 and a second insulating layer 342 and the at least one second wiring 330 may be disposed on the top surface of the second insulating layer 342.

The TFT layer 303 may be disposed between the first and second insulating layers 341 and 342 and the substrate 310. At least a portion of the TFT layer 303 may be disposed on the first area 311 and the second area 312. The at least one first wiring 320 may be disposed in the TFT layer 303.

The at least one first wiring 320 may be disposed on the first area 311 and the second area 312. the second wiring 330 may be separately disposed on the bottom and the top of the second insulating layer 342, respectively, in the second area 312. According to an embodiment, since the first wiring 320 and the second wiring 330 are disposed on the bottom and the top of the second insulating layer 342, respectively, the at least one first wiring 320 and the at least one second wiring 330 may face each other in the second area 312 with the second insulating layer 342 therebetween.

According to an embodiment, at least one of the components of the touch sensor 302 shown in FIG. 3C may be the same as or similar to at least one of the components of the touch sensor 302 shown in FIG. 3A or 3B, and a repeated description is omitted.

FIG. 4 is a plan view showing a display according to an embodiment of the disclosure.

Referring to FIG. 4, a display 400 may include a display panel 401 and a pixel layer including a plurality of pixels 451, 452, 453, 454, 456, 457 and 458 (collectively pixels 450). For example, a display panel 401 may include a substrate 410. the substrate 410 may include a first substrate 410a and a second substrate 410b.

The first substrate 410a may be disposed under the plurality pixels 451, 452, 453, 454, 456, 457 and 458 and the first substrate 410a may be disposed on a first area 411. The second substrate 410b may be disposed on a second area 412 extending out of the plurality pixels 451, 452, 453, 454, 456, 457 and 458 from a first area 411, and at least a partial area of the second area 412 may be bendable.

The display panel 401 may include at least one first wiring and at least one second wiring 430 and a wiring layer (e.g., 340 in FIG. 3A).

The at least one first wiring 420 may be electrically connected with the pixels of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 and may be disposed from the first area 411 to the second area 412.

The at least one second wiring 430 may be disposed on at least a partial area of the second area 412 and may be electrically connected with the at least one first wiring 420 on the second area 412.

According to an embodiment, at least a portion of the second substrate 410b may be formed in a COP structure,

which is a bending structure. For example, the COP structure may be formed by further extending some plastic layers in the second substrate 410b, mounting a display driver 480 (e.g., a DDI), and then bending the second substrate 410b.

The second substrate 410b can provide the area for mounting the display driver 480 by extending from the first substrate 410a and is deformed in a curved surface shape, whereby the display driver 380 can be disposed on the rear surface of the first substrate 410a. The bent area of the second substrate 410b may have an elliptical or semicircular cross-section. The display driver 480 for controlling the display panel 401 may be disposed at an end of the second substrate 410b. The display driver 480 may be electrically connected with the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 disposed on the first substrate 410a through the at least one first wiring 420 and the at least one second wiring 430. For example, in an embodiment, the display driver 480 may be set to output display information by controlling the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 disposed on the substrate 410.

The at least one data line D1, D2 may include a first data line D1 or a second data line D2. For example, the first data line D1 may be electrically connected with at least some pixels 451, 453, and 457 disposed at odd-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458, and the second data line D2 may be electrically connected with at least some pixels 452, 454, 456 and 458 disposed at even-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458.

The at least one scan line S1, S2 may include a first scan line S1 or a second scan line S2. For example, the first scan line S1 may be electrically connected with at least some odd-numbered pixels 451, 453, and 457 disposed at odd-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 and the second scan line S2 may be electrically connected with at least some even-numbered pixel layers 452, 454, 456 and 458 disposed at even-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458.

The wire layer (e.g., 340 in FIG. 3A) may include a first insulating layer (e.g., 341 in FIG. 3A) and a second insulating layer (e.g., 342 in FIG. 3A). The first data line D1, the second data line D2, the first scan line S1, and the second scan line S2 may dispose under the first insulating layer (e.g., 341 in FIG. 3A) The second insulating layer (e.g., 342 in FIG. 3A) may separate the first data line D1 and the second data line D2 in at least a bending region of a second area (e.g., 312 in FIG. 3A). Further, the second insulating layer (e.g., 342 in FIG. 3A) may separate the first scan line S1 and the second scan line S2 in at least the bending region of the second area (e.g., 312 in FIG. 3A).

According to an embodiment, the data lines, the first data line D1 of the at least one data line D1, D2 can be electrically connected with at least some odd-numbered pixels 451, 453, and 457 disposed at odd-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 and the second data line D2 of the at least one data line D1, D2 can be electrically connected with at least even-numbered pixels 452, 454, 456 and 458 disposed at even-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458.

According to an embodiment, the scan lines, the first scan line S1 of the at least one scan line S1, S2 can be electrically connected with at least some odd-numbered pixel layers 451, 453, and 457 disposed at odd-numbered positions of the plurality of pixels 451, 452, 453, 454, 456, 457 and 458 and the second scan line S2 of the at least one scan line S1, S2

can be electrically connected with at least even-numbered pixels **452**, **454**, **456** and **458** disposed at even-numbered positions of the plurality of pixels **451**, **452**, **453**, **454**, **456**, **457** and **458**.

For example, the at least one data line **D1**, **D2** and the at least one scan line **S1**, **S2** can separately connect the plurality of pixels **451**, **452**, **453**, **454**, **456**, **457** and **458** in accordance with the arranged positions (e.g., odd-numbered positions or even-numbered positions) without connecting all the plurality of pixels **451**, **452**, **453**, **454**, **456**, **457** and **458** regardless of the arranged positions. Accordingly, it is possible to reduce the at least one data line **D1**, **D2** and the at least one scan line **S1**, **S2**.

FIG. 5 is a lateral cross-sectional view showing a state before a display **600** according to other various embodiments is bent according to an embodiment of the disclosure.

Referring to FIG. 5, the display **600** may include a display panel **601**. The display panel **601** may include a substrate **610**. A pixel layer **650** including a plurality of pixels **650a**. A first area **611**, a second area **612**, a first wiring **620**, a second wiring **630**, a wiring layer **640**, and a display driver **680** (e.g., a DDI) may be disposed on the substrate **610**. For example, the second wiring **630** may extend from the first wiring **620** at a first position, for example, a bending start position of the second area **612**. The second wiring **630** may be separated from the first wiring **620** forming a dual structure between the first position and a second position of the second area **612**. The second wiring **630** may be electrically connected back to the first wiring **620** at the second position, for example, a bending end position of the second area **612**. For example, in the first area **611**, the first wiring **620** and the first insulating layer **641** are disposed, and, in the second area **612**, the first wiring **620** and the second wiring **630** may be separated and doubly disposed with the second insulating layer **642** therebetween. Accordingly, even if any one of the first wiring **620** and the second wiring **630** is cut by a crack, electric connection with the display driver **680** can be maintained through the other wiring, so the display **600** can be operated. Accordingly, it is possible to not only reduce wiring problems of the display **600**, but also reduce display malfunctions. The pixel layer **650** may be disposed under the first insulating layer **641**.

According to an embodiment, the substrate **610** may include a first substrate **610a** and a second substrate **610b**, and the first substrate **610a** and the second substrate **610b** can be easily understood through the embodiments described above, so they are not described in detail.

The first wiring **620** or the second wiring **630** are doubly disposed in the second area **612** (e.g., a bending region) of the second substrate **610b** while separated with each other, so it is possible to mitigate a problem (e.g., insulator cracks or breakage of wire) that may occur due to interference between a window (not shown) of an electronic device (e.g. **101** in FIG. 1) and the second area **612** (e.g., the bending region) of the second substrate **610b** and it is also possible to reduce the width of the second area **612** (e.g., the bending region) of the second substrate **610b**.

FIG. 6 is a lateral cross-sectional view showing a state before a touch sensor **702**, according to an embodiment of the disclosure.

Referring to FIG. 6, the display may include the touch sensor **702**, at least one first wiring **761**, at least one second wiring **762**, a wiring layer **740**, or a touch sensor driver IC (T-IC) **781**. The touch sensor **702** may be electrically connected at least one first wiring **761**, at least one second wiring **762**. The at least one first wiring **761** may be disposed in a first area **711** and a second area **712**. The at least one

second wiring **762** may be disposed in the second area **712**. The second area **712** may be bendable.

For example, the at least one second wiring **762** may be separated in an electrically connected state at a first position of the second area **712**, for example, at a bending start position of the second area **712**. The second wiring **762** may be separated by a second insulating layer **742**, between the first position and a second position of the second area **712**, for example, at a bending end position of the second area **712**. The second wiring **762** may be electrically connected back to the at least one first wiring **761** into one wiring at the second position of the second area **712**, for example, the bending end position of the second area **712**. For example, the wiring layer **740** may include a first insulating layer **741** and a second insulating layer **742**. The first wiring **761** and the first insulating layer **741** may be disposed in the first area **711**. The first wiring **761** and the second wiring **762** may be separated by the second insulating layer **742** of the wiring layer **740** and doubly disposed in a dual structure in the second area **712**. Accordingly, even if the first wiring **761**, that is, one of the first wiring **761** and the second wiring **762**, for example, the first wiring **761**, is cut by a crack, the other wiring, for example, the second wiring **762** can electrically connect the T-IC **781** and the touch sensor **702**. Accordingly, wiring problems, such as a disconnection, for the touch sensor **702** can be reduced.

A plurality of electrodes (not shown) included in the touch sensor **702** may be disposed on the top of the first insulating layer **741**.

As described above, since the at least one first wiring **761** and the at least one second wiring **762** are separately by the second insulating layer **742** and doubly disposed in a dual structure in the second area **712** (e.g., a bending region) of the touch sensor **702**, it is possible to mitigate a problem (e.g., insulator cracks or breakage of wire) that may occur due to interference between a window (not shown) of an electronic device (e.g., **101** in FIG. 1) and the second area **712** (e.g., the bending region) of the touch sensor **702** and it is also possible to reduce the width of the second area **712** (e.g., the bending region) of the touch sensor **702**.

FIG. 7 is a lateral cross-sectional view showing another embodiment of a wiring layer **840** of a display **800** according to an embodiment of the disclosure.

Referring to FIG. 7, a display **800**, according to one of various embodiments, may include a display panel **801**, a touch sensor **802**. A pixel layer **850** including a plurality of pixels **851**, **852** and **853**. The display panel **801** may include a substrate **810**. The substrate **810** may be disposed under the pixel layer **850** and may include a first area **811** on which the pixel layer **850** is disposed and a second area **812** extending out of the pixel layer **850** from the first area **811**. At least a partial area of the second area **812** may be bendable. The display **800** may include at least one first wiring **820**, at least one second wiring **830**, or at least one wiring layer **840**. The at least one first wiring **820** may be electrically connected with the plurality of pixels **851**, **852** and **853** and may be extended from the first area **811** to the second area **812**. The at least one second wiring **830** electrically connected with the at least one first wiring **820** may be disposed on at least a partial area of the second area **812**.

According to an embodiment, the substrate **810** may include first and second substrates **810a** and **810b**. The first substrate **810a** may be disposed in the first area **811**, the second substrate **810b** may be bent at a side of the first area **811** such that a portion of the second substrate **810b** (e.g., the portion on which the display driver **880** is mounted) is disposed on the rear surface of the first substrate **810a**. The

first substrate **810a** may be disposed under a plurality of pixels **851**, **852** and **853**. The second substrate **810b** may be bent in at least a partial area of the second area **812**. For example, the second substrate **810b** may extend and bend from the first substrate **810a**.

According to an embodiment, the display **801** may further include at least one protective film **870**. The at least one protective film **870** may be attached to the lower portion of the first substrate **810a** or to an end of the second substrate **810b**.

The substrate **810**, the first area **811**, the second area **812**, the at least one first wiring **820**, and the at least one second wiring **830** can be easily understood through the embodiments described above, so a repeated description is omitted.

The at least one wiring layer **840** includes a first insulating layer **841** and a second insulating layer **842**. The pixel layer **850** may be disposed on the first insulating layer **841**.

The second insulating layer **842** may be disposed between the at least one first wiring **820** and the at least one second wiring **830** to be able to separate the at least one first wiring **820** and the at least one second wiring **830**.

The second insulating layer **842** may include a wiring extension **831** extending from the second area **812** and covering the display driver **880** (e.g., a DDI) of the display **800**. For example, the second insulating layer **842** may include a start position **842a** and an end position **842b**.

The wiring extension **831** can extend from the end position **842b** of the second insulating layer **842** and can cover the display driver **880**.

The display driver **880** (e.g., a DDI) may generate noise due to interference with at least one part (e.g., an antenna) of an electronic device (e.g., **101** in FIG. 1) disposed adjacent to the display driver **880**, so the operation of the display driver **880** may be hindered.

Accordingly, in an embodiment, the wiring extension **831** covering the display driver **880** (e.g., a DDI) is configured to mitigate noise, so it is possible to not only mitigate noise due to interference with the at least one part (e.g., an antenna) when an electronic device (**101** in FIG. 1) operates, but also improve the performance and strength of the display driver **880** (e.g., a DDI).

According to an embodiment, the wiring extension **831** may include a ground layer to increase the effect of mitigating noise due to the at least one part (e.g., an antenna).

FIG. 8 is a lateral cross-sectional view showing a display **900** according to an embodiment of the disclosure.

Referring to FIG. 8, the display **900**, according to one of various embodiments, may include a display panel **901**, a touch sensor **902**. A pixel layer **950** including a plurality of pixels **951**, **952**. The display panel **901** may include a substrate **910**.

The substrate **910** may include a first substrate **910a**, a second substrate **910b**, and a third substrate **910c**.

The first substrate **910a** may be disposed under the pixel layer **950**.

The second substrate **910b** may be disposed at a first side of the first substrate **910a** and may be disposed on a second area **912** extending out of the pixel layer **950** from the first side of the first area **911** in which the pixel layer **950** is disposed, and at least a partial area of the second area **912** may be bendable.

The third substrate **910c** may be disposed at a second side of the first substrate **910a** and may be disposed on a third area **913** extending out of the pixel layer **950** from the second side of the first area **911** in which the pixel layer **950** is disposed, and at least a partial area of the third area **913** may be bendable.

The second area **912** and the third area **913** may extend and bend from the first side and the second side of the first area **911**, respectively.

The second substrate **910b** disposed on the second area **912** may include at least one first wiring **920** and at least one second wiring **930**.

The at least one first wiring **920** may be electrically connected with the plurality of pixels **951**, **952** and may be disposed on the first area **911** and the second area **912**.

The at least one second wiring **930** may be electrically connected with the at least one first wiring **920** on the second area **912**.

A wiring layer **940** may be disposed between the at least one first wiring **920** and the at least one second wiring **930** to be able to separate the at least one first wiring **920** and the at least one second wiring **930**.

The wiring layer **940** may include a first insulating layer **941** and a second insulating layer **942**. The first insulating layer **941** may be disposed on the first area **911**, and the second insulating layer **942** may be disposed on the second area **912**. The second insulating layer **942** may separate the first at least one wiring **920** and the at least one second wiring **930** at least in a bending region of the second area **912**. The pixel layer **950** may be disposed in the first insulating layer **941**.

According to an embodiment, the second substrate **910b** and the third substrate **910c** may be formed in the COP structure, which is a bendable structure. For example, the second substrate **910b** and third substrate **910c** may have an elliptical or semicircular cross-section. A display driver **980** (e.g., a DDI) for controlling the plurality of pixels **951**, **952** may be disposed at an end of the second substrate **910b**. The display driver **980** may be electrically connected with the plurality of pixels **951**, **952** disposed on the first substrate **910a** through the first wiring **920** and the second wiring **930**. For example, in an embodiment, the display driver **980** may be set to provide display information by controlling the pixels **951**, **952** disposed on the first substrate **910a**.

According to an embodiment, the touch sensor **902** may be disposed on the top of the first insulating layer **941** and may be disposed on the first area **911**. The touch sensor **902** may include a plurality of electrodes (not shown). At least one wiring **961** electrically connected with the plurality of electrodes of the touch sensor **902** may be disposed on the third area **913**.

According to an embodiment, the display **901** may further include at least one protective film **970**. The at least one protective film **970** may be attached to the lower portion of the first substrate **910a** or to an end of the second substrate **910b**.

According to an embodiment, a T-IC **981** for controlling the touch sensor **902** may be disposed at an end of the at least one wiring **961**. The T-IC **981** may be electrically connected with the plurality of electrodes of the touch sensor **902** through the at least one wiring **961**. For example, a plurality of first electrodes and second electrodes of the touch sensor **902** can generate electrical signals through a touch input on a window (not shown) of an electronic device (e.g., **101** in FIG. 1). The electrical signals generated by the plurality of first electrodes and second electrodes of the touch sensor **902** can be sensed through the T-IC (e.g., **981** in FIG. 981). The T-IC (**981** in FIG. 981) can transmit the sensed signals to a processor (e.g., **120** in FIG. 1) of an electronic device (e.g., **101** in FIG. 1) and the processor (e.g., **120** in FIG. 1) can display the sensed signals through the display **900**.

As described above, the second substrate **910b** or the third substrate **910c** may be disposed on a second area **912** or a

third area **913**, respectively. The touch sensor **902** disposed on the top of the first insulating layer **941** may be disposed in the first area **911**, and at the least one wiring **961** electrically connected with the plurality of electrodes of the touch sensor **902** may be disposed in the third area **913**.

According to an embodiment, since the at least one first wiring **920** and the at least one second wiring **930** may be separately and doubly disposed in the second area (e.g., a bending region) of the second substrate **910b**, it is possible to mitigate a problem (e.g., insulator cracks or breakage of wire) that may occur due to interference between a window (not shown) of an electronic device (e.g., **101** in FIG. **1**) and the second area (e.g., the bending region) of the second substrate **910b** and to reduce the width of the second area (e.g., the bending region) of the second substrate **910b**. Since the at least one wiring **961** of the touch sensor **902** is disposed in the third area **913**, it is possible to mitigate interference between a window (not shown) of an electronic device (e.g., **101** in FIG. **1**) and the third area **913** (e.g., a bending region) and to reduce the width of the third area **913** (e.g., the bending region).

FIG. **9** is a lateral cross-sectional view showing a display **1000** according to an embodiment of the disclosure.

Referring to FIG. **9**, the display **1000**, according to one of various embodiments, may include a display panel **1001**, a touch sensor **1002**, and a pixel layer **1050** including a plurality of pixels **1051**, **1052**. The display panel **1001** may include a substrate **1010**.

The substrate **1010** may include a first substrate **1010a**, a second substrate **1010b**, and a third substrate **1010c**.

The pixel layer **1050** may be disposed over the first substrate **1010a**.

The second substrate **1010b** may be disposed at a first side of the first substrate **1010a** and may include a second area **1012** extending out of the pixel layer **1050** from the first side of the first area **1011** on which the pixel layer **1050** is disposed, and at least a partial area of the second area **1012** may be bendable.

The third substrate **1010c** may be disposed at a second side of the first substrate **1010a** and may include a third area **1013** extending out of the pixel layer **1050** from the second side of the first area **1011** on which the pixel layer **1050** is disposed, and at least a partial area of the third area **1013** may be bendable.

The second area **1012** or the third area **1013** may extend and bend from the first side or the second side of the first area **1011**, respectively. For example, the second area **1012** may extend from a first side of the first area **1011** and the third area **1013** may extend from a second side of the first area **1011**.

The second substrate **1010b** disposed on the second area **1012** may include at least one first wiring **1020** and at least one second wiring **1030**.

The at least one first wiring **1020** may be electrically connected with at least some pixels of the plurality of pixels **1050a** and may be extended from the first side of the first area **1011** to the second area **1012**.

The at least one second wiring **1030** may be electrically connected with the at least one first wiring **1020** on the second area **1012** while separated with the at least one first wiring **1020** by a second insulating layer **1042**.

At least one wiring layer **1040** may be disposed on the first area **1011**, the second area **1012**, and the third area **1013**. The wiring layer **1040** may include a first insulating layer **1041**, the second insulating layer **1042**, and a third insulating layer **1043**. The first insulating layer **1041** may be disposed on the first area **1011** and the second insulating layer **1042**

may be disposed on the second area **1012** and may separate the at least one first wiring **1020** and the at least one second wiring **1030**. The third insulating layer **1043** may be disposed on the third area **1013** and may separate at least one third wiring **1061** and a at least one fourth wiring **1062**, which are to be described below. The pixel layer **1050** may be disposed in the first insulating layer **1041**.

According to an embodiment, the second substrate **1010b** and the third substrate **1010c** may be formed in the COP structure, which is a bendable structure. For example, the bent second substrate **1010b** and third substrate **1010c** may have an elliptical or semicircular cross-section. A display driver **1080** (e.g., a DDI) for controlling the display panel **1001** may be disposed at an end of the second substrate **1010b**. The display driver **1080** (e.g., a DDI) may be electrically connected with the plurality of pixels **1051**, **1052**, included in the first area **1011** through the at least one first wiring **1020** and the at least one second wiring **1030**. For example, in an embodiment, the display driver **1080** may be set to provide display information by controlling the pixels **1050a** included in the first substrate **1010a**.

According to an embodiment, a plurality of electrodes (not shown) may be disposed on the touch sensor **1002** and may be disposed on the first area **1011**. The touch sensor **1002** may include the plurality of electrodes (not shown). At least a partial area of the third area **1013** may be bendable.

The second area **1012** or third area **1013** may extend and bend from the first side and the second side of the first area **1011**, respectively.

The third area **1013** may include the at least one third wiring **1061** and the fourth wiring **1062**.

The at least third wiring **1061** may be electrically connected with the plurality of electrodes (not shown) and may be connected from the first area **1011** to the third area **1013**.

The at least one fourth wiring **1062** may be electrically connected with the at least one third wiring **1061** in the third area **1013**.

A third insulating layer **1043** may be disposed between the at least one third wiring **1061** and the at least one fourth wiring **1062** to be able to separate the at least one third wiring **1061** and the at least fourth wiring **1062**.

According to an embodiment, the display **1001** may further include at least one protective film **1070**. The at least one protective film **1070** may be attached to the lower portion of the first substrate **1010a** or to an end of the second substrate **1010b**.

According to an embodiment, a T-IC **1081** for controlling the touch sensor **1002** may be disposed at an end of at least one the third wiring **1061**. The T-IC **1081** may be electrically connected with the plurality of electrodes (not shown) of the touch sensor **1002** through the third wiring **1061** and the at least one fourth wiring **1062**. For example, the plurality of electrodes (not shown) can generate electrical signals through a touch input on a window (not shown) of an electronic device (e.g., **101** in FIG. **1**). The electrical signals generated by the plurality of electrodes (not shown) can be sensed by the T-IC **1081** through the at least one third wiring **1061** and the fourth wiring **1062**. The T-IC **1081** can transmit the sensed signals to a processor (e.g., **120** in FIG. **1**) of an electronic device (e.g., **101** in FIG. **1**) and the processor (e.g., **120** in FIG. **1**) can display the sensed signals through the display **1000**.

As described above, since the at least one first wiring **1020** and the at least one second wiring **1030** may be separately and doubly disposed in the second area **1012** (e.g., a bending region) of the second substrate **1010b**, it is possible to mitigate interference between a window (not

shown) of an electronic device (e.g., **101** in FIG. 1) and the second area (e.g., the bending region) of the second substrate **1010b** and to reduce the width of the second area **1012** (e.g., the bending region) of the second substrate **1010b**. Since the at least one third wiring **1061** and the at least one fourth wiring **1062** of the touch sensor **1002** are separated and doubly disposed in the third area **1013** (e.g., a bending region), it is possible to mitigate interference between a window (not shown) of an electronic device (e.g., **101** in FIG. 1) and the third area **1013** (e.g., the bending region) and to reduce the width of the third area **1013** (e.g., the bending region).

FIG. 10 is a front view showing the pattern of a second wiring of a display according to an embodiment of the disclosure.

FIG. 11 is a front view showing another embodiment of the pattern of the second wiring of the display according to an embodiment of the disclosure.

Referring to FIG. 10, the pattern of a second wiring **2000** may be formed in a shape similar to the waveform of a square wave. For example, the pattern of the second wiring **2000** may be a pattern in which if a side protrudes, the opposite side also protrudes.

Other patterns other than the pattern described above may be applied to the pattern of the second wiring **2000**.

Referring to FIG. 11 showing another embodiment of the pattern of the second wiring, the pattern **2001** of the second wiring may be formed in a shape similar to the waveform of a triangle wave. For example, the pattern of the second wiring **2001** may be formed in a zigzag shape. Other patterns other than the pattern similar to the waveform of a triangle pattern may be applied to the pattern of the second wiring **2001**.

According to various embodiments, a display may include: a pixel layer including a plurality of pixels; and a substrate disposed under the pixel layer and including a first area on which the pixel layer is disposed, and a second area extending out of the pixel layer from the first area, at least a partial area of the second area being bendable, wherein the substrate includes: a wiring layer including at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed from the first area to the second area, and at least one second wiring disposed in the at least partial area and electrically connected with the at least one first wiring in the second area.

According to various embodiments, the wiring layer may further include a first insulating layer and a second insulating layer, and the first insulating layer is disposed on the first area and the second insulating layer may be disposed on the second area.

According to various embodiments, the display may include one or more insulating layers disposed in the first area and at least one of the one or more insulating layers may at least partially include the same material as the first insulating layer.

According to various embodiments, the one or more insulating layers may include at least one of a TFE, a PDL, or a TFT Passivation layers.

According to various embodiments, a display may include: a display panel including a first area including a plurality of pixels, and a second area including a bendable bending region; at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed on the bending region of the second area; and at least one second wiring electrically connected with the at least one first wiring in the second area, and disposed on the bending region of the second area.

According to various embodiments, the substrate may be attached to the at least partial area of the bending region by an adhesive.

According to various embodiments, at least a portion of the second wiring may be wider than at least a portion of the first wiring.

According to various embodiments, a pattern of the second wiring may include a shape of at least one of a waveform of a square wave or a waveform of a triangle wave.

According to various embodiments, a display may include: a pixel layer including a plurality of pixels; and a substrate disposed under the pixel layer, including a first area on which the plurality of pixel layers is disposed, and a second area extending out of the pixel layer from the first area, at least a partial area of the second area being bendable, wherein the substrate includes: at least one first wiring electrically connected with at least one first pixels of the plurality of pixels, and disposed from the first area to the second area; and at least one second wiring electrically connected with at least one second pixels different from first pixels electrically connected with the first wiring, and disposed from the first area to the second area.

According to various embodiments, a wiring layer may be further included between the at least one first wiring and the at least one second wiring.

According to various embodiments, the wiring layer may further include a first insulating layer and a second insulating layer, in which the first insulating layer may be disposed on the first area and the second insulating layer may be disposed on the second area.

According to various embodiments, the at least one first wiring and the at least one second wiring may include at least one data line or at least one scan line.

According to various embodiments, the at least one data line may include first and second data lines, when seen from above the display, the first data line may be electrically connected with pixels disposed at odd-numbered positions of the plurality of pixels, and when seen from above the display, the second data line may be electrically connected with pixel layers disposed at even-numbered positions of the plurality of pixel layers. The at least one scan line may include first and second scan lines, the first scan line may be electrically connected with the pixels disposed at odd-numbered positions of the plurality of pixels, and the second scan line may be electrically connected with the pixels disposed at even-numbered positions of the plurality of pixels.

According to various embodiments, a display includes: a substrate including a first area and a second area extending from the first area, at least a partial area of the second area being bendable; at least one first wiring disposed from the first area to the second area; at least one second wiring disposed on the at least a partial area of the second area, and electrically connected with the at least one first wiring in the second area; and at least one wiring layer disposed between the at least one first wiring and the at least one second wiring and separating the at least one first wiring and the at least one second wiring.

According to various embodiments, the substrate may include at least one of a display substrate or a touch substrate.

According to various embodiments, the at least one first wiring may be disposed on a first surface of the at least one wiring layer and the at least one second wiring may be disposed on a second surface opposite to the first surface of the at least one wiring layer.

According to various embodiments, the at least one first wiring and the at least one second wiring may form double wires by being separated by the wiring layer.

According to various embodiments, the at least one wiring layer may further include a first insulating layer and a second insulating layer, and the first insulating layer may be disposed on the first area and the second insulating layer may be disposed on the second area.

According to various embodiments, the at least one wiring layer may include a wiring extension extending from the second insulating layer and covering the display driver of the display.

According to various embodiments, the at least one first wiring may include a data line or a scan line, the data line may be electrically connected with pixels disposed at odd-numbered positions of the plurality of pixels, and the scan line may be electrically connected with pixels disposed at even-numbered positions of the plurality of pixels.

According to various embodiments, a display may include; a substrate including a first area, a second area extending from a first side of the first area, and a third area extending from a second side of the first area, at least a partial area of the second area being bendable, and at least a partial area of the third area being bendable; at least one first wiring disposed from the first side of the first area to the second area; at least one second wiring disposed on the at least a partial area of the second area, and electrically connected with the at least one first wiring in the second area; at least one third wiring disposed from the second side of the first area to the third area; and at least one fourth wiring disposed on the at least a partial area of the third area, and electrically connected with the at least third wiring in the third area.

According to various embodiments, a wiring layer separating the at least one first wiring and second wiring may be included between the at least one first wiring and the at least one second wiring.

According to various embodiments, the wiring layer may further includes a first insulating layer, a second insulating layer and a third insulating layer, and the first insulating layer may be disposed on the first area, the second insulating layer disposed between the at least one first wiring and the at least one second wiring and separating the at least one first wiring and the at least one second wiring is disposed on the second area, and the third insulating layer disposed between the at least one third wiring and the at least one fourth wiring and separating the at least third and the at least one fourth wiring is disposed on the third area.

According to various embodiments, the at least one first wiring and the at least one second wiring may be electrically connected with the display driver of the display, and the at least one third wiring and the at least one fourth wiring may be electrically connected with a touch panel display driver of the display.

According to various embodiments, a width of at least a portion of the second wiring may be greater than a width of at least a portion of the first wiring, and a width of at least a portion of the fourth wiring may be greater than a width of at least a portion of the at least one third wiring.

While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

What is claimed is:

1. A display comprising:

a display panel including a first area including a plurality of pixels, and a second area including a bendable bending region;

at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed on the first area and the bending region of the second area; and at least one second wiring electrically connected with the at least one first wiring in the second area, and disposed on the bending region of the second area; and

a wiring layer including a first insulating layer and a second insulating layer, the first insulating layer being disposed on the first area and the second insulating layer being disposed on the second area, wherein the at least one first wiring is disposed on a bottom surface of the first insulating layer and the second insulating layer, and the at least one second wiring is disposed on a top surface of the second insulating layer.

2. The display of claim 1, further comprising:

a first insulating layer and a second insulating layer, wherein the first insulating layer is disposed on the first area and the second insulating layer is disposed on the second area.

3. The display of claim 1, wherein at least a portion of a pattern of the second wiring includes a shape of at least one of a waveform of a square wave or a waveform of a triangle wave.

4. The display of claim 1, wherein a width of at least a portion of the second wiring is greater than a width of at least a portion of the first wiring.

5. A display comprising:

a substrate including a first area and a second area extending from a first side of the first area, at least a partial area of the second area being bendable;

at least one first wiring disposed from the first area to the second area;

at least one second wiring disposed on the at least a partial area of the second area, and electrically connected with the at least one first wiring in the second area;

at least one wiring layer disposed between the at least one first wiring and the at least one second wiring, and separating the at least one first wiring and the at least one second wiring; and

a wiring layer including a first insulating layer and a second insulating layer, the first insulating layer being disposed on the first area and the second insulating layer being disposed on the second area,

wherein the at least one first wiring is disposed on a bottom surface of the first insulating layer and the second insulating layer, and the at least one second wiring is disposed on a top surface of the first insulating layer and the second insulating layer.

6. The display of claim 5,

wherein the at least one first wiring includes a data line or a scan line,

wherein the data line is electrically connected with pixels disposed at odd-numbered positions of the plurality of pixels, and

wherein the scan line is electrically connected with pixels disposed at even-numbered positions of the plurality of pixels.

7. The display of claim 5, wherein the at least one wiring layer includes a wiring extension extending from the second insulating layer, and covering a display driver of the display.

8. The display of claim 5, wherein the at least one first wiring and the at least one second wiring form double wirings by being separated by the wiring layer.

27

9. The display of claim 5, wherein the substrate includes at least one of a display substrate or a touch substrate.
10. The display of claim 5, wherein the substrate includes a third area extending from a second side of the first area, at least a partial area of the third area being bendable.
11. The display of claim 10, further comprising: at least one third wiring disposed from the second side of the first area to the third area; and at least one fourth wiring disposed on the at least a partial area of the third area, and electrically connected with the at least third wiring in the third area.
12. The display of claim 11, wherein the wiring layer further includes a third insulating layer, wherein the first insulating layer is disposed on the first area, wherein the second insulating layer disposed between the at least one first wiring and the at least one second wiring, and separating the at least one first wiring and the at least one second wiring is disposed on the second area, and wherein the third insulating layer disposed between the at least one third wiring and the at least one fourth wiring, and separating the at least third wiring and the at least one fourth wiring is disposed on the third area.
13. The display of claim 11, wherein a width of at least a portion of the at least one second wiring is greater than a width of at least a portion of the at least one first wiring, and wherein a width of at least a portion of the at least one fourth wiring is greater than a width of at least a portion of the at least one third wiring.
14. The display of claim 11, wherein the at least one first wiring and the at least one second wiring are electrically connected with a display driver of the display, and

28

- wherein the at least one third wiring and the at least one fourth wiring are electrically connected with a touch panel display driver of the display.
15. A display comprising: a pixel layer including a plurality of pixels; and a substrate disposed under the pixel layer and including a first area on which the pixel layer is disposed, and a second area extending out of the pixel layer from the first area, at least a partial area of the second area being bendable, wherein the substrate includes: at least one first wiring electrically connected with at least one pixel of the plurality of pixels, and disposed from the first area to the second area, at least one second wiring disposed in the at least partial area, and electrically connected with the at least one first wiring in the second area, and a wiring layer including a first insulating layer and a second insulating layer, the first insulating layer being disposed on the first area and the second insulating layer being disposed on the second area, wherein the at least one first wiring is disposed on a bottom surface of the first insulating layer and the second insulating layer, and the at least one second wiring is disposed on a top surface of the second insulating layer.
16. The display of claim 15, wherein the first insulating layer is disposed entirely within the first area, and wherein the second insulating layer is disposed entirely within the second area.
17. The display of claim 15, wherein the second insulating layer at least partially includes the same material as the first insulating layer.
18. The display of claim 17, wherein the first insulating layer or the second insulating layer includes at least one of a thin film encapsulation, a pixel define layer, or a thin film transistor passivation layer.

* * * * *