



US010652052B2

(12) **United States Patent**  
**Zerbe et al.**

(10) **Patent No.:** **US 10,652,052 B2**  
(45) **Date of Patent:** **\*May 12, 2020**

(54) **SELECTABLE-TAP EQUALIZER**

(2013.01); **H04L 25/03057** (2013.01); **H04L 25/03343** (2013.01); **H04L 25/03885** (2013.01)

(71) Applicant: **Rambus Inc.**, Sunnyvale, CA (US)

(72) Inventors: **Jared L. Zerbe**, Woodside, CA (US); **Vladimir M. Stojanovic**, Lexington, MA (US); **Fred F. Chen**, San Francisco, CA (US)

(58) **Field of Classification Search**

CPC ..... H04B 3/32; H04B 1/0475; H04B 15/00; H04B 15/02; H04B 1/1027; H04B 2001/0425; H04B 2001/1045; H04B 7/005; H04L 25/03019

See application file for complete search history.

(73) Assignee: **Rambus Inc.**, Sunnyvale, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(56)

**References Cited**

**U.S. PATENT DOCUMENTS**

3,381,245 A 4/1968 Guanella  
3,761,818 A 9/1973 Tazaki et al.  
(Continued)

**OTHER PUBLICATIONS**

“Jedec Standard—Double Data Rate (DDR) SDRAM Specification—JESD79”, Jedec Solid State Technology Association, Jun. 2000, pp. 1-76. 76 Pages.

(Continued)

*Primary Examiner* — Curtis B Odom

(21) Appl. No.: **16/432,283**

(22) Filed: **Jun. 5, 2019**

(65) **Prior Publication Data**

US 2019/0342127 A1 Nov. 7, 2019

**Related U.S. Application Data**

(60) Continuation of application No. 16/126,121, filed on Sep. 10, 2018, now Pat. No. 10,355,888, which is a (Continued)

(51) **Int. Cl.**

**H04L 25/03** (2006.01)  
**H04B 1/10** (2006.01)

(Continued)

(52) **U.S. Cl.**


CPC ..... **H04L 25/03019** (2013.01); **H04B 1/1081** (2013.01); **H04L 7/0058** (2013.01); **H04L 7/0087** (2013.01); **H04L 7/0331** (2013.01); **H04L 25/03025** (2013.01); **H04L 25/03038**

(57)

**ABSTRACT**

A signaling circuit having a selectable-tap equalizer. The signaling circuit includes a buffer, a select circuit and an equalizing circuit. The buffer is used to store a plurality of data values that correspond to data signals transmitted on a signaling path during a first time interval. The select circuit is coupled to the buffer to select a subset of data values from the plurality of data values according to a select value. The equalizing circuit is coupled to receive the subset of data values from the select circuit and is adapted to adjust, according to the subset of data values, a signal level that corresponds to a data signal transmitted on the signaling path during a second time interval.

**20 Claims, 22 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/715,032, filed on Sep. 25, 2017, now Pat. No. 10,103,907, which is a continuation of application No. 15/490,725, filed on Apr. 18, 2017, now Pat. No. 9,806,916, which is a continuation of application No. 15/209,454, filed on Jul. 13, 2016, now Pat. No. 9,660,840, which is a continuation of application No. 14/789,832, filed on Jul. 1, 2015, now Pat. No. 9,419,825, which is a continuation of application No. 14/616,629, filed on Feb. 6, 2015, now Pat. No. 9,106,397, which is a continuation of application No. 14/145,960, filed on Jan. 1, 2014, now abandoned, which is a continuation of application No. 13/729,510, filed on Dec. 28, 2012, now Pat. No. 8,654,829, which is a division of application No. 12/269,488, filed on Nov. 12, 2008, now Pat. No. 8,467,437, which is a division of application No. 11/871,666, filed on Oct. 12, 2007, now Pat. No. 7,508,871, which is a continuation of application No. 10/195,129, filed on Jul. 12, 2002, now Pat. No. 7,292,629.

- (51) **Int. Cl.**  
*H04L 7/00* (2006.01)  
*H04L 7/033* (2006.01)

- (56) **References Cited**

U.S. PATENT DOCUMENTS

3,978,284	A	8/1976	Yoshino et al.
4,359,778	A	11/1982	Lee
4,382,249	A	5/1983	Jacobsthal
4,581,747	A	4/1986	Prezas et al.
5,003,555	A	3/1991	Bergmans
5,243,625	A	9/1993	Verbakel et al.
5,282,225	A	1/1994	Nikias et al.
5,539,774	A	7/1996	Nobakht et al.
5,659,581	A	8/1997	Betts et al.
5,694,424	A	12/1997	Ariyavisitakul
5,703,903	A	12/1997	Blanchard et al.
5,761,254	A	6/1998	Behrin
5,793,815	A	8/1998	Goodnow et al.
5,809,033	A	9/1998	Turner et al.
5,835,440	A	11/1998	Manning
5,940,442	A	8/1999	Wong et al.
6,038,264	A	3/2000	Uesugi
6,061,395	A	5/2000	Tonami
6,067,319	A	5/2000	Copeland
6,067,326	A	5/2000	Jonsson et al.
6,084,931	A	7/2000	Powell et al.
6,107,946	A	8/2000	Jeong
6,178,213	B1	1/2001	McCormack et al.
6,204,785	B1	3/2001	Fattarusio et al.
6,222,782	B1	4/2001	Chon
6,236,645	B1	5/2001	Agazzi
6,282,210	B1	8/2001	Rapport et al.
6,289,045	B1	9/2001	Hasegawa et al.
6,373,911	B1	4/2002	Tajjima et al.
6,396,329	B1	5/2002	Zerbe
6,463,109	B1	10/2002	McCormack et al.
6,530,062	B1	3/2003	Donnelly et al.
6,643,787	B1	11/2003	Zerbe et al.
6,665,351	B2	12/2003	Hedberg
6,674,377	B1	1/2004	Li
6,687,235	B1	2/2004	Chu
6,691,214	B1	2/2004	Li et al.
6,724,329	B2	4/2004	Casper
6,744,814	B1	6/2004	Blanksby et al.
6,751,255	B1	6/2004	Reuven
6,771,725	B2	8/2004	Agazzi et al.
6,861,886	B1	3/2005	Ludden et al.

6,862,315	B1 *	3/2005	Garg	H04L 25/03133
				375/232
6,965,262	B2	11/2005	Zerbe	
6,996,202	B2	2/2006	McCormack et al.	
7,079,610	B1	7/2006	Johansson et al.	
7,099,424	B1	8/2006	Chang et al.	
7,113,540	B2	9/2006	Yousef et al.	
7,248,635	B1	7/2007	Arneson et al.	
7,269,212	B1 *	9/2007	Chau	H04L 25/03878
				326/80
7,292,629	B2	11/2007	Zerbe et al.	
7,330,506	B2	2/2008	Gorecki et al.	
7,366,267	B1	4/2008	Lee et al.	
7,484,064	B2	1/2009	Ware et al.	
7,508,871	B2	3/2009	Zerbe et al.	
7,548,601	B2	6/2009	Sidiropoulos	
7,873,115	B2	1/2011	Zerbe et al.	
8,023,584	B2	9/2011	Zerbe et al.	
8,306,104	B2	11/2012	Agazzi et al.	
8,467,437	B2	6/2013	Zerbe et al.	
8,654,829	B2 *	2/2014	Zerbe	H04L 25/03038
				375/229
9,106,397	B2	8/2015	Zerbe et al.	
2001/0010712	A1	8/2001	Hedberg	
2002/0066110	A1	5/2002	Cloonan et al.	
2002/0095541	A1	7/2002	Cranford, Jr. et al.	
2002/0176481	A1	11/2002	Shiina et al.	
2002/0181360	A1	12/2002	Hamada et al.	
2005/0033902	A1	2/2005	Tamura	
2007/0172012	A1	7/2007	Agazzi	

OTHER PUBLICATIONS

Ariyavisitakul et al., "Reduced-Complexity Equalization Techniques for Broadband Wireless Channels," IEEE Journal on Selected Areas in Communications, vol. 15, No. 1, Jan. 1997, pp. 5-15. 11 pages.

Ariyavisitakul et al., "Tap-Selectable Decision-Feedback Equalization," IEEE Transactions on Communications, vol. 45, No. 12, Dec. 1997, pp. 1497-1500. 4 pages.

Baker, Alan J., "An Adaptive Cable Equalizer for Serial Digital Video Rates to 400Mb/s," 1996 IEEE International Solid-State Circuits Conference, Session 10, Low-Power & Communication Signal Processing, Paper FA 10.7. 3 pages.

Choi et al., "A CMOS 3.5Gbps Continuous-Time Adaptive Cable Equalizer with Joint Adaptation Method of Low-Frequency Gain and High-Frequency Boosting," 2003 Symposium on VLSI Circuits Digest of Technical Paper. 4 pages.

Cova et al., "Characterization of Individual Weights in Transversal Filters and Application to CCD's," IEEE Journal of Solid-State Circuits, vol. SC-17, No. 6, Dec. 1982, pp. 1054-1061. 8 pages.

Current, Wayne K., "Current-Mode CMOS Multiple-Valued Logic Circuits," Feb. 1994, IEEE Journal of Solid-State Circuits, vol. 29, No. 2, pp. 95-107. 13 pages.

Dally et al., "Digital Systems Engineering," Cambridge University Press, New York, NY, pp. 334-347 and 352, 1998. 17 pages.

Dally et al., "Multi-gigabit Signaling with CMOS," DARPA funded presentation, May 12, 1997. 26 pages.

Exhibit 26: Yang et al., "A Scalable 32Gb/s Parallel Data Transceiver with On-Chip Timing Calibration Circuits," IEEE International Solid State Circuits Conference, pp. 258-259, 2000. 2 pages.

Farjad-Rad et al., "0.622-8 Gbps 150mW Serial 10 Macrocell with Fully Flexible Preemphasis and Equalization," Symposium on VLSI Circuits Digest of Technical Papers, Jun. 2003. 4 pages.

Farjad-Rad et al., "A 0.4 m CMOS 10-Gb/s 4-PAM Pre-Emphasis Serial Link Transmitter," IEEE Journal of Solid State Circuits, vol. 34, pp. 580-585, May 1999. 22 pages.

Farjad-Rad et al., "An equalization scheme for 10Gb/s 4-PAM signaling over long cables," Presentation Center for Integrated Systems, Department of Electrical Engineering, Stanford University, Jul. 28, 1997. 22 pages.

Fiedler et al., "A 1.0625 Gbps Transceiver with 2x-Oversampling and Transmit Signal Pre-Emphasis," 1997 IEEE International Solid-State Circuits Conference, Session 15, pp. 238-239, 464, Feb. 7, 1997. 3 pages.

(56)

**References Cited**

OTHER PUBLICATIONS

Granberg, Tom, "Handbook of Digital Techniques for High-Speed Design," Prentice Hall Modern Semiconductor Design Series, Copyright 2004 by Pearson Education, Inc. 12 pages.

Gustavson, David et al., "Provisional Patent Application With Title: SLD RAM Architecture", U.S. Appl. No. 60/057,092, filed Aug. 27, 1997. 340 Pages.

IBM Technical Disclosure Bulletin, "Clock Recovery Circuit," pp. 219-220, Jul. 1969. 2 pages.

Institute of Electrical and Electronics Engineers, "802.3ab—A Tutorial Presentation," Slides, Mar. 1998. 63 pages.

Kuczynski et al., "A 1 Mb/s Digital Subscriber Line Transceiver Signal Processor," 1993 IEEE International Solid State Circuit Conference. 7 pages.

Moncayo, Alfredo, "Bus Design and Analysis at 500MHz and Beyond," Presented at the Design SuperCon, 1995. 19 pages.

Moon, Yongsam et al., "A 1Gbps Transceiver With Receiver-End Deskewing Capability Using Non-Uniform Tracked Oversampling and a 250-750MHz Four-Phase DLL", 1999 Symposium on VLSI Circuits Digest of Technical Papers, 1999, pp. 47-48. 2 Pages.

Raghavan et al., "Nonuniformly Spaced Tapped-Delay-Line Equalizers," IEEE Transactions on Communications, vol. 41, No. 9, pp. 1290-1295, 1993. 6 pages.

Schlegel, Michael, "4 Modulation Schemes for High Bit Rate Data Transmission in the Loop Plant," Apr. 19, 2001, pp. 1-29, www.bib.frlippe.de/voltext/dipl/schlegel/chapter4.htm printed Aug. 10, 2000. 29 pages.

Sidiropoulos et al., "A 700 Mb/s/pin CMOS Signaling Interface Using Current Integrating Receivers," IEEE Journal of Solid-State Circuits, vol. 32, No. 5, pp. 681-690, May 1997. 10 pages.

Stojanovic et al., "Adaptive Equalization and Data Recovery in a Dual-Mode (PAM2/4) Serial Link Transceiver," Rambus, Inc., Department of Electrical Engineering, Stanford University, Jan. 2004. 4 pages.

\* cited by examiner




FIG. 1  
(Prior Art)




FIG. 2




FIG. 3





FIG. 4

FIG. 5






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12

FIG. 13






FIG. 14




FIG. 15

230 →




FIG. 17

FIG. 16

FIG. 18




FIG. 19




FIG. 21




FIG. 20




FIG. 22




FIG. 23

FIG. 24





FIG. 25






FIG. 26





FIG. 27

FIG. 28






FIG. 30




FIG. 29




FIG. 31




FIG. 32

FIG. 33





FIG. 34





FIG. 35

FIG. 36



## SELECTABLE-TAP EQUALIZER

## CLAIM OF PRIORITY

This application is a continuation of U.S. patent application Ser. No. 16/126,121 filed on Sep. 10, 2018 (still pending), which is a continuation of U.S. patent application Ser. No. 15/715,032 filed on Sep. 25, 2017 (now U.S. patent Ser. No. 10/103,907), which is a continuation of U.S. patent application Ser. No. 15/490,725 filed on Apr. 18, 2017 (now U.S. Pat. No. 9,806,916), which is a continuation of U.S. patent application Ser. No. 15/209,454 filed on Jul. 13, 2016 (now U.S. Pat. No. 9,660,840), which is a continuation of U.S. patent application Ser. No. 14/789,832 filed on Jul. 1, 2015 (now U.S. Pat. No. 9,419,825), which is a continuation of U.S. patent application Ser. No. 14/616,629 filed on Feb. 6, 2015 (now U.S. Pat. No. 9,106,397), which is a continuation of U.S. patent Ser. No. 14/145,960 filed on Jan. 1, 2014 (abandoned), which is a continuation of Ser. No. 13/729,510 filed on Dec. 28, 2012 (now U.S. Pat. No. 8,654,829), which is a division of U.S. patent application Ser. No. 12/269,488 filed on Nov. 12, 2008 (now U.S. Pat. No. 8,467,437), which is a division of U.S. patent application Ser. No. 11/871,666 filed on Oct. 12, 2007 (now U.S. Pat. No. 7,508,871), which is a continuation of U.S. patent application Ser. No. 10/195,129 filed on Jul. 2, 2002, now U.S. Pat. No. 7,292,629.

## FIELD OF THE INVENTION

The present invention relates generally to high speed signaling within and between integrated circuit devices, and more particularly to reducing latent signal distortions in high speed signaling systems.

## BACKGROUND

Equalizing driver circuits are often used in high speed signaling systems to mitigate the effects of inter-symbol interference and crosstalk. Referring to signaling system **100** of FIG. 1, for example, data values queued in buffer **104** are output to signal path **102** by output driver **101** simultaneously with transmission of an equalizing signal by equalizing driver **109**. In the example shown, the equalizing driver **109** includes a shift register **113** and a bank of output drivers **111** to generate an equalizing signal based on the two most recently transmitted data values and the data value to be transmitted after the present, reference value. Thus, the equalizing driver **109** constitutes a three-tap (i.e., three data source) equalizer for reducing inter-symbol interference that results from dispersion of signals transmitted near in time to the reference value (i.e., dispersion-type ISI).

While the equalizing driver **109** is effective for reducing relatively low-latency distortions such as dispersion-type ISI, other types of systematic distortions, such as signal reflections (also referred to as reflection-type ISI), tend to have a much higher latency (i.e., occur much later in time relative to transmission of the reference value) and therefore would require a substantially larger number of taps and a correspondingly larger shift register to counteract. For example, in the system of FIG. 1, a first reflection,  $A_T$ , occurs when a reference signal encounters an impedance discontinuity at a transmit-side interface **105** between a transmit-side portion (**102A**) and a backplane portion (**102B**) of the signal path **102** (e.g., a connector interface to a backplane). Because the reflection bounces between the interface **105** and the output of the transmit circuit, the reflection will arrive at the input of a receiver **103** with a

latency (i.e., delay relative to arrival of the unreflected reference signal) equal to approximately twice the reflection flight time between the transmit-side interface **105** and the transmit circuit output. Impedance discontinuities at the input to receiver **103** and at a receive-side interface **107** between a receive-side portion (**102C**) and the backplane portion (**102B**) of the signal path **102** similarly produce reflections,  $A_R$ ,  $C_T$ ,  $C_R$  and D that arrive at the receiver **103** at respective, latent times according to the additional distance traveled by the reflections. FIG. 2 is a waveform diagram of reflections  $A_T$ ,  $A_R$ , B,  $C_T$ ,  $C_R$  and D illustrating their respective latencies relative to reference signal arrival time, T ( $A_{2TR}$  corresponds to additional reflections produced by the interface **105**). Because such reflections may occur at latencies on the order of tens or even hundreds of signal transmission intervals, the shift register **113** would need to be substantially deeper in order to store the tap values needed to mitigate the resulting distortions. Moreover, the precise time at which reflections arrive at the receiver **103** are dependent upon system configuration, meaning that a generally applicable equalizer, whether implemented on the transmit or receive side of the signaling system **100**, would need a relatively large number of equalizing taps to be able to compensate for a reflection occurring at any time between the signal transmit time and a worst case latency. Unfortunately, each additional equalizing tap increases the parasitic capacitance of the transmit or receive circuit, degrading the frequency response of the circuit and potentially increasing the impedance discontinuity (and therefore the magnitude of reflected signal) at the circuit input/output.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

FIG. 1 illustrates a prior-art signaling system;

FIG. 2 is a waveform diagram of reflected signals produced by the prior-art signaling system of FIG. 1;

FIG. 3 illustrates a signaling system according an embodiment of the invention;

FIG. 4 illustrates an exemplary relationship between clock and data signals in the signaling system of FIG. 3;

FIG. 5 illustrates the manner in which pre-emphasis and selectable-tap equalization are employed to reduce low- and high-latency distortions in the signaling system of FIG. 3;

FIG. 6 illustrates a transmit device having circuitry for selecting between temporal equalization and cross-talk cancellation data sources;

FIG. 7 illustrates transmit and receive devices configured to perform near-end cross-talk cancellation;

FIG. 8 illustrates a transceiver device that includes both an equalizing transmitter and an equalizing receiver;

FIG. 9 illustrates an equalizing transceiver according to an embodiment in which both transmitted and received data values are stored and selectively used to source equalizer taps;

FIG. 10 illustrates an exemplary buffer that may be used within the receiver of FIG. 3;

FIG. 11 is a flow diagram of an exemplary method of selecting a data value having desired symbol latency from the buffer of FIG. 10;

FIG. 12 illustrates an exemplary embodiment of a tap select circuit;

FIG. 13 illustrates an exemplary embodiment of the select logic of FIG. 12;

FIG. 14 illustrates a generalized select circuit that may be used to select Q tap values from the buffer circuit of FIG. 12;

FIG. 15 illustrates an embodiment of a switch element that may be used within the switch matrix of FIG. 14;

FIG. 16 illustrates an embodiment of an equalizing receiver;

FIG. 17 illustrates the receive circuit of FIG. 16 in greater detail;

FIG. 18 illustrates an exemplary timing relationship between clock, data and equalization signals in the equalizing receiver of FIG. 16;

FIG. 19 illustrates a current-sinking output driver that may be used within the equalizing receiver of FIG. 16;

FIG. 20 illustrates an embodiment of a push-pull type of sub-driver circuit that may be used within an equalizing output driver;

FIG. 21 illustrates another embodiment of a sub-driver circuit that may be used within an equalizing output driver;

FIG. 22 illustrates an alternative type of equalizing circuit that may be used in embodiments of the invention;

FIG. 23 illustrates an embodiment of a level shifting circuit that may be used within the equalizing circuit of FIG. 22;

FIG. 24 illustrates another type of equalizing circuit that may be used in embodiments of the invention;

FIG. 25 illustrates an embodiment of a level shifting circuit that used within the equalizing circuit of FIG. 24;

FIG. 26 illustrates an equalizing receiver according to an embodiment of the invention;

FIG. 27 illustrates a shift register and tap selector that may be used within the equalizing receiver of FIG. 26;

FIG. 28 illustrates an equalizing receiver for receiving a double data rate, multilevel input signal according to an embodiment of the invention;

FIG. 29 illustrates an exemplary encoding of bits according to the level of a sampled, multilevel input signal;

FIG. 30 illustrates an exemplary timing relationship between clock, data and equalization signals in an equalizing receiver;

FIG. 31 illustrates an embodiment of an equalizing receiver that generates receive and equalization clock signals having the phase relationship shown in FIG. 30;

FIG. 32 illustrates the use of embedded scoping to generate a trace of a data signal over a single symbol time;

FIG. 33 illustrates an embodiment of a signaling system that employs embedded scoping to determine equalizer tap selections, tap weights and tap polarities;

FIG. 34 illustrates an exemplary trace record for a pulse waveform captured by an embedded scope within the signaling system of FIG. 33;

FIG. 35 illustrates a method of setting equalization coefficients in a signaling system according to the invention; and

FIG. 36 illustrates a signaling system that employs path length symmetry to reduce the total number of equalization taps needed to compensate for reflection-type ISI.

### DETAILED DESCRIPTION

In the following description, specific nomenclature is set forth to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that these specific details may not be required to practice the present invention. In some instances, the interconnection between circuit elements or circuit blocks may be shown as multi-conductor or single conductor signal lines. Each of the multi-conductor signal lines may alternatively be single signal conductor lines, and each of the single conductor

signal lines may alternatively be multi-conductor signal lines. A signal is said to be “asserted” when the signal is driven to a low or high logic state (or charged to a high logic state or discharged to a low logic state) to indicate a particular condition. Conversely, a signal is said to be “deasserted” to indicate that the signal is driven (or charged or discharged) to a state other than the asserted state (including a high or low logic state, or the floating state that may occur when the signal driving circuit is transitioned to a high impedance condition, such as an open drain or open collector condition). A signal driving circuit is said to “output” a signal to a signal receiving circuit when the signal driving circuit asserts (or deasserts, if explicitly stated or indicated by context) the signal on a signal line coupled between the signal driving and signal receiving circuits. A signal line is said to be “activated” when a signal is asserted on the signal line, and “deactivated” when the signal is deasserted. Additionally, the prefix symbol “I” attached to signal names indicates that the signal is an active low signal (i.e., the asserted state is a logic low state). A line over a signal name (e.g., ‘<signalname>’) is also used to indicate an active low signal. Active low signals may be changed to active high signals and vice-versa as is generally known in the art.

Signaling systems and circuits for equalizing low- and high-latency signal distortions are disclosed herein in various embodiments (herein, equalizing refers to counteracting, canceling or otherwise reducing signal distortion). In one embodiment, low-latency distortions (e.g., dispersion-type ISI, cross-talk, etc.) are reduced by a transmit-side equalization circuit, and high-latency distortions (e.g., signal reflections) are reduced by a receive-side equalization circuit; the latency of receive-side equalization taps being offset relative to the reception time of a reference signal by the number of transmit-side equalization taps.

Because data values received within an equalizing receiver are stored for parallel transfer to application logic, stored data is available to supply receive-side equalizer taps; no additional shift register or other storage circuit is necessary to store equalizer data. In one embodiment, a select circuit is provided to selectively route a relatively small subset of the stored data values to equalizing taps within the equalizing receiver. By this arrangement, reflected signals arriving at various, latent times may be counteracted by routing of selected stored data values to the receive-side equalization taps. Because the number of equalizing taps within the equalizing receiver is small relative to the range of time for which distortion events are mitigated, the parasitic capacitance of the equalizing receiver is small relative to the parasitic capacitance that would result from providing a dedicated tap for each stored data value.

### Signaling System with Selectable-Tap Equalizer

FIG. 3 illustrates a signaling system 117 according to an embodiment of the invention. The system 117 includes an equalizing transmitter 115 and equalizing receiver 116 coupled to one another via a high-speed signal path 122, and a controller 141 coupled to the transmitter 115 and the receiver 116 via relatively low-speed signal paths 142A and 142B, respectively. In one embodiment, the signal path 122 is formed by component signal paths 122A, 122B and 122C (e.g., transmission lines that introduce respective, nonzero propagation delays and exhibit respective impedance characteristics), each disposed on respective circuit boards that are coupled to one another via circuit board interfaces 125 and 127 (e.g., connectors). In a specific implementation, signal path 122B is formed on a backplane and signal paths

122A and 122C are formed on respective daughterboards (e.g., line cards) that are removably coupled to the backplane via connectors 125 and 127. The transmitter 115 and receiver 116 are implemented in respective integrated circuit (IC) devices that are mounted on the daughterboards. The controller, which may be a general or special purpose processor, state machine or other logic circuit, is implemented within a third integrated circuit device mounted to a yet another circuit board. In the embodiment of FIG. 3, signal paths 142A and 142B are used to convey configuration information from the controller 141 to the transmitter 115 and receiver 116, respectively, and may be disposed on the same circuit board (or circuit boards) as signal path 122 or implemented by an alternative structure such as a cable. The controller may alternatively be coupled to the transmitter 115 and receiver 116 by a shared signal path such as a multi-drop bus. The operation of the controller 141 is discussed in greater detail below. In alternative embodiments, the IC devices containing the transmitter 115, receiver 116 and controller 141 may be mounted to a common structure with the signal paths 122, 142A and 142B coupled directly to the IC devices (e.g., all three ICs mounted to a circuit board and coupled to one another via circuit board traces, or all three ICs packaged within a single multi-chip module with signal paths 122 and 142 formed between the ICs by bond wires or other conducting structures). Also, the transmitter 115, receiver 116 and controller 141, or any subset thereof, may be included within the same IC device (e.g., system on chip) and the signal paths 122 and/or 142 implemented by a metal layer or other conducting structure within the IC device.

The transmitter 115 transmits data on the signal path 122 during successive time intervals, referred to herein as symbol times. In one embodiment, illustrated by the timing diagram of FIG. 4, each symbol time,  $T_s$ , corresponds to a half cycle of a transmit clock signal, TCLK, such that two data values (e.g., values A and B) are transmitted on signal path 122 per transmit clock cycle. The transmitted data signal arrives at the input of receiver 116 after propagation time,  $T_p$ , and is sampled by the receiver 116 in response to edges of a receive clock signal, RCLK. Still referring to FIG. 4, the receive clock signal has a quadrature phase relation to data valid windows (i.e., data eyes) in the incoming data signal such that each sample is captured at the midpoint of a data eye. In alternative embodiments, the sampling instant may be skewed relative to data eye midpoints as necessary to satisfy signal setup and hold time requirements in the receiver 116. Also, more or fewer symbols may be transmitted per cycle of the transmit clock signal.

The equalizing transmitter 115 includes a transmit shift register 124, output driver 121 and equalizer circuit 129; the equalizer circuit 129 itself including a shift register 120 and a bank of output drivers 131. At the start of each symbol time, the data value at the head of the transmit shift register 124, referred to herein as the primary data value, is driven onto the signal path 122 by the output driver 121, and the equalizer circuit 129 simultaneously drives an equalizing signal onto the signal path 122. This type of equalization is referred to herein as transmit preemphasis. In one embodiment, the signal driven onto the signal path 122 by the output driver 121 (referred to herein as the primary signal) is a multi-level signal having one of four possible states (e.g., defined by four distinct signal ranges) and therefore constitutes a symbol representative of two binary bits of information. In alternative embodiments, the primary signal may have more or fewer possible states and therefore represent more or fewer than two binary bits. Also, the primary signal

may be single-ended or differential (an additional signal line is provided to carry the complement signal in the differential case), and may be a voltage or current mode signal.

Each of the output drivers 131 within the equalizer circuit 129 form either a pre-tap driver or post-tap driver according to whether the source data value has already been transmitted (post-tap data) or is yet to be transmitted (pre-tap data). In the specific embodiment of FIG. 3, the equalizer includes N post-tap drivers sourced by data values within the shift register 120 and one pre-tap driver sourced by a data value within the transmit shift register 124. Accordingly, the resultant equalizing signal driven onto the data path 122 will have a signal level according to data values having symbol latencies of  $-1, 1, 2, \dots, N$ , where the symbol latency of a given data value refers to the number of symbol times by which transmission of the data value precedes the transmission of the primary value. Different numbers of post-tap and pre-tap drivers may be provided in alternative embodiments, thereby allowing for equalization based on values having different symbol latencies.

Still referring to FIG. 3, the receiver 116 includes a sampling circuit 123, buffer 132, tap select circuit 128 and tap select logic 139. Data signals are sampled by the sampling circuit 123, then stored in the buffer 132 for eventual use by application logic (not shown). Because the buffered data is stored for at least a predetermined time, and represents historical data up to a predetermined number of symbol latencies, the buffered data forms an ideal source of post-tap data values. That is, in contrast to transmit-side buffering of post-tap data values (which requires dedicated storage such as shift register 120), buffering of received data in receiver 116 incurs no additional storage overhead because the received data values are buffered in any event to facilitate transfer to receive-side application logic. Additionally, the tap select circuit 128 enables a subset of data values within the buffered data to be selected to source equalizer taps in a receive-side equalizer circuit. Because the subset of data values may be selected according to the precise symbol latencies of reflections and other high-latency distortions, a relatively small number of data values may be selected to form receive-side equalization taps having latencies that match the latencies of the distortions. By this arrangement, high latency distortions may be reduced by receive-side equalization without dramatically increasing the parasitic capacitance of the receiver (i.e., as would result from a large number of receive-side equalization taps).

In one embodiment, the tap select logic is a configuration circuit that outputs a tap select signal according to a configuration value. As discussed below, the configuration value may be automatically generated by system 117 (e.g., at system startup) or may be empirically determined and stored within the configuration circuit or elsewhere within system 117.

Still referring to FIG. 3, numerous alternative types of equalization circuits may be used within the receiver 116. For example, in one embodiment, the receiver 116 includes an output driver 140 (illustrated in dashed outline in FIG. 3 to indicate its optional nature) to drive an equalizing signal onto the signal path 122 (and therefore to the input of the sampling circuit 123) coincidentally with the symbol time of an incoming signal. In another embodiment, the sampling circuit 123 includes a preamplifier having an equalizing subcircuit. In yet another embodiment, an equalizing subcircuit is coupled to the sampling circuit itself. Each of these embodiments is described in further detail below.

Still referring to FIG. 3, the distribution of low- and high-latency equalization functions between the equalizing

transmitter **115** and equalizing receiver **116** is achieved through use of a dead range within the receive-side buffer **132**. That is, the range of stored data values that may be selected to source receive-side equalization taps (i.e., R) is offset from the sampling instant by a number of symbol times, M. In one embodiment, M is equal to N, the number of post-tap drivers, such that transmit preemphasis is used to reduce distortions resulting from symbol transmissions up to N symbol times prior to transmission of the primary signal, and receive-side equalization is used to reduce distortions resulting from symbol transmissions more than N symbol times prior to transmission of the primary signal. For example, if there are four post-tap drivers in the transmitter **116** (i.e., M=N=4), then the lowest latency value within the range, R, of stored data values is M+1=5 symbol times, and the receiver **116** is said to have a dead range of four symbol times. In the embodiment of FIG. 3, buffer **132** is formed by a shift register having a dead range component **133** and a selectable-range component **135**, the tap selector **128** being coupled to the selectable-range component **135** to select the subset of tap data sources therefrom. In alternative embodiments, the dead range component of the buffer **132** may include fewer than M storage elements or even zero storage elements, depending on the time required to receive data and transfer data into the buffer **132**. Also, the tap selector **128** may be coupled to one or more storage elements within the dead range component **133** to enable the size of the dead range to be programmed according to the configuration of the transmit circuit **115**. Finally, as discussed below, the buffer **132** may include one or more parallel registers in addition to (or instead of) the shift register formed by components **133** and **135**.

FIG. 5 illustrates the manner in which pre-emphasis at the transmitter **115** and selectable-tap equalization within the receiver **116** are employed to reduce low- and high-latency distortions in the signaling system of FIG. 3. Waveform **148** depicts the state of the signal path **122** during and after non-equalized transmission of a primary signal to illustrate the low- and high-latency distortions that may result. The primary signal is transmitted during a transmit interval **149** (i.e., a symbol time) that starts at time T, and the corresponding primary value is used to generate a transmit-side equalization signal (i.e., preemphasis signal) over a window of N symbol times following the transmit interval **149**. The transmit-side equalization signal is used to reduce low-latency distortions that may result from any number of sources including, without limitation, dispersion-type ISI, inductive and capacitive coupling (which may be compensated, for example, by sourcing a pre-emphasis output driver within bank **131** with a value being transmitted on a neighboring signal path), and low-latency reflections (e.g., reflections that do not travel significantly further than the unreflected primary signal and therefore arrive at the receiver shortly after the primary signal). The primary signal is sampled by the receiver **116** during a reception interval (i.e., data valid window) that corresponds to the transmit interval **149**, the reception interval being shifted relative to the transmit interval according to the signal flight time between the transmitter **115** and receiver **116**. The selectable-tap equalizer within the receiver **116** has a dead range of M symbol times and a selectable range of R symbol times. Accordingly, the sampled primary value (i.e., the primary received during the reception interval) is selectable to source an equalizer tap within the receiver **116** when the symbol latency of the sampled primary value is greater than M symbol times and less or equal to R symbol times. Thus, during given reception interval, previously received values

having symbol latencies ranging from M+1 to R may be selected by the tap selector **128** of FIG. 3 and used to reduce high-latency distortions. Intervals **150<sub>1</sub>**, **150<sub>2</sub>**, and **150<sub>3</sub>** within interval **153** illustrate equalization windows achieved by tap selections within the tap selector **128**. For example, interval **150<sub>1</sub>** corresponds to one or more tap selections used to equalize a distortion occurring shortly after the dead range, while interval **150<sub>3</sub>** corresponds to one or more tap selections used to reduce a distortion caused by a signal transmission dozens or even hundreds of symbol times prior to the current reception interval. In the transmit circuit **115** of FIG. 3 and other equalizing transmitters disclosed herein, the polarity of signal contributions which form the transmit preemphasis signal (including any cross-talk cancellation component thereof) may be fixed or programmable and may be established (or controlled) within the data shift registers (i.e., **124** and **120**) or by the output drivers themselves (e.g., output drivers within bank **131**). Similarly, in the receive circuit **116** of FIG. 3 and other equalizing receivers disclosed herein, the polarity of signal contributions which form the receiver equalization signal (including any cross-talk cancellation component thereof) may be fixed or programmable and may be established (or controlled) within a data storage circuit (i.e., buffer **132**) or within a receiver equalization circuit.

The ability to control tap data latencies with the tap select logic **139** and tap selector **128** of FIG. 3 enables the equalization windows **150** to be shifted within the selectable range, R, as necessary to reduce high-latency distortions, thereby permitting generalized application of system **117** in environments having a variety of different distortion characteristics. In the signaling system **117** of FIG. 3, the controller **141** is used to configure one or more of the values of N, M and R (i.e., the number of transmit-side post-tap equalizers, the receive-side dead range and the receive-side selectable range) according to system needs. In one embodiment, the controller includes a non-volatile memory to store empirically or analytically determined values of N, M and R. Alternatively, the signaling system **117** may include a separate storage (e.g., flash memory, or other non-volatile media) to store values of N, M and R (or values that may be used to determine N, M and R), the controller **141** being coupled to access such separate storage via signal path **142** or another path. In either case, when the signaling system **117** is initially powered on, the controller **141** communicates the post-tap equalizer count, N, to the transmitter **115** and the dead range and selectable range values, M and R, to the receiver **116**. Alternatively, the values of N, M and R may be determined at production time (e.g., through system testing) or design time, and pre-programmed into configuration circuitry within the transmitter **115** and/or receiver **116**, or fixed by design of the transmitter **115** and/or receiver **116**. In such embodiments, the controller **141** and signal path **142** may be omitted altogether.

As discussed below, embodiments of the invention may additionally include circuitry to automatically determine distortion latencies and to select correspondingly latent data tap sources from the buffer **132**, thus providing a system-independent solution for reducing systematic distortion events of virtually any latency. The controller **141** may be used to coordinate operation of the transmitter **115** and receiver **116** during such automatic distortion latency determination, and also to determine appropriate settings of N, M and R based on such distortion latencies.

#### Far-End and Near-End Cross-Talk Cancellation

As discussed above in reference to FIG. 3, the transmit-side equalizer circuit **129** may be used to reduce signal

distortion resulting from inductive and capacitive coupling of signals transmitted on neighboring signal paths; a type of equalization referred to as far-end cross-talk cancellation. In one embodiment, the output driver bank **131** includes additional output drivers to generate equalization signals based on values being transmitted on signal paths that are adjacent or otherwise proximal to the signal path **122**. By appropriate polarity control (performed, for example, within the output drivers or data shift register), an equalizing signal having a polarity opposite that of an interfering neighboring signal is transmitted on the signal path **122**, thereby reducing the signal interference.

The number of equalizer taps needed for cross-talk cancellation within a given signaling system is dependent on the physical layout of signal paths relative to one another. For example, in a system in which signal paths **122** are arranged relative to one another such that cross-talk interference is negligible (e.g., paths **122** are spaced apart, arranged in an orthogonal disposition (e.g., twisted pair), etc.), no equalizer taps may be needed for cross-talk cancellation. By contrast, in a system in which signal paths form parallel adjacent paths (e.g., parallel traces on a printed circuit board or parallel conductors within a multi-conductor cable), one or more equalizer taps may be needed for each adjacent pair of signal paths. In one embodiment of the invention, equalizer taps are selectively coupled to either pre-tap, post-tap or cross-talk cancellation data sources (i.e., primary value being transmitted on neighboring path). By this arrangement, equalizer taps may be selectively configured, according to system requirements, to provide either temporal equalization (i.e., pre-tap and/or post-tap equalization) or cross-talk cancellation.

FIG. 6 illustrates a transmit device **151** having circuitry for selecting between temporal equalization and cross-talk cancellation data sources. The transmit device **151** includes transmitters **152<sub>1</sub>** and **152<sub>2</sub>**, each for transmitting data signals on a respective signal path **122<sub>1</sub>** and **122<sub>2</sub>**. Respective sources of transmit data values (TX DATA1 and TX DATA2) are provided from other logic (not shown) within transmit device **151**. Although only two transmitters **152** are shown, additional transmitters may be provided in accordance with the number of signal paths **122** and/or the number of sources of transmit data values.

Each of the transmitters **152** includes a transmit shift register (**124<sub>1</sub>**, **124<sub>2</sub>**), output driver (**121<sub>1</sub>**, **121<sub>2</sub>**), post-tap data shift register (**120<sub>1</sub>**, **120<sub>2</sub>**) and output driver bank (**131<sub>1</sub>**, **131<sub>2</sub>**) that operate generally as described in reference to FIG. 3. Each transmitter **152** additionally includes a tap data source selector (**153<sub>1</sub>**, **153<sub>2</sub>**) having one or more multiplexers for selectively coupling either a local data value (e.g., a pre-tap or post-tap data value from corresponding transmit shift register **124** or post-tap data shift register **120**) or a remote data value (e.g., a primary value supplied from the head of a transmit shift register **124** of another transmitter, or a post-tap data value supplied from the post-tap data shift register of another transmitter) to be the equalization tap data source. For example, multiplexer A within tap data source selector **153<sub>1</sub>** has a first input coupled to a storage element within post-tap data shift register **120<sub>1</sub>** and a second input coupled to the output of transmit shift register **124<sub>2</sub>**, and selects, according to a select signal SEL<sub>1A</sub>, either a post-tap data value within shift register **120<sub>1</sub>**, or the remote primary value output by shift register **124<sub>2</sub>** to be the tap data source for an output driver within output driver bank **131<sub>1</sub>**. Multiplexer J within tap data source selector **153<sub>1</sub>** has a first input coupled to a storage element within the transmit shift register **124<sub>1</sub>** and a second input coupled to the output of the

transmit shift register **124<sub>2</sub>**, and selects, according to a select signal SEL<sub>1J</sub>, either a pre-tap data value within the transmit shift register **124<sub>1</sub>**, or the remote primary value to be the data tap source for an output driver within output driver bank **131<sub>1</sub>**.

To enable cancellation of crosstalk interference that lasts for more than a single symbol time, additional multiplexers may be provided within the tap data source selectors **153** to select between local data values (pre- or post-tap) and remote post-tap data values. For example, multiplexer K within tap data source selector **153<sub>1</sub>** has a first input coupled to receive a pre-tap data value from transmit shift register **124<sub>1</sub>** and a second input coupled to receive a remote post-tap data value from post-tap register **120<sub>2</sub>**, and selects between the two inputs according to select signal SEL<sub>1K</sub>. Tap data source selector **153<sub>2</sub>** similarly includes one or more multiplexers to select between pre-tap, post-tap and/or cross-talk cancellation data sources for output driver bank **131<sub>2</sub>**. By this arrangement, output drivers within banks **131** may alternatively be used to generate temporal equalization signals or cross-talk cancellation signals according to system needs.

Although the multiplexers within tap data source selectors **153<sub>1</sub>** and **153<sub>2</sub>** are depicted as two-input multiplexers, multiplexers having more than two inputs may alternatively be used. For example, multiplexer A of data source selector **153<sub>1</sub>** may include one or more inputs to receive pre-tap data values from register **124<sub>1</sub>**, one or more inputs to receive post-tap data values from post-tap register **120<sub>1</sub>**, and/or one or more inputs to receive cross-talk cancellation data values (i.e., remote primary, pre-tap and/or post-tap values from any number of other transmitters **152**). In general, each output driver within an output driver bank **131** may be sourced by a multiplexer that selects between any number of pre-tap, post-tap and/or cross-talk cancellation data sources. Also, not all output drivers within output driver banks **131** need be fed by multiplexers, but rather may be coupled to dedicated tap data sources.

In one embodiment, the select signals, SEL<sub>1</sub> (including signals SEL<sub>1A</sub>, SEL<sub>1J</sub>, SEL<sub>1K</sub>, etc.) and SEL<sub>2</sub>, are generated by a configuration circuit (not shown) within transmit device **151** or elsewhere in a signaling system that includes transmit device **151**. The configuration circuit may be pre-programmed or may be programmed at system start-up, for example, by a controller similar to controller **141** of FIG. 3.

As described in reference FIG. 6, selective-tap transmit-side preemphasis may be used to cancel or reduce interference between signals transmitted in the same direction on neighboring or otherwise proximal signal lines (i.e., far-end cross-talk). Selective-tap receive-side equalization may similarly be used to reduce interference between outgoing and incoming transmissions on proximal signal lines; interference referred to herein as near-end cross-talk.

FIG. 7 illustrates transmit and receive devices (**118** and **119**, respectively) configured to perform near-end cross-talk cancellation. The transmit device **118** includes an output driver **121**, transmit shift register **124**, post-tap data shift register **120**, and output driver bank **131**, all of which operate generally as described above in reference to transmit device **115** of FIG. 3 to enable generation of an equalized transmit signal (TX OUT) on signal path **122<sub>1</sub>**. Though not shown in FIG. 7, the transmit device **118** may additionally include select circuitry as described in reference to FIG. 6 to enable selection of various equalization data sources.

The receive device **119** includes a sampling circuit **123**, buffer **132**, tap select circuit **137**, tap select logic **139** and equalization circuit (e.g., included within the sampling cir-

circuit **123** or implemented as an output driver **140**) to receive an incoming signal (RX IN) on signal path **122**. As shown in FIG. 7, the incoming signal, RX IN, has a smaller amplitude than the transmit signal, TX OUT, (e.g., due to transmission losses) and therefore is particularly susceptible to near-end cross-talk interference. To counteract cross-talk interference from the TX OUT transmission, pre-tap, primary and post-tap data values used to generate the TX OUT signal (i.e., from transmit shift register **124** and post-tap data shift register **120**) are supplied to the tap select circuit **137** within the receiver **119**. By this arrangement, the tap select logic **139** may select, as tap values for the receiver equalization circuit, any combination of the received data values stored within buffer **132**, and the pre-tap, post-tap and primary data values used to generate the TX OUT signal. As discussed above in reference to FIG. 3, tap select logic **139** outputs a control signal to the tap selector **137** to control tap data source selection according to system configuration information. Thus, the pre-tap, post-tap and/or primary data values may be selected with the polarity necessary to achieve a subtractive effect on the corresponding cross-talk interference (the appropriate polarity being established or controlled within the buffer **132** or receiver equalizing circuit), thereby enabling reduction of near-end cross-talk interference. Although only a single tap select circuit **137** is shown in FIG. 7, any number of tap select circuits may be used.

#### Bi-Directional Signaling

Although a unidirectional signaling system is depicted in FIG. 3, embodiments of the invention are equally applicable in a bidirectional signaling system. FIG. 8, for example, illustrates a transceiver device **151** that may be coupled to either or both sides of signal path **122**, and that includes both an equalizing transmitter **115** and an equalizing receiver **116** according to embodiments described herein (transmitters and receivers according to the cross-talk canceling embodiments described in reference to FIGS. 6 and 7 may also be used). The transceiver device **151** additionally includes an application logic circuit **154** to provide transmit data to the equalizing transmitter **115** and to receive sampled data from the equalizing receiver **116**. The application logic circuit **154** also outputs an enable signal (ENABLE) to alternately enable the transmitter **115** to transmit data on the signal path **122** or the receiver **116** receive data from the signal path **122**.

FIG. 9 illustrates an equalizing transceiver **155** according to an embodiment in which both transmitted and received data values are stored and selectively used to source equalizer taps. The transceiver **155** includes a transmit shift register **124**, output driver **121**, post-tap data shift register **120** and output driver bank **131** (which may include output drivers sourced by pre-tap data values, cross-talk cancellation values, or by tap data source selectors as described in reference to FIG. 6), all of which operate generally as described in reference to FIG. 3 to output, during a given transmit interval, a primary signal and corresponding equalization signal onto signal path **122**. The transceiver also includes a sampling circuit **123**, buffer circuit **132**, tap selector **156** and tap select logic **157**. The sampling circuit **123** samples data signals transmitted on signal path **122** (i.e., by a remote transmitter or transceiver) and stores the corresponding data values in buffer circuit **132**. The tap selector **156** is coupled to the buffer circuit **132** as well as the transmit shift register (including the head of the transmit shift register which contains the primary data value) and the post-tap data shift register **120**, and therefore enables any

combination of received data values (i.e., from buffer **132**) and pre-tap, primary and/or post-tap transmit data values to be selected as source data taps within an equalizing circuit (i.e., output driver **140** or an equalizing circuit within the sampling circuit **123**). The tap select logic **157** outputs a control signal to the tap selector according to system configuration information (i.e., information indicative of desired symbol latencies) and the historical state of the enable signal (ENABLE). Thus, depending on the desired symbol latencies of data taps, and the times at which the transceiver **155** is transitioned between sending and receiving data (i.e., turnaround times), the tap select logic **157** and tap selector **156** operate to select tap values from the transmit shift register **124**, data tap shift register **120**, and/or buffer circuit **132** in any combination. The selected tap values are then used to source equalizer taps within an equalizing output driver **140** or an equalizing circuit within sampling circuit **123**.

Although the transceiver embodiments described in reference to FIGS. 8 and 9 include an enable line to alternately enable transmission or reception of signals, in alternative embodiments, the enable line may be omitted and transmission and reception of signals may occur simultaneously (i.e., simultaneous bi-directional signaling). In such a system, multilevel signaling may be used to enable an outgoing signal to be transmitted simultaneously (in effect, superimposed on) an incoming signal. Because the receive circuit has access to the transmitted data values, the receive circuit may subtract the locally transmitted signal from an incoming signal to recover only the desired portion (i.e., remotely transmitted portion) of the incoming signal. In such a system, the locally transmitted signal may produce dispersion- and reflection-type ISI that may be compensated by an equalizing receiver having, as an example, the configuration of FIG. 9, but omitting the enable line. In such an embodiment, the transmit shift register **124** and post-tap data register **120** may be selected by tap select circuit **156** to source tap data values for equalization of low- and/or high-latency distortions resulting from the local signal transmission (i.e., by output driver **121**). Note that the post-tap data register may need to be extended (i.e., have an increased number of entries) to enable reduction of high-latency distortions resulting from the local signal transmission. The receive circuit tap selections, controlled by tap select logic **157**, may be determined empirically or during run-time, for example, by using the methods and circuits described below for determining equalization tap latencies, weights and polarities.

#### Data Tap Selection

FIG. 10 illustrates an exemplary buffer **159** that may be used within the receiver **116** of FIG. 3 and that includes both a serial shift register **161** as well as a number (K) of parallel-load registers **165<sub>1</sub>-165<sub>K</sub>**. At each edge of a receive clock signal, RCLK, a newly sampled data value **160** is loaded from sampling circuit **123** into the shift register **161**. The shift register is formed by N storage elements (depicted as flip-flops **163<sub>1</sub>-163<sub>N</sub>**, though latches or other types of storage elements may be used) coupled in daisy chain fashion such that, as the newly sampled value **160** is loaded into the first storage element **163<sub>1</sub>** in the shift register **161**, the contents of each storage element **163** except the last (**163<sub>N</sub>**) is shifted to the next storage element in the chain in response to a receive clock signal (RCLK). Thus, designating the output of storage element **163<sub>1</sub>** to have symbol latency i, the symbol latency of the input value **160** is i-1,

and the symbol latencies of the outputs of the remaining storage elements **163** in the shift register **161** are, from left to right,  $i+1$ ,  $i+2$ , . . . , and  $i+(N-1)$ , respectively.

A shift counter **169** (which may be included within or separate from buffer circuit **159**) maintains a count of the number of data values shifted into the shift register **161**, incrementing the shift count in response to each transition of RCLK. In one embodiment, the shift counter **169** asserts a load signal **164** (LD) upon reaching a count that corresponds to a full shift register, then rolls the shift count back to a starting value. The load signal **164** is routed to strobe inputs of storage elements within the parallel-load registers **165**, enabling parallel load register **165<sub>1</sub>** to be loaded with the contents of the shift register, and enabling each of the parallel-load registers **165<sub>2</sub>-165<sub>K</sub>** to be loaded with the content of a preceding one of the parallel load registers (i.e., **165<sub>2</sub>** is loaded with the content of **165<sub>1</sub>**, **165<sub>3</sub>** is loaded with **165<sub>2</sub>**, and so forth). By this arrangement, the symbol latency of a data value stored within any of the parallel-load registers **165** is dependent on how many data values have been shifted into the shift register since the last assertion of the load signal **164**; a measure indicated by the shift count. For example, if the shift count is 1, indicating that the load signal **164** was asserted at the immediately preceding edge of RCLK, then the content of storage element **167<sub>1</sub>** of parallel-load register **165<sub>1</sub>** has a symbol latency of  $i+1$  (i.e., one symbol time older than the content of storage element **163<sub>1</sub>** of the shift register). When the next value is shifted into the serial shift register **161**, the contents of the parallel registers **165** remain unchanged, meaning that the latency of each data value stored in the parallel registers **165** is increased by a symbol time. Thus, the content latency (i.e., latency of a stored value) of a given storage element within one of parallel registers **165** is dependent upon the value of the shift count. Referring to parallel load register **165<sub>1</sub>**, for example, the content latency of storage element **167<sub>1</sub>** is  $i+SC$  (SC being the shift count), the content latency of storage element **167<sub>2</sub>** is  $i+SC+1$ , and so forth to storage element **167<sub>N</sub>**, which has a content latency of  $i+(N-1)+SC$ . The content latencies of storage elements within the parallel-load registers **165<sub>2</sub>-165<sub>K</sub>** are similarly dependent upon the shift clock value, SC, but are increased by N for each parallel load away from register **165<sub>1</sub>**. That is, the content latency of the leftmost storage element within register **165<sub>2</sub>** is  $i+N+SC$ , and the content latency of the leftmost storage element within register **165<sub>K</sub>** is  $i+(K-1)N+SC$ . The content latencies of the storage elements within registers **165<sub>2</sub>-165<sub>K</sub>** are incrementally related to the content latency of the corresponding leftmost storage element in the same manner that the content latencies of storage elements **167<sub>2</sub>-167<sub>N</sub>** relate to the content latency of storage element **167<sub>1</sub>**.

FIG. 11 illustrates, in flow diagram form, a method of selecting a data value having symbol latency  $i+X$  from the buffer **159** of FIG. 10,  $i$  being the content latency of storage element **163<sub>1</sub>**. At **175**,  $X$  is compared with  $N$ , the number of storage elements within the shift register **161** and within each of the parallel-load registers **165**. If  $X$  is less than  $N$ , then the desired data value is located within the shift register which, after being initially loaded, always contains data values having symbol latencies ranging from  $i$  to  $i+N-1$ . Thus, if  $X$  is less than  $N$ , then as shown at **177**, the desired value is in the shift register (REG=SR) at bit position  $X$  (BIT= $X$ ), where the bit position corresponds to left-to-right numbered storage elements.

If  $X$  is not less than  $N$ , then the desired data value is located at a shift-count-dependent bit position within one of the parallel-load registers **165**. Thus, if  $X$  is less than  $N+SC$

(**179**), the desired data value is located within register **165<sub>1</sub>** at bit position  $X-SC$ , as indicated at **181**. To understand this result, consider what happens if a data value having a desired symbol latency is initially within the rightmost storage element, **167<sub>N</sub>**, within parallel-load register **165<sub>1</sub>**. As a new value is shifted into the serial shift register **161** and the shift count is incremented, the symbol latency of storage element **167<sub>N</sub>** is increased, and the storage element one position to the left of storage element **167<sub>N</sub>** (i.e., **167<sub>N-1</sub>**) now contains the data value having the desired symbol latency and is therefore selected to supply the data value to an equalizer tap.

Returning to FIG. 11, if  $X$  is greater than or equal to  $N+SC$ , then  $X$  is compared with  $2N+SC$  at **183**. If  $X$  is less than  $2N+SC$ , then parallel-load register **165<sub>2</sub>** contains the desired tap value at bit position  $X-N-SC$  as indicated at **185**. The decision flow continues in this manner to **187** at which point  $X$  is compared with  $(K-1)N+SC$ . If  $X$  is less than  $(K-1)N+SC$ , then parallel-load register **165<sub>K-1</sub>** contains the desired tap value at position  $X-(K-1)N-SC$  as indicated at **189**. Otherwise,  $X$  is located within the final parallel-load register, **165<sub>K</sub>** at position  $X-KN-SC$  as indicated at **191**.

FIG. 12 illustrates an exemplary embodiment of a tap select circuit for selecting a tap value ( $DATA_{i+X}$ ) from a buffer circuit **210** that includes an eight-bit serial shift register **161** and two eight bit parallel-load registers **165<sub>1</sub>**, **165<sub>2</sub>**. For purposes of illustration, it is assumed that the data value in the first (leftmost) storage element within the shift register **161** has a symbol latency of one and that the dead range is four symbol times (i.e., the leftmost four storage elements within the shift register **161** are not used to source tap values to the equalizer). By this arrangement, immediately after a parallel load operation, the data values stored in parallel-load register **165<sub>1</sub>** will have symbol latencies ranging from 2-9 symbol times, and the data values stored in parallel-load register **165<sub>2</sub>** will have symbol latencies ranging from 10-17 symbol times. Accordingly, reflections (or other distortions) appearing at the receiver input between 5 and 17 symbol times after the corresponding primary signal may be reduced by selecting data values having corresponding symbol latencies from the buffer circuit **210** to drive the receive-side equalizer taps (i.e., to be tap data values). Multiplexers **205**, **207<sub>1</sub>** and **207<sub>2</sub>** are responsive to low order bits of a latency value **200** ( $X[4:0]$ ) to select tap positions within the shift register **161**, parallel-load register **165<sub>1</sub>**, and parallel-load register **165<sub>2</sub>**. The latency value **200** is additionally supplied to a select logic circuit **201** which generates a register select signal, SEL[1:0], to select one of the three registers **161**, **165<sub>1</sub>** and **165<sub>2</sub>** within the buffer circuit **210** to source the tap data value,  $DATA_{i+X}$ . It should be noted that, because the range of tap values extends over 13 possible symbol times (symbol latencies from 5-17), a smaller, four-bit latency value may alternatively be used to select a tap value. As described below, however, using a latency value large enough to select any of the bit positions within the buffer circuit **210** enables the size of the dead range to be adjusted (i.e., programmed) according to application needs.

The least significant two bits of the latency value **200** (i.e.,  $X[1:0]$ ) are input to multiplexer **205** to select one of the four selectable data values within the serial shift register **161**. The least three significant bits of the latency value **200** (i.e.,  $X[2:0]$ ) are input to a subtract circuit **203** which subtracts the shift count **202** from the three-bit latency value to produce a tap select value for the parallel-load registers **165<sub>1</sub>**, **165<sub>2</sub>**. In one embodiment, for example, the select value **200** corresponds to a desired symbol latency as shown in Table

15

1 below, and the shift count **202** is encoded in a three-bit value, SC[2:0], as shown in Table 2 below. Thus, when the shift count **202** is eight (SC[2:0]=000), and the select value is nine (X[4:0]=01000), the output of the subtract circuit **203** will be: X[2:0]-SC[2:0]=0; a value that corresponds to the leftmost bit position within each of the parallel-load registers **165**. This is a desired result as the leftmost bit positions within registers **165** have symbol latencies 9 and 17 when the shift count is eight. The multiplexer **209** will generate a select signal **204** (SEL[1:0]) to select the data value from register **165**<sub>1</sub> (symbol latency=9) to source the tap data value (this operation is discussed below). As a further example, when the shift count **202** is one and the select value **200** is nine, the output of the subtract circuit **203** will be: 000-001=111 (decimal 7); the rightmost bit position within each of the parallel-load registers **207**. Again, this is a desired result as the rightmost bit positions with registers **165** have symbol latencies 9 and 17 when the shift count is one.

TABLE 1

X[4]	X[3]	X[2]	X[1]	X[0]	Tap Latency
0	0	1	0	0	5
0	0	1	0	1	6
0	0	1	1	0	7
0	0	1	1	1	8
0	1	0	0	0	9
0	1	1	0	0	10
0	1	1	0	0	11
0	1	1	0	0	12
0	1	1	0	0	13
0	1	1	0	0	14
0	1	1	0	0	15
0	1	1	0	0	16
1	0	0	0	0	17

TABLE 2

SC[2]	SC[1]	SC[0]	Shift Count
0	0	1	1
0	1	0	2
0	1	1	3
1	0	0	4
1	1	0	5
1	1	1	6
1	1	1	7
0	0	0	8

FIG. 13 illustrates an exemplary embodiment of the select logic **201** of FIG. 12. The select logic **201** includes a comparator circuit **215** to compare the latency select value **200** with N (the size, in bits, of each of registers within buffer circuit **210**), a summing circuit **217** to sum the shift count **202** with N (thereby generating SC+N), and a comparator circuit **219** to compare the latency select value **202** with the output of the summing circuit **217**. If the latency select value **200** is less than N, the output of comparator **215** will go high, causing inverter **223** to drive the high order bit of select signal **204** low and OR gate **221** to drive the high order bit of the select signal **204** high. That is, SEL[1:0]=01 so that multiplexer **209** will select the shift register **161** to source the tap data value; the desired result when the select value **200** is less than N. If the select value **200** is greater than or equal to N, the output of comparator **215** will go low, thereby driving the high order bit of select signal **204** high, and enabling the output of comparator **219** to control, via OR gate **221**, the state of the low order bit of select signal

16

**204**. If the latency select value **200** is less than the output of summing circuit **217** (SC+N), the output of comparator **219** will be low causing select signal SEL[0] to be low, thereby producing SEL[1:0]=10 and selecting parallel-load register **165**<sub>1</sub> to source the tap data value. If the latency select value **200** is greater than or equal to the output of the summing circuit **217**, the output of comparator **219** will be high, resulting in a select value of SEL[1:0]=11, thereby selecting parallel-load register **165**<sub>2</sub> to source the tap data value.

Reflecting on the structure of FIG. 13, it should be noted that the summing circuit and comparators may have numerous implementations depending on the size of N and the number of bits used to form the latency select value **200** and shift count **202**. For example, where the latency select value **200** and shift count **202** have the five- and three-bit configurations shown, and N is eight, the sum of the shift count and N (performed by circuit **217** in FIG. 13) may be formed simply by including an additional bit in parallel with the three shift count bits, the additional bit forming the most significant bit of the resulting sum (i.e., sum[3]) while SC[2:0] form the less significant three bits of the sum (i.e., sum[2:0]). As another example, the comparator **215** may be implemented by a NOR gate having inputs coupled to X[4] and X[3]. By this arrangement, the X<N output will be high only if both X[4] and X[3] are low. Numerous other logic circuits may be used to implement the select logic circuit **201** of FIG. 12 in alternative embodiments. More generally, specific numbers of bits and registers have been described for purpose of example only. Alternative embodiments may include different numbers of registers having various sizes, and latency select values and shift count values having different sizes. Also, any circuit for selecting a data value based on a latency select value may alternatively be used without departing from the spirit and scope of the present invention.

FIG. 14 illustrates a generalized select circuit **230** that may be used to select Q tap values from the buffer circuit **210** of FIG. 12. The select circuit **230** includes a switch matrix **231** and tap select logic **235**. In the embodiment of FIG. 14, each of the possible tap data sources within the buffer circuit **210** (i.e., the rightmost four bits within shift register **161** and all the bits within the parallel-load registers **165**) are coupled to respective column lines **234** of the switch matrix **231**, and each of the Q tap outputs are coupled to respective row lines **236** of the switch matrix **231**. A switch element **233** is provided at each row-column intersection to enable the tap data source for the column to be selectively coupled to the tap output for the row. The tap select logic **235** outputs a respective one of enable signals E<sub>1</sub>-E<sub>20</sub> to each column of switch elements based on latency selection values X<sub>1</sub>-X<sub>Q</sub> and shift count, SC. In the embodiment of FIG. 14, each enable signal includes Q component signals coupled respectively to the Q switch elements within a corresponding column. Thus, if the column 1 data value (i.e., the data value stored in shift register position 4), is selected to be the data source for tap Q, then select signal E<sub>j</sub>[Q:1]=100.00. More generally, E<sub>j</sub>[i]=1 for each column data value, j, to be coupled to a tap output, i. By this arrangement, the Q tap outputs may be selected from among the complete range of data values stored within buffer circuit **210**. In one embodiment, the select logic includes combinatorial logic that operates as described in reference to FIG. 10 to generate each enable signal. Alternatively, a state machine or other processing logic may be used to generate the enable signals in accordance with the latency selection values and shift count.

FIG. 15 illustrates an embodiment of a switch element 233 that may be used within the switch matrix 231 of FIG. 14. The switch element includes a transistor 235 having source and drain terminals coupled between the  $i^{\text{th}}$  row line 236<sub>*i*</sub> (TAP<sub>*i*</sub>) and the  $j^{\text{th}}$  column line 235<sub>*j*</sub> (DATA<sub>*j*</sub>) of the switch matrix, and a gate terminal coupled to receive the  $i^{\text{th}}$  component signal of enable signal  $j$  (i.e.,  $E_j[i]$ ). Thus, when the  $E_j[i]$  is high, indicating that  $i^{\text{th}}$  tap output is to be sourced by the data value at the  $j^{\text{th}}$  position within the range of selectable data values, transistor 235 is switched on to couple the selected data source to the tap output. Other types of switching elements may be used in alternative embodiments.

### Equalizing Circuits

As discussed above in reference to FIG. 3, the tap values selected by the tap select logic 139 and select circuit 128 may be used in a number of different equalizing circuits to counteract distortion events. In one equalizing receiver embodiment, illustrated in FIG. 16, an equalizing output driver 140 is coupled in parallel with the sampling circuit 123 to drive an equalizing signal back onto the signal path 122 during each symbol reception interval (i.e., symbol time during which a valid symbol is present at the input of the receiver). By this arrangement, latent distortions arriving at the receiver during a symbol reception interval may be canceled (or at least reduced) by operation of the equalizing output driver 140.

FIG. 17 illustrates the receive circuit of FIG. 16 in greater detail. As shown, the sampling circuit 123 may include any number of preamplifiers 240<sub>1</sub>-240<sub>*N*</sub> coupled in series with a sampler 241. The sampler 241 may be any type of circuit for detecting the level of an input signal, including but not limited to a latching circuit that latches the signal level in response to a rising or falling clock edge, or an integrating circuit that integrates the input signal over a finite period of time (e.g., a symbol time or portion of a symbol time). The equalizing output driver 140 may be coupled to the signal path 122 (i.e., the input of the first preamplifier 240<sub>1</sub>) or, alternatively, to the output of any of the preamplifiers 240. Also, as discussed below, the output driver 140 may be coupled to the sampler 241 to affect the sampling operation.

In one embodiment, the equalizing output driver 140 of FIGS. 15 and 16 is clocked by an equalizer clock signal, EQCLK, that is offset from the clock signal used to time the sampling instant and therefore to define the symbol reception interval (i.e., receive clock signal, RCLK), as necessary to align edges of the equalizing signal (i.e., state transitions) with edges of the incoming data signal. This timing relationship is illustrated by FIG. 18. As shown, the equalizer clock signal is aligned with edges of the incoming symbol stream so that equalization values are transmitted onto the signal path concurrently with corresponding symbol reception intervals. As discussed below, the equalizer clock signal may be further offset from the receive clock signal as shown by arrow 245 to account for the time required for the equalization data (i.e., selected tap values) to propagate through the equalizing output driver 140 or other equalizing circuit.

FIG. 19 illustrates a current-sinking output driver 250 that may be used to implement the equalizing output driver 140 of FIG. 16. The output driver includes a plurality of sub-driver circuits 251<sub>1</sub>-251<sub>*N*</sub>, each sub-driver circuit 251 including a current source 257, clocking transistor 122 and data tap transistor 253 coupled in series between an output node 254 and a reference voltage (ground in this example).

Control terminals (e.g., gate terminals) of the data tap transistors 253 of the sub-driver circuits 251 are coupled to receive respective data tap values (designated EQD<sub>1</sub>-EQD<sub>*N*</sub> in FIG. 19) from a select circuit, control terminals of the current sources 257 are coupled to respective tap weight values, EQW<sub>1</sub>-EQW<sub>*N*</sub>, and control terminals of the clocking transistors are coupled in common to receive the equalizer clock signal, EQCLK. By this arrangement, when the equalizer clock signal goes high, each of the sub-driver circuits will source a current according to its respective tap weight and data tap inputs. For example, referring to sub-driver circuit 251<sub>1</sub>, if tap data value EQD<sub>1</sub> is low, no current (or negligible) current will be drawn via output node 254. By contrast, if tap data value EQD<sub>1</sub> is high, then the sub-driver circuit 251<sub>1</sub> will draw a current from the output node 254 (and therefore from the signal path 122) according to the tap weight, EQW<sub>1</sub>. As discussed below, the tap weights provided to the output driver 250 or other equalizing circuits described herein may be predetermined values, or may be determined dynamically according to the level of the distortions to be reduced. Because the sub-driver circuits 251 are coupled in parallel to the output node, the overall equalization signal generated by output driver 250 during a given symbol time is the sum of contributions from the individual sub-driver circuits 251. Note that the output driver 250 outputs an equalization signal only when the equalizer clock signal is high (i.e., even phases of EQCLK). An additional instance of output driver 250 may be provided to output an equalization signal when a complement equalizer clock signal (i.e., /EQCLK) is high.

FIG. 20 illustrates an embodiment of a push-pull type of sub-driver circuit 260 that may be used within an equalizing output driver instead of the pull-down sub-driver circuits 251 described in reference to FIG. 19. In the push-pull type of sub-driver circuit 260, current is either sourced or sunk via the driver output according to the state of the tap data value, EQD<sub>*j*</sub>. The sub-driver circuit 260 includes switching transistors 263 and 265, and AND gate 261. A first input of the AND gate 261 is coupled to receive the tap data value, EQD<sub>*j*</sub>, and a second input of the AND gate 261 is coupled to a clock line to receive the equalizer clock signal, EQCLK. The output of the AND gate 261 is coupled to the gate terminals of transistors 263 and 265 such that, during each high phase of the equalizer clock signal, the tap data value is passed to the gate terminals of transistors 263 and 265 to establish the output state of the sub-driver circuit 260. That is, every other half cycle of the equalizer clock signal constitutes an output enable interval for the sub-driver circuit 260. If the tap data value, EQD<sub>*j*</sub>, is high during a given output enable interval, transistor 265 is switched on, causing the sub-driver circuit 260 to sink current via the output node (OUT<sub>*j*</sub>). Conversely, if the tap data value is low during the output enable interval, transistor 263 is switched on to source current via the output node. Also, though not shown in FIG. 20, a pull-down biasing circuit (e.g., current source) may be coupled between the pull-down data tap transistor 265 and ground, and a pull-up biasing circuit may be coupled between the pull-up data tap transistor 263 and the supply reference voltage (e.g., V<sub>DD</sub>) to enable weighted control of the current sourcing and sinking strength of the push-pull sub-driver circuit 260. Further, an additional instance of the sub-driver circuit 260 may be provided with a complement equalizer clock signal (/EQCLK) and complement tap data value (/EQD<sub>*j*</sub>) being input to AND gate 261 to enable the sub-driver circuit 260 to output an equalizing signal during the alternate half cycle of the equalizer clock signal.

FIG. 21 illustrates another embodiment of a sub-driver circuit 275 that may be used within an equalizing output driver. The sub-driver circuit 275 includes a differential transistor pair 277 having control terminals coupled to outputs of AND gates 261<sub>1</sub> and 261<sub>2</sub>, respectively. A tap data value (EQD<sub>i</sub>) and an equalizer clock signal (EQCLK) are input to AND gate 261<sub>1</sub>, and a complement of the tap data value (/EQD<sub>i</sub>) and the equalizer clock signal are input to AND gate 261<sub>2</sub>. By this arrangement, the tap data value and complement tap data value are applied to respective inputs of the differential pair 277 during every other half cycle of the equalizer clock signal. Output nodes of the differential pair 277 are pulled up through respective resistive loads 283 (R), and source terminals of the differential pair are coupled to ground via a current source 281. The resistive loads 283 may be, for example, termination elements coupled to the signal path (not shown) rather than resistive elements included within the sub-driver circuit 275. Accordingly, the sub-driver circuit 275 is enabled, during every other half cycle of the equalizer clock signal, to output a differential equalizing signal on output nodes OUT<sub>i</sub> and /OUT<sub>i</sub> in accordance with the complementary tap data values, EQD<sub>i</sub> and /EQD<sub>i</sub>. A counterpart instance of sub-driver circuit 275 may be provided to generate a differential equalizing signal during the alternate half clock cycle of the equalizer clock signal. The current source 281 is controlled by the tap weight value, EQW<sub>i</sub> in the manner described in reference to FIG. 19, though different weighting schemes may be used in alternative embodiments (e.g., using weight-biased pull-up elements in place of resistive elements 283).

FIG. 22 illustrates an alternative type of equalizing circuit 290 that may be used in embodiments of the invention. Instead of driving an equalization signal onto the signal path to affect the signal level of an incoming signal, equalization is performed in conjunction with preamplification of the incoming signal, and therefore affects the level of preamplification applied to the incoming signal. That is, the equalizing circuit 290 affects the preamplified signal level instead of the signal level present on the signaling path.

Equalizing circuit 290 includes a differential amplifier 294 formed by differential transistor pair 291, biasing current source 292 and resistive loads 293. Differential input signals are supplied to gate terminals of transistor pair 291 such that differentially amplified output signals are generated on output lines P<sub>OUT</sub> and /P<sub>OUT</sub>. In one embodiment, output lines P<sub>OUT</sub> and /P<sub>OUT</sub> are coupled to input terminals of a differential amplifier within a sampling circuit so that amplifier 294 effectively forms a first stage in a two-stage amplifier (i.e., amplifier 294 is a preamplifier).

Equalizing circuit 290 additionally includes a level shifting circuit 296 coupled to the differential amplifier 294 to provide preamplifier equalization. The level shifting circuit 296 includes a pair of sub-circuits 298<sub>1</sub> and 298<sub>2</sub> each coupled between a respective one of the differential amplifier outputs (P<sub>OUT</sub> and /P<sub>OUT</sub>) and a clocking transistor 299. Each of the signal subcircuits 298 includes a respective plurality of data tap transistors (295<sub>1</sub>-295<sub>N</sub> and 297<sub>1</sub>-297<sub>N</sub>) coupled in parallel between the differential amplifier output and the clocking transistor 299. The control terminals of the data tap transistors 295<sub>1</sub>-295<sub>N</sub> are coupled to receive the selected data tap values, EQD<sub>1</sub>-EQD<sub>N</sub>, respectively, and the control terminals of the data tap transistors 297<sub>1</sub>-297<sub>N</sub> are similarly coupled to receive complement versions of the selected data tap values, /EQD<sub>1</sub>-/EQD<sub>N</sub>. In one embodiment, each of the data tap transistors 295 is sized (e.g., by width-length ratio) to achieve a respective tap weight EQW<sub>N</sub>-EQW<sub>1</sub>. By this arrangement, each data tap value

may be coupled to the control terminal of a selected one of the data tap transistors 295 according to the desired tap weight. The transistors 297 are similarly weighted and therefore allow coupling of the complement data tap values according to desired tap weights. The weights of the individual data tap transistors 295 (and 297) may be incrementally related (i.e., EQW<sub>1</sub>=EQW<sub>2</sub>+K=EQW<sub>3</sub>+2K . . . , where K is a constant), exponentially related (i.e., EQW<sub>1</sub>=EQW<sub>2</sub>\*K=EQW<sub>3</sub>\*K<sup>2</sup> . . . ) or may have any other desired relationship (including having the same weight values or including subsets of weight values that are the same).

The clocking transistor 299 is switched on during every other half cycle of the equalizer clock signal to enable the operation of the subcircuits 298. The subcircuits 298 operate to increase or decrease the difference between the preamplified output signals (or even change the polarity of the difference) by drawing more current from one of the preamplifier output lines (P<sub>OUT</sub> or /P<sub>OUT</sub>) than the other in accordance with the selected data tap values. Thus, the subcircuits 298 act to differentially shift the level of the preamplified output signal generated by differential amplifier 294. An additional instance of the equalizing circuit 290 may be provided to enable preamplifier equalization during the alternate half cycle of the equalizer clock signal.

FIG. 23 illustrates an alternative level shifting circuit 305 that may be substituted for circuit 296 of FIG. 22. In circuit 305, differential pairs of data tap transistors 307<sub>1</sub>-307<sub>N</sub> are coupled to output lines P<sub>OUT</sub> and /P<sub>OUT</sub> in the same manner as in circuit 296, but instead of sizing the data tap transistors to achieve tap weighting, tap weighted current sources 311<sub>1</sub>-311<sub>N</sub> are coupled in series with the differential pairs of data tap transistors 307<sub>1</sub>-307<sub>N</sub>, respectively. For example, current source 311<sub>1</sub> is controlled by (i.e., draws a bias current according to) weight value ECM and is coupled via clocking transistors 309<sub>1</sub> to data tap transistors 307<sub>1</sub>. Similarly, current source 311<sub>2</sub> is controlled by weight value EQW<sub>2</sub> and is coupled via clocking transistors 309<sub>2</sub> to transistors 307<sub>2</sub>, and so forth. By this arrangement, the weight values EQW<sub>1</sub>-EQW<sub>N</sub> may be configured (e.g., via run-time calibration or production time programming) as necessary to establish a desired equalizing signal contribution from each differential pair of data tap values 307. An additional instance of the equalizing circuit 290 may be provided to enable preamplifier equalization during the alternate half cycle of the equalizer clock signal (i.e., by driving clocking transistors 309 with complement equalizing clock, /EQ-CLK).

FIG. 24 illustrates another type of equalizing circuit 320 that may be used in embodiments of the invention. Instead of driving an equalization signal onto the signal path to affect the signal level of an incoming signal, or affecting the preamplified signal level, a level shifting circuit 330 is coupled to low impedance inputs of a differential sampling circuit 328, and is used to affect the level of the input signal before the sampled signal is captured. The sampling circuit includes differential transistor pair 329 to precharge input nodes S<sub>IN</sub> and /S<sub>IN</sub> according to the state of a differential input (e.g., the output of a preamplifier 294 of FIG. 22, or a differential data signal), during a first half cycle of the receive clock (which enables clocking transistor 331). During a second half cycle of the receive clock signal, transistors 321 and 325 are switched on by the low-going receive clock signal, thereby enabling a cross-coupled latch formed by transistors 322, 323, 325 and 326 to latch the state of the precharged signal levels on nodes S<sub>IN</sub> and /S<sub>IN</sub>.

The level shifting circuit **330** is similar to the circuit **296** of FIG. **22** except that clocking transistor **341** is enabled by the receive clock signal (RCLK) instead of the equalizer clock signal, the equalizer clock signal being used to switch on switching transistors **335**<sub>1</sub>-**335**<sub>N</sub> and **339**<sub>1</sub>-**339**<sub>N</sub> during every other half cycle. Data tap transistors **333**<sub>1</sub>-**333**<sub>N</sub>, which are controlled by respective tap data values EQD<sub>1</sub>-EQD<sub>N</sub>, are coupled in series with the switching transistors **335**<sub>1</sub>-**335**<sub>N</sub>, respectively. Similarly, data tap transistors **337**<sub>1</sub>-**337**<sub>N</sub> are coupled in series with switching transistors **339**<sub>1</sub>-**339**<sub>N</sub> and are controlled by respective complement tap data values/EQD<sub>1</sub>-/EQD<sub>N</sub>. In one embodiment, the data tap transistors **333**, **337** and switching transistors **335**, **339** are sized to provide different current draws according to predetermined weights, EQW1-EQWN, thereby permitting different data taps to make different level-shifting contributions. In one embodiment, for example, the switching transistors **335** and **339** are binary weighted such that, when switched on, the current draw through transistor pair **333**<sub>N</sub>/**335**<sub>N</sub> is 2<sup>N-1</sup> times the current through transistor pair **333**<sub>1</sub>/**335**<sub>1</sub> (and the current draw through transistor pair **337**<sub>N</sub>/**339**<sub>N</sub> is 2<sup>N-1</sup> times the current through transistor pair **337**<sub>1</sub>/**339**<sub>1</sub>). Other weighting schemes may also be used including, without limitation, thermometer coding of high-gain transistor pairs, linear weighting schemes, or any combination of exponential (e.g., binary), linear and thermometer coded weightings.

In one embodiment, the equalizer clock is phase advanced relative to the receive clock signal such that transistors **337** and **339** are switched on in advance of clocking transistor **341**. By this arrangement, transistors **333** and **337** are poised to shift the level of the sampling circuit input nodes, S<sub>TN</sub> and/S<sub>TN</sub>, when the receive clock signal goes high. Thus, when the receive clock signal goes high, sampling circuit input nodes S<sub>TN</sub> and/S<sub>TN</sub> are differentially discharged according to the tap data values EQD<sub>1</sub>-EQD<sub>N</sub>, /EQD<sub>1</sub>-/EQD<sub>N</sub> and the respective weights of transistors **333** and **337**. Consequently, the signal levels at the input nodes, S<sub>TN</sub> and/S<sub>TN</sub>, of sampling circuit **328** are differentially shifted by the level shifting circuit **330** to reduce static offsets in the incoming data signal (applied to control terminals of differential pair **329**) caused by reflections or other distortions.

FIG. **25** illustrates an alternative level shifting circuit **342** that may be substituted for circuit **330** of FIG. **24**. The level shifting circuit **342** includes data tap transistors **333**, **33** and equalizer-clock-enabled switching transistors **335**, **339** coupled as described in reference to FIG. **24**. However, rather than being coupled to a clocking transistor **335**, the source terminals of transistors **335**<sub>1</sub>-**335**<sub>N</sub> are coupled to ground via capacitive elements **334**<sub>1</sub>-**334**<sub>N</sub>, respectively, and the source terminals of transistors **339**<sub>1</sub>-**339**<sub>N</sub> are similarly coupled to ground via capacitive elements **338**<sub>1</sub>-**338**<sub>N</sub>. By this arrangement, respective variable capacitances are coupled to the low impedance inputs, S<sub>TN</sub> and/S<sub>TN</sub>, of the sampling circuit **328** according to the states of the tap data values EQD<sub>1</sub>-EQD<sub>N</sub> and complement data tap values EQD<sub>1</sub>-EQD<sub>N</sub> applied to the inputs of data tap transistors **333** and **337**. Thus, different levels of capacitance are added to the sampling circuit input nodes, S<sub>TN</sub> and/S<sub>TN</sub>, according to the tap data values, effectively changing the discharge rates of the input nodes and therefore affecting the precharged signal level at the input nodes as desired to reduce signal distortions. In the embodiment of FIG. **25**, the data tap transistors **333**, **337** and switching transistors **335**, **339** have uniform sizes (i.e., uniform weighting), and the capacitive elements **334**, **338** have weighted capacitive values to permit a broad range of capacitances to be coupled to the input nodes of sampling circuit **328**. For example, in one embodiment, the

capacitive elements **334** are implemented by source-to-drain coupled transistors and are binary weighted (e.g., by adjusting transistor width-length ratios) such that capacitive element **335**<sub>2</sub> has twice the capacitance of capacitive element **335**<sub>1</sub>, and capacitive element **335**<sub>N</sub> has 2<sup>N-1</sup> times the capacitance of capacitive element **335**<sub>1</sub>. Other weighting relationships (e.g., thermometer coding, linear, uniform, etc.) may also be used. Also, the data tap transistors **333**, **337** and/or switching transistors **335**, **339** may be weighted in alternative embodiments instead of (or in addition to) the capacitive elements **334**, **338**.

### High Speed Tap Selector

As discussed above in reference to FIG. **3**, an incoming data signal may include two symbols per receive clock cycle (sometimes referred to as a "double data rate" signal), and each symbol may have more than two possible states (i.e., may have a signal level falling within more than two distinct ranges of signals). Also, the receive clock frequency may be so high that by the time a sampled data value is loaded into the buffer circuit **132**, the data value already has a latency of several symbol times. All these factors present challenges to the buffering and selection of tap values described in reference to FIG. **3**.

FIG. **26** illustrates an equalizing receiver **350** according to an embodiment of the invention. The receiver **350** includes a double data rate sampling circuit **351**, shift register **353**, select circuit **355** and equalizing output driver **357**. The sampling circuit **351** includes a pair of sub-circuits **361**<sub>1</sub> and **361**<sub>2</sub> to sample the incoming data signal in response to rising edges in the receive clock (RCLK) and complement receive clock (/RCLK), respectively. Falling clock edges may alternatively be used to time the sampling instant. Data samples captured in response to edges of the receive clock are referred to herein as even phase data, and data samples captured in response to edges of the complement receive clock are referred to as odd phase data. Thus, sampling circuit **351** outputs even phase data (EVEN IN) and odd phase data (ODD IN) to the shift register **353** via signal lines **362**<sub>1</sub> and **362**<sub>2</sub>, respectively. The even and odd phase data values are stored within the shift register to provide a source of selectable tap values to the select circuit **355**. In the embodiment of FIG. **26**, the dead range is assumed to be five symbol latencies (other dead ranges may be used) such that data values D<sub>T+5</sub>-D<sub>T+x</sub> are provided to the select circuit **355**, subscript T+5 indicating a latency of five symbol times relative to sampling instant, T. The select circuit **355** includes N tap selectors, **365**<sub>1</sub>-**365**<sub>N</sub>, that select from among the plurality of data values stored within the shift register **353** and output a selected tap data value to a respective one of N output sub-drivers **369**<sub>1</sub>-**369**<sub>N</sub> within the equalizing output driver **357**. Each of the output sub-drivers **369**, in turn, drives a component equalizing signal onto the signal path **122**. In alternative embodiments, the equalizing output driver **357** may be replaced by an equalizing circuit that operates within a preamplifier circuit (not shown in FIG. **26**) or sampling circuit **351** as described above in reference to FIGS. **17-20**.

FIG. **27** illustrates the shift register **353** and one of the tap selectors **365** of FIG. **26** according to more specific embodiments. The shift register includes a pair of shift sub-circuits **383**<sub>1</sub> and **383**<sub>2</sub> to store even phase data and odd phase data, respectively. In one embodiment, each of the shift sub-circuits **383** includes a number of storage elements **381** (e.g., latches) coupled in a daisy chain configuration (i.e., output to input) to enable an input data value to be shifted progres-

sively from a first (i.e., leftmost) storage element **381** in the chain to a last (rightmost) storage element **381** in the chain. Each of the shift sub-circuits **383** is responsive to the receive clock and complement receive clock signals such that the contents of each shift sub-circuit **383** is shifted during each half clock cycle of the receive clock signal. Thus, assuming that a stream of incoming symbols includes the data sequence A, B, C, D, etc., then even phase data values A, C, E, G, I, etc. will be shifted into shift sub-circuit **383**<sub>1</sub> and odd phase data values B, D, F and H will be shifted in to shift sub-circuit **383**<sub>2</sub>. Because the contents of the shift sub-circuit **383**<sub>1</sub> are shifted twice per even phase data reception, two instances of each even phase data value will be stored in the shift sub-circuit **383**<sub>1</sub>. The second instance of each even phase data value stored in shift sub-circuit **383**<sub>1</sub> is designated by a prime (i.e., ') in FIG. 27 to indicate that the data value was loaded synchronously with the loading of a newly received odd phase data value into shift sub-circuit **383**<sub>2</sub>. Similarly, two instances of each odd phase data value are stored in the shift sub-circuit **383**<sub>2</sub>, with the second instance of the odd phase data value being designated by a prime to indicate that the data value was loaded synchronously with the loading of a newly received even phase data value into shift sub-circuit **383**<sub>1</sub>. Thus, from the perspective of the tap selector **365**, the shift sub-circuits **383** collectively contain a sequence of data values, A', B, C', D, E' F, G', H, that may be used to generate odd phase equalizing signals (i.e., driving an equalizing signal onto the signal path or affecting signal levels within a preamplifier or sampling circuit during odd phase symbol reception), and a sequence of data values, B', C, D', E, F', G, H', I, that may be used to generate even phase equalizing signals. Accordingly, the outputs of each of the storage elements **381** within shift sub-circuit **383**<sub>1</sub> are coupled to respective inputs of an even tap data select circuit **387**<sub>1</sub> within the tap selector **365**, and the outputs of each of the storage elements **381** within the shift sub-circuit **383**<sub>2</sub> are coupled to respective inputs of an odd tap data select circuit **387**<sub>2</sub> within the tap selector **365**. The even and odd tap data select circuits **387** are responsive to a select signal, S[2:0], to output selected tap data values from the even and odd phases sequences of data values, respectively. The select signal may be generated, for example, by tap the select logic **139** described in reference to FIG. 3.

The output of the even tap data select circuit is clocked into a flip-flop **391**<sub>1</sub> (or other storage element) at the rising edge of the receive clock signal (RCLK) so that, at any given time, the output of flip-flop **391**<sub>1</sub> is delayed by two symbol times relative to the most latent data value supplied to the even tap data select circuit **387**<sub>1</sub>. Similarly, the output of the odd tap data select circuit **387**<sub>2</sub> is clocked into a flip-flop **391**<sub>2</sub> (or other storage element) so that, at any given time, the output of flip-flop **391**<sub>2</sub> is delayed by two symbol times relative to the most latent data value supplied to the odd tap data select circuit **387**<sub>2</sub>. Thus, the flip-flops **391** effectively increase the latency of selected even and odd data tap values by two symbol times. Select circuits **393**<sub>1</sub> and **393**<sub>2</sub> are provided to extend the overall latency range of the even and odd data tap selections within tap selector **365** by allowing selection of tap data directly from the even and odd data inputs to the shift register **353** (i.e., EVEN IN and ODD IN) or from the outputs of flip-flops **391**. Select bit S[3] is provided (e.g., by the tap select logic **139** of FIG. 3) to select between the fast path data (i.e., connections **384**<sub>1</sub> and **384**<sub>2</sub> to the inputs of the sub shift circuits **383**) and the selected data values stored in flip-flops **391**. Flip-flops **395**<sub>1</sub> and **395**<sub>2</sub> (or other storage elements) are provided to synchronize the

outputs of multiplexers **393**<sub>1</sub> and **393**<sub>2</sub> with the receive clock and complement receive clock, respectively. Thus, even and odd data tap values, ETD and OTD, each having a range of latencies according to the depth of the shift sub-circuits **383** and the number of fast path taps (of which signal lines **384**<sub>1</sub> and **384**<sub>2</sub> are examples) are output to the equalizing circuit (not shown in FIG. 27) to enable even and odd phase equalization of an incoming signal.

FIG. 28 illustrates an equalizing receiver **405** for receiving a double data rate, multilevel input signal according to an embodiment of the invention. The receiver **405** includes a sampling circuit **407**, shift register **411**, select circuit **421** and equalizing output driver **427**. The sampling circuit includes even and odd phase sampling sub-circuits **409**<sub>1</sub> and **409**<sub>2</sub> to capture even and odd phase samples of the incoming multilevel data signal and to generate a multi-bit output indicative of the sampled signal level. For example, in one embodiment, the incoming data signal has one of four possible signal levels, each level being defined by a distinct range of voltages. In the specific embodiment depicted in FIG. 28, each sample is resolved (i.e., by sampling sub-circuits **409**) to a thermometer code in which bits A, B, and C have values according to which of four voltage ranges the sampled signal level falls within. Referring to FIG. 29, for example, bits A, B and C are set according to the following relationships between the sampled signal,  $V_S$ , and high, middle and low threshold voltage levels:

TABLE 3

Sampled Signal Level, $V_S$	C	B	A
$V_S > T_H$	0	0	0
$T_H > V_S > T_M$	0	0	1
$T_M > V_S > T_L$	0	1	1
$T_L > V_S$	1	1	1

Other encoding schemes may be used in alternative embodiments. Also, more or fewer threshold levels (and therefore signal ranges) may be used, and current levels may be used to indicate signal level instead of voltage levels.

Once the sampled signal is resolved to a pattern of binary bits, A, B and C (or some other number of bits), each of the bits is input to a respective one of shift registers **413**<sub>A</sub>-**413**<sub>C</sub> and used to source a tap value for selection by a respective set of select circuits **422**<sub>A</sub>-**422**<sub>C</sub> (each select circuit including N tap select selectors **423**<sub>1</sub>-**423**<sub>N</sub>). Each of the shift registers **413** and select circuits **422** operates generally as described in reference to FIGS. 21 and 22 to generate a set of selected tap values, **424**<sub>A</sub>-**424**<sub>C</sub>. Corresponding tap values from within each set **424** are provided to a respective one of output sub-drivers **429**<sub>1</sub>-**429**<sub>N</sub> within equalizing output driver **427**, where they are used to generate a multi-level equalization signal. For example, the tap values output by tap selector **423**<sub>1</sub> within each of the select circuits **422** are input to output sub-driver **429**<sub>1</sub> of the equalizing output driver **427**.

#### Equalization Clock Signal Generation

As discussed briefly in reference to FIG. 18, it is desirable for the equalization signal generated by a receive-side equalizing output driver to be driven onto the signal path in phase alignment with data eyes in the incoming data signal. While the receive clock (or complement receive clock) may be used to clock the equalizing output driver (or preamp or sampling circuit equalizer), propagation delay through the

equalizing driver tends to become significant in high frequency systems, producing undesired timing offset between the incoming data signal and the equalization signal. In one embodiment, clock data recovery circuitry within an equalizing receiver is used to generate an equalization clock signal (EQCLK) that is phase advanced relative to the receive clock signal according to the propagation delay (i.e., clock-to-Q) of an equalizing output driver. By this timing arrangement, illustrated in FIG. 30, the equalizing output driver outputs an equalization signal having the desired phase relation with the incoming data signal. As shown, by advancing the equalization clock relative to the receive clock according to the clock-to-Q delay of the equalizing output driver, a desired phase relationship between the incoming data signal (RX DATA) and equalization signal (EQ DATA) is achieved. Note that, in the exemplary diagram of FIG. 30, the equalization data tap is assumed to have a symbol latency of five symbol times, such that an equalization signal based on received symbol A is transmitted by the equalizing output driver during the reception interval for symbol F.

FIG. 31 illustrates an embodiment of an equalizing receiver 450 that generates receive and equalization clock signals having the phase relationship shown in FIG. 30. The receiver 450 includes a sampling circuit 451, shift register 453, clock-data-recovery (CDR) circuit 457, application logic 455, tap data selector 461, signal generator 462, equalizer clock generator 459, and equalization data source selector 463. An incoming data signal (DATA) on signal path 122 is sampled by the sampling circuit 451 in response to a receive clock signal (RCLK). The samples are output to the shift register 453 where they are stored for parallel output to the application logic 455 and the CDR circuit 457. In the embodiment of FIG. 31, the receive clock signal includes multiple component clock signals including a data clock signal and its complement for capturing even and odd phase data samples, and an edge clock signal and complementary edge clock signal for capturing edge samples (i.e., transitions of the data signal between successive data eyes). The data and edge samples are shifted into the shift register 453 and then supplied as parallel words (i.e., a data word and an edge word) to a phase control circuit 467 within the CDR circuit 457. The phase control circuit 467 compares adjacent data samples (i.e., successively received data samples) within the data word to determine when data signal transitions have taken place, then compares an intervening edge sample with the preceding data sample (or succeeding data sample) to determine whether the edge sample matches the preceding data sample or succeeding data sample. If the edge sample matches the data sample that preceded the data signal transition, then the edge clock is deemed to be early relative to the data signal transition. Conversely, if the edge sample matches the data sample that succeeds the data signal transition, then the edge clock is deemed to be late relative to the data signal transition. Depending on whether a majority of such early/late determinations indicate an early or late edge clock (i.e., there are multiple such determinations due to the fact that each edge word/data word pair includes a sequence of edge and data samples), the phase control circuit 467 asserts an up signal (UP) or down signal (DN). If there is no early/late majority, neither the up signal nor the down signal is asserted. So long as a calibration signal 474 (CAL) from the application logic 455 remains deasserted, the up and down signals, when asserted, pass through AND gates 468<sub>1</sub> and 468<sub>2</sub>, respectively, to up/down inputs of mix logic 471.

The mix logic circuit 471 receives a set of phase vectors 472 (i.e., clock signals) from a reference loop circuit 470. The phase vectors have incrementally offset phase angles within a cycle of a reference clock signal (REF CLK). For example, in one embodiment, the reference loop outputs a set of eight phase vectors that are offset from one another by 45 degrees (i.e., choosing an arbitrary one of the phase vectors to have a zero degree angle, the remaining seven phase vectors have phase angles of 45, 90, 135, 180, 225, 270 and 315 degrees). The mix logic 471 maintains a phase count value which includes a vector select component to select a phase-adjacent pair of the phase vectors (i.e., phase vectors that bound a phase angle equal to  $360^\circ/N$ , where N is the total number of phase vectors), and an interpolation component (INT) which is output to a mixer circuit 473 along with the selected pair of phase vectors (V1, V2). The mixer circuit mixes the selected pair of phase vectors according to the interpolation component of the phase count to generate complementary edge clock signals and complementary data clock signals that collectively constitute the receive clock signal.

The mix logic 471 increments and decrements the phase count value in response to assertion of the up and down signals, respectively, thereby shifting the interpolation of the selected pair of phase vectors (or, if a phase vector boundary is crossed, selecting a new pair of phase vectors) to incrementally retard or advance the phase of the receive clock signal. For example, when the phase control logic 467 determines that the edge clock leads the data transition and asserts the up signal, the mix logic 471 increments the phase count, thereby incrementing the interpolation component of the count and causing the mixer to incrementally increase the phase offset (retard the phase) of the receive clock signal. At some point, the phase control signal output begins to dither between assertion of the up signal and the down signal, indicating that edge clock components of the receive clock signal have become phase aligned with the edges in the incoming data signal.

The equalizer clock generator 459 receives the phase vectors 472 from the reference loop 470 and includes mix logic 481 and an equalizer clock mixer 483 that operate in the same manner as the mix logic 471 and receive clock mixer 473 within the CDR circuit 457. That is, the mix logic 481 maintains a phase count value that is incrementally adjusted up or down in response to the up and down signals from the phase control circuit 467. The mix logic selects a phase-adjacent pair of phase vectors 472 based on a vector select component of the phase count, and outputs the selected vectors (V1, V2) and interpolation component of the phase count (INT) to the equalizer clock mixer 483. The equalizer clock mixer 483 mixes the selected vectors in accordance with the interpolation component of the phase count to generate the equalizer clock signal, EQCLK. The equalizer clock signal, which may include complementary component clock signals, is output to the equalizing output driver 465 (or other type of equalization circuit as described above) to time the output of equalizing signals onto signal path 122.

The equalizer data source selector 463 is responsive to the calibration signal 474 to select either the tap selector 461 (which operates as described above to select data tap values from the shift register 453 and/or one or more parallel registers) or the signal generator 462 that outputs clock pattern 10101010 (e.g., a bi-stable storage element that toggles between states in response to each EQCLK transition). When the calibration signal 474 is low, the equalization data source selector 463 selects the tap selector 461 to

supply selected data values to the equalizing output driver 465. When the calibration signal 474 is high, the receiver 450 enters a calibration mode in which the signal generator 462 is selected to supply the clock pattern to the equalizing output driver 465. Also, in calibration mode, the high state of the calibration signal 474 disables AND gates 468<sub>1</sub> and 468<sub>2</sub> from passing the up and down signals to the mix logic 471. Thus, the phase count within the CDR circuit remains unchanged in calibration mode, while up and down signals generated by the phase control circuit 467 are used to increment and decrement the phase count value within the mix logic 481. In one embodiment, no signals are transmitted on the signal path 122 while the receiver 450 is in calibration mode, so that the only signal present at the input of the sampling circuit 451 is the clock pattern output by the equalizing output driver 465. By this arrangement, edge and data samples corresponding to the clock pattern are captured in the shift register 453 and supplied to the phase control circuit 467 to determine whether the receive clock signal (RCLK) is early or late relative to the clock pattern samples. Accordingly, the phase control circuit 467 will assert an up or down signal (as the case may be) to adjust the phase of the receive clock signal relative to the incoming data stream. Because the receive clock phase is effectively locked, however (i.e., by operation of the AND gates 468), only the phase count within the equalization clock generator will be adjusted. Thus, the normal-mode CDR operation is effectively carried out in reverse while the receiver 450 is in calibration mode. Instead of shifting the phase of the receive clock signal to achieve alignment with transitions in the incoming data signal, the phase of the equalizer clock signal is shifted to align transitions in the incoming data signal (i.e., the clock pattern output by the equalizing output driver) with the receive clock signal. By this operation, the equalizer clock signal is advanced relative to an edge clock component of the receive clock signal by a time substantially equal to the clock-to-Q delay of the equalizing output driver 465. Thus, the overall effect of the calibration mode operation is to advance the phase of the equalization clock according to the clock-to-Q time of the equalizing output driver as shown in FIG. 30. In this way, the equalizing output driver 465 drives an equalizing signal onto the signal path 122 in phase alignment with the incoming data signal.

In one embodiment, the calibration signal 474 is asserted for a time interval previously determined to be sufficient to achieve phase alignment between transitions in the transmitted clock pattern and the edge clock component of the receive clock signal. Alternatively, the up and down signals generated by the phase control circuit may be monitored in the calibration mode to determine when the up and down signals begin to alternate, thereby indicating that the desired phase alignment has been obtained. In either case, after phase alignment has been obtained, the calibration signal is deasserted to enable normal operation of the receive circuit. At this point, the CDR circuit returns to adjusting the phase count within mix logic 471 in response to the up and down signals from the phase control circuit 467. Because the mix logic 481 within the equalizer clock generator 459 continues to respond to the same up and down signals, the phase offset between the equalizer clock signal and the receive clock signal (i.e., the phase offset established in the calibration mode) is maintained as the phases of the two clocks are adjusted. Thus, in normal-mode operation, the equalizer clock signal and receive clock signal retain the phase offset established in calibration mode, but otherwise track one another.

It should be noted that signal patterns other than the clock pattern 1010101 may be generated by the signal generator 462 and used to achieve the desired phase relationship between the equalizer clock signal and the receive clock signal. For example, the signal generator may be implemented by a pseudo random bit sequence (PRBS) generator that generates a pseudo random bit sequence. More generally, any signal generator, random or otherwise, that generates a sequence of values having a sufficient transition density (i.e., transitions per unit time) to enable phase locking in the equalizing receiver 450 (i.e., phase locking between transitions in the waveform output by output driver 465 and the receive clock signal) may be used to implement signal generator 462.

#### Determination of Equalization Tap Latencies, Weights and Polarities

Referring again to FIG. 3, tap selection logic may be implemented in a number of different ways. In one embodiment, for example, the tap select logic 139 includes a configuration circuit that may be programmed with configuration information that specifies the tap data sources to be selected by select circuit 128. The configuration circuit may include a nonvolatile memory, fusible circuit, etc. that is programmed at production time according to the symbol latency, amplitude and polarity of empirically observed (or analytically determined) distortions. Alternatively, the configuration circuit may include memory (volatile or nonvolatile) which is initialized with predetermined configuration information during system startup. In yet another embodiment, referred to herein as a self-calibrating embodiment, a signaling system includes circuitry to automatically determine the symbol latency, amplitude and polarity of distortions on the signaling path between a transmitter and receiver, and to program a configuration circuit within the tap select logic with configuration information that indicates the tap data sources to be selected by a select circuit and the tap weights and polarities to be applied by an equalization circuit.

In one self-calibrating embodiment of the invention, a technique called embedded scoping is used to determine the symbol latency, amplitude and polarity of signal path distortions. The symbol latency of a given distortion, once known, is used to select one or more tap data values having corresponding symbol latencies, and the distortion amplitude and polarity are used to determine the weight and polarity to be applied to the selected tap data value in generating an equalization response. Also, the symbol latency of a given distortion may be used to determine whether to counteract the distortion through transmitter preemphasis or receiver equalization (or both), and the overall range of symbol latencies for detected distortions may be used to determine an appropriate dead range for the signaling system.

Embedded scoping involves iteratively receiving a sequence of symbols in a receiver and comparing the received symbol sequence with a local generation of the sequence to confirm error-free reception. With each receive-and-confirm iteration, a threshold voltage used to distinguish between symbol values in the incoming signal is offset from a calibrated level by a progressively larger amount until a symbol in the sequence no longer matches the expected value. The threshold voltage offset at which the failure occurs is referred to herein as a pass/fail offset and represents a measure of the signal level at the sampling instant at which the failure occurred. Thus, by sweeping the threshold

voltage through a range of threshold voltages until the pass/fail offsets for each symbol in the symbol sequence have been detected, a sample plot for the incoming signal may be developed. Further, by sweeping the receive clock signal through an incremental sequence of phase offsets, and determining the pass/fail offset at each phase offset, a complete trace of the incoming signal may be generated. Also, the granularity and start stop points of the phase offsets and/or threshold voltage steps may be controlled (e.g., by configuring a programmable circuit or register) to enable the waveform trace to be constrained to selected points of interest in the incoming signal (e.g.,  $\pm N^\circ$  from an intended sampling instant,  $N$  representing a sweep angle).

FIG. 32 illustrates the use of embedded scoping to generate a time-based trace 490 of an incoming data signal 486. The range of threshold voltage offsets over which the incoming signal 486 is sampled is indicated by  $V_T$ , and the range of phase offsets at which the signal is sampled is indicated by  $\phi$ . Each sample point within the sweep is indicated by a respective dot within a grid of sample points 480. Note that the sweep may be obtained by stepping the voltage threshold through the range of  $V_T$  values for each value of  $\phi$ , or, alternatively, by stepping the clock phase through the range of  $\phi$  values for each value of  $V_T$ .

Still referring to FIG. 32, 488 indicates a pair of samples for which a pass/fail condition is detected. A corresponding pass/fail offset (PFO) is determined according to the difference between the calibrated  $V_T$  level ( $V_T(\text{CAL})$ ) and the average of the  $V_T$  offsets between the pass and fail samples, and recorded as a measure of the incoming signal. That is, the pass/fail offset may be used to establish a data point within the trace 490 as shown. After sweeping through all the sample points within the grid 480 (which sweep may be repeated numerous times to obtain an average and to discard statistical outliers), a measure of the incoming signal is obtained as illustrated graphically by the trace 490.

Embedded scoping has a number of benefits over traditional signal measurement techniques. First, because the technique is non-invasive (i.e., no probe contact), the electrical characteristics of the system under test are unaltered, thereby yielding potentially more accurate results. Also, the trace is generated from the perspective of the receive circuit itself, meaning that any non-ideal characteristics of the receive circuit are accounted for in the resulting signal trace information. Finally, because all components needed for embedded scoping may be included within a finished signaling system, embedded scoping may be used to perform numerous run-time analyses, including determining the latency and amplitude of reflections and other distortions within the signaling system.

FIG. 33 illustrates a signaling system 500 according to an embodiment of the invention. The signaling system 500 includes a receive device 509 and transmit device 501 that employ embedded scoping to determine equalizer tap selections, tap weights and tap polarities. The transmit device 501 includes a pattern generator 503, data selector 505, equalizing transmitter 507 and application logic 502. The application logic 502 performs the core function of the transmitting device (e.g., signal processing, instruction processing, routing control, or any other function) and provides transmit data (TX DATA) to a first input of the data selector 505. During normal operation, the application logic 502 outputs a logic low scope signal 506 (SCOPE) to the data selector 505 to select the transmit data to be passed to the equalizing transmitter 507 for transmission to the receive device 509 via signal path 122 (which may include or be connected to numerous sources of discontinuity such as connectors, vias,

stubs, etc.). During a scoping mode of operation, the application logic 502 drives the scope signal 506 high to enable a scoping mode of operation within the transmit circuit 501. In the scoping mode, the data selector 505 selects a repeating single-symbol pulse sequence (e.g., a test signal such as: 00100 . . . 00100 . . . 00100 . . .) generated by the pattern generator 503 to be transmitted to the receive device 509. The receive device 509 includes an equalizing receiver 510 to receive the incoming data signal, a pattern register 511 to store a local version of the single-symbol pulse sequence, a multiplexer 512 to enable the pattern register 511 to be switched between load and barrel-shifting modes, a XOR gate 513 to compare the received data sequence with the locally generated sequence, and application logic 515 (or other logic) to generate a clock adjust signal (CLK ADJ) and threshold voltage adjust signal (THRESH ADJ) to sweep the receive clock and threshold voltage used within the equalizing receiver through their scoping ranges. The application logic 515 additionally builds a trace record (i.e., data indicative of the incoming data sequence) based on the output of XOR gate 513.

When the receive device 509 is in a scoping mode of operation, the multiplexer 512 is initially set to load the pattern register 511 with the output of the equalizing receiver 510. After a desired sequence of data (e.g., the single-symbol pulse sequence) is shifted into the pattern register 511, the multiplexer 512 is set to enable the barrel-shifting mode of the pattern register 513. That is, the multiplexer 512 selects the output of the pattern register 511 to be fed back to the input of the pattern register 511 so that the contents of the pattern register 511 are continuously rotated through the pattern register 511 (i.e., a barrel shifting operation). By this arrangement, the data sequence loaded into the pattern register 511 is repeatedly output, bit by bit, to a first input of the XOR gate 513. The data sequence received by the equalizing receiver is input to a second input of the XOR gate 513 so that the received data sequence is compared, bit by bit, with the data sequence stored within the pattern register 511. By selecting the length of the repeatedly transmitted data sequence to match the storage size of the pattern register 511, the pattern register contents are repeatedly compared with a newly received version of the same data sequence (i.e., putatively the same data sequence). Any reception error will result in a mismatch between the received value and the corresponding value within the pattern register and therefore, when compared by XOR gate 513, will result in an error signal being output from the XOR gate 513 to the application logic 515. The application logic 515 may then record the adjusted threshold voltage and clock phase offset at which the error occurred to a signal level for a timing offset within a waveform trace.

FIG. 34 illustrates an exemplary waveform trace 527 of a pulse data sequence captured by an embedded scope within the signaling system of FIG. 33. As shown, a primary pulse 529 arrives at the receiver at symbol time,  $T_0$ ; a negative reflection 531 of the primary pulse appears at symbol time  $T_5$  and a positive reflection 533 appears at symbol time  $T_{12}$ . Thus, referring to FIG. 33, the application logic 515 of receiver 509 may store configuration information in a select logic circuit within the equalizing receiver 510 (or elsewhere within the receive device 509) to enable selection of stored data values having symbol latencies of five and twelve symbol times as tap data sources for an equalizing circuit. Alternatively, the application logic 515 may directly output select signals to select the desired stored data values as tap data sources. The application logic 515 may also generate tap weights and tap polarity values in accordance with the

amplitude and polarity of the distortions **531** and **533**, and store or output the weights and polarity values as necessary to apply the appropriate tap weights and polarities within the equalizing receiver **510**.

FIG. **35** illustrates a method of setting equalization coefficients in a signaling system according to the invention. In the embodiment shown, transmit-side equalization coefficients are set first (**541**), then receive-side equalization coefficients are set (**551**). The transmit-side coefficients are set by transmitting a test signal at **543** (e.g., a pulse signal, step, etc.), then generating a waveform trace (**545**) using the embedded scoping techniques described above. The transmit-side equalization coefficients, including tap data sources, tap weights and tap polarities, are then set at **547** to produce a received waveform trace that most closely corresponds to the ideal waveform (e.g., pulse, step, etc.) output by the transmitter. The transmit-side equalization coefficients may be determined analytically (i.e., by computing the coefficients based on the waveform trace generated at **545**) or iteratively, by repeating operations **543** and **545** for different combinations of coefficient settings until a coefficient setting that provides a desired waveform is determined.

After the transmit-side equalization coefficients have been set, the receive-side coefficients are set by transmitting the test signal at **553** (i.e., a pulse, step or other signal transmitted with equalization according to the coefficients set at **547**), then generating a waveform trace of the received waveform (**555**) using the embedded scoping techniques described above. The receive-side equalization coefficients, including tap data sources, tap weights and tap polarities, are then set at **557** to produce a received waveform that most closely corresponds to the ideal waveform (i.e., waveform having reduced high-latency distortion). The receive-side equalization coefficients may be determined analytically as described in reference to FIGS. **31-33**, or iteratively, by repeating operations **553** and **555** for different combinations of coefficient settings until a coefficient setting that provides a desired waveform is determined.

Note that selection of tap data sources within the transmitter may include outputting test signals on neighboring signal paths simultaneously with the test signal transmission at **543** to allow determination of which transmit-side equalizer taps, if any, should be sourced by cross-talk cancellation data values (i.e., data values being transmitted on neighboring signal paths) and the corresponding tap weights.

#### Reducing Equalization Taps Through Path Length Symmetry

As discussed above in reference to FIG. **3**, the tap select logic **139** and select circuit **128** enable equalization over a relatively wide range of symbol latencies using a small number of equalizer taps. In embodiments of the invention, the total number of equalizer taps is further reduced through symmetry in the electrical distances between signal path discontinuities.

FIG. **36** illustrates a signaling system that employs path length symmetry to reduce the total number of equalization taps needed to compensate for reflection-type ISI. The system includes a pair of circuit boards **571** and **573** (e.g., line cards, port cards, memory modules, etc.) having integrated circuit (IC) devices **575** and **577** mounted respectively thereon. IC device **575** includes a transmit circuit coupled to a connector interface **581** (e.g., a connector or a terminal to be received by a connector) via signal path segment **582**, and IC device **577** includes a receive circuit coupled to a connector interface **585** via signal path segment

**586**. The connector interfaces **581** and **585** are coupled to one another through signal path segment **592** (e.g., backplane trace, cable, etc.) to form an overall signal path between the transmit circuit and receive circuit.

Because the connector interfaces **581** and **585** tend to have at least slightly different impedances than the impedance of path segments **582**, **586** and **592**, reflections are produced at connector interfaces as shown by reflection flight paths  $A_T$ ,  $A_R$ ,  $C_T$  and  $C_R$ . More specifically, the reflection flight path indicated by  $A_T$  results from the primary signal reflecting off connector interface **581**, and the reflection reflecting off the output node of the transmit circuit within IC **575**. Thus, the reflection flight time over path  $A_T$  exceeds the unreflected primary signal flight time by twice the signal propagation time between the connector interface **581** and the transmit circuit output node; i.e., the signal propagation time on path segment **582**. Similarly, the reflection flight time over path  $A_R$  (reflection off receiver input, then off connector interface **585**) exceeds the unreflected primary signal flight time by twice the signal propagation time between the connector interface **585** and the receive circuit input; the signal propagation time on path segment **586**. Accordingly, if path segments **582** and **586** are designed or calibrated to have equal electrical lengths (i.e., equal signal propagation delays), reflections  $A_T$  and  $A_R$  will arrive at the input of the receive circuit of IC device **577** at substantially the same time. Consequently, a single equalization tap having a symbol latency that corresponds to the latent arrival of the coincident  $A_T/A_R$  reflections may be used to cancel or at least reduce both reflections. Because reflection flight paths  $C_T$  and  $C_R$  are made equal by equalizing the electrical lengths of path segments **582** and **586**, a single equalization tap that corresponds to the latent arrival of coincident  $C_T/C_R$  reflections may be used to cancel or at least reduce both reflections. Thus, by designing or calibrating path segments **582** and **586** to have equal electrical lengths (which path segments may optionally include an on-chip path segment between the transmit circuit output and an IC device **575** output node and/or an on-chip path segment between the receive circuit input and an IC device **577** input node), one equalization tap within either the transmit circuit or receive circuit may be used to cancel or reduce a distortion that would otherwise require two or more taps.

In one embodiment, the electrical lengths of path segments **582** and **586** are made equal (or substantially equal—as achievable through practicable manufacturing techniques) by design which may include, but is not limited to: 1) making the physical lengths of path segments **582** and **586** substantially equal, whether implemented by printed traces, cables or other types of conductors; 2) including inductive or capacitive structures (e.g., vias, ferrite materials, narrowed or widened trace regions, or any other impedance-altering structures) statically coupled in series or parallel with path segments **582** and/or **586** to equalize otherwise different electrical lengths of the path segments; and/or 3) including inductive and/or capacitive structures that may be run-time coupled (e.g., through pass gates or other electrically or magnetically controllable structures) in series or parallel with path segments **582** and/or **586** to equalize otherwise different electrical lengths of the path segments. More generally, any technique for adjusting the electrical lengths of path segments **582** and **586** to achieve coincident arrival of two or more signal reflections at the input of an equalizing receiver may be used without departing from the spirit and scope of the present invention.

Regarding run-time coupling of impedance-altering structures to path segments **582** and/or **586**, such impedance-altering structures may be selectively coupled to path segments **582** and/or **586** through operation of a configuration circuit (e.g., volatile or non-volatile storage, or fusible or otherwise one-time programmable circuit). For example a configuration value that corresponds to the desired electrical length of a path segment may be programmed into the configuration circuit and used to control pass gates or other switching elements for switchably coupling the impedance-altering structures to the path segment. The desired setting of the configuration value may be determined, for example, by using the embedded scoping technique described above in reference to FIGS. **27-29** to determine relative arrival times of signal reflections and therefore propagation time differences between signal reflections.

Although the invention has been described with reference to specific exemplary embodiments thereof, it will be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

1. A device, comprising:
  - an equalizing circuit having taps to perform one of adjusting a received signal or adjusting a signal threshold used in sampling the received signal;
  - a storing circuit to store historical data values; and
  - a select circuit to select, based on a latency signal, one of the historical data values from the storing circuit, the selected one to be used by the equalizing circuit to perform the one of adjusting the received signal or adjusting the signal threshold.
2. The device of claim **1**, wherein each of the data values comprises a multi-bit value having at least four possible logic states.
3. The device of claim **1**, wherein the received signal is to be received from a signal path and wherein the equalizing circuit comprises an output driver to drive an equalizing signal onto the signal path.
4. The device of claim **3**, wherein the device comprises circuitry to provide an equalization clock to drive the output driver according to timing that causes the selected one of the historical data values to be driven onto the signal path in manner coincident with an inbound data value.
5. The device of claim **1**, wherein the device comprises a preamplifier to amplify the received signal and wherein the preamplifier comprises the equalizing circuit.
6. The device of claim **1**, wherein the device comprises a sampling circuit and wherein the equalizing circuit is coupled to the sampling circuit to adjust sampling of the received signal.
7. The device of claim **1**, wherein the latency signal is to be configured to select one of the historical data values according to a selected symbol latency value that is greater than  $M+1$  and less than or equal to  $R$ , where  $M$  is at least one, and  $R$  is at least one hundred, wherein the device comprises a circuit to store the selected symbol latency value.
8. The device of claim **7**, wherein the device further comprises circuitry to automatically determine at least one distortion latency and cause the selected symbol latency value to be dependent on the at least one distortion latency.
9. The device of claim **1**, wherein the storing circuit comprises a shift register, the shift register to shift the historical data values in synchronism with each new data symbol conveyed by the received signal.

**10.** The device of claim **9**, wherein the storing circuit further comprises at least one parallel load register to receive a subset of the historical data values, wherein the latency signal is to cause selection of the selected one of the historical data values from either one of the shift register or the at least one parallel load register according to a value of the latency signal.

**11.** A device, comprising:

- means for performing one of adjusting a received signal or adjusting a signal threshold used in sampling the received signal using taps;
- means for storing historical data values; and
- means for selecting, based on a latency signal, one of the historical data values from the means for storing, the selected one to be used by the means for performing to perform the one of adjusting the received signal or adjusting the signal threshold.

**12.** The device of claim **11**, wherein the received signal is to be received from a signal path and wherein the means for performing comprises an output driver to drive an equalizing signal onto the signal path.

**13.** The device of claim **11**, wherein the device comprises a preamplifier to amplify the received signal and wherein the preamplifier comprises the taps, such that the means for performing comprises the taps of the preamplifier.

**14.** The device of claim **11**, wherein the device comprises a sampling circuit and wherein the means for performing is coupled to the sampling circuit to adjust sampling of the received signal.

**15.** A device, comprising:

- an integrated circuit having
  - an equalizing circuit having taps to perform one of adjusting a received signal or adjusting a signal threshold used in sampling the received signal,
  - a storing circuit to store historical data values, and
  - a select circuit to select, based on a latency signal, one of the historical data values from the storing circuit, the selected one to be used by the equalizing circuit to perform the one of adjusting the received signal or adjusting the signal threshold;

wherein the latency signal is to cause the equalizing circuit to select a subset of one or more of the historical data values within the storing circuit to be selected to source at least one of the taps of the equalizing circuit.

**16.** The device of claim **15**, wherein the device comprises wire bonds, and wherein the received signal is to be received from the wire bonds and sampled to recover the historical data values.

**17.** The device of claim **15**, wherein the device comprises a signal trace, and wherein the received signal is to be received from the signal trace and sampled to recover the historical data values.

**18.** The device of claim **15**, wherein each of the data values comprises a multi-bit value having at least four possible logic states.

**19.** The device of claim **15**, wherein the device comprises circuitry to provide an equalization clock to the equalizing circuit to cause the selected one of the historical data values to be applied in performing the one of adjusting the one of the received signal and the signal threshold in manner coincident with an inbound data value.

**20.** The device of claim **15**, wherein the latency signal is to be configured to select one of the historical data values according to a selected symbol latency value that is greater than  $M+1$  and less than or equal to  $R$ , where  $M$  is at least one, and  $R$  is at least one hundred, wherein the device comprises a circuit to store the selected symbol latency

**35**

value, and wherein the device further comprises circuitry to automatically determine at least one distortion latency and cause the selected symbol latency value to be dependent on the at least one distortion latency.

\* \* \* \* \*

5

**36**