

(19) **United States**

(12) **Patent Application Publication**  
Jin et al.

(10) **Pub. No.: US 2013/0078964 A1**

(43) **Pub. Date: Mar. 28, 2013**

(54) **METHOD OF FORWARDING  
COMMUNICATION SERVICE BASED ON  
VEHICLE AND SYSTEM THEREOF, AND  
TERMINAL SUPPORTING THE SAME**

**Publication Classification**

(51) **Int. Cl.**  
*H04W 4/04* (2009.01)  
*H04W 88/02* (2009.01)  
(52) **U.S. Cl.**  
USPC ..... **455/414.1; 455/550.1; 455/566**

(75) Inventors: **Young Kyu Jin**, Seoul (KR); **Young Ho Rhee**, Yongin-si (KR); **Young Shil Jang**, Suwon-si (KR); **Il Ku Chang**, Seongnam-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(57) **ABSTRACT**

(21) Appl. No.: **13/570,947**

(22) Filed: **Aug. 9, 2012**

(30) **Foreign Application Priority Data**

Sep. 26, 2011 (KR) ..... 10-2011-0097003

A method of forwarding a communication service based on a vehicle is provided. The method includes registering a portable terminal located in the vehicle in a vehicle electronic system; and forwarding a received communication service connection request message to another terminal, when a communication service connection request message is transmitted to a registered portable terminal.

100




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



**METHOD OF FORWARDING  
COMMUNICATION SERVICE BASED ON  
VEHICLE AND SYSTEM THEREOF, AND  
TERMINAL SUPPORTING THE SAME**

**PRIORITY**

[0001] This application claims priority under 35 U.S.C. §119(a) to Korean Patent Application No. 10-2011-0097003, which was filed in the Korean Intellectual Property Office on Sep. 26, 2011, the entire disclosure of which is incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

**[0002] 1. Field of the Invention**

[0003] The present invention relates generally to communication service forwarding, and more particularly, to a method of forwarding a communication service based on a vehicle for selectively or automatically forwarding a communication service to another terminal when connection of the communication service occurs in at least one terminal in a predetermined group defined based on the vehicle.

**[0004] 2. Description of the Related Art**

[0005] A portable terminal supports a call function, and has been used in very wide fields due to its convenience of use and portability. Such a portable terminal provides various input schemes to provide user functions. For example, a conventional portable terminal provides a touchpanel and a display unit such that a user may process an operation performed by selecting an image output on the display unit. Further, the portable terminal generates a touch event according to a corresponding user operation and controls an application program corresponding to a user function based on the generated touch event.

[0006] A portable terminal user may drive a vehicle. The user of a portable terminal should focus on driving. Using a conventional portable terminal while driving a vehicle may result in motor vehicle crash.

[0007] Accordingly, the conventional portable terminal user has used a speaker phone or an earphone to minimize driving distraction. However, using a speaker phone or an earphone while driving may cause a problem of breaking the driver's focus on driving.

**SUMMARY OF THE INVENTION**

[0008] The present invention has been made in view of the above problems, and provides a method of forwarding a communication service based on a vehicle that allows a vehicle driver to pay attention only to driving by forwarding a communication service connection of a terminal located in the vehicle to a certain terminal, a system thereof, and a terminal supporting the same.

[0009] The present invention further provides a method of forwarding a communication service based on a vehicle that allows a user to use the communication service in a stable environment although a certain person in the vehicle uses the communication service, a system thereof, and a terminal supporting the same.

[0010] In accordance with an aspect of the present invention, a method of forwarding a communication service based on a vehicle is provided. The method includes registering a portable terminal located in the vehicle in a vehicle electronic system; and forwarding a received communication service connection request message to another terminal, when a com-

munication service connection request message is transmitted to a registered portable terminal.

[0011] In accordance with another aspect of the present invention, a system for forwarding a communication service based on a vehicle is provided. The system includes the vehicle; a vehicle electronic system, located in the vehicle, for communicating with a portable terminal; the portable terminal, located in the vehicle for communicating with the vehicle electronic system to be registered in the vehicle electronic system; a transmission terminal requesting communication service connection to the portable terminal; and a mobile communication system establishing a communication channel between a forwarding terminal designated by the portable terminal and the transmission terminal.

[0012] In accordance with another aspect of the present invention, a terminal for supporting forwarding of a communication service based on a vehicle is provided. The terminal includes a first communication unit supporting a communication service function; a second communication unit supporting signal transmission/reception necessary for registration in a vehicle electronic system in the vehicle; and a controller controlling signal transmission/reception for registration in the vehicle electronic system, and controlling the communication service connection request message to be forwarded to a forward terminal selected according to an input signal or a preset automatic forwarding terminal when the first communication unit receives the communication service connection request message.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0013] The aspects, objects, features and advantages of the present invention will be more apparent from the following detailed description in conjunction with the accompanying drawings, in which:

[0014] FIG. 1 is a diagram illustrating the configuration of a system for forwarding a communication service based on a vehicle according to an embodiment of the present invention;

[0015] FIG. 2 is a block diagram illustrating a vehicle electronic system shown in FIG. 1 in detail;

[0016] FIG. 3 is block diagram illustrating a portable terminal shown in FIG. 1 in detail;

[0017] FIG. 4 is a block diagram illustrating a controller shown in FIG. 3 in detail;

[0018] FIG. 5 is a diagram illustrating a screen interface associated with a communication service forwarding function according to an embodiment of the present invention;

[0019] FIG. 6 is a diagram illustrating a screen interface associated with a communication service forwarding function according to an embodiment of the present invention;

[0020] FIG. 7 is a flowchart illustrating a method of operation of a portable terminal for supporting a communication service forwarding function according to an embodiment of the present invention;

[0021] FIG. 8 is a flowchart illustrating a method of forwarding a communication service based on a vehicle according to an embodiment of the present invention; and

[0022] FIG. 9 is a flowchart illustrating a method of forwarding a communication service based on a vehicle according to another embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS  
OF THE PRESENT INVENTION

[0023] Embodiments of the present invention are described with reference to the accompanying drawings in detail. The same reference numbers are used throughout the drawings to refer to the same or like parts. Detailed descriptions of well-known functions and structures incorporated herein is omitted to avoid obscuring the subject matter of the present invention.

[0024] FIG. 1 is a diagram illustrating a configuration of a system 10 for forwarding a communication service based on a vehicle according to an embodiment of the present invention.

[0025] Referring to FIG. 1, the system 10 for forwarding a communication service based on a vehicle according to the present invention includes a vehicle electronic system 200 provided on a vehicle 201, at least one portable terminals 101, 102, and 103 mounted in the vehicle 201, a transmission terminal 109 requesting communication service connection to the portable terminal 101, 102, and 103, and a mobile communication system 300. Hereinafter, it is assumed that a plurality of portable terminal provided in the vehicle 201. However, only one terminal is located in the vehicle 201 according to situations.

[0026] In the system 10 for forwarding a communication service, when certain portable terminals 101, 102, 103 enter the vehicle 201, it establishes a communication channel with the portable terminals 101, 102, 103 to register the portable terminals 101, 102, 103 into the vehicle electronic system 200. Next, when a message requesting communication service connection to a certain portable terminal, for example, a first portable terminal 101, the first portable terminal 101 forwards a communication service connection request message to another terminal, for example, a second portable terminal 102 or a third terminal 103. In this case, the first portable terminal 101 forwards a communication service connection request message to another portable terminal 102 or 103 which is currently registered in a vehicle electronic system 200. The communication service connection request message includes at least one of a message in which the transmission terminal 109 requests a voice call to the first portable terminal 101, a message in which the transmission terminal 109 requests a video phone call to the first portable terminal 101, a message in which the transmission terminal 109 transmits an e-mail or Social Network Service (SNS) message to the first portable terminal 101.

[0027] The first portable terminal 101 ensures that the communication service connection request service is forwarded to a certain terminal outside the vehicle 201. Through this, the system 10 for forwarding a communication service allows a user to drive in a stable environment such that a user with the first portable terminal 101 may pay attention to driving. Further, the system 10 for forwarding a communication service of the present invention transfers the communication service connection request message transferred to the first portable terminal 101 to another portable terminal 102 or 103 such that a person with another portable terminal 102 or 103 uses a corresponding communication service not to lose a contact. To accomplish this, a communication means is provided in a vehicle electronic system 200, which recognizes at least one portable terminal 101, 102, 103 which includes portable terminals in a close range, for example, portable terminals in a vehicle 201.

[0028] Accordingly, when at least one portable terminal 101, 102, 103 enters the vehicle 201, the vehicle electronic system 200 recognizes and registers corresponding portable terminals 101, 102, 103, and support communication service forwarding between the registered portable terminals 101, 102, 103. Further, the vehicle electronic system 200 receives forwarding setting information from at least one portable terminal entering the vehicle 201, and forwards a communication service connection request message received based on the received forwarding setting information to another portable terminal. A detailed configuration of a vehicle electronic system 200 for supporting the foregoing function will be given with reference to FIG. 2.

[0029] The mobile communication system 300 forms a mobile communication service channel between the portable terminals 101, 102, 103 and the transmission terminal 109. Moreover, the mobile communication system 300 forms a communication service channel with the vehicle electronic system 200, and support signal transmission/reception necessary to support a communication service forwarding function of the present invention. The mobile communication system 300 includes a 2G network device, a 3G network device, and a 4G network device for supporting a communication service between the portable terminal and the transmission terminal 109. Moreover, the mobile communication system 300 communicates with the vehicle electronic system 200 using the foregoing network devices, and support formation of a communication channel between the vehicle electronic system 200, the portable terminals 101, 102, 103, and the transmission terminal 109, if necessary.

[0030] The portable terminals 101, 102, 103 are located inside or outside the vehicle according to an operation of the user with the portable terminals 101, 102, 103. In particular, the portable terminals 101, 102, 103 are classified into a first portable 101 possessed by a driver, and a second portable terminal 102 and a third portable terminal 103 possessed by other persons in the vehicle with the driver. Here, the first portable terminal 101 is defined as a terminal transmitting a communication service connection request message, and at least one of a second portable terminal 102 and a third portable terminal 103 is defined as a terminal receiving the communication service connection request message that the first portable terminal 101 forwards. When the first portable terminal 101 is mounted in the vehicle 210 or the transmission terminal 109 transmits a communication service connection request message, the first portable terminal 101 outputs forwarding group information. Accordingly, the first portable terminal 101 user selects a certain terminal which will forward the communication service connection request message. The first portable terminal 101 may automatically forward a communication service to one of the second portable terminal 102 or the third portable terminal 103 belonging to the forwarding group information based on forwarding setting information without receiving a separate selection signal according to user setting. Additionally, the first portable terminal 101 controls a certain portable terminal located outside the vehicle 201 to perform the communication service forwarding. The foregoing embodiment illustrates that three terminals 101, 102, 103 are provided in the vehicle 201. However, the present invention is not limited thereto. That is, there is only one of the portable terminals 101, 102, 103 in the vehicle 201, and more portable terminal may also exist therein. When only one terminal exists, the first portable

terminal **101** performs the foregoing preset communication service forwarding according to forwarding setting information.

[0031] The transmission terminal **109** is a terminal transmitting a communication service connection request message to one of the portable terminals **101**, **102**, and **103**. The transmission terminal **109** transmits a call connection request message, an SMS or multi-media message, or at least one of an e-mail or SNS message to one of the portable terminals **101**, **102**, and **103**. A communication service connection request message generated by the transmission terminal **109** is transferred to a certain portable terminal **101**, and is forwarded to the second portable terminal **102** or the third portable terminal **103** according to setting of the first portable terminal **101**. The transmission terminal **109** returns a message indicating that a communication service forwarding function is being performed according to presence of support of a mobile communication **10**, support of the vehicle electronic system **200**, and support of portable terminals **101**, **102**, **103**. Accordingly, the transmission terminal **109** informs a user that a communication service connection request message transmitted by the transmission terminal **109** is being forwarded, and receive and output forwarded terminal information according to return information.

[0032] As illustrated above, when a user carrying a portable terminal operates in a vehicle mode according to board on the vehicle **201**, the system **10** for forwarding a communication service forwards a received communication service connection request message to another portable terminal according to the control of the user or automatically. Accordingly, when the user who possesses the portable terminal is driving a vehicle **201**, the system **10** for forwarding a communication service provides an environment in which the driver can pay attention to driving, thereby preventing a motor vehicle crash.

[0033] The system **10** for forwarding a communication service informs the transmission terminal **109** that a communication service is forwarded in a communication service forwarding procedure such that the transmission terminal **109** operates a communication service in a state it recognizes the communication service forward situation. An alarm message indicating during or termination of the communication service forwarding becomes at least one of a first portable terminal **101** and a vehicle electronic system **200** instructing communication service forwarding. In this procedure, at least one of the first portable terminal **101** and the vehicle electronic system **200** simultaneously transmits information indicating that the first portable terminal **101** operates in a vehicle mode and forwarding group information to the transmission terminal **109**, and simultaneously transmits information indicating a terminal, for example, a second portable terminal **102** as a forwarding terminal. The transmission terminal **109** then operates a communication service in a state in which the first portable terminal **101** recognizes that a driver is driving the vehicle **201** and performs a communication service forwarding with a second portable terminal **102**.

[0034] Further, the first portable terminal **101** transfers information indicating that a vehicle mode is operated and forwarding setting information having information designated as a forwarding terminal by the first portable terminal **101**, for example, information designating the second portable terminal **102** as an automatic forwarding terminal to the transmission terminal **109**. At the same time, when receiving a communication service connection request from the transmission terminal **109**, the first portable terminal **101** controls

such that a corresponding connection request message is forwarded to the second portable terminal **102**. The first portable terminal **101** outputs the reception of a communication service connection request message and a message indicating automatic forwarding of the second portable terminal **102** to a display unit. The second portable terminal **120** is a terminal located in the vehicle **201** or in another place outside vehicle **201**.

[0035] FIG. 2 is a block diagram illustrating a vehicle electronic system **200** shown in FIG. 1 in detail.

[0036] Referring to FIG. 2, a vehicle electronic system **200** includes a vehicle communication unit **210**, a vehicle input unit **220**, a vehicle memory **250**, and a vehicle controller **260**. The vehicle electronic system **200** recognizes at least one portable terminal **101**, **102**, **103** located in a vehicle **201** based on the vehicle communication unit **210** and generates a communication service-forwarding group according to recognition of the portable terminals **101**, **102**, and **103**. Then, at least one of the portable terminals **101**, **102**, and **103** receives forwarding group information from the vehicle electronic system **200**, and forward a receive communication service connection request message based on the received forwarding group information to another portable terminal.

[0037] As illustrated above, the vehicle communication unit **210** recognizes portable terminals **101**, **102**, **103**, and supports information transmission/reception necessary for registration of the portable terminals **101**, **102**, **103** for generating a communication service-forwarding group. To accomplish this, when power supplied to the vehicle communication unit **210**, it performs message broadcasting for searching whether there are portable terminals **101**, **102**, **103** around it with a constant period. The vehicle communication unit **210** includes at least one of communication module, for example, a ZigBee module, a Z-Wave module, an Ethernet module, a WiFi module, or a Bluetooth module capable of communicating with portable terminals **101**, **102**, **103**, and form a communication channel with portable terminals **101**, **102**, **103** with the communication module. The vehicle communication unit **210** performs a function of a base station or an Access Point (AP) capable of recognizing the portable terminals **101**, **102**, **103**. When the portable terminals **101**, **102**, **103** are recognized, the vehicle communication unit **210** collects identification information of corresponding portable terminals **101**, **102**, **103** automatically or through an authentication procedure. The collected identification information is transferred to the vehicle controller **260**. Here, the identification information includes various information such as phone numbers, IDs, and photographs of portable terminals **101**, **102**, and **103** as information for identifying the respective portable terminals **101**, **102**, and **103**. The foregoing IDs of the portable terminals **101**, **102**, and **103** is registered as each item of forwarding group information.

[0038] The vehicle input unit **220** is configured for generating an input necessary for controlling the vehicle electronic system **200**. The vehicle input unit **220** generates an input signal for supplying power to the vehicle electronic system **200** and an input signal for activating the vehicle communication unit **210** according to the control of a passenger. Further, the vehicle input unit **220** generates an input signal for manually inputting forwarding setting information and an input signal for manually inputting identification information based on the control of the passenger. The generated input signals are transferred to the vehicle controller **260** and con-

verted to a command language for communication service forwarding of the present invention.

**[0039]** The vehicle memory **250** stores an Operating System (OS) necessary to operate the vehicle electronic system **200** and various application programs necessary for operating the vehicle. In particular, the vehicle memory **250** stores forwarding group information **250** configured by identification information of the portable terminals **101**, **102**, and **103** registered in the vehicle electronic system **200**. The forwarding group information **251** by identification information of terminals performing registration of portable terminals **101**, **102**, and **103** communicating with a vehicle communication unit **210** of the vehicle electronic system **200**. The forwarding group information **251** is transmitted to the portable terminals **101**, **102**, **103**.

**[0040]** The vehicle controller **260** controls activation of the vehicle electronic system **200** based on the control of the passenger, and controls various signal flows necessary to support a communication service forwarding function of the present invention. For example, the vehicle controller **260** controls a vehicle communication unit **210** for recognizing portable terminals **101**, **102**, and **103** located in the vehicle **201**, collecting identification information of recognized terminals, generating forwarding group information **251** based on the collected identification information, distributing the generated forwarding group information **251**, and forwarding a communication service when a certain portable terminal, for example, the first portable terminal **101** receives the communication service connection request message.

**[0041]** More specifically, when a passenger, for example, a driver, generates an input signal for recognizing peripheral portable terminals **101**, **102**, **103** or it is set such that peripheral portable terminals **101**, **102**, and **103** are recognized, the vehicle controller **260** controls the vehicle communication unit **210** to perform message broadcasting for recognizing peripheral portable terminals **101**, **102**, and **103**. The vehicle controller **260** collects identification information of the portable terminals **101**, **102**, **103** from the portable terminals **101**, **102**, and **103** responding to corresponding message broadcasting. The identification information includes phone number information, phone-book information, and photograph information of corresponding portable terminal. The identification information may only include a phone number, and a passenger may separately input name information and photograph information as the identification information. Further, the vehicle controller **260** requests identification with various information such as phone numbers or images to the respective portable terminals **101**, and receive corresponding identification information from the portable terminals **101**, **102**, and **103**.

**[0042]** When the collection of the identification information is terminated, the vehicle controller **260** generates forwarding group information **251** based on the identification information of the portable terminals **101**, **102**, and **103**. In this procedure, the vehicle controller **260** registers a certain portable terminal, for example, a first portable terminal **101** as a driver terminal, and the second portable terminal **102** and the third portable terminal **103** as a follower passenger terminal. To accomplish this, the vehicle controller **260** registers a driver terminal based on intensity of a transmission/reception signal in a communication procedure. The passenger controls the vehicle input unit **220** to register a terminal corresponding to certain identification information as the first portable terminal **101** as the driver terminal.

**[0043]** When generation of the forwarding group information is terminated, the vehicle controller **260** transmits corresponding forwarding group information **251** to the first portable terminal **101**. The vehicle controller **260** transmits the forwarding group information **251** to all the first to third terminals **101**, **102**, and **103**. The vehicle controller **260** provides the forwarding group information **251** to only a portable terminal requesting it.

**[0044]** If the communication service forwarding function is activated, that is, if a communication service connection request message is transmitted to a certain portable terminal, a corresponding portable terminal requests the forwarding group information **251** to the vehicle controller **260**. Then, the vehicle controller **260** provides the forwarding group information **251** to a corresponding portable terminal. As illustrated previously, when the vehicle controller **260** previously provides the forwarding group information **251** to portable terminals **101**, **102**, and **103**, a separate procedure for the forwarding group information **251** is omitted. When the portable terminal receiving the communication service connection request message selects a forwarding function, the vehicle controller **260** controls a portable terminal selected as a forwarding function to perform a communication service function of a corresponding portable terminal.

**[0045]** For example, if the transmission terminal **109** transmits a communication service connection request message to a first portable terminal not receiving the forwarding group information **251**, the vehicle controller **260** provides the forwarding group information **251** to the first portable terminal **101**. Further, if the first portable terminal **101** designates the second portable terminal **101** as a forwarding selection terminal, the vehicle controller **260** forwards a communication service connection request message to the second portable terminal **102**. When receiving the communication service connection request message, the second portable terminal **102** outputs it and performs a communication service function with a transmission terminal **109** according to the preference of the user. In this procedure, the vehicle controller **260** ensures that a communication service is forwarded based on a communication service path including the transmission terminal **109**, the mobile communication system **300**, the first portable terminal **101**, the vehicle communication unit **210**, and the second portable terminal **102**. When forwarding selection terminal information of the first portable terminal **101** is provided to the mobile communication system **300**, the vehicle controller **260** ensures that a communication service is performed based on a communication service path including the transmission terminal **109**, the mobile communication system **300**, and the second portable terminal **102**. Various communication service paths will be described in detail with reference to following drawings.

**[0046]** FIG. 3 is block diagram illustrating one of portable terminals **101**, **102**, and **103** in detail according to an embodiment of the present invention. Portable terminals **101**, **102**, and **103** illustrated in FIG. 1 were described above. Portable terminal **100** is similar to portable terminals **101**, **102**, and **103** and it will be described with reference to a configuration of one portable terminal. Hereinafter, in order to describe a forwarding function, it is assumed that a terminal receiving a communication service connection request message is a first portable terminal **101**, and a forwarding selection terminal is a second portable terminal **102**. This distinction will illustrate a communication service forwarding function. However, the present invention is not limited thereto. That is, all terminals

located in the vehicle **201** are terminals performing a communication service forwarding function according to setting of a passenger or a driver. A certain terminal not located in the vehicle **201** act as a forwarding selection terminal of the first portable terminal **101**.

[0047] Referring to FIG. 3, a portable terminal **100** of the present invention includes a first communication unit **110**, a second communication unit **170**, an input unit **120**, an audio processor **130**, a display unit **140**, a memory **150**, and a controller **160**. Although this embodiment illustrates that the portable terminal **100** includes two communication units, the present invention is not limited thereto. That is, the first communication unit **110** and the second communication unit **170** is configured by one communication module, for example, a 3G or 4G support communication module, and accordingly the portable terminal **100** communicates with a vehicle electronic system **200** and the mobile communication system **300** based on the one communication module. Accordingly, it will be understood that the first communication unit **110** and the second communication unit **170** identify a subject for performing communication. As a result, a portable terminal **100** of the present invention is operated by one communication module or a plurality of communication modules. Further, the portable terminal **100** of the present invention includes an input unit **120** and a display unit **140** for supporting a touch function as input means for generating input signals.

[0048] The first communication unit **110** is configured by a communication module capable of establishing a communication channel with the mobile communication system **300**. The first communication unit **110** establishes a communication channel for voice call, a communication channel for video call, and a communication channel for transmitting data such as images or messages under the control of the controller **160**. That is, the first communication unit **110** establishes a voice call channel, a data communication channel, and a video call channel with the mobile communication system **300**. In particular, the first communication unit **110** of the first portable terminal **101** of the present invention receives and transfers a communication service connection request message to the controller **160**, and transfers data associated with a communication service received from the transmission terminal **109** to the second communication unit **170** under a control of the controller **160**. Further, the first communication unit **110** of the first portable terminal **101** transfers data associated with a communication service received by the second communication unit **170** to the transmission terminal **109** through the mobile communication system **300**.

[0049] The first communication unit **110** of the second portable terminal **102** directly establishes a communication channel with the transmission terminal through the mobile communication system **300** after communication service forwarding is terminated from the first portable terminal **101** according to a system design scheme. To accomplish this, if the communication service forwarding of the first portable terminal **101** is performed, the first communication unit **110** of the second portable terminal **102** is activated under the control of the fellow passenger or automatically.

[0050] The second communication unit **170** is configured by a communication module capable of establishing a communication channel with a vehicle communication unit **210** included in the vehicle electronic system **200**. Accordingly, when the vehicle communication unit **210** is configured by a near-distance communication module, the second communication unit **170** is configured by a near-distance communica-

tion module compatible with the vehicle communication unit **210**. The portable terminal **100** establishes a communication channel with the vehicle electronic system **200** based on the second communication unit **170** to provide identification information for generating forwarding group information to the vehicle electronic system **200**.

[0051] In particular, the second communication unit **170** of the first portable terminal **101** transfers a communication service connection request message received from the transmission terminal **109** to the second communication unit **170** of the second portable terminal **102** through the vehicle communication unit **210** under the control of the user. The second communication unit **170** of the second portable terminal **102** receives the communication service connection request message and transfers the received communication service connection request message to the controller **160** to inform it that it is forwarded from the first portable terminal **101**. When the second portable terminal **102** user accepts forwarding, the second portable terminal **102** transfers it to the first terminal **101**, and performs a communication service with the transmission terminal **109** based on a communication service path including the transmission terminal **109**, the first communication unit **110**, the second communication unit **170**, the vehicle communication unit **210**, and of the first portable terminal **101**. The second portable terminal **102** operates the first communication unit **110** to exclude the first portable terminal **101** and the vehicle communication unit **210**, and to directly communicate with the transmission terminal **109**.

[0052] The input unit **120** generates various input signals necessary for the operation of the portable terminal **100** under the control of the user. The input unit **120** includes a plurality of input keys and function keys for receiving input of numerals or character information, and setting various functions. The function keys include arrow keys, side keys, and shortcut keys set to perform certain functions. Further, the input unit **120** generates and transfers key signals associated with user setting and function control of the portable terminal **100** to the controller **160**. The input unit **120** is implemented by using a Qwerty keypad, a 3\*4 keypad, or a 4\*3 keypad, or the like including a plurality of keys. Further, the input unit **120** is implemented by a Qwerty key map, a 3\*4 keypad, a 4\*3 keypad, a menu map, a control key map, or the like output on the display unit **140**. Further, when the display unit **140** of the portable terminal **100** is supported in the form of a full touchscreen, the input unit **120** includes only side keys provided at a side surface of a case of the portable terminal **100**. The input unit **120** generates and transfers an input signal for setting an automatic vehicle mode operation or a vehicle mode release operation to the controller **160**. In particular, when receiving the communication service connection request message, the input unit **120** of the first portable terminal **101** generates an input signal for request such that a corresponding message is forwarded to the second portable terminal **102**. When receiving the communication service connection request message forwarding, the input unit **120** of the second portable terminal **102** generates an input signal accepting forwarding or generates an input signal such that a message forwarded to another portable terminal, for example, a third portable terminal **103** is again forwarded.

[0053] The audio processor **130** outputs various audio data necessary for operating the portable terminal **100**, and supports a function collecting audio data to support a call function of the portable terminal **100**. To accomplish this, the audio processor **130** includes a speaker SPK for outputting

audio data and a microphone MIC for collecting the audio data. In particular, the audio processor **130** of the present invention outputs various effect sounds or guide sounds corresponding to audio data indicating vehicle mode performing by a portable terminal **100** registered in the vehicle communication unit **210**, audio data informing the user of the reception of a communication service connection request message from the transmission terminal **109** while in vehicle mode, audio data informing the user of the occurrence of message forwarding, and audio data informing acceptance of a forwarding function. The audio processor **130** may not output a corresponding sound effect or guide sound according to user setting. The output of the audio data is substituted by a vibration function.

[0054] When the portable terminal **100** is configured by a touchscreen, the display unit **140** includes a display panel and a touchpanel. The display unit may include a structure in which a touchpanel is located in a front surface of a display panel.

[0055] The display panel displays information input by the user and information provided to the user as well as various menus. That is, the display panel provides various screens, for example, an idle screen, a menu screen, a message creation screen, and a call screen according to utilization of the portable terminal **100**. The display panel is a Liquid Crystal Display (LCD) or an Organic Light Emitted Diode (OLED) and the like. Furthermore, the display panel is located in an upper part or a lower part of the touchpanel. Particularly, the display panel of the present invention outputs various screens necessary for applying a communication service forwarding function. The various screens will be described in detail with reference to following drawings.

[0056] The touchpanel is located in one of an upper part or a lower part of the display panel, generate a touch event according to contact of a touch object, for example, user finger, and transfer the generated touch event to the controller **160**. In this case, a sensor configuring the touchpanel is arranged in a matrix pattern. Corresponding location information with respect to a touch event occurring on the touchpanel and information about a type of touch event are transferred to the controller **160**. In particular, the touchpanel of the present invention is set according to a screen corresponding to a communication service forwarding function. For example, when an icon or an image corresponding to at least one terminal included in the forwarding group information **251** are output on the display panel, the touchpanel is set to select corresponding image or icon. The set touchpanel generates a touch event according to a user touch and transfers the generated touch event to the controller **160**.

[0057] The memory **150** stores a key map or a menu map for operating the display unit **140** as well as application program necessary for a function operation according to an embodiment of the present invention. The key map or the menu map is various forms. That is, the key map becomes a keyboard map, a 3\*4 key map, a Qwerty key map, or a control key map for controlling an operation of a currently activated application program. Further, the menu map is used as a menu map for controlling a currently activated application program. The memory **150** may include a program area and a data area.

[0058] The program area stores an OS for booting the portable terminal **100** and operating the foregoing structural elements, and application programs for playing various files, for example, an application program for supporting a call

function of the portable terminal **100**, a web browser accessing an Internet server, an MP3 application program for playing sounds, an image output application program for displaying photographs, and a moving image playback application program. In particular, the program area of the present invention stores a forwarding support program **151**.

[0059] The forwarding support program **151** is a program for supporting a communication service forwarding function of the portable terminal **100**. When the portable terminal **100** enters a vehicle mode or when receiving a communication service connection request message after it enters the vehicle mode, the forwarding support program **151** is loaded into the controller **160** and supports a communication service forward function of the present invention. To accomplish this, the forwarding support program **151** includes a routine for operating the second communication unit **170**, a routing providing identification information according to a request of the vehicle communication unit **210**, a routine for receiving and storing the forwarding group information **251**, a routine for requesting and receiving the forwarding group information **251** to the vehicle electronic system **200** when the communication service connection request message is received from the transmission terminal **109**, and a routine for outputting the received forwarding group information **251** to the display unit **140**. The forwarding support program **151** includes a routine for forwarding a communication service connection request message to a forwarding terminal selected from the forwarding group information **251**, for example, a second portable terminal, and a routine for performing communication service forwarding between the transmission terminal **109** and the second portable terminal **102** when the second portable terminal **102** accepts the forwarding.

[0060] The data area is an area for storing data created according to use of the portable terminal **100**, and stores phone-book data, at least one icon according to a widget function, and various contents. Further, the data area stores user input provided from the touchpanel. In particular, the data area stores forwarding setting information **153**.

[0061] The forwarding setting information **153** becomes forwarding selection terminal information previously defined by the user. The portable terminal forwarding setting information **153** provides forward setting information **153** to the vehicle electronic system **200** in a vehicle mode entering procedure. The portable terminal forwarding setting information **153** designates the second portable terminal **102** as an automatic forwarding selection terminal, and designation information is provided to the vehicle electronic system **200** as the forward setting information. If the forwarding group information **251** is received from the vehicle electronic system **200**, the portable terminal forwarding setting information creates forwarding setting information **153** designating a certain terminal included in the received forwarding group information **251** as the automatic forwarding selection terminal, and feed it back to the vehicle electronic system **200**.

[0062] The vehicle electronic system **200** then stores the forwarding setting information **153** in the vehicle memory **250**. When the first portable terminal **101** performs a communication service forwarding function, the vehicle electronic system **200** forwards the communication service connection request message to the second portable in the forward setting information **153**. In this procedure, the first portable terminal **101** does not output separate forwarding group information **251**, and receives an input signal with respect to whether to perform a communication service forwarding function.

[0063] Further, when receiving a corresponding input signal, the first portable terminal 101 provides a communication service connection request message to the vehicle electronic system 200, and the vehicle electronic system 200 automatically transfers the communication service connection request message to the second portable 102. The first portable terminal 101 or the vehicle electronic system 200 receiving the forwarding setting information 153 from the first portable terminal 101 provides the forwarding setting information 153 to the mobile communication system 300. The mobile communication system 300 then transfers a communication service connection request message of a transmission terminal 109 to the second portable terminal according to a vehicle mode entry of the first portable terminal 101 or signal feedback according to generation of an input signal for activating a forwarding function.

[0064] The controller 160 controls power supply to respective structural elements of the portable terminal 100 to perform an initializing procedure. Further, the controller 160 controls various signal flows necessary for applying a communication service forwarding function of the present invention. To accomplish this, the controller 160 includes a configuration as illustrated in FIG. 4.

[0065] FIG. 4 is a diagram illustrating a configuration of a controller 160 of the portable terminal forwarding setting information 153 according to the present invention.

[0066] Referring to FIG. 4, the controller 160 includes a forwarding group information collector 161, a forwarding group information output unit 163, and a forwarding supporting unit 165.

[0067] When a portable terminal enters in the vehicle 201, the forwarding supporting unit 165 receives a message that a vehicle communication unit 210 included in a vehicle electronic system 200 broadcasts. The controller 160 then establishes a communication channel with the vehicle electronic system 200, and automatically registers in the vehicle electronic system 200 according to the user control or an access history. In the registration procedure, the controller 160 provides identification information of the forwarding supporting unit 165 to the vehicle electronic system 200. The vehicle electronic system 200 performs a function of an AP with respect to the forwarding supporting unit 165. Receiving identification information from the forwarding supporting unit 165, the vehicle electronic system 200 generates forwarding group information 251 based on the received identification information. If the registration in the vehicle electronic system 200 is terminated, the controller 160 determines that it has entered vehicle mode, and outputs an indicator informing of a corresponding operation, for example, a vehicle mode entry to an indicator region.

[0068] The forwarding group information collector 161 is an element collecting forwarding group information 251 generated by the vehicle electronic system 200. In the case in which the vehicle electronic system 200 generates the forwarding group information 251 according to a design scheme of a system designer, when the forwarding group information 251 is transferred regardless of the generation of a separate event, the forwarding group information collector 161 of the first portable terminal 101 receives the forwarding group information 251 and control the memory 150 to store it. Further, the forwarding group information collector 161 requests the forwarding group information 251 to the vehicle electronic system 200 and receives it from vehicle electronic system 200 when a communication service connection

request message is received from the transmission terminal 109. The forwarding group information collector 161 of the second portable terminal 102 provides identification information to the vehicle electronic system 200. When receiving the forwarding group information 251 or communication service forwarding from the first portable terminal 101 in response thereto, the forwarding group information collector 161 receives the forwarding group information 251 from the first portable terminal 101 or the vehicle electronic system 200. Based on this, the second portable terminal 102 again forwards the received communication service forwarding to another terminal, for example, the third portable terminal 103 or rejects the communication service forwarding.

[0069] If the forwarding supporting unit 165 receives the forwarding group information, the forwarding group information output unit 163 outputs it to the display unit 140. The forwarding group information output unit 163 outputs the forwarding group information 251 with output to a screen according to reception of the communication service connection request message. A screen interface associated with output to the forwarding group information will be described in detail with reference to drawings to be illustrated below.

[0070] The forwarding supporting unit 165 supports a communication service forwarding function of the forwarding supporting unit 165. When the user selects a link item corresponding to a certain portable terminal in an output state of the forwarding group information 251, the forwarding supporting unit 165 collects information linked with the corresponding item, for example, information for performing communication connection with the second portable terminal 102, and transfers a communication service connection request message to the second portable terminal 102 based on the collected information. The forwarding supporting unit 165 ensures that that a communication service connection request message is forwarded using the second communication unit 170 establishing a communication channel with the vehicle communication unit 210. When receiving the communication service connection request message provided through the vehicle communication unit 210, the forwarding supporting unit 165 of the second portable terminal 102 ensures that it is output to the display unit 140. Further, when the user accepts forwarding, the forwarding supporting unit 165 of the second portable terminal 102 transfers the forwarding acceptance message to the first portable terminal 101 through the vehicle communication unit 210. The forwarding supporting unit 165 of the first portable terminal 101 checks a forwarding acceptance message received through the vehicle communication unit 210, perform communication service connection with the transmission terminal 109, and ensures that data transmitted/received to and from the transmission terminal 109 are forwarded to the second portable terminal 102 through the vehicle communication unit 210. Further, the forwarding supporting unit 165 provides forwarding information to the second portable terminal 102, for example, a phone number of the second portable terminal 102 to the mobile communication system 300 such that the transmission terminal 109 and the second portable terminal 102 perform a mutual communication service.

[0071] FIG. 5 is a diagram illustrating a screen interface of a forwarding supporting unit 165 according to an embodiment of the present invention. Hereinafter, a screen interface will be described with reference to a call service of communication services.

[0072] The first portable terminal **101** receives a call service connection request message from the transmission terminal **109**. Accordingly, the first portable terminal **101** outputs a screen according to the reception of the communication service connection request message as illustrated in a screen **501**. The first portable terminal **101** ensures that the transmission terminal **109** determines photograph information corresponding to the transmission terminal **109** stored in a phone-book corresponding to an item stored in the phone-book and outputs the determined photograph information to the display unit **140**. When there is no photograph information, the first portable terminal **101** ensures that the phone number information or name information corresponding to the transmission terminal **109** are output to the display unit **140**.

[0073] Further, the first portable terminal **101** receives the forwarding group information **251** and output the received forwarding group information as illustrated in a screen **501** of FIG. **5**. The forwarding group information **251** contains information “wife” corresponding to the second portable terminal **102** and information “Tom” corresponding to the third portable terminal **103**. Accordingly, the display unit **140** outputs a first link item **51** and a second link item **52** corresponding to the second portable terminal **102** and the third portable terminal **103**. In particular, the first portable terminal **101** configures the first link item **51** and the second link item **52** based on photograph and image information included in the forwarding group information **251**. When there is no photograph or image information, the first portable terminal **101** substitutes and outputs phone number or name information of respective portable terminals for the first link item **51** and the second link item **52**.

[0074] The first portable terminal **101** user generates an input signal designating one of the first link item **51** and the second link item **52** as a forwarding selection terminal. When the display unit **140** supports a touchscreen function, the user generates an input signal touching a first link item **51** corresponding to the second portable terminal **102** output on the display unit **140**. The first portable terminal **101** then outputs a screen indicating that it performs call service forwarding as illustrated in screen **503**. During this procedure, the first portable terminal **101** transfers a call service connection request message to the second portable terminal **102**. Moreover, the first portable terminal **101** may process data transmission/reception associated with call service forwarding by background processing. After the first portable terminal **101** does not return to a previous screen but maintains screen **503** indicating that call service forwarding is being performed, when a corresponding call service is terminated, it controls returning to a previous screen.

[0075] When the second portable terminal **102** returns a forwarding acceptance message with respect to a call service connection request message, the first portable terminal **101** outputs a screen corresponding to acceptance of the call service forwarding. Moreover, the first portable terminal **101** ensures that it is restored to a screen output on the display unit **140**.

[0076] Restoration to the previous screen is changed according to a system design scheme. For example, when a call service forwarding function and data transmission/reception associated with a call service are performed through the vehicle communication unit **210**, the first portable terminal **101** may maintain output of screen **503** to a call service termination. When the second portable terminal **102** excludes the first portable terminal **101** and the vehicle electronic sys-

tem **200** but directly operates a call service with the transmission terminal **109** after acceptance of call service forwarding, the first portable terminal **101** restores a previous screen after completing call forwarding.

[0077] Additionally, when the first portable terminal **101** is located in the vehicle **201** and enters a vehicle mode by performing registration in the vehicle electronic system **200**, it outputs a vehicle mode indicator **141** indicating that it is in a vehicle mode on a side of the screen or an indicator region. Accordingly, the user easily recognizes that the first portable terminal **101** is currently operated in a vehicle mode, and accordingly a communication service is forwarded.

[0078] FIG. **6** is a diagram illustrating an example of a screen interface of a portable terminal **100** according to another embodiment of the present invention.

[0079] The first portable terminal **101** receives a call service connection request message from the transmission terminal **109**. The first portable terminal **101** then outputs a screen according to the reception of a call service connection request message as illustrated in screen **601** in the same manner as in the screen **501**. Further, the first portable terminal **101** outputs the forwarding group information **251** received from the vehicle electronic system **200** as illustrated in the screen **601** of FIG. **6**. Accordingly, the first portable terminal **101** outputs a call service connection request screen in which the first link item **51** and the second link item **52** are output to a side of the screen.

[0080] After outputting the screen **601** to the display unit **140** for a predetermined time, when a predetermined time elapses, the first portable terminal **101** outputs a screen **603**. The first portable terminal **101** checks forwarding setting information **153** stored in the memory **150**, automatically designates a forwarding selection terminal, for example, a second portable terminal **102**, and ensures that call service forwarding to the second portable terminal **102** is performed. The first portable terminal **101** highlights the display to allow a user to recognize that the second portable terminal **102** is designated as a forwarding selection terminal. When a call service connection request message from the transmission terminal **109** through background processing without an output procedure of screens **601** and **603**, the first portable terminal **101** controls the second portable terminal **102** registered as the forwarding group information to automatically forward the call service connection request message. The second portable terminal **102** is located in the vehicle **201** and becomes a terminal registered with forwarding group information **251** by the vehicle electronic system **200**. Further, the second portable terminal **102** is not located in the vehicle **201**, but becomes a terminal of a certain place designated by the first portable terminal **101**. The second portable terminal **102** then performs a call with the transmission terminal **109** and transfers a calling content to the first portable terminal **101** with messages to remove a driving hindrance factor of performing a direct call by the user. In this procedure, the first portable terminal **101** informs the transmission terminal **109** that it is forwarded to the second portable terminal **102** to form a call channel with the second portable terminal **102** in a state that the user recognizes during forwarding.

[0081] The first portable terminal **101** user controls a forwarding function to a certain terminal before a predetermined time elapses. When receiving the call service connection request message, the first portable terminal **101** user checks the transmission terminal **109** and ensures that a corresponding call service connection request message to the third por-

table terminal 103. To accomplish this, the first portable terminal 101 selects an input signal selecting a second link item 52 corresponding to the third portable terminal 103. The display unit 140 of the first portable terminal 101 then outputs a screen indicating that call service forwarding is being performed to "Tom" being a third portable terminal 103 user as illustrated in screen 605.

[0082] If the call forwarding is terminated, the first portable terminal 101 restores a previous screen as illustrated in screen 607. Here, the screen 607 indicates that a first portable terminal 101 previously outputs map information. Accordingly, although the user receives a call service connection request message, the first portable terminal 101 user confirms map information without being disturbed, to safely arrive at his destination.

[0083] Additionally, as illustrated previously, the second portable terminal 102 or the third portable terminal 103 selected to forward a communication service outputs forwarding ground information 251 on a screen and output a screen informing communication service forwarding. Accordingly, the second portable terminal 102 of the third portable terminal 103 ensures that communication service forwarding is accepted or corresponding communication service forwarding is again forwarded to another terminal.

[0084] As illustrated above, the communication service forwarding function of the present invention automatically performs vehicle mode entry when a driver is located in the vehicle 201 to pay attention to driving, and support such that a communication service to a forwarding selection terminal set or selected by the user based on a vehicle mode. The communication service forwarding function of the present invention is automatically released when the user releases a vehicle mode or the portable terminal is beyond a communication distance of the vehicle communication unit 210. Accordingly, the portable terminal 100 of the present invention ensures that a communication service forwarding function is released to perform service support according to a general communication service function.

[0085] The foregoing embodiment has illustrated a configuration of a system and portable terminals for supporting a communication service forwarding function and functions thereof. Hereinafter, various methods for supporting a communication service forwarding function of the present invention will be described in detail with reference to the accompanying drawings.

[0086] FIG. 7 is a flowchart illustrating a method of operation of a portable terminal for supporting a communication service forwarding function according to an embodiment of the present invention, particularly, which is a flowchart illustrating an operation method of a first portable terminal 101 first receiving a communication service connection request message from a transmission terminal 109.

[0087] Referring to FIG. 7, in the operation method of a portable terminal according to the present invention, a controller 160 of a first portable terminal 101 receives power from a power supply and perform power distribution necessary for operations of respective structural elements in step 701.

[0088] Next, the first portable terminal 101 determines whether it enters a vehicle mode in step 703. To accomplish this, the first portable terminal 101 is located within an allowable communication range and performs registration in the vehicle communication unit 210. The vehicle communication unit 210 performs a function of an AP with respect to the first

portable terminal 101. If establishing a communication channel with the vehicle communication unit 210, the first portable terminal 101 provides identification information to the vehicle electronic system 200 through the vehicle communication unit 210. If registration of the vehicle communication unit 210 is terminated, the first portable terminal 101 determines it as entering the vehicle mode. In this case, the first portable terminal 101 outputs a pop-up window inquiring presence of entering the vehicle mode on the display unit 140, and ensures that entering the vehicle mode is cancelled or the vehicle mode is not entered.

[0089] When the first portable terminal 101 does not enter the vehicle mode at step 703, it supports a terminal function according to user input in step 705. For example, the first portable terminal 101 ensures that certain user functions such as a navigation function, a file search function, a file playback function, and a broadcasting receiving function are performed according to an input signal provided from the input unit 120 or a display unit 140 of an input function.

[0090] When entering the vehicle mode is performed at step 703, the portable terminal 101 receives forwarding group information 251 from a vehicle electronic system 200 in step 707. To accomplish this, the vehicle electronic system 200 collects identification information of portable terminals located in the vehicle 201 in a registration procedure, and generate forwarding group information 251 based on the collected identification information of the portable terminals. A procedure of receiving forwarding group information 251 is performed after step 709 to be described later.

[0091] The first portable terminal 101 then determines whether a communication service connection request message is received from the transmission terminal 109 in step 709. To accomplish this, the transmission terminal 109 transmits a communication service connection request message to the first portable terminal 101 through the mobile communication system 300. When a separate communication service connection request message is not received, the first portable terminal 101 performs a user function according to user input while maintaining a vehicle mode state.

[0092] When the communication service connection request message is received from the transmission terminal 109 at step 709, the first portable terminal 101, the first portable terminal 101 outputs a screen according to reception of the communication service connection request message on a display unit 140. The first portable terminal 101 outputs forwarding group information 251 together with the display unit 140. The first portable terminal 101 determines whether an automatic mode of a communication service forwarding function is set in step 711. The automatic mode of the communication service forwarding function is a mode of forwarding a communication service to a certain preset portable terminal without selection of a terminal performing forwarding. When the automatic mode is not set, the first portable terminal 101 transfers a communication service connection request message to a forwarding terminal selected by the user in step 713. The user designates a certain terminal from the forwarding group information 251 output on the display unit 140 as a forwarding selection terminal.

[0093] However, when the automatic mode is selected at step 711, the first portable terminal 101 determines whether an input signal for selecting a forwarding terminal is generated in step 715. When a certain forwarding terminal is selected at step 715, the process may go to step 713. To accomplish this, the first portable terminal 101 waits for a

predetermined time for selecting the forwarding terminal. Further, the first portable terminal 101 outputs information with respect to a terminal automatically performing communication service forwarding on the display unit 140. When a separate forwarding terminal is not selected at step 715, the first portable terminal 101 controls a forwarding selection terminal previously set in the forwarding setting information 153, for example, the second portable terminal 102 to automatically perform the communication service forwarding in step 717. Here, the second portable terminal 102 is a terminal belonging to the forwarding group information 251 generated by the vehicle electronic system 200. The second portable terminal 102 is a terminal that the first portable terminal 101 user optionally inputs.

[0094] Accordingly, the first portable terminal 101 forwards a communication service connection request message received while a driver is driving a vehicle to another portable terminal that lets the driver to pay attention to driving. Further, although the first portable terminal 101 user does not drive the vehicle, the first portable terminal 101 ensures that communication service forwarding to another portable terminal in the vehicle 201 is easily performed according to a need of the user.

[0095] FIG. 8 is a flowchart illustrating a method of forwarding a communication service based on a vehicle according to an embodiment of the present invention. Hereinafter, a call service will be described as an example of communication services.

[0096] Referring to FIG. 8, in the method of forwarding a communication service according to the present invention, portable terminals 101, 102, and 103 communicates with a vehicle electronic system 200 within an allowable communication range, for example, in a vehicle 201 to perform registration in a vehicle communication unit 210 in step 801. The portable terminals 101, 102, and 103 perform an SSID search of the vehicle communication unit 210. When security is set, the portable terminals performs an authentication procedure and be registered in the vehicle communication unit 210. Conversely, when the security is not set, the portable terminals are registered in the vehicle communication unit 210 without performing the authentication procedure.

[0097] When the portable terminals 101, 102, 103 are registered in the vehicle electronic system 200, the vehicle electronic system 200 requests IDentification (ID) information for communication service forwarding to the respective portable terminals 101, 102, 103 in step 803. Then, the portable terminals 101, 102, and 103 provide each ID information to the vehicle electronic system 200 in step 805. Here, the ID information contains terminal ID, phone numbers, a name, and photograph information. The vehicle electronic system 200 collecting the ID information from the respective portable terminals 101, 102, and 103 combines the collected ID information to generate forwarding group information 251.

[0098] A transmission terminal 109 then requests call connection with a first portable terminal 101 to a mobile communication system 300 in step 807. Then, the mobile communication system 300 controls the first portable terminal 101 to transmit a message corresponding to a call service connection request in step 809. To accomplish this, the mobile communication system 300 searches a base station in which the first portable terminal 101 is located and controls a corresponding base station to transmit a call service connection request message to the first portable terminal 101.

[0099] The first portable terminal 101 receiving the call service connection request message requests the forwarding group information 251 to the vehicle electronic system 200 in step 811. The step of providing the forwarding group information 251 is adjusted to be performed immediately after the vehicle electronic system 200 generates the forwarding group information 251. The forwarding group information 251 is provided to respective portable terminals 101, 102, and 103 without separate request from the portable terminals 101, 102, and 103. Accordingly, the respective portable terminals 101, 102, and 103 store and manage the forwarding group information 251 while they are located in the vehicle 201.

[0100] If the vehicle electronic system 200 receives a request signal of the forwarding group information 251, it provides the forwarding group information 251 to the first portable terminal 101 in step 813. Then, the first portable terminal 101 ensures that the received forwarding group information 251 and a screen interface according to reception of the call service connection request message are output on the display unit 140. Accordingly, the first portable terminal 101 user recognizes that a current state is a state that call service connection is requested from the transmission terminal 109 and a call service forwarding to the second portable terminal 102 and the third portable terminal 103 is possible. Next, the first portable terminal 101 user generates an input signal designating a certain terminal, for example, the second portable terminal 102 as a forwarding selection terminal. The generated input signal, namely, a forwarding selection terminal designation signal is then transferred to the vehicle electronic system 200 in step 815.

[0101] When the vehicle electronic system 200 receives the forwarding selection terminal designation signal, it transmits a call service forwarding acceptance presence message to the second portable terminal 102 designated in step 817. The second portable terminal 102 then outputs a screen interface regarding presence of a call service forwarding acceptance on a display unit. Accordingly, the second portable terminal 102 user recognizes that the first portable terminal 101 currently instructs call service forwarding. The second portable terminal 102 outputs the forwarding group information 251 together with the display unit 140 such that the user again forwards the received call service forwarding to another portable terminal, for example, the third portable terminal 103.

[0102] When the second portable terminal 102 user accepts the call service forwarding, the second portable terminal 102 transfers a call service forwarding acceptance message to the first portable terminal 101 through the vehicle electronic system 200 in step 819. Accordingly, the first portable terminal 101 transfers an alarm message informing the mobile communication system 300 that call service forwarding to the second portable terminal 102 is performed in step 821.

[0103] The mobile communication system 300 then transfers the alarm message to the transmission terminal 109 and form a communication channel for call connection of the transmission terminal 109 in step 823.

[0104] Accordingly, a communication path including the transmission terminal 109, the mobile communication system 300, the first portable terminal 101, the vehicle electronic system 200, and the second portable terminal 102 is formed, and a call service between the second portable terminal 102 and the transmission terminal 109 is supported through the communication path. In more detail, when the transmission terminal 109 transfers a first voice signal to a mobile communication system 300 in step 825a voice signal transfer

procedure is performed, that is, the mobile communication system 300 transfers the first voice signal to the first portable terminal 101 in step 827, the first portable terminal 101 transfers the first voice signal to the vehicle electronic system 200 in step 829, and the vehicle electronic system 200 transfers the first voice signal to the second portable terminal 102 in step 831. The voice signal transfer procedure of the second portable terminal 102 includes a step of transferring a second voice signal to a vehicle electronic system 200 by the second portable terminal 102 in step 833, a step of transferring the second voice signal to the first portable terminal 101 by the vehicle electronic system 200 in step 835, a step of transferring the second voice signal to a mobile communication system 300 by the first portable terminal 101 in step 837, and a step of transferring the second voice signal to the transmission terminal 109 by the mobile communication system 300 in step 839.

[0105] FIG. 9 is a signal flowchart illustrating a method of forwarding a communication service according to a second embodiment of the present invention.

[0106] Hereinafter, a call service forwarding method will be described as an example of communication service forwarding methods. Before the description, step 901, step 903, and step 905 are implemented in the same manner as step 801, step 803, and step 805, respectively, and thus a detailed description thereof is omitted.

[0107] Referring to FIG. 9, in the call service forwarding method, a vehicle electronic system 200 generates forwarding group information 251 based on ID information received from the portable terminals 101, 102, and 103, and provide the generated forwarding group information 251 to the mobile communication system 300 in step 907. To accomplish this, the vehicle electronic system 200 includes a communication module capable of communicating with the mobile communication system 300. When forwarding setting information setting to automatically forward a communication service connection request message to another terminal is included in the forwarding group information 251, the method of forwarding a communication service of the present invention omits a part of following procedures and establishes a communication channel between a forwarding terminal set with automatic forwarding and the transmission terminal 109. The mobile communication system 300 informs the first portable terminal 101 that a communication service connection request message according to communication service connection request from the transmission terminal 109. Moreover, the mobile communication system 300 informs the transmission terminal 109 that the first portable terminal 101 is in a vehicle mode, and a corresponding communication service connection request message is transferred to a second portable terminal 102 designated as a forwarding terminal. Subsequently, both of the second portable terminal 102 and the transmission terminal 109 accept communication service connection, the mobile communication system 300 establishes a communication channel between the second portable terminal 102 and the transmission terminal 109.

[0108] The transmission terminal 109 requests call service connection with the first portable terminal 101 to the mobile communication system 300 in step 909. To accomplish this, the transmission terminal 109 may input phone numbers of the first portable terminal 101, and perform call dial based on the phone numbers.

[0109] When the mobile communication system 300 receives request of a call service connection with the first

portable terminal 101, it transfers a call service connection request message and forwarding group information 251 to the first portable terminal 101 in step 911.

[0110] When the first portable terminal 101 receives the call service connection request message and the forwarding group information 251, it outputs them to the display unit 140. The first portable terminal 101 user then recognizes reception of the call service connection request, and generates an input signal for selecting another terminal, for example, a second portable terminal from the forwarding group information 251, and designates the selected terminal as a forwarding terminal. Accordingly, the first portable terminal 101 provides a designation signal for designating the second portable terminal as a forwarding terminal for call service forwarding to the vehicle electronic system 200 in step 913.

[0111] When the vehicle electronic system 200 receives a forwarding terminal designation signal from the first portable terminal 101, it transfers a call service forwarding acceptance presence message to a second portable terminal 102 designated by the forwarding terminal designation signal in step 915. When receiving the call service forwarding acceptance presence message, the second portable terminal 102 then outputs the reception of a corresponding message to the display unit such that the second portable terminal 120 user checks presence of forwarding. When the user accepts the forwarding, the second portable terminal 102 ensures that a call service forwarding acceptance message is transferred to the vehicle electronic system 200 in step 917.

[0112] When receiving the call service forwarding acceptance message, the vehicle electronic system 200 transfers the call service forwarding acceptance message to the first portable terminal 101 in step 919, and the first portable terminal 101 transfers an alarm message informing that the call service is forwarded to the second portable terminal 102 to the mobile communication system 300 in step 921. The mobile communication system 300 transfers a call acceptance presence message with the second portable terminal 102 according to call service forwarding to the transmission terminal 109 in step 923. When accepting it, the transmission terminal 109 transfers a call acceptance message with the second portable terminal 102 to the mobile communication system 300 in step 925. Subsequently, the mobile communication system 300 transfers call acceptance of the transmission terminal 109 to the first portable terminal 101 in step 927, and form a call channel between the transmission terminal 109 and the second portable terminal 102 in step 929.

[0113] As illustrated above, the method of forwarding a communication service of the present invention performs a communication service based on a communication path including a transmission terminal 109, a mobile communication system 300, and a second portable terminal 120 according to communication service forwarding. More specifically, a voice signal transmitting procedure of the transmission terminal 109 includes a step of transmitting a first voice signal to a mobile communication system 300 by the transmission terminal 109 in step 931, and a step of transferring a first voice signal to a second portable terminal 102 by the mobile communication system 300 in step 933. Further, a voice signal transmitting procedure of the second portable terminal 102 includes a step of transferring a second voice signal to the mobile communication system 10 by the second portable terminal 102 in step 35, and a step of transferring the second voice signal to the transmission terminal 109 by the mobile communication system 10 in step 937.

[0114] As illustrated above, when a first portable terminal **101** is located in the vehicle **201**, and enters a vehicle mode, a method of forwarding a communication service according to an embodiment of the present invention forwards a communication service dialed from the first portable terminal, for example, call connection request to another terminal, so that a driver with the first portable terminal **101** can pay attention to driving. Accordingly, the method of the present invention ensures that stable driving is achieved.

[0115] Here, the foregoing embodiment has illustrated the method of forwarding a communication service of the present invention with reference to a call service. However, the present invention is not limited thereto. The method of forwarding a communication service of the present invention may support a forwarding function with respect to reception of SMS, multi-media message, e-mail or SNS message. To do this, the first portable terminal **101** outputs a screen interface including forwarding information **251** to check whether to forward a service to another terminal before reception of a message according to a corresponding message service.

[0116] When entering a vehicle mode, the first portable terminal **101** ensures that a corresponding message is automatically forwarded to another portable terminal according to forwarding setting information **153**. To do this, the first portable terminal **101** checks forwarding setting information **153** in a vehicle mode entering procedure to set to which terminal the foregoing message are forwarded with default. In this procedure, a first portable terminal **101** user configures forwarding setting information **153** using the first portable terminal **101**, and directly operate the vehicle electronic system **200** to configure the forwarding setting information **153**. In this case, another terminal receiving forwarding of a corresponding communication service is located in the vehicle **201**, and become a terminal included in the forwarding group information **251** or a certain terminal of a certain place optionally designated by the first portable terminal **101** user.

[0117] In the meantime, the foregoing method has illustrated that the second portable terminal **102** directly accepts call service forwarding by way of example. However, the second portable terminal **102** can again apply call service forwarding to another portable terminal, for example, a third portable terminal **103**. To do this, when receiving a message inquiring presence of call service forwarding acceptance, the second portable terminal **102** receives the forwarding group information **251** from the first portable terminal **101** or the vehicle electronic system **200**, and output it on a display unit. As the second portable terminal **102** again applies call service forwarding to the third portable terminal **103**, when the third portable terminal accepts it, a communication path is configured to include the transmission terminal **109**, the mobile communication system **300**, the first portable terminal **101**, the vehicle electronic system **200**, and the third portable terminal **103**. The communication path is configured by a path including the transmission terminal **109**, the mobile communication system **300**, and the third portable terminal **103**.

[0118] The foregoing portable terminal **100** may further include various additional modules according to provision forms. That is, when the portable terminal **100** is a communication terminal, it includes parts that are not mentioned such as a near-distance communication module for near-distance communication, an interface exchanging data in a wired communication scheme or a wireless communication scheme of the mobile terminal **100**, an Internet communication module communicating with an Internet to perform an Internet

function, and a digital broadcasting module receiving and broadcasting digital broadcasting. Since the structural elements can be variously changed according to convergence trend of a digital device, no elements can be listed. However, the portable terminal **100** includes structural elements equivalent to the foregoing structural elements. Further, the terminal **100** of the present invention may be substituted by specific constructions in the foregoing arrangements according to the provided form or another structure. This can be easily understood to those skilled in the present art.

[0119] Further, the portable terminal **100** according to an embodiment of the present invention includes various types of devices supporting a communication service forward function. For example, the mobile terminal **100** includes an information communication device and a multimedia device such as a Portable Multimedia Player (PMP), a digital broadcasting player, a Personal Digital Assistant (PDA), a music player (e.g., an MP3 player), a portable game terminal, a Smart-Phone, a notebook computer, and a handheld PC as well as various mobile communication terminals corresponding to various communication systems.

[0120] In a method of forwarding a communication service based on a vehicle, a system thereof, and a terminal supporting the same, when a communication service connection request is received from a driver, it forwards a communication service to a terminal carried by a certain person to perform stable driving.

[0121] Additionally, although a driver or a passenger performs a communication service, the present invention allows a user to use the communication service at a more comfortable and safer time.

[0122] While the present invention has been shown and described with reference to certain embodiments and drawings of the portable terminal, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims and their equivalents.

What is claimed is:

1. A method of forwarding on a communication service based on a vehicle, the method comprising:
  - registering a portable terminal located in the vehicle in a vehicle electronic system; and
  - forwarding a received communication service connection request message to another terminal, when a communication service connection request message is transmitted to a registered portable terminal.
2. The method of claim 1, further comprising:
  - entering a vehicle mode based on whether the registered portable terminal is in the vehicle electronic system;
  - requesting identification information necessary to forward the communication service connection request message to the another terminal by the registered portable terminal operating in the vehicle mode;
  - collecting the identification information necessary for the forwarding by the registered portable terminal; and
  - generating forwarding group information based on the identification information by the vehicle electronic system.
3. The method of claim 2, further comprising at least one of:
  - receiving the forwarding group information by the portable terminal and outputting the forwarding group information when the registered portable terminal receives the

communication service connection request message, and designating another terminal included in the forwarding group information as a forwarding terminal by the registered portable terminal according to an input signal and automatically designating the another terminal included in the forwarding group information as the forwarding terminal by the registered portable terminal according to preset information.

4. The method of claim 3, wherein forwarding a received communication service connection request message comprises:

- providing a forwarding terminal designation signal to the vehicle electronic system by the registered portable terminal;
- transferring a forwarding acceptance presence message to a terminal designated as the forwarding terminal by the vehicle electronic system;
- providing a forwarding acceptance message to the registered portable terminal through the vehicle electronic system by the forwarding terminal based on forwarding acceptance; and
- providing an alarm message informing a user that a communication service connection request is forwarded to the another terminal in a mobile communication system.

5. The method of claim 4, further comprising:

transferring the alarm message to a transmission terminal requesting the communication service connection of the mobile communication system and outputting the alarm message by the transmission terminal,

supporting a communication service based on a communication path including the registered portable terminal, the vehicle electronic system, the forwarding terminal, the mobile communication system, and the transmission terminal requesting the communication service connection, and

supporting a communication service based on a communication path including the forwarding terminal, the mobile communication system, and the transmission terminal having requested the communication service connection.

6. The method of claim 2, further comprising:

providing the forwarding group information to a mobile communication system,

wherein forwarding a received communication service connection request message includes automatically transferring the communication service connection request message to an automatic forwarding terminal set in the forwarding group information by the mobile communication system.

7. The method of claim 6, further comprising:

informing the registered portable terminal that the communication service connection request message has been received by the mobile communication system;

informing a terminal having requested the communication service connection that the registered portable terminal is in a vehicle mode by the mobile communication system;

informing the registered portable terminal that the communication service connection request message has been transferred to the automatic forwarding terminal by the mobile communication system; and

establishing a communication channel with the terminal by the mobile communication system when communication service connection between the automatic forward-

ing terminal and the terminal having requested the communication service connection is accepted.

8. The method of claim 1, further comprising:

generating forwarding setting information including identification information of another terminal to which a corresponding message is forwarded by the registered portable terminal when the communication service connection request message is received; and

wherein forwarding a received communication service connection request message comprises at least of:

automatically forwarding the communication service connection request message to a forwarding terminal set in the forwarding setting information by the registered portable terminal,

outputting reception of the communication service connection request message, and automatically forwarding the communication service connection request message to the forwarding terminal set in the forwarding setting information when there is no reception of an input signal for designating a registered forwarding terminal after a predetermined time elapses by the registered portable terminal, and

outputting the reception of the communication service connection request message and forwarding the communication service connection request message to a forwarding terminal corresponding to a corresponding input signal when an input signal for designating a registered forwarding terminal is received before a predetermined time elapses by the registered portable terminal.

9. The method of claim 1, further comprising at least one of:

restoring to a previous screen of the reception of the communication service connection request message after the forwarding by the registered portable terminal,

outputting a screen indicating that forwarding is performed to communication termination between a forwarding terminal and a terminal having requested communication service connection after the forwarding, and restoring a previous screen at the communication termination time,

outputting forwarding group information by the forwarding terminal having received the communication service connection request message, and

forwarding, again, the communication service connection request message to another designated forwarding terminal according to a received input signal.

10. A system for forwarding a communication service based on a vehicle, the system comprising:

the vehicle;

a vehicle electronic system, located in the vehicle, for communicating with a portable terminal;

the portable terminal, located in the vehicle for communicating with the vehicle electronic system to be registered in the vehicle electronic system;

a transmission terminal requesting communication service connection to the portable terminal; and

a mobile communication system establishing a communication channel between a forwarding terminal designated by the portable terminal and the transmission terminal.

11. The system of claim 10, wherein a registered portable terminal of the portable terminal forwards a communication service connection request message from the transmission terminal to a terminal designated as a forward terminal

according to an input signal or automatically when the registered portable terminal is operated in a vehicle mode according to registration in the vehicle electronic system.

**12.** The system of claim **10**, wherein the vehicle electronic system comprises:

- a vehicle communication unit communicating with the portable terminal to collect identification information of the portable terminal;
- a vehicle controller generating forwarding group information based on the collected identification information; and
- a vehicle memory unit storing the forwarding group information.

**13.** The system of claim **12**, wherein the portable terminal comprises:

- a communication module receiving the forwarding group information and the communication service connection request message;
- a display unit outputting a received message and the forwarding group information when the communication service connection request message is received;
- an input unit generating an input signal for designating another terminal included in the forwarding group information as a forwarding terminal; and
- a controller controlling the another terminal included in the forwarding group information to be automatically designated as the forwarding terminal according to preset information or the terminal designated to the input signal is designated as the forwarding terminal.

**14.** The system of claim **13**, wherein the portable terminal comprises a memory storing forwarding setting information designating a registered terminal as an automatic forwarding terminal according to the input signal from the input unit,

wherein the controller controls the communication service connection request message to be automatically forwarded to the automatic forwarding terminal when the communication service connection request message is received.

**15.** The system of claim **14**, wherein the mobile communication system receives a message indicating designation of the forwarding terminal and transfers the message to the transmission terminal, and

transfers the communication service connection request message to the automatic forwarding terminal based on the forwarding group information when designation of the automatic forwarding terminal is included in the forwarding group information.

**16.** The system of claim **14**, wherein the forwarding terminal outputs the forwarding group information when the forwarded communication service connection request message is received, and forwards again the communication service connection request message to another forwarding terminal designated according a received input signal.

**17.** A terminal supporting forwarding of a communication service based on a vehicle, the terminal comprising:

- a first communication unit supporting a communication service function;
- a second communication unit supporting signal transmission/reception necessary for registration in a vehicle electronic system in the vehicle; and
- a controller controlling signal transmission/reception for registration in the vehicle electronic system, and controlling the communication service connection request

message to be forwarded to a forward terminal selected according to an input signal or a preset automatic forwarding terminal when the first communication unit receives the communication service connection request message.

**18.** The terminal of claim **17**, further comprising a memory storing forwarding setting information setting an automatic forwarding terminal selected to automatically forward the communication service connection request message when the communication service connection request message is received; and

wherein the second communication unit provides identification information upon registration in a vehicle electronic system, and receive generated forwarding group information based on identification information of terminals located in the vehicle from the vehicle electronic system.

**19.** The terminal of claim **18**, wherein the controller:

controls the communication service connection request message to be automatically forwarded to the automatic forwarding terminal set in the forwarding setting information,

controls the communication service connection request message to be forwarded to the automatic forwarding terminal when a predetermined time elapses without selection of a separate forwarding terminal after output of the forwarding group information, and

controls the communication service connection request message to be forwarded to a corresponding forwarding terminal when an input signal for selecting a registered forwarding terminal is generated before a predetermined time elapses after the output of the forwarding group information.

**20.** The terminal of claim **18**, further comprising:

- a display unit outputting at least one of:
- a screen indicating reception of the communication service connection request message and the forwarding group information when the communication service connection request message is received,
- a screen indicating automatic forwarding terminal information set to be automatically forwarded after a predetermined time elapses among the forwarding group information,
- a screen indicating that a communication service forwarding according to forwarding the communication service connection request message is performed,
- a screen indicating that the terminal is operated in a vehicle mode,
- a previous screen, restored after forwarding the communication service connection request message is terminated,
- a communication service forwarding screen output before call termination between a forwarding terminal and a terminal having requested a communication service connection after forwarding the communication service connection request message, and
- a previous screen, restored after call termination between the forwarding terminal and the terminal having requested the communication service connection after forwarding the communication service connection request message is performed.