



US009066236B2

(12) **United States Patent**  
**Filippi et al.**

(10) **Patent No.:** **US 9,066,236 B2**  
(45) **Date of Patent:** **Jun. 23, 2015**

- (54) **SYSTEM AND METHOD FOR CLONING A WI-FI ACCESS POINT** 7,903,817 B2\* 3/2011 Cam-Winget et al. .... 380/270  
8,023,497 B2 9/2011 Jayaram et al.  
8,228,861 B1 7/2012 Nix
- (71) Applicant: **Time Warner Cable Enterprises LLC**, New York, NY (US) 2002/0022483 A1 2/2002 Thompson et al.  
2004/0008645 A1 1/2004 Janevski et al.

(72) Inventors: **Geoff Filippi**, Ashburn, VA (US); **John Anthony Chen**, Ashburn, VA (US)

(73) Assignee: **TIME WARNER CABLE ENTERPRISES LLC**, New York, NY (US)

(Continued)  
FOREIGN PATENT DOCUMENTS  
KR 10-2006-0032091 A 4/2006

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 7 days.

OTHER PUBLICATIONS  
Kadlec, Jaroslav, et al., "Precise measurement of wireless network roaming functionality and network component parameters applied for automation systems", Third International Conference on Systems (Icons 2008); pp. 373-376, (Apr. 13-18, 2008).

(21) Appl. No.: **13/954,174**

(Continued)

(22) Filed: **Jul. 30, 2013**

(65) **Prior Publication Data**  
US 2013/0347065 A1 Dec. 26, 2013

*Primary Examiner* — Gilberto Barron, Jr.  
*Assistant Examiner* — Abdulhakim Nobahar  
(74) *Attorney, Agent, or Firm* — The Marbury Law Group, PLLC

**Related U.S. Application Data**

(63) Continuation of application No. 13/250,290, filed on Sep. 30, 2011, now Pat. No. 8,555,364.

(57) **ABSTRACT**

(51) **Int. Cl.**  
**H04L 29/06** (2006.01)  
**H04W 12/08** (2009.01)

Systems and methods for cloning a Wi-Fi access point. A determination is made by a network monitoring device to transition communications between a Wi-Fi device and a first access point (AP) to a second AP. The SSID and the security configuration information, and, optionally, network address translation (NAT) information of the first access point are acquired and provided to a second AP. The second AP instantiates the SSID and the security configuration information and, optionally, the NAT information. The networking monitoring device directs the first AP to cease using the SSID and the security configuration information and, optionally, the NAT information in response to receipt of confirmation that the second AP has instantiated the SSID and the security configuration information and, optionally, the NAT information of the first AP.

(52) **U.S. Cl.**  
CPC ..... **H04W 12/08** (2013.01); **H04L 63/0272** (2013.01); **H04L 63/20** (2013.01)


(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 7,606,570 B2 10/2009 Karaoguz et al.
- 7,738,871 B2\* 6/2010 Olvera-Hernandez et al. .... 455/436
- 7,792,072 B2 9/2010 Devarapalli et al.

**24 Claims, 12 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS


2005/0261970 A1 11/2005 Vucina et al.  
2006/0018281 A1 1/2006 Sadot et al.  
2006/0079228 A1 4/2006 Marsico et al.  
2006/0140150 A1 6/2006 Olvera-Hernandez et al.  
2006/0223527 A1\* 10/2006 Lee et al. .... 455/432.2  
2007/0217354 A1 9/2007 Buckley  
2007/0280453 A1 12/2007 Kelley et al.  
2008/0102832 A1 5/2008 Sengupta et al.  
2008/0165740 A1 7/2008 Bachmann et al.  
2008/0304458 A1 12/2008 Aghvami et al.  
2008/0316982 A1\* 12/2008 Murty et al. .... 370/338  
2009/0054037 A1 2/2009 Kaippallimalil  
2009/0141685 A1\* 6/2009 Berglund ..... 370/331  
2009/0286534 A1 11/2009 Garg et al.

2010/0040016 A1 2/2010 Lor et al.  
2010/0111055 A1 5/2010 Chiu et al.  
2010/0325425 A1 12/2010 Park et al.  
2011/0103349 A1 5/2011 Choi et al.  
2011/0249595 A1 10/2011 Rozov  
2012/0089834 A1 4/2012 Li

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in PCT Application No. PCT/US2011/047714, mailed Jan. 18, 2012.  
International Search Report and Written Opinion issued in PCT Application No. PCT/US2011/047721, mailed Apr. 9, 2012.  
International Preliminary Report on Patentability (Chapter 1 of the Patent Cooperation Treaty) issued in PCT Application No. PCT/US2011/047721 mailed Mar. 7, 2013.

\* cited by examiner






FIG. 2




FIG. 3

FIG. 4A





FIG. 4B






FIG. 5





FIG. 6

FIG. 7







FIG.8



**FIG. 9**




FIG. 10




FIG. 11

## SYSTEM AND METHOD FOR CLONING A WI-FI ACCESS POINT

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of application Ser. No. 13/250,290 filed on Sep. 30, 2011. The Ser. No. 13/250,290 is incorporated by reference herein, in its entirety, for all purposes.

### BACKGROUND

High speed data (HSD) service providers typically offer subscribers a gateway device that provides wired connectivity to a fiber, coax or hybrid medium and a Wi-Fi access point (AP) for connectivity within the home or business. The subscriber typically configures the AP with an SSID and a password and may also select an encryption key for encrypting data. In neighborhoods where a single HSD service provider has a significant subscriber base, many Wi-Fi APs are operational but are accessible only to a single SSID. Wi-Fi devices may be configured to access an open Wi-Fi network. If the Wi-Fi AP is configured with filters and/or encryption, then only those Wi-Fi devices configured to meet the filtering parameters and/or with the encryption key may use those AP.

Thus, access to either an open network or a secured network requires a Wi-Fi device to be configured specifically for the network to be accessed. When the Wi-Fi device moves out of range of one AP and into range of another AP, the Wi-Fi device must be reconfigured. Again, if the AP is configured to provide a secured network, the Wi-Fi device must have access to the security parameters of the secured network.

Public Wi-Fi APs, also known as “hot spots,” also require users to register and set up their wireless device using parameters that differ from the subscriber’s home settings. Typically, these parameters include security settings that may include a hotspot SSID and a 12-40 character password or pass phrase. Additionally, a user of a public Wi-Fi AP may be required to sign up/register using a web browser on their wireless device in order to gain access. These extra steps may deter users of Wi-Fi devices from connecting to hot spots. In addition, advanced users may prefer their own SSID and securities and are less likely to trust wireless hot spots. Due to these issues, many network service subscribers that have Wi-Fi enabled mobile devices only enable them at their home, making their mobile devices less useful.

One alternative to Wi-Fi is a mobile device that bridges cellular service to Wi-Fi devices that do not have a cellular radio. A mobile bridging device thus acts as a Wi-Fi AP and uses the cellular service as the connection to the Internet. Mobile bridging devices require that at least one user have an account with a cellular provider. Additionally, mobile bridging devices have limited battery life. A user of a mobile bridging AP faces the same issues previously described.

Some terrestrial network service providers have placed secured Wi-Fi access points in businesses. Patrons may access the Internet for the duration of their stays. However, when a patron leaves the establishment, the Wi-Fi signal degrades and the connection to the Internet is quickly lost.

Under these circumstances, a significant number of Wi-Fi enabled devices are underutilized and a significant amount of Wi-Fi bandwidth that could be used for roaming by other subscribers of HSD service providers is going unused.

### SUMMARY

Embodiments herein are directed to enabling Wi-Fi roaming. A system and method that facilitates Wi-Fi roaming is

described in “System and Method for Wi-Fi Roaming,” application Ser. No. 12/859,964 filed on Aug. 20, 2010, which application is incorporated herein by reference at least for its disclosure of configuring access points to provide session continuity to roaming Wi-Fi enabled devices.

In an embodiment, a gateway supports both a local access point (AP) and a virtual AP. The local AP is accessible only to an “owner” of the gateway. The virtual AP (VAP) is accessible to devices associated with the owner of the gateway and to roaming Wi-Fi devices. A datastore conveys information about the roaming Wi-Fi devices to the VAP to permit them to access the VAP without the need for manual configuration of the VAP.

In another embodiment, a roaming Wi-Fi device may communicate with a gateway via a tunnel to maintain session connectivity during roaming.

In still another embodiment, a session may be initiated on one network, such as a Wi-Fi network or a cellular network, handed off to another network, such as a cellular network or a Wi-Fi network, and then returned to the network on which the session was initiated.

### DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a home gateway according to an embodiment.

FIG. 2 is a block diagram illustrating a network of home gateways operating in conjunction with a central datastore according to an embodiment.

FIG. 3 is a block diagram illustrating a roaming Wi-Fi device according to an embodiment.

FIGS. 4A and 4B are block diagrams illustrating a virtual private network connection between a home gateway and a roaming Wi-Fi device according to two embodiments.

FIG. 5 is a block diagram illustrating a communication continuously provided to a hybrid Wi-Fi device over a Wi-Fi roaming network and a cellular data network according to an embodiment.

FIG. 6 is a block diagram illustrating a hybrid device according to an embodiment.

FIG. 7 is a block diagram of a computing device.

FIG. 8 is a block diagram illustrating functional components of a server.

FIG. 9 is a flow diagram illustrating a process by which a virtual access point serving a Wi-Fi device is cloned according to embodiments.

FIG. 10 is a block diagram illustrating an architecture of a Wi-Fi roaming network that includes a network monitoring module according to an embodiment.

FIG. 11 is a flow diagram illustrating a process by which a link is established between a Wi-Fi device and a new access point according to an embodiment.

### DETAILED DESCRIPTION

As used herein, the term “access point” or “AP” encompasses a device that serves as a point of logical connection for Wi-Fi devices such as laptop computers, notebook computers, PDAs, VoIP phones and dual network (cellular plus Wi-Fi) phones. A typical AP may be configured to confirm that a particular wireless user is authorized to connect to the network (authentication), manage the encryption and decryption of data packets, and, when configured as router, forwards IP packets from one IP host to another over an arbitrary link. An AP may also be configured as a bridge that converts packets from a wired Ethernet frame format into an 802.11 Wi-Fi frame format.

As used herein, the term “HSD service provider” encompasses HSD service providers that provide HSD services over fiber, fiber-hybrid-coax, twisted pair, and coax, and wireless networks and HSD over combinations of those media.

As used herein, the term “home gateway” encompasses a wireless network and/or terrestrial network connected devices with one or more physical Wi-Fi (IEEE 802.11a/b/g/n) APs. While it is anticipated that a home gateway may be located in the residence of a subscriber of an HSD service provider, other embodiments are possible. By way of illustration and not by way of limitation, a device performing some or all of the functions of a “home gateway” as described herein may be located outside of a residence and may be part of the HSD service provider’s plant.

As used herein, the term “authentication” encompasses passing authentication credentials to a Wi-Fi access point that identifies a user of a Wi-Fi device as authorized to access the Wi-Fi access point. For example, the authentication credentials may include the MAC address of the Wi-Fi device and the SSID of the subscriber’s network. An AP and a Wi-Fi device authenticate via authentication request frames sent by the Wi-Fi device and authentication response frames sent by the AP in response to the request. If a Wi-Fi device and an AP are configured to use a shared key, the exchange of authorization frames will include the Wi-Fi device using the shared key to encrypt challenge text. The AP will use the same key to decrypt the challenge text to verify that the Wi-Fi device has possession of the correct key.

As used herein, the term “association” encompasses a process by which an AP and a Wi-Fi device establish a link for sending and receiving data. The term “reassociation” encompasses a process by which a Wi-Fi device that is associated with an AP seeks to associate with a different AP. The “association” (or reassociation) of a Wi-Fi device and an AP may be initiated by a Wi-Fi device sending an association request frame (or, if appropriate, a reassociation request frame) that may include the Wi-Fi device’s SSID and supported data rates. The access point may respond by sending a response frame containing an association ID along with other information regarding the access point.

As used herein, the term “security credentials” encompasses a subscriber’s security protocol (for example, Wired Equivalent Privacy or WEP, and Wi-Fi Protected Access or WPA) and a security key consistent with the protocol used.

FIG. 1 is a block diagram illustrating a home gateway according to an embodiment.

A home gateway **100** comprises a service provider network interface **105** that connects an HSD service provider network to wired networked devices through one or more wired network ports **120** and to wireless devices through one or more AP transceivers **130**. The AP transceivers transmit and receive data over a wireless link **160** to and from wireless devices. In an embodiment, the wireless link may be an 802.11x compliant link (sometimes referred to herein as a “Wi-Fi” link).

The home gateway **100** may also include processing circuitry **110** that implements software instructions to manage the general operation of the home gateway **100**, including by way of example the receiving, transmission and routing of data, housekeeping functions, quality of service functions, and signal power management among others. The processing circuitry **110** may be a single processing device or a plurality of processing devices. Such a processing device may be, for example, any one or more of a microprocessor, microcontroller, digital signal processor, field programmable gate array, programmable logic device, logic circuitry, state machine, analog circuitry, digital circuitry, and/or any device that

manipulates signals (analog and/or digital) based on operational instructions. The processing circuitry **110** may comprise a memory (not illustrated), read-only memory, random access memory, volatile memory, non-volatile memory, flash memory, static memory, dynamic memory, optical or magnetic storage, and/or any device that stores digital information.

In an embodiment, the wireless link **160** is a wireless link of a wireless network conforming to a communication protocol such as 802.11(a, b, g, or n).

The interface **105**, the network ports **120** and selected functions of AP transceiver **130** may be implemented in hardware, firmware or software. Other functions of transceiver **130** may be implemented in analog RF (Radio Frequency) circuitry as will be understood by one skilled in the art. When implemented in software, the operational instructions used to implement the functions and features of these devices can also be implemented on processing circuitry **110**.

In an embodiment, the AP transceiver **130** modulates the data to produce an RF signal of the wireless link **160**. In an embodiment of the present invention, the AP transceiver **130** transmits at one of a plurality of power levels, as determined by a power management application implemented by the software **145**. By way of illustration and not by way of limitation, the transmit power of the AP transceiver **130** may be increased when the home gateway **100** is providing services to roaming Wi-Fi devices as further described below. In another embodiment, the transmit power is limited according to applicable laws of the jurisdiction in which the home gateway **100** is operated.

AP transceiver **130** is further operable to receive signals from a Wi-Fi device over wireless link **160**. In this instance, the transceiver **130** receives an RF signal and demodulates the RF signal to obtain a base-band signal to recapture a packet of data.

The interfaces **105**, the network ports **120** and the transceiver **130** may be assigned separate unique MAC addresses to permit the operations of these components to be monitored by external devices and to provide external management of these components.

The AP roaming module **140** is configured to interface with the AP transceiver **130** and to create and manage one or more access points that are logically separate from a home AP (the logical AP sometimes referred to herein as a “virtual access point” or “VAP”). In an embodiment, a processor **150** of the AP roaming module **140** operates software **145** to create and manage the VAP and to allow the VAP to emulate the operation of a physical AP at the MAC layer while operating with distinct SSID and key sets. The SSID and key sets may be stored in a memory **155**. In another embodiment, the processor **150** of the AP roaming module **140** may operate software **145** to provide partial emulation of the IP and Application Layer behavior of physical AP to provide authentication, accounting and diagnostic functions that are independent of the physical AP. At the IP layer, the VAP may be provided a distinct IP address and a fully qualified domain name (FQDN). At the Application Layer, the behavior of distinct physical APs may be emulated by providing each VAP with its own set of SNMPv3 secrets and SNMPv2 communities, RADIUS shared secrets, and Web and telnet login identities. These emulations provide the service provider or other manager of the Wi-Fi roaming network access to the configuration settings of the one or more VAPs through either automated or manual means.

The software **145** also permits a subscriber to register designated SSID and security credentials in association with a Wi-Fi device’s unique MAC address.

5

In an embodiment, when a subscriber establishes an SSID and security credentials at the home gateway **100**, the subscriber may be offered an option to subscribe to a Wi-Fi roaming service. In another embodiment, the offer to subscribe to a roaming service may be dependent on the number of installed gateways of the service provider in proximity to home gateway **100**. In this embodiment, the roaming module is configured by the service provider to offer the roaming service when the dependency is met.

FIG. **2** is a block diagram illustrating a network of home gateways operating in conjunction with a central datastore according to an embodiment.

As illustrated in FIG. **2**, an HSD service provider has installed a plurality of home gateways in an HSD service area **214**, including HG **1**, HG **2**, HG **3** and HG **N** (**220**, **222**, **224**, and **226**). HG **1**-HG **N** each comprises a Wi-Fi roaming module **140** that comprises software **145**. The software **145** further comprises a graphical user interface (GUI) **212**. (These elements are only illustrated for HG **1 220** for clarity.)

In an embodiment, an HG **1 220** communicates with a wired networked device **216** and a Wi-Fi device **218** over a wireless link. By way of illustration and not by way of limitation, Wi-Fi device **218** complies with the 802.11a/b/g/n standard. The Wi-Fi device **218** may be configured with a home SSID and with security credentials that permit it to access HG **1 220** to send and receive data. While only one Wi-Fi device **218** and one wired networked device **216** are illustrated, this is not meant as a limitation. Additional Wi-Fi devices **218** and wired networked devices **216** may be configured to communicate with HG **1 220**.

In this embodiment, the service provider has installed HG **2** through HG **N** in HSD service area **214** and has elected to offer roaming Wi-Fi services to its subscribers in the HSD service area **214**. The Wi-Fi roaming module **140** uses software **145** to present an offer for Wi-Fi roaming services to the subscriber associated with HG **1 220**. The offer may be presented on Wi-Fi device **218** or wired networked devices **216** using GUI **212**. When the subscriber associated with HG **1 220** accepts the offer for Wi-Fi roaming services, the GUI **212** presents the subscriber with a request for information. In an embodiment, the request may be pre-populated with the home SSID of HG **1 220**, the subscriber's name, and the MAC address of the Wi-Fi device **218**. The subscriber may be invited to add the MAC addresses of additional Wi-Fi devices **218** associated with the subscriber. The requested information is sent to a Wi-Fi roaming datastore **230** and stored in a Wi-Fi roaming record **232** associated with the subscriber. In an embodiment, the Wi-Fi roaming datastore **230** may be implemented on a server device as illustrated in FIG. **8**.

In an embodiment, a subscriber who subscribes to the Wi-Fi roaming service may also subscribe to a network provided class of service (CoS). A CoS may define a roaming coverage, such as local coverage versus national coverage. A CoS may establish a priority, such as standard versus premium, which determines the priority of a Wi-Fi device under conditions of network congestion. A CoS may also establish a service measure, such as a bandwidth limit (Mb/s) or a data quota over time (2 GB/month).

Note that the CoS of the roaming subscriber does not directly affect the CoS of the owner of the home gateway providing access to a roaming Wi-Fi device. However, in order to prevent any degradation of service quality to the owner of the home gateway, additional resources may be allocated to the home gateway owner's network to account for the bandwidth consumed by the roaming subscriber.

In an embodiment, the Wi-Fi roaming datastore **230** may associate the MAC address of HG **1 220** and the subscriber's

6

SSID, security credentials, Wi-Fi device MAC address(es) and CoS with an already pre-provisioned subscriber account which includes billing and network usage information.

In an embodiment, the MAC address of the HG **1 220** allows the network provider to find HG **1 220** on the network to allow the operations of HG **1 220** to be monitored, to permit maintenance of HG **1 220** and, when necessary, to assist the subscriber associated with HG **1 220** to configure the device.

FIG. **3** is block diagram illustrating a roaming Wi-Fi device according to an embodiment.

When the Wi-Fi device **218** is configured to use the local SSID and security credentials of HG **1 220** (sometimes also referred to herein as the "home gateway"), the Wi-Fi device **218** may scan for a non-local Wi-Fi VAP (sometimes also referred to as a "foreign gateway").

In an embodiment, the Wi-Fi device **218** actively seeks VAPs by sending probe request frames, as for example, to the Wi-Fi VAP in HG **2 222** and to the Wi-Fi VAP in HG **3 224**. The probe request frame may include the SSID of the home gateway associated with Wi-Fi device **218**. In an alternate embodiment, the Wi-Fi device **218** first listens for AP-transmitted beacon signals and takes note of the corresponding signal strengths. The beacons contain information about the access point, supported data rates, etc. Wi-Fi device **218** may use this information along with the signal strength to determine that it is appropriate to send a probe request frame.

When a Wi-Fi VAP belonging to the network service provider such as Wi-Fi VAP in HG **2 222** or Wi-Fi VAP in HG **3 224** detects a probe request frame, it determines whether the SSID and the Wi-Fi device MAC data associated with Wi-Fi AP in HG **1 220** are found in a local memory to which the receiving Wi-Fi VAP has access. Alternatively, the receiving Wi-Fi VAP may check the Wi-Fi roaming datastore **230** to determine whether values matching those sent in the probe request are stored there. If the values are found in either the memory or the datastore, a probe response frame is sent from the acknowledging VAP to the Wi-Fi device **218**. The Wi-Fi device **218** then authenticates and associates (or reassociates) with the responding VAP as per the normal IEEE 802.11 (Wi-Fi) standard. The SSID/Wi-Fi device MAC data may be stored in the memory **155** (see FIG. **1**) of a Wi-Fi VAP as a result of a previous association with that Wi-Fi VAP.

The Wi-Fi device **218** may pre-authenticate with a Wi-Fi VAP such as the Wi-Fi VAP in HG **2 222** or the Wi-Fi VAP in HG **3 224** before reassociating with that VAP. Pre-authentication is described in detail in "System and Method for Wi-Fi Roaming," application Ser. No. 12/859,964 filed on Aug. 20, 2010, which application is incorporated herein by reference.

In an embodiment, after the pre-authentication of the Wi-Fi device **218** with the Wi-Fi VAP in HG **2 222**, a tunnel (not illustrated) between HG **2 222** and HG **1 220** is established. The tunnel does not carry traffic unless and until the Wi-Fi device **218** reassociates with the Wi-Fi VAP in HG **2 222**. During the reassociation process, the IP address of Wi-Fi device **218** assigned by the HG **1 220** remains the same. In this way, the connection to HG **1 220** is maintained and the transition from the AP in HG **1 220** to the VAP in HG **2 222** is nearly seamless. When the Wi-Fi device **218** acts to disassociate from the Wi-Fi AP in HG **1 220** and reassociate with the Wi-Fi AP in HG **2 222**, the time required to complete the transfer from one AP to another is significantly reduced.

In another embodiment, the SSID/Wi-Fi device MAC data of the Wi-Fi device **218** may be found in the memory **155** (see FIG. **1**) of the Wi-Fi VAP in HG **2 222**. In this embodiment, the security information of the Wi-Fi device **218** is acquired from the Wi-Fi roaming datastore **230**.

In another embodiment, the Wi-Fi VAPs may delete the SSID/security credential/Wi-Fi device MAC data from its memory 155 (see FIG. 1), and the Wi-Fi VAP in HG 2 222 of a subscriber who has not actively associated with that Wi-Fi VAP for a period of time.

In an embodiment, when the roaming subscriber associates with a foreign Wi-Fi VAP, the roaming subscriber accesses the network provider's network via the foreign Wi-Fi VAP. In this embodiment, the roaming subscriber may access the Internet directly via the home gateway in which the foreign Wi-Fi VAP resides. In this embodiment, the Wi-Fi device will need to obtain a new IP address and/or network address translation (NAT) as it moves from one HGNAP to another. An established session using a session based protocol, such as TCP/IP, VoIP, IPTV, etc., will be interrupted during this process.

In an alternate embodiment, the roaming subscriber may communicate with his or her home gateway via a virtual private network (VPN), Layer 2 Transport Protocol (L2TP), or any other network encapsulation protocol.

FIG. 4A is a block diagram illustrating a virtual private network connection between a home gateway and a roaming Wi-Fi device according to an embodiment.

In this embodiment, a roaming Wi-Fi device 414 is associated with (connected to) a foreign VAP 412 in a foreign gateway 410. The foreign gateway 410 connects to the Internet 418 via an Internet connection 424. A home gateway 402 is associated with a subscriber who is also associated with the roaming Wi-Fi device 414. The home gateway 402 connects to the Internet via an Internet connection 422. In an embodiment, the Internet connections 422 and 424 may be established over a wired or wireless network. By way of illustration and not by way of limitation, the Internet connections 422 and 424 may be established over a cable network, a fiber network, a DSL connection, a satellite network, and a cellular network.

The home gateway 402 and the foreign gateway 410 comprise VPN software 416. The VPN software comprises both a VPN server and a VPN client. The home gateway 402 uses the VPN software to instantiate a VPN server on home gateway 402. The association of the roaming Wi-Fi device 414 to the foreign VAP 412 causes the foreign gateway 410 to use the VPN software 416 to instantiate a VPN client on the foreign gateway 410 and to establish a VPN connection 426 over the Internet connections 422 and 424. The Wi-Fi device 414 communicates with home gateway 402 via the VPN. The Wi-Fi device communicates with the Internet via the VPN and the Internet connection 422 of the home gateway 402. At any given time, the IP address of the Wi-Fi device, which was issued by the home gateway, 402 remains the same and the end point of the session (that is, the user's home gateway) is also the same. Thus, established sessions are maintained. In this way, VoIP calls, IPTV program delivery and other services that rely on session-based protocols can be handed off without loss of communications. The VPN may be established using known protocols such as L2TP, L2F and PPTP.

The VPN 426 provides the roaming subscriber with the same network functionality that the subscriber would have if connected directly to the home gateway (either through a wired or wireless link). For example, if the home gateway is configured to permit the subscriber to access content on a DVR, the same access would be available to the subscriber through a VAP of the service provider.

The VPN 426 also isolates the gateway in which the serving Wi-Fi VAP resides from the activities of the subscriber. Thus, if the subscriber is guilty of misconduct (spam, denial of service attacks), the subscriber's activities are not associated with the IP address of the owner of the serving gateway.

In an embodiment, the roaming service may be provided as a valued added service. In this embodiment, the class of service (CoS) determines what a subscriber pays for service and what a subscriber receives in return. Referring again to FIG. 2, the Wi-Fi roaming datastore 230 may be implemented using authentication, authorization, and accounting (AAA) management software. For example, the Wi-Fi roaming datastore 230 may be implemented on a server operating the RADIUS networking protocol. RADIUS is a client/server protocol that runs in the application layer, using UDP as transport. A home gateway operates a RADIUS client component that communicates with the RADIUS server.

In this embodiment, the AAA management software performs the subscriber authentication processes described above to authenticate users or devices before granting them access to the VAP devices of the network service provider. The AAA management software may also provide accounting of roaming services used by a subscriber account and provide billing information to a billing system (not illustrated).

By way of illustration, the unique MAC address of the Wi-Fi device may be used as the username of the account in the RADIUS server. The SSID would be the password for the account. If the Wi-Fi MAC address and SSID presented by the Wi-Fi device match what is stored in the RADIUS server, the security credentials and CoS are returned to the foreign home gateway and the VAP is set up and instantiated.

In yet another embodiment, a network service provider that does not have its own edge network (sometimes referred to herein as an "over-the-top network") may not cooperate with network service providers that have edge networks. For the over-the-top network service providers to make their roaming networks available to the subscribers of the other network service providers, the over-the-top network service providers will need to make sure that each of its foreign gateways can establish a network connection to the home gateway device without being blocked by the edge network service providers at either end.

FIG. 4B is a block diagram illustrating a virtual private network connection between a home gateway of an over-the-top service provider and a roaming Wi-Fi device according to an embodiment. In this embodiment, a roaming Wi-Fi device 414 is associated with (connected to) a foreign VAP 412 in a foreign gateway 410. The foreign gateway 410 connects to the Internet 418 via an Internet connection 424. A home gateway 402 is associated with a subscriber who is also associated with the roaming Wi-Fi device 414. The home gateway 402 connects to the Internet via an Internet connection 422. In an embodiment, the Internet connections 422 and 424 may be established over a wired or wireless network. By way of illustration and not by way of limitation, the Internet connections 422 and 424 may be established over a cable network, a fiber network, a DSL connection, a satellite network, and a cellular network.

An over-the-top service provider home gateway device first establishes a VPN connection 426 to an over-the-top service provider ISP Server 420. A VAP receiving a probe request first checks with the Wi-Fi roaming datastore 230 of the over-the-top service provider. If authentication credentials sent in the probe request are found in the Wi-Fi roaming datastore 230 of the over-the-top service provider, the information is also sent to the ISP Server 420, so that its VPN connections 426 may be mapped by the ISP Server 420. In this way, a seamless connection from the Wi-Fi Device 414 can be made to the home gateway 402 through the foreign gateway 410 via the ISP Server 420.

In yet another embodiment, an “over-the-top” network service provider may want to provide services to subscribers with roaming Wi-Fi Devices that have no corresponding home gateways. In this embodiment, the over-the-top network service provider will collect the subscriber Wi-Fi roaming record **232** by other means than that of the home gateway device and store it in the Wi-Fi roaming datastore **230**. A VAP receiving a probe request first checks with the Wi-Fi roaming datastore **230** of the over-the-top service provider. If authentication credentials sent in the probe request are found in the Wi-Fi roaming datastore **230** of the over-the-top service provider, the information is also sent to the ISP Server **420**, so that the VPN connection **426** may be mapped by the ISP Server **420**. In this way, a seamless connection from the Wi-Fi Device **414** can be made to **420** through the foreign gateway **410** and then out to the Internet **418**.

Alternatively, the cooperating network service providers may establish a “central” repository for roaming authentication information. The central repository may be a distributed storage system that is accessible through a single interface. The interface may route authentication requests based on one or more attributes of the VAP that are reflected in the probe request.

In another embodiment, the operator of the roaming Wi-Fi network is not the HSD service provider that serves the roaming subscriber. Rather, the operator acquires Wi-Fi capacity from such service providers and provides roaming services for a fee. In this embodiment, the Wi-Fi roaming datastore **230** is accessible to or operated by the operator of the roaming Wi-Fi network.

As previously discussed, the Wi-Fi device may be a Wi-Fi phone that is also configured to access a cellular network (sometimes referred to as a “hybrid Wi-Fi device”). In an embodiment, a hybrid Wi-Fi device may be further configured to establish and tear down VPN tunnels between itself and a home gateway without the need for additional logic or hardware in the network over which a tunnel would be established. Thus, in this embodiment, the VPN tunnel logic has been moved to the edge of the network.

FIG. **5** is a block diagram illustrating a communication continuously provided to a hybrid Wi-Fi device over a Wi-Fi roaming network and a cellular data network according to an embodiment.

In an embodiment, a Wi-Fi hybrid device **502** comprises a Wi-Fi radio (not illustrated) and a cellular radio (not illustrated) to allow the Wi-Fi hybrid device **502** to communicate with a Wi-Fi VAP, such as Wi-Fi VAP **512** within HG N **536** and with a cell tower such as cell tower **506** of the cellular network **504**. By way of illustration and not by way of limitation, the cellular data network **504** may be a General Packet Radio Service network, an EDGE Enhanced Data network, an Evolution Data Optimized network, a Universal Mobile Telecommunications System network, a High Speed Packet Access network, a Long Term Evolution and a Wide Interoperability for Microwave Access network or a network meeting another standard.

The Wi-Fi hybrid device **502** is configured to be “aware” of the home gateway HG **1 530**. The HG **1 530** is part of a network of home gateways that operate together to form an HSD service area (see, FIG. **2, 214**). For the purposes of FIG. **5**, the HG N **536** is considered to be on the outer boundary of this HSD service area.

The Wi-Fi hybrid device **502** uses a “virtual IP address” (VIP) to send IP packets to, and receive IP packets from, HG **1 530** while roaming. From the point of view of the HG **1 220**, there are two IP address associated with the virtual private network (VPN) operating over HG roaming VPN tunnel **520**.

The first IP address is associated with the Wi-Fi hybrid device **502** end-point. A second IP address is assigned by the HG **1 220** but controlled by the Wi-Fi hybrid device **502** and is used for data communication (service IPNIP). The two IP addresses are in the same subnet.

The HG roaming VPN tunnel **520** may be implemented using any layer 2 encapsulation protocols, such as L2TP, PPTP and L2F among others. The VPN may be encrypted, using techniques such as L2TP over IPSEC, if the Class of Service (CoS) has that attribute as defined by the customers when they signed up for the service.

At a point in time, the Wi-Fi hybrid device **502** is connected to HG **1 220** through the HG N **226** and the HG roaming VPN tunnel **520** and has an idle-state data connection to a cellular network **504**. Thus, at this point in time, the Wi-Fi hybrid device **502** is sending packets to the HG **1 530** connected to the cellular data network **504** but is not sending packets over the cellular data network **504**.

The Wi-Fi hybrid device **502** may detect that it is moving away from accessible home gateways within the HSD service area.

In an embodiment, the Wi-Fi hybrid device **502** detects this condition by determining that there is only a single roaming HG within its range. In another embodiment, the Wi-Fi hybrid device **502** detects this condition by determining that the signal strengths from all of the roaming HGs within its range are declining. In still another embodiment, the Wi-Fi hybrid device **502** detects this condition by utilizing a digital map showing all known HGs in the HSD service area and determining that it is physically moving to an area without roaming HG coverage. In an embodiment, the location of the hybrid device **502** relative to the digital map may be determined using a GPS module **600** (see FIG. **6**).

When the Wi-Fi hybrid device **502** determines that it is leaving its HSD service area, the Wi-Fi hybrid device **502** forms a cellular VPN tunnel **525** to the HG **1 530** using its cellular radio (not illustrated) over the cellular data network **504**. The cellular VPN tunnel **525** may be implemented using any layer 2 encapsulation protocols, such as L2TP, PPTP, and L2F among others. The cellular VPN tunnel **525** may be encrypted, using techniques such as L2TP over IPSEC, if the Class of Service (CoS) has that attribute as defined by the customers when they signed up for the service. The Wi-Fi hybrid device is now considered multihomed.

The cellular VPN tunnel **525** is in the same virtual local area network (ULAN) and in the same subnet as the IP address associated with the Wi-Fi hybrid device **502** end-point IP and the VIP address assigned by the HG **1 530** to the Wi-Fi hybrid device **502** as described above. From the perspective of HG **1 530**, following the formation of the cellular VPN tunnel **525**, the Wi-Fi hybrid device **502** has a second physical connection to it with another IP address associated with the Wi-Fi hybrid device **502** end point.

It should be noted that the cellular radio component (not illustrated) of the Wi-Fi hybrid device **502** may have an IP address assigned to it by the provider of cellular network **504**. However, other than passing the VPN IP traffic through, this IP address is not used to communicate packets to the HG **1 530**.

Wi-Fi hybrid device **502** monitors the condition of the Wi-Fi link signal to HG N **536** to determine whether a threshold has been reached. In an embodiment, this threshold may be defined by the Class of Service (CoS) assigned to a subscriber at the time the service agreement between the subscriber and the service provider was executed. Once the threshold is reached, the Wi-Fi hybrid device **502** reassigns the service IP/VIP from its Wi-Fi radio to its cellular radio.

The Wi-Fi hybrid device **502** may send an ARP to HG **1 530**. From the perspective of HG **1 530**, it appears that the service IP/NIP moved from the Wi-Fi radio interface to the cellular radio interface in real-time. IP packets directed to and from the Wi-Fi hybrid device **502** will then immediately start using the cellular VPN tunnel **525** for communication thereby maintaining any previously established sessions. When the HG roaming VPN tunnel **520** connection becomes unacceptable, it will be torn down and only the cellular VPN tunnel **525** will remain.

At this point in the time the Wi-Fi hybrid device **502** is connected to HG **1 530** through the cellular VPN tunnel **525**. From the point of view of the HG **1 220**, at this point in time there are two IP addresses associated with the virtual private network (VPN) operating over the cellular VPN tunnel **525**. The first IP address is associated with the Wi-Fi hybrid device **502** end-point. A second IP address is assigned by the HG **1 530** but controlled by the Wi-Fi hybrid device **502** and is used for data communication (service IP/VIP). The two IP addresses are in the same subnet.

In an embodiment, the Wi-Fi hybrid device **502** may monitor the availability of a VAP that belongs to its HSD service area. In an embodiment, the Wi-Fi hybrid device **502** detects this condition by determining that a single roaming HG has come within its range. In another embodiment, the Wi-Fi hybrid device **502** detects this condition by determining that the signal strengths from all of the roaming HGs within its range are increasing. In still another embodiment, the Wi-Fi hybrid device **502** detects this condition by utilizing a digital map showing all known HGs in the HSD service area and determining that it is physically moving to an area that has roaming coverage. In an embodiment, the location of the hybrid device **502** relative to the digital map may be determined using a GPS module **600** (see FIG. 6).

When the Wi-Fi hybrid device **502** determines that it is entering its HSD service area, the Wi-Fi hybrid device **502** associates with a VAP that is part of the HSD service area, such as HG N VAP **512** in the HG N **536**. The HG N **536** forms an HG roaming VPN tunnel **520** connection to its associated HG over its service provider network. The HG roaming VPN tunnel **520** may be implemented using any layer 2 encapsulation protocols, such as L2TP, PPTP, and L2F among others. The VPN may be encrypted, using a technique such as L2TP over IPSEC, if the Class of Service (CoS) has that attribute as defined by the customers when they signed up for the service.

The HG roaming VPN tunnel **520** is in the same virtual local area network (VLAN) and in the same subnet as the IP address associated with the Wi-Fi hybrid device **502** end-point IP and the VIP address assigned by the HG **1 530** to the Wi-Fi hybrid device **502** as described above. From the perspective of HG **1 220**, following the formation of the HG roaming VPN tunnel **520**, the Wi-Fi hybrid device **502** has a second physical connection to it with another IP address associated with the Wi-Fi hybrid device **502** end point. The Wi-Fi hybrid device is now considered multihomed.

Wi-Fi hybrid device **502** monitors the condition of the Wi-Fi link signal to HG N **536** to determine whether a threshold has been reached. In an embodiment, this threshold may be defined by the Class of Service (CoS) assigned to a subscriber at the time the service agreement between the subscriber and the service provider was executed. Once the threshold is reached, the Wi-Fi hybrid device **502** reassigns the service IP/VIP from its cellular radio to its Wi-Fi radio. The Wi-Fi hybrid device **502** may send an ARP to HG **1 220**. From the perspective of HG **1 530**, it appears that the service IP/VIP moved from the cellular radio interface to the Wi-Fi radio interface in real-time. IP packets directed to and from

the Wi-Fi hybrid device **502** will then immediately start using the HG roaming VPN tunnel **520** for communication thereby maintaining any previously established sessions. When the HG roaming VPN tunnel **520** connection is determined to be reliable, the cellular VPN tunnel **525** will be torn down.

During the handoff phases, packets may be lost. However, if protocols such as TCP/IP are used, lost packets will be re-transmitted and thus session quality may be maintained.

In yet another embodiment, when the hybrid device **502** becomes multihomed, instead of relinquishing its second network path (**520** or **525**) to the HG **1 530**, it forms a channel or Ethernet bonding where the independent VPN tunnels **520** and **525** combine to form a redundant array of independent network interfaces (RAIN). Using this method, data packets may be striped across the network interfaces in the same manner that I/O is striped across disks in a RAID array. In some cases, the combination can be for redundancy (mirrored—same data packets go down both paths), or for increased throughput (striped—alternate data packets go down each path) as desired by the subscriber at that moment.

In an embodiment, the combinations allowed, either mirrored and/or striped, or none, may be defined by the Class of Service (CoS) assigned to a subscriber at the time the service agreement between the subscriber and the service provider was executed.

In another embodiment, the defined Class of Service (CoS) as assigned to a subscriber at the time the service agreement between the subscriber and the service provider was executed may be changed by the subscriber during a limited period of time (temporary basis), or for the remaining duration of the service agreement (permanent basis) as the need arises, or as a promotion by the service provider for the purposes of up selling the subscriber.

In the various embodiments set forth above, the determination as to which virtual access point a Wi-Fi device is communicating with is made by the Wi-Fi device based on criteria established by the manufacturer of the Wi-Fi device, the supplier of its software, or the user. Within a network, Wi-Fi devices may behave differentially in response to a particular set of circumstances.

In an embodiment, the roaming of Wi-Fi devices in a Wi-Fi roaming network is facilitated by using a “cloning” process to allow a VAP over which a Wi-Fi device is communicating to move with the roaming Wi-Fi device. From the perspective of the Wi-Fi device, the VAPs it communicates with are indistinguishable from one another.

FIG. 9 is a flow diagram illustrating a process by which a virtual access point serving a Wi-Fi device is cloned according to embodiments.

A determination is made that it is appropriate to transition a Wi-Fi device communicating via a current VAP to a new VAP. (Block **902**.) The determination to transition a Wi-Fi device from the current VAP to a new VAP may be based on any number of factors or combination of factors, including the following:

The signal strength and/or the signal quality of the current VAP may have degraded below a threshold.

The signal strength and/or the signal quality of the new VAP may be above a threshold.

The bandwidth of the current VAP is over utilized or the bandwidth of the new VAP is under utilized.

A second Wi-Fi device needs to transition to the current VAP of the first Wi-Fi device in order to maintain a session.

The Wi-Fi device is perceived to be moving relative to the current VAP and is predicted to be moving out of range of the current VAP and into range of the new VAP.

An estimate of a future state of the Wi-Fi roaming network and the impact this future state may have on the connectivity of the Wi-Fi device.

Once the determination is made that it that it is appropriate to transition a Wi-Fi device communicating via a current VAP to a new VAP, a new VAP is selected for the Wi-Fi device. (Block 904.) The selection of the new VAP is not preconfigured. Rather, the new VAP is selected dynamically by applying selection rules to various factors and combinations of factors. The selection rules may evaluate a new VAP based on one or more of its proximity to the Wi-Fi device, based on its signal characteristics, based on its channel availability, and/or based on the movement and relative location of the Wi-Fi device. The selection rules may also consider a current state of the Wi-Fi roaming network vis-à-vis the Wi-Fi device or consider factors to estimate a future state of the Wi-Fi roaming network and select the new VAP accordingly.

The selection of the new VAP is followed by a transition of communications between the Wi-Fi device and the current VAP to the new VAP. (Block 906.) In this process, the SSID and security information associated with the Wi-Fi device and its home gateway (FIGS. 2, 3, and 10; HG 1 220) are provided to the new VAP. A new tunnel between the new VAP and the home gateway of the Wi-Fi device is established.

Depending on the protocols used to convey data between a current VAP and the home gateway, other information may be required from the current VAP. Public IP addresses are commonly used for Internet servers. Private IP addresses are assigned by local administrators or systems and are only meant to be locally unique. Private IP addresses are commonly used for home or corporate client devices. When a client that is on a private IP space needs to connect to a server on the public Internet, or a host on a different private network, it becomes necessary to use Network Address Translation (NAT). NAT is used to map one or many IP addresses to one or many different IP addresses. The state of this NAT mapping must be maintained by the NAT device. This allows multiple private clients to be addressable behind a single public IP address. When a device on the home network connects to a wireless access point, typically a router functioning within the same device (wireless router) provides this NAT function.

A tunnel from a VAP to a home gateway (see, for example, VPNs 1004 and 1006 connecting foreign VAPs operating in HG 2 222 and HG 3 224 to home gateway HG 1 220 as illustrated in FIG. 10) may be established using different technologies. When the tunnel from the foreign VAP carries link-layer (Layer 2) protocols to the home gateway, then NAT function is performed on the home gateway. When the tunnel carries network layer (Layer 3) protocols from the foreign VAP to the home gateway, then the NAT function is performed by the foreign VAP. When the protocols used by the current tunnel and the new tunnel are network layer protocols, state of the NAT function of the current VAP is synchronized to the new VAP. During a handoff, the NAT state is transferred before the handoff is determined to be complete. In an embodiment, a list of NAT mappings used by the current VAP is sent to the new VAP during the handoff process.

FIG. 10 is a block diagram illustrating an architecture of a Wi-Fi roaming network that includes a network monitoring module according to an embodiment.

As illustrated in FIG. 10, an HSD service provider has installed a plurality of home gateways in an HSD service area 214, including HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226). In an embodiment, the HG 1 220 is the home gateway that is associated with the Wi-Fi device 218. From the perspective of Wi-Fi device 218, HG 2, HG 3 and HG N (222, 224 and 226) are foreign gateways operating foreign

access points. The operation of these elements is described in detail in the discussion of FIG. 2 and FIG. 3 above.

In an embodiment, a Wi-Fi network monitoring module 1002 is illustrated as in communication with each of the plurality of home gateways including HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226) via the Internet 210. Also illustrated in an alternative embodiment in which each of the HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226) comprises a network monitoring module (1002A, 1002B, 1002C, 1002N).

In an embodiment the network monitoring module 1002 may be implemented as a standalone device, such as a computing device (see FIG. 8) or as component of another device connected to the Internet 210, such as Wi-Fi roaming datastore 230 (indicated by dashed lines encompassing both Wi-Fi roaming datastore 230 and network monitoring module 1002 in FIG. 10).

Similarly, network monitoring modules 1002A, 1002B, 1002C, and 1002N may be implemented as a separate module in a home gateway (see, FIG. 1, home gateway Block 100) or as an addition to AP roaming module 140 illustrated in FIG. 1.

The network monitoring modules 1002 and 1002A, 1002B, 1002C, and 1002N may be implemented as software that is executed by a general processor (see, for example, FIG. 8, Block 801 and FIG. 1, Block 150) or as hardware that utilizes a processor dedicated to perform operations assigned to the network monitoring modules.

The network monitoring module (Block 1002 or 1002A, 1002B, 1002C, or 1002N) receives status information from each of the home gateways HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226). For example, the network monitoring module (Block 1002 or 1002A, 1002B, 1002C, or 1002N) may receive signal quality, signal strength, bandwidth usage measures and other metrics from each home gateway relating the AP point operating on that gateway and to APs that are known to that home gateway. In an embodiment, this information is conveyed over the Internet 210.

In an embodiment, each of the home gateways HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226) may present credentials to the network monitoring module 1002 in order to send status information to the network monitoring module 1002 for storage and to retrieve status information stored on the network monitoring module 1002.

In another embodiment, each of the home gateways HG 1, HG 2, HG 3 and HG N (220, 222, 224, and 226) maintains a database comprising the status information of all home gateways in a network of home gateways. Alternatively, a home gateway may monitor beacon messages sent from APs operating on home gateways within a network and maintain status information for a limited set of home gateways.

The network monitoring module (Block 1002 or 1002A, 1002B, 1002C, or 1002N) may also receive information regarding the state of Wi-Fi device 218. This information may include whether the Wi-Fi device 218 is currently communicating with an AP operating on its home gateway HG 1 220 or with a VAP operating on a foreign gateway HG 2, HG 3 and HG N (Blocks 222, 224, and 226).

In an embodiment, a Wi-Fi device that is in communication with an AP operating on its home gateway or a VAP operating on a current foreign gateway, such as HG2 222, may be cloned (see, FIG. 9, Block 906) for operation on a new foreign gateway, such as HG 3 224. The cloning process will be described below using an example in which the Wi-Fi device 218 is currently communicating with foreign gateway HG 2 222. In this example, the current foreign gateway HG 2 222

has established a VPN tunnel **1004** with the home gateway HG **1 220** of the Wi-Fi device **218**.

Referring to FIGS. **10** and **11**, when a Wi-Fi device, such as Wi-Fi device **218**, is moved within range of a neighboring access point, such as the VAP operating on HG **3 224**, the Wi-Fi device **218** will send out probe request frames that include the SSID it is actively scanning. (FIG. **11**, Block **1102**.) The probe request frames will also contain the Medium Access Control (MAC) address of the Wi-Fi device **218** as defined by IEEE 802.11 networks. When a foreign gateway, such as HG **3 224**, receives a probe request frame, the foreign gateway may determine whether the Wi-Fi device **218** is “known” to the foreign gateway. (FIG. **11**, block **1104**.) The determination may be made by the foreign gateway by performing a lookup in its local memory to determine if the SSID of Wi-Fi device **218** is stored therein. If the SSID broadcast by the Wi-Fi device **218** is not found in the local memory of HG **3 224**, the foreign gateway may query the Wi-Fi roaming datastore **230** for the presence of the SSID/MAC address combination of the Wi-Fi device.

When the SSID/MAC address of the Wi-Fi device **218** is found in either the local memory of the HG **3 224** or in the Wi-Fi roaming datastore **230** (that is when the determination at block **1104** is “YES”), the HG **3 224** will retrieve the corresponding security credentials and class of service (COS) information associated with the Wi-Fi device **218**. When the combination is not present in its local memory or the Wi-Fi roaming datastore **230** (that is when the determination at block **1104** is “NO”), the foreign gateway HG **3 224** will respond to the probe request with a probe response message. (FIG. **11**, block **1106**.)

In this embodiment, the foreign gateway HG **3 224** does not respond to the presence of the SSID of the Wi-Fi device **218** in local memory or in the Wi-Fi roaming datastore **230** by sending a probe response frame as previously described. Rather, the HG **3 224** establishes a VPN tunnel **1006** to the home gateway of the Wi-Fi device **218**, such as the HG **1 220**. (FIG. **11**, block **1108**.) The HG **3 224** may query the network monitoring module **1002** via the Internet **210** or the network monitoring module **1002A** via the VPN tunnel **1006** as to whether or not the Wi-Fi device **218** is currently communicating with a foreign VAP. (FIG. **11**, block **1110**.) When the Wi-Fi device **218** is not currently communicating with a foreign VAP, (that is, when the determination at block **1110** is “NO”), the VAP operating on HG **3 224** will respond to the probe request with a probe response message. (FIG. **11**, block **1106**.)

When the Wi-Fi device **218** is communicating with a foreign VAP (that is, when the determination at block **1110** is “YES”), the network monitoring module **1002** or the network monitoring module **1002A** (see, FIG. **10**) will communicate with HG **3 224** that the Wi-Fi device **218** is currently communicating with a foreign VAP. (FIG. **11**, block **1111**.) In this example, the Wi-Fi device **218** is currently communicating with the foreign VAP operating on the HG **2 222**. In response to this communication, the HG **3 224** will enter an idle ready state.

While in the idle ready state, the HG **3 224** may use the Internet **210** to provide signal quality, signal strength and other metrics of the HG **3 224** to the network monitoring module **1002** or may use the VPN tunnel **1006** to provide the same to the network monitoring module **1002A** (FIG. **11**, block **1112**.) The network monitoring module **1002** or **1002A** may store these metrics in memory **155** (see, FIG. **1**).

At a point in time, a decision is made whether it would be beneficial for the Wi-Fi device **218** to cease communicating with the current foreign VAP (in this example, HG **2 222**) and

to communicate with a different foreign VAP (in this example, HG **3 224**). (FIG. **9**, Blocks **902** and **904** and FIG. **11**, Block **1114**.) In this example, this determination may be made by the network monitoring module **1002** or the network monitoring module **1002A**.

When the decision is that the Wi-Fi device **218** should continue to communicate with its current access point, (that is, when the determination at block **1114** is “NO”), the HG **3 224** will remain in the idle ready state and will periodically communicate the signal quality, signal strength and other metrics to the network monitoring module **1002** or the network monitoring module **1002A**. When the determination is made that the Wi-Fi device **218** should communicate with a different AP, the network monitoring module **1002** or the network monitoring module **1002A** sends details of the configuration of the access point with which Wi-Fi device **218** is currently communicating to the new access point. (FIG. **9**, Block **906** and FIG. **11**, Block **1114**.) In this example, an instruction would be issued to the HG **3 224** (the new access point) to instantiate a new VAP with the same SSID, security credentials, MAC address, and state as that of the HG **2 222** (the current access point). (FIG. **11**, block **1116**.) This instruction may be issued by the network monitoring module **1002** or the network monitoring module **1002A**. The implementation of these instructions results in the cloning of the access point operating on the HG **2 222** onto the platform of HG **3 224**.

The HG **3 224** communicates with the network monitoring module **1002** or the network monitoring module **1002A** that the instructions have been implemented. (FIG. **11**, block **1118**.) Data transmissions from the Wi-Fi device **218** are subsequently received and processed by the HG **3 224**. (FIG. **11**, block **1120**.) The VAP operating on the HG **2 222** and the VPN between the HG **1 220** and the HG **2 222** are torn down.

In an embodiment, the VAP operating on the HG **2 222** and the VPN between the HG **1 220** and the HG **2 222** are not torn down immediately. Rather, both the VAPs operating on HG **2 222** and HG **3 224** remain operational along with the two VPNs that connect HG **2 222** and HG **3 224** to the HG **1 220**. This dual operational mode remains active until a determination is made that the connection between the Wi-Fi device **218** and the new foreign VAP operating on HG **3 224** is operating at a satisfactory level. For example, the HG **1 220** may check packets received from the current foreign gateway HG **2 222** against packets received from the new foreign gateway HG **3 224** to determine that packets are being delivered by the new foreign gateway without errors or drops. Once this determination has been made by the home gateway HG **1 220**, the VPN from the HG **2 222** and the VAP operating on the HG **2 222** may be torn down.

From the perspective of the Wi-Fi device **218**, an established connection to an access point moves as the device moves. An established session continues on the new access point. (FIG. **11**, block **1122**.) The continued connection does not depend on the behaviors of different Wi-Fi devices in complying with the IEEE 802.11 standard for preauthentication and reassociation and permits roaming when Wi-Fi Protected Access (WPA) is implemented. Cloning of a virtual access point also allows for fast roaming in which hand-offs between home gateways may occur in less than 1/10th of a second which is sufficient time to allow timing-sensitive applications like video or VoIP to continue to function with little or no degradation in quality.

FIG. **6** is a block diagram illustrating a hybrid device according to an embodiment.

A hybrid device **620** may include a processor **601** coupled to an internal memory **602**, to a display **603** and to a SIMM **621** or similar removable memory unit. Additionally, the

hybrid device **620** may have a cellular antenna **604** for sending and receiving electromagnetic radiation that is connected to a cellular transceiver **605** coupled to the processor **601**. In some implementations, the transceiver **605** and portions of the processor **601** and memory **602** may be used for multi-network communications. The hybrid device **620** may also include a key pad **606** or miniature keyboard and menu selection buttons or rocker switches **607** for receiving user inputs. The hybrid device **620** may also include a GPS navigation device **600** coupled to the processor and used for determining the location coordinates of the hybrid device **620**. Additionally, the display **603** may be a touch-sensitive device that may be configured to receive user inputs.

A wireless transceiver **630** provides wireless communications via wireless antenna **632**. By way of illustration and not by way of limitation, the wireless transceiver may be compliant with 802.11x standards.

The processor **601** may be any programmable microprocessor, microcomputer or multiple processor chip or chips that can be configured by software instructions (applications) to perform a variety of functions, including the functions of the various embodiments described herein. In an embodiment, the hybrid device **620** may include multiple processors **601**, such as one processor dedicated to cellular and/or wireless communication functions and one processor dedicated to running other applications.

Typically, software applications may be stored in the internal memory **602** before they are accessed and loaded into the processor **601**. In an embodiment, the processor **601** may include or have access to an internal memory **602** sufficient to store the application software instructions. The memory may also include an operating system **622**. In an embodiment, the memory also includes a tunneling module **624** that provides additional functionality to the hybrid device **620** to permit the hybrid device **620** to create and tear down tunnels to a home gateway as previously described.

The internal memory of the processor may include a secure memory (not illustrated) which is not directly accessible by users or applications and that is capable of recording MDINs and SIMM IDs as described in the various embodiments. As part of the processor, such a secure memory may not be replaced or accessed without damaging or replacing the processor.

In an embodiment, additional memory chips (e.g., a Secure Data (SD) card) may be plugged into the hybrid device **620** and coupled to the processor **601**. In an embodiment, the tunneling module **624** may be provided on an SD card or other external memory device to add the tunneling functionality to an existing mobile device, thereby converting the mobile device to a hybrid device.

Additionally, the internal memory **602** may be a volatile or nonvolatile memory, such as flash memory, or a mixture of both. For the purposes of this description, a general reference to memory refers to all memory accessible by the processor **601**, including internal memory **602**, removable memory plugged into the computing device, and memory within the processor **601** itself, including the secure memory.

The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art, the order of steps in the foregoing embodiments may be performed in any order. Further, words such as “thereafter,” “then,” “next,” etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods.

As previously described, the subscriber may interact with the various servers and network components using a variety of the computing devices, including a personal computer. By way of illustration, the functional components of a computing device **760** are illustrated in FIG. 7. Such a computing device **760** typically includes a processor **761** coupled to volatile memory **762** and a large capacity nonvolatile memory, such as a disk drive **763**. The computing device **760** may also include a floppy disc drive **764** and a compact disc (CD) drive **765** coupled to the processor **761**. Typically the computing device **760** will also include a pointing device such as a mouse **767**, a user input device such as a keyboard **768** and a display **769**. The computing device **760** may also include a number of connector ports **766** coupled to the processor **761** for establishing data connections or network connections or for receiving external memory devices, such as a USB or FireWire® connector sockets. In a notebook configuration, the computer housing includes the pointing device **767**, keyboard **768** and the display **769** as is well known in the computer arts.

While the computing device **760** is illustrated as using a desktop form factor, the illustrated form is not meant to be limiting. For example, some or all of the components of computing device **760** may be implemented as a desktop computer, a laptop computer, a mini-computer, or a personal data assistant.

A number of the embodiments described above may also be implemented with any of a variety of computing devices, such as the server device **800** illustrated in FIG. 8. Such a server device **800** typically includes a processor **801** coupled to volatile memory **802** and a large capacity nonvolatile memory, such as a disk drive **803**. The server device **800** may also include a floppy disc drive and/or a compact disc (CD) drive **806** coupled to the processor **801**. The server device **800** may also include network access ports **804** coupled to the processor **801** for establishing data connections with network circuits **805** over a variety of wired and wireless networks using a variety of protocols.

The foregoing method descriptions and the process flow diagrams are provided merely as illustrative examples and are not intended to require or imply that the blocks of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art the order of blocks in the foregoing embodiments may be performed in any order. Words such as “thereafter,” “then,” “next,” etc. are not intended to limit the order of the blocks; these words are simply used to guide the reader through the description of the methods. Further, any reference to claim elements in the singular, for example, using the articles “a,” “an,” or “the,” is not to be construed as limiting the element to the singular.

The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention. Functionality of various logical blocks may be performed by other logical blocks or circuits. Additionally, functionality of various logical blocks may be performed by additional logical blocks or circuits that are not separately illustrated.

The hardware used to implement the various illustrative logics, logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Alternatively, some blocks or methods may be performed by circuitry that is specific to a given function.

In one or more exemplary aspects, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. The blocks of a method or algorithm disclosed herein may be embodied in a processor-executable software module, which may reside on a computer-readable medium. Computer-readable media include both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such computer-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that may be used to carry or store desired program code in the form of instructions or data structures and that may be accessed by a computer. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above should also be included within the scope of computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a machine readable medium and/or computer-readable medium, which may be incorporated into a computer program product.

The preceding description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the following claims and the principles and novel features disclosed herein.

What is claimed is:

**1.** A network monitoring device comprising:

a memory; and  
 a processor coupled to the memory, wherein the processor is configured with processor-executable instructions to perform operations comprising:  
 receiving via a network transition event information;  
 determining to transition communications between a Wi-Fi device and a first virtual access point (VAP) to another VAP based on the transition event information;  
 selecting a second VAP to which to transition the communications from one or more other VAPs;  
 providing an SSID and a security configuration information of the first VAP to the second VAP via the network;  
 directing the second VAP to instantiate the SSID and the security configuration information of the first VAP, wherein a network monitoring device establishes a link with the second VAP when the Wi-Fi device is associated with the first VAP, and  
 wherein the network monitoring device receives metrics from the second VAP when the Wi-Fi device is associated with the first VAP; and  
 tearing down the first VAP in response to determining that communications from the second VAP exceed a measure of performance.

**2.** The network monitoring device of claim **1**, wherein the transition event information comprises at least one of a measure of a signal strength or a signal quality of the first VAP is below a first threshold, a measure of signal strength or a signal quality of at least one of the one more other VAPs is above a second threshold, a measure of bandwidth utilization of the first VAP is above a third threshold, a measure of bandwidth utilization of at least one of the one more other VAPs is below a fourth threshold, a second Wi-Fi device needs to transition to the first VAP, and the Wi-Fi device is predicted to be moving out of range of the first VAP and into range of at least one of the one more other VAPs.

**3.** The network monitoring device of claim **1**, wherein the operation of selecting a second VAP to which to transition the communications from the one more other VAPs comprises:  
 receiving metrics from one or more other VAPs;  
 applying a rule to one or more of the metrics of the one or more other VAPs to select the second VAP from the one or more other VAPs.

**4.** The network monitoring device of claim **3**, wherein the metrics comprise at least one of a proximity of the Wi-Fi device to each of the one or more other VAPs, a change in the proximity of the Wi-Fi device to each of the one or more other VAPs, a signal characteristic of each of the one or more other VAPs, a channel availability of each of the one or more other VAPs, and an estimate of a future state of to each of the one or more other VAPs.

**5.** The network monitoring device of claim **1**, wherein the process of providing the SSID and the security configuration information of the first VAP to the second VAP via the network further comprises providing network address translation (NAT) information of the first VAP to the second VAP.

**6.** A system for transitioning a connection between access points, the system comprising:

a Wi-Fi device;  
 a network monitoring device; and  
 one or more virtual access points (VAPs), wherein each of the one or more VAPs is configured to perform operations comprising:  
 receiving a probe message from the Wi-Fi device, wherein the probe message comprises an SSID and a MAC address of the Wi-Fi device;

21

determining whether the Wi-Fi device is known to the VAP from the SSID and the MAC address of the Wi-Fi device; establishing a link to the network monitoring device when the Wi-Fi device is known to the VAP; determining via the link whether the Wi-Fi device is associated with a first VAP using the SSID, the MAC address of the Wi-Fi device and a security configuration information of the first VAP; and providing the network monitoring device metrics of the VAP when the Wi-Fi device is associated with the first VAP; wherein the network monitoring device is configured to perform operations comprising:

- receiving via a network transition event information;
- determining to transition communications between a Wi-Fi device and the first VAP to one of the one or more VAPs using the transition event information;
- selecting a second VAP from among the one or more VAPs to which to transition the communications from the first VAP;
- providing the SSID and the security configuration information of the first VAP to the second VAP via the network; and
- directing the second VAP to instantiate the SSID and the security configuration information of the first VAP, wherein communications are established between the Wi-Fi device and the second VAP using the SSID, the MAC address of the Wi-Fi device and the security configuration information of the first VAP, and wherein the first and second VAPs communicate with a home gateway and wherein the home gateway is configured to perform operations comprising tearing down the first VAP when the home gateway determines that communications from the second VAP exceed a measure of performance.

7. The system of claim 6, wherein the transition event information comprises at least one of a measure of a signal strength or a signal quality of the first VAP is below a first threshold, a measure of signal strength or a signal quality of at least one of the one more VAPs is above a second threshold, a measure of bandwidth utilization of the first VAP is above a third threshold, a measure of bandwidth utilization of at least one of the one more VAPs is below a fourth threshold, a second Wi-Fi device needs to transition to the first VAP, and the Wi-Fi device is predicted to be moving out of range of the first VAP and into range of at least one of the one more VAPs.

8. The system of claim 6, wherein the operation determining to transition communications between a Wi-Fi device and the first VAP to the second VAP based on the transition event information comprises:

- receiving metrics from the one or more VAPs;
- applying a rule to one or more of the metrics of the one or more VAPs to select the second VAP from among the one or more VAPs.

9. The system of claim 8, wherein the metrics comprise at least one of a proximity of the Wi-Fi device to each of the one or more VAPs, a change in the proximity of the Wi-Fi device to each of the one or more VAPs, a signal characteristic of each of the one or more VAPs, a channel availability of each of the one or more VAPs, and an estimate of a future state of to each of the one or more VAPs.

10. The system of claim 6, wherein the process of providing the SSID and the security configuration information of the first VAP to the second VAP via the network further comprises providing network address translation (NAT) information of the first VAP to the second VAP.

22

11. The system of claim 6, wherein the Wi-Fi device comprises at least one of a laptop computer, a notebook computer, a PDA, a VoIP phone and a dual network Wi-Fi phone.

12. The system of claim 6, wherein the first and second VAPs communicate with the Wi-Fi device via a communication protocol selected from the group consisting of IEEE 802.11(a), 802.11(b), 802.11(g), and 802.11(n).

13. A method for transitioning a communication in a network, the method comprising:

- receiving by a network monitoring device transition event information;

- determining by the network monitoring device to transition communications between a Wi-Fi device and a first virtual access point (VAP) to a another VAP based on the transition event information;

- selecting by the monitoring device a second VAP to which to transition the communications from one or more other VAPs;

- providing by the monitoring device an SSID and the security configuration information of the first VAP to the second VAP via the network;

- directing by the network monitoring device the second VAP to instantiate the SSID and the security configuration information of the first VAP,

- wherein the network monitoring device and the second VAP establish a link when the Wi-Fi device is known to the second VAP, and

- wherein the network monitoring device receives metrics from the second VAP when the Wi-Fi device is associated with the first VAP; and

- tearing down by the network monitoring device the first VAP in response to determining that communications from the second VAP exceed a measure of performance.

14. The method of claim 13, wherein the transition event information comprises at least one of a measure of a signal strength or a signal quality of the first VAP is below a first threshold, a measure of signal strength or a signal quality of at least one of the one more other VAPs is above a second threshold, a measure of bandwidth utilization of the first VAP is above a third threshold, a measure of bandwidth utilization of at least one of the one more other VAPs is below a fourth threshold, a second Wi-Fi device needs to transition to the first VAP, and the Wi-Fi device is predicted to be moving out of range of the first VAP and into range of at least one of the one more other VAPs.

15. The method of claim 13, wherein selecting by the monitoring device a second VAP to which to transition the communications from one or more other VAPs comprises:

- receiving metrics from one or more other VAPs; and
- applying a rule to one or more of the metrics of the one or more other VAPs to select the second VAP from the one or more other VAPs.

16. The method of claim 15, wherein the metrics comprise at least one of a proximity of the Wi-Fi device to each of the one or more other VAPs, a change in the proximity of the Wi-Fi device to each of the one or more other VAPs, a signal characteristic of each of the one or more other VAPs, a channel availability of each of the one or more other VAPs, and an estimate of a future state of to each of the one or more other VAP.

17. The method of claim 13, wherein providing the SSID and the security configuration information of the first VAP to the second VAP via the network further comprises providing network address translation (NAT) information of the first VAP to the second VAP.

23

18. A method for transitioning a communication in a network, the method comprising:

receiving by one or more virtual access points (VAPs) a probe message from a Wi-Fi device, wherein the probe message comprises an SSID and a MAC address of the Wi-Fi device;

determining by each of the one or more VAPs whether the Wi-Fi device is known to the VAP from the SSID and the MAC address of the Wi-Fi device;

establishing by each of the one or more VAPs a link to a network monitoring device when the Wi-Fi device is known to the VAP;

determining by each of the one or more VAPs via the link whether the Wi-Fi device is associated with a first VAP using the SSID, the MAC address of the Wi-Fi device and a security configuration information of the first VAP;

providing by each of the one or more VAPs the network monitoring device metrics of the VAP when the Wi-Fi device is associated with the first VAP;

receiving by the network monitoring device transition event information;

determining by the network monitoring device to transition communications between a Wi-Fi device and the first VAP to a second VAP selected from the one or more VAPs using the transition event information;

selecting a second VAP from among the one or more VAPs to which to transition the communications from the first VAP;

providing the SSID and the security configuration information of the first VAP to the second VAP; and

directing the second VAP to instantiate the SSID and the security configuration information of the first VAP,

wherein communications are established between the Wi-Fi device and the second VAP using the SSID, the MAC address of the Wi-Fi device and the security configuration information of the first VAP, and

wherein the first and second VAPs communicate with a home gateway and wherein the home gateway is configured to perform operations comprising tearing down the

24

first VAP when the home gateway determines that communications from the second VAP exceed a measure of performance.

19. The method of claim 18, wherein the transition event information comprises at least one of a measure of a signal strength or a signal quality of the first VAP is below a first threshold, a measure of signal strength or a signal quality of at least one of the one more VAPs is above a second threshold, a measure of bandwidth utilization of the first VAP is above a third threshold, a measure of bandwidth utilization of at least one of the one more VAPs is below a fourth threshold, a second Wi-Fi device needs to transition to the first VAP, and the Wi-Fi device is predicted to be moving out of range of the first VAP and into range of at least one of the one more VAPs.

20. The method of claim 18, wherein determining to transition communications between a Wi-Fi device and the first VAP to the a second VAP comprises:

receiving metrics from the one or more VAPs; and  
applying a rule to one or more of the metrics of the one or more VAPs to select the second VAP from among the one or more VAPs.

21. The method of claim 20, wherein the metrics comprise at least one of a proximity of the Wi-Fi device to each of the one or more VAPs, a change in the proximity of the Wi-Fi device to each of the one or more VAPs, a signal characteristic of each of the one or more VAPs, a channel availability of each of the one or more VAPs, and an estimate of a future state of to each of the one or more VAP.

22. The method of claim 18, wherein providing the SSID and the security configuration information of the first VAP to the second VAP via the network further comprises providing network address translation (NAT) information of the first VAP to the second VAP.

23. The system of claim 18, wherein the Wi-Fi device is selected from the group consisting of a laptop computer, a notebook computer, a PDA, a VoIP phone and a dual network Wi-Fi phone.

24. The system of claim 18, wherein the first and second VAPs communicate with the Wi-Fi device via a communication protocol selected from the group consisting of IEEE 802.11(a), 802.11(b), 802.11(g), and 802.11(n).

\* \* \* \* \*