

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number
WO 01/12336 A1

(51) International Patent Classification⁷:

B05B 5/16

(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).

(21) International Application Number: PCT/US00/22546

(22) International Filing Date: 17 August 2000 (17.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/377,333 18 August 1999 (18.08.1999) US

(71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors: GAW, Chinto, Benjamin; 2264 Regis Court, Cincinnati, OH 45244 (US). HUANG, Chow-Chi; 8138 Glenridge Court, West Chester, OH 45069 (US). KHAN, Ayub, Ibrahim; 8705 Birchbark, Cincinnati, OH 45249 (US). LEPPLA, Jeffrey, Keith; 106 Upnor Road, Baltimore, MD 21212 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— *With international search report.*

[Continued on next page]

(54) Title: HAND-HELD ELECTROSTATIC SPRAYER APPARATUS



WO 01/12336 A1

(57) Abstract: An electrostatic spraying device which is designed to be portable, hand-held, self-contained and battery (15) operated, with a disposable cartridge (31). The electrostatic spraying device is configured to provide a precise essentially constant flow rate of a product being applied, to provide uniformity and ease of application of the product, as well as to conserve product usage.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

HAND-HELD ELECTROSTATIC SPRAYER APPARATUS

BACKGROUND OF THE INVENTION1. Field of the Invention

5 This invention relates to electrostatic spraying apparatus, and more specifically to electrostatic spraying apparatus for spraying cosmetic products.

2. Background Information

10 Traditionally most skin care or cosmetic products, such as lotions, perfumes, and make-up, for example, have been applied by a limited number of methods. For example, frequently they are simply applied by the hand of the user, who would spread or rub the product onto the skin with the fingers or with the aid of an application pad. These products are also frequently sold in pump sprays or pre-pressurized aerosol containers, so as to have the product atomized and sprayed with the aid of a propellant gas.

15 More recently, electrostatic spraying devices have been developed for the application of personal care products, such as skin care and cosmetic products. However, many of these more recent apparatus can still be bulky and/or require bench top equipment and external electrical wiring, which can make them cumbersome or hard to use.

20 Typically, the known application methods and apparatus have a number of drawbacks. For example, frequently these methods and devices are unable to deliver a desired target product flow rate with great accuracy and precision, thus resulting in uneven coverage and wasted product. These drawbacks can be particularly troublesome when applying cosmetics, such as foundation, for example. Applying too much foundation in an uneven manner can result in both excessive wasted amounts of potentially expensive cosmetics, as well as an unsatisfactory and unattractive final appearance of the skin to which the foundation is applied. For example, when 25 all the skin is covered the natural skin tones cannot show through, and the user can feel like she is wearing a mask. Consequently, known application processes and products frequently make it difficult to adequately conceal skin flaws and yet create a finished "look" which is both natural in appearance and long lasting.

30 Objects of the Invention:

An object of the present invention is to create a hand-held, self-contained electrostatic spraying device which is easy to use.

35 Another object of the present invention is to create an electrostatic spraying device that provides a precise essentially constant flow rate of product, to provide uniformity and ease of application, as well as to conserve product usage.

Another object of the present invention is to provide a disposable cartridge to be used in the electrostatic spraying device, which disposable cartridge is configured to hold a supply of product suitable for electrostatic spraying, and is easy and convenient to use.

Another object of the present invention is to create an electrostatic spraying device that 5 permits the application of a cosmetic foundation product in substantially uniformly spaced droplets so as to create a desirable appearance or "look" for foundation users, such that the foundation conceals skin flaws, yet appears natural.

Another object of the present invention is to create a hand-held, self-contained electrostatic spraying device which is easy to use which eliminates the need for bench top 10 equipment and external electrical wiring.

Summary of the Invention:

These objects can be achieved by an electrostatic spraying device which is designed to be a hand-held, self-contained, battery operated electrostatic spraying device, with a disposable cartridge.

15 The electrostatic spraying device can comprise a housing configured to be held by the hand of a user, a disposable cartridge configured to contain a supply of product, such as a cosmetic product, and a nozzle for spraying the product onto the skin of the recipient. An electrode for electrostatically charging the product can be disposed to charge the product prior to its dispersal. The device can also be configured for moving the product from the supply of 20 product, past the electrode, and to a dispersal point. A self-contained power supply arrangement can also be disposed within the housing to provide electrical power for the device.

25 The electrostatic spraying device is preferably designed in size and weight to be easily held and operated by the hand of the user. Further, the device is preferably self-contained such that essentially all of necessary components, such as the product supply and power supply, can be contained within the housing of the device. Therefore, preferably no external, potentially bulky or cumbersome, sources for product or power are required. This permits the electrostatic spraying device to be portable, since it can be used in virtually any location, and can be easily transported by the user from one location to another.

30 The housing of the device can include a gripping area substantially contoured to the shape of a user's hand. This gripping area can be contoured such that the device can be easily used by an individual applying product to him- or herself, or by an individual applying product to another person, such as in a salon setting, for example.

35 In at least one preferred embodiment the disposable cartridge can contain a reservoir configured to contain the supply of product to be electrostatically sprayed. The disposable cartridge can be designed to be removed by the user from the electrostatic spraying device, and

discarded upon depletion of the product therein. A new cartridge can then be inserted into the device to refill the product supply.

In one embodiment, the nozzle from which the product is dispersed can also be a part of the disposable cartridge. By having the nozzle as part of the disposable cartridge, a new clean 5 nozzle is provided every time the cartridge is replaced, thereby resulting in less clogging of the nozzle, and thus necessitating less or no cleaning of the nozzle by the user. The electrode which charges the product can also be part of the disposable cartridge.

The disposable cartridge can also include an insulator for insulating the supply of product from electrostatic charge. In one embodiment, the nozzle, the electrode and the insulator can 10 together forming a single integrated part. This single part can be formed, for example, by two shot molding.

The electrostatic spraying device can also have a motor arrangement having a speed in the range 1.1 to 6.6 revolutions per minute. In one embodiment of the electrostatic spraying device, the device can have two speed settings, thus, for example, providing a product dispensing 15 rate from about 0.05 milliliters of product per minute to about 0.5 milliliters of product per minute.

In one embodiment, apparatus for moving the product from the product supply to a point of dispersal can include a motor and a gearbox, with a driver configured to engage with an actuator on the disposable cartridge. The cartridge can have a piston arrangement slidably 20 mounted within its casing, connected to the actuator, wherein upon actuation of the motor, a piston is configured to pressurize the product in the casing and thereby move the product from the casing, past the electrode, into the nozzle, and then out of the electrostatic spraying device. In one embodiment, the piston can be connected to a piston rod, wherein the piston rod comprises a threaded portion having a pitch thread from about 0.016 inch to about 0.025 inch.

25 **Brief Description of the Drawing:**

The preferred embodiments will be discussed below with reference to the following drawings:

Figure 1 shows a cross-sectional view of one embodiment of the electrostatic spraying device;

30 Figure 1A, shows a split front view of the same embodiment shown in Figure 1;

Figure 2A shows a perspective view of the exterior of the embodiment shown in Figure 1 with the cap removed;

Figure 2B shows the same embodiment as Figure 2A, with the cap fitted on the housing;

35 Figure 3A shows an expanded view of one embodiment of the cartridge and the motor/gearbox component;

- Figure 3B shows a perspective view of the same embodiment as shown in Figure 3A;
- Figure 4 is a schematic of a possible arrangement for a controller circuit of the high-voltage power supply;
- 5 Figure 5 is a schematic of a possible arrangement for the spraying device circuit;
- Figure 6 shows a cross-sectional view of one embodiment of the cartridge;
- Figure 7 shows a cross-sectional view of the nozzle-end of one embodiment of the cartridge;
- Figure 8 shows a cross-sectional view of another embodiment of the electrostatic spraying device;
- 10 Figure 9 is a schematic of another possible arrangement for the spraying device circuitry;
- Figure 10 shows a perspective view of the exterior of the embodiment shown in Figure 8;
- Figure 11 shows a schematic for a possible circuit arrangement for at least one embodiment of the electrostatic spraying device;
- Figure 12A shows a top view of one embodiment of the insulator;
- 15 Figure 12B and 12C show cross-sectional views of the insulator embodiment shown in Figure 12A;
- Figure 12D shows a perspective view of the insulator embodiment shown in Figure 12A;
- Figures 13A shows a top view of another embodiment of the insulator;
- Figure 13B shows a cross-sectional view of the insulator embodiment shown in Figure 13A;
- 20 Figure 14A shows a top view of one embodiment of the high-voltage contact;
- Figures 14B and 14C show cross-sectional views of the same embodiment of the high-voltage contact as shown in Figure 14A;
- Figure 14D shows a perspective view of the high-voltage contact shown in Figure 14A;
- 25 Figure 15 shows a schematic of a wiring diagram for one embodiment of the electrostatic spraying device;
- Figure 16A shows a side view of a possible embodiment of a stand for the electrostatic spraying device with the device therein;
- Figure 16B shows a perspective view of the same stand and device shown in Figure 16A;
- 30 Figure 17A shows a side view of another embodiment of the electrode having an annular contact;
- Figure 17B shows a front view of the electrode shown in Figure 17A;
- Figure 17C shows a top view of the electrode shown in 17A;
- Figure 17D shows a perspective view of the electrode shown in Figure 17A;

Figures 18A and 18B show essentially the same embodiment of the present invention as shown in Figure 8, with Figure 18B showing an enlarged view of a contact area;

Figure 19A shows another perspective view of the same or similar contact area as shown in Figure 18B; and

5 Figure 19B shows a simplified view of the same area shown in Figure 19A.

Description of the Preferred Embodiments:

Figures 1 and 1A show a preferred embodiment of an electrostatic spraying device. In this embodiment the device is designed to be a hand-held, self-contained spraying device, with a disposable cartridge

10 In brief, Figure 1 shows a gearbox/motor component 14 which can be fixed onto a left or first housing 17. This component preferably comprises a precision motor 14a connected to a gearbox 14b. The motor/gearbox 14 can be affixed into place by either mechanical or adhesive means. Below the motor/gearbox 14 can be positioned a power supply, for example, a battery 15 is shown. Also affixed to the left housing 17 is a high-voltage power supply 1 used for charging 15 an electrode 3 through a high voltage contact 2, and a high voltage power supply controller circuit 18. Figure 1 also shows an "on-off" or apply switch 8 disposed substantially on the top of the device with a motor speed selector switch 9 adjacent thereto. A disposable cartridge 31 has been inserted into the device, such that an actuator 11 of the cartridge 31, is engaged with a driver 13 attached to the motor/gearbox component 14. Additional details of the shown components are set 20 out below. While Figure 1 illustrates the internal components attached to the left housing 17, it is also possible to attach the components to a second or right housing 20.

Figures 2A and 2B show one possible embodiment for the housing of the inventive device. As shown, the device can have a three part housing, including a second or right housing 20, the first or left housing 17, as discussed above, and a cap portion 5, each of which can be 25 injection molded. The housing is designed to allow an easy essentially vertical assembly of the internal component into the second housing 17. The first housing 20 can then be fastened to the second housing 17 with three screws 41 which are preferably formed from plastic. Once assembled, the two housing halves 17, 20, together form an insert-channel 22 to permit the easy 30 insertion of the disposable cartridge 31 by a user. Once the cartridge 31 is in place, the cap 5 can be snapped onto the remainder of the housing. The two housing halves 17, 20 are also designed to form individual openings 40 for the tip of a nozzle 4, the "on-off" or apply switch 8, and the speed selector switch 9 (see Figure 1). This apply switch or button 8 can contain an LED indicator which indicates when the button or switch 8 is activated. One example of switch 8 could be activated, for example, by depressing. Further, a grounding circuit can be attached to, or

adjacent, the apply switch 8, thereby grounding the user when the housing is grasped for activation.

To fit the cap 5 onto the rest of the housing, a circular, or curved, hook 23 on the cap 5 is first engaged with a groove 24 on the left housing 17, at about a 10-20 degree angle. The cap 5 5 can then be rotated down until resilient snaps 25 are deflected inward allowing them to pass over corresponding mating posts 26 on the housing, and then return to their original position. This snap-and-post arrangement secures the cap 5 tightly to the housing. The cap 5 also has a front surface 27, on a vertical rib, which is disposed to press a safety switch 7 once the cap 5 is installed 10 on the housing, thereby completing the electrical circuit needed to operate the device. This safety switch 7 thereby substantially prevents the accidental shocking of the user when the cap 5 is removed because the electrical circuit is broken. To essentially prevent the cap 5 from dislodging or sliding out under pressure, a back surface 28, of this same vertical rib is disposed to simultaneously press against a protrusion 29 on the housing, once the cap 5 is snapped into place. Further, the cap 5 also has horizontal ribs 30 which serve to hold-down the disposable cartridge 15 31 during operation of the device.

Once assembled, the housing is ergonomically designed to be easily gripped by the hand of a user. The embodiment shown in Figures 2A and 2B is substantially "shoe-shaped" with a narrowed center area 80 contoured to be gripped by the hand. This gripping area basically extends up and around the device such that the device can be gripped about the middle and the thumb or index finger can be conveniently and comfortably located on the apply switch 8. The housing is designed to permit the user of the device to comfortably grip the device in a variety of ways, thereby allowing the user to either apply the product to themselves or to a different recipient of the product. Therefore, the inventive electrostatic spraying device can be easily used both at home or in a salon setting. For example, one way of gripping the device can be gripping 20 around the middle with the fingers pointing downward and wrapping around the bottom, allowing the thumb to rest on the apply switch 8. In this position the product could be easily sprayed by the user on themselves or another individual. For self application, the device can also be gripped with the nozzle 4 facing the user, and with the user's thumb being wrapped around the bottom of the gripping area 80, and the remainder of the hand being placed on top of the device, with one 25 finger on the apply button 8. The light weight and balance of the device also allows these alternative grips. Additionally, the gripping area 80 also serves the function of positioning the hand of the user a substantial distance away from the nozzle 4, thereby substantially reducing or possibly preventing the attraction of the charged product to the hand of the user rather than to the desired area, namely, the grounded skin of the recipient. To accomplish this not only is the 30 gripping area 80 positioned a substantial distance from the nozzle 4, but it is also recessed on the 35

bottom portion of the device so as to allow the front of the device to also help block the hand from the nozzle 4.

Figures 3A and 3B show one embodiment of the motor/gearbox 14 (i.e., motor 14a and gearbox 14b) and one embodiment of the disposable cartridge 31. Figure 3A shows an expanded view of Figure 3B. The motor/gearbox component 14 has electrical contacts 67, including positive and negative terminals, at motor 14a end of the component. At the opposite end the driver 13 is fastened to a shaft 34 of gearbox 14b, for example, with a set screw 12 (see Figure 1). The driver 13 has a number of protruding fingers 32, for example, three, which can fit into matching recesses on the back 33 of an actuator 11, which actuator 11 can be part of the replaceable and disposable cartridge 31. The actuator 11 has internal threads 37 for passage of one end of a threaded shaft 21, and a snap bead 16 to snap into an open end of a casing or barrel 10 of the cartridge 31. The opposite end of the threaded shaft 21 can have a piston 6 affixed to it. The threaded shaft 21 can thereby connect the piston 6 with the actuator 11, such that the piston 6 can slide along an inner surface of the casing 10, toward a nozzle 4 of the cartridge 31, in response the turning of the actuator 11 by the motor/gearbox 14. This movement of the piston 6 can thus displace product from the cartridge 31. This positive displacement of the product can be driven, in at least one embodiment, by threaded shaft 21 having a pitch thread from about 0.016 inch to about 0.025 inch. The precision motor 14a and the gearbox 14b can have a reduction ratio of about 1024:1, and a speed in the range of about 1.1 to 6.6 revolutions per minute. In at least one embodiment the threaded shaft 21 can be formed by injection molding.

One preferred embodiment of the motor 14a is commercially available from Maxon Precision Motors, Inc., 838 Mitten Road, Burlingame, CA 94010 [Maxon DC motor RE Ø10 mm, precious metal brushes. 1.5 watt, model number 118399; (416)697-9614]. Likewise a preferred embodiment of the gear head or gearbox 14b is also available from Maxon Precision Motors, Inc. [Ø10mm, 0.1 Nm max. torque, 1024:1 reduction ratio, model number 110312].

This positive displacement arrangement results in a very precise uniform flow rate of product through the device and thus onto the recipient, thus permitting a substantially uniform application of the product. This can also result in a reduction in the amount of product needed to achieve the desired result. For example, in at least one embodiment, less than 0.5 grams of product can be used per application. Further, the speed selection switch 9 (discussed in more detail below) permits at least two constant flow rates. These flow rates can preferably be from about 0.05 milliliters of product per minute to about 0.5 milliliters of product per minute. Further, in at least one embodiment, the torque transmitted by the motor 14a and gearbox 14b, to the actuator 11, can be about 5 times the actual torque needed to dispense the product from the cartridge 31. This excess torque thereby essentially ensures a constant steady flow rate

throughout each, and during each, application of the product from the cartridge 31 regardless of any changes in tolerances which may occur.

To further explain, as seen in Figure 3A, the casing 10 provides an internal product chamber or reservoir 38 for containing the product to be sprayed. In at least one embodiment, 5 each disposable cartridge reservoir 38 can contain about 2 or 3 milliliters of product. The movement of the piston 6 pressurizes the reservoir 38, and thus delivers the product to the nozzle 4, which nozzle 4 is disposed on the opposite end of the disposable cartridge 31 from the actuator 11. Since this inventive cartridge 31 is essentially in the form of a novel syringe which is engaged and driven by a direct drive motor, the disclosed positive displacement mechanism can 10 deliver a target flow rate with great accuracy and precision.

As shown in Figure 3A, the electrode 3 can be disposed adjacent the nozzle 4. In at least one embodiment this electrode 3 can be an injection molded 40% carbon-fiber filled Acrylonitrile Butadiene Styrene(ABS) component. This 40% carbon-fiber filled Acrylonitrile Butadiene Styrene(ABS) is commercially available from RTP Company 580 East Front Street, Winona, MN 15 55987 [RTP 687 Acrylonitrile Butadiene Styrene (ABS) 40% Carbon Fiber PAN reinforced; (800) 433-4787]. In at least one embodiment, the carbon fibers could possibly be disposed substantially length-wise in the direction of flow of the current through the electrode.

The electrode 3 includes, or forms, two plug seals 35, one sealing against the casing 10 and the other sealing against the nozzle 4 (these seals 35 are discussed in more detail below). The 20 electrode 3 can also have an extension leg or legs 36 which can be designed to fit into a corresponding recess or receptacle on the left housing 17 of the spraying device. Extension leg 36 can thereby prevent the disposable cartridge 31 from rotating during operation. Extension leg 36 of the electrode 3 also can make contact with the high voltage contact 2 which can be located on the left housing 17 to permit the electrical charging of the electrode 3 by the high-voltage power 25 supply 1. In at least one embodiment of the invention, extension leg 36 can be in the form of a tab (as shown), in a different embodiment the extension leg 36 can be in the form of an annular rim 36a about the exterior of the casing 10 (see Figures 17A-17D).

The high voltage contact 2 can be made of a variety of materials, for example, conductive plastic or metal, such as copper. In at least one embodiment this high voltage contact 2 can be an 30 injection molded 40% carbon-fiber filled Acrylonitrile Butadiene Styrene(ABS) component. The carbon fiber can be disposed substantially lengthwise, in the direction of current flow in the contact. This 40% carbon-fiber filled Acrylonitrile Butadiene Styrene(ABS) is commercially available from RTP Company 580 East Front Street, Winona, MN 55987 [RTP 687 Acrylonitrile Butadiene Styrene (ABS) 40% Carbon Fiber PAN reinforced; (800) 433-4787].

The nozzle 4 provides an orifice 39 for the product, to thereby direct the flow of the product. The electrode 3 is disposed to charge the product that has been moved from the reservoir 38 into the orifice 39. Once the charged product exits orifice 39, droplets are formed by electrostatic repulsion as the charged fluid is dispersed.

5 Figure 4 shows a schematic of one possible embodiment of the controller circuit 18 (see Figure 1) for the high voltage power supply 1 used to charge the electrode 3. The high voltage power supply 1 can include a transformer, a high voltage assembly and the controller circuit 18. This controller circuit 18 can be configured to be essentially separate from the rest of the power supply 1. This controller 18 can generate AC pulses which can be controlled to be about 200 10 volts, peak to peak. This signal can then be stepped up to about 8,000 volts by the transformer and can then be nearly doubled in the high voltage assembly. The circuit topology can be that of a flyback transformer. This type of circuit can be used to generate low cost high voltage power supplies, wherein the underlying principle is to use the inductive spike that results when the current direction is switched in an inductor to generate a high voltage pulse.

15 The second portion of the circuit 18 can include the flyback transformer and a high voltage rectifier/doubler. The transformer can increase the approximate 200 volt input to approximately 8,000 volts. The transformer can have, for example, 40 turns on the primary coil and 2,500 turns on the secondary coil. The high voltage structure can have diodes D2 and D3 and capacitor C4 can be configured as a charge pump that nearly doubles the AC input voltage, 20 resulting in a output of about 14KV.

25 In at least one embodiment, to minimize electrical leakage and corona, the transformer and the high voltage structure can be encapsulated in epoxy. Further, in at least one embodiment a potentiometer can be used in place of resistor R3 to permit the final voltage output to be adjusted, and permit compensation for sub-nominal batteries. An additional resistor can also be added to limit the current output, for example, a 1 gigaohm (1 billion ohms) resistor can be used to limit the current output to approximately 10 microamp.

30 Figures 5 and 9 illustrate circuit diagrams of different arrangements for circuitry which may be used with at least one embodiment of the inventive electrostatic spraying device. The power supply 15 shown is a battery. In at least one preferred embodiment this power supply can be a user replaceable battery or batteries, for example, a standard "9V" battery. It is also within the scope of the present invention that this power supply could vary, for example, the power supply could be user-rechargeable cells, a non-user serviceable rechargeable power pack, or an external source (i.e. "line" supply).

35 In at least one embodiment the power supply 15 can be separated from the rest of the circuit by an "ON" switch 47. This switch 47 can provide the benefit of prolonging the active life

of a self-confined power supply 15 such as a battery, as well as potentially adding a margin of safety to a line-voltage power supply, wherein only when the "ON" Switch 47 is closed is voltage then supplied to the remainder of the circuit. One preferred embodiment for the switch 47 would be a toggle design, which would maintain its setting until its next actuation.

5 As explained above, a safety switch 7 can be included (see Figures 5 and 2A) which is actuated when the cap 5 is placed on the housing. This switch 7 is designed to prevent the accidental shocking of a user of the device by coming in contact with the high voltage contact 2. This switch preferably is of the "momentary" type such that it maintains a normally open position when it is not activated, and forms a closed circuit upon activation.

10 In Figure 5, the "on-off" or apply switch 8, which is depressed or turned to the "on" position by the user, depending on the type of switch employed, completes the power supply circuit, sending power to the drive motor 14a branch, the high voltage power supply 1 branch and the power on indicator 48 branch. Each branch can be in parallel to one another. The power-on indicator 48 can be an LED that emits light in the green range of the visible EM (electromagnetic) 15 spectrum. As shown in Figure 5, this indicator 48 can serve to indicate both that the product is being both charged by the electrode 3 and/or dispensed by the motor 14a.

In Figure 9 the circuitry arrangement is different, wherein the indicator 48 indicates when the "ON" switch 47 is actuated, thereby indicating that power is available to be sent to the other branches once the apply switch 8 is activated, and the circuit is completed. Since the shown 20 power-on indicator 48 is an LED an impedance 49, with a preferred current value of about 560 ohms, serves as a current-limiting device. This impedance 49 may be a separate component or may be integrated into an LED lamp assembly, or may be eliminated if a different type of power-on indicator 48 is used which does not require it.

The speed selector switch 9, allows the user to choose between a "high" speed and a 25 "low" speed for the dispensing of the product by the motor 14a. The high speed, for example, could provide a motor speed of about 6.6 RPM, and a product flow rate of about 0.5 ml/min. The low speed, for example, could provide a motor speed of about 1.1 RPM, and a product flow rate of about 0.05 ml/min.

A voltage regulator 19 controls the input voltage to the motor 14a. The nominal voltage 30 output from the voltage regulator can preferably be about 3.3 volts. To achieve the high speed, the speed selector switch 9 sends this full voltage directly to the motor. To achieve the low speed the speed selector switch sends this voltage through a voltage reducing device 50, for example, a Zener diode, which reduces the voltage supplied to the motor to preferably about 2.6 volts. This speed selector switch 9 could have a variety of forms, for example, it could be a toggle-type 35 switch.

In the arrangement shown in Figure 5, to permit the current to flow in only one direction a rectifier diode 51 is included. This rectifier diode 51 can prevent damage to the high voltage power supply from voltage being applied in the wrong direction and additionally prevent the high voltage power supply 1 from sending current to the drive motor 14a in the wrong direction. This 5 can occur when the high voltage supply 1 has a capacitor that stores charge and then releases it back through the circuit, which can cause the drive motor 14 to turn in the reverse direction. A rectifier diode 51 is not needed if the possibility of these types of adverse situations are eliminated in other ways.

10 The current output from the high voltage power supply 1 can be limited by a variety of mechanisms. For example, it can limit its own output or, as shown in Figures 5 and 9, a resistor 52 can be placed in series with the power supply 1 output. The resistor 52 can preferably have a value of 1,000,000,000 ohms (1 gigaohm).

15 To help avoid electrostatic shock to the user and to aid in the dispersal of the product, a ground contact 53 can establish a ground between the device circuits and the user. This ground can prevent the building-up of potential between the user and the device, which can result in an electrostatic shock to the device user. Further this ground can prevent charge from building-up on the skin of the user as the charged particles accumulate on the face of user, which charged particles on the skin could possibly repel additional product that is being applied to the same area. Therefore, when the user of the device is not the recipient of the product, such as in a salon 20 setting, it can be advantageous for the recipient to remain in constant or occasional contact with the user of the device. Preferably, this ground contact 53 is integrated into, and/or is substantially adjacent to, the apply switch 8, wherein the user cannot energize the high-voltage power supply without simultaneously grounding herself to the device. The apply switch 8 can be made of metal 25 and/or a conductive contact or a grounding electrode can be located next to the apply switch 8, for example.

Figure 6 shows one embodiment of the inventive disposable cartridge 31. These cartridges 31 are designed to contain multiple applications of product, and to be easily removed from the device, and disposed by the user, once the cartridge product supply is substantially depleted or is no longer desired. A new cartridge 31, containing the same or different product, 30 can then be easily inserted by the user into the device. Further, this type of inventive disposable cartridge 31 can have the additional benefit of having the spray nozzle 4 as a component of the cartridge 31 itself, rather than as part of the spraying device. This provides the user with a new clean, unclogged nozzle 4 each time a new cartridge 31 is installed into the device, thereby requiring less maintenance of the device, on the part of the user. However, it is also within the 35 scope of at least one embodiment of the present invention that these cartridges 31 could

potentially be designed such that the nozzle might be separate from, or part of, the device rather than part of the cartridge 31. Likewise, the electrode 3 could also be designed to be part of, or separate from, the device, rather than part of the cartridge 31. Further, it is also possible that the cartridges 31 could be designed to be refillable, rather than disposable.

5 As shown in Figure 6 and Figure 7, in at least one embodiment, an insulator 60 can be disposed within the nozzle 4. The nozzle 4 can have a tip 4a (see Figure 7). The insulator 60 can be substantially cylindrical in shape, with one end, disposed closest to the nozzle tip, having a conical tip portion 61. The opposite end of this insulator can have a substantially cylindrical portion 62, and a narrower substantially cylindrical portion 66 can be located between the two 10 end portions, such that an annular shaped ledge 63 is formed between the two substantially cylindrical portions 62, 66. On this ledge 63 the electrode 3, having a substantially annular body portion 3a can be positioned around the exterior surface of the insulator 60, with the electrode extension leg 36 extending therefrom. As shown in figure 7, the wider end 62 of the insulator 60, which wider end 62 slightly tapers, and a portion of the electrode body 3a can be inserted onto a 15 collar portion 10a of the casing 10 of the disposable cartridge 31. The exterior surface of the wider end 62 can serve as a plug, forming a plug seal 62a with the collar portion 10a. An annular rim on the electrode 3 as well as two substantially annular portions extending from this rim, serve as two plug seals 35, with one side forming a plug seal 35 sealing against a portion of the casing collar portion 10a, and the opposite side forming a second plug seal 35 sealing against a portion of 20 the nozzle 4.

A very narrow product flow pathway or channel 64 runs through the center of the insulator 60. Channel 64 has a wider-channel-portion 64a on the end closest to reservoir 38. This wider-channel-portion 64a has a "neckdown" section 64b connecting it to channel 64, thereby 25 preferably creating product turbulence at this point, as the product passes from the wider-channel-portion 64a to channel 64. The channel 64 serves to further restrict the flow of the product. Another channel or aperture 65 is disposed through the insulator 60, substantially transverse to channel 64. Aperture 65 serves to focus the charge from the electrode 3 through aperture 65 to the product as it moves past aperture 65, prior to the product being dispersed from the nozzle 4, thereby electrostatically charging the product. Aperture 65 is positioned within the insulator 60 at 30 a distance substantially closer to the tip 4a of the nozzle 4, than to the product supply in reservoir 38. In this manner, namely, by restricting the product flow through channel 64, and positioning aperture 65 closer to the nozzle tip 4a, the electrical charge from the electrode 3 that travels back to the product supply in reservoir 38 can be minimized.

In at least one embodiment the insulator 60 and the nozzle 4 can be made from Delrin, 35 which is commercially available from E.I. du Pont de Nemours and Company (Dupont), 1007

Market Street, Wilmington, DE 19898 [Delrin 500P (NC010, Medium Viscosity Acetal); (800) 441-7515]. The piston 6 can be made from a variety of materials, such as, high-density polyethylene(HDPE), commercially available from Dow Chemical Company, Midland, Michigan [High Density Polyethylene (HDPE), 30460M, Fluorine treated; 800-232-2436]; or from low-density polyethylene (LDPE), fluorine treated. The actuator 11, for example, can be formed from acrylonitrile butadiene styrene (ABS), or from 20% Calcium Filled Polypropylene (PP), which is commercially available from Ferro Corporation, 1000 Lakeside Avenue, Cleveland, OH 44114 [20% Calcium Filled Polypropylene (PP), High Gloss, GPP20YJ3395DK; (216) 641-8580]. Casing 10 can be formed from Barex 210, which is commercially available from BP Chemicals, Inc., 440 Warrensville Center Road, Cleveland, OH 44120 [Barex 210 Injection Grade, impact modified acrylonitrile-methyl acrylate copolymer; (216) 586-5847]. The housing 17, 20 and cap 5, can preferably be formed from Magnum 545 Acrylonitrile Butadiene Styrene (ABS), this can be purchased from Dow Chemical Company, Midland, Michigan [800-232-2436].

In one embodiment the nozzle, electrode and insulator can be formed as one integral part, formed for example by two shot molding. Preferably, the first plastic material molded can be white Delrin, and the second plastic material can preferably be the conductive ABS. Known multi-shot injection molding techniques provide the advantages of permitting multiple colors and/or materials to be sequentially injected in a single, continuous process, and thereby speed throughput, and minimize production and assembly operations. Multi-shot injection techniques can also result in a variety of benefits and cost savings, such as in machinery, labor and utilities, for example.

In one embodiment of the disposable cartridge 31, there can be a distance of about 0.5 inches between the product supply and the center of aperture 65, and about 0.25 inches from the center of aperture 65 to the very tip 4a of nozzle 4, thereby forming about a 2:1 distance ratio. A distance of about 0.170 inches can be between the center of aperture 65 and the extreme tip of the conical portion 61 of the insulator 60.

Figure 8 shows a cross-section of another embodiment of the electrostatic spraying device, wherein the same or similar components have been given the same reference numbers as the embodiment shown in Figure 1.

Figure 10 shows a perspective view of the exterior of the embodiment of the electrostatic spraying device shown in Figure 8. This housing has a sleeker design than the previously discussed embodiment. This embodiment has an additional housing component 5a, which is a removable cover allowing easy access to the battery, or batteries 15. The cap 5, for the insertion of the cartridge, in this embodiment attaches to the front portion of the housing, and has a release button 77 to aid in its removal. Additionally, a separate power-on indicator 48 is positioned on

the back of the device. The speed selector switch 9 can have 3 positions, for example, a high, low and power off position.

Figure 11 shows a schematic for another possible circuit arrangement for at least one embodiment of the electrostatic spraying device, including circuitry for the motor power supply and the high voltage power supply.

Figure 12A shows a top view of one possible embodiment of the insulator 60. Figures 12B and 12C show cross-sectional views of the embodiment shown in Figure 12A. Channel 64 has a diameter of about 0.03 inches in this embodiment. Channel 64 can preferably have a diameter of about 0.020 to 0.030 inches. A groove or pathway 78 can also be formed at the tip of the insulator 60 to thereby focus the charge from the electrode 3 through this groove 78 and to the product prior to its dispersal to nozzle tip 4a. Additionally, in this embodiment the wider-channel-portion 64a encompasses a substantially larger portion of the wider substantially cylindrical end 62 of the actuator 60. Figure 12D shows a perspective view of this same embodiment.

Figures 13A shows a top view and Figure 13B shows a cross-sectional view of another possible embodiment of the insulator 60. In this embodiment the insulator 60 contains the aperture 65 which, as discussed above, serves to focus the charge from the electrode 3 to the product as it passes aperture 65. Aperture 65 can preferably be about 0.020 to 0.030 inches in diameter.

Figure 14A shows a top view of one possible embodiment of the high-voltage contact 2, which contact 2 provides charge to the electrode 3, as discussed above. An end contact portion 72 makes electrical contact with the electrode 3 and electrical connection 71 connects the contact 2 to the high voltage power supply 1. This electrical connection 71 can be in the form of a spade connection, for example. Figures 14B and 14C show cross-sectional views of this same embodiment and Figure 14D shows a perspective view of this embodiment of the contact 2.

Figure 15 shows a schematic of a wiring diagram for one embodiment of the electrostatic spraying device.

As shown in Figures 16A and 16B, a stand 70 can also be provided. This stand 70 can be preferably made from plastic, and is designed to permit the nozzle end of the device to be inserted past a receiving or neck portion 73 with metal insert (not shown) of the stand 70, and into a base portion 74. This base portion 74 can be designed to rest upon a surface. The neck portion 73 can be configured to provide support to a bottom edge or surface 75 of the device. Not only can this stand provide a convenient resting or storage spot for the device, it will also allow any residual charge which may have built-up on the device and/or the product therein to dissipate out through the stand.

Figure 17A shows a side view of another possible embodiment of the electrode 3. In this embodiment of the electrode, the contact or extension leg can be in the form of an annular rim or protrusion 36a. This annular contact 36a can be configured to encircle the exterior surface of casing 10. The remainder of this electrode 3 can be designed substantially the same or similar to the previously described electrode embodiment which has the contact in the form of an extension leg 36. Figures 17B-17D show additional views of this embodiment of the electrode 3, wherein Figure 17B shows a front view of the electrode 3, Figure 17C shows a top view of the electrode 3 and Figure 17D shows a perspective view of the electrode 3.

Figures 18A and 18B show essentially the same embodiment of the present invention as shown in Figure 8, with Figure 18B showing an enlarged view of the contact area between the end contact portion 72 of the high voltage contact 2, and the extension leg 36 of the electrode 3.

Likewise, Figure 19A shows another perspective view of the contact area between the electrode 3 and the high voltage contact 2. Figure 19B shows a simplified view of this same area, showing the cartridge 31 with the extension leg 36 extending therefrom and in contact with the contact portion 72 of the high voltage contact 2.

The inventive device can be used to spray on a variety of products, including numerous personal care products, such as make-up, perfume, medical products, deodorants, etc. In particular, the inventive device is well-suited for the application of a topical product, especially a cosmetic foundation product to the skin of a recipient.

A preferred cosmetic product is a liquid foundation, and more preferably a multiphase (emulsion) composition that can be sprayed onto the recipient's skin with the electrostatic spraying device disclosed herein. This electrostatic spraying can provide the advantages of low product usage and small particle atomization, allowing the creation of an on-surface deposition of discrete dots of the foundation. That is to say, by electrostatically charging the product, tiny droplets of foundation each having essentially the same charge are formed. Because these droplets have like charges they repel one another and therefore disperse and preferably spray onto the skin as discrete dots, preferably of less than about 150 microns, more preferably less than about 100 microns, most preferably less than about 80 microns (e.g., less than about 30 microns) in average size. Because these dots are preferably non-continuous when deposited on the skin, these dots can camouflage skin imperfections and still allow natural skin tones to be revealed. Further, because the foundation product can be a multiphase formula foundation, one of the phases can possibly comprise a formula which can also permit the recipient's natural skin tones to show in the areas where that phase of the product is deposited on the skin. At the same time, due to the dispersal of the product in the form of non-continuous dots, less product is consumed as

compared to conventional techniques, such as a non-charged spray, or manually applied product, which might coalesce into a film or be applied as a film, over the skin.

Preferred multiphase, electrostatically sprayable topical compositions are described in commonly-assigned, concurrently-filed U.S. Patent Application Serial Nos. 60/149,566, entitled 5 "Electrostatically Sprayable Topical Compositions Having Insulating External Phase and Conductive Internal Phase", Attorney's Docket No. 7730P; U.S. Patent Application Serial Nos. 60/149,586, entitled "Discontinuous Films From Skin Care Compositions", Attorney's Docket No. 7729P; and U.S. Patent Application Serial Nos. 60/149,585, entitled "Wear Resistant Topical Compositions Having Improved Feel", Attorney's Docket No. 7732P, all of which were filed on 10 August 18, 1999 in the names of Thomas E Rabe, et al. Other preferred electrostatically sprayable topical compositions are described commonly-assigned, concurrently filed U.S. Patent Application Serial No. 60/149,565, entitled "Stable, Electrostatically Sprayable Topical Compositions", Attorney's Docket No. 7731P, filed August 18, 1999 in the names of Thomas E Rabe, et al. as well as in the aforementioned 7729P and 7732P applications. The disclosures of 15 each of these applications are hereby incorporated herein by reference.

Other suitable methods, examples, and related details for electrostatically spraying a product are described in the following U.S. patents, all of which are incorporated herein by reference:

U.S. Patent No. 4,549,243 issued October 22, 1985, entitled Electrostatic Spray 20 Apparatus with Capillary Feed of Liquid to the Spray Nozzle.

U.S. Patent No. 4,561,037 issued December 24, 1985, entitled Electrostatic Spraying.

U.S. Patent No. 4,663,639 issued December 5, 1987, entitled Printer.

U.S. Patent No. 5,121,884 issued December 16, 1999, entitled Electrostatic Spraying Device, Intended for use in Dispersing Materials Normally Dispersed by Aerosol Sprays.

25 U.S. Patent No. 5,932,011, issued August 3, 1999, entitled Electrostatic Spraying Devices with Hazardous Condition Warning System.

All of the patents, patent applications and publications recited herein are hereby incorporated by reference as if set forth in their entirety herein.

The invention as described hereinabove in the context of the preferred embodiments is not 30 to be taken as limited to all of the provided details thereof, since modifications and variations thereof may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. An electrostatic spraying device being configured and disposed to electrostatically charge and dispense a product from a supply to a point of dispersal, wherein said device comprises:

a reservoir configured to contain the supply of product;

a nozzle to disperse the product, said nozzle being disposed at the point of dispersal; and

a channel disposed between said reservoir and said nozzle, wherein said channel permits the electrostatic charging of the product upon said product moving within said channel.

2. An electrostatic spraying device having a disposable cartridge which is configured to contain a supply of product to be electrostatically sprayed, said device being configured and disposed to electrostatically charge and dispense the product from the supply to a point of dispersal, wherein said disposable cartridge comprises:

a reservoir configured to contain the supply of product;

a nozzle to disperse the product, said nozzle being disposed at the point of dispersal; and

a channel disposed between said reservoir and said nozzle, wherein said channel permits the electrostatic charging of the product upon said product moving within said channel.

3. The electrostatic spraying device according to Claim 1, further comprising:

a housing to provide outer shell support;

a power supply to provide electrical power; and

a positive displacement mechanism connected to said power supply to move the product from said supply to the point of dispersal.

4. The electrostatic spraying device according to Claim 1, further comprising an insulator, wherein said channel is disposed within said insulator.

5. The electrostatic spraying device according to Claim 4, further comprising an aperture within said insulator, said aperture permits the product to be electrostatically charged.

6. The electrostatic spraying device according to Claim 5, further comprising an electrode to receive electrical power from a power supply and deliver electrical power through said aperture to the product.

7. The electrostatic spraying device according to Claim 6, wherein a portion of said electrode is disposed between said reservoir and said nozzle.

8. The electrostatic spraying device according to Claim 7, wherein said portion of said electrode is disposed closer to said nozzle than to said reservoir.

9. The electrostatic spraying device according to Claim 6, wherein said electrode extends outwardly from a point of connection to said device.

10. The electrostatic spraying device according to Claim 6, wherein said nozzle, said electrode and said insulator together form a single integrated part.

11. The electrostatic spraying device according to Claim 6, wherein said electrode aligns said disposable cartridge within said electrostatic spraying device.




Fig. 1

2/20




Fig. 1A

3/20




Fig. 2A




Fig. 2B




Fig. 3A

5/20




Fig. 3B

6/20




Fig. 4

7/20




Fig. 5

8/20




Fig. 6





Fig. 7

9/20



10/20




Fig. 9

11/20




Fig. 10

12/20




Fig. 11

13/20




Fig. 12B





Fig. 12C




Fig. 12D

14/20




Fig. 13A








Fig. 13B

15/20



16/20




Fig. 15

17/20




Fig. 16B




Fig. 16A

18/20




Fig. 17A




Fig. 17B




Fig. 17C




Fig. 17D

19/20

Fig. 18A





Fig. 18B



20/20




Fig. 19A




Fig. 19B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/22546

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B05B5/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 18561 A (GREEN MICHAEL LESLIE ; PRENDERGAST MAURICE JOSEPH (GB); PROCTER & G) 7 May 1998 (1998-05-07) page 9, line 5 - line 6 page 10, line 26 - line 33	1,4-10
A	---	2,3
X	WO 96 40441 A (ICI PLC ; GREEN MICHAEL LESLIE (GB); NOAKES TIMOTHY JAMES (GB); PRE) 19 December 1996 (1996-12-19) page 12, line 1 - line 12 page 13, line 3 - line 6	1,4-10
A	-----	2,3

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 October 2000

Date of mailing of the international search report

23/10/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Juguet, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/22546

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
WO 9818561	A 07-05-1998	AU 4567297	A	22-05-1998
		CN 1235564	A	17-11-1999
		EP 0934122	A	11-08-1999
-----	-----	-----	-----	-----
WO 9640441	A 19-12-1996	AU 711793	B	21-10-1999
		AU 3525995	A	26-04-1996
		AU 723746	B	07-09-2000
		AU 5829496	A	30-12-1996
		BR 9509252	A	21-10-1997
		CA 2200181	A	11-04-1996
		CA 2222519	A	19-12-1996
		CN 1159773	A	17-09-1997
		CN 1192168	A	02-09-1998
		CZ 9701003	A	13-08-1997
		EP 0776253	A	04-06-1997
		EP 0837736	A	29-04-1998
		WO 9610459	A	11-04-1996
		HU 76948	A	28-01-1998
		JP 11510403	T	14-09-1999
		JP 10506324	T	23-06-1998
		NZ 292945	A	28-05-1999
		PL 319482	A	04-08-1997
		SK 42197	A	10-09-1997
		ZA 9604689	A	09-12-1996