

(21) (A1) **2,258,912**  
(86) 1998/05/12  
(87) 1998/11/19

(72) STANLEY, James Gregory, US

(71) AUTOMOTIVE SYSTEMS LABORATORY, INC., US


(51) Int.Cl. <sup>6</sup> B60R 21/32

(30) 1997/05/12 (60/046,233) US

(30) 1998/05/11 (075,584) US


(54) **SYSTEME DE PREDICTION DE LA TENSION D'UNE  
CEINTURE DE SECURITE COMPRENANT UN  
ACCELEROMETRE MONTE SUR LE CADRE DU SIEGE ET  
UN DETECTEUR DE MASSE**

(54) **SEAT BELT TENSION PREDICTION SYSTEM USING AN  
ACCELEROMETER MOUNTED TO THE SEAT FRAME AND  
A WEIGHT SENSOR**



(57) Un système et un procédé de prédition de la tension d'une ceinture de sécurité comprennent un accéléromètre (20) dont un signal de sortie réagit à une accélération verticale du véhicule, un détecteur de masse (30) dont un signal de sortie réagit à la force exercée par une masse située sur le siège, et un processeur (50) qui calcule la tension de la ceinture de sécurité. Le processeur est pourvu d'une pluralité d'entrées qui sont couplées de manière opérationnelle aux sorties de l'accéléromètre et du détecteur de masse. Une programmation appropriée

(57) A vehicle seat belt tension prediction system and method comprises an accelerometer (20) having an output signal responsive to vertical acceleration of the vehicle, a seat weight sensor (30) having an output signal responsive to the force exerted by a mass resting on the seat, and a processor means (50) for calculating seat belt tension. The processor is provided with a plurality of inputs operatively coupled to the accelerometer output and seat weight sensor output. Suitable programming is provided to instruct the processor (50) to calculate the



(21)(A1) **2,258,912**  
(86) 1998/05/12  
(87) 1998/11/19

est prévue pour donner ordre au processeur (50) de calculer la masse moyenne située sur le siège du véhicule et prédire la force qui devrait s'exercer sur le siège pour un niveau mesuré d'accélération verticale supposant une tension de ceinture nulle. Le processeur (50) compare ensuite la force réelle mesurée par le détecteur de masse (30) du siège à la force prédictive pour déterminer la tension de la ceinture de sécurité, ceci éliminant le matériel complexe se trouvant en contact physique avec le système de ceinture de sécurité.

average mass resting on the vehicle seat and predict the force that should be exerted on the seat for a measured level of vertical acceleration assuming zero belt tension. The processor (50) then compares the actual force measured by the seat weight sensor (30) with the predicted force to determine seat belt tension thereby obviating the necessity of complex hardware in physical contact with the seat belt system.


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>B60R 21/32</b>		A1	(11) International Publication Number: <b>WO 98/51546</b> (43) International Publication Date: 19 November 1998 (19.11.98)
(21) International Application Number: PCT/US98/09696			(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(22) International Filing Date: 12 May 1998 (12.05.98)			
(30) Priority Data: 60/046,233 12 May 1997 (12.05.97) US 09/075,584 11 May 1998 (11.05.98) US			<b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(71) Applicant: AUTOMOTIVE SYSTEMS LABORATORY, INC. [US/US]; Suite B-12, 27200 Haggerty Road, Farmington Hills, MI 48331 (US).			
(72) Inventor: STANLEY, James, Gregory; 21945 Daleview Drive, Novi, MI 48374 (US).			
(74) Agent: LYON, Lyman, R.; Lyon, P.C., Suite 207, 3883 Telegraph Road, Bloomfield Hills, MI 48302-1476 (US).			

(54) Title: SEAT BELT TENSION PREDICTION SYSTEM USING AN ACCELEROMETER MOUNTED TO THE SEAT FRAME AND A WEIGHT SENSOR



(57) Abstract

A vehicle seat belt tension prediction system and method comprises an accelerometer (20) having an output signal responsive to vertical acceleration of the vehicle, a seat weight sensor (30) having an output signal responsive to the force exerted by a mass resting on the seat, and a processor means (50) for calculating seat belt tension. The processor is provided with a plurality of inputs operatively coupled to the accelerometer output and seat weight sensor output. Suitable programming is provided to instruct the processor (50) to calculate the average mass resting on the vehicle seat and predict the force that should be exerted on the seat for a measured level of vertical acceleration assuming zero belt tension. The processor (50) then compares the actual force measured by the seat weight sensor (30) with the predicted force to determine seat belt tension thereby obviating the necessity of complex hardware in physical contact with the seat belt system.

**SEAT BELT TENSION PREDICTION SYSTEM USING AN  
ACCELEROMETER MOUNTED TO THE SEAT FRAME AND A WEIGHT  
SENSOR**

**CROSS REFERENCE TO RELATED APPLICATIONS**

The instant application claims the benefit of copending U.S.

5 Provisional Application Serial No. 60/046,233, filed May 12, 1997.

Co-pending U.S. Application Serial No. 08/993,701 entitled "Seat Weight Sensor Having Fluid Filled Bladder", filed on December 18, 1997, claiming benefit of U.S. Provisional Application Serial No. 60/032,380 filed on December 19, 1996, and assigned to the assignee 10 of the instant invention discloses a hydrostatic weight sensor comprising a fluid filled bladder and a pressure sensor for sensing the weight of an occupant in a vehicle seat for controlling a safety restraint system. U.S. Application Serial No. 08/993,701 also discloses a load distributor for distributing loads across the load bearing surface of the 15 hydrostatic weight sensor. U.S. Application Serial No. 08/993,701 and U.S. Provisional Application Serial No. 60/032,380 are incorporated herein by reference.

Co-pending U.S. Application Serial No. 09/003,672 entitled "Automotive Seat Weight Sensing System", filed on January 7, 1997, 20 claiming benefit of U.S. Provisional Application Serial No. 60/034,018 filed on January 8, 1997, and assigned to the assignee of the instant invention discloses a seat weight sensing system comprising a plurality of hydrostatic weight sensors each of which is in accordance with U.S. Application Serial No. 08/993,701. U.S. Application Serial No. 25 09/003,672 and U.S. Provisional Application Serial No. 60/034,018 are incorporated herein by reference.

Co-pending U.S. Application Serial No. 09/003,870 entitled "Vehicle Seat Sensor Having Self-Maintaining Air Bladder", filed on January 7, 1997, claiming benefit of U.S. Provisional Application Serial

30 No. 60/035,343 filed on January 16, 1997, and assigned to the assignee of the instant invention discloses an apparatus for automatically maintaining the supply of sensing fluid in a hydrostatic weight sensor. U.S. Application Serial No. 09/003,870 and U.S. Provisional Application Serial No. 60/035,343 are incorporated herein by reference.

35 Co-pending U.S. Application Serial No. 09/003,868 entitled "Seat Weight Sensor with Means for Distributing Loads", filed on January 7, 1997, claiming benefit of U.S. Provisional Application Serial No. 60/058,084 filed on September 4, 1997, and assigned to the assignee of the instant invention discloses a load distributor for distributing sensed load across the load bearing surface of a hydrostatic weight sensor. U.S. Application Serial No. 09/003,868 and U.S. Provisional Application Serial No. 60/058,084 are incorporated herein by reference.

40 Co-pending U.S. Application Serial No. 09/003,673 entitled "Seat Weight Sensor Having Self-Regulating Fluid Filled Bladder", filed on January 7, 1997, claiming benefit of U.S. Provisional Application Serial No. 60/058,119 filed on September 4, 1997, and assigned to the assignee of the instant invention discloses a hydrostatic weight sensor having a means for automatically regulating the amount of sensing fluid 45 therein. U.S. Application Serial No. 09/003,673 and U.S. Provisional Application Serial No. 60/058,119 are incorporated herein by reference.

50 Co-pending U.S. Application Serial No. 09/003,746 entitled "Seat Weight Sensor Using Fluid Filled Tubing", filed on January 7, 1997, claiming benefit of U.S. Provisional Application Serial No. 60/065,986 filed on November 14, 1997, and assigned to the assignee of the instant invention discloses a hydrostatic weight sensor incorporating a fluid filled tube. U.S. Application Serial No. 09/003,746 and U.S. Provisional Application Serial No. 60/065,986 are incorporated herein by reference.

55 Co-pending U.S. Application Serial No. 09/003,744 entitled "Low Profile Hydraulic Seat Weight Sensor", filed on January 7, 1997, claiming benefit of U.S. Provisional Application Serial No. 60/065,832

filed on November 14, 1997, and assigned to the assignee of the instant invention discloses a hydrostatic weight sensor constructed from plates or sheets of semi-rigid material and filled with a liquid, grease, Bingham 65 fluid or thixotropic material. U.S. Application Serial No. 09/003,744 and U.S. Provisional Application Serial No. 60/065,832 are incorporated herein by reference.

### TECHNICAL ART

The instant invention relates generally to automotive passenger 5 restraint systems and more specifically to a system and method for predicting seatbelt tension in a vehicle utilizing a seat weight sensor and an accelerometer.

### BACKGROUND OF THE INVENTION

Automotive manufacturers and the National Highway 5 Transportation Safety Association are investigating methods to disable vehicle air bags in situations where they may cause more harm than good. Typically, airbags have been developed to deploy with enough force to restrain a 175 lb. adult in a high velocity crash. Deployment of the same air bags when children are seat occupants may cause serious 10 injury due to the force generated upon inflation of the bag.

As a result, seat weight sensors and systems are being developed in an attempt to determine when the passenger seat occupant is a child.

Such systems should identify when the occupant is small, or even 15 when a child is in a rear facing infant seat, a forward facing child seat or a booster seat. Occupant weight measurement when a child seat is present is further complicated by the downward force applied to the child seat by the tension of a seat belt. When a child seat is strapped tightly, the seat belt forces the child seat into the vehicle seat and can

20 often artificially increase the measured weight, which may lead to air bag deployment when children or infants are present in the seat.

A variety of methods have been used for seat belt tension measurement. Copending U.S. Provisional Application Serial No. 25 60/067,071 entitled "Villari Effect Seat Belt Tension Sensor", and copending U.S. Provisional Application Serial No. 60/070,319 entitled "Compressive Villari Effect Seatbelt Tension Sensor", both assigned to the assignee of the instant invention, disclose two seat belt tension measurement systems utilizing sensors that operate on the principle 30 known as the Villari effect. The Villari effect refers to the tendency of certain materials with magnetostrictive properties to inhibit or enhance the strength of an electromagnetic field within the material when the material is being subjected to compression or tensile stress. By measuring the field strength in magnetostrictive material placed in line 35 with a seat belt mechanism, for example in a seat belt latch or a seat belt retractor, the relative tension in the belt may be calculated.

Furthermore, belt deflection techniques which guide a seat belt through a mechanical system that forces the belt out of a straight line 40 when there is low tension have been used. Under high tension the seat belt forces the displacement of a mechanical deflector. This force may then be sensed utilizing an electromechanical switch. Tension measurement mechanisms have also been incorporated in the buckle of the seat belt. In one embodiment, a sliding buckle is biased back with a 45 spring. When the belt is under heavy tension, the buckle pulls forward to control a switch that provides feedback to a vehicle processor.

The aforementioned seat belt tension measurement methods suffer from a number of disadvantages. Initially, a great number of additional 50 parts are required for seat belt retractors or buckle configurations. This adds complexity (and therefore cost) to vehicle assembly and provides

for considerable difficulty in retrofitting existing vehicles. Additionally, several of the aforementioned tension systems provide only a threshold level of tension detection.

55

The present invention may be used to detect whether the seat belt is under high tension thereby denoting that an infant seat is present. Furthermore, significant tension in the belt can be predicted without resorting to the complex instrumentation required to measure actual belt 60 tension. Known belt tension measurement systems that directly contact the seat belt require additional hardware and sensors that increase component count and vehicle assembly complexity.

### SUMMARY OF THE INVENTION

The instant invention overcomes the aforementioned problems by 5 providing a seat belt tension prediction system employing an accelerometer and a seat weight sensor to accurately determine the tension in a vehicle seat belt and thereby discriminate between the presence of a tightly belted child seat or other object and an adult occupant.

10

The instant invention measures the "bounce", or vertical acceleration, experienced by a weight on a seat weight measurement means by monitoring an accelerometer that is rigidly mounted to the vehicle seat. The bounce can be thought of as the temporary 15 acceleration of the weight on the seat caused by the vehicle traversing bumps or holes in the road. This road-induced bounce causes oscillations in the force acting upon the seat that may be measured by a seat weight sensor.

20 A "free" or unbelted mass positioned on a vehicle seat will bounce up and down on the seat and may, for example, completely lose contact

with the seat in extreme cases. The weight sensor would correspondingly interpret this extreme case as a "spike" of zero force acting on the seat. Usually, however, the output signal produced by the 25 weight sensor will oscillate with a small amplitude that is dependent upon the total mass acting upon the seat and the amplitude of the road-induced vehicle bounce. When the force acting downwardly on the seat is increased due to the tension in a tight seat belt, the amplitude of oscillation of an output signal produced by the weight sensor will be 30 reduced because a component of the force caused by the tension in the seatbelt is constant. Accordingly, a seatbelt tension may be calculated by determining the vertical acceleration of the vehicle and the variation in force exerted on the seat as measured by the seat weight sensor.

35 A conventional accelerometer provides an electrical signal proportional to the vertical acceleration that the seat, and therefore the mass in the seat, experiences. When actual vertical acceleration is compared to the oscillating output signal produced by the weight sensor, a measure of the force on the seat attributable to the tension in 40 the seat belt may be calculated. The road-induced vertical acceleration acting on the vehicle is used to predict the amount of force exerted downwardly on the seat given that no seat belt tension is present.

45 A conventional microprocessor is adapted to accept output signals from the accelerometer and the seat weight sensor. The accelerometer output is responsive to the amount of vertical acceleration caused by road bounce acting on the vehicle seat and the weight sensor output is responsive to the amount of force exerted downwardly on the vehicle seat.

50

A normalized measurement of seatbelt tension may be calculated by the processor by first calculating an average mass on the seat using the weight sensor output. The expected variation in force is then

calculated by multiplying the aforementioned average mass on the seat  
55 by the actual acceleration as measured by the accelerometer over a predetermined time period. A normalized seatbelt tension may then be calculated by dividing the variation in force as measured by the seat weight sensor over a predetermined time period by the expected or calculated variation in force over the aforementioned period.

60

The resultant scalar tension measure will approximate unity for unbelted or loosely belted occupant situations where the mass acting on the seat is free to travel vertically. Accordingly, the normalized tension scalar will decrease when extremely high belt tension is present thereby  
65 forcing the mass onto the seat.

Alternatively, the processor may calculate an expected force exerted on the seat due to road-induced vehicle bounce at discrete time intervals, assuming that no belt tension exists, and compare the results  
70 with the measured force exerted on the seat at the each discrete point in time. The ratio between the measured force and the calculated or expected force exerted on the seat provides an indication of belt tension.

75 Known seat weight sensors may comprise one or more pads employing force sensitive resistive (FSR) elements disposed within the seat to provide a weight measurement. These arrangements are typically used as weight threshold systems that are used in conjunction with a processor to disable a passenger air bag when the seat is empty.

80

Conventional load cells attached to the seat mounting posts have also been used in research applications. The use of load cells as weight measurement means in the instant invention requires that the seatbelts or passenger restraints are not mounted directly to the vehicle seat  
85 because a load cell system that weighs the entire seat and its contents

including the seatbelts and their mounting points will not be responsive to the force applied to the seat by the tension in the seatbelt.

Mechanisms employing string actuated potentiometers to measure 90 downward seat displacement have also been utilized as weight measurement means. In these mechanisms, a weight resting upon a seat pad causes the pad to sag or curve downwardly, thereby displacing a string that is positioned across the bottom of the seat pad. One end of the string is connected to a potentiometer shaft that is rotated when 95 the string is displaced. The rotation of the potentiometer shaft causes the resistance at the potentiometer output to change. A processor is adapted to measure the changing resistance at the potentiometer output, thereby providing a signal proportional to string displacement, and therefore, the force caused by a mass present on the seat.

100

Copending U.S. Application Serial No. 08/993,701 further discloses a weight sensor employing a gas filled bladder disposed within the seat pad to calculate seat weight. When a load is applied to the seat a differential pressure sensor operatively coupled to the bladder 105 generates a signal that is responsive to the pressure on the fluid within the bladder and therefore indicative of the force acting upon the seat. A signal processor having an input operatively coupled to the pressure sensor then calculates the force exerted on the seat as well as the mass present.

110

By determining the amount of mass present in a vehicle seat and the amount of tension present in a passenger restraint belt, corrective action may be taken to further protect a vehicle occupant by adapting other restraint system components, such as the air bag control system.

115

The ability to sense the tension present in a seat belt may be used in conjunction with a seat weight sensor to determine the presence of

an occupant in a vehicle seat and the relative size of the occupant. This information may be used either to deactivate seatbelt pretensioners, 120 and/or modify the inflation profile of an air bag.

Furthermore, by sensing the amount of tension present in the seat belt, the deployment of an airbag may be inhibited in the presence of infant seats or in situations where occupants are small so as to reduce 125 their risk of injury from the inflating air bag. Therefore, a system that can reliably predict the amount of tension present in a seat belt may be used to great advantage in vehicle safety systems.

One significant advantage of the instant invention is that it does 130 not require numerous ancillary components that are in direct contact with the seat belt system. The present invention can predict whether there is significant tension in the seat belt without directly measuring seat belt tension.

135 Therefore, one object of the instant invention is to provide a seat belt tension measurement system that does not require a mechanism in direct contact with the seat belt or its associated assembly.

Another object of the instant invention is to use road-induced 140 vertical acceleration exerted on every vehicle as a forcing function for a seat weight sensor signal. The oscillation of an accelerometer signal compared with the oscillation of a weight sensor signal at discrete time intervals provides the data required to calculate seat belt tension.

145 A yet further object of the present invention is to provide a seat belt tension prediction system that requires minimal additional components beyond a seat weight measurement means and the attendant processor adapted to receive and process various vehicle instrumentation signals. The instant invention requires only an

150 accelerometer or equivalent acceleration sensing device and a conventional microprocessor or equivalent processing means in conjunction with a seat weight sensor to accurately calculate seat belt tension.

155 A yet further object of the instant invention is to provide a seat belt tension prediction system that is useful in determining the presence of an infant seat in a vehicle. The present invention measures the component of force acting on a vehicle seat that is attributable to tension in the seat belt as well as the component of force attributable to 160 the presence of a mass on the seat, thereby providing a means to predict whether the occupant is an adult or a child.

165 The instant invention will be more fully understood after reading the following detailed description of the preferred embodiment with reference to the accompanying drawings. While this description will illustrate the application of the instant invention in an automotive safety restraint system, it will be readily understood by one of ordinary skill in the art that the instant invention may also be utilized in other tension measurement systems.

170

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagrammatical view of a preferred embodiment of the instant invention.

5 Fig. 2 is a diagrammatical view of an alternative seat weight sensor arrangement taken along the line 2-2 of Fig. 1.

Fig. 3 is a diagrammatical view of an alternative embodiment of the instant invention.

10 Fig. 4 is a diagrammatical view of an alternative embodiment of the instant invention.

Fig. 5 is a view of the instant invention taken along the line 5-5 of Fig. 4.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)**

Referring to Fig. 1, a seat belt tension prediction system and method 10 for a vehicle 12 having a seat 14 is comprised of an accelerometer 20 and a seat weight sensor 30. The accelerometer 20 is provided with an output signal 22 that is responsive to the amount of vertical acceleration acting upon the vehicle 12 and, therefore, on the vehicle seat 14. The accelerometer 20 must be rigidly secured to a vehicle structural member 16 that experiences the same vertical acceleration that the vehicle seat 14 is subjected to when traversing variations in terrain. In a preferred embodiment of the instant invention the resolution of the accelerometer 20 is greater than .005 g to provide sufficient sensitivity to small variations in vertical acceleration.

The seat weight sensor 30 is provided with an output signal 32 that is responsive to the amount of force exerted downwardly on the vehicle seat 14. Accordingly, the seat weight sensor output signal 32 will also be responsive to additional force upon the vehicle seat 14 exerted by tension in a seat belt 34. The output signal 32 from the weight sensor 30 must have an update period small enough to allow the weight sensor 30 to sense oscillations in force on the seat 14 caused by the vehicle's vertical acceleration. In a preferred embodiment of the instant invention the update period of the weight sensor output signal 32 is less than 25 milliseconds. Additionally, the weight sensor output signal 32 may be AC coupled to filter low frequency signal oscillations that normally occur as a result of occupant movement, thus ignoring those oscillations that are not produced by road-induced vertical acceleration.

Furthermore, a processor 50 is provided, having a first input 52 operatively coupled to the accelerometer output signal 22 and a second

**input 54** operatively coupled to the seat **weight sensor output signal 32**.

The **processor 50** is further operatively coupled to a vehicle **airbag control system 60** whereby the **processor 50** may provide an **output signal 56**, or a plurality thereof, to the **airbag control system 60** to inhibit deployment of an airbag and/or to modify its inflation profile.

The **processor 50** may comprise an analog or digital microprocessor or any equivalent thereof. Although the preferred embodiment of the instant invention utilizes a conventional digital microprocessor, it is readily understood by one having ordinary skill in the art that alternative means such as relay logic circuitry, analog processors, analog to digital converters and TTL logic circuitry may be employed as processor means to practice the instant invention.

45

In an alternative embodiment of the instant invention shown in FIG. 2, seat **weight sensor 40** comprises a plurality of **force sensitive resistive elements 42** disposed within the vehicle **seat 14** for measuring force. The **force sensitive resistive elements 42** provide as an **output signal 44** a variable electrical resistance responsive to the amount of force acting on the **elements 42**, that may be operatively coupled to the **input 54** of **processor 50**. The variable resistance **output signal 44** is generally inversely proportional to the amount of force acting on the **seat 14**.

55

Referring to Fig. 3 and as disclosed in U.S. Application Serial No. 08/993,701, a **hydrostatic seat weight sensor 70** as incorporated in an alternative embodiment of the instant invention, comprises a gas filled **bladder 72** mounted within the vehicle **seat 14** and a **differential pressure sensor 74** operatively coupled to the **bladder 72** for measuring the difference in pressure between the **bladder 72** and the atmosphere. The **differential pressure sensor 74** provides a **pressure sensor output 76** that is responsive to the force exerted downwardly on the **seat 14**. The

65 differential pressure sensor output 76 is operatively coupled to input 54 of processor 50 thereby providing an indication of the force acting downwardly on the seat 14.

70 As shown in FIG. 4, an alternative seat weight sensor comprises a plurality of load cells 80 disposed between the vehicle seat 14 and the vehicle structure 16 such that the entire weight of the seat 14 rests upon the load cells 80. The load cells 80 are provided with an output 82 that is responsive to the amount of force acting upon the seat 14. When utilizing load cells 80 as a weight sensors, it is critical that the 75 seat belt 34 is mounted to the vehicle 12 such that load cell 80 is responsive to the force upon the seat 14 generated by tension present in the seat belt 34. For example, Figs. 4 and 5 provide illustrations of a seat belt 34 configuration wherein the load cells 80 are responsive to both the tension applied by the seat belt 34 and the force resulting from a mass resting on the seat 14.

80

In operation, and in accordance with the preferred embodiment of the instant invention, the accelerometer 20 measures the vertical acceleration of the seat 14 and provides an output signal 22 to the processor 50. A normalized seatbelt tension measure is then calculated 85 by the processor 50 to detect high belt tension and thereby determine the presence of a child seat.

90 The processor 50 is programmed to calculate an average mass of an object resting on the seat by dividing the output 32 of the weight sensor 30 by the earth's gravitational constant, g. This calculation may be performed at a predetermined time during the operation of the vehicle 12, or preferentially, performed continuously by assuming that the vertical acceleration of the vehicle 12 and the belt tension are negligible, and averaging the resultant successive mass calculations.

95

100 A predicted variation in force exerted on the **seat 14** is calculated in the **processor 50** by multiplying the aforementioned average mass by the measured variation in vertical acceleration as provided by the **accelerometer 20** over a predetermined time period. The variation in vertical acceleration over time may be determined by integrating the absolute value of the difference between the **accelerometer output 22** and the earth's gravitational constant  $g$  over the aforementioned time period.

105 The variation, or fluctuation of the actual force exerted on the **seat 14** is then determined by integrating the absolute value of the difference between the seat weight sensor **output 32** and the average force exerted on the **seat 14**. The normalized tension measurement is then calculated by dividing the variation in actual force exerted on the 110 seat over the same time period as measured by the **weight sensor 30**, by the predicted variation in force exerted on the **seat 14**. The time period over which the predicted force variation is calculated must be sufficient to allow road induced bounce to impart vertical acceleration to the **vehicle 12**. In a preferred embodiment of the instant invention the 115 time period used to calculate the normalized belt tension is .5 seconds.

120 In an alternative embodiment of the instant invention the **processor 50** calculates the force exerted downwardly on the **seat 14** at discrete time intervals utilizing the vertical acceleration measurement provided by the **accelerometer 20**, and assuming that no **seat belt 34** tension is present in the system, and then compares the resultant predicted force with the actual measured force at each discrete point in time to calculate belt tension. As an example, the predicted force 125 acting on the **seat 14** may be calculated by programming the **processor 50** to perform the following algorithm:

$$F = M(g - A) + BT, \text{ where}$$

**F** is the force acting downwardly onto the seat 14,

**M** is the mass of the object on the seat 14,

130 **g** is the gravitational acceleration exerted on the mass **M** by the earth,

**A** is the vertical acceleration of the vehicle 12, excluding the earth's gravity, and

**BT** is the vertical component of the tension present in the belt 34.

135 The vertical acceleration **A** of the vehicle 12 fluctuates around zero and thus causes variations in the force **F** acting on the seat 14.

The belt tension **BT** approximates a constant value that is near zero for most occupant seating situations except for the presence of tightly belted child seats. The belt tension **BT** is generally a small value

140 because belt tension greater than a few pounds of force has been found to be uncomfortable for most vehicle occupants thereby making it unlikely that an occupant is present when there is significant tension in the seat belt 34.

145 As previously disclosed, the **output signal 32** of the **weight sensor 30** is divided by the earth's gravitational constant **g** by **processor 50** to calculate the average mass **M** present in the **vehicle seat 14**. The **processor 50** then calculates a predicted force acting downwardly on the **seat 14** at discrete time intervals using the aforementioned average mass, with the assumption that the belt tension **BT** is zero. Still assuming zero belt tension **BT**, the **processor 50** then compares the actual value of the force **F** as measured at each discrete point in time by the **weight sensor 30** with the calculated or predicted force. The difference between the predicted and actual values of force **F** provides 155 an indication of the tension present in the belt **BT**.

In an alternative method for predicting belt tension **BT**, the **processor 50** monitors the **weight sensor output signal 32** at discrete time intervals and measures the amplitude of the oscillations of the

160 **output signal 32** at each discrete point in time. The **processor 50** further monitors the **accelerometer output signal 22** at the corresponding discrete time intervals and calculates the amplitudes of the oscillations of the **accelerometer output signal 22**. The resultant accelerometer amplitude measurements are then sequentially multiplied  
165 by the average mass **M** present in the **vehicle seat 14** to calculate the predicted force acting on the **seat 14** at each discrete point in time. The ratio of the actual force acting on the **seat 14** to the calculated force at each time interval thereby provides a measure of seat belt tension.

170 A tightly belted mass present in the vehicle **seat 14** will produce a reduced ratio of actual force to predicted force as compared to the ratio calculated when a "free" mass is positioned in the vehicle **seat 14**. Therefore, the smaller the ratio between actual force as indicated by the  
175 **weight sensor 30** to predicted force as calculated using the average mass **M** and the **accelerometer output signal 22**, the greater the belt tension **BT**, and the higher the probability that an infant seat is tightly belted down onto the vehicle **seat 14**. The **processor 50** may be provided with a look-up table whereby **seat belt 34** tension may be  
180 determined given a specific calculated tension ratio.

Accordingly, and as shown in Fig. 1, where the **processor 50** calculates a level of tension in the **seat belt 34** in excess of a predetermined maximum, the **processor 50** will generate an **output 56**  
185 operatively coupled to an **air bag control system 60** to inhibit deployment of the air bag. Alternatively, where the **processor 50** calculates a level of tension in the **seat belt 34** below the predetermined maximum and the seat **weight sensor 30** indicates that the occupant's weight is below a predetermined minimum, the **processor 50** will provide  
190 an **output 56** to the **air bag control system 60** to reduce the inflation profile thereof according to the measured weight of the occupant.

While specific embodiments of the instant invention have been described in detail, those with ordinary skill in the art will appreciate 195 that various modifications and alternatives to those details could be developed in light of the overall teachings of the disclosure. Accordingly, the particular arrangements disclosed are meant to be illustrative only and not limiting as to the scope of the invention, which 200 is to be given the full breadth of the appended claims and any and all equivalents thereof.

**I claim:**

1. A system for measuring seat belt tension in a vehicle having an airbag control system and a seat, comprising:

- 5 a.) an accelerometer rigidly secured to said vehicle in proximity to the seat thereof, said accelerometer having an output signal responsive to the vertical acceleration of said vehicle;
- b.) a seat weight sensor having an output signal responsive to the force exerted by a mass on said seat; and
- 10 c.) a computer processor having first and second inputs, the first input being operatively coupled to the output signal of said accelerometer and the second input being operatively coupled to the output signal of said seat weight sensor, wherein said processor calculates tension in said seat belt by comparing the output signal of said seat weight sensor at discrete time intervals with predicted fluctuations in the force exerted on the seat caused by vertical acceleration acting upon the mass, assuming no seatbelt tension.

2. The system of claim 1 wherein said seat weight sensor comprises a hydrostatic seat weight sensor disposed within the seat.

3. The system of claim 1 wherein said seat weight sensor comprises a plurality of load cells adapted to be responsive to the force exerted on the seat by said seat belt.

4. The system of claim 1 wherein said seat weight sensor comprises a plurality of force sensitive resistive elements disposed within the seat.

5. The system of claim 1 wherein said computer processor further comprises an output operatively coupled to said air bag control system for inhibiting the operation thereof upon the calculation of high seat belt tension.

5

6. The system of claim 2 wherein said computer processor further comprises an output operatively coupled to said air bag control system for inhibiting the operation thereof upon the calculation of high seat belt tension.

5

7. The system of claim 3 wherein said computer processor further comprises an output operatively coupled to said air bag control system for inhibiting the operation thereof upon the calculation of high seat belt tension.

5

8. The system of claim 4 wherein said computer processor further comprises an output operatively coupled to said air bag control system for inhibiting the operation thereof upon the calculation of high seat belt tension.

5

9. A method for predicting seatbelt tension in a vehicle having a seat, an accelerometer rigidly secured to said vehicle in proximity to the seat, said accelerometer having an output signal responsive to the vertical acceleration of said vehicle, a seat weight sensor having an output signal responsive to the force exerted by a mass acting on the seat, and a processor having a first input operatively coupled to the output signal of said accelerometer and a second input operatively coupled to the output signal of said weight sensor comprising:

5 a.) measuring the actual variation in force due to vertical acceleration exerted on the seat over a predetermined time period;

10 b.) calculating the average mass on the seat;

c.) calculating the predicted variation in force due to vertical acceleration exerted on the seat by multiplying the average mass on the seat by the variation in vertical acceleration over the predetermined time period; and

15 d.) dividing the actual variation in force by the predicted variation in force whereby the quotient represents normalized seatbelt tension.

20

10. A method for predicting seatbelt tension in a vehicle having a seat, an accelerometer rigidly secured to said vehicle in proximity to the seat, said accelerometer having an output signal responsive to the vertical acceleration of said vehicle, a seat weight sensor having an output signal responsive to the force exerted by a mass on the seat, and a processor having a first input operatively coupled to the output signal of said accelerometer and a second input operatively coupled to the output signal of said weight sensor comprising:

5 a.) measuring the force due to vertical acceleration exerted on the seat at discrete time intervals;

b.) calculating the average mass on the seat;

c.) calculating at discrete time intervals a predicted force acting

on the seat due to vertical acceleration, assuming the tension in said seat belt is zero; and

15 d.) calculating at discrete time intervals the difference between the measured force exerted on the seat and the predicted force whereby the difference is indicative of seat belt tension.

11. A method for predicting seatbelt tension in a vehicle having a seat, an accelerometer rigidly secured to said vehicle in proximity to the seat, said accelerometer having an output signal responsive to the vertical acceleration of said vehicle, a seat weight sensor having an 5 output signal responsive to the force exerted by a mass on the seat, and a processor having a first input operatively coupled to the output signal of said accelerometer and a second input operatively coupled to the output signal of said weight sensor comprising:

10 a.) measuring the force due to vertical acceleration exerted on the seat at discrete time intervals;

b.) calculating the average mass on the seat;

c.) measuring the vertical acceleration acting on said vehicle at discrete time intervals;

d.) calculating at discrete time intervals a predicted force exerted on the seat by multiplying the vertical acceleration at each time interval by the average mass, assuming the tension in said seat belt is zero; and

e.) calculating at discrete time intervals the ratio between the measured force exerted on the seat and the predicted force exerted on the seat whereby the ratio is indicative of seat belt tension.

15

20

