




(22) **Date de dépôt/Filing Date:** 2005/11/30
 (41) **Mise à la disp. pub./Open to Public Insp.:** 2006/06/01
 (45) **Date de délivrance/Issue Date:** 2014/04/08
 (30) **Priorité/Priority:** 2004/12/01 (GB04 26385.1)

(51) **Cl.Int./Int.Cl. A61F 2/46** (2006.01)
 (72) **Inventeurs/Inventors:**
 RAUGEL, PATRICK, FR;
 PINOT, LOIC, FR
 (73) **Propriétaire/Owner:**
 STRYKER IRELAND LIMITED, IE
 (74) **Agent:** SMART & BIGGAR

(54) **Titre : DISPOSITIF D'INSERTION D'UN COTYLE FLEXIBLE**
 (54) **Title: PROSTHETIC IMPLANATATION INSERTER FOR A FLEXIBLE ACETABULAR CUP**



(57) **Abrégé/Abstract:**

A prosthesis implantation inserter for use with a flexible acetabular cup which has an opening or openings in its peripheral rim comprising engagement means which in an operational position frictionally engage the said opening or openings, and release means which can be operated to withdraw the engagement means from the opening or openings.



Abstract

A prosthesis implantation inserter for use with a flexible acetabular cup which has an opening or openings in its peripheral rim comprising engagement means which in an operational position frictionally engage the said opening or openings ,and release means which can be operated to withdraw the engagement means from the opening or openings.

**PROSTHETIC IMPLANATATION INSERTER
FOR A FLEXIBLE ACETABULAR CUP**

This invention relates to a prosthesis implantation inserter for use with a flexible acetabular cup. Flexible acetabular cups have shown their ability to transfer the load in a natural manner to the patient's pelvis. An acetabular cup of this kind is described in European Patent Application EP-A-0 552 949.

To achieve an initial stability and a long term implantation of a flexible acetabular cup prosthesis it is necessary to ensure that the position of the implant is appropriate and that the contact between the bone and the outer surface of the prosthesis is maximized. Moreover, the stability is achieved due to an interference fit between the host bone cavity and the implant. The outcome during the implantation is its inclination to deform itself. As a consequence, it is difficult to place the acetabular cup adequately and guarantee an intimate contact with the bone.

Some embodiments of the present invention may provide an instrument to overcome these difficulties.

US Patent No. 5,954,727 shows a positioning tool for reversibly engaging an acetabular cup, an elongate cylindrical section of the positioning tool being insertable through a posterior opening in the cup. The outer diameter of the cylindrical portion is expandable to engage the inner wall of the cup in an interference fit to prevent movement of the cup relative to the tool and hold the cup in engagement when planting the cup at a desired position.

US Patent No. 5,098,437 also shows the use of a positioning rod which has spring elements which engage a circumferential groove on the inner surface of the implant.

74705-41

- 2 -

Neither of these constructions are suitable for use with a flexible acetabular cup due to the flexibility of the cup itself.

In European Patent Application EP-A-0 552 949 the flexibility of the cup is provided by a separation or opening in its peripheral rim and the present invention
5 utilizes one opening or separation of this type.

According to an embodiment of the present invention, a prosthesis implantation inserter for use with a flexible acetabular cup which has an opening or openings in its peripheral rim comprises engagement means which in an operational position frictionally engage the said opening or openings, and release means which
10 can be operated to withdraw the engagement means from the opening or openings.

According to another embodiment of the present invention, there is provided a prosthesis implantation inserter in combination with and for insertion of an acetabular cup which has a radially extending opening or openings in its peripheral rim, and in which said inserter includes engagement means which in an operational
15 position frictionally engage said opening or openings, and release means which can be operated to withdraw the engagement means from the opening or openings, in which said acetabular cup is flexible, the flexibility of which is achieved by said opening or openings, and the dimensions of the engagement means are slightly larger than the dimensions of the opening or openings so that they act to deform the
20 opening or openings when they are engaged thereby in the operational position.

It will be appreciated that although only one opening is shown in European Patent Application EP-A-0 552 949 a flexible acetabular cup could have a number of openings in its rim and wall to provide the required flexibility.

Preferably the engagement means act to deform the opening or
25 openings when they are engaged thereby in its operational position.

74705-41

- 2a -

The engagement means which contact the opening or openings can be slightly larger than the opening so that the flexible cup grips the engagement means by friction which acts to secure the cup to the inserter.

5 When the cup is in position it can be guided and inserted into the acetabulum and impacted. Once the position of the prosthesis satisfies the surgeon the engagement means can be removed by operating the release means and the cup inserter is removed without any risk of compromising the position or the stability of the implant.

-3-

In a preferred construction the inserter includes a locator adapted to locate the rim of the acetabular cup and in relation to which the engagement means can be moved by the release means.

Thus the engagement means may comprise a sliding component positioned on the locator.

The engagement means can be resiliently biased towards its operational position and in one preferred embodiment the engagement means can include an engagement portion or portions which is or are shaped to co-operate with the shape of the opening or openings in the peripheral rim of the cup with which it is to be used.

Thus, the engagement portion can be shaped to engage a keyhole-shaped opening in the peripheral rim of the cup with which it is adapted to be used.

Alternatively, the engagement portion can be shaped to engage a substantially radially extending slot in the peripheral edge of the cup with which it is to be used.

In another embodiment the engagement portion can be shaped as a series of radially extending fins adapted to engage a series of radially extending openings in the form of slots in the peripheral rim of the cup with which it is to be used.

The locator against which the peripheral rim of the acetabular cup is located can be shaped to accommodate an acetabular cup with a rim which mimics the natural shape of the acetabulum.

In a convenient construction the inserter can include a body portion which carries the engagement means, a handle and a trigger which can operate the release means.

Preferably the body portion, handle and trigger are detachable from the engagement means.

The invention also includes a prosthesis implantation inserter in combination with an acetabular cup with which it is to be used.

Also included within the invention is a prosthesis implantation inserter as set forth above in combination with a flexible acetabular cup with which it is to be used and in which the engagement means, detached from the body portion, handle and trigger, and engaged in the cup are located in a sterile package.

The invention can be performed in various ways and some embodiments will now be described by way of example and with reference to the accompanying drawings in which :

Figure 1 is an isometric view of an acetabular cup inserter according to the present invention with an acetabular cup in place therein;

Figure 2 is a side view of the acetabular cup inserter and an acetabular cup as shown in Figure 1;

Figure 3 is a cross-sectional side view of the acetabular cup inserter and the acetabular cup shown in Figures 1 and 2;

Figure 4 is an enlarged cross-sectional view of part of the acetabular cup inserter shown in Figure 3 with the engagement means in its operational position engaged into an opening in the rim of the cup;

Figure 5 is an enlarged view of part of the cup inserter with the engagement means in its released position;

-5-

Figure 6 is an isometric view of a flexible acetabular cup with which the inserter can be used;

Figure 7 is an isometric view of the cup inserter without the cup;

Figure 8 is an enlarged view of part of the inserter without the cup;

Figure 9 is an isometric view of an alternative construction of a cup inserter on which a cup with 9 slots is secured;

Figure 10 is an isometric view of a flexible cup of which the flexibility is achieved by 9 slots;

Figure 11 is an isometric view of part of the cup inserter and the appropriate engagement means for a cup with 9 slots;

Figure 12 is a diagrammatic front view of a flexible cup with an anatomic rim;

Figure 13 is a detailed side view of the cup inserter on which is secured a flexible cup with an anatomic rim; and,

Figure 14 is an isometric view of the flexible cup shown in Figure 12 with the engagement means engaged but removed from the remainder of the inserter.

Figure 6 shows a flexible acetabular cup 1 of the type described in EP-A-0 552 949 and which has a keyhole shaped opening 2 in its peripheral rim 3.

An inserter, according to the present invention and for use with an acetabular cup 1 as shown in Figure 6, is shown in Figure 3 and comprises engagement means

-6-

4 carried on a locator 5 which is mounted on a main body 6 which is in the form of a hollow tube carrying an operating rod 7. One end of the operating rod 7 is screw threaded to locate in and engage a socket 8 in the engagement means 4. The other end of the operating rod 7 is enlarged and indicated by reference numeral 9 and is mounted in an enlarged bore 10. The end of the portion 9 carries a flange 11 which is engaged by a compressed coil spring 12 which is in turn held in place by an end stop 13. The operating rod 7 is therefore biased to the left to force the engagement portion towards the position shown in Figure 3 and which is its operational position. The engagement means can be withdrawn from its operational position towards the right by a trigger 14 when moved in the direction of the arrow 15.

A handle 16 is provided to facilitate handling.

In Figures 4 and 5 the cup 1 to be inserted is shown in position on the inserter. As will most clearly be seen from Figure 4 the rim 3 of the cup rests against the locator 5 which is in the form of a substantially flat disc and which bears against a flared circumference shaped collar 18 on the end of the main body portion 6 which has four arms 24.

The overall shape of the engagement means is most clearly shown in Figures 7 and 8 and comprises a cylindrical portion 19 which extends through a circular opening 20 in the location plate 5 and extends into a cylindrical socket 21 in the collar 18 as is most clearly shown in Figure 4.

The engagement means also includes a shaped engagement portion 22 whose cross-sectional shape is similar to the cross-sectional shape of the horseshoe-shaped opening 2 in the cup to be fitted. The edges of the engagement portion 22 are chamfered, as indicated by reference numeral 23. The dimensions of the engagement portion 22 are slightly larger than the dimensions of the opening 2 with which it is intended to be used. The lower part of the engagement portion 22 also

has an extension 25 which acts as a guide between two of the arms 24 and passes through an opening 26 in the location plate 5.

When engagement means 4 are in the operational position, as shown in Figure 4, the cup to be implanted is pushed over the engagement portion 22 so that, due to its flexible nature, it distorts slightly so that the edges of the opening 2 are gripped by friction on the surface of the engagement portion 22 adjacent its edge. In this position the location plate 5 is held in position by the shaped collar.

The locator plate 5 can be replaced by smaller or larger plates depending on the outer diameter of the cup 1. Preferably the diameter of the locator plate 5 is smaller than the outer dimensions of the cup 1, as shown in Figures 3 and 4, so that the rim 3 of the cup is visible when the cup is secured to the inserter. This is desirable in order to help the surgeon to control the position of the cup in relation with other anatomical landmarks.

The location means 4 can be interchangeable with other location means in order to match the specific shape or size of the cup to be implanted.

In order to remove the inserter once the cup has been placed in the acetabulum by the surgeon the trigger 14 is operated in the direction indicated by the arrow 15. This action acts to withdraw the engagement means 4 to the position shown in Figure 5 thus moving the engagement portion 22 out of the opening 2 and thus releasing the inserter from the cup. The chamfer 23 on the engagement portion 22 assists release.

The position of the "pinch" of the engagement means 4 can be adjusted by changing the shape and the oversize of the engagement portion 22.

The inserter can also be used with flexible cups of alternative constructions, for example the cup 29 shown in Figure 10. In this construction the flexibility is

achieved by replacing the opening 2 of the cup shown in Figure 6 by a number of slots 30, disposed regularly or not around the peripheral rim 31 of the cup. In order to operate with this type of cup the engagement means 4 of the construction shown in Figures 1 to 8 is replaced by the engagement means 32 shown in Figure 11. With this arrangement the part of the cylindrical portion 19 which passes through the location plate 5 and enters the socket 21 is retained as is a guide extension 25 which passes between the arms 24, but the outer shaped portion 22 is replaced by a dome 35 and a series of shaped fins 36 which are shaped to engage the slots 30 in the rims 31 of the cup 29. The thickness of the fins is slightly larger than the width of the slots 30 so that there is slight deformation of the cup as it is pushed onto the fins. In the position shown in Figure 11 the engagement means are in their withdrawn position, that is after the inserter has been removed from the cup. In the operational engagement position the fins will project further outwards and there is allowance at the rear of the fins for the withdrawal action.

Once again the dimensions of the location plate can be adjusted as required with regard to the visible rim 31 of the cup.

The engagement means 32 is held on the operating rod 7 in a similar manner to that described with regard to the earlier construction.

In a further alternative construction (not shown) the number of openings 30 can be reduced in number and the flexibility could even rely on a single slot. To operate with this type of construction the number of fins 36 would be adjusted appropriately.

The material employed to produce the cup 1 or 29 can be composite material, alternatively metal alloys are commonly employed for orthopaedic prostheses such as titanium alloys, cobalt, chromium or molybdenum alloys can be used. They all provide the desired flexibility and the inserter can be used with any of these material cups.

The engagement means and/or the location plate 5 can be stainless steel alloys commonly employed for producing orthopaedic instruments or other metallic alloys. Alternatively plastics or composite material can be used and in such a case the parts can be made by machining, injection moulding or any process suitable with the material concerned.

Figures 12 and 13 show how the cup inserter, according to the present invention, can also be used with a cup which has a rim 40 which is shaped with peaks and valleys that mimic the natural shape of the acetabulum, for example of the type shown in EP-A-04 255 528.4. The cup 41 shown in Figures 12 to 14 has a shaped opening 42 in its rim 40 which is of a keyhole shape similar to the opening 2 in the rim of the cup shown in Figure 6. In order to accommodate the shaped rim the facing surface 44 of the location plate 5 is shaped appropriately.

Figure 13 shows a cup 41 of the kind shown in Figures 12 and 13 located on the shaped engagement portion 22 and the engagement means and locator plate 5 removed from the main body portion, trigger and handle. The removal is achieved by unscrewing the operating rod 7 from the socket 8 in the cylindrical portion 19 of the engagement means 4.

The cup 41 which is to be used can be delivered pre-positioned on the engagement means 4 as shown in Figure 14 in a sterile packaging in order to simplify attaching the cup to the cup inserter. To secure the cup to the inserter, the cylindrical portion 19 is threaded onto the operating rod 7 in the cylindrical socket 21 and tightened by rotating the end stop 13. In such an arrangement the engagement means and/or the location plate 5 can be disposable. Preferably both of these are made of a plastic material and injection moulded.

74705-41

- 10 -

CLAIMS:

1. A prosthesis implantation inserter in combination with and for insertion of an acetabular cup which has a radially extending opening or openings in its peripheral rim, and in which said inserter includes engagement means which in an
5 operational position frictionally engage said opening or openings, and release means which can be operated to withdraw the engagement means from the opening or openings, in which said acetabular cup is flexible, the flexibility of which is achieved by said opening or openings, and the dimensions of the engagement means are
10 slightly larger than the dimensions of the opening or openings so that they act to deform the opening or openings when they are engaged thereby in the operational position.
2. A combination as claimed in claim 1, which includes a locator adapted to locate the rim of the acetabular cup and in relation to which the engagement means can be moved by the release means.
- 15 3. A combination as claimed in claim 2 in which the engagement means comprise a sliding component positioned in the locator.
4. A combination as claimed in any one of claims 1 to 3 in which the engagement means are resiliently biased towards the operational position.
5. A combination as claimed in any one of claims 1 to 4 in which the
20 engagement means includes an engagement portion or portions which is or are shaped to co-operate with the shape of the opening or openings in the peripheral edge of the cup with which it is to be used.
6. A combination as claimed in claim 5 in which the engagement portion is shaped to engage a keyhole-shaped opening in the peripheral edge of the cup with
25 which it is adapted to be used.

74705-41

- 11 -

7. A combination as claimed in claim 5 in which the engagement portion is shaped to engage a substantially radially extending slot in the peripheral edge of the cup with which it is adapted to be used.
8. A combination as claimed in claim 5 in which the engagement portions
5 are shaped as a series of radially extending fins adapted to engage a series of radially extending openings in the form of slots in the peripheral edge of the cup with which it is to be used.
9. A combination as claimed in any one of claims 2 to 8 in which the
10 locator is shaped to accommodate an acetabular cup with a rim which mimics the natural shape of the acetabulum.
10. A combination as claimed in any one of claims 1 to 9 including a body portion which carries the engagement means, a handle and a trigger which can operate the release means.
11. A combination as claimed in claim 10 in which the body portion, handle
15 and trigger are detachable from the engagement means.
12. A combination as claimed in claim 11 in combination with a flexible acetabular cup with which it is to be used and in which the engagement means detach from the body portion, handle and trigger and engage in the cup are located in a sterile package.

1/5




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5





Figure 7




Figure 8




Figure 9




Figure 10




Figure 11

5/5




Figure 12




Figure 13




Figure 14

