



(19) **United States**

(12) **Patent Application Publication**

Reddy et al.

(10) **Pub. No.: US 2002/0041191 A1**

(43) **Pub. Date: Apr. 11, 2002**

(54) **PROGRAMMABLE LOGIC DEVICE WITH HIERARCHICAL INTERCONNECTION RESOURCES**

(75) Inventors: **Srinivas T. Reddy**, Fremont, CA (US); **Richard G. Cliff**, Milpitas, CA (US); **Christopher F. Lane**, Campbell, CA (US); **Ketan H. Zaveri**, San Jose, CA (US); **Manuel M. Mejia**, San Jose, CA (US); **David Jefferson**, San Jose, CA (US); **Bruce B. Pedersen**, San Jose, CA (US); **Andy L. Lee**, San Jose, CA (US)

Correspondence Address:  
**FISH & NEAVE**  
**1251 AVENUE OF THE AMERICAS**  
**50TH FLOOR**  
**NEW YORK, NY 10020-1105 (US)**

(73) Assignee: **Altera Corporation**

(21) Appl. No.: **09/956,748**

(22) Filed: **Sep. 19, 2001**

**Related U.S. Application Data**

(60) Continuation of application No. 09/488,025, filed on Jan. 20, 2000, now patented, which is a continuation of application No. 09/363,162, filed on Jul. 28, 1999, now patented, which is a division of application No. 08/855,192, filed on May 13, 1997, now patented, which is a non-provisional of provisional application No. 60/028,206, filed on Oct. 10, 1996 and which is a non-provisional of provisional application No. 60/037,815, filed on Feb. 5, 1997 and which is a non-provisional of provisional application No.

60/028,207, filed on Oct. 10, 1996said application application number is a continuation of application No. 09/454,624, filed on Dec. 6, 1999, now abandoned, which is a continuation of application No. 08/920,298, filed on Aug. 28, 1997, now patented.

**Publication Classification**

(51) **Int. Cl.<sup>7</sup>** ..... **H03K 19/177**  
(52) **U.S. Cl.** ..... **326/41**

(57) **ABSTRACT**

A programmable logic device has a plurality of super-regions of programmable logic disposed on the device in a two-dimensional array of intersecting rows and columns of super-regions. Horizontal and vertical inter-super-region interconnection conductors are associated with each row and column, respectively. Each super-region includes a plurality of regions of programmable logic, and each region includes a plurality of subregions of programmable logic. Inter-region interconnection conductors are associated with each super-region, principally for bringing signals into the super-region and interconnecting the regions in the super-region. Local conductors are associated with each region, principally for bringing signals into the region. At the super-region level the device may be horizontally and vertically isomorphic, which helps make it possible to produce devices with low aspect ratios of one or nearly one. Shared driver circuits may be provided (e.g., for (1) receiving signals from the subregions and the horizontal and/or vertical conductors, and (2) applying selected received signals to the inter-region conductors, the horizontal and vertical conductors, and possibly also the local conductors). The horizontal and/or vertical conductors may be axially segmented and buffering circuitry may be provided for programmably stitching together axial segments to make longer conductors.





FIG. 1







FIG. 4





FIG. 5






FIG. 7




FIG. 8






FIG. 9





FIG. 10



## PROGRAMMABLE LOGIC DEVICE WITH HIERARCHICAL INTERCONNECTION RESOURCES

[0001] This application claims the benefit of provisional application No. 60/028,206, filed Oct. 10, 1996, provisional application No. 60/028,207, filed Oct. 10, 1996, and provisional application No. 60/037,815, filed Feb. 5, 1997. This is a continuation of application Ser. No. 09/488,025, filed Jan. 20, 2000, which is a continuation of application Ser. No. 09/363,162, filed Jul. 28, 1999 (now U.S. Pat. No. 6,181,160), which is a division of application Ser. No. 08/855,192, filed May 13, 1997 (now U.S. Pat. No. 5,977,793). Application Ser. No. 09/488,025 is also a continuation of application Ser. No. 09/454,624, filed Dec. 6, 1999, which is a continuation of application Ser. No. 08/920,298, filed Aug. 28, 1997 (now U.S. Pat. No. 5,999,016). All of application Ser. Nos. 08/855,192, 08/920,298, 09/363,162, 09/454,624, and 09/488,025 are hereby incorporated by reference herein in their entireties.

### BACKGROUND OF THE INVENTION

[0002] This invention relates to programmable logic devices, and more particularly to programmable logic devices with increased logic and interconnection capability.

[0003] Programmable logic devices are well known as is shown, for example, by Pedersen et al. U.S. Pat. No. 5,260,610, Cliff et al. U.S. Pat. No. 5,260,611, Cliff et al. U.S. Pat. No. 5,689,195, and Cliff et al. U.S. Pat. No. 5,909,126. All of these references are hereby incorporated by reference herein in their entirety.

[0004] There is continued interest in programmable logic devices with greater logic capacity. This calls for devices with larger numbers of regions of programmable logic. It also calls for logic devices with more programmable interconnection resources for making needed connections between the increased numbers of logic regions. It is important, however, to add interconnection resources judiciously so that those resources do not begin to take up excessive amounts of space on the device, thereby unduly interfering with the amount of additional logic that can be included in the device. To accomplish this it would be desirable to find ways to organize programmable logic devices, and especially the interconnection resources in programmable logic devices, so that the efficiency of utilization of the interconnection resources can be greater. In this way more interconnectivity can be provided in the device to serve more logic in the device without simply directly scaling up the interconnection resources with the increased logic capability.

[0005] An example of a possible problem associated with merely scaling up known programmable logic device architectures is illustrated by the case of the architecture shown in above-mentioned Cliff et al. U.S. Pat. No. 5,689,195. In this type of device regions of programmable logic are disposed on the device in a plurality of rows of such regions. Each row has an associated plurality of horizontal interconnection conductors for selectively conveying signals to, from, and between the regions in that row. Region-feeding conductors are associated with each region for selectively bringing signals from the associated horizontal conductors into the region as input signals. Output signals produced by each region are selectively applied to the associated horizontal conductors. Vertical interconnection conductors are

provided for selectively conveying signals between the rows of the device. Accordingly, a programmable logic device having this type of architecture basically comprises a row of logic regions and associated interconnection conductors that has been replicated a number of times and then provided with vertical interconnection conductors for interconnecting the rows. To meet the demand for larger and larger devices it may not be practical to indefinitely increase the number of regions in a row or the number of rows due to manufacturing constraints. For example, the aspect ratio of the device may tend to become too large.

[0006] In view of the foregoing, it is an object of this invention to provide improved organizations ("architectures") for programmable logic devices.

[0007] It is a more particular object of this invention to provide programmable logic device architectures that can efficiently accommodate larger numbers of programmable logic regions.

[0008] It is another more particular object of this invention to provide programmable logic device architectures which permit higher densities of logic regions and which have more uniform horizontal and vertical characteristics so that there is less preference for one direction over the other and therefore less tendency toward designs with high aspect ratios.

### SUMMARY OF THE INVENTION

[0009] These and other objects of the invention are accomplished in accordance with the principles of the invention by providing programmable logic array integrated circuit devices having a plurality of super-regions of programmable logic disposed on the device in a two-dimensional array of intersecting rows and columns of super-regions. Each super-region includes a plurality of regions of programmable logic and a plurality of inter-region interconnection conductors for conveying signals to and between the regions in that super-region. In some embodiments each super-region may be somewhat like a short, folded row in the exemplary devices described in the background section of this specification. For example, in these embodiments the regions in each super-region may be disposed along both sides of that super-region's inter-region interconnection conductors. Thus in these embodiments a super-region may be viewed as a row of regions that is folded back along the associated inter-region interconnection conductors. Each region preferably includes a plurality of subregions of programmable logic. A typical subregion is programmable to perform any of several logical operations on a plurality of input signals applied to the subregion to produce an output signal of the subregion. Programmable logic connectors are associated with the regions for selectively bringing signals from the associated inter-region conductors into the region for use as inputs to the subregions in that region. Other programmable logic connectors selectively apply the subregion output signals to the associated inter-region conductors.

[0010] A plurality of horizontal inter-super-region interconnection conductors is associated with each row of super-regions for selectively conveying signals to, from, and between the super-regions in the associated row. Similarly, a plurality of vertical inter-super-region interconnection conductors is associated with each column of super-regions for selectively conveying signals to, from, and between the

super-regions in the associated column. Programmable logic connectors are provided for selectively applying signals on the horizontal and vertical inter-super-region conductors to the inter-region conductors. Additional programmable logic connectors are provided for selectively applying subregion output signals to the horizontal and vertical inter-super-region conductors. And programmable logic connectors are provided for selectively interconnecting horizontal and vertical inter-super-region conductors.

**[0011]** The architectures of this invention can be made more uniform with respect to the horizontal and vertical axes of the device. These architectures therefore lend themselves more readily to square or nearly square layouts. This is desirable because such layouts have low aspect ratios of one or nearly one. It may also be possible to achieve greater logic densities with the architectures of this invention. The inter-super-region interconnection conductors provide a next level of routing hierarchy (beyond the routing provided at the region and super-region levels). Connectivity within the device is increased by segmenting (and thereby rendering reusable) wiring channels in aligned super-regions. Any necessary interconnections between super-regions are then made using inter-super-region conductors.

**[0012]** Other features that the programmable logic devices of this invention may have are the provision of two types of horizontal and/or vertical inter-super-region interconnection conductors. These are so-called "global" horizontal and/or vertical conductors that extend along the entire length of the associated row or column of super-regions, and so-called "half" horizontal and/or vertical conductors that extend along one of two mutually exclusive halves of the length of the associated row or column of super-regions. The mutual exclusivities mentioned in the preceding sentence are preferred but not absolutely required.

**[0013]** As a possible addition or alternative to providing separate global horizontal and half horizontal conductors, two axially aligned half horizontal conductors can be programmably "stitched" together to provide a global horizontal conductor when such a conductor is needed. Thus it may be possible to omit the dedicated global horizontal conductors. Or it may be preferred to have only global horizontal conductors and no half horizontal conductors. The same options exist with respect to the above-described global vertical and half vertical conductors. The design choices made with regard to the foregoing options may be influenced by the size of the device (e.g., the number of logic subregions, regions, and super-regions on the device).

**[0014]** If stitching of conductors is provided as mentioned in the preceding paragraph, it may be provided by programmable buffers between the conductors being stitched.

**[0015]** The above-mentioned programmable logic connectors for selectively bringing signals from the inter-region conductors into the region may include local conductors that are interleaved between horizontally adjacent regions. The local conductors may be of two types: (1) region-feeding conductors for bringing signals into the adjacent region or regions, and (2) local feedback conductors for making output signals of the region available as inputs to the region and possibly also horizontally adjacent regions. The region-feeding conductors are programmably connectable to the adjacent inter-region interconnection conductors in order to receive signals from the inter-region interconnection conductors.

**[0016]** The above-mentioned programmable logic connectors for (1) applying signals on the horizontal and vertical inter-super-region conductors to the inter-region conductors, (2) applying subregion output signals to the inter-super-region conductors, and (3) selectively interconnecting horizontal and vertical inter-super-region conductors may include drivers which are effectively shared for these various purposes. For example, one or more of these drivers may be associated with each logic subregion. Programmable logic connectors are provided for applying any of several signals to each driver. For example, these signals may include (1) one or more output signals of the associated subregion, (2) one or more global or half vertical conductor signals, and (3) one or more global or half horizontal conductor signals. The output signal of each driver may be programmably connected to (1) one or more global or half horizontal conductors, (2) one or more global or half vertical conductors, (3) one or more inter-region interconnection conductors, and (4) one or more local conductors. These drivers are therefore shared for many purposes such as (1) driving subregion output signals out onto the global and half conductors, as well as onto the inter-region interconnection conductors, (2) making connections between horizontal and vertical conductors, and (3) driving subregion output signals back onto local conductors.

**[0017]** Some of the programmable logic connectors feeding drivers as described in the preceding paragraph (e.g., those programmable logic connectors near the periphery of the device) may also receive signals from input/output ("I/O") pins of the device. This enables the associated drivers to also be used to drive signals from the I/O pins to the destinations mentioned above. Some I/O pins may also have dedicated drivers that programmably feed one or more global or half conductors and/or one or more inter-region interconnection conductors.

**[0018]** Each subregion is fed by multiple inputs. In architectures with local conductors interleaved between horizontally adjacent regions, some of these inputs come from the local conductors to the left of the region that includes that subregion, and some of these inputs come from the local conductors to the right of the region that includes that subregion.

**[0019]** I/O pins along the top, bottom, left, and right sides of the device may programmably select their output and/or output enable signals from one or more of the local conductors adjacent the respective top, bottom, left, or right side of the device.

**[0020]** From the foregoing it will be apparent that the region-feeding local conductors are preferably not directly connected to the global or half conductors. In order to reach a local line, these global or half conductor signals must first be routed through the above-mentioned drivers and also in most cases through inter-region interconnection conductors. This interconnection architecture reduces the number of programmable connections used to connect signals to the local lines.

**[0021]** Some devices may not have dedicated local feedback lines. This saves programmable interconnect which is wasted if the local feedback lines are not used. For these devices, the functionality of the local feedback lines can be achieved by routing signals to the region-feeding conductors (e.g., via the inter-region interconnection conductors). If this

is done, it may be advantageous to make some of the inter-region interconnection conductors span only a very small number of the logic regions, while other inter-region interconnection conductors span larger numbers of the logic regions.

[0022] From the foregoing it will be seen that the interconnection resource architectures of this invention are hierarchical to an increased degree (e.g., from global or half global to inter-region to local). Such architectures help to reduce the area required for a programmable logic device with a given amount of logic capability by decreasing the total number of programmable interconnections required. Such architectures also help to increase the speed of the device by reducing the parasitic loading due to excessive numbers of programmable interconnections.

[0023] Further features of the invention, its nature and various advantages will be more apparent from the accompanying drawings and the following detailed description of the preferred embodiments.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is a simplified plan view of a portion of an illustrative embodiment of a programmable logic device constructed in accordance with the principles of this invention.

[0025] FIG. 2 is a somewhat more detailed, but still simplified, plan view of an illustrative embodiment of a representative portion of the FIG. 1 apparatus in accordance with this invention.

[0026] FIG. 3 is an even more detailed, but still simplified plan view of an illustrative embodiment of a representative portion of the FIG. 2 apparatus in accordance with this invention.

[0027] FIG. 4 is a more detailed, but still simplified, schematic block diagram of an illustrative embodiment of a representative portion of the FIG. 1 apparatus in accordance with this invention.

[0028] FIG. 5 is a simplified block diagram of representative portions of another illustrative embodiment of a programmable logic device constructed in accordance with the invention.

[0029] FIG. 6 is a more detailed, but still simplified, schematic block diagram of a representative portion of FIG. 5.

[0030] FIG. 7 shows a representative portion of FIG. 6 in still more detail, but with some modifications in accordance with this invention.

[0031] FIG. 8 is a schematic block diagram of an illustrative embodiment of circuitry that may be used in programmable logic devices in accordance with this invention.

[0032] FIG. 9 is a simplified block diagram showing an illustrative use of programmable logic devices in accordance with this invention.

[0033] FIG. 10 is another simplified block diagram showing an alternative illustrative use of programmable logic devices in accordance with this invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0034] Various aspects of the invention will first be described with reference to embodiments of the type shown

in FIGS. 1-4. Thereafter, some of these aspects will be further described with reference to embodiments of the type shown in FIGS. 5-8, which also show some additional possible aspects of the invention. Illustrative uses of the programmable logic devices of this invention are described with reference to FIGS. 9 and 10.

[0035] As shown in FIG. 1, an illustrative embodiment of a programmable logic array integrated circuit device 10 constructed in accordance with this invention includes a plurality of super-regions 20 of programmable logic disposed on the device in a two-dimensional array of intersecting rows and columns of super-regions. A plurality of horizontal inter-super-region interconnection conductors 30 is associated with each of the rows, and a plurality of vertical inter-super-region interconnection conductors 40 is associated with each of the columns. The preferred embodiments of the invention take advantage of recent developments in semiconductor fabrication, which allow an additional layer of metal to be provided, by using that additional layer to run conductors 30 and 40 over super-regions 20. This is one way in which the present invention can help increase logic density on device 10. The number of rows and columns (i.e., seven in each case) shown in FIG. 1 is merely illustrative, and any number of rows and columns can be provided as desired. Also, although not shown in FIG. 1, it will be understood that device 10 may additionally include input and/or output pins for connecting device 10 to external circuitry. Such input and/or output pins (generically referred to simply as input/output or I/O pins) may be disposed around the periphery of the device and may be programmably connectable to various ones of conductors 30 and 40. See also the techniques used for input/output connections in FIG. 6.

[0036] It will be understood that terms like "row" and "column", "horizontal" and "vertical", "left" and "right", "upper" and "lower", and other directional or orientational terms are used herein only for convenience, and that no fixed or absolute directions or orientations are intended by the use of these terms. For example, the words in each of the word pairs mentioned above can be reversed if desired.

[0037] An illustrative embodiment of a representative super-region 20 is shown in more detail in FIG. 2. In the FIG. 2 embodiment, super-region 20 includes two rows of regions 50 of programmable logic disposed on respective opposite sides of a plurality of horizontal inter-region interconnection conductors 60. For example, super-region 20 may include eight regions 50 on each side of conductors 60. This embodiment of super-region 20 is therefore somewhat like a row of 16 regions 50 that has been folded in half, back on itself, with the associated interconnection conductors 60 between the two halves of the row.

[0038] An illustrative embodiment of a representative region 50 is shown in more detail in FIG. 3. In the FIG. 3 embodiment, region 50 includes a plurality of subregions 70 of programmable logic. For example, region 50 may include eight subregions 70. Each subregion 70 is programmable to perform any of a plurality of logic functions on input signals 80 applied to the subregion. For example, each subregion 70 may include a programmable four-input look-up table for producing a look-up table output which is any logical combination of the four inputs 80 applied to the subregion. Each region 70 may additionally include a register and

programmable switches for allowing the look-up table output to be selectively registered by the register. The output **90** of the subregion may then be either the registered or unregistered look-up table output. The outputs **90** of the subregions are selectively applied to inter-region conductors **60** via programmable logic connectors ("PLCs") **100**. Although only one PLC **100** connection to a conductor **60** is shown for each output **90** in **FIG. 3**, it will be understood that each output **90** may have such connections to more than one of conductors **60**, if desired. Each output **90** is also fed back within region **50** so that it can be used as an input to any of the subregions **70** in that region.

[0039] Each region **50** also includes a plurality of region-feeding conductors **110** for selectively bringing signals from inter-region conductors **60** into the region. PLCs **120** programmably connect conductors **60** to conductors **110** for this purpose. PLCs **120** may be only partially populated with possible connections (i.e., each of conductors **110** may be programmably connectable to only a subset of conductors **60**). However, the population densities and distributions are preferably such that each conductor **60** has several possible ways into region **50** via conductors **110**.

[0040] PLCs **130** allow the signals on conductors **110** and **90** to be programmably selectively applied to subregion inputs **80**. PLCs **130** may be fully populated or partially populated, as desired. Again, however, if PLCs **130** are only partially populated, the population densities and distributions are preferably such that each conductor **90** and **110** has at least a couple of ways into each subregion **70** via conductors **80**.

[0041] From the foregoing it will be seen that within a super-region **20** the regions communicate with one another via the inter-region conductors **60** of that super-region.

[0042] The illustrative region structure shown in **FIG. 3** is generally like the corresponding portion of the structure shown in above-mentioned Cliff et al. U.S. Pat. No. 5,689,195 (see especially **FIG. 3** of that patent). However, **FIG. 3** is somewhat simplified as compared to the Cliff et al. FIG. It will be understood that, if desired, additional features from the Cliff et al. structure can be included in regions provided in devices of the present invention. Examples of such possible other features are additional conductors for so-called fast lines and/or clock signals, carry and/or cascade interconnections between subregions **70**, register control signals derived from local conductors such as **90** and/or **110**, etc. The detailed structure of subregions **70** can be as shown in **FIG. 8** of the same Cliff et al. reference. Alternatively, subregions **70** can be constructed entirely differently (e.g., as product term logic). Similarly, regions **50** can have a different construction from what is shown in **FIG. 3** and described above. For example, some of the features shown in McClintock et al. U.S. Pat. No. 5,543,732, McClintock et al. U.S. Pat. No. 5,614,840, Cliff et al. U.S. Pat. No. 5,541,530, Leong et al. U.S. Pat. No. 5,592,106, Reddy et al. U.S. Pat. No. 5,694,058, Pedersen U.S. Pat. No. 5,872,463, and Cliff et al. U.S. Pat. No. 5,909,126 can be employed if desired. These additional references are also hereby incorporated by reference herein.

[0043] **FIG. 4** shows an illustrative embodiment of the interconnections between a representative super-region **20** and the horizontal and vertical inter-super-region interconnection conductors **30** and **40** that are associated with the

row and column that include that super-region. It will be understood that each of the circuit paths shown in **FIG. 4** is only representative of several similar circuit paths. For example, although only one PLC **100a** and associated structures **90**, **150**, **152**, and **102a** are shown in **FIG. 4**, multiple groups of such elements are in fact associated with each super-region **20**. The same is true for PLCs **10b**, **170**, and **210** and their associated elements.

[0044] Subregion output signals **90** are applied to certain inputs of PLCs **100a**, **10b**, **170**, and **210**. (PLCs **100a** and **100b** may be subsets of PLCs **100** in **FIG. 3**.) Signals from horizontal inter-super-region conductors **30** can be applied to other inputs of PLCs **100a** by PLCs **150** and conductors **152**. PLCs **100a** select from among the signals they receive and apply the selected signals to conductors **60** via drivers **102**. In this way signals on horizontal inter-super-region conductors **30** can be selectively brought into the super-region.

[0045] Signals from vertical inter-super-region conductors **40** can be applied to other inputs of PLCs **100b** by PLCs **180** and conductors **182**. PLCs **100b** select from among the signals they receive and apply the selected signals to conductors **60** via drivers **102b**. In this way signals on vertical inter-super-region conductors **40** can be selectively brought into the super-region.

[0046] Signals from horizontal inter-super-region conductors **30** can be applied to other inputs of PLCs **170** by PLCs **160** and conductors **162**. PLCs **170** can select these horizontal inter-super-region conductor signals or subregion output signals **90** for application to vertical inter-super-region conductors **40** via drivers **172**. Elements **160**, **170**, and **172** therefore allow signals on horizontal conductors **30** to be applied to vertical conductors **40**. Elements **170** and **172** additionally allow subregion outputs **90** to be applied to vertical conductors **40**.

[0047] Signals from vertical inter-super-region conductors **40** can be applied to other inputs of PLCs **210** by PLCs **200** and conductors **202**. PLCs **210** can select these horizontal inter-super-region conductor signals or subregion output signals **90** for application to horizontal inter-super-region conductors **30** via drivers **212**. Elements **200**, **210**, and **212** therefore allow signals on vertical conductors **40** to be applied to horizontal conductors **30**. Elements **210** and **212** additionally allow subregion outputs **90** to be applied to horizontal conductors **30**.

[0048] **FIG. 4** also shows PLCs **120** and drivers **122** for selectively driving signals on region interconnection conductors **60** into the regions of the super-region (as in **FIG. 3**).

[0049] As described above for PLCs **120**, PLCs **150**, **160**, **180**, and **200** may have full or partial populations of programmable connections from their respective input conductors **30** and **40** to their respective output conductors **152**, **162**, **182**, and **202**. If partial populations are used, the densities and distributions of the programmable connections are preferably such that each input conductor **30** or **40** has several ways to get to PLCs **100a**, **100b**, **170**, and **210**.

[0050] Drivers **102a**, **102b**, **172**, and **212** are preferably programmably controlled tri-state drivers so that more than one such driver can be connected to a conductor **30**, **40**, or **60**. Only one of the drivers connected to a conductor will

typically be active; the other drivers will be tri-stated. Alternatively, all of the drivers **172** and **212** connected to a conductor **30** or **40** may be tri-stated, and the conductor may be used for another purpose (e.g., bringing a signal into the device from an input/output pin of the device).

**[0051]** The output signals of drivers **102a**, **102b**, **172**, and **212** are shown in **FIG. 4** as having fixed (i.e., non-programmable) connections to conductors **30**, **40**, and **60**. This implies that each driver **102a**, **102b**, **172**, and **212** has a fixed output connection to one particular conductor **30**, **40**, and **60**. It will be understood, however, that as an alternative to this construction each driver **102a**, **102b**, **172**, and/or **212** could have programmable connections to one or more of the associated conductors **30**, **40**, and **60**.

**[0052]** The subregion output signals **90** shown in **FIG. 4** can come directly from particular subregion outputs **90** shown in **FIG. 3**. Alternatively, there may be programmable switching between the subregion outputs **90** shown in **FIG. 3** and the inputs **90** shown in **FIG. 4** so that each input **90** in **FIG. 4** can be selected from among several outputs **90** of the type shown in **FIG. 3**.

**[0053]** From the foregoing it will be seen that devices of this invention can be constructed with no significant preferences for communication via horizontal conductors **30** as opposed to vertical conductors **40** or vice versa. For example, there can be the same number of horizontal conductors **30** for each row as there are vertical conductors **40** for each column. There can be the same number of routes of each kind via PLCs **102a** as there are via PLCs **102b**. There can be the same number of routes of each kind via PLCs **172** as there are via PLCs **210**. There is therefore no preference for communication either horizontally or vertically, and if the device is made with approximately the same number of rows and columns, it can be substantially the same in either direction at the level of communication between the super-regions. Devices of this invention can accordingly have the advantage that they are not merely rows of programmable logic that are repeated to make two-dimensional arrays. Rather, they can be truly isomorphic in both directions for purposes of inter-super-region communication. And with the same or approximately the same numbers of rows and columns, devices of this invention can have advantageously low aspect ratios of one or nearly one.

**[0054]** The alternative illustrative programmable logic integrated circuit device **510** shown in **FIG. 5** includes several rows and several columns of super-regions **520** of programmable logic. For example, there may be **20** rows and ten columns of super-regions **520** on device **510**.

**[0055]** Each super-region **520** includes several regions **530** of programmable logic. For example, each super-region **520** may include eight regions **530**.

**[0056]** Each region **530** includes several subregions **540** of programmable logic. For example, each region **530** may include ten subregions **540**. To avoid undue clutter in **FIG. 5**, the subregions **540** are shown individually in only the extreme upper left-hand region **530**.

**[0057]** Each subregion **540** is typically programmable to perform any of several relatively elementary logic operations on input signals applied to that subregion. For example, each subregion **540** may include a four-input look-up table which is programmable to provide any logical

combination of four input signals applied to that subregion. Each subregion **540** may also include a register and associated PLCs for selectively registering the output signal of the look-up table.

**[0058]** A plurality of horizontal inter-super-region interconnection conductors **550** is associated with each row of super-regions **520**. Each group of conductors **550** may include global horizontal conductors (which extend along the entire length of the associated row of super-regions **520**) and half horizontal conductors (which extend along respective left or right halves of the associated row of super-regions **520**). Axially aligned half horizontal conductors **550** may be programmably interconnected by PLCs **552** to effectively make a global horizontal conductor **550**. Depending on such factors as the size of device **510**, dedicated global horizontal conductors may be omitted and sole reliance placed on interconnecting axially aligned half horizontal conductors **550** when a global horizontal conductor is needed. As another alternative, all of conductors **550** may be global and the half horizontal conductors may be omitted.

**[0059]** A plurality of vertical inter-super-region interconnection conductors **560** is associated with each column of super-regions **520**. Like each group of horizontal conductors **550**, each group of vertical conductors **560** may include global vertical conductors (extending along the entire length of the associated column), or half vertical conductors (extending along respective top or bottom halves of the associated column), or both global and half vertical conductors. Axially aligned half vertical conductors **560** may be programmably interconnected by PLCs **562** between those conductors. Although **FIG. 5** shows the vertical conductors **560** associated with each column of super-regions **520** collected together in a single group, it may be preferable to distribute the vertical conductors **570** for each column among the regions **530** in that column as shown in **FIG. 6**.

**[0060]** Each super-region **520** has an associated plurality of inter-region interconnection conductors **570** that extend along the regions **530** in that super-region. Conductors **570** are frequently referred to below as "fractional horizontal" or simply "fractional" conductors.

**[0061]** A representative portion of device **510** is shown in more detail in **FIG. 6**. In particular, **FIG. 6** shows the lower right-hand corner of device **510**. The greatest amount of detail is shown toward the right in **FIG. 6**. Some of that detail is omitted toward the left. **FIG. 6** shows that regions **530** are interspersed with local conductors **580**. These are of two types: (1) region-feeding conductors **580a** and (2) local feedback conductors **580b**. The region-feeding conductors **580a** on each side of each region **530** are programmably connectable by PLCs **572** to the fractional conductors **570** associated with the super-region **520** that includes that region in order to bring signals from the fractional conductors **570** into the adjacent regions. Each subregion **540** has several main input conductors **590**, some of which come from the left and some of which come from the right. For example, each subregion **540** may have four input conductors **590**, two from the left and two from the right. Each of conductors **590** is programmably connectable by PLCs **582** to the local conductors **580** to the left or right of the associated subregion **540**, depending on the direction from which that conductor **590** comes to the subregion.

**[0062]** Each subregion **540** has at least one main output conductor **600**. (In connection with less crowded **FIG. 7** it

will be explained that each subregion **540** preferably has more than one output. But for present purposes it will suffice to show and describe one representative main output conductor **600**.) At least one PLC **610** is associated with each subregion output conductor **600**. The signal on the subregion output conductor **600** is applied to one input terminal of the associated PLC **610**. Other inputs to each PLC **610** are (1) signals from several adjacent global horizontal and half horizontal conductors **550** (brought into the associated region via lateral conductors **552**), and (2) signals from several adjacent global vertical and half vertical conductors **560**. PLCs **610** that are adjacent to horizontal or vertical I/O pins **630** and/or **640** may also have as inputs signals from those I/O pins. In the simplest case each PLC **610** is programmable to select one of its inputs as its output. The output of each PLC **610** is applied to an associated driver **620**.

[0063] The output of each driver **620** can be applied to (1) one or more adjacent global or half horizontal conductors **550** (via PLCs **622**), (2) one or more adjacent fractional horizontal conductors **570** (via PLCs **624**), (3) one or more adjacent global or half vertical conductors **560** (via PLCs **626**), (4) one or more adjacent region-feeding conductors **580a** (via PLCs **628**), and/or (5) local feedback conductors **580b**.

[0064] From the foregoing it will be seen that in addition to providing the paths by which subregion output signals **600** are driven out to conductors **550**, **560**, **570**, and **580**, PLCs **610** and drivers **620** provide the paths by which conductors **550** and **560** can be interconnected, and the paths by which signals on conductors **550** and **560** are brought into the super-regions **520**. For the most part this last-mentioned routing involves communication to the fractional horizontal conductors **570** of each super-region and from the fractional horizontal conductors to the region-feeding conductors **580a** of each region (although it may occasionally be possible to route a signal from a conductor **550** or **560** more directly to a region **530** via the local conductors **580** of that region without making use of the adjacent conductors **570**). This method of routing reduces the number of programmable connections used to connect signals to region-feeding conductors **580a**. In effect, conductors **550** and **560** provide communication between super-regions **520**, while the conductors **570** associated with each super-region provide most of the communication between the regions **530** in that super-region. Local conductors **580** (especially local feedback conductors **580b**) provide most of the communication between the subregions **540** adjacent to those conductors **580**.

[0065] It will be noted that interleaving local conductors **580** between horizontally adjacent regions **530** provides additional local signal routing between the subregions **540** in horizontally adjacent regions **530**. For example, the output signal **600** of a subregion **540** in the middle region **530** shown in FIG. 6 can be applied as an input to a subregion **540** in the right-hand region **530** using only a local conductor **580** and without the need to use a fractional horizontal conductor **570**.

[0066] Local conductors **580** adjacent the edges of device **510** are used as the sources for the output data and output enable signals of I/O pins **630** and **640**. PLCs **584** select the output data signals, and PLCs **586** select the output enable

signals. Each output data signal is applied to the data input terminal of an associated tri-state driver **650**, and each output enable signal is applied to the control input terminal of an associated tri-state driver **650**.

[0067] FIG. 6 shows that some of I/O pins **630** and **640** may have dedicated drivers **632a**, **632b**, **642** that programmably feed one or more conductors **550**, **570**, and **560** via PLCs **634a**, **634b**, and **644**, respectively.

[0068] FIG. 7 shows a representative portion of FIG. 6 in still more detail. However, FIG. 7 also shows that some of the interconnection resources that are included in FIG. 6 can be omitted and their functions performed by other interconnection resources as will now be explained.

[0069] FIG. 7 shows that each subregion **540** may have more than one main output **600**. For example, each of PLCs **610** in FIG. 7 is shown as receiving both the registered and combinatorial output signals of the associated subregion **540**, and there are two such PLCs **610** associated with each subregion. The other inputs to each PLC **610** are as described above in connection with FIG. 6. Although FIGS. 6 and 7 show each PLC **610** receiving inputs **600** from only one subregion **540**, this is not necessarily the case, and each PLC **610** could instead receive inputs **600** from two or more subregions **540** if desired.

[0070] In the embodiment shown in FIG. 7 drivers **620** drive only to conductors **550** (via PLCs **622**), conductors **560** (via PLCs **626**), and conductors **570** (via PLCs **624**). Drivers **620** do not have direct connections to region-feeding conductors **580a**, and local feedback conductors **580b** are entirely omitted. Conductors **580a** therefore serve for both region-feeding and local feedback. Moreover all region-feeding and local feedback signals must also pass through fractional horizontal conductors **570**. Because of the greater number of uses to which conductors **570** are put in this embodiment, it may be desirable to axially segment some of conductors **570**. Each axial segment of such a conductor **570** would extend to only a small number of regions **530** (e.g., one or two regions **530**), while the unsegmented conductors **570** would extend to all the regions **530** in the associated super-region **520**. Eliminating dedicated local feedback conductors **580b** as shown in FIG. 7 saves substantial amounts of local interconnect when local feedback is not needed.

[0071] FIG. 7 also shows that in addition to main outputs **600**, each subregion **540** may have one or more direct connections **700** to adjacent subregions. For example, one of direct connections **700** may be usable for an arithmetic carry out signal from one subregion to another. Another of direct connections **700** may be usable for a cascade connection from one subregion to another. Above-mentioned Cliff et al. U.S. Pat. No. 5,689,195 is exemplary of how carry and cascade connections may be provided and used in programmable logic devices.

[0072] A typical device may include 20 rows of super-regions **520**, with each row having 80 regions **530**. Each region **530** may have ten subregions **540**. Each row may have 480 half horizontal conductors **550** for each half of the row. The device may have a total of 6400 half vertical conductors **560** (40 for each half of each column of regions **530**). A device of this size may not need global horizontal or global vertical conductors. Each super-region **520** may be spanned by 120 fractional horizontal conductors **570**. Each



of these conductors may be programmably connected to two of the region-feeding conductors **580a** in each group of conductors **580a** that it spans. Each group of local lines **580** may include 24 region-feeding conductors **580a** and ten local feedback conductors **580b**. There may be two drivers **620** per subregion **540**. Each of drivers **620** may feed two half horizontal conductors **550**, three fractional horizontal conductors **570**, and one half vertical conductor **560**. Each PLC **610** may be fed by two half vertical conductors **560**, six half horizontal conductors **550**, and two subregion outputs **600**. As has been mentioned in connection with **FIG. 6**, some of PLCs **610** may also be fed by an I/O pin **630** and/or **640**, with each I/O pin typically feeding four different PLCs **610**. A typical device **510** may have **480** I/O pins **630** and **640**.

[0073] It will be understood that the foregoing device size, numbers of interconnection conductors, numbers of PLCs, etc., are only illustrative, and that other sizes and numbers can be used if desired.

[0074] **FIG. 8** shows an illustrative embodiment of a preferred bi-directional buffering circuit **552/562** in accordance with this invention. As the reference number **552/562** suggests, this circuit can be used for programmably connecting two half horizontal conductors **550** as shown at **552** in **FIG. 5**, or for programmably connecting two vertical conductors **560** as shown at **562** in **FIG. 5**.

[0075] Programmable function control element ("FCE") **810** controls the direction of buffering (i.e., whether from the left-hand conductor **550** or **560** to the right-hand conductor **550** or **560** or vice versa). FCE **820** controls segmentation (i.e., whether or not the left- and right-hand conductors **550** and **560** are connected to one another). If FCE **810** is programmed logic 0 and FCE **820** is programmed logic 1, the output of NOR gate **830** is logic 0 and all of transistors **840** and **850** are off, thereby disconnecting the left- and right-hand segments of conductor **550** or **560** from one another. On the other hand, if both of FCEs **810** and **820** are programmed logic 0, then the output of NOR gate **830** is logic 1 and both of transistors **840** are off while both of transistors **850** are on. This allows the signal on left-hand conductor segment **550** or **560** to flow through transistor **850b**, to be amplified by serially connected inverting drivers **860** and **880**, and to then be applied to the right-hand conductor segment **550** or **560** via transistor **850a**. Inverter **870** is a small level-corrector for the circuit. Various forms of the word "amplify" are sometimes used herein and in the appended claims to refer to the signal strengthening and restoration that is performed by buffering circuit elements such as **860** and **880**.

[0076] If FCE **810** is programmed logic 1 and FCE **820** is programmed logic 0, the output of NOR gate **830** is logic 0 and transistors **840** are on while transistors **850** are off. This allows the signal on right-hand conductor segment **550** or **560** to flow through transistor **840b**, to be amplified by drivers **860** and **880**, and to be applied to the left-hand conductor segment **550** or **560** via transistor **840a**.

[0077] Programming both of FCEs **810** and **820** logic 1 produces the same condition as programming FCE **810** logic 1 and programming FCE **820** logic 0.

[0078] From the foregoing, it will be seen that circuit **552/562** is programmable to either (1) electrically isolate the

left- and right-hand conductor segments **550** or **560** from one another, (2) cause the left-hand conductor segment **550** or **560** to drive the right-hand segment via buffering circuit elements **860** and **880**, or (3) cause the right-hand conductor segment **550** or **560** to drive the left-hand segment via the buffering circuit elements.

[0079] Among the advantages of using programmable segmentation buffer circuitry of the type shown in **FIG. 8** is that cutting off an unused conductor segment conserves power that would otherwise be wasted to drive the entire line. Such circuitry also facilitates scaling of programmable logic device architectures by providing a way of buffering long interconnection conductors. Segmentation and buffering reduces the load seen by the drivers (such as **620**) driving the segmented and buffered conductors. This allows driver size and power to be reduced. Segmentation and buffering also improves timing for both corner-to-corner and same quadrant paths, and it improves fitting of logic into programmable logic devices by segmenting global conductors. Circuit **552/562** can be used for segmentation and buffering of conductors of any kind and length, not just the half horizontal and half vertical conductors that are specifically mentioned above.

[0080] Those skilled in the art will appreciate that the programmable logic devices of this invention have many possible uses. For example, **FIG. 9** illustrates use of a programmable logic device **1002** of this invention in a digital processing system **1000** including other digital components such as processing unit **1004**, memory **1006**, input device or circuitry **1008**, and output device or circuitry **1010**. System **1000** may be any computer or computer-like system with the addition of programmable logic device **1002** to perform any desired functions of or for the system. For example, programmable logic device **1002** may be programmed from memory **1006** under the control of processing unit **1004**. Thereafter, programmable logic device **1002** may operate under the control of processing unit **1004** on data or other signals supplied from processing unit **1004**, memory **1006**, and/or input **1008** in order to produce output data or other signals that are applied to processing unit **1004**, memory **1006**, and/or output **1010**. Processing unit **1004** may be a general-purpose processor (e.g., a microprocessor), as is typical if processor **1004** is the processor of a general-purpose computer system that includes programmable logic device **1002**. Alternatively, processing unit **1004** may be any special-purpose circuitry for performing or controlling any particular functions or tasks. The various components and interconnections shown in **FIG. 5** are only illustrative. Various ones of these components and interconnections can be omitted if desired. Similarly, additional components and interconnections can be included if desired. For example, input **1008** and output **1010** could be combined into one input/output device or circuit. Any suitable technologies can be used for any of components **1004**, **1006**, **1008**, and **1010**.

[0081] **FIG. 10** shows that the programmable logic devices of this invention (e.g., device **1002**) can be mounted on a printed circuit board **1020**, possibly with other circuitry (e.g., of the various types shown in **FIG. 9**). In a printed circuit board implementation of **FIG. 9** type circuitry, input device or circuitry **1008** from **FIG. 9** is likely to be embodied as input interface circuitry **1008'** for use in making connections to external input devices and/or circuits (not shown). Similarly, output device or circuitry **1010** from

**FIG. 9** is likely to be embodied as output interface circuitry **1010'** for use in making connections to external output devices and/or circuits (not shown). In other respects the components and connections shown in **FIG. 10** may be similar to the corresponding components and connections shown in **FIG. 9**. Again, various components and connections shown in **FIG. 10** can be omitted from circuit board **1020** if desired, and/or other components and connections can be added to that board.

**[0082]** Various technologies can be used to implement programmable logic devices employing the super-regions, regions, and subregions of this invention, as well as the various components of those super-regions, regions, and subregions (e.g., the PLCs and the programmable function control elements ("FCEs") which control the PLCs). For example, each PLC can be a relatively simple programmable connector such as a switch or a plurality of switches for connecting any one of several inputs to an output. Alternatively, each PLC can be a somewhat more complex element which is capable of performing logic (e.g., by logically combining several of its inputs) as well as making a connection. In the latter case, for example, each PLC can be product term logic, implementing functions such as AND, NAND, OR, or NOR. Examples of components suitable for implementing PLCs are EPROMs, EEPROMs, pass transistors, transmission gates, antifuses, laser fuses, metal optional links, etc. As has been mentioned, the components of PLCs can be controlled by various, programmable, function control elements ("FCEs"). (With certain PLC implementations (e.g., fuses and metal optional links) separate FCE devices are not required.) FCEs can also be implemented in any of several different ways. For example, FCEs can be SRAMs, DRAMs, first-in first-out ("FIFO") memories, EPROMs, EEPROMs, function control registers (e.g., as in Wahlstrom U.S. Pat. No. 3,473,160), ferro-electric memories, fuses, antifuses, or the like. From the various examples mentioned above it will be seen that this invention is applicable to both one-time-only programmable and reprogrammable devices.

**[0083]** It will be understood that the foregoing is only illustrative of the principles of this invention and that various modifications can be made by those skilled in the art without departing from the scope and spirit of the invention. For example, the number of rows and columns of super-regions can be varied. Similarly, the number of regions in each super-region can be varied, as can the number of subregions in each region. The numbers of the various types of interconnection resources such as PLCs **100**, **120**, **150**, **160**, **170**, **180**, **200**, **210**, **572**, **582**, **610**, **622**, **624**, and **626**, drivers **102**, **172**, **212**, and **620**, etc., can all be varied as desired. Various types of programmable logic can be used in the subregions, and various technologies can be used for the PLCs and other elements of the device, all as suggested above.

The invention claimed is:

1. A programmable logic device comprising:

- a plurality of super-regions of programmable logic arranged in a two-dimensional array of rows and columns, each super-region comprising:

- regions of programable logic, each region comprising a plurality of subregions of programmable logic, each subregion programmable to perform a logic operation on an input signal applied to each subregion;

- an inter-region interconnection conductor;

- at least one region feeding conductor;

- a first programmable logic connector configured to selectively interconnect a region feeding conductor and the inter-region interconnection conductor;

- at least one input conductor wherein:

- each input conductor is associated with at least one subregion;

- each input conductor is selectively interconnected to a region feeding conductor by a second programmable logic connector; and

- each input conductor is configured to convey a signal from the region feeding conductor to an associated subregion;

- a first local feedback conductor associated with each subregion configured to convey an output signal from each subregion so that the output signal is available for programmable application as an input signal to another subregion in the associated region; and

- a second local feedback conductor associated with each subregion configured to convey the output signal to the inter-region interconnection conductor;

- a plurality of horizontal inter-super-region interconnection conductors associated with each of the rows of super-regions wherein each horizontal inter-super-region interconnection conductor is programmable to couple any super-region in the associated row to another super-region in the associated row;

- a plurality of vertical inter-super-region interconnection conductors associated with each of the columns of super-regions wherein each vertical inter-super-region interconnection conductor is programmable to couple any super-region in the associated column to another super-region in the associated column; and

- a first plurality of programmable logic connectors configured to selectively interconnect the horizontal and vertical inter-super-region interconnection conductors.

2. The programmable logic device of claim 1 further comprising a second plurality of programmable logic connectors configured to selectively apply a signal on the inter-region interconnection conductors associated with a super-region directly to a subregion of the super-region as the input signal.

3. The programmable logic device of claim 1 further comprising a third plurality of programmable logic connectors configured to selectively apply a signal on the inter-super-region interconnection conductors to an inter-region interconnection conductor.

4. The programmable logic device of claim 1 further comprising a fourth plurality of programmable logic connectors configured to selectively apply a signal on the inter-super-region interconnection conductors to a subregion in a super-region as the input signal.

5. The programmable logic device of claim 1 wherein each subregion may include a four-input look-up table.

6. The programmable logic device of claim 5 wherein the four-input look-up table is programmable to provide any logical combination of four input signals applied to that subregion.

7. The programmable logic device of claim 1 wherein each subregion may include a register and at least one associated programmable logic connector for selectively registering the output signal of the look-up table.

8. The programmable logic device of claim 1 wherein the inter-region interconnection conductor extends along the regions in the associated super-region.

9. The programmable logic device of claim 1 wherein the regions are disposed on either side of the inter-region interconnection conductor.

\* \* \* \* \*