



(86) 1993/09/20

(87) 1994/04/14

(45) 2001/05/29

(72) Hickerson, William, US

(73) CURTISS-WRIGHT FLIGHT SYSTEMS, INC., US


(51) Int.Cl.⁶ B25B 28/00

(30) 1992/09/29 (07/952,688) US

(30) 1993/07/20 (08/094,502) US

(54) **OUTIL DE SAUVETAGE**

(54) **RESCUE TOOL**



(57) A light weight, quiet and emergency safe, portable "jaws of life" spreading tool (10) actuated by an electric motor (13). Full high torque at any position, with selectable spreading or cutting motions under high loads is achieved by the use of a rotary, multiple stage, speed reducing gearbox driven by the motor. The gearbox contains an input stage (14) from the electric motor running on a 12 volt DC power supply, and a compound planetary output stage (18). The arms or jaws (12a, 12b) of the device are separately driven by the planetary or spindle gears and, for convenience, are attached to external rings on the gears, by heavy duty pins (30). The arms or jaws are removable for interchanging between cutting and spreading configurations, or replacement with general purpose arms capable of both cutting and spreading operations.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 :

B66F 3/00

A1

(11) International Publication Number:

WO 94/07788

(43) International Publication Date:

14 April 1994 (14.04.94)

(21) International Application Number: PCT/US93/08914

(22) International Filing Date: 20 September 1993 (20.09.93)

(30) Priority data:

07/952,688

29 September 1992 (29.09.92)

US

08/094,502

20 July 1993 (20.07.93)

US

(71) Applicant: CURTISS-WRIGHT FLIGHT SYSTEMS, INC. [US/US]; 300 Fairfield Road, Fairfield, NJ 07004 (US).

(72) Inventor: HICKERSON, William ; 37 Big Springs Road, Hardyston Township, NJ 07419 (US).

(74) Agent: KLAUBER, Stefan, J.; Klauber & Jackson, Continental Plaza, 4th Floor, 411 Hackensack Avenue, Hackensack, NJ 07601 (US).

(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

With amended claims.

2145754

(54) Title: RESCUE TOOL



(57) Abstract

A light weight, quiet and emergency safe, portable "jaws of life" spreading tool (10) actuated by an electric motor (13). Full high torque at any position, with selectable spreading or cutting motions under high loads is achieved by the use of a rotary, multiple stage, speed reducing gearbox driven by the motor. The gearbox contains an input stage (14) from the electric motor running on a 12 volt DC power supply, and a compound planetary output stage (18). The arms or jaws (12a, 12b) of the device are separately driven by the planetary or spindle gears and, for convenience, are attached to external rings on the gears, by heavy duty pins (30). The arms or jaws are removable for interchanging between cutting and spreading configurations, or replacement with general purpose arms capable of both cutting and spreading operations.

RESCUE TOOLFIELD OF THE INVENTION

5 This invention relates to portable devices which deliver spreading or cutting motion under high loads and particularly those devices used for emergency rescue conditions and commonly referred to as "Jaws of Life" (registered trademark) type devices.

10

BACKGROUND OF THE INVENTION

Rescue tools known as "Jaws of Life" type devices are specialized tools used by various rescue personnel such
15 as police, firemen, paramedics generally for the purpose of extricating accident victims from vehicles whose exits have been rendered inoperable. These tools require spreading and closing forces for opening or ripping apart inoperable doors or for cutting through relatively thick
20 metal layers. Pushing and pulling forces of 7,000 to 15,000 pounds at the tips are considered to be normal for the proper operation of such tools. In the past, in order to achieve such high forces, the tools have been almost exclusively hydraulic and powered by gasoline engines,
25 for example as described in U.S. Patent No. 4,842,249.

With self contained hydraulic and gasoline units the tools were sufficiently portable for use under adverse conditions commonly encountered with the rescue of
30 accident victims. Nevertheless, many "portable" units weigh in excess of 200 pounds and/or require at least two persons for operation or transport, since many "portable" units have separated powering and operation units.

35 Some tools, such as described in U.S. Patent No. 4,896,862 are designed as separate jaw elements for use with various available powered inputs such as a pneumatic or hydraulic pumps or electric motors which drive

threaded actuating elements. Though described as being powered with an electric motor, most devices are powered by gasoline or other fuel operated devices which provide the requisite driving power in a portable fashion. Electric power sources are not readily available in most emergency situations and portable batteries have not been considered capable of providing the requisite torque for effective operation of such devices.

As a result of the widespread use of hydraulic systems with fuel operated powering, as a general proposition, many of the existing tools also require constant costly maintenance of various components in order to maintain effectiveness.

Major drawbacks for most hydraulic system tools include their inability to generate full tip spreading force upon initial spreading application, the position at which such forces are needed most. Gasoline powered hydraulic devices are also very noisy and because of fuel containment exigencies, require special transport compartments. Other severe drawbacks include their detrimental susceptibility to environmental conditions including explosive atmospheres and inclement weather. A gasoline powered unit is dangerous to operate under many accident conditions wherein the speed required in the rescue is that of saving a victim from imminent harm in spreading flames.

2a

SHORT DESCRIPTION OF THE INVENTION

The present invention seeks to provide a low maintenance, relatively inexpensive, safely operable, quiet, light weight, portable, battery powered "jaws of life" spreading and cutting rescue device having full spreading power in all positions.

The present invention further seeks to provide such portable battery powered rescue device having a rotary, multiple stage, speed reducing (torque increasing) gearbox.

Still further the present invention seeks to provide such rescue device with a compound planetary output stage which provides operational forces comparable to existing hydraulically operated rescue devices.

The present invention also seeks to provide such rescue device with replaceable arms which can be of cutting, spreading, or general use configuration as desired.

In accordance with one aspect of the invention there is provided a light weight portable rescue device having spreading arms for delivering a rotational spreading motion under very high loads, comprising a portable heavy duty motor, and means for converting the output of the motor to a low controllable speed and high torque to at least one of said spreading arms, wherein said means for converting the

output of the motor to a low controllable speed and high torque to at least one of said spreading arms comprises a rotary multiple stage gear box having a compound planetary output stage.

In accordance with another aspect of the invention there is provided a light weight portable rescue device having two arms which deliver rotational motion, therebetween, under very high loads, said rescue device comprising a portable heavy duty electric motor, and gear means for converting the output of the motor to a low controllable speed and high torque to at least one of said arms.

In accordance with still another aspect of the invention there is provided a light weight portable rescue device having two arms which deliver rotational motion, therebetween, under very high loads, said rescue device comprising a portable heavy duty motor, and gear means for converting the output of the motor to a low controllable speed and high torque to at least one of said arms, wherein said device further comprises means for providing said high torque to at least one of said arms wherein said rotational motion is in a direction wherein said arms move toward each other and said device further comprises means for providing said high torque to at least one of said arms wherein said rotational motion is in a direction wherein said arms move away from each other.

3a

In accordance with yet another aspect of the invention there is provided a light weight portable rescue device having two arms for delivering a rotational motion between said arms under very high loads, comprising a portable heavy duty motor, and gear means for converting the output of the motor to a low controllable speed and high torque to at least one of said arms, with said arms being replaceably removable from said device, and wherein said device further comprises means for providing said high torque to at least one of said arms wherein said rotational motion is in a direction wherein said arms move toward each other and said arms comprise cutting means and said device further comprises means for providing said high torque to at least one of said arms wherein said rotational motion is in a direction wherein said arms move away from each other and wherein the arms comprising cutting means are replaced with arms comprising spreading means.

These and other objects, features and advantages will become more evident from the following discussion and the drawings in which:

3b

SHORT DESCRIPTION OF THE DRAWINGS

Figure 1 is an isometric view of one embodiment of the device of the present invention with an in-line gear driving motor;

Figure 2 is an isometric partial cutaway of the planetary gear arrangement in the embodiment of Figure 1.

Figures 3 and 4 are right and left side views of a second embodiment of the device of the present invention with a motor parallel to the gearing and with a pulley drive;

Figure 5 is a top cutaway view of the device shown in Figures 3 and 4 showing the drive and torque increasing gear system;

Figure 6 is a side view of the arm attachment pin; and

Figure 7 is a top view showing the handle attachment in the various embodiments.

Figure 8 is an exploded view of the embodiment of Figures 3-5 showing the removable arms and pin attachments;

Figure 9 is a side view of the device of the present invention having arms configured with cutting blades; and

Figure 10 is a side view of the device of the present invention having combination serrated cutting blade and expanding elements.

DETAILED DESCRIPTION OF THE INVENTION

15

Generally the present invention comprises a truly light weight portable rescue device of the "Jaws of Life" type having arms which will quietly deliver cutting and/or spreading motions under very high loads and in any arm position. The device comprises a portable heavy duty motor, such as a motor utilized in operating portable winches, which is most preferably powered by a DC power supply such as typical 12 volt DC vehicle batteries. The output of the motor is converted to a low controllable speed and high torque by a rotary multiple stage gear box having a compound planetary output stage. The geared output permits the effective utilization of portable battery powering for use in a "Jaws of Life" type device.

30 In addition, the geared output permits high torque in all directions, thereby effectively providing a high torque drive for both spreading (outwardly moving arms) and cutting (inwardly moving arms). As a result, the device of the present invention is effectively operable with interchangeable cutting and spreading arms, or even combination cutting and spreading arms in a single drive unit. This is in marked contrast to many "Jaws of Life"

35

2145754

5

type devices, such as with piston driven spreaders, e.g. as described in US Patent No. 4,333,330; or other spreader devices which use screw gears or hydraulics, which provide a maximum torque in only one direction.

- 5 The gear box comprises a sun gear which is driven by the motor and planetary spindle gears driven by the sun gear. The output stage of the planetary spindle gears is connected to one or more of the spreading (or cutting) arms which emanate from a common vertex via ring gears
10 and ring lugs. Because of the rotary output, the drive direction is easily reversed for selective cutting or spreading operations.

- For safe operation it is preferred that the self
15 contained electric motor be of an explosion proof type and that a fail-safe, electrically off, brake be interposed between the motor input and the geared output. Since the device is electrically powered by a vehicle battery there is no ignitable fuel and the tool is
20 relatively safe for most rescue operations. The only maintenance required is periodic gear lubrication and even this can be dispensed with in a closed, self lubricating system.

- 25 Actuators, including gear boxes which have arms that extend from rotating ring gears of planetary gear systems and which are useful in the present invention, include those utilized in positioning aircraft flight control surfaces. Such actuators are disclosed in U.S. Patent
30 Nos. 4,721,016; 4,742,730; 4,825,723; and 5,120,285 as well as U.S. Patent Nos. 5,106,354 which discloses a gear system designed for specific use in folding aircraft wings.

- 35 For ease and precision in operation, the device is provided with a large handle for stable two hand control and the handle is provided with a power switch for

2145754

6

actuating of the arms in either the arms spreading (ripping) or arm closing (cutting or snipping) modes. The planetary gears drive ring gears with external ring lugs which are attached to the appropriate arms (high strength spreaders, sharpened cutters, combination spreaders and cutters, and the like) via removable pins. This provides the rapid ability to tailor the rescue tool to the particular situation. Either both arms are moved away from an original position or more preferably for simplified construction, one arm is fixed in position on the housing of the device and the other arm moves relative thereto.

A particularly desirable configuration for the geared torque increasing means is a compound planetary containing gearbox comprised of floating planet gears which eliminate the conventional carrier and planet support bearings.

Since the power supply (a 12 volt DC battery) is available in nearly any vehicle, and separable from the device, the present invention is truly lightweight (typically, with a weight of about thirty pounds as compared to common devices weighing in excess of 200 pounds and which require two people for operation) and substantially more portable than those of the prior art, with effective utilization by one person. Since the device carries no fuel it is also easily transported without the specialized carriers necessary with gasoline powered hydraulic equipment. In addition, the device is nearly as safe as simple mechanically operated tools under inclement conditions.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

35

With specific reference to the drawings, the embodiment shown in Figure 1 depicts a rescue device 10 of the

2145754

7

present invention, which, with spreading arms 12a and 12b having flat opposing surfaces, is specifically designed for ripping open or spreading operations. The spreading arms 12a and 12b, because of the high stress forces placed on them, are comprised of high strength tool steel and are apertured to reduce weight. The spreading tips of arms 12a and 12b are solid and stepped for appropriate selective placement in correspondingly sized openings.

Heavy duty explosion proof motor 13, is powered by a 12 volt DC battery such as a vehicle battery (not shown) via power cable 9. The motor 13 directly drives the gearbox shown in Figure 2. Input gears 14 translate rotary movement from motor 13, to turn sun gear 17. Centrally positioned sun gear 17 in turn causes rotation of planetary spindle gears 18 to drive ring gears 19, thereby providing the requisite high torque movement of arm 12a relative to fixed arm 12b. Arm 12a is removably attached to the pair of ring gear lugs 19a and arm 12b is removably attached to the pair of lugs 19b affixed to housing 32. Both arms 12a and 12b are attached by removable pins 30 (more clearly seen in Figure 6) to the driving ring gear lugs 19a and housing lugs 19b respectively, whereby they can be removed and replaced with other arms such as cutting arms, suitable for particular rescue situations. Figure 8 depicts an exploded view of the device of Figure 5, showing the relative removable placement of the pins 30, gear lugs 19a and 19b and the arms 12a and 12b. Arms 120a and 120b, shown in Figure 9, exemplify cutting arms with curved blade surfaces 121a and 121b respectively. Arms 220a and 220b, shown in Figure 10, provide maximum general utility with serrated cutting blades 221a and 221b and spreading or ripping tips 222a and 222b.

The pins 30 comprise heavy duty machined steel rods with carrying ring 30a and reusable cotter type closing clip

30b.

The device is gripped with two hands placed on full length handle 11 (more clearly seen in Figure 7). Handle 11 is affixed to adjacent walls of housing 32 to provide for better control in handling. The handle 11 also contains a trigger switch (not shown) for discriminately turning the device on and off. A second switch (not shown) permits selective change of gear drive direction, whereby the direction of the arm movement is changed according to whether the arms are of a cutting or spreading configuration, or with general utility arms, according to the desired operation. Vinyl grips 11a and 11b facilitate the gripping.

15

Arm 12b is forked and is attached to housing lugs 19b and does not move during operation. Arm 12a is attached to lugs 19b of the ring gears 19, driven by the planetary output drive gears 18, whereby the spreading forces are concentrated on arm 12a and the relative movement between the arms 12a and 12b. Arm 12a fits within the fork of arm 12b, whereby they nest together in the adjacent closed position.

25 In the second embodiment shown in Figures 3-5, the device 10' is shown with a pulley drive 15, as opposed to the direct input gear drive shown for the embodiment of Figures 1 and 2. This permits a more compact design without the outward extension of the motor.

30

In this second embodiment, the arms 12a' and 12b' are shown in closed nested position, the initial spreading position. Arm 12b' is attached to the housing via lugs 29b and pin 30. Arm 12a' is attached to the driving ring gears 29 via ring gear lugs and pin 30.

In operation, as shown in Figure 5, motor 13' drives

2145754

shaft 13a' through safety fail safe brake 31 and pulley 15a. Pulley belt 15b, connecting pulleys 15a and 15c, in turn drives gear pulley 15c, which is attached to sun gear 16 for rotational power input to sun gear 17'. Sun gear 17', as with the embodiment shown in Figures 1 and 2, drives the multiple planetary gears of spindle gears 18'. As before, the planetary gears drive ring gears 29 for rotary movement of the attached arm 12a'. The gearing of the sun gear 17' and spindle gears 18' causes a reduction in rotational speed with an increase in torque which is transmitted to the moving arm 12a'.

The full torque forces, in excess of 7500 pounds, at the tips of the arms 12a' and 12b' are immediately available for ripping closed doors and the like from narrow confined areas without the necessity of separately providing starter openings.

For maintenance, grease fitting 33 is provided for periodic lubrication of gear box 20.

It is understood that the above description and drawings exemplify the present invention and that details contained therein are not to be construed as limitations on the present invention. Changes may be made such as in the geometry, dimensions, interrelation and types of elements without departing from the scope of the present invention as defined in the following claims.

2145754

10

WHAT IS CLAIMED IS:

1 1. A light weight portable rescue device having spreading
2 arms for delivering a rotational spreading motion under
3 very high loads, comprising a portable heavy duty motor,
4 and means for converting the output of the motor to a low
5 controllable speed and high torque to at least one of
6 said spreading arms, wherein said means for converting
7 the output of the motor to a low controllable speed and
8 high torque to at least one of said spreading arms
9 comprises a rotary multiple stage gear box having a
10 compound planetary output stage.

1 2. The light weight portable rescue device of claim 1,
2 wherein said portable heavy duty motor is an electric
3 motor capable of being powered by an electric battery,
4 and wherein said multiple stage gear box comprises a sun
5 gear, driven by the output of the motor, and two or more
6 planetary gears driven by said sun gear to provide said
7 compound planetary output to said at least one spreading
8 arm to effect said rotational spreading motion between
9 the spreading arms.

1 3. The light weight portable rescue device of claim 2,
2 wherein said planetary gears drive ring gears with said
3 compound planetary output, and wherein said ring gears
4 are removably attached to said at least one spreading
5 arm.

1 4. The light weight portable rescue device of claim 3,
2 wherein said device further comprises a housing for said
3 gear box and wherein one of said spreading arms is
4 removably attached to said housing.

1 5. The light weight portable rescue device of claim 4,
2 wherein the spreading arm, attached to the housing,
3 comprises a forked base, with said forked base being

29 SEP 1994

4 attached to the housing and wherein a spreading arm,
5 attached to a ring gear, is movably rotationally
6 positioned within the forked base.

1 6. The light weight portable rescue device of claim 5,
2 wherein said device further comprises one or more input
3 gears between the output of said motor and the sun gear
4 to effect the driving of the sun gear.

1 7. The light weight portable rescue device of claim 1,
2 wherein said device further comprises offset torque
3 transmission drive means.

1 8. The light weight portable rescue device of claim 7,
2 wherein said offset torque transmission drive means
3 comprises a motor pulley, a sun gear pulley and a drive
4 belt therebetween, with said motor rotationally driving
5 said motor pulley with said motor output, and said sun
6 gear pulley being affixed to a shaft of said sun gear.

1 9. The light weight portable rescue device of claim 8,
2 wherein said motor and said sun gear are substantially
3 parallel to each other.

1 10. The light weight portable rescue device of claim 8,
2 wherein said spreading arms have free ends which comprise
3 coextensive tips and wherein said tips are
4 correspondingly stepped to permit firm grip on jagged
5 metal and for creating wedge shaped openings.

1 11. The light weight portable rescue device of claim 10,
2 wherein said spreading arms are comprised of tool steel.

1 12. A light weight portable rescue device having two arms
2 which deliver rotational motion, therebetween, under very

29 SEP 1994

3 high loads, said rescue device comprising a portable
4 heavy duty electric motor, and gear means for converting
5 the output of the motor to a low controllable speed and
6 high torque to at least one of said arms.

1 13. The light weight portable rescue device of claim 12,
2 wherein said portable heavy duty motor is an electric
3 motor capable of being powered by an electric battery.

1 14. A light weight portable rescue device having two arms
2 which deliver rotational motion, therebetween, under very
3 high loads, said rescue device comprising a portable
4 heavy duty motor, and gear means for converting the
5 output of the motor to a low controllable speed and high
6 torque to at least one of said arms, wherein said device
7 further comprises means for providing said high torque to
8 at least one of said arms wherein said rotational motion
9 is in a direction wherein said arms move toward each
10 other and said device further comprises means for
11 providing said high torque to at least one of said arms
12 wherein said rotational motion is in a direction wherein
13 said arms move away from each other.

1 15. The light weight portable rescue device of claim 14,
2 wherein said arms comprise cutting means for cutting when
3 said rotational motion is in a direction wherein said
4 arms move toward each other and wherein said arms further
5 comprise spreading means for spreading when said
6 rotational motion is in a direction wherein said arms
7 move away from each other.

1 16. A light weight portable rescue device having two arms
2 for delivering a rotational motion between said arms
3 under very high loads, comprising a portable heavy duty
4 motor, and gear means for converting the output of the

5 motor to a low controllable speed and high torque to at
6 least one of said arms, with said arms being replaceably
7 removable from said device, and wherein said device
8 further comprises means for providing said high torque to
9 at least one of said arms wherein said rotational motion
10 is in a direction wherein said arms move toward each
11 other and said arms comprise cutting means and said
12 device further comprises means for providing said high
13 torque to at least one of said arms wherein said
14 rotational motion is in a direction wherein said arms
15 move away from each other and wherein the arms comprising
16 cutting means are replaced with arms comprising spreading
17 means.

1 17. The light weight portable rescue device of claim 16,
2 wherein said portable heavy duty motor is an electric
3 motor capable of being powered by an electric battery.

2145754

1/9




FIG. 1

SUBSTITUTE SHEET

2/9




FIG. 2

2145754




FIG. 3





FIG. 4

5/9



6/9




FIG. 7




FIG. 6

7/9




FIG. 8




FIG. 9

9/9




FIG. 10

