



US009392741B2

(12) **United States Patent**
Kowalchuk et al.

(10) **Patent No.:** **US 9,392,741 B2**
(45) **Date of Patent:** ***Jul. 19, 2016**

(54) **VARIABLE GEOMETRY METER ROLLER**

(71) Applicant: **CNH Canada, Ltd.**, Saskatoon (CA)

(72) Inventors: **Trevor Lawrence Kowalchuk**,
Saskatoon (CA); **Jack Donald Turner**,
Saskatoon (CA); **Gordon Anthony**
Engel, Saskatoon (CA)

(73) Assignee: **CNH Industrial Canada, Ltd.**,
Saskatoon, Saskatchewan (CA)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/095,440**

(22) Filed: **Dec. 3, 2013**

(65) **Prior Publication Data**

US 2014/0083343 A1 Mar. 27, 2014

Related U.S. Application Data

(60) Division of application No. 13/071,812, filed on Mar.
25, 2011, now Pat. No. 8,601,962, which is a
continuation of application No. 13/045,280, filed on
Mar. 10, 2011, now Pat. No. 8,671,857.

(51) **Int. Cl.**

A01C 7/20 (2006.01)
A01C 7/12 (2006.01)
A01C 7/02 (2006.01)
A01C 7/08 (2006.01)

(52) **U.S. Cl.**

CPC . **A01C 7/20** (2013.01); **A01C 7/081** (2013.01);
A01C 7/121 (2013.01); **A01C 7/126** (2013.01);
A01C 7/127 (2013.01)

(58) **Field of Classification Search**

CPC **A01C 7/20**; **A01C 7/00**; **A01C 7/121**;
A01C 7/12; **A01C 7/08**; **A01C 7/127**; **A01C**
7/081; **A01C 7/126**; **A01C 7/712**
USPC 111/178, 177, 171, 170
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,636,897 A	1/1972	Brink
3,790,026 A	2/1974	Neumeister
3,912,122 A	10/1975	Knapp et al.
3,913,798 A	10/1975	Allen
4,473,016 A	9/1984	Gust
5,024,173 A	6/1991	Deckler
5,189,965 A	3/1993	Hobbs et al.
5,549,060 A	8/1996	Schick et al.
5,601,209 A	2/1997	Barsi et al.
5,655,468 A	8/1997	Ledermann et al.
5,924,370 A	7/1999	Gregor et al.
5,947,040 A	9/1999	Gregor
5,996,515 A	12/1999	Gregor et al.
6,240,861 B1	6/2001	Memory
6,598,548 B2	7/2003	Lempriere
6,928,940 B2	8/2005	Soun
7,311,050 B2	12/2007	Eastin et al.
2005/0217551 A1	10/2005	Mayerle
2008/0163807 A1	7/2008	Dean et al.
2009/0314191 A1	12/2009	Friggstad



Primary Examiner — Christopher J Novosad


(74) *Attorney, Agent, or Firm* — Rebecca L. Henkel

(57) **ABSTRACT**

An agricultural metering device with a variable geometry
meter roller is provided. The agricultural metering device
includes a meter roller having a plurality of flutes. An aggre-
gate cross sectional area of the flutes increases along a longi-
tudinal axis of the meter roller.

20 Claims, 6 Drawing Sheets












FIG. 3





VARIABLE GEOMETRY METER ROLLER

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 13/071,812, entitled "Variable Geometry Meter Roller", filed Mar. 25, 2011 which is a continuation of U.S. patent application Ser. No. 13/045,280, entitled "Variable Geometry Meter Roller", filed Mar. 10, 2011, which are both herein incorporated by reference in their entirety.

BACKGROUND

The invention relates generally to metering systems and, more particularly, to a metering device with variable geometry.

Generally, seeding implements are towed behind a tractor or other work vehicle. These seeding implements typically include one or more ground engaging tools or openers that form a seeding path for seed deposition into the soil. The openers are used to break the soil to enable seed deposition. After the seeds are deposited, each opener is followed by a packer wheel that packs the soil on top of the deposited seeds.

In certain configurations, an air cart is used to meter and deliver agricultural product (e.g., seeds, fertilizer, etc.) to ground engaging tools within the seeding implement. Certain air carts include a metering system and air conveyance system configured to deliver metered quantities of product into an airflow that transfers the product to the openers. However, the metering system may include meter rollers with a limited ability to control product flow. For example, some meter rollers may have a uniform geometric shape that does not compensate for a change in product size. With such meter rollers, an undesirable quantity of product may be metered and/or the cross sectional area of the flutes may be insufficient to meter product having large diameter particles. Thus, an operator will typically replace meter rollers when switching between products. Consequently, multiple assembly/disassembly steps may be involved, thereby decreasing productivity and increasing planting costs.

BRIEF DESCRIPTION

In one embodiment, an agricultural metering device includes a meter roller having a plurality of flutes. An aggregate cross sectional area of the flutes increases along a longitudinal axis of the meter roller.

In another embodiment, an agricultural metering device includes a meter roller having a plurality of ridges extending between a first longitudinal end of the meter roller and a second longitudinal end of the meter roller. The metering device also includes a plurality of flutes. Each flute is formed between a pair of adjacent ridges. The metering device includes a cross sectional area of each flute in a plane generally parallel to the first and second longitudinal ends which increases along a longitudinal axis of the meter roller.

In another embodiment, an agricultural metering device includes a meter roller. The meter roller includes a first longitudinal end, a second longitudinal end, and a longitudinal passage extending through the meter roller from the first longitudinal end to the second longitudinal end. The longitudinal passage is configured to receive a drive shaft. The meter roller also includes a plurality of flutes extending between the first and second longitudinal ends. A cross sectional area of

each flute in a plane generally parallel to the first and second longitudinal ends increases along a longitudinal axis of the meter roller.

DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

FIG. 1 is a side view of an air cart having a metering system that may utilize a variable geometry meter roller;

FIG. 2 is a schematic diagram of an exemplary metering system which may be employed within the air cart of FIG. 1;

FIG. 3 is a perspective view of an embodiment of a metering system with meter rollers having a parallel rotational axis;

FIG. 4 is a cross-sectional side view of a meter box of the metering system of FIG. 3;

FIG. 5 is a schematic diagram of another embodiment of a metering system;

FIG. 6 is a top view of an embodiment of a metering system having a meter roller sleeve assembly;

FIG. 7 is a top view of the meter roller sleeve assembly of FIG. 6, illustrating meter roller sleeve adjustment;

FIG. 8 is a perspective view of an embodiment of a meter roller having variable geometry flutes;

FIG. 9 is a cross-sectional side view of the meter roller of FIG. 8, taken along line 9-9; and

FIG. 10 is a cross-sectional side view of the meter roller of FIG. 8, taken along line 10-10.

DETAILED DESCRIPTION

FIG. 1 is a side view of an air cart having a metering system that may utilize a variable geometry meter roller. In the illustrated embodiment, an implement 10 is coupled to an air cart 12 such that the air cart 12 towed behind the implement 10 during operation and transport. The implement 10 includes a tool frame 14 with a ground engaging tool 16. The ground engaging tool 16 is configured to excavate a trench into the soil 18 for seed and/or fertilizer deposition. In the illustrated embodiment, the ground engaging tool 16 receives product (e.g., seeds, fertilizer, etc.) from a product distribution header 20 via hose 22 extending between the header 20 and the ground engaging tool 16. Although only one ground engaging tool 16, product distribution header 20, and hose 22 are employed within the illustrated embodiment, it should be appreciated that the implement 10 may include additional tools 16, headers 20 and/or hoses 22 in alternative embodiments to facilitate product delivery to the soil 18. As illustrated, the implement 10 includes wheel assemblies 24 which contact the soil surface 18 and enable the implement 10 to be pulled by a tow vehicle.

As previously discussed, the air cart 12 is coupled to the implement 10, and towed behind the implement 10. As will be appreciated, in certain embodiments, the air cart 12 may be towed directly behind a tow vehicle, with the implement 10 towed behind the air cart 12. Likewise, the implement 10 and the air cart 12 may be part of a single unit, or the implement 10 and the air cart 12 may be separate units that are coupled together.

The air cart 12 includes a storage tank 26, a frame 28, wheels 30, a metering system 32, and an air source 34. The frame 28 includes a towing hitch configured to couple to the implement 10 or tow vehicle. In certain configurations, the storage tank 26 includes multiple compartments for storing

various flowable particulate materials. For example, one compartment may include seeds, and another compartment may include a dry fertilizer. In such configurations, the air cart 12 may be configured to deliver both the seeds and fertilizer to the implement 10. Seeds and/or fertilizer within the storage tank 26 are gravity fed into the metering system 32.

In the present embodiment, the metering system 32 includes sectioned meter rollers to regulate the flow of material from the storage tank 26 into an air flow provided by the air source 34. The air flow then carries the material through a hose 36 to the implement 10, thereby supplying the ground engagement tool 16 with seeds and/or fertilizer for deposition within the soil. Although only one hose 36 is included in the illustrated embodiment, additional hoses may be employed in alternative embodiments to transfer product from the air cart 12 to the implement 10.

A control assembly may be communicatively coupled to the metering system 32 and the air source 34 to regulate flow of product to the implement 10. The control assembly may include a spatial locating device, such as a Global Positioning System (GPS) receiver. In such a configuration, the control assembly will receive geographical position information from the GPS receiver, thereby facilitating position determination of the air cart 12. As such, the control assembly may implement "Smart Farming" whereby the metering system 32 is controlled based on the geographical position of the metering system 32, air cart 12, and/or implement 10.

FIG. 2 is a schematic diagram of exemplary metering system which may be employed within the air cart of FIG. 1. As illustrated, the air source 34 is coupled to a conduit 38 configured to enable air 40 to flow past the metering system 32. In other embodiments, the conduit 38 may include multiple conduit sections with one conduit section coupling the air source 34 to the top of the metering system 32 and another conduit section coupling the bottom of the metering system 32 to the implement. In such a configuration, air 40 flows through the metering system 32, from top to bottom. The air 40 enters the metering system 32, combines with the metered product, and exits the metering system 32 as a mixture of product and air.

The air source 34 may be a pump or blower powered by an electric or hydraulic motor, for example. Flowable particulate material 42 (e.g., seeds, fertilizer, etc.) within the storage tank 26 flows by gravity into the metering system 32. The metering system 32 includes a meter roller 44. However, in certain embodiments, more than one meter roller 44 may be configured to regulate the flow of material 42 into the air flow 40. In certain embodiments, the metering system 32 may include multiple meter rollers 44 disposed adjacent to one another along a longitudinal axis of the rollers 44, or in other embodiments, the meter rollers 44 may be positioned so their rotational axes are parallel to one another. For example, certain metering systems 32 include eight meter rollers 44 arranged in a linear configuration. Such systems 32 are known as "8-run" metering assemblies. However, alternative embodiments may include more or fewer meter rollers 44, e.g., 5, 6, 7, 8, 9, or more.

Each meter roller 44 includes an interior passage/cavity 46 configured to receive a shaft that drives the meter roller 44 to rotate. In the illustrated embodiment, the cavity 46 has a hexagonal cross section. However, alternative embodiments may include various other cavity configurations (e.g., triangular, square, keyed, splined, etc.). The shaft is coupled to a drive unit, such as an electric or hydraulic motor, configured to rotate the meter rollers 44. Alternatively, in certain embodiments, the meter rollers 44 may be coupled to a wheel by a gear assembly such that rotation of the wheel drives the meter

rollers to rotate. Such a configuration will automatically vary the rotation rate of the meter rollers based on the speed of the air cart.

Each meter roller 44 also includes multiple ridges 48 and flutes 50. The number and geometry of the flutes 50 are particularly configured to accommodate the material 42 being distributed. The illustrated embodiment includes six flutes 50 and a corresponding number of ridges 48. Alternative embodiments may include more or fewer flutes 50 and/or ridges 48. For example, the meter roller 44 may include 2, 4, 6, 8, 10, 12, 14, 16, 18, 20, or more flutes 50 and/or ridges 48. In addition, the depth of the flutes 50 and/or the height of the ridges 48 are configured to accommodate the material 42 within the storage tank 26. For example, a meter roller 44 having deeper flutes 50 and fewer ridges 48 may be employed for larger seeds, while a meter roller 44 having shallower flutes 50 and more ridges 48 may be employed for smaller seeds. Other parameters such as flute pitch (i.e., rotation relative to a longitudinal axis) and flute angle (i.e., rotation relative to a radial axis) may also be varied in alternative embodiments. Furthermore, in certain embodiments, a meter roller 44 having variable geometry flutes 50 may be employed to accommodate a variety of seed sizes.

For a particular meter roller configuration, the rotation rate of the meter roller 44 controls the flow of material 42 into the air stream 40. Specifically, as the meter roller 44 rotates, material is transferred through an opening 52 in the metering system 32 into the conduit 38. The material then mixes with air from the air source 34, thereby forming an air/material mixture 54. The mixture then flows to the row units of the implement 10 via the pneumatic conduits, where the seeds and/or fertilizer are deposited within the soil. In the present embodiment, the metering system 32 may be deactivated by stopping rotation of the meter rollers 44, thereby substantially blocking the flow of material through the opening 52. Conversely, the metering system 32 may be activated by engaging rotation of the meter rollers 44. In this manner, product flow to the row units may be temporarily suspending while the ground engaging tools are in a non-working position or when product flow from a particular meter roller 44 is undesirable.

FIG. 3 is a perspective view of a metering system 32 with meter rollers having a parallel rotational axis. As illustrated, the metering system 32 includes multiple meter boxes 56 positioned adjacent to one another. In this embodiment, eight meter boxes 56 are included in the metering system 32. However, in other embodiments, 1, 2, 3, 4, 5, 6, 7, 8, 9, or more meter boxes 56 may be employed within the metering system 32. The meter boxes 56 enable product to flow directly to a meter roller (not shown) disposed inside each meter box. Furthermore, a primary distribution hose 58 and a secondary distribution hose 60 extend through each of the meter boxes 56 in a direction generally parallel to the rotational axes of the meter rollers. In alternative embodiments, the distribution hoses 58 and 60 may extend through the meter boxes 56 in a direction generally perpendicular to the rotational axes of the meter rollers.

The distribution hoses 58 and 60 facilitate product flow to the ground engaging tools. In addition, the distribution hoses 58 and 60 enable product to be combined or isolated before flowing to the ground engaging tools. For example, product from one or more meter boxes 56 may flow into the distribution hoses 58, while product from other meter boxes 56 may flow into the distribution hoses 60. In certain embodiments, product from a separate metering system may be delivered to the hoses 58 and/or 60 before the hoses receive product from the meter boxes 56. In this manner, multiple products may be combined within the hoses 58 and/or 60.

5

Each of the meter boxes **56** includes a sprocket **62** coupled to the meter roller (not shown). While substantially uniform sprockets **62** are employed in the illustrated embodiment, it should be noted that alternative embodiments may utilize sprockets that vary in size and/or number of teeth. As such, the rotational speed of each meter roller may be particularly adjusted by selecting a sprocket having a desired size and/or number of teeth. In the illustrated embodiment, the meter rollers are disposed inside the meter boxes **56** and are driven to rotate by the sprockets **62**. Further, the meter rollers are positioned so that their rotational axes are parallel to one another.

In the illustrated embodiment, the metering system **32** includes a drive sprocket **64** and an idler sprocket **66**. The drive sprocket **64**, the idler sprocket **66**, and the sprockets **62** include teeth configured to interface with a chain that drives the sprockets **62** to rotate, thereby rotating the meter rollers. However, it should be appreciated that a pulley/belt arrangement may be employed in alternative embodiments to drive the meter rollers to rotate. In certain embodiments, the chain may be routed from the drive sprocket **64** over the top of an adjacent sprocket **62**, under the bottom of a subsequent sprocket **62**, and then over the top of the next sprocket **62**, and so on, along the length of the metering system **32**. The chain may then extend across the top of the idler sprocket **66**, and loop around to the drive sprocket **64**. In such a configuration, when the drive sprocket **64** is driven to rotate by a drive unit, the chain will drive each sprocket **62** to rotate a respective meter roller. The drive unit may be stopped or started to cause each individual sprocket **62** to rotate. Further, a clutch, such as an electrical or a mechanical clutch, may be positioned between each sprocket **62** and a respective meter roller. The clutch may enable each meter roller to be selectively engaged or disengaged, thereby enabling individual control of each meter roller. Furthermore, the clutches may be configured to provide controlled slippage, thereby enabling the meter rollers to operate at varying speeds relative to one another.

Each of the meter boxes **56** includes a selection bar configured to enable product to be distributed into either distribution hose **58** or **60**. Furthermore, a tube adjustment bar **68** extends out from the metering system **32** and is configured to control the position of the selection bars. For example, in one position, the tube adjustment bar **68** enables product metered in the meter boxes **56** to flow into the primary distribution hoses **58**, while in another position, the tube adjustment bar **68** enables product metered in the meter boxes **56** to flow into the secondary distribution hoses **60**.

FIG. 4 is a cross-sectional side view of a meter box **70** of the metering system of FIG. 3. The meter box **70** includes a roller section **72** and a distribution section **74**. Product enters the roller section **72** and is directed toward the meter roller **44** via a sloped member **76**. The meter roller **44** is positioned within an opening **78** in the meter box **70**, and the meter roller **44** is secured in place and driven by a drive shaft inserted through the cavity **46**. The drive shaft, in turn, is connected to the sprocket **62**, thereby driving the meter roller **44** to rotate as the sprocket is driven by the chain.

The distribution section **74** includes a tube selection assembly **80** to determine whether product flows into the primary distribution hose **58** or the secondary distribution hose **60**. The tube selection assembly **80** includes a selection bar **82** attached to a hinge **84**. Furthermore, the hinge **84** is coupled to the adjustment bar so that movement of the adjustment bar drives the selection bar **82** to rotate in directions depicted by arrows **86**. When the selection bar **82** is in the illustrated position, product from the meter roller **44** flows into the primary distribution hose **58** through an opening **88**.

6

When the selection bar **82** is rotated to the left such that the bar contacts the opposite side of the distribution section housing, product from the meter roller **44** will flow into the secondary distribution hose **60** through an opening **90**. In certain embodiments, the selection bar **82** may be positioned in a central position between the sides of the distribution section housing to enable product to flow from the meter roller **44** into both the primary distribution hose **58** and the secondary distribution hose **60**.

As illustrated by arrow **92**, product enters the meter box **70** through the top of the roller section **72**. The product is directed to the meter roller **44** via the sloped member **76**. As the meter roller **44** rotates, product flows into the distribution section **74**. Depending on the position of the tube selection assembly **80**, product will flow to either or both of the distribution hoses **58** and **60**. Product flowing into to the primary distribution hose **58** along the direction **94** may combine with any other product within the primary distribution hose **58**, and the combined products will flow toward the implement. Likewise, product that flows into the secondary distribution hose **60** along the direction **96** may combine with any other product within the secondary distribution hose **60**, and the combined products will flow toward the implement.

FIG. 5 is a schematic diagram of another embodiment of a metering system **98**. As illustrated, a drive unit **100** is coupled to each meter box **56**. The drive units **100** are configured to individually control the rotation of each meter roller. As will be appreciated, the drive units **100** may be any suitable device that may drive the meter rollers to rotate, such as an electric or hydraulic motor, for example. A controller **102** is coupled to the drive units **100** via a wiring assembly **104**. The controller **102** is configured to send signals to the drive units **100** to selectively engage and disengage rotation of the meter rollers, and to control the speed of meter roller rotation. In such a configuration, the meter rollers may be individually controlled to enable selective meter roller rotation and speed control.

FIG. 6 is a top view of an embodiment of a metering system having a meter roller sleeve assembly **106**. In the illustrated embodiment, meter rollers **44** are disposed within meter roller sleeves **108**. The meter roller sleeves **108** are cup shaped or cylindrical, and are configured to surround at least a portion of the meter rollers **44**. In certain embodiments, the meter roller sleeves **108** may be configured to surround an entire meter roller. As discussed in detail below, the meter roller sleeves **108** may assist in controlling the flow rate of product from the meter rollers **44**. Furthermore, a sleeve adjustment bar **110** is coupled to each of the meter roller sleeves **108** via sleeve adjustment assemblies **112**.

In addition, bar adaptors **114** are coupled to each end of the sleeve adjustment bar **110**. The sleeve adjustment bar **110** and/or the bar adaptors **114** may be adjusted to cause the sleeves **108** to expose more or less of the surface area of the meter rollers **44**. As more of the surface of the meter rollers **44** is exposed, a greater amount of product may be distributed by the meter rollers **44**. Conversely, as less of the surface of the meter rollers **44** is exposed, a smaller amount of product may be distributed by the meter rollers **44**. Thus, the amount of product distributed by the meter rollers **44** may be controlled by adjusting the position of the meter rollers sleeves **108**. As depicted, the meter roller sleeves **108** expose a portion of the meter rollers **44** having a length **116**.

As will be appreciated, certain products may be metered at a low rate, such as canola, for example. Consequently, meter rollers configured to dispense such products may be turned at a very slow rate. Unfortunately, hydraulic drive systems configured to rotate the meter rollers may "stall" if turned too

slowly. However, in the illustrated embodiment, the sleeves **108** may cover a portion of the meter roller **44**, thereby enabling the meter roller to rotate faster, while still metering the appropriate amount of product. The faster turn rate may substantially reduce or eliminate the possibility of stalling the hydraulic drive system. Other products, such as peas or fertilizer, may utilize a faster turn rate, so the meter roller sleeves **108** may be positioned to cover a smaller surface area of the meter roller **44**. Furthermore, the position of the meter roller sleeves **108** may be adjusted, either alone or in conjunction with varying the rotational rate of the meter rollers **44**, to control product flow rate through the metering system.

The meter roller sleeves **108** may enable a metering system to meter a variety of products with a single meter roller configuration, thereby obviating the process of exchanging meter rollers when switching products. For example, an operator may select a particular meter roller configuration (e.g., having a desired flute depth, number of flutes, etc.) to facilitate accurate metering of a particular product. The operator may then remove the current meter roller, and install a new meter roller having the desired properties. Due to the duration of the meter roller replacement process, the implement will spend less time in the field, thereby reducing seeding efficiency. In contrast, because the illustrated embodiment facilitates varying product flow rate by adjusting the position of the sleeves **108** and/or the speed of the meter rollers **44**, a particular meter roller configuration may be utilized to meter a variety of products, thereby increasing the efficiency of seeding operations.

In addition to controlling the collective group of meter roller sleeves **108**, individual meter roller sleeves **108** may be independently adjusted. For example, the sleeve adjustment assembly **112** of a particular meter roller sleeve **108** may be adjusted to cause the meter roller sleeve **108** to cover more or less of the corresponding meter roller **44** than the other meter roller sleeves **108**. Specifically, each meter roller sleeve **108** may be adjusted by rotating the meter roller sleeve **108** about a threaded rod of the sleeve adjustment assembly **112**, thereby extending or retracting the sleeve **108**. Alternatively, the meter roller sleeve **108** may be adjusted by rotating an adjustment bolt of the sleeve adjustment assembly **112**. Such fine tuning may be used to adjust product flow rate to particular groups of row units, thereby compensating for variations in the number of row units per group.

FIG. 7 is a top view of the meter roller sleeve assembly **106** of FIG. 6, illustrating meter roller sleeve adjustment. As illustrated, the sleeve adjustment bar **110** and/or the bar adaptors **114** are coupled to an actuation unit **118**. The actuation unit **118** is configured to move the sleeve adjustment bar **110** and/or the bar adaptors **114** relative to the meter rollers **44**. The actuation unit **118** may be operated via hydraulics, a solenoid, an electromechanical device, or any other type of suitable device configured to provide the desired actuation. Furthermore, the actuation unit **118** enables the meter roller sleeves **108** to be adjusted (i.e., moved back and forth) during operation, such as while planting or fertilizing a field. Specifically, the sleeve adjustment bar **110** may move to expose a length **120** of the meter rollers **44**. As will be appreciated, the sleeve adjustment bar **110** may be moved automatically, such as via the actuation unit **118**, or manually. When the sleeve adjustment bar **110** is moved, each of the sleeves **108** are moved with the bar **110**.

Furthermore, the individual sleeves **108** may be adjusted such that different sleeves **108** cover different portions of the meter rollers **44**. For example, one sleeve **108** may be adjusted via an adjustment assembly **122**, thereby causing the sleeve **108** to expose a portion of the meter roller **44** having a length

124. As illustrated, the length **124** is smaller than the length **120**. However, by adjusting the adjustment assembly **122** in an opposite direction, the length **124** may be greater than the length **120**. Another adjustment assembly **126** may be adjusted to cause the sleeve **108** to expose a length **128** of the meter roller **44**. The length **128** is smaller than the length **124** and the length **120**. However, as previously discussed, the adjustment assembly **126** may be adjusted to cause the length **128** to be greater than the length **120** and/or the length **124**. Further, any of the adjustment assemblies **112** may be adjusted to cause the sleeves **108** to cover a different portion of a respective meter roller **44**. Such adjustments may be made manually, or via individual actuation units that may be attached to each meter roller sleeve **108** to individually fine tune the position of the meter roller sleeves **108**. Each meter roller sleeve **108** may also be used to completely block product flow to a respective meter roller **44** by completely covering the meter roller **44**. Such a complete product shut off may also be performed by either an actuator controlled or manual controlled arrangement.

As discussed in detail below, the meter roller sleeve assembly **106** may employ meter rollers **44** having variable geometry flutes. Such meter rollers **44** may provide increasing displacement along the length of the meter roller **44**. Therefore, the product flow rate may vary non-linearly as the meter roller sleeve **108** covers varying portions of the meter roller **44**.

FIG. 8 is a perspective view of a meter roller **130** having variable geometry flutes. The meter roller **130** includes alternating flutes **132** and ridges **134**. As illustrated, an aggregate cross sectional area of the flutes increases along a longitudinal axis of the meter roller, thereby providing a meter roller having a displacement that varies with axial position. In the illustrated embodiment, each flute twists about the longitudinal axis as the flute extends between first and second longitudinal ends of the meter roller. At a first end **136**, the flutes **132** have a width **138**, while the ridges **134** have a width **140**. Further, at a second end **142**, the flutes **132** have a width **144**, while the ridges **134** have a width **146**. As illustrated, the width **138** of the flutes **132** at the first end **136** is smaller than the width **144** of the flutes **132** at the second end **142**. Conversely, the width **140** of the ridges **134** at the first end **136** is greater than the width **146** of the ridges **134** at the second end **142**.

In the illustrated embodiment, an angle **148** between the flutes **132** and the first end **136** is less than 90 degrees. However, it should be appreciated that in alternative embodiments, the angle **148** may be equal to or greater than 90 degrees. The flutes **132** have a generally arcuate profile, reaching a depth **150**. However, in other embodiments, the flute profile may form other shapes, such as square, triangular, circular, etc. Thus, as illustrated, the meter roller **130** has flutes **132** that expand in width and depth as they extend from the first end **136** to the second end **142**. Furthermore, the meter roller **130** has a longitudinal passage **152** extending between the ends **136** and **142**. The passage **152** enables a drive shaft to be inserted therein to drive the meter roller **130**. Although the opening **152** is depicted with a hexagonal shape, any other shapes may be used, such as triangular, square, pentagonal, etc., may be employed in alternative embodiments.

As will be appreciated, the illustrated meter roller **130** with variable geometry flutes may be combined with a meter roller sleeve as described previously. As such, the meter roller sleeve may enable only a portion of the meter roller **130** to meter product. In such a configuration, the meter roller may be adjusted to efficiently deliver various product sizes. Furthermore, a combination of a meter roller sleeve and the meter

9

roller 130 may enable further control of metering properties, such as metering rates and operating rotations per minute.

FIG. 9 is a cross-sectional side view of the meter roller 130 of FIG. 8, taken along line 9-9. The meter roller 130 has a surface area 154 in a plane generally parallel to the first end. The surface area 154 is the area of the depicted circular cross-section that excludes the aggregate area of the flutes 132 (i.e., the collective sum of each individual area 156 of the flutes 132), and the area of the passage 152. Furthermore, the area 156 of each flute 132 has a width 158 and a depth 160. The depth 160 of each flute 132 varies across the width 158 to create a generally arcuate shape. It should be noted that the width of each ridge 134 is greater than the width 158 of each flute 132.

FIG. 10 is a cross-sectional side view of the meter roller 130 of FIG. 8, taken along line 10-10. The meter roller 130 has a surface area 162. The surface area 162 is the area of the depicted circular cross-section that excludes the aggregate area of the flutes 132 (i.e., the collective sum of each area 164 of the flutes 132), and the area of the passage 152. Furthermore, the area 164 of each flute 132 has a width 166 and a depth 168. The depth 168 of each flute 132 varies across the width 166 to create a generally arcuate shape. It should be noted that each of the ridges 134 has a smaller width than the width 166 of each flute 132.

As will be appreciated, the surface area 162 of the cross-section of FIG. 10 is smaller than the surface area 154 of the cross-section of FIG. 9. In addition, the cross-sectional surface area of the meter roller 130 continuously decreases from the first end to the second end of the meter roller 130. Furthermore, it is noted that the aggregate area of the flutes 132 (i.e., the collective sum of each individual area 164 of the flutes 132) of FIG. 10 is greater than the aggregate area of the flutes 132 of FIG. 9 (i.e., the collective sum of each individual area 156 of the flutes 132). As such, the cross-sectional aggregate area of the flutes 132 continuously increases from the first end to the second end of the meter roller 130. Furthermore, the width 166 and the depth 168 of each flute 132 in FIG. 10 is greater than the width 158 and the depth 160 of each flute 132 in FIG. 9. Thus, the width and the depth of the flutes 132 continuously increases from the first end to the second end of the meter roller 130.

While only certain features of the invention have been illustrated and described herein, many modifications and changes will occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

The invention claimed is:

1. An agricultural metering system, comprising:

a plurality of a meter rollers;

a corresponding plurality of meter roller sleeves, wherein each meter roller sleeve of the plurality of meter roller sleeves is disposed about a respective meter roller of the plurality of meter rollers, and each meter roller sleeve of the plurality of meter roller sleeves moves in operation relative to the respective meter roller to selectively cover a first portion of the respective meter roller during operation of the agricultural metering system and a second portion of the respective meter roller, larger than the first portion, during operation of the agricultural metering system; and

a control bar coupled to the plurality of meter roller sleeves, wherein the control bar collectively moves the plurality of meter roller sleeves in operation relative to the plurality of meter rollers.

10

2. The agricultural metering system of claim 1, wherein each meter roller sleeve of the plurality of meter roller sleeves is configured to move independently relative to the respective meter roller.

3. The agricultural metering system of claim 2, comprising an adjustment assembly extending between each meter roller sleeve of the plurality of meter roller sleeves and the control bar, wherein the adjustment assembly is configured to independently move each meter roller sleeve of the plurality of meter roller sleeves relative to the respective meter roller via rotation of the meter roller sleeve.

4. The agricultural metering system of claim 1, comprising an actuator coupled to the control bar, wherein the actuator is configured to drive the control bar to move the plurality of meter roller sleeves.

5. The agricultural metering system of claim 1, wherein each meter roller of the plurality of meter rollers is configured to provide a product flow rate that varies non-linearly as a function of coverage by a respective meter roller sleeve of the plurality of meter roller sleeves.

6. The agricultural metering system of claim 1, wherein each meter roller sleeve of the plurality of meter roller sleeves moves in operation relative to the respective meter roller along a longitudinal axis of the respective meter roller.

7. The agricultural metering system of claim 1, wherein at least one meter roller sleeve of the plurality of meter roller sleeves is disposed about an entire circumference of the respective meter roller.

8. An agricultural metering system, comprising:

a plurality of a meter rollers;

a corresponding plurality of meter roller covers, wherein each meter roller cover of the plurality of meter roller covers is disposed over at least part of a respective meter roller of the plurality of meter rollers, and each meter roller cover of the plurality of meter roller covers moves in operation relative to the respective meter roller to selectively cover a first portion of the respective meter roller during operation of the agricultural metering system and a second portion of the respective meter roller, larger than the first portion, during operation of the agricultural metering system; and

a control bar coupled to the plurality of meter roller covers, wherein the control bar collectively moves the plurality of meter roller covers in operation relative to the plurality of meter rollers.

9. The agricultural metering system of claim 8, wherein each meter roller cover of the plurality of meter roller covers is configured to move independently relative to the respective meter roller.

10. The agricultural metering system of claim 9, comprising an adjustment assembly coupled to each meter roller cover of the plurality of meter roller covers, wherein the adjustment assembly is configured to move each meter roller cover of the plurality of meter roller covers relative to the respective meter roller via rotation of the meter roller cover.

11. The agricultural metering system of claim 8, comprising an actuator coupled to the control bar, wherein the actuator is configured to drive the control bar to move the plurality of meter roller covers.

12. The agricultural metering system of claim 8, wherein each meter roller of the plurality of meter rollers is configured to provide a product flow rate that varies non-linearly as a function of coverage by a respective meter roller cover of the plurality of meter roller covers.

11

13. The agricultural metering system of claim 8, wherein each meter roller cover of the plurality of meter roller covers moves in operation along a longitudinal axis of the respective meter roller.

14. An agricultural metering system, comprising:
a first meter roller;

a first meter roller sleeve disposed about the first meter roller, wherein the first meter roller sleeve moves in operation relative to the first meter roller to selectively cover a first portion of the first meter roller during operation of the agricultural metering system and a second portion of the first meter roller, larger than the first portion of the first meter roller, during operation of the agricultural metering system; and

a control bar coupled to the first meter roller sleeve, wherein the control bar moves the first meter roller sleeve in operation relative to the first meter roller.

15. The agricultural metering system of claim 14, wherein the first meter roller sleeve moves in operation along a longitudinal axis of the first meter roller.

16. The agricultural metering system of claim 14, comprising a second meter roller and a second meter roller sleeve, wherein the second meter roller sleeve is disposed about the second meter roller, and the second meter roller sleeve moves in operation relative to the second meter roller to selectively cover a first portion of the second meter roller and a second portion of the second meter roller, larger than the first portion of the second meter roller;

12

wherein the control bar is coupled to the second meter roller sleeve, and the control bar collectively moves the first and second meter roller sleeves in operation relative to the first and second meter rollers.

17. The agricultural metering system of claim 16, wherein the first meter roller sleeve moves in operation independently of the second meter roller sleeve relative to the first and second meter rollers.

18. The agricultural metering system of claim 17, comprising an adjustment assembly extending between the control bar and each meter roller sleeve of the first and second meter roller sleeves, wherein the adjustment assembly is configured to independently move the first meter roller sleeve relative to the first meter roller via rotation of the first meter roller sleeve, and the adjustment assembly is configured to independently move the second meter roller sleeve relative to the second meter roller via rotation of the second meter roller sleeve.

19. The agricultural metering system of claim 14, comprising an actuator coupled to the control bar, wherein the actuator is configured to drive the control bar to move the first meter roller sleeve.

20. The agricultural metering system of claim 14, wherein the first meter roller is configured to provide a product flow rate that varies non-linearly as a function of coverage by the first meter roller sleeve.

* * * * *