




US 20130111905A1

(19) **United States**(12) **Patent Application Publication**  
**Pekar et al.**(10) **Pub. No.: US 2013/0111905 A1**(43) **Pub. Date: May 9, 2013**(54) **INTEGRATED OPTIMIZATION AND  
CONTROL OF AN ENGINE AND  
AFTERTREATMENT SYSTEM**(52) **U.S. Cl.**  
USPC ..... 60/686(75) Inventors: **Jaroslav Pekar**, Pacov (CZ); **Daniel  
Pachner**, Praha (CZ)(57) **ABSTRACT**(73) Assignee: **HONEYWELL SPOL. S.R.O.**, Prague  
(CZ)(21) Appl. No.: **13/290,025**(22) Filed: **Nov. 4, 2011****Publication Classification**(51) **Int. Cl.**  
**F01K 17/00** (2006.01)

An engine and one or more aftertreatment subsystems integrated into one system for optimization and control. At least one controller may be connected to the engine and the one or more aftertreatment subsystems. The controller may contain and execute a program for the optimization and control of the one system. Controller may receive information pertinent to the engine and the one or more aftertreatment subsystems for the program. The controller may prescribe setpoints and constraints for measured variables and positions of actuators according to the program to aid in effecting the optimization and control of the one system.






FIGURE 1

1100.1829101




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5

## INTEGRATED OPTIMIZATION AND CONTROL OF AN ENGINE AND AFTERTREATMENT SYSTEM

### BACKGROUND

**[0001]** The present disclosure pertains to internal combustion engines and particularly to engines having aftertreatment mechanisms.

### SUMMARY

**[0002]** The disclosure reveals an engine and one or more aftertreatment subsystems integrated into one system for optimization and control. At least one controller may be connected to the engine and the one or more aftertreatment subsystems. The controller may contain and execute a program for the optimization and control of the one system. Controller may receive information pertinent to the engine and the one or more aftertreatment subsystems for the program. The controller may prescribe setpoints and constraints for measured variables and positions of actuators according to the program to aid in effecting the optimization and control of the one system.

### BRIEF DESCRIPTION OF THE DRAWING

**[0003]** FIG. 1 is a diagram of a basic scheme of the present system for integrated optimization and control of an engine with one or more aftertreatment subsystems;

**[0004]** FIG. 2 is a diagram of an illustrative example engine map;

**[0005]** FIG. 3 is a diagram of an illustrative example engine or aftertreatment subsystem interconnected with a controller;

**[0006]** FIG. 4 is a diagram of the example in FIG. 3 with an engine and a multiple of aftertreatment subsystems; and

**[0007]** FIG. 5 is a diagram of an illustrative example of an approach for the engine and aftertreatment system.

### DESCRIPTION

**[0008]** The modern combustion engine appears to be a very complex system. The complexity growth may be driven namely by governmental legislation that restricts combustion engine emissions. Therefore, the original equipment manufacturers (OEMs) may be forced to add various equipment items, sensors and actuators to the engine to achieve the prescribed limits and to optimize engine operating costs, e.g., fuel economy, urea consumption, and so forth. Under these conditions, an engine operation optimization and design of an optimal control system may be a challenging task.

**[0009]** Some approaches may incorporate optimizing the engine and individual aftertreatment systems involving, e.g., selective catalytic reduction (SCR), diesel oxidation catalysts (DOC), diesel particulate filter (DPF), and so on, separately. These approaches do not necessarily provide a systematic way of optimization. They may involve time consuming and expensive tasks. Furthermore, it is not necessarily ensured that their results will be optimal. There might be a better solution.

**[0010]** Another approach may be to optimize the engine together with the aftertreatment subsystem (AFS) as a one system. Such an approach may enable one to find the global optimal behavior of the engine with an aftertreatment subsystem from an economical and technical point of view while satisfying virtually all of the prescribed emission limits. The engine and aftertreatment subsystem may have appropriate

sensors and actuators as needed to effect an optimization program for the engine and aftertreatment subsystem or subsystems as one system. The engine may be seen as an exhaust gas source for the aftertreatment subsystem. The properties of the engine out exhaust gas as sensed may be influenced within certain range by manipulating available engine actuators such as those of a turbocharger waste gate (WG), variable geometry turbocharger (VGT), exhaust gas recirculation (EGR), start of injection (SOI), throttling valve (TV), and so on. Various degrees of freedom may be used to prepare or modify the exhaust gas properties for optimal operation of the aftertreatment subsystem at virtually all of the engine operating points. For example, if the actual state of the aftertreatment subsystem does not enable a reduction of emissions due to low temperature as sensed in some operating regimes, then the engine actuators may be controlled to increase temperature so that the engine exhaust gas out emissions do not violate prescribed limits. On the other hand, if the state of the aftertreatment subsystem enables a reduction of a significant amount of pollutants, the engine actuators may be controlled in a way to also achieve the best fuel economy.

**[0011]** An engine optimization and control design may be formulated as a rigorous mathematical optimization problem. The present approach may offer a modular and systematic solution to the problem. The approach may incorporate dividing the engine and aftertreatment optimization and control design into two stages: (i) an off-line part and (ii) an on-line part (real-time).

**[0012]** (i) The off-line part may be formulated as a mathematical optimization problem with constraints (known as mathematical programming) and the results may be various engine maps prescribing setpoints and constraints for different kinds of measured variables from sensors and positions of virtually all engine actuators for virtually all major operating points or conditions of the engine, e.g., over the engine speed and torque map. Virtually all of the maps may be parameterized by various variables of the engine and aftertreatment system but may be also parameterized by measured fuel and/or urea consumption and corresponding costs, by their ratio, or other relevant economically related quantities. Information about actual market prices of fuel and other fluids used by the engine and aftertreatment system may be incorporated to parameterize the control system and may be used as a tuning parameter during the engine's lifetime. This approach may enable a slight tuning of the controller behavior when the prices of the fluids used are changed, which can ensure economically optimal operation of the engine in view of such changes during its lifetime.

**[0013]** (ii) The on-line part may consist of one or more feedback single or multivariable real-time controllers. These controllers may be implemented, for example, as model based predictive controllers (MPCs). The feedback controllers may ensure realization of virtually all of the setpoints, but also satisfaction of virtually all of the constraints computed in the off-line part. The feedback controllers may also ensure disturbance rejection, a minimization of an impact of engine components production variability, and aging of the engine. Furthermore, the feedback controllers may also be designed to deliver needed performance during an engine transient operation.

**[0014]** FIG. 1 is a block diagram of a basic scheme of the present system for integrated optimization and control of an engine with one or more aftertreatment systems. The various blocks represent an engine 11, and several aftertreatment

systems (AFSs) 12 and 13. Aftertreatment system 13 may be the last system and be denoted by an “N”. “N” may also indicate the total number of aftertreatment systems. An aftertreatment system 12 between engine 11 and aftertreatment system N may be denoted by an “i”. There may be any number of aftertreatment systems. If there is one aftertreatment system, then it may be represented as system N, wherein N=1.

[0015] “ $x_0$ ” within the symbol for engine 11 may indicate an internal state of the engine. “ $x_i$ ” and “ $x_N$ ” may indicate internal states of AFSi 12 and AFSN 13, respectively. “ $v_i$ ” and “ $v_N$ ” may represent an external input 15 to engine 11. The external input may incorporate disturbance, fluid price, and so on. Similarly, “ $v_i$ ” and “ $v_N$ ” may represent external inputs 24 and 25 for AFSi 12 and AFSN 13, respectively. A “ $u_0$ ” input 16 may represent an actuator or actuators of engine 11, a “ $u_i$ ” input 26 may represent an actuator or actuators of AFSi 12, and a “ $u_N$ ” input 27 may represent an actuator or actuators of AFSN 13. Inputs 16, 26 and 27 may incorporate actuator inputs.

[0016] “ $J_0(x_0, v_0, u_0)$ ” on an output 17 may represent a subsystem cost function of  $x_0$ ,  $v_0$  and/or  $u_0$  for engine 11. “ $g(x_0, v_0, u_0) \leq 0$ ” also on output 17 may represent subsystem constraints of  $x_0$ ,  $v_0$  and/or  $u_0$  for engine 11. “ $y_0$ ” may represent an interconnection output 18 from engine 11 which may be an interconnection input “ $y_{i-1}$ ” 19 to AFSi 12, assuming that AFSi 12 is the first AFS connected to engine 11, where  $i=1$ . However, there may be one or more AFSs connected between engine 11 and AFSi 12. “ $y_i$ ” may represent an interconnection output 21 from AFSi 12 which may be an interconnection input “ $y_{N-1}$ ” 22 to AFSN 13, assuming that AFSN 13 is connected to AFSi 12. However, there may be one or more AFSs connected between AFSi 12 and AFSN 13. “ $y_N$ ” may represent an output 23 of the AFSN 13 and the preceding AFSs from “1” through “N-1”.

[0017] “ $J_i(x_i, v_i, u_i, y_{i-1})$ ” on an output 28 may represent a subsystem cost function of  $x_i$ ,  $v_i$ ,  $u_i$  and/or  $y_{i-1}$  for AFSi 12. “ $J_i(\cdot)$ ” may be an abbreviated designation of the subsystem cost function. “ $g(x_i, v_i, u_i, y_{i-1}) \leq 0$ ” also on output 28 may represent subsystem constraints of  $x_i$ ,  $v_i$ ,  $u_i$  and/or  $y_{i-1}$  for AFSi 12. “ $g(\cdot)$ ” may be an abbreviated designation of the subsystem constraints. “ $J_N(x_N, v_N, u_N, y_{N-1})$ ” on an output 29 may represent subsystem cost function of  $x_N$ ,  $v_N$ ,  $u_N$  and/or  $y_{N-1}$  for AFSN 13. “ $g(x_N, v_N, u_N, y_{N-1}) \leq 0$ ” also on output 29 may represent subsystem constraints of  $x_N$ ,  $v_N$ ,  $u_N$  and/or  $y_{N-1}$  for AFSN 13. The similar designations may be made for additional AFSs, if any, between engine 11 and AFSi 12 and between AFSi 12 and AFSN 13, as done herein with the xs, vs, us and ys.

[0018] FIG. 2 may aid in illustrating off-line optimization. An objective may be to compute optimal steady-state engine maps for virtually all of the operating points, for example, in an engine speed-torque space as shown with a graph 31 of engine torque (nm) versus engine speed (rpm). Graph 31 illustrates an example k-th operating point 32 plotted at a specific torque and engine speed. The k-th operating point may represent any point at various locations on graph 31.

[0019] An optimization problem in each operating point may be indicated by:

$$\min_U J = \sum_{i=0}^N J_i(x_i, v_i, u_i, y_{i-1}); U = \{u_0, u_1, \dots, u_N\}$$

$$\text{s.t. } g(x_i, v_i, u_i, y_{i-1}) \leq 0; i = 0, 1, \dots, N.$$

The resulting optimal steady-state maps may be indicated by:

$$u_i^{SS} = f_{u_i}(v_0, \dots, v_N) \text{ and}$$

$$y_i^{SS} = f_{y_i}(v_0, \dots, v_N).$$

[0020] Abbreviated designations of the steady-state map indications may be  $u_i^{SS} = f_{u_i}(\cdot)$  and  $y_i^{SS} = f_{y_i}(\cdot)$ , respectively. It may be noted that the maps may also be parameterized by  $x_i$  under certain conditions.

[0021] An on-line part (real-time) for an i-th aftertreatment subsystem or an engine may be illustrated in FIG. 3. A controller may be integrated with an engine and an AFS. An engine or AFS\_i 41 may have an internal state of  $x_0$  or  $x_i$ , respectively. An actuator input  $u_0$  or  $u_i$  43 may go to the engine or AFS\_i 41, respectively. The actuator input 43 may come from a controller\_0 or a controller\_i 42, respectively. Controller 42 may provide steady state maps as represented by symbols  $u_0^{SS} = f_{u_0}(\cdot)$  and  $y_0^{SS} = f_{y_0}(\cdot)$  or  $u_i^{SS} = f_{u_i}(\cdot)$  and  $y_i^{SS} = f_{y_i}(\cdot)$ , respectively. The controller\_i 42 may be implemented by MPC controller. External inputs  $v_0, \dots, v_N$  44 (i.e., disturbance, fluid price, and so forth) may be provided to controller 42. A specific input  $v_0$  or  $v_i$  45 may be input to engine or AFS\_i 41, respectively. An interconnection output  $y_{i-1}$  47 from an engine or an AFS\_{i-1} may be an input 46 to AFS\_i 41 and controller\_i 42. There may be an interconnection output  $y_0$  or  $y$  47 from the engine or AFS\_i 41 as an input 46 for an AFS\_{i+1} or an AFS\_N. Interconnection output 47 may also go to controller\_i 42. In general, 47 may contain also signals which are not interconnections but measurements of variables that can be useful for integrated optimization.

[0022] The on-line part for an i-th subsystem of FIG. 3 may be illustrated as an engine and multiple AFSs connected in a diagram of FIG. 4. Two or more controllers 42 of FIG. 4 may be combined as one controller 42. The numerical labels are the same for similar components and lines as shown in FIG. 3.

[0023] FIG. 5 is diagram of a two-part engine and aftertreatment optimization control approach 50 with an off-line stage 51 and an on-line stage 52. At the off-line stage 51 may be a mathematical optimization of the engine and aftertreatment system at symbol 53, an engine map with setpoints and constraints at symbol 54, and a parameterization of engine maps at symbol 55. At the on-line stage 52 may be feedback real-time controller or controllers at symbol 56, a realization of setpoints at symbol 57, and a satisfaction of constraints at symbol 58.

[0024] Some of the items or activities of the disclosed system in FIGS. 1-5 not covered by one or more controllers may be performed by a processor/computer.

[0025] A recap of the disclosure is provided in the following. An engine and aftertreatment system may incorporate an engine, an aftertreatment mechanism connected to the engine, and a controller connected to the engine and the aftertreatment mechanism. The controller may have an optimization program. The optimization program may be for optimized performance of the engine and the aftertreatment mechanism integrated as one system. Optimized performance may incorporate reducing emissions and increasing fluid efficiency of the one system.

[0026] The optimization program may incorporate the aftertreatment mechanism for reducing emissions from an exhaust of the engine to a prescribed level, and increasing



fluid efficiency of the engine and the aftertreatment mechanism while the emissions are reduced at least down to the prescribed level.

**[0027]** The engine may incorporate a control input to actuators on the engine, an interconnection output and an information output. The information output may indicate engine costs and/or engine constraints. The aftertreatment mechanism may incorporate an interconnection input connected to the interconnection output of the engine, a control input to actuators on the aftertreatment mechanism, an interconnection output, and an information output. The information output may indicate aftertreatment mechanism costs and/or aftertreatment mechanism constraints. The costs and constraints may be a basis incorporated in the optimization program for optimized performance of the engine and the aftertreatment mechanism integrated as one system.

**[0028]** The controller may further incorporate a first input connected to the interconnection output of the engine, a first output connected to the control input to actuators of the engine, a second input connected with the interconnection input of the aftertreatment mechanism, a third input connected to the interconnection output of the aftertreatment mechanism, and a second output connected to the control input to actuators of the aftertreatment mechanism.

**[0029]** The controller may further incorporate a feedback loop for disturbance rejection, minimizing an impact of variability of performance of the engine, and/or delivering predetermined performance of the aftertreatment mechanism during transient operation of the engine, and maps prescribing setpoints and constraints for measured variables and positions of engine actuators for one or more operating points of the engine. The maps may be parameterized by variables of the engine and the aftertreatment mechanism. The maps may be a basis incorporated in the optimization program for optimized performance of the engine and the aftertreatment mechanism integrated as one system.

**[0030]** An approach for engine and aftertreatment optimization and control may incorporate formulating an off-line part which involves mathematically optimizing an engine and aftertreatment system, providing engine maps prescribing setpoints and constraints for measured variables from sensors and positions of engine actuators for operating points and conditions of the engine, and parameterizing the engine maps with variables of the engine and the aftertreatment system.

**[0031]** The approach for engine and aftertreatment optimization and control may also incorporate formulating an on-line part providing one or more feedback real-time controllers realizing the setpoints of the engine and aftertreatment system, and satisfying computed constraints with the one or more controllers. The one or more controllers may be model predictive controllers.

**[0032]** The one or more controllers may ensure disturbance rejection, minimization of input of engine components production variability, and/or engine aging. The one or more controllers may deliver needed performance during an engine transient operation.

**[0033]** The approach may further incorporate parameterizing the engine and aftertreatment system by measured fuel, urea consumption and/or corresponding costs. The approach may also further incorporate parameterizing a control system with market price information of fuel and other fluids used by the engine and aftertreatment system. There may also be parameterizing the control system to tune the controller when there are changes of prices of fluids used by the engine and

aftertreatment system to ensure economically optimal operation of the engine during the changes.

**[0034]** There may be a system of an engine and aftertreatment subsystem incorporating an engine, an aftertreatment subsystem connected to the engine, and a controller connected to the engine and the aftertreatment subsystem. The controller may receive signals from sensors of the engine and the aftertreatment subsystem, process the signals, and provide signals to actuators of the engine and the aftertreatment subsystem according to an optimization program for optimized performance of the engine and the aftertreatment subsystem as one system. The optimized performance may incorporate reducing emissions and increasing fluid efficiency of the one system.

**[0035]** The external inputs of the engine and the aftertreatment subsystem may be connected to the controller. The controller may incorporate engine maps for operating points of the engine. The maps may be a basis for optimized performance of the engine and the aftertreatment subsystem as one system. The maps may prescribe setpoints and constraints for measured variables from the sensors and for actuators.

**[0036]** The engine may incorporate an external input and an actuator input from the controller, and an interconnection output connected to the controller. The external input may have external information pertinent to the engine.

**[0037]** The aftertreatment subsystem may incorporate an interconnection input connected to the interconnection output of the engine and connected to the controller, an external input, an actuator input from the controller, and an interconnection output connected to the controller. The external input may have external information pertinent to the aftertreatment subsystem.

**[0038]** The engine may further incorporate an internal state and an information output. The information output may indicate engine costs as a function of the engine internal state, the external input and/or the actuator input.

**[0039]** The aftertreatment subsystem may further incorporate an internal state and an information output. The information output may indicate aftertreatment costs as a function of the aftertreatment subsystem internal state, the external input, actuator input, and/or the interconnection input.

**[0040]** The information output of the engine may indicate engine constraints as a function of the internal state, the external input and/or the actuator input of the engine. The information output of the aftertreatment subsystem may indicate aftertreatment constraints as a function of the internal state, the external input, the actuator input, and/or the interconnection input of the aftertreatment subsystem. The costs and constraints may be a basis for optimized performance of the engine and the aftertreatment subsystem as one system.

**[0041]** An approach for controlling a combined engine and aftertreatment system may incorporate providing an engine, adding one or more aftertreatment subsystems to result in a combined engine and aftertreatment system, connecting one of the one or more aftertreatment subsystems to an exhaust output of the engine, and manipulating actuators of the engine and the one or more aftertreatment subsystems with one or more controllers to change the properties of the exhaust for optimal operation of the combined engine and aftertreatment system. Optimal operation may incorporate reduction of emissions and improvement of fluid efficiency of the combined engine and aftertreatment system.

**[0042]** To change the properties of the exhaust may incorporate reducing an amount of pollutants in the exhaust to a

magnitude equal to or less than a prescribed magnitude. Manipulating the actuators of the engine may increase fuel economy of the engine if the one or more aftertreatment subsystems reduce an amount of pollutants in the exhaust to a magnitude equal to or less than the prescribed magnitude.

**[0043]** The approach may further incorporate providing one or more engine maps as a basis for optimal operation of the combined engine and aftertreatment system, processing the one or more engine maps prescribing setpoints and/or constraints for measured variables and positions of the actuators on the engine for operating points and/or conditions of the engine, and parameterizing the engine maps by variables of the engine and of the one or more aftertreatment subsystems.

**[0044]** The approach may further incorporate parameterizing the engine maps by costs of fuel consumed by the engine and/or urea consumed by the one or more aftertreatment subsystems. The one or more engine maps may incorporate a speed and torque map of the engine. The one or more controllers may be connected to the engine and the one or more aftertreatment subsystems of the combined engine and aftertreatment system. The one or more controllers may ensure realization of the setpoints, and/or ensure satisfaction of the constraints.

**[0045]** In the present specification, some of the matter may be of a hypothetical or prophetic nature although stated in another manner or tense.

**[0046]** Although the present system and/or approach has been described with respect to at least one illustrative example, many variations and modifications will become apparent to those skilled in the art upon reading the specification. It is therefore the intention that the appended claims be interpreted as broadly as possible in view of the related art to include all such variations and modifications.

What is claimed is:

1. An engine and aftertreatment system comprising:  
an engine;  
an aftertreatment mechanism connected to the engine; and  
a controller connected to the engine and the aftertreatment mechanism; and  
wherein:  
the controller comprises an optimization program; and  
the optimization program optimizes performance of the engine and the aftertreatment mechanism integrated as one system.
2. The system of claim 1, wherein the optimization program comprises:  
the aftertreatment mechanism reducing emissions from an exhaust from the engine to a prescribed level; and  
increasing fluid economy of the engine while the emissions are reduced at least down to the prescribed level;
3. The system of claim 1, wherein the engine comprises:  
a control input to actuators on the engine;  
an interconnection output; and  
an information output; and  
wherein the information output indicates engine costs and/or engine constraints; and  
the costs and constraints are a basis incorporated in the optimization program for optimizing performance of the engine and the aftertreatment mechanism integrated as one system.

4. The system of claim 3, wherein the aftertreatment mechanism comprises:

- an interconnection input connected to the interconnection output of the engine;
  - a control input to actuators on the aftertreatment mechanism;
  - an interconnection output; and
  - an information output; and
- wherein the information output indicates aftertreatment mechanism costs and/or aftertreatment mechanism constraints.

5. The system of claim 4, wherein the controller comprises:  
a first input connected to the interconnection output of the engine; and

- a first output connected to the control input to actuators of the engine.

6. The system of claim 5, wherein the controller further comprises:

- a second input connected with the interconnection input of the aftertreatment mechanism;
- a third input connected to the interconnection output of the aftertreatment mechanism; and
- a second output connected to the control input to actuators of the aftertreatment mechanism.

7. The system of claim 1, wherein the controller further comprises:

- a feedback loop for disturbance rejection, minimizing an impact of variability of performance of the engine, and/or delivering needed performance of the aftertreatment mechanism during transient operation of the engine;
- maps prescribing setpoints and constraints for measured variables and positions of engine actuators for one or more operating points of the engine; and

wherein:

- the maps are parameterized by variables of the engine and the aftertreatment mechanism; and
- the maps are a basis incorporated in the optimization program for optimizing performance of the engine and the aftertreatment mechanism integrated as one system.

8. A process for controlling a combined engine and aftertreatment system, comprising:

- providing an engine;
- adding one or more aftertreatment subsystems to result in a combined engine and aftertreatment system;
- connecting one of the one or more aftertreatment subsystems to an exhaust output of the engine; and
- manipulating actuators of the engine to change the properties of the exhaust for optimal operation of the one or more aftertreatment subsystems and optimal operation of the engine.

9. The process of claim 8, further comprising:

- wherein to change the properties of the exhaust comprises reducing an amount of pollutants in the exhaust to a magnitude equal to or less than a prescribed magnitude; and

manipulating the actuators of the engine to increase fuel economy of the engine if the one or more aftertreatment subsystems reduce an amount of pollutants in the exhaust to a magnitude equal to or less than the prescribed magnitude.

10. The process of claim 8, further comprising:

- processing one or more engine maps prescribing setpoints and/or constraints for measured variables and positions of the actuators on the engine for operating points and/or conditions of the engine; and

parameterizing the engine maps by variables of the engine and of the one or more aftertreatment subsystems.

**11.** The process of claim **10**, further comprising parameterizing the engine maps by costs of fuel consumed by the engine and/or urea consumed by the one or more aftertreatment subsystems.

**12.** The process of claim **10**, wherein the one or more engine maps comprise a speed and torque map of the engine.

**13.** The process of claim **9**, further comprising:  
providing one or more controllers connected to the engine and the one or more aftertreatment subsystems; and  
wherein  
the one or more controllers ensure realization of the set-points; and/or  
the one or more controllers ensure satisfaction of the constraints.

**14.** A system of an engine and aftertreatment subsystem comprising:

an engine;  
an aftertreatment subsystem connected to the engine; and  
a controller connected to the engine and the aftertreatment subsystem; and  
wherein the controller receives signals from sensors of the engine and the aftertreatment subsystem, processes the signals and provides signals to actuators of the engine and the aftertreatment subsystem according to an optimization program which optimizes performance of the engine and the aftertreatment subsystem as one system.

**15.** The system of claim **14**, wherein:

the engine comprises:  
an external input; and  
an actuator input from the controller;  
an interconnection output to the controller; and  
wherein the external input comprises external information pertinent to the engine;

the aftertreatment subsystem comprises:

an interconnection input connected to the interconnection output of the engine and to the controller;  
an external input;

an actuator input from the controller; and  
an output connected to the controller; and  
wherein the external input comprises external information pertinent to the aftertreatment subsystem.

**16.** The system of claim **15**, wherein the engine further comprises:

an internal state; and  
an information output; and  
wherein the information output provides engine costs as a function of the internal state, the external input and/or the actuator input.

**17.** The system of claim **16**, wherein the aftertreatment subsystem further comprises:

an internal state; and  
an information output; and  
wherein the information output provides cost as a function of the internal state, the aftertreatment external input, actuator input, and/or the interconnection input.

**18.** The system of claim **16**, wherein:

the information output of the engine provides indicates engine constraints as a function of the internal state, the external input and/or the actuator input of the engine; and

the information output of the indicates provides aftertreatment constraints as a function of the internal state, the external input, the actuator input, and/or the interconnection input of aftertreatment subsystem.

**19.** The system of claim **15**, wherein:

the external inputs of the engine and the aftertreatment subsystem are connected to the controller;  
the controller comprises steady state engine maps for operating points of the engine; and  
the maps prescribe setpoints and constraints for measured variables from the sensors and for portions of the actuators.

**20.** The system of claim **15'**, further comprising one or more aftertreatment subsystems connected to the aftertreatment subsystem.

\* \* \* \* \*