

US012175871B2

(12) **United States Patent**  
**Madrigal et al.**

(10) **Patent No.:** **US 12,175,871 B2**

(45) **Date of Patent:** **Dec. 24, 2024**

(54) **NETWORK COMPUTER SYSTEM TO EVALUATE AN OPERATOR OF A FREIGHT VEHICLE**

(58) **Field of Classification Search**

CPC ..... B60W 40/09; G07C 5/008; G07C 5/08; G08G 1/123; G08G 1/20; H04W 4/04  
(Continued)

(71) Applicant: **Uber Technologies, Inc.**, San Francisco, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,953,720 A 4/1976 Kelch  
5,880,958 A 3/1999 Helms et al.  
(Continued)

(72) Inventors: **Luis Madrigal**, San Francisco, CA (US); **Eyal Lasker**, San Francisco, CA (US); **Xiao Guo**, San Francisco, CA (US); **Padmini Pyapali**, San Francisco, CA (US); **Tony Ran Zhang**, San Francisco, CA (US)

FOREIGN PATENT DOCUMENTS

CN 101951545 1/2011  
CN 103692969 4/2014  
(Continued)

(73) Assignee: **UBER TECHNOLOGIES, INC.**, San Francisco, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Alfred Round et al. "Future Ride: Adopting New Technologies to Paratransit in the United States", Working Paper, UCTC No. 306, University of California Transportation Center, 51 pages.

(Continued)

(21) Appl. No.: **18/340,548**

(22) Filed: **Jun. 23, 2023**

(65) **Prior Publication Data**

US 2023/0360527 A1 Nov. 9, 2023

*Primary Examiner* — Qutbuddin Ghulamali

(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.

**Related U.S. Application Data**

(63) Continuation of application No. 17/526,524, filed on Nov. 15, 2021, now Pat. No. 11,727,803, which is a  
(Continued)

(51) **Int. Cl.**

**G08G 1/123** (2006.01)  
**B60W 40/09** (2012.01)

(Continued)


(52) **U.S. Cl.**

CPC ..... **G08G 1/127** (2013.01); **B60W 40/09** (2013.01); **G06Q 10/063** (2013.01);  
(Continued)

(57) **ABSTRACT**

A computer system can determine historical interval data of a freight operator from completed freight service requests associated with the freight operator. Additionally, while the freight operator is fulfilling a current freight service request, the computer system can determine at least a first likely downtime interval for a non-operating activity of the freight operator prior to the freight operator arriving at a pickup location or a destination location of the current freight service request, based on the historical interval data. Also, the computer system can determine an estimated arrival time for the freight operator to arrive at the pickup location or the destination location of the current freight service request, based at least in part on the first likely down time interval. Moreover, the computer system can update a record asso-

(Continued)



ciated with the freight operator to reflect the estimated arrival time.

**20 Claims, 4 Drawing Sheets**

**Related U.S. Application Data**

continuation of application No. 16/849,504, filed on Apr. 15, 2020, now Pat. No. 11,176,822, which is a continuation of application No. 16/380,580, filed on Apr. 10, 2019, now Pat. No. 10,657,813, which is a continuation of application No. 15/804,829, filed on Nov. 6, 2017, now Pat. No. 10,293,832.

(60) Provisional application No. 62/576,859, filed on Oct. 25, 2017.

(51) **Int. Cl.**

- G06Q 10/063* (2023.01)
- G06Q 10/0639* (2023.01)
- G07C 5/00* (2006.01)
- G07C 5/08* (2006.01)
- G08G 1/00* (2006.01)
- G08G 1/127* (2006.01)
- G08G 1/14* (2006.01)
- H04W 4/40* (2018.01)
- H04W 4/46* (2018.01)
- B60W 40/08* (2012.01)

(52) **U.S. Cl.**

CPC ..... *G06Q 10/06398* (2013.01); *G07C 5/008* (2013.01); *G07C 5/08* (2013.01); *G07C 5/0841* (2013.01); *G08G 1/123* (2013.01); *G08G 1/148* (2013.01); *G08G 1/20* (2013.01); *H04W 4/40* (2018.02); *H04W 4/46* (2018.02); *B60W 2040/0818* (2013.01)

(58) **Field of Classification Search**

USPC ..... 340/439  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,411,897	B1	6/2002	Gaspard	
6,456,207	B1	9/2002	Yen	
6,516,056	B1	2/2003	Justice et al.	
6,591,253	B1	7/2003	Dinkin et al.	
6,728,749	B1*	4/2004	Richardson	..... G06F 9/4887 709/200
6,879,962	B1	4/2005	Smith et al.	
7,315,780	B2	1/2008	Sugahara et al.	
7,353,181	B2	4/2008	Nel	
7,385,529	B2	6/2008	Hersh et al.	
7,552,063	B1	6/2009	McEachern	
7,561,069	B2	7/2009	Horstmeyer	
8,131,307	B2	3/2012	Lubeck et al.	
8,271,316	B2	9/2012	Blackshaw et al.	
9,135,803	B1	9/2015	Fields et al.	
9,256,852	B1	2/2016	Mylymaki	
9,478,150	B1	10/2016	Fields et al.	
9,552,564	B1	1/2017	Martenis	
9,908,530	B1	3/2018	Fields et al.	
9,921,070	B1	3/2018	Nimchuck et al.	
9,955,326	B2	4/2018	Avrahami	
10,126,138	B1*	11/2018	Farmer	..... G06Q 50/40
10,832,294	B1*	11/2020	Bentley	..... G06Q 10/063
11,386,789	B1*	7/2022	Bajaj	..... G08G 1/205
2002/0034292	A1	3/2002	Tuoriniemi et al.	
2002/0049622	A1*	4/2002	Lettich	..... G06Q 10/08 705/7.11

2002/0065738	A1	5/2002	Riggs et al.	
2002/0095308	A1	7/2002	Pragelas et al.	
2002/0138338	A1	9/2002	Trauth et al.	
2002/0188517	A1	12/2002	Banerjee et al.	
2002/0194129	A1	12/2002	Furuya et al.	
2003/0036935	A1	2/2003	Nel	
2003/0087648	A1	5/2003	Mezhvinsky et al.	
2003/0233190	A1	12/2003	Jones	
2004/0106399	A1	6/2004	Ki	
2004/0112959	A1	6/2004	Jun	
2004/0158483	A1	8/2004	LeCouturier	
2004/0219933	A1	11/2004	Faith	
2004/0249699	A1	12/2004	Laurent et al.	
2004/0249818	A1	12/2004	Isaac	
2004/0260470	A1	12/2004	Rast	
2004/0260513	A1*	12/2004	Fitzpatrick	..... G06Q 50/12 702/182
2005/0096837	A1	5/2005	Yoshizumi	
2005/0149382	A1	7/2005	Fenner et al.	
2005/0227704	A1	10/2005	Ferra et al.	
2005/0278063	A1	12/2005	Hersh et al.	
2006/0059023	A1	3/2006	Mashinsky	
2006/0136254	A1	6/2006	Greenstein	
2006/0155460	A1	7/2006	Raney	
2006/0195348	A1	8/2006	Peterkofsky et al.	
2006/0200306	A1	9/2006	Adameczyk	
2006/0200396	A1	9/2006	Satterfield et al.	
2006/0206387	A1	9/2006	Peterkofsky et al.	
2006/0217885	A1	9/2006	Crady et al.	
2007/0103342	A1	5/2007	Milleville	
2007/0221791	A1	9/2007	Voelk et al.	
2008/0086322	A1	4/2008	Wallace	
2008/0114629	A1	5/2008	Pavlov	
2008/0125967	A1	5/2008	Sprigg	
2008/0140597	A1	6/2008	Satir	
2008/0158016	A1	7/2008	Wang	
2008/0189207	A1	8/2008	Wurster	
2008/0195428	A1	8/2008	O'Sullivan	
2008/0270019	A1	10/2008	Anderson	
2008/0270204	A1	10/2008	Poykko	
2008/0312991	A1	12/2008	Bharadwaj	
2009/0030770	A1	1/2009	Hersh et al.	
2009/0037095	A1	2/2009	Jani et al.	
2009/0049119	A1	2/2009	Marcinkiewicz et al.	
2009/0083111	A1	3/2009	Carr	
2009/0099971	A1	4/2009	Salemme	
2009/0125228	A1	5/2009	Dicke	
2009/0177502	A1	7/2009	Doinoff et al.	
2009/0216600	A1	8/2009	Hill	
2009/0222284	A1	9/2009	McEachern	
2009/0254270	A1	10/2009	Yu	
2009/0313077	A1	12/2009	Wheeler	
2010/0017275	A1	1/2010	Carlson	
2010/0076988	A1	3/2010	Kenedy et al.	
2010/0243724	A1	9/2010	Golla	
2011/0010300	A1	1/2011	Audet	
2011/0099040	A1	4/2011	Felt et al.	
2011/0060600	A1	5/2011	Fox et al.	
2011/0137696	A1	6/2011	Meyer et al.	
2011/0153495	A1	6/2011	Dixon et al.	
2012/0036082	A1	2/2012	Cha et al.	
2012/0130627	A1	5/2012	Islam et al.	
2012/0179764	A1	7/2012	Erdal	
2012/0253548	A1	10/2012	Davidson	
2013/0030873	A1	1/2013	Davidson	
2013/0041720	A1	2/2013	Spires	
2013/0245991	A1	9/2013	Kriss	
2013/0335193	A1	12/2013	Hanson et al.	
2014/0122147	A1	5/2014	Christie et al.	
2014/0200804	A1	7/2014	Wippler	
2014/0229399	A1	8/2014	Ranganathan et al.	
2014/0249742	A1	9/2014	Krivacic et al.	
2014/0324633	A1	10/2014	Pollak et al.	
2014/0330596	A1	11/2014	Depura et al.	
2015/0006428	A1	1/2015	Miller et al.	
2015/0081162	A1	3/2015	Mitchell et al.	
2015/0088581	A1	3/2015	Ikawa	
2015/0161696	A1	6/2015	Jones et al.	
2015/0379468	A1	12/2015	Harvey	

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0012391	A1	1/2016	Burnett	
2016/0042303	A1	2/2016	Medina et al.	
2016/0047646	A1	2/2016	Ochsendorf et al.	
2016/0071056	A1	3/2016	Ellison et al.	
2016/0104111	A1	4/2016	Jones et al.	
2016/0202069	A1	7/2016	Wippler et al.	
2016/0273922	A1	9/2016	Stefan	
2016/0300186	A1	10/2016	Scharaswak et al.	
2016/0334236	A1	11/2016	Mason et al.	
2017/0046658	A1	2/2017	Jones et al.	
2017/0109696	A1	4/2017	Serjeantson et al.	
2017/0124506	A1	5/2017	Khan	
2017/0144671	A1	5/2017	Memani et al.	
2017/0249847	A1	8/2017	Marueli	
2018/0025417	A1	1/2018	Brathwaite et al.	
2018/0068269	A1	3/2018	Pillai et al.	
2018/0096300	A1	4/2018	Boye et al.	
2018/0211217	A1	7/2018	Berdinis et al.	
2018/0211218	A1	7/2018	Berdinis et al.	
2018/0211541	A1	7/2018	Rakah et al.	
2019/0051174	A1*	2/2019	Haque .....	G08G 1/202
2019/0095859	A1	3/2019	Pike et al.	
2019/0118825	A1	4/2019	Madrigal et al.	
2019/0122551	A1	4/2019	Madrigal et al.	
2019/0130351	A1	5/2019	Arena	
2019/0213529	A1	7/2019	Donnelly et al.	
2019/0232967	A1	8/2019	Madrigal et al.	
2019/0318298	A1	10/2019	Driegert	
2019/0385119	A1	12/2019	Chang et al.	
2020/0027348	A1	1/2020	Madrigal et al.	
2020/0080853	A1	3/2020	Tam	
2020/0282988	A1	9/2020	Madrigal et al.	
2021/0042705	A1	2/2021	Suen et al.	
2021/0097315	A1*	4/2021	Carruthers .....	G08B 13/19645
2021/0097862	A1*	4/2021	Engle .....	G06Q 10/02
2022/0148425	A1*	5/2022	Madrigal .....	B60W 40/09
2023/0360527	A1*	11/2023	Madrigal .....	G06Q 10/06398

FOREIGN PATENT DOCUMENTS

CN	103761635	4/2014
CN	103870893	6/2014
CN	105069594	11/2015
EP	2827289	1/2015
JP	2002123887	4/2002
JP	2006/323784	11/2006
JP	2017165509	9/2017
KR	1020170026805	3/2017
NL	2017377	3/2018
WO	WO 1995/027964	10/1995
WO	WO 2016/133594	8/2016
WO	WO 2017/025955	2/2017
WO	WO 2017/107854	6/2017
WO	WO 2018/106730	6/2018
WO	WO 2018/107046	6/2018
WO	WO 2018/136179	7/2018

OTHER PUBLICATIONS

Examination Report for AU 2010325793, dated Jun. 21, 2013.  
 Examination Report No. 2 for AU 2015202596 dated May 22, 2017.  
 Extended European Search Report for EP 10835261.8, dated Oct. 10, 2016.  
 Hunt, J.B. Carrier 230 Tutorial: Load Board Features [Video], <https://www.jbhunt.com/blog/2018/03/01/360-load-board-features> Mar. 1, 2018.  
 Hunt, J.B. "Find a Load, Make an Offer with Carrier 360: Watch the Video," <https://www.jbhunt.com/blog/2017/10/25/carrier-360-video> Oct. 25, 2017".  
 Hunt, J.B. "Get your Next Load Recommendations from JP Hunt 360 Account", <http://jbhunt.com/blog/2017/09/28/find-loads-carrier-360/> Sep. 28, 2017.  
 Hunt, J.B., "Booking & Dispatching Loads <https://www.jbhunt.com/blog/2018/05/22/carrier-360-dispatching-freight/> May 22, 2018".  
 Hunt, J.B., "Carrier 360 Introduces I'm Not Driving Mode," <https://jbhunt.com/blog/2019/06/03/carrier-360-introduces-im-not-driving-mode/> Jun. 3, 2019".  
 Hunt, J.B., "Carrier 360 Tutorial: Creating Favorite Lanes [Video] <https://jbhunt.com/blog/2018/04/13/carrier-360-favorite-lanes/> Apr. 13, 2018".  
 Hunt, J.B., "Carrier 360 Tutorial: Load Board Features [Video], <https://www.jbhunt.com/blog/2018/03/01/360-load-board-features>" Mar. 1, 2018.  
 Hunt, J.B., "Eight Things you can do using your J.B. Hunt 360 account," <https://www.jbhunt.com/blog/2017/06/13/jbhunt-360>, Jun. 13, 2017".  
 Hunt, J.B., "Get your next load recommendation from J.B. Hunt 360," <https://www.jbhunt.com/blog/2017/08/02/360-load-recs/> Aug. 2, 2017".  
 Hunt, J.B., "Loads Delivered to You: Three Ways to Find Loads Using Carrier 360 by J.B. Hunt," <https://www.jbhunt.com/blog/2017/09/28/find-loads-carrier-360/> Sep. 28, 2017".  
 Hunt, J.B., "Simpler is Better: Easy check calls and automated detention," <https://www.jbhunt.com/blog/2018/11/19/check-calls-detention-carrier-360> Nov. 19, 2018".  
 International Preliminary Report on Patentability for PCT/US2019/036622, dated Aug. 4, 2020.  
 International Search Report and Written Opinion for PCT/US2018/057538, dated Jan. 25, 2019.  
 International Search Report and Written Opinion for PCT/US2019/012516, dated Apr. 24, 2019.  
 International Search Report and Written Opinion for PCT/US2019/036622, dated Sep. 23, 2019.  
 International Search Report and Written Opinion issued for PCT/US2017/066765, dated Apr. 13, 2018.  
 Kuebix, "Effectively Managing Big Data in Your Supply Chain: How to take action now that will ensure success in the future.", Aug. 22, 2017.  
 Search Report mailed Oct. 1, 2013, for EP 10835261.8.  
 Shigemitsu et al. "AVM System", Fujistu Ten Technicl Journl No. 33, 27:34, 2009.  
 U.S. Appl. No. 15/804,838, filed Nov. 6, 2017, 22 pages.  
 U.S. Appl. No. 16/529,489, filed Aug. 1, 2019, 22 pages.  
 Written Opinion for PCT/US2019/012516, dated Oct. 11, 2019.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

# NETWORK COMPUTER SYSTEM TO EVALUATE AN OPERATOR OF A FREIGHT VEHICLE

## PRIORITY CLAIM

This application is a continuation of U.S. patent application Ser. No. 17/526,524, filed Nov. 15, 2021, which is a continuation of U.S. patent application Ser. No. 16/849,504 (now U.S. Pat. No. 11,176,822), filed Apr. 15, 2020, which application is a continuation of U.S. patent application Ser. No. 16/380,580 (now U.S. Pat. No. 10,657,813), filed Apr. 10, 2019, which application is a continuation of U.S. patent application Ser. No. 15/804,829 (now U.S. Pat. No. 10,293,832), filed Nov. 6, 2017, which claims benefit of priority to U.S. Provisional Patent Application No. 62/576,859, filed Oct. 25, 2017; the aforementioned priority applications being hereby fully incorporated by reference in their entireties.

## BACKGROUND

Generally, freight vehicles have a heightened standard of care with respect to their operation, as compared to other types of road vehicles. As such, a greater amount of skill and diligence may be required from freight operators as compared to other drivers. For example, freight operators may be required to have special class driving licenses. While requirements of freight operators and vehicles is heightened, there are generally few mechanisms in place to monitor freight operators, given the large distances freight operators travel.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an example network computer system to evaluate a freight operator;

FIG. 2 illustrates an example method for evaluating a freight operator;

FIG. 3 illustrates an example method for determining a time of arrival for a freight vehicle to arrive at a destination location; and

FIG. 4 illustrates a computer system upon which aspects described herein may be implemented.

Throughout the drawings, identical reference numbers designate similar, but not necessarily identical elements. The figures are not necessarily to scale, and the size of some parts may be exaggerated to more clearly illustrate the example shown. Moreover, the drawings provide examples and/or implementations consistent with the description. However, the description is not limited to the examples and/or implementations provided in the drawings.

## DETAILED DESCRIPTION

Examples provide for a network computer system that can continuously or periodically monitor an operator (e.g., a freight vehicle operator) operating a freight vehicle (e.g., a freight truck) during a time interval. The network computer system can evaluate driving and/or non-driving related freight service performances of the operator while the operator is performing the freight service during a time interval. The network computer system can base the evaluations on interval data (e.g., location information of the freight vehicle, vehicle operation information of the freight vehicle, and mobile device information of a mobile device the operator is using during the time interval) provided by the

mobile device the operator is using during that time interval. For example, the network computer system can evaluate performance metrics related to the operation of the freight vehicle the operator is operating based on the vehicle operation information of the interval data (e.g., fuel consumption, braking performance, acceleration, when the engine is applying power, when the engine is idle, when the engine is off, etc.). In some implementations, the network computer system can determine one or more sub-intervals that the freight vehicle is switched off or the operator has left the freight vehicle the operator was operating, when the freight vehicle is idle. Additionally, in other implementations, the network computer system can evaluate the operator during a time interval where the operator could be assigned multiple freight services and/or operate multiple freight vehicles to perform one or more assigned freight services. In some implementations, the network computer system can assign a freight service request from a requester to an available operator.

In some examples, a network computer system is configured to remotely evaluate freight operators in a manner that is objective and specific to the freight services industry. For example, as described herein, a network computer system can base its evaluations on data (e.g., interval data) generated and/or collected from a mobile device associated with the freight operator and/or an electronic logging device of the freight service vehicle. Additionally, such evaluations may be made specific to the freight services industry (e.g., how safe a freight operator operates the freight vehicle based on the number of left turns the freight vehicle takes).

In other examples, the network computer system can determine a time of arrival for the freight vehicle that the operator is operating, based on the interval data (e.g., location information of the freight vehicle, vehicle operation information of the freight vehicle, and mobile device information of a mobile device the operator is using during the time interval). For example, at a given instance, the network computer system can determine a time of arrival based at least in part on (i) a distance between the current location of the freight vehicle to the given destination location, (ii) a time for the freight vehicle to travel the distance, and (iii) a duration of one or more required downtime intervals during which a restriction exists against the operator operating the freight vehicle.

According to some examples, a network computer system may remotely monitor a freight vehicle based on data (e.g., interval data) generated and/or collected from a mobile device and/or an electronic logging device of the freight service vehicle. Additionally, the time of arrival can be continuously or periodically updated, as to enable entities operating storage facilities that are to receive loads or have loads picked up (e.g., warehouse at the pick-up location and the warehouse at the destination location) to appropriately allocate the correct amount of resources to accommodate an incoming freight vehicle.

As provided herein, the terms “user,” “operator” and “service provider” are used throughout this application interchangeably to describe person utilizing a provider application on a computing device to provide on-demand freight services to a freight service requester. A freight service requester can be a person or group of people who utilize a requester application on a computing device to request, over one or more networks, on-demand freight services from a network computing system.

One or more examples described herein provide that methods, techniques, and actions performed by a computing device are performed programmatically, or as a computer-

implemented method. Programmatically, as used, means through the use of code or computer-executable instructions. These instructions can be stored in one or more memory resources of the computing device. A programmatically performed step may or may not be automatic.

Additionally, one or more examples described herein can be implemented using programmatic modules, engines, or components. A programmatic module, engine, or component can include a program, a sub-routine, a portion of a program, or a software component or a hardware component capable of performing one or more stated tasks or functions. As used herein, a module or component can exist on a hardware component independently of other modules or components. Alternatively, a module or component can be a shared element or process of other modules, programs, or machines.

Moreover, examples described herein can generally require the use of specialized computing devices, including processing and memory resources. For example, one or more examples described may be implemented, in whole or in part, on computing devices such as servers, desktop computers, cellular or smartphones, personal digital assistants (e.g., PDAs), laptop computers, printers, digital picture frames, network equipment (e.g., routers), wearable computing devices, and tablet devices. Memory, processing, and network resources may all be used in connection with the establishment, use, or performance of any example described herein (including with the performance of any method or with the implementation of any system). For instance, a computing device coupled to a data storage device storing the computer program and configured to execute the program corresponds to a special-purpose computing device. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

Furthermore, one or more examples described herein may be implemented through the use of instructions that are executable by one or more processors. These instructions may be carried on a computer-readable medium. Machines shown or described with figures below provide examples of processing resources and computer-readable mediums on which instructions for implementing examples described can be carried and/or executed. In particular, the numerous machines shown with examples described include processor(s) and various forms of memory for holding data and instructions. Examples of computer-readable mediums include permanent memory storage devices, such as hard drives on personal computers or servers. Other examples of computer storage mediums include portable storage units, such as CD or DVD units, flash memory (such as carried on smartphones, multifunctional devices or tablets), and magnetic memory. Computers, terminals, network enabled devices (e.g., mobile devices, such as cell phones) are all examples of machines and devices that utilize processors, memory, and instructions stored on computer-readable mediums. Additionally, examples may be implemented in the form of computer-programs, or a computer usable carrier medium capable of carrying such a program.

Alternatively, one or more examples described herein may be implemented through the use of dedicated hardware logic circuits that are comprised of an interconnection of logic gates. Such circuits are typically designed using a hardware description language (HDL), such as Verilog and VHDL. These languages contain instructions that ultimately define the layout of the circuit. However, once the circuit is

fabricated, there are no instructions. All the processing is performed by interconnected gates.

#### System Description

FIG. 1 illustrates an example network computer system to evaluate a freight operator. In particular, network computer system **100** uses data obtained over a given time interval (“interval data **131**”) to evaluate various facets of a freight operator’s performance. According to some examples, the network computer system **100** can evaluate and/or monitor an operator based on interval data **131** that is periodically or continuously obtained from mobile device **140** (e.g., smartphones, tablet computers, virtual reality or augmented reality handsets, on-board computing systems of vehicles, etc.). Interval data **131** is data generated from mobile device **140** and/or electronic logging device (ELD) **155** that is related to an operator operating freight vehicle **150** during a time interval or a duration of time that the operator is being monitored.

In some implementations, network computer system **100** can evaluate and/or monitor the operator in the context of an on-demand freight service. In such implementations, network computer system **100** can manage the on-demand freight service by assigning a freight service request from a requester to an available operator. Additionally, network computer system **100** can evaluate and/or monitor the operator while the operator is fulfilling the freight service request. The freight service request can include one or more load identifiers for one or more loads to be transported and routing information. The routing information can include the pick-up location (e.g., a warehouse where the load is being housed), the destination location (e.g., the location where the load is to be dropped off), the preferred time or window of time to pick up the load at the pick-up location, and/or the preferred time or window of time of freight service completion (e.g., the preferred time to drop-off the load at the destination location). Additionally, network computer system **100** can determine a hauling route for operator to take based on the routing information. In some implementations, network computer system **100** can take into account toll locations, traffic data and/or traffic data when determining a hauling route. In such implementations, location information for one or more tolls in one or more geographic regions, weather data and/or traffic data can be obtained from a third-party provider. In other implementations, weather data and/or traffic data can be obtained from one or more sensors of freight vehicle **150** and other freight vehicles traveling in and around the same region or hauling route as freight vehicle **150**.

As illustrated in FIG. 1, network computer system **100** can include evaluator **108**, monitor **124**, operator store **124**, real-time data-base **126**, and communication interface **128**. During a time interval that the operator is operating freight vehicle **150** (e.g., between a pick-up/start location and a destination location specified in an assigned freight service request), network computer system **100** can control or cause mobile device **140** to provide or transmit interval data **131** to network computer system **100**. In such examples, network computer system **100** can obtain interval data **131** from mobile device **140**, over network **130** and through communication interface **128**. Additionally, interval data **131** can include, for a given time interval, location information **133** of freight vehicle **150** (e.g., based on the location information provided by a location based resource of mobile device **140**), vehicle operation information **135** of freight vehicle **150** (e.g., acceleration, braking, when the engine is idle, mileage, fuel consumption, an identifier of freight vehicle

150, etc.), and mobile device information 137 of mobile device 140 (e.g., sensor data).

Network computer system 100 can directly and wirelessly (e.g., WIFI, Bluetooth, BLE (Bluetooth low energy), NFC, or other appropriate short-range communication) obtain some of vehicle operation information 135 from ELD 155. In such examples, ELD 155 can obtain vehicle operation information 135 directly from the electronic computing unit (ECU) of freight vehicle 150. Examples of vehicle operation information 135 include acceleration, braking, when the engine is idle, mileage, fuel consumption, freight vehicle 150 error codes, and an identifier of freight vehicle 150. In some implementations, network computer system 100 can wirelessly obtain vehicle operation information 135 obtained from ELD 155 through mobile device 140. In such implementations, mobile device 140 can include in interval data 131 being provided to network computer system 100 vehicle operation information 135 obtained from ELD 155. In other implementations, network computer system 100 can control or cause mobile device 140 to connect with ELD 155. In such implementations, network computer system 100 can provide an instruction to mobile device 140 to connect to ELD 155.

Network computer system 100 can continuously or periodically update interval data 131 received from mobile device 140 and/or ELD 155. As illustrated in FIG. 1, network computer system 100 can include activity data store 126 that maintains a record (or set of records) for individual operators or freight operators who are providing freight services. For example, activity data store 126 can maintain separate records for individual operators. Network computer system 100 can associate each record for each operator with an operator identifier and a recent set of interval data 131 obtained from mobile device 140 of each operator.

Mobile device 140 can communicate an operator identifier to network computer system 100 using service application 145. Since mobile device 140 is the source of interval data 131, an operator can be evaluated over a duration in which the operator is operating multiple freight vehicles. Thus, network computer system 100 can evaluate the performance of the operator regardless of which freight vehicle the operator is operating.

According to some examples, the network computer system 100 can evaluate the driving and/or non-driving related freight service performances of an operator operating freight vehicle 150 during that time interval, based on the obtained interval data 131. For example, evaluator 102 can obtain interval data 131 (e.g., location information 133, vehicle operation, and mobile device 140 information) of an operator from activity data store 126 to evaluate a driving and/or non-driving related freight service performance of the operator during a time interval. Additionally, evaluator 102 can evaluate the operator by comparing interval data 131 of the operator to an operator model stored in operator model database 114. In some implementations, evaluator 102 can quantify (e.g., score) the driving and non-driving related performance of the operator during a time interval that operator is operating freight vehicle 150.

Evaluator 102 can include driving evaluator 108 to evaluate a driving related freight service performance of the operator during a time interval when the operator is operating freight vehicle 150. Driving evaluator 108 can include safety logic 104 to determine a manner that operator is operating freight vehicle 150 that is deemed safe, based on, for example models, rules, regulations etc. Additionally, driving evaluator 108 can include performance logic 106 to determine performance metrics of the operator operating

freight vehicle 150. The performance metrics can include wear and tear to freight vehicle 150 (e.g., the operator's performance in shifting gears and the effect it has on the transmission of freight vehicle 150) and/or depletable vehicle resources efficiency (e.g., fuel efficiency) as the operator operates freight vehicle 150, based on, for example, models.

Safety logic 104 can utilize interval data 131 of an operator to determine whether the operator is operating freight vehicle 150 in a way that is deemed safe. Additionally, the determination can be based on a comparison between interval data 131 of the operator to an operator model. For example, safety logic 104 can determine a driving pattern or tendency, based on detected characteristics of a type of action that the driver performed (e.g., operator repeatedly braked very hard and/or accelerated sharply). Additionally, the determination can be based on a comparison between vehicle operation information 135, included in interval data 131 of the operator during a time interval when the operator was operating freight vehicle 150, and the operator model. In other examples, safety logic 104 can determine that during that same time interval, freight vehicle 150 took a high number of left turns in comparison to the operator model. The determination can be based on the comparison between mobile device information 137 of mobile device 140 (e.g., sensor information, for example, accelerometer information and/or gyroscope information of one or more sensors of mobile device 140) included in interval data 131 and the operator model. Taken together, safety logic 104 can further determine that the operator operated freight vehicle 150 not as safely as the operator model. Additionally, safety logic 104 can quantify such a determination by determining a safety score for the operator based on the comparison between interval data 131 of the operator and the operator model.

Performance logic 106 can utilize interval data 131 of an operator to determine performance metrics of the operator operating freight vehicle 150. The determination can be based on a comparison between interval data 131 of the operator during a time interval that the operator operated freight vehicle and an operator model. For example, performance logic 106 can determine the operator braked hard, accelerated aggressively, and freight vehicle 150 had a low fuel efficiency (based on miles traveled versus the amount of fuel consumed). The determination can be based on the comparison between vehicle operation information 135 included in interval data 131 and an operator model. Taken together, performance logic 106 can determine that the operator operated freight vehicle 150 not as well as the operator model. Additionally, performance logic 106 can quantify such a determination by determining a performance score for the operator.

Evaluator 102 can include non-driving evaluator 112 to evaluate a non-driving related performance of an operator during a time interval when the operator is operating freight vehicle 150. For example, evaluator 102 can evaluate an operator on the trustworthiness or reputation of the operator. In some implementations, non-driving evaluator 112 can determine a reputation or trustworthiness of the operator by evaluating how reliable, professional, and/or timely the operator is when performing their assigned freight service. Additionally, the reputation of the operator can be based on the comparison between interval data 131 of the operator to an operator model.

In some implementations, non-driving evaluator 112 can determine a timeliness of an operator based on interval data 131 (e.g., location information 133 of freight vehicle 150,

vehicle operation information **135** of freight vehicle **150** and/or mobile device information **137** of mobile device **140**) of the operator, a hauling route of the freight service and preferred times of arrival to a pick-up location and/or a destination location that is specified in a freight service request. The hauling route can include a pick-up location and/or a destination location that is specified in the freight service request. In some examples, non-driving evaluator **112** can determine when freight vehicle **150** arrives at the pick-up location and/or the destination location, based on the location information provided by mobile device **140**. Additionally, non-driving evaluator **112** can determine the timeliness of the operator by comparing the arrival times to the pick-up location and/or the destination location to the preferred times to pick up the load at the pick-up location and/or to drop off the load at the destination location.

Additionally, non-driving evaluator **112** can quantify the determination of timeliness by comparing the how close the arrival times were to the preferred times to an operator model. In some examples, non-driving evaluator **112** can quantify the timeliness of the operator (e.g. a timeliness score) to the pick-up location. In other examples, non-driving evaluator **112** can quantify the timeliness of the operator to the destination location. In yet other examples, non-driving evaluator **112** can quantify the overall freight service completion time (from the pick-up location to the destination location).

In some implementations, an individual at the pick-up location and/or destination location (e.g., the operator and/or requester) can confirm whether the operator picked up the load at the pick-up location and/or dropped off the load at the destination location. In such implementations, the individual can transmit a confirmation message from a mobile device (e.g., mobile device **140**) to network computer system **100**. For example, the individual can transmit the confirmation message from service application **145**, through network(s) **130** and to network computer system **100**. The confirmation message can include whether the load was picked up at the pick-up location or dropped-off/received at the destination location. In some examples, non-driving evaluator **112** can determine the time when the confirmation message was sent by the individual or received by network computer system **100**. Additionally, non-driving evaluator **112** can take into account such times when determining the timeliness of the operator or confirming the pickup/drop-off times.

In other implementations, non-driving evaluator **112** can determine whether the operator is picking up a load or dropping off a load based on sensor information generated by mobile device **140**. In such implementations, mobile device **140** can include one or more sensors (e.g., accelerometer and/or gyroscope) and the data generated from the one or more sensors can be included in interval data **131** (e.g., mobile device information **137** of mobile device **140**) to be utilized by non-driving evaluator **112**. In some examples, non-driving evaluator **112** can determine that the sensor information correlates to the operator picking-up the load. In other examples, non-driving evaluator **112** can determine that the sensor information correlates to the operator dropping off the load. In conjunction with location information of mobile device **140**, non-driving evaluator **112** can confirm that the load was picked up at the pick-up location and/or dropped off at the destination location. Additionally, non-driving evaluator **112** can determine when the load was picked up and/or dropped off and take into account when the load was picked up and/or dropped off when determining the timeliness of the operator.

Non-driving evaluator **112** can also utilize feedback provided by a requester to evaluate the non-driving aspects of the operator's performance. In some implementations, the requester can provide feedback by providing a rating or other quantitative metric related to one or more parameters of the operator's freight service performance. For example, network computer system **100** can provide an instruction to a service application running on a mobile device of a requester of a freight service request to generate a feedback user interface. The feedback user interface can enable the requester to provide a rating or other quantitative metric for one or more parameters of the operator's freight service performance. Examples of parameters of the operator's freight service performance that the requester can provide a rating or other quantitative metric for include, timeliness of operator to pick-up location, timeliness of operator to destination location, speed of loading the load, professionalism, courteousness, the overall delivery service of the requester and state of load at drop off. Additionally, non-driving evaluator **112** can utilize the provided ratings and quantitative metrics to determine an overall reputation score for the operator. In some implementations, non-driving evaluator **112** can compare the ratings and quantitative metrics provided by the mobile device of the requester to an operator model when determining a reputation score for the operator.

In some implementations, the requester can also provide qualitative comments in conjunction with their quantitative assessment of the operator's freight service performance. For example, the instruction to generate the feedback user interface can also include an instruction to enable the requester to input qualitative comments. In some instances, the instruction can cause the feedback user interface to generate a text box for the requester to manually input their comments. In other instances, the instruction can cause the feedback user interface to generate a dropdown menu of pre-generated comments for the requester to select.

Other non-driving related freight service performance examples that evaluator **102** can evaluate operator on include whether the operator has left freight vehicle **150** (e.g., cab **152**). In some implementations, non-driving evaluator **112** can utilize off-truck detect logic **110** to determine whether the operator has left freight vehicle **150**, based on the sensor information (e.g., accelerometer information and/or gyroscope information) of mobile device **140** (e.g., mobile device information **137** of mobile device **140**). In some examples, off-truck detect logic **110** can determine that the sensor information correlates to the operator stepping out of cab **152** of freight vehicle **150** (e.g., an acceleration in a negative direction). Additionally, mobile device **140** can time stamp the sensor information as to when such information was detected. As such, off-truck detect logic **110** can determine when the operator left cab **152**. In other implementations, off-truck detect logic **110** can determine whether the operator has left freight vehicle **150** based on whether mobile device **140** is wirelessly or directly connected to ELD **155**. For example, off-truck detect logic **110** can determine ELD **155** has been disconnected from mobile device **140**. In such an example, off-truck detect logic **110** can determine that the operator may have left cab **152** based in part on determining mobile device **140** and ELD **155** are no longer connected. Additionally, off-truck detect logic **110** can determine and utilize the times of when mobile device **140** and ELD **155** were disconnected when evaluating the operator.

Activity data store **126** can update an operator account with corresponding operator evaluations (driving and non-driving related) of one or more operators provided by

evaluator **102**. In some implementations, evaluator **102** can identify an operator identifier associated with interval data **131** and/or rating/quantitative metric that each operator evaluation is based on. Additionally, evaluator **102** can associate each operator evaluation with the identified operator identifier associated with interval data **131** and/or rating/quantitative metric that each operator evaluation is based on. In such implementations, activity data store **126** can update each operator account based on the operator identifier associated with each operator evaluation and the operator identifier associated with each operator account. Additionally, activity data store **126** can provide to operator store **124** each operator evaluation and the associated operator identifier obtained from evaluator **102**. Operator store **124** can store each operator evaluation of each operator that evaluator **102** provided.

Additionally, network computer system **100** can store historical interval data **131** of each operator in an operator store **124**. For example, as illustrated in FIG. 1, network computer system **100** can include operator store **124** that can store interval data **131** (e.g., location information **133**, vehicle operation information **135**, and mobile device **140** information) and corresponding operator identifier provided by mobile device **140**. In some implementations, operator store **124** and activity data store **126** can be separate databases. In other implementations, operator store **125** and activity data store **126** can be included in the same database.

Evaluator **102** can select an operator model to compare interval data **131** of an operator to, based on freight service parameters associated with each operator model that most resembles the parameters of the freight service the operator performed. In such implementations, evaluator **102** can include an operator model database **114**. Operator model database **114** can store multiple operator models or just one generic operator model. In examples where operator model database **114** stores multiple operator models, each operator model can be associated with one or more freight service parameters. Examples of freight service parameters include a specific load weight, a range of load weight, a specific freight vehicle size, a range of freight vehicle sizes, a type of freight vehicle (e.g., a freight vehicle with refrigeration capabilities versus a freight vehicle without refrigeration capabilities), a type of load (e.g., perishable versus non-perishable loads, fragile versus non-fragile loads, etc.), weather conditions encountered and/or traffic conditions encountered.

Evaluator **102** can further analyze interval data **131** of the operator in light of weather data and/or traffic data when determining the driving and non-driving performance of the operator while operating freight vehicle **150**. In some implementations, evaluator **102** can obtain sensor information that includes the weather information and/or traffic information from a third-party provider. Alternatively, the weather information and/or traffic information can be obtained from one or more sensors from freight vehicle **150** and other freight vehicles traveling in and around the same region as freight vehicle **150**. In either implementation, evaluator **102** (e.g., safety logic **104**, performance logic **106** and/or non-driving evaluator **112**) can obtain the weather information and/or traffic information of the same region where the operator was operating freight vehicle **150** and during the same time interval as when interval data **131** was taken.

In some examples, safety logic **104** can determine a high safety score for the operator if compared to the operator model, safety logic **104** determines there was a higher rate of soft braking, a higher number of times freight vehicle **150** is accelerating, and that there were heavy rains and heavy

traffic conditions at the time interval data **131** was taken and at the at the locations freight vehicle **150** was traveling in. In another example, performance logic can determine a low performance score for the operator if compared to the operator model, performance logic **106** determines a higher rate of hard braking, higher number of times freight vehicle **150** accelerated aggressively, fuel consumption was higher, and that it was sunny and traffic conditions were light at the time interval data **131** was taken and at the locations freight vehicle **150** was traveling in. In yet another example, non-driving evaluator **112** can determine a high timeliness score for the operator if compared to the operator model, non-driving evaluator **112** determines there was a delay to the pick-up location, a delay to the destination location, and there were heavy traffic conditions at the time interval data **131** was taken and at the locations freight vehicle **150** was traveling in.

Network computer system **100** can include monitor **116** to monitor an operator while an operator operates freight vehicle **150** during a time interval. As illustrated in FIG. 1, monitor **116** can include service time logic **118**, vehicle monitor **122** and operator restriction monitor **120**. In some implementations, monitor **116** can determine whether the operator has exceeded a freight service time restriction (e.g., the maximum amount of time an operator is legally allowed to operate freight vehicle **150** or a predetermined time an operator can operate freight vehicle **150**). For example, vehicle monitor **122** can periodically or continuously obtain interval data **131** of an operator for monitor **116** to determine whether an amount of time the operator has operated freight vehicle **150** is equal to or exceeded a freight service time restriction. In some implementations, vehicle monitor **122** can periodically or continuously obtain, from activity data store **126** and/or operator store **124**, interval data **131** (e.g., location information **133**, vehicle operation, and mobile device **140** information) of an operator operating freight vehicle **150**.

In some implementations, service time logic **118** can determine the amount of time an operator has operated freight vehicle **150** during a time interval (e.g., a hauling event, a day, a week, a month, etc.) based on interval data **131** obtained from activity data store **126** and/or operator store **124**. For example, service time logic **118** can determine how long an operator has operated freight vehicle **150** by determining (i) when mobile device **140** was connected to ELD **155**, (ii) when mobile device **140** was disconnected from ELD **155**, (iii) when the engine was turned on and/or (iv) when the engine was turned off. Additionally, in some implementations, service time logic **118** can determine the amount of time the operator has operated freight vehicle **150** by taking into account (i) instances or sub-intervals of when the operator stops operating freight vehicle **150** (e.g., by determining, from vehicle operation information **135**, when the engine of freight vehicle **150** is off), (ii) instances or sub-intervals of when freight vehicle **150** is idle (e.g., by determining, from vehicle operation information **135** and location information of mobile device **140**, when the engine is on but freight vehicle **150** is not moving), and (iii) instances or sub-intervals of when operator has left freight vehicle **150** (e.g., from location information of mobile device **140** and/or whether mobile device **140** has disconnected from electronic logging device **155**).

Additionally, in such implementations, monitor **116** can include operator restriction monitor **120** to determine whether the operator has exceeded a freight service time restriction, by determining whether the amount of time the operator has operated freight vehicle **150** is equal to or

greater than the freight service time restriction. In some implementations, operator restriction monitor **120** can obtain data indicating the amount of time the operator has operated freight vehicle **150** in a time interval from service time logic **118**. Additionally, operator restriction monitor **120** can compare the amount of time the operator has operated freight vehicle **150** to the freight service time restriction. In some examples, operator restriction monitor **120** can determine that the amount of time the operator has operated freight vehicle **150** is equal to or exceeds the freight service time restriction. Additionally, operator restriction monitor **120** can restrict the operator from accepting or selecting a freight service request presented on service application **145**. For instance, operator restriction monitor **120** can provide an instruction to service application **145** to restrict the operator from selecting or accepting any freight service request presented by service application **145**.

In other examples, operator restriction monitor **120** can determine that the amount of time the operator has operated freight vehicle **150** is less than the freight service time restriction. In such examples, operator restriction monitor **120** can limit which freight service request the operator can select or accept that is presented on service application **145**. For instance, operator restriction monitor **120** can determine the amount of time remaining before the operator will exceed the freight service time restriction (e.g., based on interval data **131** of the operator, operator restriction monitor **120** can determine the amount of time remaining between the amount of time the operator has already operated freight vehicle **150** and the freight service time restriction). Additionally, operator restriction monitor **120** can determine an estimated service completion time for each freight service request obtained by network computer system **100**. For instance, operator restriction monitor **120** can take into account the pick-up location, destination location, any indicated preferred time of freight service completion included in the freight service request. Taken together, operator restriction monitor **120** can identify one or more freight service requests obtained by network computer system **100** that have an estimated service completion time that is less than or equal to the amount of time remaining before the operator will exceed the freight service time restriction. In some implementations, operator restriction monitor **120** can provide an instruction to service application **145** to present only the identified one or more freight service requests. In other implementations, operator restriction monitor **120** can provide an instruction to service application **145** to limit the operator to only be able to select a freight service request that is one of the identified one or more freight service requests.

Other parameters, operator restriction monitor **120** can take into account when determining the estimated service completion time for each freight service request obtained by network computer system **100**, include (i) traffic data, (ii) weather data, and (iii) interval data **131** of the operator (e.g., current location of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150**, and information of mobile device **140**) operating freight vehicle **150**, when determining the estimated service completion time for each freight service request obtained by network computer system **100**.

In some implementations, monitor **116** can monitor the progress of an operator fulfilling an assigned freight service request and provide data to arrival component **134** to determine, at any given instance, a time of arrival that freight vehicle **150** is to arrive at a pick-up location and/or a destination location (e.g., a warehouse). Additionally, arrival

component **134** can provide the time of arrival to storage facility device **160** of entities operating the storage facilities that are to receive loads or have loads picked up (e.g., warehouse at the pick-up location and the warehouse at the destination location). That way, entities operating storage facilities that are to receive loads or have loads picked up can appropriately allocate the correct amount of resources to accommodate an incoming freight vehicle **150**. For example, in circumstances where freight vehicle **150** is delayed, network computer system **100**, via arrival component **134**, can notify the entities of the delay by transmitting a new time of arrival to storage facility device **160**. As such, instead of the entities having their resources waiting idly by until freight vehicle **150** arrives, the entities can properly allocate resources for receiving the load from freight vehicle **150** or for the load to be picked up by an operator assigned to the freight service request, based on the new time of arrival. In some implementations, service application **165** can present the time of arrival and any update to the time of arrival (e.g., the transmitted new time of arrival) to the entities.

Arrival component **134** can determine, at any given instance a time of arrival that freight vehicle **150** is to arrive at the destination location or the pick-up location based on interval data **131** (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150**, and information of mobile device **140**) of an operator operating freight vehicle **150**. For example, at any given instance when the operator is operating freight vehicle **150**, arrival component **134** receive from vehicle monitor **122** interval data (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150**, and information of mobile device **140**) associated with the operator operating freight vehicle **150**. Additionally, based on interval data **131**, arrival component **134** can determine (i) a current location of freight vehicle **150** based on the location information provided by a location based resource of mobile device **140**, (ii) a distance between the current location of the freight vehicle to the destination or pick-up location specified in the freight service request, and (iii) a time for the freight vehicle to travel the determined distance.

Arrival component **134** can take into account environmental information when determining an estimated time of arrival, weather and/or traffic conditions the operator may be currently in while performing their assigned freight service. For example, a third-party provider can provide environmental information that includes weather information and/or real-time traffic information to arrival component **134**. Arrival component **134** can determine the current weather and/or current traffic conditions at the current location of the operator and freight vehicle **150** based on the environmental information and the location information of mobile device **140**. Additionally, arrival component **134** can determine any delays the operator is encountering and determine and/or adjust the estimated time of arrival based on the delays that the operator is encountering.

In some implementations, arrival component **134** can determine traffic conditions and/or weather conditions the operator may encounter while performing their assigned freight service based on the sensor data and the hauling route the operator is taking. For example, arrival component **134** can determine that an accident occurred on the hauling route the operator is currently taking. In such an example, arrival component **134** can determine an estimated delay the operator may encounter and determine and/or adjust the estimate time of arrival based on the potential delay. In other

13

examples, arrival component **134** can determine that weather conditions on the hauling route the operator is currently taking will likely get worse and cause a delay. In such examples, arrival component **134** can determine and/or adjust the estimated time of arrival based on the potential delay.

In various implementations, arrival component **134** can take into account the minimum number of downtime intervals (e.g., rest periods or periods of time an operator is not operating freight vehicle **150** so as to not exceed a freight service time restriction) and the duration of each downtime intervals an operator should take, when determining the estimated time of arrival that freight vehicle **150** is to arrive at the pick-up location and/or destination location. In such implementations, the number of downtime intervals and the duration of each downtime interval can be based on (i) an estimated time for freight vehicle **150** to arrive at the destination location (e.g., based on the current location of freight vehicle **150**), (ii) a distance between the current location of freight vehicle **150**, (iii) the amount of time the operator has operated freight vehicle **150** (as determined from data generated by service time logic **118**), and (iv) the service time restriction (as provided by operator restriction monitor **120**).

In some implementations, arrival component **134** can take into account environmental information (e.g., traffic and/or weather information) when determining the minimal amount of time or downtime intervals that an operator should take as to not exceed a freight service time restriction. For example, the traffic conditions and weather conditions an operator may encounter or is currently encountering may cause freight vehicle **150** to slow down and cause delays. As such, arrival component **134** may determine that the operator should take more downtime intervals due to the traffic and weather conditions the operator is encountering or may encounter. Meaning the minimum number of downtime intervals may increase. In other examples, arrival component **134** may determine that the traffic conditions and/or the weather conditions the operator may encounter or is encountering may not inhibit the speed of freight vehicle **150**. As such, arrival component **134** may determine the operator could take less downtime intervals. Meaning the minimum number of downtime intervals may decrease.

In some implementations, service time logic **118** can determine that an operator is currently in a downtime interval and arrival component **134** can utilize such data to determine a remaining amount of downtime the operator should be in before being able to resume operating freight vehicle **150**. In such implementations, service time logic **118** can make such determinations based on interval data **131** of the operator provided by vehicle monitor **122**. For example, service time logic **118** can determine that an operator is currently in a downtime interval and the amount of downtime the operator has left, based on vehicle operation information **135** of freight vehicle **150** (e.g., instances of when the engine was turned off) and/or mobile device information **137** of mobile device **140** (e.g., instances of when mobile device **140** was disconnected from electronic logging device **155** and/or instances of when the operator is not at the same location as freight vehicle **150**) included in interval data **131**. Additionally, based on the determined minimum duration of each downtime interval an operator should take, arrival component **134** can determine the amount of downtime remaining before the operator can resume operating freight vehicle **150**.

In some examples, a downtime interval can include the estimated amount of time an operator is to pick up a load at

14

the pick-up location. Arrival component **134** can determine the estimated amount of time an operator picks up a load at a pick-up location, based on historical interval data **131** (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150** and mobile device information **137** of mobile device **140**) stored in operator store **124**. In other examples, a downtime interval can include the estimated amount of time an operator is to change out a load that is already in trailer **154**. In such examples, an operator could be assigned to multiple freight service requests, and upon arriving at one destination location, the operator is to drop off one load, but pick up another load, before proceeding to the next destination location. Arrival component **134** can determine the estimated amount of time an operator changes out a load, based on historical interval data **131** (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150** and mobile device information **137** of mobile device **140**) stored in operator store **124**.

In yet other examples, a downtime interval can include one or more instances or sub-intervals that an operator may have to go to a weigh station. In such examples, arrival component **134** can determine the number of weight stations an operator may have to stop at, based on at least on the weight of the load being transported by freight vehicle **150**, the hauling route the operator is currently taking, and whether a weigh station bypass is associated with freight vehicle **150**. Additionally, a downtime interval can include the average amount of time an operator may spend at a weigh station. For example, arrival component **134** can determine the average amount of time an operator may spend at a particular weigh station, based on the time stamps and the location information of mobile device **140** arriving and departing a known weigh station. In some implementations, arrival component **134** can obtain location information of weigh stations from a third-party provider. In other implementations, operator store **124** can store the location information of weigh stations in one or more geographic regions.

Arrival component **134** can take into account the number of fuel stops freight vehicle **150** will likely have to take when determining the time of arrival freight vehicle is estimated to arrive at the pick-up location and/or destination location. Additionally, arrival component **134** can take into account the distance between the current location of freight vehicle **150** (e.g., location information **133**) to the pick-up and/or destination location specified in the freight service request, when determining the number of fuel stops freight vehicle **150** will likely have to take. Additionally, arrival component **134** can determine from vehicle operation information **135** (e.g., the amount of fuel used as compared to the average distance travelled) of interval data **131**, provided by vehicle monitor **122**, the fuel efficiency of freight vehicle **150**. Taken together, arrival component **134** can determine the number of fuel stops the operator may need to take to travel to the destination location.

Arrival component **134** can take into account size of a load a weight of the load and/or a type of the load to be transported by freight vehicle **150** when determining the estimated time of arrival. For example, the heavier the load, the slower freight vehicle **150** can travel. Additionally, the heavier the load, the worse the fuel efficiency of freight vehicle **150**. Meaning freight vehicle **150** may need more fuel to travel to a destination location specified in a freight service request. In some examples, arrival component **134** can take into account, the type of load, for example, whether the load is fragile or not, when determining the estimated

time of arrival. For instance, a fragile load could cause the operator to operate freight vehicle **150** more carefully and/or more slowly. In some implementations, the load size and/or weight can be included in the freight service request. In other implementations, the size and/or weight of the load may be detected by one or more sensors (e.g., optical and weight bearing sensors) included in trailer **154**. In such examples, the sensor data including the size and/or weight of the load can be included in interval data **131** provided by mobile device **140** and/or electronic logging device **155**.

In some implementations, arrival component **134** can take into account the size, weight and/or type of the load when determining the minimum number of downtime intervals the operator should take. For example, arrival component **134** may determine that the weight, size and/or type of load (e.g., a fragile load) of the load may cause freight vehicle **150** to travel slower. Arrival component **134** may determine the operator should take more downtime intervals. Meaning the minimum number of downtime intervals may increase. Additionally, arrival component **134** can also take into account the minimum number of downtime intervals the operator should take, when determining the estimated time of arrival of freight vehicle **150** to the pick-up and/or destination location.

Arrival component **134** can also include dock logic **132** to optimize the receiving and/or delivery of loads at the pick-up and/or destination location, respectively. In some implementations, dock logic **132** can assign a dock to freight vehicle **150** to either pick up a load specified in a freight service request and/or to drop off a load specified in a freight service request. In such implementations, the assignment of the dock can be based at least on the estimated time of arrival of freight vehicle **150**. Additionally, in other implementations, the assignment of the dock can be based on the estimated time of arrival of other freight vehicles that may also be arriving at approximately the same time. In such implementations, arrival component **134** can similarly determine the time of arrival of other freight vehicles as it can for freight vehicle **150**.

In various implementations, dock logic **132** can send dock routing instructions to an operator. The dock routing instructions can include instructions to route freight vehicle **150** to the dock assigned to the operator. The dock route can be based on the location information provided by a location based resource of mobile device **140** (e.g., location information **133** of freight vehicle **150**) and the location information of the dock assigned to the operator. In some implementations, dock logic **132** can provide the dock routing information to mobile device **140** when dock logic **132** determines that freight vehicle **150** is within a proximity distance threshold of the pick-up location, destination location or the assigned dock. In such implementations, dock logic **132** can determine that freight vehicle **150** is within the proximity distance threshold based on interval data **131** of the operator (e.g., the location information of mobile device **140**) and the pick-up location and/or destination location specified by the freight service request or the location information of the assigned dock. Dock logic **132** can obtain interval data **131** of the operator from vehicle monitor **122**.

Dock logic **132** can verify the identity of an operator that is picking up and/or dropping off a load specified in a freight service request that the operator that is also assigned to. For example, dock logic **132** can determine if identifier information provided by mobile device **140** of the corresponding operator matches the identifier information already associated with a freight service request. Examples of identifier information include, an operator identifier (e.g., a name of

the operator, a photograph of the operator, a phone number of the operator, an identifier associated with government identification of the operator, etc.), a load identifier, a vehicle identifier of freight vehicle **150** that is transporting or will be transporting the load (e.g., VIN number of the freight vehicle), and a freight service identifier (e.g., location information of the pick-up location, location information of the destination location, an alpha numeric identifier, a load identifier, etc.).

Dock logic **132** can cause mobile device **140** of an operator assigned to the freight service request to provide identifier information that dock logic **132** can use to verify the identity of the operator. For example, dock logic **132** can cause mobile device **140** to provide the identifier information when freight vehicle **150** of the operator is within a proximity distance threshold of the pick-up location and/or destination location. Dock logic **132** can determine whether freight vehicle **150** is within a proximity distance threshold of the pick-up location and/or destination location based on the location information of mobile device **140** and the location information of the pick-up and/or destination location specified in the assigned freight service request, respectively. Upon dock logic **132** determining that freight vehicle is within the proximity distance threshold, dock logic **132** can provide instructions to mobile device **140** to provide the identifier information. In such implementations, dock logic **132** can utilize the identifier information provided by mobile device **140** to identify a copy of a freight service request with the same identifier information that is stored in operator store **124**.

Network **130** can include one or more networks. Network **130** can be a conventional type, wired or wireless, and can have numerous configurations include a star star configuration, token ring configuration, or other configurations. Furthermore, network **130** can include an intranet, a local area network (LAN), a wide area network (WAN) (e.g., the Internet), and/or other interconnected data paths across which multiple devices can communicate. In some embodiments, network **130** can be a peer-to-peer network. Network **130** can also be coupled with or include portions of a telecommunications network for sending data using a variety of different communication protocols. In some embodiments, network **130** can include Bluetooth (or Bluetooth low energy) communication networks or a cellular communications network for sending and receiving data including via short messaging service (SMS), multimedia messaging service (MMS), hypertext transfer protocol (HTTP), direct data connection, WAP, email, etc. Although FIG. **1** illustrates one network **130**, network **130** can be more than one network. For example, as illustrated in FIG. **1**, network computer system **100**, mobile device **140**, and in some implementations ELD **155** can communicate over network **130** using wired or wireless connections, or combinations thereof. Methodology

FIG. **2** illustrates an example method for evaluating a freight operator during a time interval that the operator is operating a freight vehicle. FIG. **3** illustrates an example method for determining a time of arrival for a freight vehicle to arrive at a destination location. In the below discussions of FIGS. **2** and **3**, reference may be made to reference characters representing like features as shown and described with respect to FIG. **1** for purpose of illustrating a suitable component for performing a set or sub-step being described.

FIG. **2** illustrates an example method for evaluating a freight operator. In some implementations, as illustrated in FIG. **2**, network computer system **100** can associate an operator with a mobile device (**200**). For example, mobile

device **140** can provide interval data **131** (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150** and mobile device information **137** of mobile device **140**) of an operator during a time interval the operator is operating freight vehicle **150**, with a mobile identifier associated with mobile device **140**. In some implementations, interval data **131** can additionally include an operator identifier. Additionally, network computer system **100** (e.g., operator store **124** and/or activity data store **126**) can associate the mobile identifier with an operator record (or set of records) based on the operator identifiers associated with the operator record and the interval data.

Mobile device **140** can communicate an operator identifier to network computer system **100** using service application **145**. Since mobile device **140** is the source of interval data **131**, an operator can be evaluated over a duration that the operator is operating multiple freight vehicles. Thus, network computer system **100** can evaluate the performance of the operator regardless of which freight vehicle the operator is operating.

Network computer system **100** can monitor the operator using mobile device **140** (**202**). Additionally, network computer system **100** can cause or control the mobile device to acquire operator related information, for example, interval data **131** of an operator operating freight vehicle **150** (**204**). In some examples, network computer system **100** can periodically or continuously obtain interval data **131** of an operator operating freight vehicle **150** by controlling mobile device **140** to acquire and provide interval data **131** to network computer system **100** over a time interval. In some examples, interval data **131** of the operator can include location information of freight vehicle **150** (**206**). Location information **133** of freight vehicle **150** can be based on the location information provided by a location abased resource of mobile device **140**. In other examples, interval data **131** of the operator can further include vehicle operation information **135** of freight vehicle **150** while freight vehicle **150** is in operation (**208**). Examples of vehicle operation information **135** of freight vehicle **150** include acceleration, braking, when the engine is idle, mileage, fuel consumption, mass air flow, freight vehicle **150** error codes, and an identifier of freight vehicle **150**. In yet other examples, interval data **131** of the operator can include mobile device information **137** of mobile device **140** (**210**). In such examples, mobile device information **137** can include sensor information (e.g., accelerometer information, gyroscope information, etc.) generated from one or more sensors of mobile device **140** (e.g., accelerometer, gyroscope, etc.).

In some implementations, some of vehicle operation information **135** of freight vehicle **150** can be obtained by ELD **155**. ELD **155** can be connected to the electronic computing unit (ECU) of freight vehicle **150**. Additionally, in such implementations, ELD **155** can provide vehicle operation information **135** obtained from the ECU to mobile device **140** wirelessly (e.g., WIFI, Bluetooth, BLE (Bluetooth low energy), NFC, or other appropriate short-range communication). Additionally, mobile device **140** can provide interval data **131** that includes vehicle operation information **135** obtained from ELD **155** to network computer system **100**. In other implementations, network computer system **100** can obtain vehicle operation information **135** from ELD **155** directly from ELD **155**.

Based on interval data **131**, network computer system **100** can determine one or more sub-intervals that freight vehicle **150** is switched off or the operator has left freight vehicle **150** when freight vehicle **150** is idle (**212**). For example,

non-driving evaluator **112** can determine when freight vehicle **150** is idle based on mobile device information of mobile device **140** (e.g., sensor information indicating a lack of acceleration or movement detected by accelerometer or gyroscope of mobile device **140**), location information **133** of freight vehicle **150** (e.g., the location information of mobile device **140** indicating mobile device **140** has not changed over consecutive instances or sub-intervals) and/or vehicle operation information **135** of freight vehicle **150** (e.g., consecutive instances or sub-intervals where the engine power is off and there is no acceleration or deceleration). Additionally, non-driving evaluator **112** can determine freight vehicle **150** is off based on vehicle operation information **135** of freight vehicle **150** (e.g., consecutive instances or sub-intervals where the engine power is off).

In other examples, non-driving evaluator **112** (e.g., off-truck detect logic **110**) can determine whether the operator has left freight vehicle **150** (e.g., cab **152**), based on mobile device information **137** of mobile device **140**. For example, off-truck detect logic **110** can determine from sensor information (e.g., accelerometer information and/or gyroscope information) of mobile device **140** that the operator has left cab **152**. In such an example, off-truck detect logic **110** can determine that the sensor information correlates to the operator stepping out of cab **152** of freight vehicle **150** (e.g., an acceleration in a negative direction). Additionally, mobile device **140** can time stamp the sensor data as to when the acceleration was detected. As such, off-truck detect logic **110** can determine when the operator left cab **152**. In other implementations, off-truck detect logic **110** can determine whether the operator has left freight vehicle **150** based on whether mobile device **140** is wirelessly or directly connected to ELD **155**. For example, off-truck detect logic **110** determines ELD **155** has disconnected from off-truck detect logic **110**. In such an example, off-truck detect logic **110** can determine that the operator may have left cab **152** based on determining mobile device **140** and ELD **155** are no longer connected.

Network computer system **100** can evaluate the operator over the time interval using the operator related information, for example, interval data **131** of an operator operating freight vehicle **150** (**214**). For example, evaluator **102** can obtain interval data **131** (e.g., location information of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150**, and mobile device information **137** of mobile device **140**) of an operator from activity data store **126** to evaluate the driving and/or non-driving related freight service performances of the operator during a time interval. Additionally, evaluator **102** can evaluate the operator by comparing interval data **131** of the operator to an operator model stored in operator model database **114**. The operator model can standardize how freight vehicle **150** should be operated. In some implementations, evaluator **102** can quantify (e.g., score) the driving and non-driving related performance of the operator while operating freight vehicle **150**.

Evaluator **102** can include driving evaluator **108** to evaluate a driving related freight service performance of the operator during a time interval when the operator is operating freight vehicle **150**. Driving evaluator **108** can include safety logic **104** to determine whether operator is operating freight vehicle **150** in a way that is deemed safe, based on, for example models, rules, regulations etc. Additionally, driving evaluator **108** can include performance logic **106** to determine performance metrics of the operator operating freight vehicle **150**. The performance metrics can include wear and tear to freight vehicle **150** (e.g., the operator's performance in shifting gears and the effect it has on the

transmission of freight vehicle 150) and/or depletable vehicle resources efficiency (e.g., fuel efficiency) as the operator operates freight vehicle 150, based on, for example, models.

Safety logic 104 can utilize interval data 131 of an operator to determine whether the operator is operating freight vehicle 150 in a way that is deemed safe. Additionally, the determination can be based on a comparison between interval data 131 of the operator to an operator model. For example, safety logic 104 can determine a driving pattern or tendency, based on detected characteristics of a type of action that the driver performed (e.g., the operator repeatedly braked very hard and/or accelerated sharply). Additionally, safety logic 104 can base the determination on a comparison between vehicle operation information 135 included in interval data 131 of the operator during a time interval when the operator was operating freight vehicle 150 and the operator model. In other examples, safety logic 104 can determine that during that same time interval, freight vehicle 150 took a high number of left turns in comparison to the operator model. Safety logic 104 can base the determination on the comparison between mobile device information 137 of mobile device 140 (e.g., sensor information, for example, accelerometer information and/or gyroscope information of one or more sensors of mobile device 140) included in interval data 131 of the operator during a time interval when the operator was operating freight vehicle 150 and the operator model. Taken together, safety logic 104 can further determine that the operator operated freight vehicle 150 in a dangerous manner not as safely as the operator model. Additionally, safety logic 104 can quantify such a determination by determining a safety score for the operator based on the comparison between interval data 131 of the operator and the operator model.

Performance logic 106 can utilize interval data 131 of an operator to determine performance metrics of the operator operating freight vehicle 150. Performance logic 106 can make such a determination based on a comparison between interval data 131 of the operator during the time interval and an operator model. For example, performance logic 106 can determine that the operator had operated freight vehicle 150, the operator braked hard, accelerated aggressively, freight vehicle 150 consumed a lot of fuel and had a low fuel efficiency (based on miles traveled versus the amount of fuel consumed). Performance logic 106 can make such a determination based on the comparison between vehicle operation information 135 included in interval data 131 and an operator model. In some implementations, the determination can be alternatively or additionally based on the comparison between mobile device information 137 of mobile device 140 (e.g., the acceleration data of mobile device 140 can indicate the acceleration of freight vehicle 150) included in interval data 131 during the time interval. Taken together, performance logic 106 can determine that the operator, during the time interval, did not operate freight vehicle 150 as well as the operator model. Additionally, performance logic 106 can quantify such a determination by determining a performance score for the operator.

Evaluator 102 can include non-driving evaluator 112 to evaluate non-driving related performance of an operator during a time interval when the operator is operating freight vehicle 150. For example, evaluator 102 can evaluate the operator on the trustworthiness or reputation of the operator. In some implementations, non-driving evaluator 112 can evaluate the reputation of the operator by evaluating how reliable, professional, and/or timely the operator is when

performing the assigned freight service. Additionally, the reputation of the operator can be based on the comparison between interval data 131 of the operator to an operator model.

Non-driving evaluator 112 can determine a timeliness of an operator based on an interval data 131 (e.g., location information 133 of freight vehicle 150, vehicle operation information 135 of freight vehicle 150 and/or mobile device information of mobile device 140) of the operator, a hauling route of the freight service and preferred times of arrival to a pick-up location and/or a destination location that is specified in a freight service request. The hauling route can include a pick-up location and/or a destination location that is specified in the freight service request. In some examples, non-driving evaluator 112 can determine when freight vehicle 150 arrives at the pick-up location and/or the destination location, based on the location information provided by mobile device 140. Additionally, non-driving evaluator 112 can determine the timeliness of the operator by comparing the arrival times to the pick-up location and/or the destination location to the preferred times to pick up the load at the pick-up location and/or to drop off the load at the destination location.

Additionally, non-driving evaluator 112 can quantify the determination of timeliness by comparing the how close the arrival times were to the preferred times to an operator model. In some examples, non-driving evaluator 112 can quantify the timeliness of the operator (e.g. a timeliness score) to the pick-up location. In other examples, non-driving evaluator 112 can quantify the timeliness of the operator to the destination location. In yet other examples, non-driving evaluator 112 can quantify the overall freight service completion time (from the pick-up location to the destination location).

In some implementations, an individual at the pick-up location and/or destination location (e.g., the operator and/or requester) can confirm whether the operator picked up the load at the pick-up location and/or dropped off the load at the destination location. In such implementations, the individual can transmit a confirmation message from a mobile device (e.g., mobile device 140) to network computer system 100. For example, the individual can transmit the confirmation message from service application 145, through network(s) 130 and to network computer system 100. The confirmation message can include whether the load was picked up at the pick-up location or dropped-off/received at the destination location. In some examples, non-driving evaluator 112 can determine the time when the confirmation message was sent by the individual or received by network computer system 100. Additionally, non-driving evaluator 112 can take into account such times when determining the timeliness of the operator or confirming the pickup/drop-off times.

In other implementations, non-driving evaluator 112 can determine whether the operator is picking up a load or dropping off a load based on sensor information generated by mobile device 140. In such implementations, mobile device 140 can include one or more sensors (e.g., accelerometer and/or gyroscope) and the data generated from the one or more sensors can be included in interval data 131 (e.g., mobile device information 137 of mobile device 140) to be utilized by non-driving evaluator 112. provided to non-driving evaluator included in interval data 131. In some examples, non-driving evaluator 112 can determine that the sensor information correlates to the operator picking-up the load. In other examples, non-driving evaluator 112 can determine that the sensor information correlates to the operator dropping off the load. In conjunction with the

location information of mobile device **140**, non-driving evaluator **112** can confirm that the load was picked up at the pick-up location and/or dropped off at the destination location. Additionally, non-driving evaluator **112** can determine when the load was picked up and/or dropped off and take into account when the load was picked up and/or dropped off when determining the timeliness of the operator.

Non-driving evaluator **112** can also utilize feedback provided by a requester to evaluate the non-driving aspects of the performance of the operator. In some implementations, the requester can provide feedback by providing a rating or other quantitative metric related to one or more parameters of the operator's freight service performance. For example, network computer system **100** can provide an instruction to a service application running on a mobile device of a requester of a freight service request to generate a feedback user interface. The feedback user interface can enable the requester to provide a rating or other quantitative metric for one or more parameters of the operator's freight service performance. Examples of parameters of the operator's freight service performance that the requester can provide a rating or other quantitative metric for include, timeliness of operator to pick-up location, timeliness of operator to destination location, speed of loading the load, professionalism, courteousness, the overall delivery service of the requester and state of load at drop off. Additionally, non-driving evaluator **112** can utilize the provided ratings and quantitative metrics to determine an overall reputation score for the operator. In some implementations, non-driving evaluator **112** can compare the ratings and quantitative metrics provided by the mobile device of the requester to an operator model when determining a reputation score for the operator.

In some implementations, the requester can also provide qualitative comments in conjunction with their quantitative assessment of the operator's freight service performance. For example, the instruction to generate the feedback user interface can also include an instruction to enable the requester to input qualitative comments. In some instances, the instruction can cause the feedback user interface to generate a text box for the requester to manually input their comments. In other instances, the instruction can cause the feedback user interface to generate a dropdown menu of pre-generated comments for the requester to select.

Other non-driving related freight service performance examples that evaluator **102** can evaluate operator on include whether the operator has left freight vehicle **150** (e.g., cab **152**). In some implementations, non-driving evaluator **112** can utilize off-truck detect logic **110** to determine whether the operator has left freight vehicle **150**, based on the sensor information (e.g., accelerometer information and/or gyroscope information) of mobile device **140** (e.g., mobile device information **137** of mobile device **140**). In some examples, off-truck detect logic **110** can determine that the sensor information correlates to the operator stepping out of cab **152** of freight vehicle **150** (e.g., an acceleration in a negative direction). Additionally, mobile device **140** can time stamp the sensor information as to when such information was detected. As such, off-truck detect logic **110** can determine when the operator left cab **152**. In other implementations, off-truck detect logic **110** can determine whether the operator has left freight vehicle **150** based on whether mobile device **140** is wirelessly or directly connected to ELD **155**. For example, off-truck detect logic **110** can determine ELD **155** has been disconnected from mobile device **140**. In such an example, off-truck detect logic **110** can determine that the operator may have left cab **152** based in part on determining mobile device **140** and ELD **155** are

no longer connected. Additionally, off-truck detect logic **110** can determine and utilize the times of when mobile device **140** and ELD **155** were disconnected when evaluating the operator.

Evaluator **102** can select an operator model to compare interval data **131** of an operator to, based on freight service parameters associated with each operator model that most resembles the parameters of the freight service the operator performed. In such implementations, evaluator **102** can include an operator model database **114**. Operator model database **114** can store multiple operator models or just one generic operator model. In examples where operator model database **114** stores multiple operator models, each operator model can be associated with one or more freight service parameters. Examples of freight service parameters include a specific load weight, a range of load weight, a specific freight vehicle size, a range of freight vehicle sizes, a type of freight vehicle (e.g., a freight vehicle with refrigeration capabilities versus a freight vehicle without refrigeration capabilities), a type of load (e.g., perishable versus non-perishable loads, fragile versus non-fragile loads, etc.), weather conditions encountered and/or traffic conditions encountered.

Evaluator **102** can further analyze interval data **131** of the operator in light of weather data and/or traffic data when determining the driving and non-driving performance of the operator while operating freight vehicle **150**. In some implementations, evaluator **102** can obtain environmental information that includes the weather information and/or traffic information from a third-party provider. Alternatively, the weather information and/or traffic information can be obtained from one or more sensors from freight vehicle **150** and other freight vehicles traveling in and around the same region as freight vehicle **150**. In either implementation, evaluator **102** (e.g., safety logic **104**, performance logic **106** and/or non-driving evaluator **112**) can obtain the weather information and/or traffic information of the same region where the operator was operating freight vehicle **150** and during the same time interval as when interval data **131** was taken.

In some examples, safety logic **104** can determine a high safety score for the operator if compared to the operator model, safety logic **104** determines there was a higher rate of soft braking, a higher number of times freight vehicle **150** is accelerating, and that there were heavy rains and heavy traffic conditions at the time interval data **131** was taken and at the at the locations freight vehicle **150** was traveling in. In another example, performance logic can determine a low performance score for the operator if compared to the operator model, performance logic **106** determines a higher rate of hard braking, higher number of times freight vehicle **150** accelerated aggressively, fuel consumption was higher, and that it was sunny and traffic conditions were light at the time interval data **131** was taken and at the at the locations freight vehicle **150** was traveling in. In yet another example, non-driving evaluator **112** can determine a high timeliness score for the operator if compared to the operator model, non-driving evaluator **112** determines there was delay to the pick-up location, delay to the destination location, and there were heavy traffic conditions at the time interval data **131** was taken and at the locations freight vehicle **150** was traveling in.

Network computer system **100** can include monitor **116** to monitor an operator while an operator operates freight vehicle **150** during a time interval. As illustrated in FIG. 1, monitor **116** can include service time logic **118**, vehicle monitor **122** and operator restriction monitor **120**. In some

implementations, monitor **116** can determine whether the operator has exceeded a freight service time restriction (e.g., the maximum amount of time an operator is legally allowed to operate freight vehicle **150** or a predetermined time an operator can operate freight vehicle **150**). For example, vehicle monitor **122** can periodically or continuously obtain interval data **131** of an operator to determine whether an amount of time the operator has operated freight vehicle **150** is equal to or exceeded a freight service time restriction.

In some implementations, service time logic **118** can determine the amount of time an operator has operated freight vehicle **150** during a time interval (e.g., a hauling event, a day, a week, a month, etc.) based on interval data **131** obtained from activity data store **126** and/or operator store **124**. For example, service time logic **118** can determine how long an operator has operated freight vehicle **150** by determining (i) when mobile device **140** was connected to ELD **155**, (ii) when mobile device **140** was disconnected from ELD **155**, (iii) when the engine was turned on and/or (iv) when the engine was turned off. Additionally, in some implementations, service time logic **118** can determine the amount of time the operator has operated freight vehicle **150** by taking into account (i) instances or sub-intervals of when the operator stops operating freight vehicle **150** (e.g., by determining, from vehicle operation information **135**, when the engine of freight vehicle **150** is off), (ii) instances or sub-intervals of when freight vehicle **150** is idle (e.g., by determining, from vehicle operation information **135** and the location information of mobile device **140**, when the engine is on but freight vehicle **150** is not moving), and (iii) instances or sub-intervals of when operator has left freight vehicle **150** (e.g., from location information of mobile device **140** and/or whether mobile device **140** has disconnected from ELD **155**).

Additionally, in such implementations, monitor **116** can include operator restriction monitor **120** to determine whether the operator has exceeded a freight service time restriction, by determining whether the amount of time the operator has operated freight vehicle **150** is equal to or greater than the freight service time restriction. In some implementations, operator restriction monitor **120** can obtain data indicating the amount of time the operator has operated freight vehicle **150** in a time interval from service time logic **118**. Additionally, operator restriction monitor **120** can compare the amount of time the operator has operated freight vehicle **150** to the freight service time restriction. In some examples, operator restriction monitor **120** can determine that the amount of time the operator has operated freight vehicle **150** is equal to or exceeds the freight service time restriction. Additionally, operator restriction monitor **120** can restrict the operator from accepting or selecting a freight service request presented on service application **145**. For instance, operator restriction monitor **120** can provide an instruction to service application **145** to restrict the operator from selecting or accepting any freight service request presented by service application **145**.

In other examples, operator restriction monitor **120** can determine that the amount of time an operator has operated freight vehicle **150** is less than the freight service time restriction. In such examples, operator restriction monitor **120** can limit which freight service request the operator can select or accept that is presented on service application **145**. For instance, operator restriction monitor **120** can determine the amount of time remaining before the operator will exceed the freight service time restriction (e.g., based on interval data **131** of the operator, operator restriction monitor **120** can determine the amount of time remaining between

the amount of time the operator has already operated freight vehicle **150** and the freight service time restriction). Additionally, operator restriction monitor **120** can determine an estimated service completion time for each freight service request obtained by network computer system **100**. For instance, operator restriction monitor **120** can take into account the pick-up location, destination location, any indicated preferred time of freight service completion included in the freight service request. Taken together, operator restriction monitor **120** can identify one or more freight service requests obtained by network computer system **100** that have an estimated service completion time that is less than or equal to the amount of time remaining before the operator will exceed the freight service time restriction. In some implementations, operator restriction monitor **120** can provide an instruction to service application **145** to present only the identified one or more freight service requests. In other implementations, operator restriction monitor **120** can provide an instruction to service application **145** to limit the operator to only be able to select a freight service request that is one of the identified one or more freight service requests.

Other parameters, operator restriction monitor **120** can take into account when determining the estimated service completion time for each freight service request obtained by network computer system **100**, include (i) traffic data, (ii) weather data, and (iii) interval data **131** of an operator (e.g., current location of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150**, and information of mobile device **140**) operating freight vehicle **150**, when determining the estimated service completion time for each freight service request obtained by network computer system **100**.

FIG. 3 illustrates an example method for determining a time of arrival for a freight vehicle to arrive at a destination location. In some implementations, and similar to the example method illustrated in FIG. 2, network computer system **100** can associate an operator with mobile device **140** (**300**). Additionally, network computer system **100** can determine a current location of freight vehicle **150** being operated by the operator (**302**). For example, monitor **116** can obtain the location information of mobile device **140** from operator store **124** and/or activity data store **126**. Additionally, monitor **116** can determine the current location of freight vehicle **150** being operated by the operator based on the location information of mobile device **140**.

Network computer system **100** can determine a time of arrival for freight vehicle **150** to arrive at a given destination location (**304**). The destination location can be included in the freight service request assigned to the operator. In some examples, arrival component **134** can determine from interval data **131** (e.g., location information **133** of freight vehicle **150**, vehicle operation information **135** of freight vehicle **150** and mobile device information **137** of mobile device **140**) of the operator during a time interval when the operator is operating freight vehicle **150**, a time of arrival for freight vehicle **150** to arrive at the destination location. Additionally, based on interval data **131**, arrival component **134** can at any given instance a time of arrival for freight vehicle **150** to arrive at the destination location based on (i) a distance between the current location of freight vehicle **150** to the given destination location and (ii) a time for freight vehicle **150** to travel to the destination location.

Arrival component **134** can determine the distance between the current location of freight vehicle **150** to the destination location based on the location information of mobile device **140** and location information of the destina-

tion location included in the freight service request. Additionally, arrival component 134 can determine a time for freight vehicle 150 to travel to the destination location, based on the distance between the current location of freight vehicle 150 to the destination location and vehicle operation information 135 of freight vehicle 150 and/or mobile device information 137 of mobile device 140 (e.g., service time logic 118 can determine from vehicle operation information 135 of freight vehicle 150 and/or sensor data (accelerometer) and location information 133 of freight vehicle 150 from location information from a location based resource of mobile device 140 the speed that freight vehicle 150 is traveling).

In various implementations, arrival component 134 can take into account the minimum number of downtime intervals (e.g., rest periods or periods of time an operator is not operating freight vehicle 50 so as to not exceed a freight service time restriction) and the duration of each downtime intervals an operator should take, when determining the estimated time of arrival that freight vehicle 150 is to arrive at the pick-up location and/or destination location. In such implementations, the number of downtime intervals and the duration of each downtime interval can be based on (i) an estimated time for freight vehicle 150 to arrive at the destination location (e.g., based on the current location of freight vehicle 150), (ii) a distance between the current location of freight vehicle 150, (iii) the amount of time the operator has operated freight vehicle 150 (as determined from data generated by service time logic 118), and (iv) the service time restriction (as provided by operator restriction monitor 120).

In some implementations, arrival component 134 can take into account environmental information (e.g., traffic and/or weather information) when determining the minimal amount of time or downtime intervals that an operator should take as to not exceed a freight service time restriction. For example, the traffic conditions and weather conditions an operator may encounter or is currently encountering may cause freight vehicle 150 to slow down and cause delays. As such, arrival component 134 may determine that the operator should take more downtime intervals due to the traffic and weather conditions the operator is encountering or may encounter, which may result in the minimum number of downtime intervals increasing. In other examples, arrival component 134 may determine that the traffic conditions and/or the weather conditions the operator may encounter or is encountering may not inhibit the speed of freight vehicle 150. As such, arrival component 134 may determine the operator could take less downtime intervals. Meaning the minimum number of downtime intervals may decrease.

In various implementations, arrival component 134 can take into account when determining an estimated time of arrival, weather and/or traffic conditions the operator may be currently in while performing their assigned freight service. For example, a third-party provider can provide environmental information that includes weather information and/or real-time traffic information to arrival component 134. Arrival component 134 can determine the current weather and/or current traffic conditions at the current location of the operator and freight vehicle 150 based on the environmental information and the location information of mobile device 140. Additionally, arrival component 134 can determine any delays the operator is encountering and determine and/or adjust the estimated time of arrival based on the delays that the operator is encountering.

In some implementations, arrival component 134 can determine traffic conditions and/or weather conditions the

operator may encounter while performing their assigned freight service based on the sensor data and the hauling route the operator is taking. For example, arrival component 134 can determine that an accident occurred on the hauling route the operator is currently taking. In such an example, arrival component 134 can determine an estimated delay the operator may encounter and determine and/or adjust the estimate time of arrival based on the potential delay. In other examples, arrival component 134 can determine that weather conditions on the hauling route the operator is currently taking will likely get worse and cause a delay. In such examples, arrival component 134 can determine and/or adjust the estimated time of arrival based on the potential delay.

In some implementations, service time logic 118 can determine that an operator is currently in a downtime interval and arrival component 134 can utilize such data to determine a remaining amount of downtime the operator should be in before being able to resume operating freight vehicle 150. In such implementations, service time logic 118 can make such determinations based on interval data 131 of the operator provided by vehicle monitor 122. For example, service time logic 118 can determine that an operator is currently in a downtime interval and the amount of downtime the operator has left, based on vehicle operation information 135 of freight vehicle 150 (e.g., instances of when the engine was turned off) and/or mobile device information 137 of mobile device 140 (e.g., instances of when mobile device 140 was disconnected from electronic logging device 155 and/or instances of when the operator is not at the same location as freight vehicle 150) included in interval data 131. Additionally, based on the determined minimum duration of each downtime interval an operator should take, arrival component 134 can determine the amount of downtime remaining before the operator can resume operating freight vehicle 150.

In some examples, a downtime interval can include the estimated amount of time an operator is to pick up a load at the pick-up location. Arrival component 134 can determine the estimated amount of time an operator picks up a load at a pick-up location, based on historical interval data 131 (e.g., location information 133 of freight vehicle 150, vehicle operation information 135 of freight vehicle 150 and mobile device information 137 of mobile device 140) stored in operator store 124. In other examples, a downtime interval can include the estimated amount of time an operator is to change out a load that is already in trailer 154. In such examples, an operator could be assigned to multiple freight service requests, and upon arriving at one destination location, the operator is to drop off one load, but pick up another load, before proceeding to the next destination location. Arrival component 134 can determine the estimated amount of time an operator changes out a load, based on historical interval data 131 (e.g., location information 133 of freight vehicle 150, vehicle operation information 135 of freight vehicle 150 and mobile device information 137 of mobile device 140) stored in operator store 124.

Arrival component 134 can take into account the number of fuel stops freight vehicle 150 will likely have to take when determining the time of arrival freight vehicle is estimated to arrive at the pick-up location and/or destination location. Additionally, arrival component 134 can take into account the distance between the current location of freight vehicle 150 (e.g., location information 133) to the pick-up and/or destination location specified in the freight service request, when determining the number of fuel stops freight vehicle 150 will likely have to take. Additionally, arrival

component **134** can determine from vehicle operation information **135** (e.g., the amount of fuel used as compared to the average distance travelled) of interval data **131**, provided by vehicle monitor **122**, the fuel efficiency of freight vehicle **150**. Taken together, arrival component **134** can determine the number of fuel stops the operator may need to take to travel to the destination location.

Arrival component **134** can take into account size of a load a weight of the load and/or a type of the load to be transported by freight vehicle **150** when determining the estimated time of arrival. For example, the heavier the load, the slower freight vehicle **150** can travel. Additionally, the heavier the load, the worse the fuel efficiency of freight vehicle **150**. Meaning freight vehicle **150** may need more fuel to travel to destination location specified in a freight service request. In some examples, arrival component **134** can take into account, the type of load, for example, whether the load is fragile or not, when determining the estimated time of arrival. For instance, a fragile load could cause the operator to operate freight vehicle **150** more carefully and/or more slowly. In some implementations, the load size and/or weight can be included in the freight service request. In other implementations, the size and/or weight of the load may be detected by one or more sensors (e.g., optical and weight bearing sensors) included in trailer **154**. In such examples, the sensor data including the size and/or weight of the load can be included in interval data **131** provided by mobile device **140** and/or electronic logging device **155**.

In some implementations, arrival component **134** can take into account the size, weight and/or type of the load when determining the minimum number of downtime intervals the operator should take. For example, arrival component **134** may determine that the weight, size and/or type of load (e.g., a fragile load) of the load may cause freight vehicle **150** to travel slower. Arrival component **134** may determine the operator should take more downtime intervals. Meaning the minimum number of downtime intervals may increase. Additionally, arrival component **134** can also take into account the minimum number of downtime intervals the operator should take, when determining the estimated time of arrival of freight vehicle **150** to the pick-up and/or destination location.

Arrival component **134** can also include dock logic **132** to optimize the receiving and/or delivery of loads at the pick-up and/or destination location, respectively. In some implementations, dock logic **132** can assign a dock to freight vehicle **150** to either pick up a load specified in a freight service request and/or to drop off a load specified in a freight service request. In such implementations, the assignment of the dock can be based at least on the estimated time of arrival of freight vehicle **150**. Additionally, in other implementations, the assignment of the dock can be based on the estimated time of arrival of other freight vehicles that may also be arriving at approximately the same time. In such implementations, arrival component **134** can similarly determine the time of arrival of other freight vehicles as it can for freight vehicle **150**.

In various implementations, dock logic **132** can send dock routing instructions to an operator. The dock routing instructions can include instructions to route freight vehicle **150** to the dock assigned to the operator. The dock route can be based on the location information provided by a location based resource of mobile device **140** (e.g., location information **133** of freight vehicle **150**) and the location information of the dock assigned to the operator. In some implementations, dock logic **132** can provide the dock routing information to mobile device **140** when dock logic

**132** determines that freight vehicle **150** is within a proximity distance threshold of the pick-up location, destination location or the assigned dock. In such implementations, dock logic **132** can determine that freight vehicle **150** is within the proximity distance threshold based on interval data **131** of the operator (e.g., location information of mobile device **140**) and the pick-up location and/or destination location specified by the freight service request or the location information of the assigned dock. Dock logic **132** can obtain interval data **131** of the operator from vehicle monitor **122**.

Dock logic **132** can verify the identity of an operator that is picking up and/or dropping off a load specified in a freight service request that the operator that is also assigned to. For example, dock logic **132** can determine if identifier information provided by mobile device **140** of the corresponding operator matches the identifier information already associated with a freight service request. Examples of identifier information include, an operator identifier (e.g., a name of the operator, a photograph of the operator, a phone number of the operator, an identifier associated with government identification of the operator, etc.), a load identifier, a vehicle identifier of freight vehicle **150** that is transporting or will be transporting the load (e.g., VIN number of the freight vehicle), and a freight service identifier (e.g., location information of the pick-up location, location information of the destination location, an alpha numeric identifier, a load identifier, etc.).

Dock logic **132** can cause mobile device **140** of an operator assigned to the freight service request to provide identifier information that dock logic **132** can use to verify the identity of the operator. For example, dock logic **132** can cause mobile device **140** to provide the identifier information when freight vehicle **150** of the operator is within a proximity distance threshold of the pick-up location and/or destination location. Dock logic **132** can determine whether freight vehicle **150** is within a proximity distance threshold of the pick-up location and/or destination location based on the location information of mobile device **140** and the location information of the pick-up and/or destination location specified in the assigned freight service request, respectively. Upon dock logic **132** determining that freight vehicle is within the proximity distance threshold, dock logic **132** can provide instructions to mobile device **140** to provide the identifier information. In such implementations, dock logic **132** can utilize the identifier information provided by mobile device **140** to identify a copy of a freight service request with the same identifier information that is stored in operator store **124**.

#### Hardware Diagram

FIG. **4** is a block diagram that illustrates a computer system upon which examples described herein may be implemented. In one embodiment, computer system **400** may correspond to a mobile computing device, such as a cellular device that is capable of telephony, messaging, and data services. Computer system **400** can correspond to a device operated by a requester or, in some examples, a device operated by the service provider (e.g., a freight operator) that provides location-based services. Examples of such devices include smartphones, handsets, tablet devices, or in-vehicle computing devices that communicate with cellular carriers. Computer system **400** includes processor **410**, memory resources **420**, display component **430** (e.g., such as a touch-sensitive display device), one or more communication systems **440** (including wireless communication systems), one or more sensors **450** (e.g., accelerometer and/or gyroscope, microphone, barometer, etc.), and one or more location detection components (e.g., GPS compo-

nent) **460**. In one example, at least one communication system **440** sends and receives cellular data over network(s) **470** (e.g., data channels and voice channels). Communication sub-systems **440** can include a cellular transceiver and one or more short-range wireless transceivers. Processor **410** can exchange data with a service arrangement system (not illustrated in FIG. 4) via the one or more communications sub-systems **440** and over network(s) **970**.

Processor **410** can provide a variety of content to display component **430** by executing instructions stored in memory resources **420**. Memory resources **420** can store instructions for service application **425**. For example, processor **410** can execute the service application **425** to read sensor data from one or more sensors **450** of the computing device, and to transmit the sensor data, along with location data of GPS component **460** as local device data to a network computer system (e.g. network computer system **100**).

Examples described herein to extend to individual elements and concepts described herein, independently of other concepts, ideas or system, as well as for examples to include combinations of elements recited anywhere in this application. Although examples are described in detail herein with reference to the accompanying drawings, it is to be understood that the concepts are not limited to those precise examples. Accordingly, it is intended that the scope of the concepts be defined by the following claims and their equivalents. Furthermore, it is contemplated that a particular feature described either individually or as part of an example can be combined with other individually described features, or parts of other examples, even if the other features and examples make no mention of the particular feature. Thus, the absence of describing combinations should not preclude having rights to such combinations.

What is claimed is:

**1.** A computer-implemented method comprising:  
 obtaining a plurality of freight service requests, wherein the plurality of freight service requests are each associated with a completion time;  
 obtaining, from a computing device of a freight operator, interval data indicative of an amount of time the freight operator has operated a freight vehicle;  
 comparing the interval data with a freight service time restriction, the freight service time restriction indicative of a predetermined amount of time the freight operator may operate the freight vehicle;  
 determining that the freight operator has operated the freight vehicle less than the freight service time restriction over a duration of time; and  
 restricting, based on the completion times, the freight operator from accepting one or more respective freight service requests of the plurality of freight service requests, wherein the respective freight service requests are associated with a time matching or exceeding the freight service time restriction.

**2.** The computer-implemented method of claim **1**, wherein the time matching or exceeding the freight service time restriction is indicative of a preferred time of freight service completion.

**3.** The computer-implemented method of claim **1**, wherein restricting the freight operator comprises providing an instruction to generate a user interface, the user interface restricts the freight operator from selecting or accepting the respective freight service requests.

**4.** The computer-implemented method of claim **1**, further comprising:  
 monitoring a progress of the freight operator fulfilling an assigned freight service request during a time interval;

determining, based on the progress, an estimated service completion time for the assigned freight service request; and

identifying one or more freight service requests that are less than or equal to the amount of time remaining before the freight operator will exceed the freight service time restriction within the time interval.

**5.** The computer-implemented method of claim **4**, further comprising displaying, on the computing device, only the identified one or more freight service requests.

**6.** The computer-implemented method of claim **4**, wherein the estimated service completion time is indicative of at least one of (i) traffic data, (ii) weather data, or (iii) the interval data.

**7.** The computer-implemented method of claim **6**, wherein the interval data is indicative of a location of the freight vehicle.

**8.** The computer-implemented method of claim **1**, further comprising:

determining a minimum number of downtime intervals, wherein the minimum number of downtime intervals is indicative of one or more periods of time the freight operator is not operating the freight vehicle as to not exceed the freight service time restriction.

**9.** A computing system comprising:

one or more processors; and

one or more tangible, non-transitory, computer readable media that store instructions that are executable by the one or more processors to cause the computing system to perform operations, the operations comprising:

obtaining a plurality of freight service requests, wherein the plurality of freight service requests are each associated with a completion time;

obtaining, from a computing device of a freight operator, interval data indicative of an amount of time the freight operator has operated a freight vehicle;

comparing the interval data with a freight service time restriction, the freight service time restriction indicative of a predetermined amount of time the freight operator may operate the freight vehicle;

determining that the freight operator has operated the freight vehicle less than the freight service time restriction over a duration of time; and

restricting, based on the completion times, the freight operator from accepting one or more respective freight service requests of the plurality of freight service requests, wherein the respective freight service requests are associated with a time matching or exceeding the freight service time restriction.

**10.** The computing system of claim **9**, wherein the time matching or exceeding the freight service time restriction is indicative of a preferred time of freight service completion.

**11.** The computing system of claim **9**, wherein restricting the freight operator comprises providing an instruction to generate a user interface, the user interface restricts the freight operator from selecting or accepting the respective freight service requests.

**12.** The computing system of claim **9**, wherein the operations further comprise:

monitoring a progress of the freight operator fulfilling an assigned freight service request during a time interval;  
 determining, based on the progress, an estimated service completion time for the assigned freight service request; and

identifying one or more freight service requests that are less than or equal to the amount of time remaining

31

before the freight operator will exceed the freight service time restriction within the time interval.

13. The computing system of claim 12, wherein the operations further comprise displaying, on the computing device, only the identified one or more freight service requests.

14. The computing system of claim 12, wherein the estimated service completion time is indicative of at least one of (i) traffic data, (ii) weather data, or (iii) the interval data.

15. The computing system of claim 14, wherein the interval data is indicative of a location of the freight vehicle.

16. One or more non-transitory computer-readable media storing instructions that are executable by one or more processors to perform operations comprising:

obtaining a plurality of freight service requests, wherein the plurality of freight service requests are each associated with a completion time;

obtaining, from a computing device of a freight operator, interval data indicative of an amount of time the freight operator has operated a freight vehicle;

comparing the interval data with a freight service time restriction, the freight service time restriction indicative of a predetermined amount of time the freight operator may operate the freight vehicle;

determining that the freight operator has operated the freight vehicle less than the freight service time restriction over a duration of time; and

restricting, based on the completion times, the freight operator from accepting one or more respective freight

32

service requests of the plurality of freight service requests, wherein the respective freight service requests are associated with a time matching or exceeding the freight service time restriction.

17. The non-transitory computer-readable media of claim 16, wherein the time matching or exceeding the freight service time restriction is indicative of a preferred time of freight service completion.

18. The non-transitory computer-readable media of claim 16, wherein restricting the freight operator comprises providing an instruction to generate a user interface, the user interface restricts the freight operator from selecting or accepting the respective freight service requests.

19. The non-transitory computer-readable media of claim 16, wherein the operations further comprise:

monitoring a progress of the freight operator fulfilling an assigned freight service request during a time interval; determining, based on the progress, an estimated service completion time for the assigned freight service request; and

identifying one or more freight service requests that are less than or equal to the amount of time remaining before the freight operator will exceed the freight service time restriction within the time interval.

20. The non-transitory computer-readable media of claim 19, wherein the operations further comprise displaying, on the computing device, only the identified one or more freight service requests.

\* \* \* \* \*