



US009101058B2

(12) **United States Patent**
Podval et al.

(10) **Patent No.:** **US 9,101,058 B2**
(45) **Date of Patent:** **Aug. 4, 2015**

(54) **IC PACKAGE AND ASSEMBLY**

2201/09181 (2013.01); H05K 2201/10734
(2013.01); Y10T 29/49128 (2015.01)

(71) Applicant: **Marvell World Trade Ltd.**, St. Michael (BB)

(58) **Field of Classification Search**

CPC H05K 1/182
USPC 361/761
See application file for complete search history.

(72) Inventors: **Shimon Podval**, Rishon LeZion (IL);
Amihud Rothmann, Haifa (IL)

(73) Assignee: **Marvell World Trade Ltd.**, St. Michael (BB)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,175,158	B1 *	1/2001	Degani et al.	257/777
2004/0233651	A1 *	11/2004	Liu et al.	361/766
2005/0117314	A1 *	6/2005	Lien	361/761
2005/0121224	A1 *	6/2005	Lien	174/250
2012/0281375	A1 *	11/2012	Hsu	361/761
2012/0314390	A1 *	12/2012	Chang	361/761
2013/0121523	A1 *	5/2013	Pahl	381/361
2014/0133118	A1 *	5/2014	Sano	361/761

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 141 days.

(21) Appl. No.: **13/944,546**

(22) Filed: **Jul. 17, 2013**

(65) **Prior Publication Data**

US 2014/0022736 A1 Jan. 23, 2014

Related U.S. Application Data

(60) Provisional application No. 61/672,422, filed on Jul. 17, 2012, provisional application No. 61/710,430, filed on Oct. 5, 2012.

(51) **Int. Cl.**

H05K 5/00 (2006.01)
H05K 1/02 (2006.01)
H05K 3/30 (2006.01)
H05K 1/18 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 1/0296** (2013.01); **H05K 1/183** (2013.01); **H05K 3/30** (2013.01); **H05K**


* cited by examiner

Primary Examiner — Forrest M Phillips

(57) **ABSTRACT**

Aspects of the disclosure provide a circuit that includes a printed circuit board (PCB) substrate formed with an opening portion that is dimensioned to accommodate an integrated circuit (IC) package. When the IC package is disposed in the opening portion and is electrically coupled to the PCB substrate for PCB assembling, a thickness of the assembled PCB is less than a thickness sum of the IC package and the PCB substrate.

17 Claims, 5 Drawing Sheets






FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2




FIG. 3

IC PACKAGE AND ASSEMBLY

INCORPORATION BY REFERENCE

This present disclosure claims the benefit of U.S. Provisional Application No. 61/672,422, "DOUBLE SIDED STAMP IC MODULE" filed on Jul. 17, 2012, and U.S. Provisional Application No. 61/710,430, "PARTIAL PCB CUT-OUT FOR DOUBLE SIDED STAMP MODULE ASSEMBLY" filed on Oct. 5, 2012, which are incorporated herein by reference in their entirety.

BACKGROUND

The background description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent the work is described in this background section, as well as aspects of the description that may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present disclosure.

Multiple integrated circuits (IC) chips can be packaged together to form a multi-chip module (MCM). When the multiple IC chips are placed side by side, the MCM package may have a relatively large surface area, and when the multiple IC chips are stacked, the MCM package may have a relatively tall height.

SUMMARY

Aspects of the disclosure provide a circuit that includes a printed circuit board (PCB) substrate formed with an opening portion that is dimensioned to accommodate an integrated circuit (IC) package. When the IC package is disposed in the opening portion and is electrically coupled to the PCB substrate for PCB assembling, a thickness of the assembled PCB is less than a thickness sum of the IC package and the PCB substrate.

In an embodiment, the IC package includes an interposer and one or more IC components mounted on at least one side of the interposer, and the interposer includes a plurality of conductive components configured to electrically couple the IC package to the PCB substrate when the conductive components are aligned with corresponding conductive components on the PCB substrate.

In an example, the IC package includes a first IC chip and a second IC chip respectively mounted on a first side and a second side of the interposer. Further, an outline portion of the interposer is notched and at least partially plated to form the conductive components electrically coupling the interposer to the PCB substrate.

According to an aspect of the disclosure, the IC package is electrically coupled with the PCB substrate via at least one of wire bonding connections, plated connections, and ball-grid array connections. Further, the opening portion can be a through opening or a partial opening.

In an example, the opening portion is a partial opening, the IC components are mounted on a first side of the interposer, and the conductive components are solder balls disposed on a second side of the interposer, and the interposer is configured to fit into the partial opening with the solder balls being electrically coupled to a layer of the PCB underlying the partial opening.

Aspects of the disclosure provide a method that includes forming a substrate of a printed circuit board (PCB) with an opening portion that is dimensioned to accommodate an integrated circuit (IC) package, and disposing the IC package in

the opening portion to assemble the IC package into the PCB, and a thickness of the assembled PCB being less than a thickness combination of the IC package and the substrate.

Aspects of the disclosure provide an integrated circuit (IC) package. The IC package includes a first integrated circuit (IC) chip mounted on a first side of an interposer with dimensions being fittable into an opening on a printed circuit board (PCB) substrate, and a plurality of conductive components disposed on the interposer configured for electrically coupling the IC package with the PCB substrate. When the IC package is disposed and assembled on the PCB substrate, a thickness of the assembled PCB is less than a thickness sum of the IC package and the PCB substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of this disclosure that are proposed as examples will be described in detail with reference to the following figures, wherein like numerals reference like elements, and wherein:

FIGS. 1A-1D show diagrams of a printed circuit board substrate example and an integrated circuit (IC) package example according to an embodiment of the disclosure;

FIG. 2 shows a cross-section diagram of an assembled printed circuit board example according to an embodiment of the disclosure; and

FIG. 3 shows a flowchart outlining a process example according to an embodiment of the disclosure.

DETAILED DESCRIPTION OF EMBODIMENTS

FIG. 1A shows a surface view for a printed circuit board (PCB) substrate **101** and an integrated circuit (IC) package **102** according to an embodiment of the disclosure. The PCB substrate **101** includes an opening portion **130** into the surface. The opening portion **130** is dimensioned to accommodate the IC package **102**. The IC package **102** includes an interposer **150** and an IC chip mounted on a side of the interposer **150** to form a portion **160** that extended above the first side of the substrate, in accordance with an embodiment. The portion **160** is fit-able to be disposed into the opening portion **130**. When the IC package **102** is assembled on the PCB substrate **101**, the portion **160** fits into the opening portion **130** to reduce a thickness of the assembled PCB. Further, the PCB substrate **101** includes conductive connectors, such as lands **120**, and the IC chip package **102** includes conductive connectors **180** that in an embodiment are aligned with the lands **120** to form electrical connections when the IC package **102** is assembled into the PCB substrate **101**.

According to an embodiment of the disclosure, the opening portion **130** is a through opening without any PCB layers. In accordance with another embodiment, the opening portion **130** is a partial opening with a few PCB layers, namely less than all PCB layers, underlying the opening portion **130**.

FIG. 1B shows a cross-section view along A-A' for the PCB substrate **101** and the IC package **102** according to an embodiment of the disclosure. In this embodiment, the opening portion **130** is a partial opening with a few PCB layers, less than all of the PCB layers, underlying the opening.

FIG. 1C shows a cross-section view along A-A' for the PCB substrate **101** and the IC package **102** according to another embodiment of the disclosure. In this embodiment, the opening portion **130** is a through opening without any PCB layers.

FIG. 1D shows a cross-section diagram of the PCB substrate **101** and the IC package **102** assembled together. In FIG.

1D, the opening portion **130** is a partial opening with a few PCB layers, less than all of the PCB layers, underlying the opening.

Generally, an electronic device, such as a cell phone, a tablet, a laptop computer, and the like, includes one or more assembled PCB boards that have various electronic components, such as discrete components, integrated components, and the like, mounted on the PCB boards. In an embodiment, the size and thickness of the assembled PCB boards affect the size and thickness of the electronic device. Thus, the assembled PCB boards need to meet a size requirement and a thickness requirement.

The IC package **102** can be any suitable package, such as a single IC chip package, a multi-chip module (MCM) package, and the like. In an embodiment, the IC package **102** is multi-chip module (MCM) package that includes multiple IC chips stacked to reduce a footprint.

Specifically, in an example, the interposer **150** in the IC package **102** has a first side (e.g., the bottom side in FIGS. 1A-1D) and a second side (e.g., the upper side in FIGS. 1A-1D). The interposer **150** is a PCB substrate of a relatively smaller size compared to the PCB substrate **101**, in an embodiment. On the first side, one or more IC chips are mounted on the interposer **150**, for example using flip-chip technologies, to form a first portion **160** extended above the first side of the interposer **150**; and on the second side, one or more IC chips are mounted on the interposer **150**, for example using flip-chip technologies, to form a second portion **170** extended above the second side of the interposer **150**. The IC chips mounted on the interposer **150** are any suitable IC chips. In an example, the IC package **102** is a modem that includes one or more IC chips for baseband processing, and one or more IC chips for radio frequency processing. For example, the baseband processing chips are mounted on the first side to form the first portion **160**, and the radio frequency (RF) processing chips are mounted on the second side to form the second portion **170**. In an embodiment, the IC package **102** includes other suitable chip, such as a power management chip, and the like, mounted on the first side or the second side of the interposer **150**. It is noted that, in an example, the IC chips are encapsulated with the interposer **150** to form the IC package **102**. The first portion **160** and the second portion **170** can have the same shape and size or can have different shapes or sizes.

According to an embodiment of the disclosure, because both sides of the interposer **150** are used for mounting IC chips, the IC package **102** is implemented with a relatively small footprint but a relatively large thickness compared to a single side mounting technology in an example.

Further, the IC package **102** includes interface connectors implemented on the interposer **150**. In an example, the size of the interposer **150** is larger than the first portion **160** and the second portion **170** by a margin, and the interface connectors are implemented on the margin. The interface connectors can be implemented using any suitable technology, such as pins, solder balls, plated connectors, and the like. The interface connectors are electrically connected with the IC chips mounted on the interposer **150** via printed circuits on the interposer **150** for example. The interface connectors are configured to form electrically couplings with corresponding connectors on a PCB substrate when the IC package **102** is assembled on the PCB substrate, such as the PCB substrate **101**. The interface connectors and the corresponding connectors on the PCB substrate can be coupled together via any suitable connections, such as wire bonding connections, plated connections, ball-grid array connections, and the like.

In the FIGS. 1A-1D example, plated connectors **180** are formed on the margin of the interposer **150**. Specifically, the interposer **150** is shaped in a stamp card that has a plurality of notches, such as half through holes, along the outlines of the interposer **150**. The notches are plated of one or more conductive layers, such as a copper layer and the like to form the plated connectors **180**. In an example, the connective layer covers the surface in the notches and extends to the notch edges on one or both sides of the interposer **150**. In an example, the plated connectors **180** are formed similarly to through-holes with pads. It is noted that, in an example, the plated connectors **180** are isolated from each other by the non-plated portion of the interposer **150**. It is also noted that the plated connectors **180** can have other suitable configuration, such as plated fingers, and the like.

The PCB board substrate **101** includes various layers, such as isolation layers, metal layers and the like stacked together. The metal layers are patterned to provide routings to electronic components mounted on the PCB board substrate **101**, the isolation layers are placed between the metal layers to provide electrical isolation. Further, the opening portion **130** is formed into the surface of the PCB board substrate **101**. The opening portion **130** can be formed by any suitable technique, such as cut-out, etching, ablation, molding, and the like. In an embodiment, suitable layers of the PCB board substrate **101** are respectively formed with openings, and then the layers are aligned and stacked to form the PCB board substrate **101** with the opening portion **130**. In another embodiment, the layers of the PCB board substrate **101** are respectively formed without the openings, and the layers are stacked to build up the PCB board substrate **101**. Then, the opening portion **130** is formed after the PCB board substrate **101** is built-up. The opening portion **130** is dimensioned to accommodate the first portion **160**, and thus the first portion **160** can fit into the opening portion **130**.

In an embodiment, the opening portion **130** is a partial opening portion, such as seen in FIG. 1B. In the FIG. 1B example, the PCB substrate **101** includes metal layers **141**, **142** and **143** within the PCB substrate **101**. It is noted that, in an example, the PCB substrate **101** has metal layers on the surfaces of the PCB substrate **101**. Due to the opening portion **130**, the metal layer **141** does not exist in the opening portion **130**. However, the metal layers **142** and **143** still exist under the opening portion **130**, and thus the metal layers **142** and **143** are patterned and used for routing purpose.

In another embodiment, the opening portion **130** is a through opening portion, such as shown in FIG. 1C. In the FIG. 1C example, all the layers of the PCB substrate **101** do not exist in the opening portion **130**.

According to an aspect of the disclosure, the plurality of lands **120** is formed to match with the interface connectors of the IC packages **102**, such as the plated connectors **180**. For example, the plurality of lands **120** is formed on the PCB substrate **101** with a margin to the opening portion **130**. The lands **120** are formed of conductive material, such as copper, and the like and are electrically connected to wires formed of the patterned metal layers of the PCB substrate **101**. Further, the lands **120** are positioned to be aligned with the interface connectors of the IC package **102**, such as the plated connectors **180**.

According to the disclosure, to assemble the IC package **102** on the PCB substrate **101**, the first portion **160** fits into the opening portion **130**, and then the plated connectors **180** are aligned with the lands **120** and in contact with the lands **120**, as shown in FIG. 1D. In an embodiment, when a plated connector **180** is in contact with a land **120**, the plated connector **180** and the land **120** form electrical connection. In

another embodiment, the plated connector **180** and the land **120** are soldered together by melting and flowing a filler metal into the notch of the plated connector **180**.

According to an aspect of the disclosure, because the first portion **160** can fit into the opening portion **130**, the thickness of the assembled PCB is less than a thickness sum of the IC package **102** and the PCB substrate **101**. In an example, the thickness of one IC chip is about 1 mm, and the thickness of the IC package substrate **102** is about 2 mm. In an embodiment, the thickness specification for an electronic device allows about 1 mm thickness addition to the thickness of a PCB substrate. When the first portion **160** fits into the opening portion **130**, the thickness of the assembled PCB is about 1 mm in addition to the thickness of the PCB substrate **101**, and satisfies the thickness specification.

FIG. 2 shows a cross-section diagram of an assembled PCB example **200** according to an embodiment of the disclosure. The PCB **200** includes a PCB substrate **201** and an IC package **202**. The PCB substrate **201** includes an opening portion **230** into the surface. The opening portion **230** is dimensioned to accommodate the IC package **202**. The IC package **202** includes an interposer **250** and an IC chip mounted on a side of the interposer **250**. The IC package **202** is fit-able to be disposed into the opening portion **230**. When the IC package **202** is assembled on the PCB substrate **201**, the IC package **202** fits into the opening portion **230** to reduce a thickness of the assembled PCB **200**.

Further, the PCB substrate **201** includes conductive connectors, such as lands **220**, and the IC chip package **202** includes conductive connectors **280** that can be aligned with the lands **220** to form electrical connections when the IC package **202** is assembled into the PCB substrate **201**.

In the FIG. 2 example, the opening portion **230** is a partial opening with a few PCB layers, less than all of the PCB layers, underlying the opening portion **230**.

The IC package **202** can be any suitable package, such as a single IC chip package, a multi-chip module (MCM) package, and the like. In an embodiment, the IC package **202** is multi-chip module (MCM) package that includes multiple IC chips stacked to reduce a footprint. In an example, the IC package **202** includes an interposer **250** having a first side and a second side. In an example, the interposer **250** is a suitable PCB-like substrate of a relatively smaller size compared to the PCB substrate **201**. On the first side, one or more IC chips are mounted on the interposer **250**, for example using flip-chip technologies, to form a first portion **260** extended above the first side of the interposer **250**. In an example, the IC chips are mounted side by side on the first side of the interposer **250**. In another example, the IC chips are stacked together and the stacked IC chips are mounted on the first side of the interposer **250**.

Further, the IC package **202** includes interface connectors implemented on the interposer **250**. In an example, the IC package **202** is a ball grid array package that has a plurality of solder balls **280** arranged in an array. The solder balls **280** are electrically connected with the IC chips mounted on the interposer **250**. The solder balls **280** are configured to form electrical couplings with corresponding connectors on the PCB substrate **201** when the IC package **202** is assembled on the PCB substrate **201**.

The PCB board substrate **201** includes various layers, such as isolation layers, metal layers and the like stacked together. The metal layers are patterned to provide routings to electronic components mounted on the PCB board substrate **201**, the isolation layers are placed between the metal layers to provide electrical isolation. Further, the opening portion **230** is formed into the surface of the PCB board substrate **201**. The

opening portion **230** can be formed by any suitable technique, such as cut-out, etching, and the like. The PCB substrate **201** includes metal layers **241**, **242** and **243** within the PCB substrate **201**. It is noted that, in an example, the PCB substrate **201** has metal layers on the surfaces of the PCB substrate **201**. Due to the opening portion **230**, the metal layer **241** does not exist in the opening portion **230**. However, the metal layer **243** still exists under the opening portion **230**, and thus the portion of the metal layer **243** under the opening portion **230** is patterned and used for routing purpose.

According to an aspect of the disclosure, the plurality of lands **220** is formed to match with the solder balls **280** of the IC packages **202**. For example, the plurality of lands **220** is formed on a metal layer underlying the opening portion **230**. In an example, the lands **220** are formed of the metal layer **242**. The lands **220** are positioned to be able to align with the solder balls **280**.

According to the disclosure, to assemble the IC package **202** on the PCB substrate **201**, the IC package **202** fits into the opening portion **230**, and then the solder balls **280** are aligned with the lands **220** and in contact with the lands **220** to form the electrical connections. In an embodiment, suitable technique is used to apply reflow solder on the lands **220** to enable the formation of the electrical connections. In an example, reflow solder is applied using masks. In an example, one or more masks are respectively dimensioned to allow the reflow solder to be applied on the lands **220**. In another example, a suitable dropper is used to apply the reflow solder on the lands **220**.

According to an aspect of the disclosure, because the IC package **202** fits into the opening portion **230**, the thickness of the assembled PCB is less than a thickness sum of the IC package **202** and the PCB substrate **201**.

FIG. 3 shows a flowchart outlining a process example according to an embodiment of the disclosure. In an example, the process is used to implement an assembled PCB. The process starts at S301 and proceeds to S310.

At S310, an IC package is formed. In an example, to form the IC package **102**, the interposer **150** is shaped to have notches in the outlines of the interposer **150** and the notches are plated to form the plated connectors **180**. Further, in an example, the baseband processing IC chips are mounted on the first side of the interposer **150** to form the first portion **160**, and the radio frequency processing IC chips are mounted on the second side of the interposer **150**. In another example, the IC package **202** is formed. The IC package **202** is a ball grid array type package that includes the solder balls **280** on a side of the interposer **250**.

At S320, a PCB substrate with an opening is formed. The opening is dimensioned to accommodate an IC package or a portion of the IC package. In an example, the PCB substrate **101** is formed with the opening portion **130**. The opening portion **130** can be a through opening or a partial opening. The opening portion **130** matches the shape and size of the first portion **160** of the IC package **102**. Further, the PCB substrate **101** includes the lands **120** formed on a margin portion of the PCB substrate **101** to the opening portion **130**. The lands **120** are configured to be align-able with the plated connectors **180**. In another example, the PCB substrate **201** is formed with the opening portion **230**. The opening portion **230** is a partial opening that accommodates the IC package **202**. Further, the PCB substrate **201** includes lands **220** formed underlying the partial opening. The lands **220** are configured to be align-able with the solder balls **280**.

At S330, the package is assembled on the PCB substrate. In an example, to assemble the IC package **102** onto the PCB substrate **101**, the first portion **160** fits into the opening por-

tion **130** to reduce the thickness of the assembled PCB. Then, the plated connectors **180** of the IC package **102** are aligned with the lands **120** on the PCB substrate **101** and are in contact with the lands **120** to form electrical connections. In an example, the plated connectors **180** are soldered with the lands **120** to form the electrical connections. Thus, the IC package **102** is assembled on the PCB substrate **101**, and the thickness of the assembled PCB is less than the thickness sum of the IC package **102** and the PCB substrate **101**. In another example, the IC package **202** is disposed in the opening portion **230**, and the solder balls **280** are aligned and in contact with the lands **220** to form the assembled PCB **200**. The thickness of the assembled PCB **200** is less than the thickness sum of the IC package **202** and the PCB substrate **201**. Then, the process proceeds to **S399** and terminates.

While aspects of the present disclosure have been described in conjunction with the specific embodiments thereof that are proposed as examples, alternatives, modifications, and variations to the examples may be made. Accordingly, embodiments as set forth herein are intended to be illustrative and not limiting. There are changes that may be made without departing from the scope of the claims set forth below.

What is claimed is:

1. A circuit, comprising:
 - an integrated circuit (IC) package that includes an interposer having an outline portion that is notched with each notch at least partially plated to form conductive components within the notches;
 - a printed circuit board (PCB) substrate formed with an opening portion that is dimensioned to accommodate the IC package; and
 - wherein when the IC package is disposed in the opening portion and is electrically coupled to the PCB substrate for PCB assembling, a thickness of the assembled PCB is less than a thickness sum of the IC package and the PCB substrate.
2. The circuit of claim 1, wherein the IC package includes the interposer and one or more IC components mounted on at least one side of the interposer, and the interposer includes the plurality of conductive components configured to electrically couple the IC package to the PCB substrate when the conductive components are aligned with corresponding conductive components on the PCB substrate.
3. The circuit of claim 2, wherein the IC package includes a first IC chip and a second IC chip respectively mounted on a first side and a second side of the interposer.
4. The circuit of claim 1, wherein the IC package is electrically coupled to the PCB substrate via at least one of wire bonding connections, plated connections, and ball-grid array connections.
5. The circuit of claim 1, wherein the opening portion is a through opening or a partial opening.
6. The circuit of claim 2, wherein the opening portion is a partial opening, the IC components are mounted on a first side of the interposer, and the conductive components are solder balls disposed on a second side of the interposer, and the interposer is configured to fit into the partial opening with the solder balls being electrically coupled to a layer of the PCB underlying the partial opening.
7. A method, comprising:
 - forming a substrate of a printed circuit board (PCB) with an opening portion that is dimensioned to accommodate an integrated circuit (IC) package;
 - mounting one or more IC components on at least one side of an interposer;
 - forming notches in an outline portion of the interposer;

plating the notches to form conductive components; and disposing the IC package in the opening portion to assemble the IC package into the PCB, and a thickness of the assembled PCB being less than a thickness combination of the IC package and the substrate.

8. The method of claim 7, further comprising forming the IC package, wherein forming the IC package further comprises:

forming the plurality of conductive components on the interposer to electrically couple the IC package to the substrate when the conductive components are aligned with corresponding conductive components on the substrate.

9. The method of claim 8, wherein mounting the one or more IC components on at least one side of the interposer further comprises:

mounting a first IC chip on a first side of the interposer; and mounting a second IC chip on a second side of the interposer.

10. The method of claim 7, further comprising: coupling the IC package electrically to the substrate via at least one of wire bonding connections, plated connections, ball-grid array connections.

11. The method of claim 7, wherein forming the substrate of the PCB with the opening portion that is dimensioned to accommodate IC package further comprises at least one of:

forming the substrate of the PCB with a through opening portion; and

forming the substrate of the PCB with a partial opening portion.

12. The method of claim 8, wherein forming the substrate of the PCB with a partial opening; forming conductive lands in a layer of the PCB underlying the partial opening; and

disposing the IC package into the partial opening with solder balls of the IC package being electrically coupled with the conductive lands in the layer of the PCB underlying the partial opening.

13. An integrated circuit (IC) package, comprising: a first integrated circuit (IC) chip mounted on a first side of an interposer with an outline portion of the interposer that is notched and at least partially plated to form conductive components with dimensions being fit-table for disposing into an opening on a printed circuit board (PCB) substrate; and

the plurality of conductive components disposed on the interposer configured for electrically coupling the IC package with the PCB substrate, wherein when the IC package is disposed and assembled in the opening formed in the PCB substrate, a thickness of the assembled PCB is less than a thickness sum of the IC package and the PCB substrate.

14. The IC package of claim 13, wherein the IC package includes a second IC chip mounted on a second side of the interposer.

15. The IC package of claim 13, wherein the conductive components are at least one of wire bonding connections, plated connections, and ball-grid array connections.

16. The IC package of claim 13, wherein the opening portion is a through opening or a partial opening.

17. The IC package of claim 13, wherein the opening portion is a partial opening, the conductive components are solder balls disposed on a second side of the interposer, and the interposer is configured to fit into the partial opening with

the solder balls being electrically coupled to a layer of the PCB substrate underlying the partial opening.

* * * * *