

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 10,938,970 B1**
(45) **Date of Patent:** **Mar. 2, 2021**

(54) **MOBILE TERMINAL**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventors: **Jaewook Lee**, Seoul (KR); **Insu Song**, Seoul (KR); **Timothy Kang**, Seoul (KR); **Minsoo Kim**, Seoul (KR); **Sunglyong Cha**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/843,828**

(22) Filed: **Apr. 8, 2020**

Related U.S. Application Data

(63) Continuation of application No. PCT/KR2019/017100, filed on Dec. 5, 2019.

(51) **Int. Cl.**
H04B 1/38 (2015.01)
H04M 1/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04M 1/0268** (2013.01); **H04M 1/0237** (2013.01)

(58) **Field of Classification Search**
CPC H04M 1/0268; H04M 1/0237; H04M 1/02; G06F 1/1681; G06F 1/1643;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,805,439 B2 * 8/2014 Kim H04M 1/72577 455/556.1
10,185,363 B2 * 1/2019 Hiroki G06F 1/1652
(Continued)

FOREIGN PATENT DOCUMENTS

CN 108664087 10/2018
EP 3258675 12/2017
(Continued)

OTHER PUBLICATIONS



PCT International Application No. PCT/KR2019/017100, International Search Report dated Oct. 20, 2020, 8 pages.
(Continued)

Primary Examiner — Pablo N Tran
(74) *Attorney, Agent, or Firm* — Lee, Hong, Degerman, Kang & Waimey

(57) **ABSTRACT**

A mobile terminal includes a first frame having a first side-face, a second frame moveable in a first direction or a second direction opposite to the first direction from the first frame, and having a second side-face facing the first side-face, and a slide bar positioned between the first side-face and the second side-face, and extending in the first direction, wherein the second frame moves in the first direction to convert a state of the mobile terminal from a first state in which the first frame and the second frame are overlapped with each other to a second state, and wherein the second frame moves in the second direction to convert the state from the second state to the first state. The mobile terminal reduces friction between the first and second frames through a simple slide structure, so that the state conversion between the first and second states is easy.

13 Claims, 14 Drawing Sheets



- (51) **Int. Cl.**
G09F 9/30 (2006.01)
G06F 1/16 (2006.01)

- (58) **Field of Classification Search**
CPC G06F 1/1656; G06F 1/1641; G06F 1/1652;
G09F 9/301; G09F 9/30; H05K 5/02;
G02F 1/1333; H04B 1/38
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,359,810 B2 * 7/2019 Miyake H01L 51/0097
10,481,638 B2 * 11/2019 Yoshizumi G06F 1/1626
10,613,586 B2 * 4/2020 Yamazaki G06F 1/1698
2014/0211399 A1 7/2014 O'Brien
2016/0216737 A1 7/2016 Hayk et al.
2017/0290530 A1 * 10/2017 Hong A61B 5/1116
2018/0102072 A1 4/2018 Lee et al.
2019/0268455 A1 8/2019 Baek et al.
2020/0089273 A1 * 3/2020 Watamura G06F 1/1626
2020/0249722 A1 * 8/2020 Cha H04M 1/0268

FOREIGN PATENT DOCUMENTS

KR 101784880 10/2017
KR 1020190001389 1/2019
KR 1020190004618 1/2019

OTHER PUBLICATIONS

European Patent Office Application Serial No. 20171360.9, Search Report dated Oct. 15, 2020, 14 pages.

* cited by examiner

FIG. 1




FIG. 3







FIG. 4



(a)



(b)

FIG. 5




FIG. 6




FIG. 7





FIG. 8




FIG. 9







FIG. 10




(a)




(b)

FIG. 11



(a)



(b)

FIG. 12





FIG. 13







FIG. 14



(a)



(b)

MOBILE TERMINAL**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of International Application No. PCT/KR2019/017100, filed on Dec. 5, 2019, the contents of which are hereby incorporated by reference herein in its entirety.

BACKGROUND**Field**

The present disclosure relates to a mobile terminal, and to a mobile terminal having a flexible display.

Discussion of the Related Art

Terminals may be generally classified as mobile/portable terminals or stationary terminals according to their mobility. Mobile terminals may also be classified as handheld terminals or vehicle mounted terminals according to whether or not a user can directly carry the terminal.

A display device is a device having a function of receiving, processing, and displaying a video that a user may watch. For example, the display device receives a broadcast selected by the user from broadcast signals transmitted from a broadcasting station, separates a video signal from the received signals, and displays the separated video signal on a display.

In recent years, because of a development of a broadcasting technology and a network technology, functions of the display device have also been considerably diversified, and a performance of the device has been improved accordingly. That is, the display device has been developed to provide not only broadcast contents but also various other contents to the user. For example, the display device may provide game play, music listening, internet shopping, user customized information, and the like using various applications as well as programs received from the broadcasting station. In order to perform such extended functions, the display device may be basically connected to other devices or networks using various communication protocols, and may provide the user with an ubiquitous computing environment. In other words, the display device has evolved into a smart device that enables connectivity to a network and continuous computing.

Recently, a flexible display, which has sufficient elasticity, and thus, be able to be deformed largely, has been developed. A size of the mobile terminal may be varied using a deforming property of the flexible display. In the mobile terminal having such a variable structure, a change in the structure of the mobile terminal must be performed stably. Further, a support structure and the like of the variable display unit may be a problem.

SUMMARY

A purpose of the present disclosure is to provide a mobile terminal having a tensioning structure that may move in association with movement of a display and a frame when the mobile terminal slides, and may maintain a flat state.

Purposes of the present disclosure are not limited to the above-mentioned purpose. Other purposes and advantages of the present disclosure as not mentioned above may be understood from following descriptions and more clearly

understood from embodiments of the present disclosure. Further, it will be readily appreciated that the purposes and advantages of the present disclosure may be realized by features and combinations thereof as disclosed in the claims.

5 One aspect of the present disclosure proposes a mobile terminal including a first frame, a second frame moving in a first direction from the first frame to convert a state of the mobile terminal from a first state to a second state, and sliding in a second direction opposite to the first direction in the second state to convert the state of the mobile terminal to the first state, a slide frame movable in the first direction or in the second direction with respect to the second frame, a flexible display unit including a first region coupled to the first frame, a second region coupled to the slide frame, and a third region positioned between the first region and the second region and bent while surrounding the second frame, a tensioning belt having one side fixed to the first frame and the other side coupled to the slide frame, and a belt roller positioned at a second directional side of the second frame, and wound with the tensioning belt.

In one implementation, one side of the tensioning belt may be disposed adjacent to a first directional end of the first frame, and the belt roller may be disposed at a second directional end of the second frame.

10 In one implementation, the first frame may include a first front portion coupled with the first region and a first rear portion spaced rearward from the first front portion, the second frame may include a second rear portion located on a rear face of the first rear portion in the first state, and the belt roller may have a diameter corresponding to a thickness of the second rear portion.

In one implementation, the mobile terminal may further include a pair of tensioning pins arranged at the first directional end of the first frame and arranged in a vertical direction, and wherein the tensioning belt may be wound around the pair of tensioning pins in an S-shape, wherein one end of the tensioning belt may be coupled to a first front portion of the first frame.

In one implementation, the tensioning belt may be in contact with one side of the tensioning pin, and the mobile terminal may further include an elastic body for pressing the other side of the tensioning pin.

In one implementation, the mobile terminal may further include a tensioning seat positioned on rear faces of the second region and the third region of the flexible display unit, wherein both ends of the tensioning seat are coupled to one end of the tensioning belt.

In one implementation, the mobile terminal may further include a link rail coupled to one of the first frame and the second frame, and extending in a third direction perpendicular to the first direction, and a support link having one end moving along the link rail and the other end coupled to the other of the first frame or the second frame.

In one implementation, the support link may be disposed in the third direction perpendicular to the first direction in the first state, and the support link may support the third region of the display unit while traversing an extended portion of the second frame in the second state.

In one implementation, the support link may include a first coupling hinge pivotably coupled to one end of the support link, and fastened to the link rail, and a second coupling hinge pivotably coupled to the other end of the support link, and fixed to one of the first frame and the second frame.

In one implementation, the link rail may include a first rail having a width of a first size and a second rail having a width of a second size greater than the first size, and the first

coupling hinge may include a slide protrusion having a thickness corresponding to the width of the first rail, and an extended end positioned at an end of the slide protrusion and having a diameter corresponding to the width of the second rail.

In one implementation, the link rail may include the second rail disposed at a center, and a plurality of first rails arranged symmetrically, and a pair of support links may be symmetrically arranged in the third direction, and wherein first coupling hinges of the pair of support links may move in opposite directions on the pair of first rails.

In one implementation, the second rail may have a shape corresponding to the extended end, and the extended end partially may overlap or may not overlap the second rail in the first state.

In one implementation, the first frame may include a first front portion coupled with the first region, and a first rear portion spaced rearward from the first front portion, and the second frame may further include a second rear portion located on a rear face of the first rear portion in the first state, and a display support positioned on a rear face of the first front portion in the first state, and positioned on a rear face of the third region of the display unit in the second state.

The features of the above-described implantations may be combined with other embodiments as long as they are not contradictory or exclusive to each other.

Effects of the present disclosure are as follows but are limited thereto.

According to the present disclosure, the display unit may be prevented from being separated when the state of the mobile terminal is converted or in the converted state of the mobile terminal, thereby improving usability.

According to the present disclosure, even when the tensioning structure is added, because a driving resistance is small, a flatness of the display unit may be increased without causing a decrease in driving force of the mobile terminal.

According to the present disclosure, because a uniform tensile force may be applied at all times, so that free stop is available in any state.

According to the present disclosure, because the tensile force is not directly applied to the display unit using the tensioning seat that receives a force of the tensioning belt, a reliability of the display unit may be improved.

Further scope of the applicability of the present disclosure will become apparent from a detailed description below. However, various changes and modifications within the spirit and scope of the present disclosure may be clearly understood by those skilled in the art, so that it is to be understood that the specific embodiments, such as the detailed description and the preferred embodiments of the present disclosure, are given by way of example only.

BRIEF DESCRIPTION OF DRAWINGS

The present invention will become more fully understood from the detailed description given herein below and the accompanying drawings, which are given by illustration only, and thus are not limitative of the present invention, and wherein:

FIG. 1 is a block diagram of a mobile terminal in accordance with the present disclosure.

FIG. 2 is an exploded perspective view of a mobile terminal according to one embodiment;

FIG. 3 shows perspective views respectively illustrating a first state and a second state viewed from one side of a mobile terminal according to one embodiment;

FIG. 4 shows rear face views respectively illustrating a first state and a second state of a mobile terminal according to one embodiment;

FIG. 5 shows cross-sectional views respectively taken along a line A-A and a line B-B of FIG. 3;

FIG. 6 illustrates cross-sectional views taken along a line C-C and a line D-D of FIG. 3;

FIG. 7 illustrates a tensioning structure coupled to a display unit;

FIG. 8 illustrates a tensioning belt and a tensioning seat;

FIGS. 9 to 12 are diagrams illustrating an assembly flowchart of a mobile terminal;

FIG. 13 illustrates a support structure based on states of a mobile terminal; and

FIG. 14 is an enlarged view of the support structure of FIG. 13.

DETAILED DESCRIPTIONS

Description will now be given in detail according to exemplary embodiments disclosed herein, with reference to the accompanying drawings. For the sake of brief description with reference to the drawings, the same or equivalent components may be provided with the same reference numbers, and description thereof will not be repeated. In general, a suffix such as “module” and “unit” may be used to refer to elements or components. Use of such a suffix herein is merely intended to facilitate description of the specification, and the suffix itself is not intended to give any special meaning or function. In the present disclosure, that which is well-known to one of ordinary skill in the relevant art has generally been omitted for the sake of brevity. The accompanying drawings are used to help easily understand various technical features and it should be understood that the embodiments presented herein are not limited by the accompanying drawings. As such, the present disclosure should be construed to extend to any alterations, equivalents and substitutes in addition to those which are particularly set out in the accompanying drawings.

It will be understood that although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are generally only used to distinguish one element from another.

It will be understood that when an element is referred to as being “connected with” another element, the element can be directly connected with the other element or intervening elements may also be present. In contrast, when an element is referred to as being “directly connected with” another element, there are no intervening elements present.

A singular representation may include a plural representation unless it represents a definitely different meaning from the context.

Terms such as “include” or “has” are used herein and should be understood that they are intended to indicate an existence of several components, functions or steps, disclosed in the specification, and it is also understood that greater or fewer components, functions, or steps may likewise be utilized.

FIG. 1A is a block diagram of a mobile terminal in accordance with the present disclosure.

The mobile terminal **100** is shown having components such as a wireless communication unit **110**, an input unit **120**, a sensing unit **140**, an output unit **150**, an interface unit **160**, a memory **170**, a controller **180**, and a power supply unit **190**. Referring now to FIG. 1A, the mobile terminal **100** is shown having wireless communication unit **110** config-

ured with several commonly implemented components. It is understood that implementing all of the illustrated components is not a requirement, and that greater or fewer components may alternatively be implemented.

More specifically, the wireless communication unit **110** typically includes one or more modules which permit communications such as wireless communications between the mobile terminal **100** and a wireless communication system, communications between the mobile terminal **100** and another mobile terminal, communications between the mobile terminal **100** and an external server. Further, the wireless communication unit **110** typically includes one or more modules which connect the mobile terminal **100** to one or more networks.

To facilitate such communications, the wireless communication unit **110** includes one or more of a broadcast receiving module **111**, a mobile communication module **112**, a wireless Internet module **113**, a short-range communication module **114**, and a location information module **115**.

Regarding the wireless communication unit **110**, the broadcast receiving module **111** is typically configured to receive a broadcast signal and/or broadcast associated information from an external broadcast managing entity via a broadcast channel. The broadcast channel may include a satellite channel, a terrestrial channel, or both. In some embodiments, two or more broadcast receiving modules **111** may be utilized to facilitate simultaneously receiving of two or more broadcast channels, or to support switching among broadcast channels.

The mobile communication module **112** can transmit and/or receive wireless signals to and from one or more network entities. Typical examples of a network entity include a base station, an external mobile terminal, a server, and the like. Such network entities form part of a mobile communication network, which is constructed according to technical standards or communication methods for mobile communications (for example, Global System for Mobile Communication (GSM), Code Division Multi Access (CDMA), CDMA2000 (Code Division Multi Access 2000), EV-DO (Enhanced Voice-Data Optimized or Enhanced Voice-Data Only), Wideband CDMA (WCDMA), High Speed Downlink Packet access (HSDPA), HSUPA (High Speed Uplink Packet Access), Long Term Evolution (LTE), LTE-A (Long Term Evolution-Advanced), and the like).

Examples of wireless signals transmitted and/or received via the mobile communication module **112** include audio call signals, video (telephony) call signals, or various formats of data to support communication of text and multimedia messages.

The wireless Internet module **113** is configured to facilitate wireless Internet access. This module may be internally or externally coupled to the mobile terminal **100**. The wireless Internet module **113** may transmit and/or receive wireless signals via communication networks according to wireless Internet technologies.

Examples of such wireless Internet access include Wireless LAN (WLAN), Wireless Fidelity (Wi-Fi), Wi-Fi Direct, Digital Living Network Alliance (DLNA), Wireless Broadband (WiBro), Worldwide Interoperability for Microwave Access (WiMAX), High Speed Downlink Packet Access (HSDPA), HSUPA (High Speed Uplink Packet Access), Long Term Evolution (LTE), LTE-A (Long Term Evolution-Advanced), and the like. The wireless Internet module **113** may transmit/receive data according to one or more of such wireless Internet technologies, and other Internet technologies as well.

In some embodiments, when the wireless Internet access is implemented according to, for example, WiBro, HSDPA, HSUPA, GSM, CDMA, WCDMA, LTE, LTE-A and the like, as part of a mobile communication network, the wireless Internet module **113** performs such wireless Internet access. As such, the Internet module **113** may cooperate with, or function as, the mobile communication module **112**.

The short-range communication module **114** is configured to facilitate short-range communications. Suitable technologies for implementing such short-range communications include BLUETOOTH™, Radio Frequency IDentification (RFID), Infrared Data Association (IrDA), Ultra-WideBand (UWB), ZigBee, Near Field Communication (NFC), Wireless-Fidelity (Wi-Fi), Wi-Fi Direct, Wireless USB (Wireless Universal Serial Bus), and the like. The short-range communication module **114** in general supports wireless communications between the mobile terminal **100** and a wireless communication system, communications between the mobile terminal **100** and another mobile terminal **100**, or communications between the mobile terminal and a network where another mobile terminal **100** (or an external server) is located, via wireless area networks. One example of the wireless area networks is a wireless personal area networks.

The location information module **115** is generally configured to detect, calculate, derive or otherwise identify a position of the mobile terminal. As an example, the location information module **115** includes a Global Position System (GPS) module, a Wi-Fi module, or both. If desired, the location information module **115** may alternatively or additionally function with any of the other modules of the wireless communication unit **110** to obtain data related to the position of the mobile terminal. As one example, when the mobile terminal uses a GPS module, a position of the mobile terminal may be acquired using a signal sent from a GPS satellite. As another example, when the mobile terminal uses the Wi-Fi module, a position of the mobile terminal can be acquired based on information related to a wireless access point (AP) which transmits or receives a wireless signal to or from the Wi-Fi module.

The input unit **120** includes a camera **121** for obtaining images or video, a microphone **122**, which is one type of audio input device for inputting an audio signal, and a user input unit **123** (for example, a touch key, a push key, a mechanical key, a soft key, and the like) for allowing a user to input information. Data (for example, audio, video, image, and the like) is obtained by the input unit **120** and may be analyzed and processed by controller **180** according to device parameters, user commands, and combinations thereof.

Such cameras **121** may process image frames of still pictures or video obtained by image sensors in a video or image capture mode. The processed image frames can be displayed on the display unit **151** or stored in memory **170**. In some cases, the cameras **121** may be arranged in a matrix configuration to permit a plurality of images having various angles or focal points to be input to the mobile terminal **100**. As another example, the cameras **121** may be located in a stereoscopic arrangement to acquire left and right images for implementing a stereoscopic image.

The microphone **122** is generally implemented to permit audio input to the mobile terminal **100**. The audio input can be processed in various manners according to a function being executed in the mobile terminal **100**. If desired, the microphone **122** may include assorted noise removing algorithms to remove unwanted noise generated in the course of receiving the external audio.

The user input unit **123** is a component that permits input by a user. Such user input may enable the controller **180** to control operation of the mobile terminal **100**. The user input unit **123** may include one or more of a mechanical input element (for example, a key, a button located on a front and/or rear surface or a side surface of the mobile terminal **100**, a dome switch, a jog wheel, a jog switch, and the like), or a touch-sensitive input, among others. As one example, the touch-sensitive input may be a virtual key or a soft key, which is displayed on a touch screen through software processing, or a touch key which is located on the mobile terminal at a location that is other than the touch screen. On the other hand, the virtual key or the visual key may be displayed on the touch screen in various shapes, for example, graphic, text, icon, video, or a combination thereof.

The sensing unit **140** is typically implemented using one or more sensors configured to sense internal information of the mobile terminal, the surrounding environment of the mobile terminal, user information, and the like. For example, the sensing unit **140** may alternatively or additionally include other types of sensors or devices, such as a proximity sensor **141** and an illumination sensor **142**, a touch sensor, an acceleration sensor, a magnetic sensor, a G-sensor, a gyroscope sensor, a motion sensor, an RGB sensor, an infrared (IR) sensor, a finger scan sensor, an ultrasonic sensor, an optical sensor (for example, camera **121**), a microphone **122**, a battery gauge, an environment sensor (for example, a barometer, a hygrometer, a thermometer, a radiation detection sensor, a thermal sensor, and a gas sensor, among others), and a chemical sensor (for example, an electronic nose, a health care sensor, a biometric sensor, and the like), to name a few. The mobile terminal **100** may be configured to utilize information obtained from sensing unit **140**, and in particular, information obtained from one or more sensors of the sensing unit **140**, and combinations thereof.

The output unit **150** is typically configured to output various types of information, such as audio, video, tactile output, and the like. The output unit **150** is shown having a display unit **151**, an audio output module **152**, a haptic module **153**, and an optical output module **154**. The display unit **151** may have an inter-layered structure or an integrated structure with a touch sensor in order to facilitate a touch screen. The touch screen may provide an output interface between the mobile terminal **100** and a user, as well as function as the user input unit **123** which provides an input interface between the mobile terminal **100** and the user.

The audio output module **152** is generally configured to output audio data. Such audio data may be obtained from any of a number of different sources, such that the audio data may be received from the wireless communication unit **110** or may have been stored in the memory **170**. The audio data may be output during modes such as a signal reception mode, a call mode, a record mode, a voice recognition mode, a broadcast reception mode, and the like. The audio output module **152** can provide audible output related to a particular function (e.g., a call signal reception sound, a message reception sound, etc.) performed by the mobile terminal **100**. The audio output module **152** may also be implemented as a receiver, a speaker, a buzzer, or the like.

A haptic module **153** can be configured to generate various tactile effects that a user feels, perceive, or otherwise experience. Atypical example of a tactile effect generated by the haptic module **153** is vibration. The strength, pattern and the like of the vibration generated by the haptic module **153** can be controlled by user selection or setting by the con-

troller. For example, the haptic module **153** may output different vibrations in a combining manner or a sequential manner.

An optical output module **154** can output a signal for indicating an event generation using light of a light source. Examples of events generated in the mobile terminal **100** may include message reception, call signal reception, a missed call, an alarm, a schedule notice, an email reception, information reception through an application, and the like.

The interface unit **160** serves as an interface with various types of external devices that can be coupled to the mobile terminal **100**. The interface unit **160**, for example, may include any of wired or wireless ports, external power supply ports, wired or wireless data ports, memory card ports, ports for connecting a device having an identification module, audio input/output (I/O) ports, video I/O ports, earphone ports, and the like. In some cases, the mobile terminal **100** may perform assorted control functions associated with a connected external device, in response to the external device being connected to the interface unit **160**.

The memory **170** is typically implemented to store data to support various functions or features of the mobile terminal **100**. For instance, the memory **170** may be configured to store application programs executed in the mobile terminal **100**, data or instructions for operations of the mobile terminal **100**, and the like. Some of these application programs may be downloaded from an external server via wireless communication. Other application programs may be installed within the mobile terminal **100** at time of manufacturing or shipping, which is typically the case for basic functions of the mobile terminal **100** (for example, receiving a call, placing a call, receiving a message, sending a message, and the like). It is common for application programs to be stored in the memory **170**, installed in the mobile terminal **100**, and executed by the controller **180** to perform an operation (or function) for the mobile terminal **100**.

The controller **180** typically functions to control overall operation of the mobile terminal **100**, in addition to the operations associated with the application programs. The controller **180** may provide or process information or functions appropriate for a user by processing signals, data, information and the like, which are input or output, or activating application programs stored in the memory **170**.

To drive the application programs stored in the memory **170**, the controller **180** may be implemented to control a predetermined number of the components mentioned above in reference with FIG. 1A. Moreover, the controller **180** may be implemented to combinedly operate two or more of the components provided in the mobile terminal **100** to drive the application programs.

The power supply unit **190** can be configured to receive external power or provide internal power in order to supply appropriate power required for operating elements and components included in the mobile terminal **100**. The power supply unit **190** may include a battery, and the battery may be configured to be embedded in the terminal body, or configured to be detachable from the terminal body.

Some or more of the components may be operated cooperatively to embody an operation, control or a control method of the mobile terminal in accordance with embodiments of the present disclosure. Also, the operation, control or control method of the mobile terminal may be realized on the mobile terminal by driving of one or more application programs stored in the memory **170**.

FIG. 2 is an exploded perspective view of a mobile terminal according to one embodiment. Further, FIG. 3 shows perspective views respectively illustrating a first state

and a second state viewed from one side of a mobile terminal according to one embodiment. Further, FIG. 4 shows rear face views respectively illustrating a first state and a second state of a mobile terminal according to one embodiment. Further, FIG. 5 shows cross-sectional views respectively

taken along a line A-A and a line B-B of FIG. 3. In these drawings, FIGS. 3A, 4A, and 5A show a first state of the mobile terminal, and FIGS. 3B, 4B, and 5B show a second state of the mobile terminal.

As shown, a mobile terminal **100** in a first state is contracted, and has a smaller size than the mobile terminal **100** in a second state. In addition, a size of a display unit **151** located disposed on a front face of the mobile terminal **100** also becomes smaller than that of the display unit **151** in the second state. The mobile terminal **100** of the first state is expanded in a first direction **D1** to be in the second state. In the second state, a size of the mobile terminal **100** and a size of the front face of the display unit **151** become larger than that in the first state as shown in FIG. 3B, and a size of the rear face of the display unit **151** is reduced as shown in FIG. 4B. That is, the display unit **151** positioned on the rear face of the mobile terminal **151** in the first state moves to the front face of the mobile terminal **100** in the second state.

In a following description, a direction in which the mobile terminal **100** and the display **151** thereof are extended or enlarged is referred to as a first direction **D1**, a direction in which the mobile terminal **100** and the display **151** thereof are contracted or retracted, or reduce to be converted into the first state from the second state is referred to as a second direction **D2**, and a direction perpendicular to the first and second directions **D1** and **D2** is referred to as a third direction.

As such, the display unit may use a flexible display unit **151** that may be bent such that the position of the display unit may be varied. The flexible display is a lightweight, unbreakable, and durable display that is built on a thin and flexible substrate that may be bent, crooked, folded, twisted, or rolled while retaining properties of a conventional flat panel display.

In addition, an electronic paper is a display technology to which properties of general ink are applied. The electronic paper may be different from the conventional flat panel display in using reflected light. The electronic paper may change information using a twisted ball or electrophoresis using a capsule.

In a state in which the flexible display unit **151** is not deformed (e.g., a state of having an infinite curvature radius, hereinafter referred to as a basic state), a display region of the flexible display unit **151** becomes flat. In a state in which the flexible display unit **151** is deformed by an external force from the basic state (e.g., a state of having a finite radius of curvature, hereinafter referred to as a deformed state), the display region may become a curved face. As shown, information displayed in the deformation state may be visual information output on the curved face. Such visual information is implemented by independently controlling light emission of sub-pixels arranged in a matrix. The sub-pixel refers to a minimum unit for implementing one color.

The flexible display unit **151** may be in a curved state (e.g., a vertically or horizontally curved state) rather than a flat state in the basic state. In this case, when the external force is applied to the flexible display unit **151**, the flexible display unit **151** may be deformed into the flat state (or a less curved state) or more curved state.

The flexible display unit **151** may be combined with a touch sensor to implement a flexible touch screen. When a touch is made on the flexible touch screen, the controller **180**

(see FIG. 1) may perform control corresponding to such touch input. The flexible touch screen may be configured to detect the touch input in the deformed state as well as in the basic state.

The touch sensor detects the touch (or touch input) applied on the touch screen using at least one of various touch schemes such as a resistive film scheme, a capacitance scheme, an infrared scheme, an ultrasonic wave scheme, a magnetic field scheme, and the like.

As an example, the touch sensor may be configured to convert a change in pressure applied on a specific portion of the touch screen, capacitance generated at the specific portion, or the like into an electrical input signal. The touch sensor may be configured such that a touch object applying a touch on the touch screen may detect touched position and area on the touch sensor, a pressure during the touch, a capacitance during the touch, and the like.

Further, the mobile terminal **100** may have a deformation detection means for detecting the deformation of the flexible display unit **151**. Such deformation detection means may be included in the sensing unit **140** (see FIG. 1).

The deformation detection means may be disposed in the flexible display unit **151** or a case (first to second frames **101** to **102** to be described later) to detect information related to the deformation of the flexible display unit **151**. In this connection, the information related to the deformation may include a direction in which the flexible display unit **151** is deformed, a degree of the deformation, a deformed position, a deformed time, an acceleration at which the deformed flexible display unit **151** is restored, and the like. In addition, the information related to the deformation may be various information that may be detected due to the bending of the flexible display unit **151**.

In addition, the controller **180** may change information displayed on the flexible display unit **151** or generate a control signal for controlling a function of the mobile terminal **100** based on the information related to the deformation of the flexible display unit **151** detected by the deformation detection means.

The state conversion (first or second state) of the flexible display unit **151**, i.e., the size change at the front and rear faces of the mobile terminal **100** of the display unit **151** based on the size change of the mobile terminal **100** may be performed manually by a force applied by the user, but may be not limited to such manual scheme. For example, when the mobile terminal **100** or the flexible display unit **151** is in the first state, the mobile terminal **100** or the flexible display unit **151** may be converted into the second state by the user or an application command without the external force applied by the user. As such, in order for the flexible display unit **151** to be automatically deformed without the external force, the mobile terminal **100** may include a driving unit **200** to be described later.

The flexible display unit **151** of the present disclosure is bent 180 degrees while being rolled on a side of the mobile terminal **100** in the first direction. Thus, a portion of the display unit **151** is disposed on the front face of the mobile terminal **100** based on such side, and the other portion thereof is disposed on the rear face of the mobile terminal **100**. A portion of the display unit **151** located on the front face of the mobile terminal **100** may be fixed to the front face so as not to move. Further, the other portion thereof located on the rear face of the mobile terminal **100** may be movable to the rear face.

In addition, the display unit **151** may be rolled on or released from the side. Accordingly, the portion disposed on the rear face of the mobile terminal **100** moves, so that the

size of the portion disposed on the front face of the mobile terminal **100** may be adjusted. Since the area of the flexible display unit **151** is determined and the flexible display unit **151** is formed of one continuous body, an area of the portion on the rear face decreases as an area of the portion on the front face increases. Such a display unit **151** may be rolled in a second frame **102**, which is movable relative to a first frame **101** to be described later, more correctly, on one of sides of the second frame **102**. The display unit **151** may be withdrawn or pulled out from or inserted or pushed into the second frame **102** while being rolled in the second frame **102** along a moving direction of the second frame **102** to adjust the area of the display unit **151** on the front face of the mobile terminal **100**. Such operation will be described in more detail below along with other relevant components of the mobile terminal **100**.

Typically, an antenna is disposed in the case or the housing of the mobile terminal **100**, but a portion where the antenna is installed in the case or the housing may be limited because of the flexible display unit **151** that covers not only the front face of the mobile terminal **100** but also the rear face thereof. For this reason, the antenna may be implemented on the flexible display unit **151**. An antenna on display (AOD) is an antenna in which a transparent film is formed by stacking an electrode layer and a dielectric layer that have patterns engraved thereon, respectively. The antenna on display may be implemented thinner than an antenna implemented using a laser direct structuring (LDS) technology using a conventional copper nickel plating scheme, so that the antenna on display may not be exposed to the outside without affecting a thickness. In addition, the antenna on display may transmit and receive a signal directly to or from the display unit **151**. Accordingly, the antenna on display may be used in the mobile terminal **100** in which the display unit **151** is located on the both faces of the mobile terminal **100** as in the present disclosure.

The mobile terminal **100** of the present disclosure includes frames **101** and **102** in which components are mounted, and the frames **101** and **102** of the present disclosure may vary in size in the first direction as shown in FIG. 2. One or more frames **101** and **102** move relative to each other, and sizes thereof may vary in the first direction. Electronic components are mounted in the frames **101** and **102**, and the flexible display unit **151** is located out of the frames **101** and **102**.

Since the mobile terminal **100** of the present disclosure includes the flexible display unit **151**, the flexible display unit **151** may be combined in a form surrounding front faces and rear faces of the frames **101** and **102**. The frame may include the first frame **101** and the second frame **102** moving in the first direction with respect to the first frame **101**. The first frame **101** and the second frame **102** include front portions, a rear portions, and side portions, respectively, and are coupled to each other. Thus, the mobile terminal **100** may have a hexahedral outer shape by such coupled first and second frames **101** and **102**.

First, the first frame **101** corresponds to a main body of the mobile terminal **100**, and may have a space therein for accommodating various components. In addition, the first frame **101** may accommodate the second frame **102** movably coupled to the first frame **101** in such a space. More specifically, as shown in FIGS. 2 and 5, the first frame **101** may include a first front portion **1011** disposed at a front portion of the mobile terminal **100** and supporting the front face of the display unit **151** and a first rear portion **1012** disposed at a rear portion of the mobile terminal and on which various components are mounted.

The first front portion **1011** and the first rear portion **1012** may be spaced apart from each other at a predetermined spacing to define a predetermined space therebetween, and may be connected to each other by a side portion **1014**. The side portion **1014** may be integrally formed with the first rear portion **1012** or the first front portion **1011**. The camera **121**, the audio output module **152**, and the input/output terminal **161**, the controller **180**, and the power supply unit **190** may be accommodated as components of the mobile terminal **100** in the space in the first frame **101**. For example, the controller **180** may be a circuit board **181** including a processor and an electronic circuit for controlling the operation of the mobile terminal, and the power supply unit **190** may be a battery **191** and related components. In addition, the driving unit **200** that controls the slide movement of the second frame **102**, which will be described later, may also be accommodated in the first frame **101**.

As described above, the display unit **151** has the continuous body, and thus, may be disposed on both the front face and the rear face of the mobile terminal **100** while being rolled in the mobile terminal **100**. The display unit **151** may include the front face positioned at the front face of the mobile terminal **100**, the rear face positioned at the rear face of the mobile terminal **100**, and the side face positioned between the front face and the rear face thereof and surrounding the side face of the mobile terminal. The front face and the rear face of the display unit **151** are flat, and the side face of the display unit **151** may form a curved face. When the flexible display unit **151** may be damaged when being bent. Thus, the flexible display unit **151** may be formed to be bent with a predetermined curvature.

The display unit **151** may be divided into a fixed portion and a variable portion. The fixed portion means a portion fixed to the frame. Because of being fixed to the frame, the fixed portion maintains a constant shape without changing a bending degree. On the other hand, the variable portion means a portion in which a bending angle or a position of the bent portion changes. The variable portion in which the position or bending angle of the bent portion changes requires a structure for supporting a rear face of the variable portion in response to the change.

The fixed portion is coupled to the first frame of the display unit and is always positioned on the front face of the display unit to form a portion of the front face of the display unit. The variable portion includes a side face located at a side portion of the mobile terminal, and a position of the side face varies depending on the position of the second frame. Based on a side face, an area of a portion disposed on the front face of the display unit and an area of a portion disposed on the rear face of the display unit vary. That is, a portion of the variable portion may be the front face and another portion of the variable portion may be the rear face based on the first and second states. The variable portion is positioned in the first direction with respect to the fixed portion relative to the mobile terminal, and an end of the variable portion is bent toward the rear face of the mobile terminal and slides on the rear face of the second frame.

The end of the variable portion of the display unit is coupled with a slide frame that guides the variable portion to slide move on the rear face of the second frame, and the slide frame moves in the first direction at the same time as the second frame moves in the first direction. As a result, a moving distance of the slide frame with respect to the first frame is twice as a moving distance of the second frame with respect to the first frame. Further, as shown in FIG. 4, the first rear portion **1012** of the mobile terminal **100** includes an exposed rear portion **1013** that is exposed to the outside

13

without being covered by the display unit **151** even in the first state. The physical input unit **120** for the manipulation of the mobile terminal **100** such as various buttons, switches, the camera **121**, and a flash, and the sensing unit **140** such as the proximity sensor **141** or a fingerprint sensor may be arranged on the exposed rear portion **1013**. The first rear portion **1012** except for the exposed rear portion **1013** may be covered by the display unit **151** in the first state as shown in FIG. 4A, and may be exposed rearwardly in the second state as shown in FIG. 4B.

In a conventional bar-shaped terminal, a display unit is provided only on a front face of the terminal. Therefore, a main camera is placed on a rear face of the terminal in order for the user to capture an object at an opposite side while looking through the display unit. On the other hand, an additional auxiliary camera is required to be disposed on the front face of the terminal in order for the user to capture himself or herself while viewing himself or herself through the display unit.

However, the display unit **151** is positioned both the front face and the rear face of the mobile terminal **100** of the present disclosure. Therefore, when the user captures himself or herself, a display unit on the same face as the camera **121**, that is, the portion of the display **151** on the rear face of the mobile terminal **100** in the drawing may be used. Further, when the user captures the object on the opposite side of the user, a display unit on the opposite face of the camera **121**, that is, the portion of the display unit **151** on the front face of the mobile terminal **100** in the drawing may be used. For this reason, the mobile terminal **100** may capture the object on the opposite side of the user and capture the user using the single camera **121**. The camera may include a plurality of cameras having different angles of view, such as wide angle, super wide angle, and telephotographic cameras. In addition to the camera, a proximity sensor, the audio output module, and the like may be positioned on the exposed rear portion **1013**, and an antenna **116** may be installed on the exposed rear portion **1013**. In order to protect the camera, the sensor, and the like of the exposed rear portion **1013** and in consideration of a design of an outer shape thereof, an exposed decor **1013** may be attached on the exposed rear portion **1013**.

The side portion **1014** may extend along edges of the first front portion **1011** and the first rear portion **1012** to surround the first frame **101**, and may form the outer shape of the mobile terminal **100**. However, as mentioned above, since the second frame **102** is accommodated in the first frame **101** and is movably coupled thereto, in order to allow the movement of the second frame **102** relative to the first frame **101**, a portion of the first frame **101** needs to be opened. As shown in FIG. 2, as an example, the second frame **102** is movably coupled to one of both side portions of the first frame **101**, so that the side portion **1014** may not be formed on the side portion in the first direction, and thus, the portion of the first frame **101** may be opened. Accordingly, the first frame **101** may include a substantially closed first side portion **101a** and a second side portion **101b**, which is disposed to be opposite to the first side portion **101a** and is opened. The side portion **1014** is exposed to the outside of the mobile terminal **100**, so that an interface unit **160** for connecting a supply port or an ear jack, the user input unit **120** such as a volume button, or the like may be disposed on the side portion **1014**. When containing a metal material, the side portion **1014** may serve as an antenna.

The second frame **102** may include a second front portion **1021** disposed at the front portion of the mobile terminal **100** and a second rear portion **1022** disposed at the rear portion

14

of the mobile terminal **100**. Like the first front portion **1011** and the first rear portion **1012** of the first frame **101**, the second front portion **1021** and the second rear portion **1022** may be formed of plate-shaped members that are generally flat. In addition, the second frame **102** also accommodates various components, and must not interfere with the components accommodated in the first frame **101** during the movement. Accordingly, the second front portion **1021** and the second rear portion **1022** may be coupled to each other in a state of being spaced apart from each other to define a predetermined space therebetween, and may have shapes that do not interfere with the components in the first frame **101**.

In addition, the display unit **151** may be bent 180 degrees while being rolled in the second frame **102** to be disposed on both the front face and the rear face of the mobile terminal **100**. For such an arrangement of the display unit **151**, the second frame **102** may include a driving roller **1028** rotatably disposed therein. The driving roller **1028** may be disposed at any position inside the second frame **102**. However, the display unit **151** should be spread flat on the front face and the rear face of the mobile terminal **100** to provide a good quality screen to the user. Further, for such spread, a proper tension must be provided on the display unit **151**. In order to provide the proper tension, the driving roller **1028** may be disposed at a first directional end of the second frame **102**. The driving roller **1028** may extend in the third direction, and may be rotatably coupled to the second frame **102**.

The display unit **151** may be rolled around the driving roller **1028** while being gently bent with a predetermined curvature. The flexible display unit **151** may include a first face on which a video is output and exposed to the outside and an inner face facing the frame at the opposite side. The driving roller **1028** may be installed to rotate freely in the second frame **102** while being in contact with the inner face of the display unit **151**. Accordingly, the driving roller **1028** may actually move the display unit **151** in a lateral direction of the mobile terminal **100**, that is, in a direction perpendicular to a longitudinal direction. As will be described later, when the second frame **102** slides, because of the tension applied by the second frame **102**, the display unit **151** moves to the front face or the rear face of the mobile terminal **100** in different directions (i.e., the first direction D1 or the second direction D2) relative to the second frame **102**. The driving roller **1028** may guide such movement while rotating.

In addition, the driving roller **1028** is disposed on a first side portion **102a** of the second frame **102**, and the first side portion **102a** actually corresponds to an outermost side portion of the mobile terminal **100**. When the first side portion **102a** of the second frame **102** is exposed, the display unit **151** rolled on the driving roller **1028** may be damaged. Accordingly, the second frame **102** may include a side frame **1024** disposed on the first side portion **102a**.

The side frame **1024** extends in the longitudinal direction of the second frame **102** to cover the first side portion **102a**, thereby protecting the driving roller **1028** and the display unit **151** rolled thereon.

Because the side face is rolled by the roller, the side face is bent with the predetermined curvature, and an inner face of the side frame may include a curved face corresponding to the curvature of the side face.

Because of the side frame **1024**, the second frame **102** may have the substantially closed first side portion **102a**, and the side frame **1024** may substantially form the outer shape of the mobile terminal **100** together with the side portion

1014 of the first frame **101**. In addition, the second frame **102** may include a second side portion **102b** that is disposed opposite the first side portion **102a** to minimize interference with the components within the first frame **101** during the movement, and is opened.

Such a second frame **102** is movably coupled to the first frame **101**, and thus may slide in the predetermined first or second direction **D1** or **D2** relative to the first frame **101**. More specifically, the second frame **102** may be movably coupled to the first frame **101** through the side portion of the first frame **101**, more precisely, through the opened second side portion **101b**, as shown. More specifically, the second side portion **102b** of the second frame is disposed relatively adjacent to the first side portion **101a** of the first frame **101** which is closed. Accordingly, the first side portion **102a** of the second frame may be disposed to be opposite to the first side portion **101a**. Accordingly, the second side portion **102b** is inserted into the first frame **101** through the side portion of the first frame, that is, the second side portion **101b** thereof. The first side portion **102a** is not inserted into the first frame **101** but is always located outside the first frame **101**, thereby forming the outer shape of the mobile terminal **100** as described above. However, when necessary, such first side portion **102b** of the second frame **102** may also be inserted into the first frame **101**.

Because of such positional relationship, the second frame **102** may extend from or contract to the first frame **101** in a direction perpendicular to the longitudinal direction of the mobile terminal **100** or the first frame **101**. That is, the first and second directions **D1** and **D2** may basically be directions perpendicular to the longitudinal direction of the mobile terminal **100** or the first frame **101**. Further, the first and second directions **D1** and **D2** may also be described as the lateral direction or the horizontal direction of the mobile terminal **100** or the first frame **101**. In addition, during the movement in the first direction **D1**, the second frame **102** extends from the first frame **101**. Accordingly, the first direction **D1** may be a direction in which the second frame **102** moves away from the first frame **101**, that is, moves outwardly of the mobile terminal **100** or the first frame **101**. On the other hand, during the movement in the second direction **D2**, the second frame **102** contracts to the first frame **101**. Thus, the second direction **D2** is a direction opposite to the first direction **D1**, so that the second direction **D2** may be a direction in which the second frame **102** moves to become closer to the first frame **101**, that is, moves inwardly of the mobile terminal **100** or the first frame **101**. When being moved in the first direction **D1**, such second frame **102** extends and applies a force to the portion of the display unit **151** disposed on the rear face of the mobile terminal **100**, so that the portion of the display unit **151** may be disposed on the front face of the mobile terminal **100**, and a region for such additional arrangement may be defined. Thus, the second frame **102** may convert the mobile terminal **100** into the second state with the display unit **151** with the relatively extended front face by moving in the first direction **D1**. On the other hand, when being moved in the second direction **D2**, the second frame **102** contracts into an original state thereof, and applies a force to the portion of the display unit **151** disposed on the front face of the mobile terminal **100** to return to the rear face of the mobile terminal **100** again. Thus, the second frame **102** may convert the mobile terminal **100** into the first state with the display unit **151** with the relatively contracted front face by moving in the second direction **D2**. Accordingly, the second frame **102** selectively

first or second direction **D1** and **D2**). Accordingly, the mobile terminal **100** may be converted into the first or second state defined above.

During the expansion and the contraction in such first and second directions **D1** and **D2**, the second frame **102** may overlap the first frame **101**, more precisely, the first front portion **1011** and the first rear portion **1012** thereof so as not to interfere with the first frame **101**. More specifically, the display unit **151** may be coupled to and supported by the first front portion **1011** of the first frame **101**, as described above. Accordingly, the display unit **151** does not need to be additionally supported by the second front portion **1021** of the second frame **102**. Rather, when the second front portion **1021** is interposed between the first front portion **1011** and the display unit **151**, the display unit **151** may be deformed or damaged because of friction with the second front portion **1021**, which is repeatedly moved. Thus, the second front portion **1021** may be disposed below the first front portion **1011**, or may be interposed between two first front portions **1011**. The second rear portion **1022** of the second frame **102** may be disposed rearward of the first rear portion **1012** of the first frame **101**. That is, the front face of the second rear portion **1022** may face the rear face of the first rear portion **1012**. In addition, the rear face of the first rear portion **1012** may be in contact with the front face of the second rear portion **1022** to stably support the movement of the second frame **102**. Because of such arrangement, the second rear portion **1022** may be exposed to the outside of the first frame, more precisely, of the first rear portion **1012**, and may be coupled to the display unit **151**.

In addition, the second frame **102** may extend and contract the size of the mobile terminal **100** itself, particularly the front face of the mobile terminal **100** by the extension and the contraction in the first and second directions **D1** and **D2**. Thus, the display unit **151** must move by such extended or reduced front face size to obtain the intended first and second states. However, when being fixed to the second frame **102**, the display unit **151** may not be moved smoothly to be adapted for the front face of the mobile terminal **100** that is extended or contracted. For this reason, the display unit **151** may be movably coupled to the second frame **102**.

More specifically, the display unit **151** may include a first side edge (or side end) **151d** disposed on the front face of the mobile terminal **100** and a second side edge **151e** opposite to the first side edge **151d** and disposed on the rear face of the mobile terminal **100**. The first side edge **151** may be disposed on the front face of the first frame **101**, that is, the front face of the first front portion **1011** thereof, and may be disposed adjacent to the side portion of the mobile terminal **100**, that is, the first side portion **101a** of the first frame. On the other hand, since the second side edge **151e** is adjacent to the rear face of the mobile terminal **100** and the second rear portion **1022** of the second frame **102**, the second side edge **151e** may be coupled to the second rear portion **1022** of the second frame **102** to be movable in the first and second directions **D1** and **D2**. In addition, since the display unit **151** is not structurally strong, a slide frame **103** may be coupled to the second side edge **151e**. The slide frame **103** may be formed of a plate-shaped member extending in the longitudinal direction of the mobile terminal **100**.

Accordingly, the second frame **103** may be coupled to the second frame, that is, the second rear portion **1022** thereof to be movable in the first and second directions **D1** and **D2** instead of the second side edge **151e**. In addition, the second frame **102** may include a slot **1025** extending in the lateral direction of the mobile terminal **100** or the second frame **102**, that is, the direction perpendicular to the longitudinal

direction thereof. Further, the slide frame **103** may be stably moved while being guided by the slot **1025**. The slide frame **103** may include, for example, a projection inserted into the slot **1025** for the movement along the slot **1025**.

Referring to FIGS. **3** to **5**, in connection with such configuration of the first to third frames **101**, **102**, and **103**, the display unit **151** may include a first region **151a** extending from one side thereof, that is, the first side edge **151d** toward the opposite second side edge **151e** by a predetermined length, and a second region **151b** disposed opposite the first region **151a**, and extending from the second side edge **151e** toward the first side edge **151d** by a predetermined length. In addition, the display unit **151** may include a third region **151c** disposed between the first and second regions **151a** and **151b**. Such first to third regions **151a**, **151b**, and **151c** may be connected to each other, and may form a continuous body of the display unit **151**. In addition, as described above, for the movement of the third region **151c** toward the front face or the rear face of the mobile terminal **100** depending on the moving direction of the second frame **102**, the first region **151a** may be fixed so as not to move to the front face of the mobile terminal **100**, and the second region **151b** may be provided to be movable on the rear face of the mobile terminal. Such configuration of the display unit **151** will be described in more detail below.

The first region **151a** may be disposed on the front face of the mobile terminal **100**, more specifically, the first frame **101**, that is, on the front face of the first front portion **1011**. The first region **151a** is fixed to the first frame **101**, that is, the front face of the first front portion **1011** so as not to be moved during the movement of the second frame **102**, and thus, the first region **151a** may always be exposed to the front face of the mobile terminal **100**.

The third region **151c** may be adjacent to the first region **151a** in a direction of the second side edge **151e**, and may extend into the second frame **102** and rolled on the driving roller **1028**. The third region **151c** may consecutively extend out of the second frame **102** again and partially cover the second frame **102**, that is, the rear face of the second rear portion **1022**. Further, the second frame **102**, that is, the second rear portion **1022**, is adjacent to the first frame **101**, that is, the first rear portion **1012** and together forms the rear case of the mobile terminal **100**, so that it may be described that the third region **151c** is also disposed on the rear face of the first frame **101**.

The second region **151b** may be adjacent to the third region **151c** in the direction of the second side edge **151e** and may be disposed on the rear face of the mobile terminal **100**, more specifically, on the second frame, that is, the rear face of the second rear portion **1022** thereof. The second region **151b** may be coupled to the slide frame **103** without being directly coupled to the second frame **102**. As shown in FIG. **4B**, the slot **1025** extending in the lateral direction (i.e., the direction perpendicular to the longitudinal direction of the mobile terminal **100**) to the second frame **102**, that is, to the second rear portion **1022** is defined. Further, the slide frame **103** may move along the slot **1025**. In FIG. **4B**, it is shown that the slot **1025** is defined in the rear face of the second frame **102**, but may be defined in the side face of the second frame **102**.

Although the second region **151b** may move in the first or second direction **D1** or **D2** with respect to the second frame **102** together with the slide frame **103**, the movement of the second region **151b** may be restricted within the rear face of the mobile terminal **100** by the slot **1025**. That is, the second region **151b** does not move out of the second frame **102** even when the second frame **102** is extended or contracted, and

may move along the slot **1025** within the second frame **102** by the extended or contracted distance of the second frame **102**. Accordingly, the second region **151b** may always be exposed to the rear face of the mobile terminal **100**.

As a result, the first region **151a** may be disposed on the front face of the mobile terminal **100** and may be always exposed to the front face regardless of the movement of the second frame **102**, and the second region **151b** may be disposed on the rear face of the mobile terminal **100** and may be always exposed to the rear face regardless of the movement of the second frame **102**. In addition, the third region **151c** may be disposed between the first and second regions **151a** and **151b**, and may be selectively placed on the front face or the rear face of the mobile terminal **100** depending on the moving directions **D1** and **D2** of the second frame **102**.

Because of such selective placement of the third region **151c**, as shown in FIG. **4B**, the first rear portion **1012** of the first frame **101** may be exposed to the outside of the mobile terminal **100** because the first rear portion **1012** is covered by the second and third regions **151b** and **151c** and the second rear portion **1022** of the display unit **151** in the first state, but, in the second state, the third region **151c** moves to the front face of the mobile terminal **100** and the second rear portion **1022** also moves in the first direction **D1**. In addition, the second front portion **1021** of the second frame **102** is hidden by the first front portion **1011** of the first frame **101** in the first state, but, in the second state, moves out of the first frame **101** to support the third region **151c** of the display unit **151** disposed on the front face of the mobile terminal **100**.

In order to prevent the second front portion **1021** from affecting the internal components during the slide movement, a separating plate **1017** may be further disposed rearward of the second front portion **1021** and fastened with the first front portion **1011**. The second front portion **1021** may move between the first front portion **1011** and the separating plate **1017** based on the slide movement of the second frame.

However, the third region **151c** may be rolled on the driving roller **1028** and bent in the second frame **102**. When converting from the first state to the second state, the third region **151c** may extend from the second frame **102** to the front face of the mobile terminal **100** while being rolled on the driving roller **1028** in one direction. On the other hand, when converting from the second state to the first state, the third region **151c** may be retracted from the front face of the mobile terminal **100** to the second frame **102** while being rolled on the driving roller **1028** in the opposite direction, and at the same time, may return to the rear face of the mobile terminal **100** from the second frame **102**.

A specific location of the foldable mobile terminal in a form of being spread like a book is easily damaged because only the specific location is folded repeatedly. On the other hand, the deformed portion of the flexible display unit **151**, that is, a portion rolled on the driving roller **1028**, may vary based on the first and second states of the mobile terminal **100**, that is, the movement of the second frame **102**. Accordingly, the mobile terminal **100** of the present disclosure may significantly reduce deformation and fatigue repeatedly applied to a specific portion of the display unit **151**, thereby preventing damage to the display unit **151**.

Based on the above-described configuration, overall operations of the mobile terminal **100** will be described as follows. As an example, the state conversion may be performed manually by the user, and an operation of the mobile terminal **100** during such manual state conversion will be

described. However, operations of the first to third frames **101** to **103** and the display unit **151**, which will be described below, may be performed in the same manner when a power source other than a user's force is used, for example, when the driving unit **200** to be described below is applied.

A rear face cover **1023** may be further disposed on a rear face of the second rear portion **1022** such that the rear face of the display unit positioned on the rear face of the mobile terminal **100** is not exposed to the outside. The rear face of the display unit may be used in the first state when the rear face cover **1023** uses a transparent material, and the rear face of the display unit may be covered such that the movement of the slide frame **103** is not exposed when the rear face cover **1023** uses an opaque material. That is, the second region and the third region of the slide frame **103** and the display unit **151** may move in the first direction and in the second direction in a space between the second rear portion **1022** and the rear face cover **1023**. The exposed decor **1013** may be further attached to the exposed rear portion of the first rear portion **1012** to protect the camera **121**, the sensor **140**, and the like. The exposed decor **1013** may be partially coated on a plate-shaped member made of a transparent glass material to cover the internal components, and may be not coated only on a required portion to allow light to reach the camera **121**, the flash or the sensing unit **140**, and the like.

FIG. 6 illustrates cross-sectional views taken along a line C-C and a line D-D of FIG. 3. Further, FIG. 6 illustrates a tensioning structure for applying a tensile force to the display unit **151**. The first region **151a** of the display unit **151** is fixed to the first frame **101**, but the slide frame **103** coupled with the second region **151b** moves, and the third region **151c** is not fixed to the frame. Therefore, the third region **151c** of the display unit **151** may be separated from the frames **101**, **102**, and **103** without being attached to the frames **101**, **102**, and **103**. The display unit **151** should be in close contact with the frames **101** and **102** to maintain a flat state, so that the screen outputted on the display unit **151** may not be distorted, and malfunctions may be prevented during touch input.

In order to maintain the display unit **151** in the flat state, a structure that slides in the first direction while supporting the third region of the display unit **151** on the frame may be disposed. For example, rails may be arranged at both sides of the display unit **151** in a direction perpendicular to the first direction, and the rails may support the display unit **151** so as not to be separated from the frame while ends of the display unit **151** respectively move along the rails.

However, even when the both ends of the display unit **151** in the third direction are respectively caught by the rails, a central portion of the display unit **151** in the third direction may not be pulled, so that the third region **151c** of the display unit **151** may not be in close contact with the second frame **102** and may not maintain the flat state. In order to keep an entirety of the display unit **151** flat, a member for providing a tensile force of pulling the display unit **151** in both first and second directions is required.

Because the first region **151a** of the display unit **151** is fixed to the first frame **101**, a force of pulling the second end of the display unit **151** in the second direction from the rear face of the mobile terminal **100** is required. The force of pulling in the second direction should be constant regardless of the state of the mobile terminal **100**, so that a conventional elastic member may not be able to be used. The conventional elastic member provides an elasticity varying depending on a length, so that the pulling force may vary based on a position of the second end of the display unit **151**.

In order to solve the above-mentioned problem, and in order to provide the force of pulling the second end of the display unit **151** in the second direction, a tensioning structure that provides a constant force of pulling the slide frame **103** positioned at the second directional end of the display unit **151** is disposed.

The tensioning structure includes a tensioning belt **242** and a belt roller **244**. The tensioning belt **242** is a member that pulls the display unit **151**. One side of the tensioning belt **242** may be fixed to the first frame **101** and the other side thereof may be fixed to the second end of the display unit **151**. Because the second end of the display unit **151** is fixed to the slide frame **103**, the other end of the tensioning belt **242** may be coupled to the slide frame **103**. A fastener **243** may be disposed such that the fastener **243** is easily fastened with the first frame **101** and the slide frame **103**, and a force of the tensioning belt **242** is transmitted to the entirety of the display unit **151**.

As shown in FIG. 6, the tensioning belt **242** is disposed to be bent at least once without being disposed in a straight line between the first frame **101** and the display unit **151**. The tensioning belt **242** is bent while being wound around the belt roller **244** located on the second frame **102**. A position of the first frame **101** to which the tensioning belt **242** is coupled is a position adjacent to the first directional end of the first frame **101**, which is a position maintaining an overlapped state with the second frame **102** in the second state. The belt roller **244** may be located at the end of the second frame **102** in the second direction. In order to secure a mounting space inside, a diameter of the belt roller **244** may be smaller than a diameter of the driving roller **1028** located at a point at the first directional end of the second frame **102** and at which the display unit **151** is bent.

The tensioning belt **242** includes a first belt between the first frame **101** and the belt roller **244** and a second belt between the belt roller **244** and the slide frame **103**. A sum of lengths of the first belt and the second belt is constant, and when a state of the mobile terminal **100** is converted from the first state to the second state, a length of the first belt is reduced and a length of the second belt is increased.

When the state of the mobile terminal **100** is converted from the first state to the second state, the second frame **102** moves in the first direction, so that the first directional end of the first frame **101** and the second directional end of the second frame **102** become close to each other, and thus, the length of the first belt is reduced. Further, because the slide frame **103** moves in the first direction with respect to the second frame **102** when the second frame **102** moves in the first direction, the length of the second belt is increased. Regardless of the first state and the second state, a length of the tensioning belt **242** may be maintained constant, so that the second end of the display unit **151** may be pulled in the second direction from the rear face of the mobile terminal **100** to be kept in a taut state.

FIG. 7 illustrates embodiments of the first end of the tensioning belt coupled to the first frame **101**. As shown in FIG. 7A, the tensioning belt may be coupled to the first frame **101** at a position of the first frame **101** adjacent to the first direction, and the first belt **2421** may be coupled to the first rear portion **1012** positioned at a rear portion of the first frame **101** without being bent. When the tensioning belt **242** itself has a small elasticity, a minute length change may be offset when the third region **151c** of the display unit **151** moves to the front face or the rear face of the display unit **151**. However, when the tensioning belt **242** itself does not have the elasticity, a smooth operation may not be performed when the state of the mobile terminal **100** is converted.

21

In another embodiment, as shown in FIG. 7B, the tensioning belt 242 may be bent twice to place a first end of the tensioning belt 242 at the first front portion of the first frame 101. The tensioning belt 242 may further include a pair of tensioning pins 245 such that the tensioning belt 242 is bent twice, and the tensioning belt 242 may be bent twice in an S shape while surrounding the pair of tensioning pins 245. Each tensioning pin 245 may further include each elastic body 246 having one side thereof abutting on the tensioning belt 242 and the other side thereof exerting a force on the tensioning pin 245 toward the tensioning belt 242. The tensioning pin 245 is positioned on the first frame 101, and the elastic body 246 is also a member fixed to the first frame 101 and does not move along the second frame 102 when the state of the mobile terminal 100 is converted.

The elastic body 246 has a restoring force of being restored to an original shape thereof after deformed when a force is applied, like silicon or rubber. Thus, when the display unit 151 moves, the tensioning belt 242 may be pulled to push the tensioning pin 245 toward the elastic body 246, but may be restored to an original state thereof after being deformed, so that the tensioning belt and the display unit 151 may be remained in the taut state.

When the state of the display 151 is converted, the elastic body 246 may receive a force with which the tensioning belt is pulled as the shape of the elastic body 246 changes, so that the display unit 151 may be stably moved while maintaining the taut state of the tensioning belt 232. In addition, the tensioning pin 245 and the elastic body 246 maintains the tensioning belt in a loose state before assembling the mobile terminal 100 for ease of the assembly, and pulls the tensioning belt 242 when assembling the mobile terminal 100 such that the tensioning belt 242 is assembled in the taut state. An assembly method will be described later.

A tensioning seat 241 positioned on the rear face of the third region 151c of the display unit 151 to evenly transmit the force of the tensioning belt 242 to the display unit 151 may be further included. FIG. 8 illustrates the tensioning structure of the mobile terminal, and illustrates a tensioning seat 241, the tensioning belt 242, the belt roller 244, and the tensioning pin 245. The tensioning seat 241 may be located on the rear face of the third region 151c, and may made of a fabric material. In order to stably support the rear face of the third region 151c even in the second state, the tensioning seat 241 may be integrally formed with a display frame.

The display frame includes a plurality of support bars extending in the third direction on the rear face of the third region 151c. The plurality of support bars are arranged in parallel with each other in the first direction to support the rear face such that the third region 151c of the display unit 151 is bent in the first direction but does not sag in the third direction. One face of the tensioning seat 241 may be coupled to the display unit 151 and the other face of the tensioning seat 241 may be coupled to the display frame including the plurality of support bars.

FIG. 8A illustrates the tensioning structure in the first state, and FIG. 8B illustrates the tensioning structure in the second state. The fasteners 243 respectively located at both ends of the tensioning belt 242 may be formed in a rigid bar shape, and the tensioning seat 241 and the tensioning belt 242 may be fastened with each other through the fastener 243. The fasteners 243 may include a first fastener 243a coupled to the slide frame 101 and a second fastener 243b coupled to the slide frame 103. Because the first fastener 243a and the tensioning pin 245 are fixed to the first frame 101, the first fastener 243a and the tensioning pin 245 may be fixed in both the first state and the second state. Further,

22

the belt roller 244 and the second fastener 243b coupled to the second frame 102 may move in the first direction as shown in FIG. 8B. The tensioning belt 242 and the tensioning seat 241 may form a closed loop to prevent the display unit 151 from being separated.

FIGS. 9 to 12 are diagrams illustrating an assembly flowchart of the same terminal. As shown in FIG. 9, components such as a battery, a driving unit, a camera, a board, and the like are mounted on the first frame 101. A front portion of the first frame 101 may be disposed at a bottom, and the front portion may be integrally formed with a side portion to define a mounting space therebetween. The second frame 102 is disposed in a vertical direction at a first directional end of the front portion (The rear face faces in an upward direction, and thus, the first direction is a left direction in the drawing.). The second frame 102 of the present embodiment includes the side portion on which the second rear portion and the driving roller are coupled. The tensioning seat 241 is wrapped on the second frame 102, and the tensioning belts 242 are respectively fastened to both ends of the tensioning seat 241. In this connection, the tensioning belt 242 may be disposed to wrap a portion of the tensioning pin 245 positioned on the front portion of the tensioning pin 245 positioned in the first direction of the first frame 101. As shown in FIG. 9B, before fastening the second frame 102 and the first frame 101 with each other, the tensioning belt 242 may be obliquely disposed to be spaced apart from the second frame 102. The second frame 102 covers a rear face of the front portion of the first frame 101 while rotating around an end where the driving roller is located, as shown in FIGS. 10 and 11. In this connection, when the second frame 102 is bent at a certain angle as shown in FIG. 10, the tensioning pin 245 may be further inserted to further add tension to the tensioning belt 242. Thereafter, as shown in FIG. 11, when the second frame 102 moves in the first direction and becomes in the second state, the first rear portion 1012 that covers the exposed rear face of the first frame 101 is inserted, so that the tensioning belt 242 is positioned between the second rear portion 1022 of the second frame 102 and the first rear portion 1012 of the first frame 101. When the first rear portion 1012 is inserted, the tensioning belt 242 may become in close contact with the second rear portion 1022, and may be pulled more strainedly.

After fastening the second rear portion 1022 to the first frame 101, as shown in FIG. 12A, the display unit 151 may be attached to the tensioning seat 241, and the rear face cover 1023 that covers a portion the display unit 151 positioned at the rear face of the display unit 151 may be further attached to cover the display unit 151. The rear face cover 1023 may protect the portion of the display unit 151 located at the rear face of the display unit 151 in the first state, and may protect the tensioning belt 242 exposed to the rear face in the second state. FIG. 13 is a diagram illustrating a support structure based on the states of the mobile terminal 100, and FIG. 14 is an enlarged diagram of the support structure of FIG. 13. The first frame 101 and the second frame 102 of the mobile terminal viewed from the front in a state in which the display unit 151 is removed are illustrated. When the state is converted from the first state to the second state, a rear face of an extended portion of the second frame 102 becomes empty, and there is no structure supporting the rear face of the second region 151b of the display. Even when the second front portion 1021 is disposed, there is a problem that a thickness of the second front portion 1021 is increased in order to obtain a rigidity for supporting the empty space corresponding to the extended

23

portion of the second frame **102**. Even when the second front portion **1021** of the second frame **102** is omitted or there is the second front portion **1021**, there is a need for a structure that supports the extended third region **151c** of the display unit **151** without increasing the thickness of the second front portion **1021**.

The present embodiment has a structure of a pivotable support link **251**. The support link **251** may be disposed in the third direction in the first state, and unfolded in the second state and disposed in the second frame **102** obliquely or in the first direction as shown in FIG. **12B**. The support link **251** disposed as shown in FIG. **12B** may fill the empty space long in the third direction to prevent sagging of the third region **151c** of the display unit **151**. One end of the support link **251** is movable in the third direction, and the other end thereof is only pivotable and does not change in a position in the third direction. In the drawing, one end of the support link **251** is fastened to the first frame **101** and the other end thereof is fastened to the second frame **102**, but may be configured in reverse.

One end of the support link **251** may be inserted into a link rail **252** fastened to the first frame **101** to move along the link rail **252**. As shown in FIG. **13**, when there are a pair of support links **251**, the pair of support links **251** may be arranged in a symmetrical manner such that a spacing between one end of one support link **251** and one end of the other support link **251** is variable, or may be arranged in parallel with each other to move while maintaining a constant spacing.

Referring to FIG. **14B**, each support link **251** has a first coupling hinge **2512** and a second coupling hinge **2513** respectively pivotably coupled to both ends of each support link **251**. The first coupling hinge **2512** moves along the link rail coupled to the first frame **101**, and the second coupling hinge **2513** is fixed to the second frame **102**. The support link **251** may have a variable angle with the first frame **101** or the second frame **102** through the first coupling hinge **2512** and the second coupling hinge **2513**, and a placement of the support link **251** may vary as shown in FIG. **13**.

The link rail **252** is a groove-shaped rail extending in the third direction. A slide protrusion **2514** protruding from the first coupling hinge **2512** may be inserted into the rail and moved. The link rail **252** includes a first rail **2521** having a width of a first size and extending in the third direction and a second rail **2522** having a width of a second size. The first rail **2521** is an elongated section in which the slide protrusion **2514** protruding from the first coupling hinge **2512** is inserted and moved, and the second rail **2522** is a portion having a larger opening for inserting the slide protrusion **2514** therein.

An end of the slide protrusion **2514** includes an extended end **2515** such that the first coupling hinge **2512** is not departed from the link rail **252**. A width of the extended end **2515** is larger than a width of the first rail **2521**, so that the first coupling hinge **2512** is not departed from the first rail **2521**. Further, the width of the extended end **2515** corresponds to or smaller than a width of the second rail **2522**, so that the first coupling hinge **2512** may be inserted through the second rail **2522**. As shown in FIG. **13**, when the pair of support links move symmetrically, in the first state, one end of one support link **251** may be in contact with one end of the other support link **251**, and the second rail **2522** may be positioned at a contact portion. The second rail **2522** may be formed in a shape corresponding to the shape of the extension end **2515**. When the support links **251** are coupled one by one through the second rail **2522**, and when the second coupling hinges **2513** are coupled to the second frame **102**

24

such that one end of one support link **251** and one end of the other support link **251** are not positioned in the second rail **2522**, the first coupling hinges **2512** of the support links **251** may move without departing from the link rail **252**.

The support link **251** may have a height corresponding to a spacing between the second rear portion of the second frame **102** and the rear face of the display unit **151** in order to support the rear face of the extended third region **151c** of the display unit **151**. Such support link **251** is disposed in the third direction in the first state and a volume thereof is not that large. Further, the support link **251** is unfolded in the second state to stably support the extended rear face of the display unit **151**.

As another example of the support structure of the display unit **151**, a display support **255** positioned on the rear face of the first front portion **1011** of the first frame **101** in the first state and positioned in the rear face direction of the display unit **151** in the second state may be further included. The display support **255** may be extended like the second front portion **1012** of the second frame **102** described above and disposed on an entirety of the rear face of the third region **151c** moved to the front face, or may also be partially disposed as shown in FIG. **13**. According to the embodiment shown in FIG. **13**, the display supports **255** may be respectively positioned at both ends in the third direction (up and down direction) to support the extended portion of the display unit **151** together with the support link **251**. The display support **255** may extend or retract as long as a space is available.

As described above, the display unit **151** may be prevented from being separated when the state of the mobile terminal **100** is converted or in the converted state of the mobile terminal **100**, thereby improving usability.

Even when the tensioning structure is added, because a driving resistance is small, a flatness of the display unit **151** may be increased without causing a decrease in driving force of the mobile terminal **100**.

Because a uniform tensile force may be applied at all times, so that free stop is available in any state.

In addition, because the tensile force is not directly applied to the display unit **151** using the tensioning seat **241**, a reliability of the display unit **151** may be improved.

Effects as not described herein may be derived from the above configurations. The relationship between the above-described components may allow a new effect not seen in the conventional approach to be derived.

In addition, embodiments shown in the drawings may be modified and implemented in other forms. The modifications should be regarded as falling within a scope of the present disclosure when the modifications are carried out so as to include a component claimed in the claims or within a scope of an equivalent thereto.

What is claimed is:

1. A mobile terminal comprising:

- a first frame;
- a second frame movable in a first direction from the first frame to convert a state of the mobile terminal from a first state to a second state, and slidable in a second direction opposite to the first direction to convert the state of the mobile terminal from the second state to the first state;
- a slide frame movable in the first direction or in the second direction with respect to the second frame;
- a flexible display device including a first region coupled to the first frame, a second region coupled to the slide

25

frame, and a third region positioned between the first region and the second region and bent to surround the second frame;

a tensioning belt having a first end fixed to the first frame and a second end coupled to the slide frame; and

a belt roller positioned at a second directional end of the second frame, wherein the tensioning belt is wound around the belt roller.

2. The mobile terminal of claim 1, wherein the first end of the tensioning belt is disposed adjacent to a first directional end of the first frame.

3. The mobile terminal of claim 2, wherein the first frame includes a first front portion coupled with the first region of the flexible display device and a first rear portion spaced behind the first front portion,

wherein the second frame includes a second rear portion located on a rear surface of the first rear portion when the mobile terminal is in the first state, and

wherein the belt roller has a diameter corresponding to a thickness of the second rear portion.

4. The mobile terminal of claim 2, further comprising a pair of tensioning pins arranged at the first directional end of the first frame and arranged in a vertical direction, and

wherein the tensioning belt is wound around the pair of tensioning pins in an S-shape, wherein the first end of the tensioning belt is coupled to a first front portion of the first frame.

5. The mobile terminal of claim 4, wherein the tensioning belt is in contact with a first side of a tensioning pin of the pair of tensioning pins, and

wherein the mobile terminal further includes an elastic body for pressing a second side of the tensioning pin.

6. The mobile terminal of claim 4, wherein the mobile terminal further includes a tensioning seat positioned on respective rear surfaces of the second region and the third region of the flexible display device, wherein both ends of the tensioning seat are coupled to the first end of the tensioning belt.

7. The mobile terminal of claim 1, further comprising:

a link rail coupled to one of the first frame or the second frame, and extending along a third direction perpendicular to the first direction; and

a support link having a first end movable along the link rail and a second end coupled to the other of the first frame or the second frame.

8. The mobile terminal of claim 7, wherein the support link is disposed in the third direction perpendicular to the first direction when the mobile terminal is in the first state, and

26

wherein the support link supports the third region of the flexible display device while traversing an extended portion of the second frame when the mobile terminal is in the second state.

9. The mobile terminal of claim 7, wherein the support link includes:

a first coupling hinge pivotably coupled to the first end of the support link, and fastened to the link rail; and

a second coupling hinge pivotably coupled to the second end of the support link, and fixed to one of the first frame or the second frame.

10. The mobile terminal of claim 9, wherein the link rail includes a first rail having a width of a first amplitude and a second rail having a width of a second amplitude greater than the first amplitude, and

wherein the first coupling hinge includes a slide protrusion having a thickness corresponding to the width of the first rail, and an extended end positioned at an end of the slide protrusion and having a diameter corresponding to the width of the second rail.

11. The mobile terminal of claim 10, wherein the second rail is disposed at a center, and the first rail comprises a pair of rails arranged symmetrically, and

wherein a pair of support links are symmetrically arranged in the third direction, and wherein first coupling hinges of the pair of support links move in opposite directions on the pair of rails.

12. The mobile terminal of claim 10, wherein the second rail has a shape corresponding to the extended end of the first coupling hinge, and

wherein the extended end partially overlaps or does not overlap the second rail when the mobile terminal is in the first state.

13. The mobile terminal of claim 1,

wherein the first frame includes:

a first front portion coupled with the first region of the flexible display device; and

a first rear portion spaced behind the first front portion, and

wherein the second frame includes:

a second rear portion located on a rear surface of the first rear portion when the mobile terminal is in the first state; and

a display support positioned on a rear surface of the first front portion when the mobile terminal is in the first state, and positioned on a rear surface of the third region of the display unit when the mobile terminal is in the second state.

* * * * *