

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 September 2007 (27.09.2007)

PCT

(10) International Publication Number
WO 2007/109104 A2

- (51) International Patent Classification: **Not classified**
- (21) International Application Number:
PCT/US2007/006572
- (22) International Filing Date: 15 March 2007 (15.03.2007)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/783,181 16 March 2006 (16.03.2006) US
- (71) Applicant (for all designated States except US): **TRIS PHARMA, INC.** [US/US]; 2033 Route 130, Suite D, Monmouth Junction, NJ 08852 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MEHTA, Ketan** [US/US]; 20 Nostrand Road, Cranbury, NJ 08550 (US). **TU, Yu-hsing** [US/US]; 19 E. Kincaid Drive, West Windsor, NJ 08550 (US).
- (74) Agents: **KODROFF, Cathy, A.** et al.; Howson And Howson, 501 Office Center Drive, Suite 210, Fort Washington, PA 19034 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MODIFIED RELEASE FORMULATIONS CONTAINING DRUG-ION EXCHANGE RESIN COMPLEXES

(57) Abstract: A coated drug - ion exchange resin complex comprising a core composed of a drug complexed with a pharmaceutically acceptable ion-exchange resin is provided. The drug - ion exchange resin complex is in admixture with a release retardant. The coating contains a polyvinyl acetate polymer and a plasticizer. Methods of making and products containing this coated complex are described.



WO 2007/109104 A2

MODIFIED RELEASE FORMULATIONS CONTAINING DRUG - ION EXCHANGE RESIN COMPLEXES

BACKGROUND OF THE INVENTION

The present invention relates to pharmaceutical preparations having a drug-ion
5 exchange resin complex that is treated to provide programmable release characteristics in the gastrointestinal tract.

One important aspect of drug therapy is the effect of a drug for an extended time and in many cases, the longer the time, the more substantial the benefit.

Use of ion-exchange resins to form a drug - ion exchange resin complex is
10 well known and is described, for example, in US Patent No. 2,990,332. In this patent, the use of an ion-exchange resin to form a complex with ionic drugs and thereby delay the drug release from such complexes is described. Such delay in drug release was deemed to be of relatively short duration. Since then there have been additional publications and patents (*e.g.*, US Patent Nos. 3,138,525; 3,499,960; 3,594,470;
15 Belgian patent 729,827; German patent 2,246,037) that describe use of such ion-exchange resin complexes with water-permeable diffusion barrier coatings of the drug - ion exchange resin complex coated to alter the release of drugs from the drug - ion exchange resin complex.

Sustained or prolonged release dosage forms of various drugs are known and
20 commercially available. However, there are only a few products available that provide sustained release of the drug from the very fine particles of coated drug-ion exchange complexes. A recent US Published Patent application, US 2005/0181050 A1, published August 18, 2005, mentions that few modified release liquids containing drug-loaded ion exchange resin particles are commercially available. It further states
25 that such products require several time consuming steps and require the use of a potentially hazardous step of coating from a solvent based solution. The regulatory authorities require that such solvents are thoroughly removed from the pharmaceutical products before ingestion.

Raghunathan in US Patent Nos. 4,221,778; 4,847,077 and *Raghunathan et al.*
30 in *J. Pharm. Sci.*, Vol 70, pp 379-384, April 1981, describe treating drug-ion exchange

resin complexes with water soluble, hydrophilic impregnating (solvating) agents such as polyethylene glycol and others so as to enable the coating of drug - ion exchange resin complexes with a water-permeable diffusion barrier. These publications indicate that the drug-ion exchange resin tended to swell when in contact with water, causing the coating layer to fracture and prematurely release the drug thereby adversely impacting the purpose of the coating (*i.e.*, control release). Attempts to minimize such rupture of the coating layer were made using impregnating (solvating) agents to control the swelling of the drug - ion exchange resin complex. Other patents describing variations of this type of product are referenced in US Published Patent Application 2003/0099711 A1, section 0006.

Further, *Kelleher et al.* in US Patent No. 4,996,047 describe using a drug content above a specified value in the drug - ion exchange resin complex to avoid the swelling of the drug - ion exchange resin complex and thereby minimizing the rupture of the coating. *Umemoto et al.*, describe in US Patent No. 5,368,852 that despite the use of impregnating agents, certain preservatives used in the liquid preparation tend to cause the rupture of the diffusion barrier coating of the drug - ion exchange resin complex. *Umemoto et al.*, reported overcoming the rupture of the coating membrane by use of a preservative that did not cause the rupture.

Another patent, US Patent No. 6,001,392 granted December 14, 1999 describes certain acrylate based (*e.g.*, EUDRAGIT polymer system) and ethyl cellulose (*e.g.*, SURELEASE, AQUACOAT) polymers for coating a drug - ion exchange resin complex using either a solvent or aqueous based coating to achieve sustained release of the drug from the drug - ion exchange resin complex. No meaningful data is disclosed regarding the integrity of the coating film. Further, there is no reported data or evidence of prolonged release of the drug from the coated drug - ion exchange resin complex beyond about 12 hours. A more recently published patent application, US 2003/0099711 A1, describes using an ethyl cellulose polymer in an aqueous based coating system. This publication further describes use of an enteric coating as an optional added coating to delay the drug release. There have been literature-reported drawbacks of using ethyl cellulose based aqueous dispersions as coatings for drug-ion exchange resin complexes.

Similarly, there have been drawbacks associated with previously used polymers of acrylate and methacrylate-based aqueous dispersion coating systems for coating drug-ion exchange resin complex. Amongst these shortcomings observed is significant tackiness upon application of the coating and during curing, which
5 complicates the coating process of drug-ion exchange resin complexes and/or requires the addition of further components such as an anti-tacking material to counteract this undesirable property.

SUMMARY OF THE INVENTION

10 The invention provides pharmaceutical preparations comprising drug(s) bound to an ion-exchange resin to provide a drug-ion exchange resin complex, admixing of such complex with a release retardant water-insoluble polymer, and coating of such admixture with a highly flexible, substantially tack-free, non-ionic, water-insoluble, water-permeable diffusion membrane which is preferably aqueous-based and provides
15 a coating membrane that maintains its film integrity, and further provides controllable modified release of the active pharmaceutical(s) in the gastrointestinal tract for a duration of up to about 24 hours.

In one aspect, the present invention provides ingestible pharmaceutical compositions comprising substantially tack free, non-ionic, water-permeable diffusion
20 barrier coatings for drug - ion exchange resin complexes that need not be based upon the use of organic solvents to dissolve the coating composition, do not use either ethyl cellulose or acrylate based polymers compositions or other standard coatings heretofore used for coating ion exchange drug resin complexes, do not require the use of impregnating (solvating) agents, provide excellent integral film coatings, and can
25 provide prolonged, programmable release of drugs from the drug - ion exchange resin complexes of up to about 24 hours.

In another aspect, the present invention provides pharmaceutical compositions comprising water-permeable diffusion barrier coatings for a drug - ion exchange resin complex that are water based, provide highly flexible coatings that are applied in
30 substantially non-tacky form, which facilitates processing of such coatings, in the presence of acceptable plasticizer levels and maintain the coating film integrity and

minimize fracturing of the coating layer even after being subjected to severe physical stress, including the compression step of a tableting operation.

In still another aspect, the present invention provides a highly flexible coating that has the potential benefit of reducing the drug-abuse of narcotics or controlled
5 drug substances. The flexible coating can reduce the ability of the subjects to get instant "high" by making it more difficult to break the barrier coating by chewing or other mechanical means due to the increased resistance of such flexible coating to easy rupture.

In a further aspect, the present invention provides oral pharmaceutical
10 compositions comprising a drug-ion exchange resin complex that does not need an enteric coating to provide prolonged release up to about 24 hours.

In yet another aspect, the present invention provides oral pharmaceutical compositions comprising a drug-ion exchange resin complex that can be formulated to give customizable, programmable release of the one or more drugs from such
15 complexes by combining the application of a release retardant in combination with a water-permeable diffusion barrier coating that is aqueous-based and which are not believed heretofore to have been used for coating films for drug-ion exchange resin complexes.

A further desirable advantage, previously reported when using ion exchange
20 resins, is to provide a reduction of undesirable tastes sometimes associated with an orally ingestible formulation, where unbearable or bad taste of the active drug may be a drawback to the recommended drug ingestion regimen.

Another aspect of the present invention is to provide a method of manufacture of drug-ion exchange resin complexes that provide flexibility, higher drug binding
25 efficiency, and drug loading and processing benefits to produce such complexes.

It has been observed by the inventors that use of heretofore known film coatings of an acrylate-based EUDRAGIT polymer system may lead to agglomeration of the particles during application and/or curing, particularly high-temperature curing. Further, such acrylate-based polymer systems have been observed by the inventors to
30 cause agglomeration and color migration in the presence of colorants in an orally ingestible liquid suspension, upon storage thereof for over about one month. Further,

the inventors have observed that ethyl cellulose-based coating systems cause flocculation when in liquid suspension, thereby creating a defective coating system.

Thus, the present invention addresses both art-recognized and what the inventors previously believe are unreported problems associated with prior art drug -
5 ion exchange resin complexes. These and other advantages of the present invention will be apparent from the following detailed description of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a coated drug-ion exchange resin composition
10 for further use in formulation with conventional pharmaceutically acceptable components to provide ingestible compositions. The finished dose compositions may take the form of liquid preparations such as suspensions or solid preparations such as tablets, capsules, liquigels, powders, wafers, strips, etc. In one preferred embodiment, the coating is an aqueous based coating. However, the invention may utilize a
15 non-aqueous, solvent-based system alone (as long as excess solvent is removed), or in conjunction with an aqueous based coating.

Controlled release particles containing pharmaceutically active drug can be manufactured that are coated with an aqueous based system and provide safe products. The use of the water based coatings, the use of a release retardant, and
20 methods of manufacture are disclosed.

The inventors have found that by using a drug-ion exchange resin having a water-permeable diffusion barrier coating as described herein, a prolonged release of drug from the drug-ion exchange resin complex is obtained without the necessary use of water soluble impregnating (solvating) agents as these terms are defined in US
25 Patent No. 4,221,778.

The drug release pattern from the compositions of the present invention may be further controlled or modified by combining the drug and resin to form the drug-ion exchange resin complex matrix prior to the application of the water-permeable diffusion barrier coating. Water-insoluble polymers useful in the barrier coating

include a single polymer or mixtures thereof, such as may be selected from polymers of ethyl cellulose, polyvinyl acetate, cellulose acetate, polymers such as cellulose phthalate, acrylic based polymers and copolymers (such as, for example, those available under EUDRAGIT brand name) or any combination of such insoluble polymers or polymer systems herein defined as a "release retardant". The water-permeable diffusion barrier coating system with or without a "release retardant" may be formulated to achieve the desired length of time of drug release rate from such drug-ion exchange resin complexes. Such coating systems could be further customized by the incorporation of individual or a combination of hydrophilic or lipophilic plasticizers with a dispersion or suspension containing the barrier coating polymer. Such plasticizers include, *e.g.*, propylene glycol, polyethylene glycol, triacetin, triethyl citrate, dibutyl sebacate, vegetable oil, lipids, etc.

Polyvinyl acetate, due to its high tensile strength in the presence of a plasticizer(s), provides a flexible coating film for use as the water-permeable diffusion barrier coating that maintains its film integrity even when subjected to severe physical force and stress such as during a compression step in a tableting machine or the grinding action of a coffee beans grinder, mill, etc. These coatings even with the addition of a plasticizer remain substantially non-tacky and process-friendly during the coating operation in a Wurster fluid bed or other coating operation and do not cause agglomeration during the coating of very fine particles of drug-ion exchange resins. Agglomeration (sometimes termed "caking" or "brick formation") during a coating operation may otherwise impede the air flow, destroy flow pattern, and/or clog the spray nozzle, thereby increasing the possibility of an imperfect and uneven coating of the drug-ion exchange resin particles.

It has been found that, by employing the compositions described above, it is possible to obtain controlled release compositions that are highly flexible and use a substantially tack-free coating system during coating application and curing. Further, the compositions of the invention do not require the use of an impregnating (solvating) agent to control the swelling or otherwise impede the rupture of the coating membrane. Thus, the compositions of the present invention can provide

programmable and prolonged release of drugs from drug - ion exchange resin complexes using the herein described water-based diffusion barrier coating systems.

The term "programmable release" is used to describe a pre-determined release profile of drug from the drug-ion exchange resin complex for up to about 24 hours.

5 Due to the prolongation of the drug release of up to about 24 hours, the compositions of the present invention have concomitant advantages: instead of taking two or three dosages per day, one may take a once-a-day dose that would provide more consistent supply (release) of the drug that otherwise may have to be taken multiple times a day. This is especially beneficial in the case of small children, elderly
10 people, or others, who have difficulty swallowing larger solid dosage forms such as tablets or capsules.

 The coated drug-ion exchange resins of the present invention are formulated into finished ingestible dosage forms such as a liquid suspension or a fast disintegrating tablet that need not be swallowed. It has also been observed that for use
15 in liquid compositions, the film forming coating of the present invention for the drug - ion exchange resin complex when formulated into a liquid suspension does not produce undesirable agglomerations and color migration of the suspended particles in the liquid in the presence of a colorant which is desirably used in medicines to be taken by children. Therefore, such prolonged release compositions may enhance
20 compliance.

 As used herein, the term "modified release" refers to compositions of the invention which are characterized by having a drug release from a drug-ion exchange complex of the invention over a period of at least about 8 hours, and preferably up to about 24 hours. For a 24 hour release product, in one aspect, less than 50% of the
25 drug is released from the drug-ion exchange resin complex of the invention at about 12 hours from administration. In another aspect, less than 60% of the drug is released from the drug-ion exchange resin complex of the invention at about 12 hours from administration. In still another aspect, less than 70% of the drug is released from the drug-ion exchange resin complex at about 12 hours. In still other embodiments, less
30 than about 80% or more of the drug is released from the drug-ion exchange resin at about 12 hours. The term "modified release" may include, *e.g.*, composition which are

extended release formulations, sustained release formulations, or delay release formulations.

As used herein in reference to numeric values provided herein, the term “about” may indicate a variability of as much as 10%. The term “comprises”,
5 “comprising” and its variants are inclusive of other components, integers, and steps. The term “consists”, “consisting”, and its variants are exclusive of other components integers and steps.

A detailed description of the components of the compositions of the present invention follows:

10 Ion-Exchange Resin

Contemplated within the scope of the invention are pharmaceutically active compounds safe for ingestion, which form a complex with an ion-exchange resin and are manufactured in accordance with Good Manufacturing Practices (GMP) for bulk pharmaceutical chemicals. Typically, these compounds are designed for oral
15 administration and administration via a nasogastric tube.

Ion- exchange resins suitable for use in these preparations are water-insoluble and comprise a preferably pharmacologically inert organic and/or inorganic matrix containing functional groups that are ionic or capable of being ionized under the appropriate conditions of pH. The organic matrix may be synthetic (*e.g.*, polymers or
20 copolymers of acrylic acid, methacrylic acid, sulfonated styrene, sulfonated divinylbenzene), or partially synthetic (*e.g.* modified cellulose and dextrans). The inorganic matrix preferably comprises silica gel modified by the addition of ionic groups. Covalently bound ionic groups may be strongly acidic (*e.g.*, sulfonic acid, phosphoric acid), weakly acidic (*e.g.*, carboxylic acid), strongly basic (*e.g.*, primary
25 amine), weakly basic (*e.g.* quaternary ammonium), or a combination of acidic and basic groups. In general, the types of ion exchangers suitable for use in ion-exchange chromatography and for such applications as deionization of water are suitable for use in the controlled release of drug preparations. Such ion-exchangers are described by H. F. Walton in “Principles of Ion Exchange” (pp: 312-343) and “Techniques and

Applications of Ion-Exchange Chromatography”(pp: 344-361) in Chromatography. (E. Heftmann, editor), van Nostrand Reinhold Company, New York (1975). Ion exchange resins that can be used in the present invention have exchange capacities of about 6 milliequivalents (meq)/gram and preferably about 5.5 meq/gram or below.

5 Typically the size of the ion-exchange particles is from about 5 microns to about 750 microns, preferably the particle size is within the range of about 40 microns to about 250 microns for liquid dosage forms although particles up to about 1,000 micron can be used for solid dosage forms, *e.g.*, tables and capsules. Particle sizes substantially below the lower limit are generally difficult to handle in all steps of the
10 processing. Generally, uncoated drug-ion exchange resin particles of the invention will tend to be at the lower end of this range, whereas coated drug-ion exchange resin particles of the invention will tend to be at the higher end of this range. However, both uncoated and coated drug-ion exchange resin particles may be designed within this size range.

15 Commercially available ion-exchange resins having a spherical shape and diameters up to about 1,000 microns are gritty in liquid dosage forms and have a greater tendency to fracture when subjected to drying-hydrating cycles. Moreover, it is believed that the increased distance that a displacing ion must travel in its diffusion into these large particles, and the increased distance the displaced drug must travel in
20 its diffusion out of these large particles, cause a measurable but not readily controlled prolongation of release even when the drug - ion exchange resin complexes are uncoated. Release of drug from uncoated drug - ion exchange resin complexes with particle sizes in the approximate range of 40 microns to 250 microns is relatively rapid. Satisfactory control of the drug release from such complexes is achieved by the
25 applied diffusion barrier coating and can be modified by the inclusion of a release retardant as described herein.

Both regularly and irregularly shaped particles may be used as resins. Regularly shaped particles are those particles that substantially conform to geometric shapes such as spherical, elliptical, cylindrical and the like, which are exemplified by
30 Dow XYS-40010.00 and Dow XYS-40013.00 (The Dow Chemical Company). Irregularly shaped particles are all particles not considered to be regularly shaped,

such as particles with amorphous shapes and particles with increased surface areas due to surface channels or distortions. Irregularly shaped ion-exchange resins of this type are exemplified by Amberlite IRP-69 (Rohm and Haas). Two of the preferred resins of this invention are Amberlite IRP-69 and Dow XYS-40010.00. Both are
5 sulfonated polymers composed of polystyrene cross-linked with about 8% of divinylbenzene, with an ion-exchange capacity of about 4.5 to 5.5 meq/g of dry resin (H^+ -form). Their essential difference is in physical form. Amberlite IRP-69 consists of irregularly shaped particles with a size range of about 5 microns to about 149 microns produced by milling the parent large size spheres of Amberlite IRP-120. The
10 Dow XYS-40010.00 product consists of spherical particles with a size range of 45 microns to 150 microns.

Other suitable ion-exchange resins include anion exchange resins, such as have been described in the art and are commercially available. These resins are particularly well suited for use with acidic drugs including, *e.g.*, nicotinic acid,
15 mefanimic acid, indomethacin, diclofenac, repaglinide, ketoprofen, ibuprofen, valproic acid, lansoprazole, ambroxol, omeprazole, acetaminophen, topiramate, and carbamazepine, pentobarbital, warfarin, triametrene, and prednisolone, as well as prodrugs, salts, isomers, polymorphs, and solvates thereof, as well as other drugs identified herein and/or known in the art.

20 An example of an anion exchange resin is a cholestyramine resin, a strong base type 1 anion exchange resin powder with a polystyrene matrix and quarternary ammonium functional groups. The exchangeable anion is generally chloride which can be exchanged for, or replaced by, virtually any anionic species. A commercially available Cholestyramine resins is PUROLITE™ A430MR resin. As described by its
25 manufacturer, this resin has an average particle size range of less than 150 microns, a pH in the range of 4-6, and an exchange capacity of 1.8 – 2.2 eq/dry gm. Another pharmaceutical grade cholestyramine resin is available as DUOLITE™ AP143/1094 [Rohm and Haas], described by the manufacturer as having a particle size in the range of 95%, less than 100 microns and 40%, less than 50 microns. The commercial
30 literature from the suppliers of these and other resin is incorporated herein by reference (PUROLITE A-430 MR; DOW Cholestyramine USP, Form No. 177-

01877-204, Dow Chemical Company; DUOLITE AP143/1083, Rohm and Haas Company, IE-566EDS – Feb 06).

Cation exchange resins, *e.g.*, AMBERLITE IRP-69, are particularly well suited for use with drugs and other molecules having a cationic functionality, including, *e.g.*, acycloguanosine, tinidazole, deferiprone, cimetidine, oxycodone, remacemide, nicotine, morphine, hydrocodone, rivastigmine, dextromethorphan, propanolol, betaxolol, 4-aminopyridine, chlorpheniramine, paroxetine, duloxetine HCl, atomoxetine HCl, risperidone, atovaquone, esmolol, naloxone, phenylpropranolamine, gemifloxacin, oxymorphone, hydromorphone, nalbupherin, and O-desmethylvenlafaxine, as well as prodrugs, salts, isomers, polymorphs, and solvates thereof, as well as other drugs identified herein and/or known in the art. Cationic exchange resins are readily selected for use of these basic drugs or other drugs identified herein and/or are those which are known to those of skill in the art.

The selected ion-exchange resins may be further treated by the manufacturer or the purchaser to maximize the safety for pharmaceutical use or for improved performance of the compositions. Impurities present in the resins may be removed or neutralized by the use of common chelating agents, anti-oxidants, preservatives such as disodium edetate, sodium bisulfite, and so on by incorporating them at any stage of preparation either before complexation or during complexation or thereafter. These impurities along with their chelating agent to which they have bound may be removed before further treatment of the ion exchange resin with a release retardant and diffusion barrier coating.

Drugs

The drugs that are suitable for use in these preparations in terms of chemical nature are acidic, basic, amphoteric, or zwitterionic molecules. Such drugs include small molecules, and selected larger molecules as well, including chemical moieties and biologicals, such as, *e.g.*, a protein or a fragment thereof (*e.g.*, a peptide, polypeptide, etc), enzyme, antibody or antibody fragment.

The drugs that are suitable for use in these preparations include drugs for the treatment of respiratory tract disorders such as, for example, antitussive expectorants such as dihydrocodeine phosphate, codeine phosphate, noscapine hydrochloride, phenylpropanolamine hydrochloride, potassium guaiaacolsulfonate, cloperastine fendizoate, dextromethorphan hydrobromide and cloperastine hydrochloride; bronchodilators such as dl-methylephedrine hydrochloride and dl-methylephedrine saccharinate; and antihistamines such as fexofenadine HCl- or dl-chlorpheniramine maleate. Other drugs useful for the invention include drugs for the treatment of digestive tract disorders such as, for example, digestive tract antispasmodics, including scopolamine hydrobromide, metixene hydrochloride and dicyclomine hydrochloride, drugs for the treatment of central nervous system disorders such as, for example, antipsychotic drugs including phenothiazine derivatives (chlorpromazine hydrochloride, eth.) and phenothiazine-like compounds (chlorprothexene hydrochloride, eth.) antianxiety drugs such as benzodiazepine derivatives (chlordiazepoxide hydrochloride, diazepam, etc.), alprazolam, etc., antidepressants such as imipramine compounds (imipramine hydrochloride, etc.), respiradone, SSRIs like sertraline HCl, paroxetine HCl, venlafaxine HCl, etc., antipyretic analgesics such as sodium salicylate, and hypnotics such as phenobarbital sodium; opioid analgesics drugs such as alfentanil, allyprodine, alphaprodine, anileridine, benzylmorphine, bezitramide, buprenorphine, butorphanol, clonitazene, codeine, cyclazocine, desmorphine, dextromoramide, dexocine, diampromide, dihydrocodeine, dihydromorphine, dimexoxadol, dimepheptanol, dimethylthiambutene, dioxaphetyl butyrate, dipipanone, eptazocine, ethoheptazine, ethylmethylthiambutene, ethylmorphine, etonitazene fentanyl, heroin, hydrocodone, hydromorphone, hydroxypethidine, isomethadone, ketobermidone, levallorphan, levorphanol, levophenacymorphan, lofentanil, meperidine, meptazinol metazocine, methadone, metopon, morphine, morphine sulfate, myrophine, nalbuphine, narceine, cicomorphine, norlevorphanol, nomethadone, nalorphine, normorphine, norpipanone, opium, oxycodone, ixmymorphine, papavretum, pentazocine, phenadoxone, phenmorphan, phenazocine, phenoperidine, iminodine, piritamide, propheptazine, promedol, properidine, propiram, propoxyphene, sufentanil, tramadol, tiline, salts

thereof, mixtures of any of the foregoing, mixed mu-agonists/antagonists, mu-antagonist combinations, and the like; and drugs for the treatment of respiratory system disorders such as, for example, coronary dilators including etafenone hydrochloride, calcium antagonists such as verapamil hydrochloride, hypotensive
5 drugs such as hydrazine hydrochloride, propranolol hydrochloride and clonidine hydrochloride, a peripheral vasodilators/vasoconstrictors such as tolazoline hydrochloride, respiradone, other respiratory agents such as prednisolone, prednisolone sodium phosphate, albuterol, albuterol sulfate, terbutaline, etc. Antibiotics may also be useful including macrolides such as, oleandomycin
10 phosphate, tetracyclines such as tetracycline hydrochloride, streptomycins such as fradiomycin, sulfate, and penicillin drugs such as amoxicillin, dicloxacillin sodium, pivmecillinam hydrochloride and carbenicillinindandly sodium. Chemotherapeutic drugs may also be used including sulfa drugs such as sulfisomidine sodium, antituberculosis drugs such as kanamycin sulfate, and antiprotozoan drugs such as
15 amodiaquine hydrochloride. An excellent sustained releasing effect is obtained in basic drugs for the respiratory tract such as dihydrocodeine phosphate, dl-methyl-ephedrine hydrochloride and phenylpropanolamine hydrochloride. Acidic drugs that can be used in the present invention include, for example, dehydrocholic acid, diflunisal, ethacrynic acid, fenoprofen, furosemide, gemfibrozil, ibuprofen, naproxen,
20 phenytoin, progencid, sulindac, theophylline, salicylic acid and acetylsalicylic acid. Basic drugs that can be used in the present invention include, for example, acetophenazine, amitriptyline, amphetamine, benztropine, biperiden, bromodiphenhydramine, brompheniramine, carbinoxamine, chloperastine, chlorcyclizine, chorpheniramine, chlorphenoxamine, chlorpromazine, clemastine,
25 clomiphene, clonidine, codeine, cyclizine, cyclobenzaprine, cyproheptadine, desipramine, dexbrompheniramine, dexchlorpheniramine, dextroamphetamine, dextromethorphan, dicyclomine, diphemanil, diphenhydramine, doxepin, doxylamine, ergotamine, fluphenazine, haloperidol, hydrocodone, hydroxychloroquine, hydroxyzine, hyoscyamine, imipramine, levopropoxyphene, maprotiline, meclizine,
30 mepenzolate, meperidine, mephentermine, mesoridazine, metformin, methadone, methylephedrine, methdilazine, methscopolamine, methysergide, metoprolol,

nortriptylene, noscapine, nylindrin, oxybutynin, oxycodone, oxymorphone, orphenadrine, papaverine, pentazocine, phendimetrazine, phentermine, phenylephrine, phenylpropanolamine, pyrilamine, tripeleminamine, triprolidine, promazine, propoxyphene, propanolol, pseudoephedrine, pyrilamine, quinidine, scopolamine, dextromethorphan, chlorpheniramine and codeine. Amphoteric drugs that can be used in the present invention include for example, aminocaproic acid, aminosalicic acid, hydromorphone, isoxurprine, levorphanol, melphalan, morphine, nalidixic acid, and paraaminosalicylic acid.

Other drugs that are contemplated include, methylphenidate, dexmethylphenidate, oxymorphone, codeine, hydrocodone, chlorpheniramine, niacin, aspirin, salts thereof, and combinations thereof. Salts include, but are not limited to, methylphenidate HCl, dexmethylphenidate HCl, oxymorphone HCl, codeine phosphate, hydrocodone bitartrate, albuterol sulfate, albuterol phosphate, chlorpheniramine maleate, dexchlorpheniramine maleate, metformin HCl, oxybutynin HCl, albuterol sulfate, saligenine hydrochloride, cetirizine hydrochloride, ranitidine HCl, all individually or in combinations.

Representative of other suitable classes of drugs and specific drugs that may not have been mentioned here may be found in US Patent 5,900,882 (columns 7 through 11), the disclosure of which is incorporated herein by reference. Further, pharmaceutically acceptable prodrugs, salts, isomers, polymorphs, and solvates of the drugs identified above, are useful in the present invention. In addition, the free base of the salts specifically listed may be substituted with other pharmaceutically acceptable salts, or use as the free base, or a prodrug form.

Drug - ion exchange resin complexes

Binding of the selected drug or combination of drugs to the ion exchange resin can be accomplished using methods known in the art. One of ordinary skill in the art with little or no experimentation can easily determine the appropriate method depending upon the drug. Typically four general reactions are used for binding of a basic drug, these are (a) resin (Na^+ -form) plus drug (salt form); (b) resin (Na^+ -form)

plus drug (as free base); (c) resin (H^+ -form) plus drug (salt form); and (d) resin (H^+ -form) plus drug (as free base). All of these reactions except (d) have cationic by-products and these by-products, by competing with the cationic drug for binding sites on the resin, reduce the amount of drug bound at equilibrium. For basic drugs,
5 stoichiometric binding of drug to resin is accomplished only through reaction (d).

Four analogous binding reactions can be carried out for binding an acidic drug to an anion exchange resin. These are (a) resin (Cl^- -form) plus drug (salt form); (b) resin (Cl^- -form) plus drug (as free acid); (c) resin (OH^- -form) plus drug (salt form); (d) resin (OH^- -form) plus drug (as free acid). All of these reactions except (d) have
10 ionic by-products and the anions generated when the reactions occur compete with the anionic drug for binding sites on the resin with the result that reduced levels of drug are bound at equilibrium. For acidic drugs, stoichiometric binding of drug to resin is accomplished only through reaction (d). The binding may be performed, for example as a batch or column process, as is known in the art.

15 Typically the drug - ion exchange resin complex thus formed is collected by filtration and washed with appropriate solvents to remove any unbound drug or by-products. The complexes can be air-dried in trays, in a fluid bed dryer, or other suitable dryer, at room temperature or at elevated temperature.

For preparing the complexes, the batch equilibration is the preferred practice
20 when loading a drug into finely divided ion exchange resin powders. Due to its fine particle size, ion exchange resin does not lend itself to conventional columnar operations used with ion exchange resins. The total ion exchange capacity represents the maximum achievable capacity for exchanging cations or anions measured under ideal laboratory conditions. The capacity which will be realized when loading a drug
25 onto ion exchange resin will be influenced by such factors as the inherent selectivity of the ion exchange resin for the drug, the drug's concentration in the loading solution and the concentration of competing ions also present in the loading solution. The rate of loading will be affected by the activity of the drug and its molecular dimensions as well as the extent to which the polymer phase is swollen during loading.

30 When utilizing a batch or equilibrium process for loading a drug onto an ion exchange resin, it is usually desirable to load as much as possible of the substance of

value onto the ion exchange resin. Complete transfer of the drug from the loading solution is not likely in a single equilibrium stage. Accordingly, more than one equilibration may be required in order to achieve the desired loading onto the ion exchange resin. The use of two or more loading stages, separating the resin from the liquid phase between stages, is a means of achieving maximum loading of the drug onto the ion exchange resin although loss of drug from the liquid phase of the final stage occurs.

Although carefully controlled laboratory experiments are required to establish precise loading and elution conditions, a few general principles can be used. High loading capacity will be favored by high charge density in the drug. A high loading rate is favored by lower molecular weight. Higher drug concentrations in the loading solution, with a minimum of competing ions, will also favor higher adsorption capacity.

The amount of drug that can be loaded onto a resin will typically range from about 1% to about 75% by weight of the drug - ion exchange resin particles. A skilled artisan with limited experimentation can determine the optimum loading for any drug resin complex. In one embodiment, loading of about 10% to about 40% by weight, more desirably, about 15% to about 30% by weight, of the drug - ion exchange resin particles can be employed. Typical loadings of about 25% by weight of the drug - ion exchange resin particles can be advantageously employed.

Thus, in one aspect, the invention provides drug - ion exchange resin complexes comprising a drug loaded in an ion exchange resin as described herein. The drugs and ion exchange resins may be readily selected from amongst those drugs and resins described herein. The invention further provides drug - ion exchange resin matrixes defined as follows.

Release Retardants

The drug release rate from the compositions of the present invention may be further prolonged or modified by treating the drug - ion exchange resin complex prior to the application of the water-permeable diffusion barrier coating described herein,

with a release retardant which is a water-insoluble polymer or a combination of a water-insoluble polymers.

Advantageously, the release retardant does not form a separate layer on the drug - ion exchange resin complex, but forms a matrix therewith. Examples of suitable release retardants include, for example, a polyvinyl acetate polymer or a mixture of polymers containing same (*e.g.*, KOLLICOAT SR 30D), cellulose acetates, ethylcellulose polymers (*e.g.*, AQUACOAT™ ECD-30 or SURELEASE™), acrylic based polymers or copolymers (*e.g.*, represented by the EUDRAGIT family of acrylic resins), cellulose phthalate, or any combination of such water-insoluble polymers or polymer systems, all herein defined as “release retardants”. These retardants when used, may further prolong or alter the release of the drug from the coated drug-ion exchange resin complex and maximize attaining the desired release profile. Further, use of a release retardant permits in some cases lowering the amount of coating thickness needed to attain a prolonged drug release of up to 24 hours.

These retardants can be used in either substantially pure form or as a commercial preparation obtained from a vendor. The preferred release retardant is a polyvinyl acetate polymer as described herein or an acrylic polymer from the EUDRAGIT family. Examples of suitable acrylic polymers from the EUDRAGIT family may include, *e.g.*, a copolymer comprising ethyl acrylate and methyl methacrylate (*e.g.*, EUDRAGIT NE-30D), or EUDRAGIT RS, RL30D, RL100, or NE, which are largely pH-independent polymers; although less desirable, certain pH-dependent members of the EUDRAGIT polymer family, *e.g.*, the L, S, and E, polymers may be selected.

The quantity of polymer that is added as a release retardant typically ranges from about 3% to about 30% or more by weight of the uncoated drug-ion exchange resin particles. More preferably the release retardant, if used, is in the range from about 5% to about 20% and most preferably in the range of about 10% to about 15% by weight of the uncoated drug-ion exchange resin particles, depending on the nature of the drug - ion exchange resin complex and the desired release profile of the medicinal agent(s).

These release retardants can be added during the formation of the drug-ion exchange resin complex either in the beginning, during the middle, or after substantial

amount of complex formation has taken place. In the more preferred embodiment, the retardant is added after the formation of drug-ion exchange resin complex. Upon admixing, the drug - ion exchange resin complex particles with the release retardant, the mixture is dried and milled appropriately. In some cases, the milling may be carried out before the complete drying of the complex and then again further drying followed by milling to obtain the desired complex characteristics.

Another embodiment is the use of an impregnating (solvating) agent as a release retardant incorporated into the pharmaceutically acceptable drug ion-exchange resin complex prior to addition of the aqueous based coating. This impregnating (solvating) agent is a hydrophilic (water soluble) agent exemplified by those materials described for example in US Patent No. 4,221,778 and published US Patent application Publication No. US 2003/009971 A1, the disclosures of which are incorporated herein by reference. Specific examples of suitable impregnating agents include propylene glycol, polyethylene glycol, polyvinyl alcohol, polyvinyl pyrrolidone (*e.g.*, KOLLIDON™ K30) mannitol, methyl cellulose, hydroxypropyl methylcellulose, hydroxypropyl cellulose, and sorbitol.

Coating System

The coating system used in the present invention provides several advantages in preparation of the coated drug - ion exchange resin complex. More particularly, the polymers used in the coating of the invention are water-insoluble and generally non-ionic in nature. The coating polymers avoid problems associated with relatively high tackiness which are encountered with application and curing of prior art coating systems (including, *e.g.*, ionic polymers and those of the EUDRAGIT™ brand polymer system). These problems with tackiness of prior art systems have been found by the present inventors to result in undesirable clumping of the coated particles and to require additional processing to separate particles coated with these polymers. Attempts to solve this problem have been made previously in the art, including, *e.g.*, the addition of anti-tacking agents to prior art coating systems. However, such agents do not satisfactorily solve these problems. Further, the well-known prior art coating

systems based upon use of many of the EUDRAGIT™ brand polymer (and ionic polymers) have been found by the present inventors to have additional drawbacks for other reasons, as they cause physical stability problems, including agglomeration and migration of color when a colorant is used for liquid suspension formulations.

5 The coating system of the present invention can be applied as a substantially tack-free dispersion, without the clumping problems associated with certain prior art coating systems during the coating process and during high temperature curing. Further, the coating system of the invention provides a high tensile strength barrier coating.

In one embodiment, the barrier coating layer is about 5% to about 200%, by weight, of the uncoated drug-ion exchange resin complex. In another embodiment, the barrier coating layer is about 25 % to about 50% by weight of the uncoated drug-ion exchange resin complex, about 30% to about 45% by weight of the uncoated complex, or about 35 to about 40% by weight of the uncoated drug-ion exchange resin complex.

10 Suitably, the present invention provides a barrier coating comprising a water insoluble polymer comprising a polyvinyl acetate polymer, or a blend of polymers comprising a polyvinyl acetate polymer. In one embodiment, the barrier coating further contains a plasticizer, which can facilitate uniform coating of the drug - ion exchange resin complex and enhances the tensile strength of the barrier coating layer.

15 The aqueous based coating dispersions of the present invention that are used to provide a diffusion barrier coating are characterized by having a relatively low tackiness in either the absence or presence of plasticizer(s) and provide a high percent elongation of the polymer film (elasticity) at break in the presence or absence of plasticizer(s). More specifically, the polymer film coating is characterized by
20 exhibiting a tackiness as measured by the Hössel method described by P. Hössel, Cosmetics and Toiletries, 111 (8) 73 (1996) at 20°C/80% RH and 30°C/75%RH of about 2 or less in the presence or absence of a plasticizer and preferably about 0.5 or less.

25 Use of a relatively low tack film barrier of the present invention using a polyvinyl acetate (PVA) polymer facilitates more rapid and easier processing of the

coating composition and permits use of lower quantities of plasticizer. This provides for enhanced elongation (elasticity) and flexibility of the film coating, a desirable property of the polymer film without significantly increasing film tackiness to undesirable levels due to use of a plasticizer.

5 A coating system useful in the invention, preferably containing a polyvinyl acetate polymer, is characterized by having film-forming ability at a relatively low temperature, *i.e.*, about 20 °C or less, without a plasticizer. The combination of a plasticizer with a polyvinyl acetate polymer system may further lower the film-forming temperature of the polyvinyl acetate system.

10 Thus, the selection criteria for the plasticizer incorporated into the aqueous based polymer dispersion composition is to enhance high flexibility or elongation (elasticity) of the film coating at break measured by the texture analyzer TA-XT2 HiR (Stable Microsystems) and by the method reported by the manufacturer in its literature [*i.e.*, Jan-Peter Mittwollen, Evaluation of the Mechanical Behavior of
15 Different Sustained Release Polymers, Business Briefing: Pharmagenetics, 2003, pp. 1-3, BASF], of at least about 100%, of at least about 125% and preferably in a range between about 150% to about 400% while not substantially increasing the tackiness of the polymer film greater than about 2 (wherein the film is measured by the Hössel method referenced above independent of any composition on which it has been
20 deposited). The higher elasticity ranges are usually achieved with coatings of the present invention through the use of a relatively small amount of plasticizer. By using relatively small amount of plasticizer, the plasticizer does not achieve high enough levels to negatively effect the properties of the coating. It has been found that these objectives are achieved by using a relatively lower percent by weight of the selected
25 plasticizer(s) based on the percent by weight of the solids in the aqueous based film forming polymer composition.

Generally, a plasticizer is used in the percent range, or a mixture of plasticizers combine to total, about 2 to about 50% by weight of the coating layer, more preferably about 2.5% to about 20% by weight of the coating layer on the coated
30 drug - ion exchange resin complex. Preferably a plasticizer in range of about 5% to

about 10% by weight of the coating layer based on the coated complex provides the most desirable properties.

Suitable plasticizers are water soluble and water insoluble. Examples of suitable plasticizers include, *e.g.*, dibutyl sebacate, propylene glycol, polyethylene glycol, polyvinyl alcohol, triethyl citrate, acetyl triethyl citrate, acetyl tributyl citrate, tributyl citrate, triacetin, and Soluphor® P (2-pyrrolidone), and mixtures thereof. Other plasticizers are described in patent application publication US 2003/0099711 A1, May 29, 2003, page 4 (0041) the disclosure of which is incorporated herein by reference.

The coating composition of the present invention is preferably applied in the form of a polyvinyl acetate (PVA) polymer based aqueous coating dispersion. The PVA is insoluble in water at room temperature. The PVA may be used in either substantially pure form or as a blend. A commercial blend contains primarily a polyvinyl acetate polymer, a stabilizer, and minor amounts of a surfactant such as sodium lauryl sulfate. More specifically, the preferred aqueous based coating solution is KOLLICOAT SR 30 D (BASF Corporation) and whose composition is about 27% PVA polymer, about 2.7% polyvinylpyrrolidone (PVP), about 0.3% sodium lauryl sulfate (solids content 30%w/w). See, also, US Patent 6,066,334, which is incorporated by reference herein. The PVP and surfactant help stabilize the aqueous dispersion of the PVA. Generally, such stabilizing components are present in an amount totaling less than about 10% w/w, and preferably less than about 5% w/w. In one embodiment, if a substantially pure form of PVA is used, it can be dissolved in a suitable non-aqueous solvent to provide a coating solution for the drug ion-exchange resin complex.

In a particularly desirable embodiment, the inventors have found that optimal modified release is obtained when the KOLLICOAT™ SR-30D aqueous dispersion is cured. Preferably, the coating is cured for about 1 to about 24 hours. In alternate embodiments, the coating is cured for about 4 to about 16 hours, and preferably about 5 hours at high temperature, *e.g.*, about 50 °C to about 65 °C, and preferably about 60 °C.

Where the barrier coating comprises a PVA polymer, the PVA polymer is present in an amount of about 70 % to about 90% w/w of the final barrier coating layer, at least about 75%, at least about 80%, about 85% w/w of the final barrier coating layer.

5 Where the barrier coating also comprises PVP as a stabilizer component (*e.g.*, as is present in KOLLICOAT™ SR 30D), the final barrier coating layer generally contains about 5 to about 10% w/w of polyvinyl pyrrolidone.

10 The release rate of the present aqueous based polymer coatings of the invention which are designed to provide finished dosage orally ingestible pharmaceutical compositions such as liquid suspension, tablets, etc. are tailored to provide the desired drug release profile over a period of about 8 to 24 hours, and preferably 12 to 24 hours. This programmable release rate may be controlled principally by two variables, *i.e.*, the diffusion barrier coating thickness of the polymeric film coating and optionally, but preferred use of “a release retardant”
15 component as described above added to the drug-ion exchange resin complex to form a fine particulate matrix prior to the polymer film coating step. The release retardant is preferably a water insoluble polymer as previously described such as a PVA dispersion which has the same or similar composition of solids as the preferred aqueous based film forming coating polymer dispersion described herein used in the
20 coating step or an acrylic based polymer available commercially under the EUDRAGIT™ brand name, manufactured by Rohm Pharma Polymers. The properties of different EUDRAGIT™ compositions commercially available are described in literature from Rohm Pharma and are also described in US patent 6,419,960 (column 10-11), the disclosure of which is incorporated herein by reference. Other water
25 insoluble polymers include those listed in column 10, lines 41-53 of US patent 6,419,960 the disclosure of which is incorporated herein by reference.

FINISHED DOSE FORMULATIONS

30 The drug - ion exchange resin complexes of the present invention, can readily be formulated with pharmaceutically acceptable excipients according to methods well known to those of skill in the art. In one embodiment, these formulations contain a

substantially coated drug - ion exchange resin complex of the invention, optionally with a release retardant. In another embodiment, such formulations may also contain a selected amount of uncoated drug - ion exchange resin complex, optionally with a release retardant as described herein. In certain formulations, mixtures of coated drug - ion exchange resin complexes and uncoated drug - ion exchange resin complexes are present. These formulations may contain any suitable ratio of coated to uncoated product.

For example, a formulation of the invention containing the active component dextromethorphan desirably contains a mixture of a coated drug-ion exchange resin complex of the invention and an uncoated drug-ion exchange resin complex of the invention, in order to achieve the optimal release profile. The uncoated dextromethorphan- ion exchange resin complex and the coated dextromethorphan - ion exchange resin complex may be present in a ratio of 100:1 to 1:100 by weight. In certain embodiments, the ratio may be in about 30:70, about 10:1 to about 1:10, or about 2:1 to about 1:2, by weight.

In yet another embodiment, the formulations of the invention may contain more than one active component. For example, the formulation may contain more than one drug loaded into an ion exchange resin to form a complex of the invention. As another example, the formulation may contain a first drug-ion exchange resin complex of the invention in combination with another active component (drug) which may be in a second drug - ion exchange resin complex of the invention. In still another example, the formulation may contain a drug-ion exchange resin complex of the invention in combination with one or more active components which are not in a drug-ion exchange resin complex.

The coated drug - ion exchange resin complex of the invention may be formulated for delivery by any suitable route including, *e.g.*, orally, topically, intraperitoneally, transdermally, sublingually, intramuscularly, rectally, transbuccally, intranasally, liposomally, via inhalation, vaginally, intraocularly, via local delivery (for example, by catheter or stent), subcutaneously, intraadiposally, intraarticularly, or intrathecally. Preferably, the complex is formulated for oral delivery.

The drug-ion exchange resin composition thus prepared may be stored for future use or promptly formulated with conventional pharmaceutically acceptable carriers to prepare finished ingestible compositions for delivery orally, nasogastric tube, or via other means. The compositions according to this invention may, for example, take the form of liquid preparations such as suspensions, or solid preparations such as capsules, tablets, caplets, sublinguals, powders, wafers, strips, gels, including liquigels, etc. In one embodiment, a tablet of the invention is formulated as an orally disintegrating tablet. Such orally dissolving tablets may disintegrate in the mouth in less than about 60 seconds.

The drug-ion exchange resin coated compositions may be formulated using conventional pharmaceutically acceptable carriers or excipients and well established techniques. Without being limited thereto, such conventional carriers or excipients include diluents, binders and adhesives (*i.e.*, cellulose derivatives and acrylic derivatives), lubricants (*i.e.*, magnesium or calcium stearate, or vegetable oils, polyethylene glycols, talc, sodium lauryl sulfate, polyoxy ethylene monostearate), thickeners, solubilizers, humectants, disintegrants, colorants, flavorings, stabilizing agents, sweeteners, and miscellaneous materials such as buffers and adsorbents in order to prepare a particular pharmaceutical composition. The stabilizing agents may include preservatives and anti-oxidants, amongst other components which will be readily apparent to one of ordinary skill in the art.

Suitable thickeners include, *e.g.*, tragacanth; xanthan gum; bentonite; starch; acacia and lower alkyl ethers of cellulose (including the hydroxy and carboxy derivatives of the cellulose ethers). Examples of cellulose include, *e.g.*, hydroxypropyl cellulose, hydroxypropyl methyl cellulose, sodium carboxy methylcellulose, microcrystalline cellulose (MCC), and MCC with sodium carboxyl methyl cellulose. In one embodiment, tragacanth is used and incorporated in an amount of from about 0.1 to about 1.0% weight per volume (w/v) of the composition, and more preferably about 0.5% w/v of the composition. Xanthan gum is used in the amount of from about 0.025 to about 0.5% w/v and preferably about 0.25% w/v.

The sustained-release ion exchange resin compositions may include a humectant composition to give the liquid greater viscosity and stability. Suitable

humectants useful in the finished formulations include glycerin, polyethylene glycol, propylene glycol and mixtures thereof.

The oral liquid compositions of the present invention may also comprise one or more surfactants in amounts of up to about 5.0% w/v and preferably from about 0.02 to about 3.0% w/v of the total formulation. The surfactants useful in the preparation of the finished compositions of the present invention are generally organic materials which aid in the stabilization and dispersion of the ingredients in aqueous systems for a suitable homogenous composition. Preferably, the surfactants of choice are non-ionic surfactants such as poly(oxyethylene)(20) sorbitan monooleate and sorbitan monooleate. These are commercially known as TWEENS and SPANS and are produced in a wide variety of structures and molecular weights.

Whereas any one of a number of surfactants may be used, preferably a compound from the group comprising polysorbate copolymers (sorbitan-mono-9-octadecenoate-poly(oxy-1,2-ethanediyl)) is employed. This compound is also added functions to keep any flavors and sweeteners homogeneously dissolved and dispersed in solution.

Suitable polysorbates include polysorbate 20, polysorbate 40, polysorbate 80 and mixtures thereof. Most preferably, polysorbate 80 is employed. The surfactant component will comprise from about 0.01 to about 2.0% w/v of the total composition and preferably will comprise about 0.1% w/v of the total weight of the composition.

A second emulsifier/surfactant useful in combination with polysorbates may be employed and is preferably a poloxamer such as Poloxamer 407. Poloxamer 407 has an HLB (hydrophilic/lipophilic balance) of about 22 and is sold under the tradename Pluronic-127 (BASF – NJ). The two surfactants can be employed in substantially equivalent amounts. For example, the Poloxamer 407 and polysorbate 80 may each be employed together at levels of approximately from about 0.02 to about 4.0% w/v of the total weight of the formulation.

Aqueous suspensions may be obtained by dispersing the drug-ion exchange resin compositions in a suitable aqueous vehicle, optionally with the addition of suitable viscosity enhancing agent(s) (e.g., cellulose derivatives, xanthan gum, etc). Non-aqueous suspensions may be obtained by dispersing the foregoing compositions

in a suitable non-aqueous based vehicle, optionally with the addition of suitable viscosity enhancing agent(s) (e.g., hydrogenated edible fats, aluminum state, etc.). Suitable non-aqueous vehicles include, for example, almond oil, arachis oil, soybean oil or soybean oil or fractionated vegetable oils such as fractionated coconut oil.

5 Useful preservatives include, but are not limited to, sodium benzoate, benzoic acid, potassium sorbate, salts of edetate (also known as salts of ethylenediaminetetraacetic acid, or EDTA, such as disodium EDTA), parabens (e.g., methyl, ethyl, propyl or butyl-hydroxybenzoates, etc.), and sorbic acid. Amongst useful preservatives include chelating agents some of which are listed above and other
10 chelating agents, e.g., nitrilotriacetic acid (NTA); ethylenediaminetetraacetic acid (EDTA), hydroxyethylethylenediaminetriacetic acid (HEDTA), diethylenetriaminepentaacetic acid (DPTA), 1,2-Diaminopropanetetraacetic acid (1,2-PDTA); 1,3-Diaminopropanetetraacetic acid (1,3-PDTA); 2,2-ethylenedioxybis[ethyiminodi(acetic acid)] (EGTA); 1,10-bis(2-pyridylmethyl)-
15 1,4,7,10-tetraazadecane (BPTETA); ethylenediamine (EDAMINE); Trans-1,2-diaminocyclohexane-N, N, N', N'-tetraacetic acid (CDTA); ethylenediamine-N, N'-diacetate (EDDA); phenazine methosulphate (PMS); 2, 6-Dichloro-indophenol (DCPIP); Bis(carboxymethyl)diaza-18-crown-6 (CROWN); porphine; chlorophyll; dimercaprol (2, 3-Dimercapto-1-propanol); citric acid; tartaric acid; fumaric acid;
20 malic acid; and salts thereof. The preservatives listed above are exemplary, but each preservative must be evaluated in each formulation, to assure the compatibility and efficacy of the preservative. Methods for evaluating the efficacy of preservatives in pharmaceutical formulations are known to those skilled in the art. Preferred preservatives are the paraben preservatives include, methyl, ethyl, propyl, and butyl
25 paraben. Methyl and propyl paraben are most preferable. Preferably, both methyl and propyl paraben are present in the formulation in a ratio of methyl paraben to propyl paraben of from about 2.5:1 to about 16:1, preferably 9:1.

In the instance where auxiliary sweeteners are utilized, the present invention contemplates the inclusion of those sweeteners well known in the art, including both
30 natural and artificial sweeteners. Thus, additional sweeteners may be chosen from the following non-limiting list: Water-soluble sweetening agents such as

monosaccharides, disaccharides and polysaccharides such as xylose, ribose, glucose, mannose, galactose, fructose, high fructose corn syrup, dextrose, sucrose, sugar, maltose, partially hydrolyzed starch, or corn syrup solids and sugar alcohols such as sorbitol, xylitol, mannitol and mixtures thereof;

5 In general, the amount of sweetener will vary with the desired amount of sweeteners selected for a particular liquid formulation. This amount will normally be 0.001 to about 90% by weight, per volume of the final liquid composition, when using an easily extractable sweetener. The water-soluble sweeteners described above, are preferably used in amounts of about 5 to about 70% by weight per volume, and most
10 preferably from about 10 to about 50% by weight per volume of the final liquid composition. In contrast, the artificial sweeteners [*e.g.*, sucralose, acesulfame K, and dipeptide based sweeteners] are used in amounts of about 0.005 to about 5.0% and most preferably about 0.01 to about 2.5% by weight per volume of the final liquid composition. These amounts are ordinarily necessary to achieve a desired level of
15 sweetness independent from the flavor level achieved from flavor oils.

Suitable flavorings include both natural and artificial flavors, and mints such as peppermint, menthol, artificial vanilla, cinnamon, various fruit flavors, both individual and mixed, essential oils (*i.e.* thymol, eucalyptol, menthol and methyl salicylate) and the like are contemplated. The amount of flavoring employed is
20 normally a matter of preference subject to such factors as flavor type, individual flavor, and strength desired. Thus, the amount may be varied in order to obtain the result desired in the final product. Such variations are within the capabilities of those skilled in the art without the need for undue experimentation. The flavorings are generally utilized in amounts that will vary depending upon the individual flavor, and
25 may, for example, range in amounts of about 0.01 to about 3% by weight per volume of the final composition weight.

The colorants useful in the present invention, include the pigments such as titanium dioxide, that may be incorporated in amounts of up to about 1% by weight per volume, and preferably up to about 0.6% by weight per volume. Also, the
30 colorants may include dyes suitable for food, drug and cosmetic applications, and known as D&C and F.D. & C. dyes and the like. The materials acceptable for the

foregoing spectrum of use are preferably water-soluble. Illustrative examples include indigoid dye, known as F.D. & C. Blue No. 2, which is the disodium salt of 5,5'-indigotindisulfonic acid. Similarly, the dye known as F.D. & C. Green No. 1 comprises a triphenylmethane dye and is the monosodium salt of 4-[4-N-ethyl p-sulfobenzylamino)diphenylmethylene]-[1-(N-ethyl-N-p-sulfoniumbenzyl)-2,5-cyclohexadienimine]. A full recitation of all F.D. & C. and D. & C. and their corresponding chemical structures may be found in the Kirk-Othmer Encyclopedia of Chemical Technology, in Volume 5, at Pages 857-884, which text is accordingly incorporated herein by reference.

Suitable oils and fats that are usable would include partially hydrogenated vegetable or animal fats, such as coconut oil, palm kernel oil, beef tallow, lard, and the like. These ingredients are generally utilized in amounts with respect to the comestible product of up to about 7.0% by weight, and preferably up to about 3.5% by weight of the final product.

Wetting agents also may be employed in the inventive compositions to facilitate the dispersion of any hydrophobic ingredients. The concentration of wetting agents in the composition should be selected to achieve optimum dispersion of the ingredient within the composition with the lowest feasible concentration of wetting agent. It should be appreciated that an excess concentration of wetting agent may cause the composition, as a suspension, to flocculate. Those skilled in the art are well versed in suitable empirical methods to determine the appropriate wetting agents and concentrations to achieve optimum dispersion and avoid flocculation. Suitable wetting agents are listed in the US Pharmacopeia 29.

In another aspect, the invention provides a product containing a coated drug - ion exchange resin complex of the invention.

In some embodiments, the coated drug - ion exchange resin complexes of the invention are in packs in a form ready for administration, e.g., a blister pack, a bottle, syringes, foil packs, pouches, or other suitable container. In other embodiments, the compositions of the invention are in concentrated form in packs, optionally with the diluent required to make a final solution for administration. In still other embodiments, the product contains a compound useful in the invention in solid form

and, optionally, a separate container with a suitable suspension base or other carrier for the drug - ion exchange resin complex useful in the invention.

In still other embodiments, the above packs/kits include other components, *e.g.*, a meter dose apparatus/device, instructions for dilution, mixing and/or
5 administration of the product, other containers, nasogastric tubes, etc. Other such pack/kit components will be readily apparent to one of ordinary skill in the art.

Devices have been described, and many are commercially available, which provide for metered drug administration, including controlled infusion devices (*e.g.*, for patient-controlled analgesia), metered-dose inhalers and implantable pumps. For
10 example, various liquid metering devices for squeezable bottles have been described [US Patent No. 6,997,358, US Patent No. 3,146,919, filed in 1960, US Patent No. 3,567,079, filed in 1968, and in GB 2201395, filed in 1986.] A device for dispensing multiple compositions is provided in US Patent No. 6,997,219.

Methods and apparatus for delivery of drugs through nasogastric tubes are
15 well known to those of ordinary skill in the art. See, *e.g.*, E. Bryson, "Drug Administration via Nasogastric Tube", *Nurs Times*, 2001, Apr 19-25 97(16):51. The present invention can be readily delivered using such devices. Suitable nasogastric tubes are available commercially and/or have been described. See, *e.g.*, US Patent No. 5,334,166; US Patent No. 5,322,073; US Patent No. 4,619,673; US Patent No.
20 4,363,323.

The following examples are provided to more specifically illustrate the modified release compositions of the present invention and not intended to be limiting. They are for illustrative purposes only and it is realized that changes and variations can be made without departing from the spirit and scope of the invention.

25 Examples 1 to 17 are illustrative of the preparation of typical coated drug-ion exchange resins complexes of the present invention. Some samples from the compositions described in these examples were further processed into finish dosage forms and others were stored for future formulation and on-going stability testing under accelerated and room temperature conditions.

Example 18 illustrates the compositions of an orally disintegrating tablet using the compositions of the current invention.

Example 19 and 20 provide the compositions containing EUDRAGIT and AQUACOAT as coating compositions that resulted in color migration and caused flocculation/agglomeration.

Example 21 and 22 illustrate formulations of the invention that reduce the abuse potential of the drugs using the coated drug-ion exchange resins of the present invention.

Preparation of Coated Drug Resin Complex

Example 1

Preparation of Coated Morphine Resin Complex

Ingredient	Quantity
Morphine Resin Complex	
Morphine Sulfate	450 g
Purified Water	5 L
AMBERLITE IRP-69 RESIN	807 g
KOLLICOAT SR-30D polymer system	501 g
Coated Morphine Resin Complex	
KOLLICOAT SR-30D polymer system	952 g
Triacetin	14 g
Purified Water	533 g
Morphine Resin Complex	600 g

The morphine resin complex was prepared by first dissolving 450 g of morphine sulfate in 5 liters of purified water, and then slowly adding 807 g of AMBERLITETM IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWRTM convection oven maintained at 50 °C until moisture content was about 25%. KOLLICOATTM SR-30D of 501 g was then slowly added to the wet resin complex in a Hobart type mixer

(Kitchen Aid) to form a uniform mass. The wet mass was again dried at 50 °C in a VWR™ convection oven to the moisture content around 20%. The semi-dried granules were then milled through a 40 mesh screen using a CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill [QUADRO].

The coating solution was prepared by dispersing 952 g of KOLLICOAT™ SR-30D, 14 g of triacetin in 533 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,350 g of the coating solution to 600 g of Morphine Resin Complex using WURSTER process that resulted in 45% weight gain. The coating conditions were controlled at an inlet temperature of 77-82 °C, product temperature of 26-33 °C, air flow of 17-18 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 5-8 g/min so that uniform coating was achieved. The Coated Morphine Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 2

Preparation of Coated Oxycodone Resin Complex

Ingredient	Quantity
Oxycodone Resin Complex	
Oxycodone HCl	450 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1,427 g
KOLLICOAT SR-30D polymer system	500 g
Coated Oxycodone Resin Complex	
KOLLICOAT SR-30D polymer system	825 g
Triacetin	12 g
Purified Water	462 g
Oxycodone Resin Complex	600 g

The Oxycodone Resin Complex was prepared by first dissolving 450 g of oxycodone HCl in 8 liter of purified water, and then slowly adding 1,427 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for

4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 15%. KOLLICOAT™ SR-30D of 500 g was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried at 50 °C VWR™ convection oven to the moisture content around 12%. The semi-dried granules were then milled through 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 825 g of KOLLICOAT™ SR-30D, 12 g of triacetin in 462 g of purified water and mixed for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,200 g of the coating solution to 600 g of Oxycodone Resin Complex using WURSTER process that resulted in 40% weight gain. The coating conditions were controlled at an inlet temperature of 70-80 °C, product temperature of 25-31 °C, air flow of 16-17 cfm, nozzle pressure of 2.5-3.0 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 3-5 g/min so that uniform coating was achieved. The Coated Oxycodone Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 3 Preparation of Coated Albuterol Resin Complex

Ingredient	Quantity
Albuterol Resin Complex	
Albuterol Sulfate	286 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1837 g
KOLLICOAT SR-30D polymer system	640 g
Coated Albuterol Resin Complex	
KOLLICOAT SR-30D polymer system	952 g
Triacetin	14 g
Purified Water	533 g
Albuterol Resin Complex	600 g

The Albuterol Resin Complex was prepared by first dissolving 286 g of albuterol sulfate in 8 liters of purified water, and then slowly adding 1837 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 30%. KOLLICOAT™ SR-30D of 640 g was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried at 50 °C in a VWR™ convection oven to the moisture content around 25%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 952 g of KOLLICOAT™ SR-30D, 14 g of triacetin in 533 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,350 g of the coating solution to 600 g of Albuterol Resin Complex using WURSTER process that resulted in 45% weight gain. The coating conditions were controlled at an inlet temperature of about 60 °C, product temperature of 31-34 °C, air flow of 18-19 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 3-6 g/min so that uniform coating was achieved. The Coated Albuterol Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 4

Preparation of Coated Methylphenidate Resin Complex

Ingredient	Quantity
Methylphenidate Resin Complex	
Methylphenidate HCl	500 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1,306 g
EUDRAGIT NE-30D polymer system	467 g

Ingredient	Quantity
Coated Methylphenidate Resin Complex	
KOLLICOAT SR-30D polymer system	635 g
Triacetin	9.5 g
Purified Water	356 g
Methylphenidate Resin Complex	600 g

The Methylphenidate Resin Complex was prepared by first dissolving 500 g of methylphenidate HCl in 8 liters of purified water, and then slowly adding 1,306 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed
 5 for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 20-30%. EUDRAGIT™ NE-30D of 467 g was then slowly added to the wet resin complex in a Hobart type mixer
 10 (Kitchen Aid) to form a uniform mass. The wet mass was then passed through a 10 mesh screen and again dried at 50 °C in a VWR™ convection oven to the moisture content around 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 635 g of KOLLICOAT™ SR-30D, 9.5 g of triacetin in 356 g of purified water and mixing for 1 hour. The
 15 coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 900 g of the coating solution to 600 g of Methylphenidate Resin Complex using Wurster process that resulted in 30% weight gain. The coating conditions were controlled at an inlet temperature of 55-62 °C, product temperature of 29-31 °C, air
 20 flow of 20-24 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Methylphenidate Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 5**Preparation of Coated Dextromethorphan Resin Complex**

Ingredient	Quantity
Dextromethorphan Resin Complex	
Dextromethorphan HBr	954 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1,758 g
KOLLIDON K-30 polymer	116 g
Purified Water	1,150 g
Coated Dextromethorphan Resin Complex	
KOLLICOAT SR-30D polymer system	762 g
Triacetin	11 g
Purified Water	427 g
Dextromethorphan Resin Complex	600 g

5 The Dextromethorphan Resin Complex was prepared by first dissolving 954 g of dextromethorphan HBr in 8 liters of purified water heated to 75-80 °C, and then slowly adding 1,758 g of AMBERLITE™ IRP-69 resin with continuous mixing while cooling down to room temperature. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 20-25%. In a separate container, KOLLIDON K-30 polymer (116 g) was dissolved in 1,150 g of purified water and slowly applied to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was then dried at 50 °C in a VWR™ convection oven to the moisture content was around 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

20 The coating solution was prepared by dispersing 762 g of KOLLICOAT™ SR-30D polymer, 11 g of triacetin in 427 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,050 g of the coating solution to 600 g of Dextromethorphan Resin Complex using Wurster process that resulted in 35% weight gain. The coating

conditions were controlled at inlet temperature of 64-71 °C, product temperature of 27-35 °C, air flow of 15-20 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Dextromethorphan Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 6

Preparation of Coated Codeine Resin Complex

Ingredient	Quantity
Codeine Resin Complex	
Codeine Phosphate	500 g
Purified Water	5 kg
AMBERLITE IRP-69 resin	1,856 g
EUDRAGIT NE-30D polymer system	668 g
Purified Water	1,150 g
Coated Codeine Resin Complex	
KOLLICOAT SR-30D polymer	635 g
Triacetin	9.5 g
Purified Water	356 g
Codeine Resin Complex	600 g

The Codeine Resin Complex was prepared by first dissolving 500 g of codeine phosphate in 5 kg of purified water, and then slowly adding 1,856 g of AMBERLITETM IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried at VWRTM convection oven maintained at 50 °C until moisture content was about 20-30%. EUDRAGITTM NE-30D polymer system (668 g) was mixed with 1,150 g of purified water and then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was dried at 50 °C in a VWRTM convection oven to the moisture content around 3-7%. The dried granules were then milled through 40 mesh screen using CO-MILTM brand mill.

The coating solution was prepared by dispersing 635 g of KOLLICOAT™ SR-30D polymer, 9.5 g of triacetin in 356 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 900 g of the coating solution to 600 g of Codeine Resin Complex using Wurster process that resulted in 30% weight gain. The coating conditions were controlled at an inlet temperature of 54-68 °C, product temperature of 30-35 °C, air flow of 19-23 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Codeine Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 7

Preparation of Coated Tramadol Resin Complex

Ingredient	Quantity
Tramadol Resin Complex	
Tramadol HCl	500 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1,345 g
KOLLICOAT SR-30D polymer	467 g
Coated Tramadol Resin Complex	
KOLLICOAT SR-30D polymer	762 g
Triacetin	11 g
Purified Water	427 g
Tramadol Resin Complex	600 g

The Tramadol Resin Complex was prepared by first dissolving 500 g of tramadol HCl in 8 liters of purified water, and then slowly adding 1,345 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 25%. KOLLICOAT™ SR-30D polymer (467 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried in a 50

°C VWR™ convection oven to the moisture content around 20%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 762 g of KOLLICOAT™ SR-30D polymer, 11 g of triacetin in 427 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,050 g of the coating solution to 600 g of Tramadol Resin Complex using Wurster process that resulted in 35% weight gain. The coating conditions were controlled at an inlet temperature of about 60-66 °C, product temperature of 25-33 °C, air flow of 16-19 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-5 g/min so that uniform coating was achieved. The Coated Tramadol Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 8

Preparation of Coated Pseudoephedrine Resin Complex

Ingredient	Quantity
Pseudoephedrine Resin Complex	
Pseudoephedrine HCl	857 g
Purified Water	5 L
AMBERLITE IRP-69 resin	1,589 g
KOLLICOAT SR-30D polymer system	668 g
Ingredient	Quantity
Coated Pseudoephedrine Resin Complex	
KOLLICOAT SR-30D polymer system	825 g
Triacetin	12 g
Purified Water	462 g
Pseudoephedrine Resin Complex	600 g

The Pseudoephedrine Resin Complex was prepared by first dissolving 857 g of pseudoephedrine HCl in 5 liter of purified water, and then slowly adding 1,589 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The

slurry was filtered and rinsed 3 times with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 25%. KOLLICOAT™ SR-30D polymer (668 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried at 50 °C in a VWR™ convection oven to the moisture content around 30%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 825 g of KOLLICOAT™ SR-30D polymer, 12 g of triacetin in 462 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,200 g of the coating solution to 600 g of Pseudoephedrine Resin Complex using Wuster process that resulted in 40% weight gain. The coating conditions were controlled at an inlet temperature of about 68-72 °C, product temperature of 26-32 °C, air flow of 16-19 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Pseudoephedrine Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 9

Preparation of Coated Phenylephrine Resin Complex

Ingredient	Quantity
Phenylephrine Resin Complex	
Phenylephrine HCl	400 g
Purified Water	8 L
AMBERLITE IRP-69 resin	1,165 g
KOLLICOAT SR-30D polymer system	467 g
Coated Phenylephrine Resin Complex	
KOLLICOAT SR-30D polymer system	825 g
Triacetin	12 g
Purified Water	462 g
Phenylephrine Resin Complex	600 g

The Phenylephrine Resin Complex was prepared by first dissolving 400 g of phenylephrine HCl in 8 liter of purified water, and then slowly adding 1,165 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 25%. KOLLICOAT™ SR-30D polymer system (467 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried at 50 °C in a VWR™ convection oven to the moisture content around 30%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 825 g of KOLLICOAT™ SR-30D polymer system, 12 g of triacetin in 462 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,200 g of the coating solution to 600 g of Phenylephrine Resin Complex using Wurster process that resulted in 40% weight gain. The coating conditions were controlled at an inlet temperature of about 60-72 °C, product temperature of 25-34 °C, air flow of 16-19 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Phenylephrine Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 10**Preparation of Coated Hydrocodone Resin Complex**

Ingredient	Quantity
Hydrocodone Resin Complex	
Hydrocodone Bitartrate	450 g
Purified Water	8 kg
AMBERLITE IRP-69 resin	1,407 g
KOLLICOAT SR-30D polymer system	500 g
Coated Hydrocodone Resin Complex	
KOLLICOAT SR-30D polymer system	952 g
Triacetin	14 g
Purified Water	533 g
Hydrocodone Resin Complex	600 g

The Hydrocodone Resin Complex was prepared by first dissolving 450 g of hydrocodone Bitartrate in 8 kg of purified water, and then slowly adding 1,407 g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 20-25%. KOLLICOAT™ SR-30D polymer (500 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried in a 50 °C VWR™ convection oven to the moisture content around 15-20%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and continued drying under 50 °C until the moisture content was between 3-7%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 952 g of KOLLICOAT™ SR-30D polymer, 14 g of triacetin in 533 g of purified water and mixed for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1,050 g of the coating solution to 600 g of Hydrocodone Resin Complex using Wurster process that resulted in 35% weight gain. The coating conditions were

controlled at an inlet temperature of about 55-66 °C, product temperature of 26-32 °C, air flow of 16-20 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-5 g/min so that uniform coating was achieved. The Coated Hydrocodone Resin Complex was then placed at 60 °C for 5 hours for curing.

5

Example 11

Preparation of Coated Venlafaxine Resin Complex

Ingredient	Quantity
Venlafaxine Resin Complex	
Venlafaxine HCl	500 g
Purified Water	5 L
AMBERLITE IRP-69 resin	1,000 g
EUDRAGIT NE-30D polymer system	467 g
Coated Venlafaxine Resin Complex	
KOLLICOAT SR-30D polymer system	635 g
Triacetin	9.5 g
Purified Water	356 g
Venlafaxine Resin Complex	600 g

10

The Venlafaxine Resin Complex was prepared by first dissolving 500 g of venlafaxine HCl in 5 L of purified water, and then slowly adding 1,000 g of AMBERLITETM IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWRTM convection oven maintained at 50 °C until moisture content was about 25%. EUDRAGITTM NE-30D polymer of 467 g was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was dried in a 50 °C VWRTM convection oven to the moisture content around 4-6%. The dried granules were then milled through a 40 mesh screen using CO-MILTM brand mill.

15

20

The coating solution was prepared by dispersing 635 g of KOLLICOATTM SR-30D polymer system, 9.5 g of triacetin in 356 g of purified water and mixing for 1 hour. The coating process was performed in a VECTORTM FLM-1 fluid bed

processor by applying 900 g of the coating solution to 600 g of Venlafaxine Resin Complex using Wurster process that resulted in 30% weight gain. The coating conditions were controlled at an inlet temperature of 40-45 °C, product temperature of 29-33°C, air flow of 40 cfm and nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-7 g/min so that uniform coating was achieved. The Coated Venlafaxine Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 12

Preparation of Coated Oxybutynin Resin Complex

Ingredient	Quantity
Oxybutynin Resin Complex	
Oxybutynin Hydrochloride	300 g
Purified Water	8 L
AMBERLITE IRP-69 Resin (anhydrous)	1586 g
KOLLICOAT SR-30D polymer system	540 g
Coated Oxybutynin Resin Complex	
KOLLICOAT SR-30D polymer system	761.9 g
Triacetin	11.4 g
Purified Water	426.7 g
Oxybutynin Resin Complex	600 g

The Oxybutynin Resin Complex was prepared by first dissolving 300 g of oxybutynin hydrochloride in 8L of purified water, and then slowly adding 1586 g of AMBERLITE™ IRP-69 resin with continuous mixing. The pH was adjusted to 3.9. The dispersion was mixed for 4 hours, and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convention oven maintained at 50 °C until moisture content was about 25%. KOLLICOAT™ SR-30D polymer system (540 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried in a 50 °C VWR™ convention oven to the moisture content about 25%. The semi-dried granules were then milled through a 40 mesh screen

using CO-MIL™ and continued drying at 50 °C until the moisture content was between 3-7%. The dried granules were then milled through a 40 mesh screen using CO-MIL™.

The coating solution was prepared by dispersing 761.9 g of KOLLICOAT™ SR-30D polymer, 11.4 g triacetin in 426.7 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1050 g of the coating solution to 600 g of Oxybutynin Resin Complex using Wurster process, resulting in a 35% weight gain. The coating conditions were controlled at an inlet temperature of about 58-72 °C, product temperature of 26-32 °C, air flow of 16-20 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and a spray rate of 4-6 g/min, so that a uniform coating was achieved. The Coated Oxybutynin Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 13

Preparation of Coated Metformin Resin Complex

Ingredient	Quantity
Metformin Resin Complex	
Metformin HCl	225 g
Purified Water	4 L
AMBERLITE IRP-69 Resin (anhydrous)	735 g
KOLLICOAT SR-30D polymer system	250 g
Purified Water	150 g
Ingredient	Quantity
Coated Metformin Resin Complex	
KOLLICOAT SR-30D polymer system	761.9 g
Triacetin	11.4 g
Purified Water	426.7 g
Metformin Resin Complex	600 g

The Metformin Resin Complex was prepared by first dissolving 225 g of metformin HCl in 4L of purified water, and then slowly adding 735g of AMBERLITE™ IRP-69 resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The

slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until moisture content was about 25%. KOLLICOAT™ SR-30D (250 g) was first mixed with 150 g of purified water and the mixture was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried in a 50 °C VWR™ convection oven to the moisture content about 20%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and drying continued at 50 °C until the moisture content was between 3-7%. The dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill.

The coating solution was prepared by dispersing 761.9 g of KOLLICOAT™ SR-30D polymer, 11.4 g triacetin in 426.7 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by applying 1050 g of the coating solution to 600 g of Metformin Resin Complex using WURSTER process, resulting in a 35% weight gain. The coating conditions were controlled at an inlet temperature of about 68-72 °C, product temperature of 28-38 °C, air flow of 16-24 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and a spray rate of 5-7 g/min, so that a uniform coating was achieved. The Coated Metformin Resin Complex was then placed at 60 °C for 5 hours for curing.

Example 14

Preparation of Coated Ibuprofen Resin Complex

Ingredient	Quantity
Ibuprofen Resin Complex	
Ibuprofen	400 g
Purified Water	8 L
PUROLITE A430MR Resin	800 g
KOLLICOAT SR-30D polymer system	250 g

Ingredient	Quantity
Coated Ibuprofen Resin Complex	
KOLLICOAT SR-30D polymer system	761.9 g
Triacetin	11.4 g
Purified Water	426.7 g
Ibuprofen Resin Complex	600 g

The Ibuprofen Resin Complex was prepared by first dissolving 400 g of Ibuprofen in 8L of purified water (adjusted to pH > 8 with 10N NaOH), and then
5 slowly adding 800 g of PUROLITE™ A430MR resin with continuous mixing. The dispersion was mixed for 4 hours and upon completion, allowed to settle before decanting the supernatant. The slurring/decanting process was repeated twice with sufficient amounts of purified water. The wet resin complex was then dried in a VWR™ convection oven maintained at 50 °C until the moisture content was about
10 25%. KOLLICOAT™ SR-30D (250 g) was then slowly added to the wet resin complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass. The wet mass was again dried in a 50 °C VWR™ convection oven to the moisture content of about 20%. The semi-dried granules were then milled through a 40 mesh screen using CO-MIL™ brand mill and drying was continued at 50 °C until the moisture content was
15 between 4-6%. The dried granules were again milled through a 40 mesh screen using CO-MIL™.

The coating solution was prepared by dispersing 761.9 g of KOLLICOAT™ SR-30D polymer, 11.4 g triacetin in 426.7 g of purified water and mixing for 1 hour. The coating process was performed in a VECTOR™ FLM-1 fluid bed processor by
20 applying 1050 g of the coating solution to 600 g of Ibuprofen Resin Complex using Wurster process, resulting in a 35% weight gain. The coating conditions were controlled at an inlet temperature of about 55-70 °C, product temperature of 28-33 °C, air flow of 16-21 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and a spray rate of 4-7 g/min, so that a uniform coating was
25 achieved. The Coated Ibuprofen Resin Complex was then placed at 60 °C for 5 hours for curing.

Preparation of Suspension**Example 15****Preparation of Albuterol Suspension**

Ingredient	Quantity
Placebo Suspension Base	
Purified Water	500 g
Citric Acid, anhydrous	4 g
FD&C Yellow #6	0.032 g
FD&C Red #40	0.072 g
High Fructose Corn Syrup 42	600 g
Methylparaben	3.6 g
Propylparaben	0.4 g
Glycerin	200 g
Sucrose	300 g
Starch	50.13 g
Xanthan Gum	4.35 g
Strawberry/Banana flavor	22.44 g
QS Purified Water	1,742.45 g
Albuterol ER Suspension	
Purified Water	100 g
Polysorbate 80	0.55 g
Coated Albuterol Resin Complex (from Example 3)	5.54 g
Placebo Suspension Base	435.6 g
Purified Water	QS 500 mL

Placebo Suspension Base was prepared by first dissolving 4 g of citric acid in 500 g of purified water in the main container, followed by adding 600 g of high fructose corn syrup and 300 g of sucrose to achieve complete solution. In a separate container, 0.032 g of FD&C Yellow #6 and 0.072 g of FD&C Red #40 were dissolved in sufficient amount of purified water and then transferred to the main container. The starch (50.13 g) was then slowly introduced to the main container under high speed/shear mixing condition to achieve uniform dispersion. In another container, 200 g of glycerin was added and heated to 45-50 °C before additions of 3.6 g of methylparaben and 0.4 g of propylparaben. After both parabens were dissolved, the solution was then cooled to room temperature and 4.35 g of xanthan gum was

slowly introduced to the solution to form a uniform dispersion. The gum dispersion was then transferred to the main container under high speed/shear mixing condition to achieve uniform suspension. The 22.44 g of strawberry/banana flavor was added and the Placebo Suspension Base was achieved by adjusting to final weight of 1,742.45 g with purified water and mixed until uniform. To prepare the final suspension, 0.55 g of polysorbate 80 was dissolved in 100 g of purified water followed by addition of 435.6 g of Placebo Suspension Base. The Coated Albuterol Resin Complex prepared as described in Example 3 (5.54 g) was then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 500 mL with appropriate amount of purified water and mixed until uniform.

Example 16
Preparation Morphine Suspension

Ingredient	Quantity
Placebo Suspension Base	
Tartaric Acid	8 g
FD&C Red #40	0.144 g
Cherry Flavor	2.06 g
High Fructose Corn Syrup 42	1,200 g
Methylparaben	7.2 g
Propylparaben	0.8 g
Glycerin	400 g
Sucrose	600 g
AVICEL RC-591 microcrystalline cellulose	48 g
Xanthan Gum	7.68 g
Purified Water	QS 3,484.91 g
Ingredient	Quantity
Morphine ER Suspension	
Purified Water	20 g
Sodium Metabisulfite	0.1 g
Polysorbate 80 surfactant	0.11 g
Coated Morphine Resin Complex (from Example 1)	3.2 g
Placebo Suspension Base	87.12 g
Purified Water	QS 100 mL

Placebo Suspension Base was prepared by first dissolving 8 g of tartaric acid in appropriate amount of purified water in the main container, followed by adding 1,200 g of high fructose corn syrup and 600 g of sucrose to achieve a complete solution. In a separate container, 0.144 g of FD&C Red #40 was dissolved in a sufficient amount of purified water and then transferred to the main container. The AVICEL RC-591 microcrystalline cellulose (48 g) was then slowly introduced to the main container under high shear mixing condition to achieve uniform dispersion. In another container, 400 g of glycerin was added and heated to 45-50 °C before additions of 7.2 g of methylparaben and 0.8 g of propylparaben. After both parabens were dissolved, the solution was then cooled to room temperature and 7.68 g of xanthan gum was slowly introduced to the solution to form a uniform dispersion. The gum dispersion was then transferred to the main container under high speed/shear mixing condition to achieve uniform suspension. The 2.06 g of cherry flavor was added and the Placebo Suspension Base was achieved by adjusting to final weight of 3,484.91 g with purified water and mixed until uniform. To prepare the final suspension, 0.1 g of sodium metabisulfite and 0.11 g of Polysorbate 80 surfactant were dissolved in 20 g of purified water followed by addition of 87.12 g of Placebo Suspension base. The Coated Morphine Resin Complex prepared according to Example 1 of 3.2 g was then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 100 mL with appropriate amount of purified water and mixed until uniform.

Example 17

Preparation Oxycodone Suspension

Ingredient	Quantity
Placebo Suspension Base	
Tartaric Acid	8 g
FD&C Red #40	0.144 g
Strawberry Flavor	2.06 g
High Fructose Corn Syrup 42	1,200 g
Methylparaben	7.2 g
Propylparaben	0.8 g
Glycerin	400 g

Ingredient	Quantity
Placebo Suspension Base (cont'd)	
Sucrose	600 g
Avicel RC-591 microcrystalline cellulose	48 g
Xanthan Gum	7.68 g
Purified Water	QS 3,484.91 g
Oxycodone ER Suspension	
Purified Water	100 g
Sodium Metabisulfite	0.5 g
Polysorbate 80 surfactant	0.55 g
Coated Oxycodone Resin Complex (from Example 2)	5.66 g
Placebo Suspension Base	435.6 g
Purified Water	QS 500 mL

Placebo Suspension Base was prepared by first dissolving 8 g of tartaric acid in appropriate amount of purified water in the main container, followed by adding 1,200 g of high fructose corn syrup and 600 g of sucrose to achieve complete solution.

- 5 In a separate container, 0.144 g of FD&C Red #40 was dissolved in sufficient amount of purified water and then transferred to the main container. The AVICEL RC-591 microcrystalline cellulose (48 g) was then slowly introduced to the main container under high shear mixing condition to achieve uniform dispersion. In another container, 400 g of glycerin was added and heated to 45-50 °C before additions of 7.2
- 10 g of methylparaben and 0.8 g of propylparaben. After both parabens were dissolved, the solution was then cooled to room temperature and 7.68 g of xanthan gum was slowly introduced to the solution to form a uniform dispersion. The gum dispersion was then transferred to the main container under high speed/shear mixing condition to achieve uniform suspension. The 2.06 g of strawberry flavor was added and the
- 15 Placebo Suspension Base was achieved by adjusting to final weight of 3484.91 g with purified water and mixed until uniform. To prepare the final suspension, 0.5 g of sodium metabisulfite and 0.55 g of polysorbate 80 surfactant were dissolved in 100 g of purified water followed by addition of 435.6 g of Placebo Suspension Base. The Coated Oxycodone Resin Complex prepared according to Example 2 (5.66 g) was
- 20 then slowly introduced to the above dispersion under gentle mixing condition. The

final suspension was obtained by adjusting the volume to 500 mL with appropriate amount of purified water and mixed until uniform.

Example 18

Orally Disintegrating Tablet Formulation

Preparation of Coated Dextromethorphan Resin Complex

Ingredient	Quantity
Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	954 g
Purified Water	8 L
AMBERLITE IRP-69 resin (anhydrous)	1,758 g
KOLLIDON K-30 brand PVP	116 g
Purified Water	1,151 g
Coated Dextromethorphan Resin Complex	
KOLLICOAT SR-30D polymer system	635 g
Triacetin	9.5 g
Purified Water	356 g
Dextromethorphan Resin Complex	600 g

The Dextromethorphan Resin Complex was prepared by first dissolving 954 g of dextromethorphan HBr in 8 L of purified water heated to 75-80 °C, followed by the addition of 1,758 g of AMBERLITE™ IRP-69 resin under gentle mixing for 4 hours. At the completion, the suspension was allowed to settle, decanted and rinsed with purified water twice and dried in an oven maintained at 50°C until moisture was around 5%. The PVP solution was prepared by dissolving 116 g of KOLLIDON K-30 brand PVP in 1,151 g of purified water and the solution was slowly added to the Dextromethorphan Resin Complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass and dried at 50°C until moisture is between 3-7%. The dried granules were then milled through a 40 mesh screen using Co-Mil™ brand mill.

The coating solution was prepared by first gently mixing 635 g of KOLLICOAT™ SR-30D polymer system, 9.5 g of triacetin and 356 g of purified water for 1 hour. The coating process was performed in VECTOR™ FLM-1 fluid bed processor by applying 900 g of the coating solution to 600 g of

Dextromethorphan Resin Complex using Wurster process that resulted in 30% weight gain. The coating conditions were controlled at an inlet temperature of 62-76 °C, product temperature of 28-35 °C, air flow of 16-20 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Dextromethorphan Resin Complex was then placed at 60 °C for 5 hours for curing.

Preparation of Uncoated Dextromethorphan Resin Complex

An Uncoated Dextromethorphan Resin Complex was prepared as follows.

Ingredient	Quantity
Uncoated Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	119.28 g
Purified Water	1 L
AMBERLITE IRP-69 RESIN (anhydrous)	223.01 g

Uncoated Dextromethorphan Resin Complex was prepared by first dissolving 119.28 g of dextromethorphan HBr in 1 L of purified water heated to 75-80 °C, followed by the addition of 223.01 g AMBERLITE IRP-69 resin under gentle mixing for 4 hours. At the completion, the suspension was allowed to settle, and was then decanted and rinsed with purified water twice and dried in an oven maintained at 50 °C until the moisture content is around 5%. The dried resin complex was hand sieved through 40 mesh screen.

Tablet Preparation

The Coated Dextromethorphan Resin and Uncoated Dextromethorphan Resin of this example were utilized in tablet preparation as follows.

Ingredient	Quantity per tablet	Quantity
Uncoated Dextromethorphan Resin	23.78 mg	4.76 g
Coated Dextromethorphan Resin	72.70 mg	14.54 g
Calcium Silicate	49 mg	9.8 g
Zeopharm	3.5 mg	0.7 g
Silicon Dioxide	5.0 mg	1.0 g
Microcrystalline Cellulose	24 mg	4.8 g
Acesulfame K sugar substitute	2 mg	0.4 g
Aspartame	5 mg	1.0 g
Peppermint	2.5 mg	0.5 g
Crospovidone	15 mg	3.0 g
Mannitol	124 mg	24.8 g
Mg Stearate	5 mg	1.0 g
Total	331.48 mg	66.30 g

A small batch of tablets were prepared by first adding quantities of the Uncoated and Coated Dextromethorphan Resin, calcium silicate, zeopharm, silicon dioxide, microcrystalline cellulose, crospovidone, Acesulfame-K sugar substitute, Aspartame and mannitol in the amounts as specified in the above formulation to a blender and mixing for 10 minutes. Magnesium stearate (1.0 g) was added to the powder blend and mixed for an additional 3 minutes. The final blend was discharged into a RIMEKTM tablet press equipped with 3/8" standard concave tooling and tablets of moderate hardness (3-6 Kp tested by VANDERKAMPTM tablet hardness tester) were compressed.

Dissolution release rate of the oral disintegrating dextromethorphan extended release tablets of the invention was conducted in 900 mL 0.4M KH₂PO₄ at paddle, 50 rpm and the results of the tablets showed comparable results to the ER suspension.

Example 19

Color Migration of Water Soluble Dyes in Finished Formulations Having Drug-Ion Exchange Resin Complexes Coated with EUDRAGIT Brand Polymer

Coating – Comparative Example

Dextromethorphan suspension prepared with uncoated and EUDRAGIT coated Dextromethorphan Resin Complex was observed to have color migration; this

color migration was more pronounced at 40 °C/ 75% RH as compared to 25 °C / 60% RH.

Preparation of Uncoated and Coated Dextromethorphan Resin Complex

5

Ingredient	Quantity
Uncoated Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	119.28 g
Purified Water	1 L
AMBERLITE IRP-69 RESIN (anhydrous)	223.01 g

10

Uncoated Dextromethorphan Resin Complex was prepared by first dissolving 119.28 g of dextromethorphan HBr in 1 L of purified water heated to 75-80°C, followed by the addition of 223.01 g AMBERLITE IRP-69 resin under gentle mixing for 4 hours. At the completion, the suspension was allowed to settle, and was then decanted and rinsed with purified water twice and dried in an oven maintained at 50°C until the moisture content was around 5%. The dried resin complex was hand sieved through a 40 mesh screen.

Ingredient	Quantity
Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	954.2 g
Purified Water	8 L
AMBERLITE IRP-69 RESIN (anhydrous)	1784.0 g
KOLLIDON K-30 polyvinyl pyrrolidone	116 g
Purified Water	528.4 g
Coated Dextromethorphan Resin Complex	
Eudragit RS-30D polymer system	334.89 g
Triethyl Citrate	20.25 g
Talc	50.19 g
Polysorbate 80 surfactant	0.29 g
Purified Water	292.2 g
Dextromethorphan Resin Complex	600 g

15

The Dextromethorphan Resin Complex was prepared by first dissolving 954.2 g of dextromethorphan HBr in 8 L of purified water heated to 75-80 °C, followed by the addition of 1784 g of AMBERLITE IRP-69 resin under gentle mixing for 4 hours.

At the completion, the suspension was allowed to settle, decanted and rinsed with purified water twice and dried in an oven maintained at 50 °C until moisture was around 5%. The PVP solution prepared by dissolving 116 g of KOLLIDON K-30 in 528.4 g of purified water was slowly added to the Dextromethorphan Resin Complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass and dried at 50 °C until moisture was between 3-7%. The dried granules were then milled through a 40 mesh screen using Co-Mil.

Coating solution was prepared by gently mixing 334.89 g of Eudragit RS-30D polymer system, 0.29g of polysorbate 80 surfactant, 20.25 g of triethyl citrate and 292.2 g of purified water for 45 minutes, followed by addition of 50.19 g of talc and continued mixing for 1 hour. The coating process was performed in Glatt GPCG-1 fluid bed processor by applying 698 g of the coating solution to 600 g of Dextromethorphan Resin Complex using WURSTER Process that resulted in 28.5% weight gain. The coated Dextromethorphan Resin Complex was placed at 60 °C for 5-hour curing.

Preparation Dextromethorphan Suspension

Ingredient	Quantity
Placebo Suspension Base	
Citric Acid	6 g
FD&C Yellow #6	0.03278 g
Orange Flavor	2.01 g
High Fructose Corn Syrup 42	600 g
Methylparaben	3.6 g
Propylparaben	0.6 g
Propylene Glycol	100 g
Sucrose	300 g
Tragacanth Gum	10.51 g
Xanthan Gum	3.59 g
Purified Water	1,015 g

Dextromethorphan Suspension	
Purified Water	10 g
Polysorbate 80 surfactant	0.22 g
Uncoated Dextromethorphan Resin Complex	2.68 g
Coated Dextromethorphan Resin Complex	1.00 g
Placebo Suspension Base	203.15 g
Purified Water	QS 200 mL

Placebo Suspension Base was prepared by first dissolving 6 g of citric acid in an appropriate amount of purified water from the total 1,015 g in the main container, followed by adding 300 g of sucrose and 600 g of high fructose corn syrup to achieve complete solution. In a separate container, 0.03278 g of FD&C Yellow #6 was dissolved in sufficient amount of purified water and then transferred to the main container. In another container, 100 g of propylene glycol was added and heated to 45-50 °C before additions of 3.6 g of methylparaben and 0.6 g of propylparaben.

After both parabens were dissolved, the solution was then cooled to room temperature and 10.51 g of tragacanth gum and 3.59 g of xanthan gum were slowly introduced to the solution to form a uniform dispersion. The gum dispersion was then transferred to the main container under high speed/shear mixing condition to achieve uniform suspension. The 2.01 g of orange flavor was added and the Placebo Suspension Base was achieved by addition of the remaining purified water and mixed until uniform. To prepare the final suspension, 0.22 g of Polysorbate 80 surfactant were dissolved in 10 g of purified water followed by addition of 203.15 g of Placebo Suspension Base. The Uncoated Dextromethorphan Resin complex of 2.68 g and Coated Dextromethorphan Resin Complex of 1 g were then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 200 mL with appropriate amount of purified water and mixed until uniform.

When a drug-ion-exchange resin complexes prepared according to the invention and coated methacrylic acid copolymers such as a EUDRAGIT brand polymer coat, was mixed with a dye in the liquid suspension, the dye tended to migrate onto the surface of the polymer and resulted in non-uniform color distribution

in the liquid. The use of a EUDRAGIT brand polymer in the finished liquid suspension containing water soluble dyes creates issues of non-uniform color distribution due to the color migration. Furthermore, the nature of the EUDRAGIT brand polymer, the polymer also caused flocculation of the resin resulting in flaky agglomerates in the liquid suspension.

Example 20

Ethylcellulose-Coated Drug - Ion Exchange Resin in a Liquid Suspension Formulation – Comparative Example

Dextromethorphan suspension prepared with uncoated and AQUACOAT™ coated dextromethorphan resin complex was observed to have loose and chunky flakes in the suspension. This was more pronounced at 40 °C/ 75% RH than at 25 °C/ 60% RH.

Preparation of Coated Dextromethorphan Resin Complex

Ingredient	Quantity
Coated Dextromethorphan Resin Complex	
AQUACOAT ECD-30 polymer system	460.08 g
Dibutyl Sebacate	33.56 g
Purified Water	115.97 g
Dextromethorphan Resin Complex (from Example 18)	600 g

Coating solution was prepared by first gently mixing 460.08 g of AQUACOAT ECD-30 and 33.56 g of dibutyl sebacate for 45 minutes, followed by addition of 115.97 g of purified water and continued mixing for 30 minutes. The coating process was performed in Glatt GPCG-1 fluid bed processor by applying 615 g of the coating solution to 600 g of Dextromethorphan Resin Complex using WURSTER process that resulted in 28.9% weight gain. The coated Dextromethorphan Resin Complex was placed at 60 °C for 5-hour curing.

Preparation of Dextromethorphan Suspension

Ingredient	Quantity
Dextromethorphan ER Suspension	
Purified Water	10 g
Polysorbate 80 surfactant	0.22 g
Uncoated Dextromethorphan Resin Complex (from Example 18)	1.50 g
Coated Dextromethorphan Resin Complex	2.68 g
Placebo Suspension Base (from Example 18)	203.14 g
Purified Water	QS 200 mL

To prepare the final suspension, 0.22 g of Polysorbate 80 were dissolved in 10 g of purified water followed by addition of 203.14 g of Placebo Suspension Base. The Uncoated Dextromethorphan Resin complex of 1.50 g and Coated Dextromethorphan Resin Complex of 2.68 g were then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 200 mL with appropriate amount of purified water and mixed until uniform.

When the ethylcellulose-coated particles were made into a liquid suspension, the coated particles showed as flaky, swollen and chunky, an indication of loose adhesion of the ethylcellulose coating to the particle surface. These ethylcellulose-coated particles exhibited in little or no significant reductions in the release rate of the drug.

Abuse Resistant Characteristics of Products of Invention

Example 21 - Preparation of Uncoated and Coated Dextromethorphan Resin Complex

Ingredient	Quantity
Uncoated Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	95.42 g
Purified Water	0.8 L
AMBERLITE IRP-69 resin (anhydrous)	175.82 g

The Uncoated Dextromethorphan Resin Complex was prepared by first dissolving 95.42 g of dextromethorphan HBr in 0.8 L of purified water heated to 75-80 °C, followed by the addition of 175.82 g AMBERLITE IRP-69 resin (anhydrous) under gentle mixing for 4 hours. At the completion, the suspension was allowed to settle, decanted and rinsed with purified water twice and dried in an oven maintained at 50 °C until moisture is around 5%. The dried resin complex was hand sieved through a 40 mesh screen.

Ingredient	Quantity
Dextromethorphan Resin Complex	
Dextromethorphan HBr USP	954 g
Purified Water	8 L
AMBERLITE IRP-69 resin (anhydrous)	1,758 g
KOLLIDON K-30 polyvinylpyrrolidone	116 g
Purified Water	1,151 g
Coated Dextromethorphan Resin Complex	
KOLLICOAT SR-30D polymer system	761 g
Triacetin	11.4 g
Purified Water	427 g
Dextromethorphan Resin Complex	1,200 g

The Dextromethorphan Resin Complex was prepared by first dissolving 954 g of dextromethorphan HBr in 8 L of purified water heated to 75-80 °C, followed by the addition of 1,758 g of AMBERLITE IRP-69 resin under gentle mixing for 4 hours. At the completion, the suspension was allowed to settle, decanted and rinsed with purified water twice and dried in an oven maintained at 50 °C until moisture is around 5%. The polyvinyl pyrrolidone (PVP) solution was prepared by dissolving 116 g of KOLLIDON K-30 PVP in 1,151 g of purified water and the solution was slowly added to the Dextromethorphan Resin Complex in a Hobart type mixer (Kitchen Aid) to form a uniform mass and dried at 50 °C until moisture is between 3-7%. The dried granules were then milled through a 40 mesh screen using CO-MIL brand mill.

Coating solution was prepared by first gently mixing 761 g of KOLLICOAT SR-30D polymer system, 11.4 g of triacetin and 427 g of purified water for 1 hour. The coating process was performed in VECTOR™ FLM-1 fluid bed processor by

applying 1050 g of the coating solution to 600 g of Dextromethorphan Resin Complex using Wurster process that resulted in 35% weight gain. The coating conditions were controlled at an inlet temperature of 59-75 °C, product temperature of 27-35 °C, air flow of 15-20 cfm, nozzle pressure of 2.5 kg/cm², accelerator air pressure of 1.0 kg/cm² and spray rate of 4-6 g/min so that uniform coating was achieved. The Coated Dextromethorphan Resin Complex was then placed at 60 °C for 5 hours for curing.

Preparation Dextromethorphan ER Suspension

Ingredient	Quantity
Dextromethorphan ER Suspension	
Purified Water	20 g
Polysorbate 80	0.11 g
Uncoated Dextromethorphan Resin Complex	0.476 g
Coated Dextromethorphan Resin Complex	1.596 g
Sodium Metabisulfite	0.1 g
Placebo Suspension Base (from Example 18)	87.12 g
Purified Water	QS 100 mL

To prepare the Dextromethorphan ER Suspension, the resin blend was prepared by mixing 0.476 g of uncoated dextromethorphan resin and 1.596 g of coated dextromethorphan resin. The blend was subsequently passed through CO-MIL™ brand mill equipped with 40 mesh screen. Dextromethorphan Suspension was prepared by dissolving 0.11 g of Polysorbate 80 surfactant and 0.1 g of sodium metabisulfite in 20 g of purified water followed by addition of 87.12 g of placebo suspension base. The resin blend of uncoated and coated Dextromethorphan Resin Complex was then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 100 mL with appropriate amount of purified water and mixed until uniform.

Another suspension was prepared with the same ingredients and procedures with the exception that the resin blend was not milled through CO-MIL™ brand mill.

Dissolution of both suspensions in 500 mL 0.1N HCl for 1 hour followed by 900 mL of pH 6.8 buffer until 24 hours under paddle, 50 rpm were compared and

results indicated no statistically significant differences. The strong external milling forces applied to the uncoated and coated resin complex did not change the dissolution behavior of its suspension when compared to the suspension prepared with un-milled resin blend, indicating that the flexible film is not disrupted.

5

The drug resin complex coated with polymer film showed enhanced resistance to abuse potential. The coated particles subjected to grinding mechanical forces as described above did not change its dissolution behaviors indicating that the combined complexation and highly flexible film make it extremely difficult to remove the drug from the coated particles with ordinary mechanical means.

10

Example 22

Preparation of Pseudoephedrine Suspension

15

Ingredient	Quantity
Placebo Suspension Base	
Citric Acid	8 g
FD&C Yellow #6	0.064 g
FD&C Red #40	0.144 g
Strawberry/Banana Flavor	44.88 g
High Fructose Corn Syrup 42	1,200 g
Methylparaben	7.2 g
Propylparaben	0.8 g
Glycerin	400 g
Sucrose	600 g
Starch	100.26 g
Xanthan Gum	8.7 g
Purified Water	QS 3484.91 g
Pseudoephedrine ER Suspension	
Purified Water	20 g
Polysorbate 80 surfactant	0.11 g
Coated Pseudoephedrine Resin Complex (from Example 8)	3.11 g
Placebo Suspension Base	87.12 g
Purified Water	QS 100 mL

Placebo Suspension Base was prepared by first dissolving 8 g of citric acid in an appropriate amount of purified water, followed by adding 600 g of sucrose and

1200 g of high fructose corn syrup to achieve complete solution. In a separate container, 0.064 g of FD&C Yellow #6 and 0.144 g of FD&C Red #40 were dissolved in a sufficient amount of purified water and then transferred to the main container. The starch (100.26 g) was then slowly introduced to the main container under high shear mixing condition to achieve uniform dispersion. In another container, 400 g of glycerin was added and heated to 45-50 °C before additions of 7.2 g of methylparaben and 0.8 g of propylparaben. After both parabens were dissolved, the solution was then cooled to room temperature and 8.7 g of xanthan gum were slowly introduced to the solution to form a uniform dispersion. The gum dispersion was then transferred to the main container under high speed/shear mixing condition to achieve uniform suspension. The 44.88 g of strawberry/banana flavor was added and the Placebo Suspension Base was achieved by addition of the remaining purified water and mixed until uniform.

To prepare the Pseudoephedrine ER Suspension, the Coated Pseudoephedrine Resin Complex of 3.11 g was passed through CO-MIL™ equipped with a 40 mesh screen. Pseudoephedrine Suspension was prepared by dissolving 0.11 g of Polysorbate 80 surfactant in 20 g of purified water followed by addition of 87.12 g of Placebo Suspension base. The Coated Pseudoephedrine Resin Complex was then slowly introduced to the above dispersion under gentle mixing condition. The final suspension was obtained by adjusting the volume to 100 mL with appropriate amount of purified water and mixed until uniform.

Another suspension was prepared with the same ingredients and procedures with the exception that the Coated Pseudoephedrine Resin Complex was not milled through CO-MIL™.

Dissolution of both suspensions in 500 mL 0.1N HCl for 1 hour followed by 900 mL of pH 6.8 buffer until 24 hours under paddle, 50 rpm were compared and results indicated no significant differences. The strong external milling forces applied to the milled coated resin complex did not change the dissolution behavior of its suspension when compared to the suspension prepared with un-milled coated resin.

All patents, patent publications, and other publications listed in this specification are incorporated herein by reference. While the invention has been described with reference to a particularly preferred embodiment, it will be appreciated that modifications can be made without departing from the spirit of the invention.

5 Such modifications are intended to fall within the scope of the appended claims.

CLAIMS:

1. A formulation having modified release characteristics comprising pharmaceutically acceptable excipients and at least one coated drug - ion exchange resin complex comprising a pharmaceutically active drug bound to a pharmaceutically acceptable ion exchange resin and having a high tensile strength water-permeable, water-insoluble, non-ionic polymeric barrier coating,
wherein when the formulation is an orally disintegrating tablet, the coated drug-ion exchange resin complex further comprises a release retardant in a matrix with the drug-ion exchange resin complex.
2. The formulation according to claim 1, wherein said barrier coating is characterized by being substantially tack-free when applied to the complex in the absence of an anti-tacking agent.
3. The formulation according to claim 1 or claim 2, wherein the coated drug-ion exchange resin complex further comprises a release retardant in a matrix with the drug-ion exchange resin complex.
4. The formulation according to any of claims 1 to 3, wherein said release retardant is selected from the group consisting of a polyvinyl acetate polymer, a cellulose acetate, an ethylcellulose polymers, and cellulose phthalate.
5. The formulation according to any of claims 1 to 4, wherein the barrier coating has a tackiness of about 2 or less when measured by the Hössel method at 20 °C/80% relative humidity and 30 °C/75% relative humidity.
6. The formulation according to claim 5, wherein the barrier coating has a tackiness of about 0.5 or less.

7. The formulation according to any of claims 1 to 6, wherein the barrier coating has an elongation factor of at least about 100%.
8. The formulation according to claim 7, wherein the barrier coating has an elongation factor in the range of about 150% to 400%.
9. The formulation according to any one of claims 1 to 8, wherein the barrier coating comprises 5% to 200% by weight of the uncoated complex.
10. The formulation according to claim 9, wherein the barrier coating comprises 25 % to 50% by weight of the uncoated complex.
11. The formulation according to claim 9 or claim 10, wherein the barrier coating comprises 30% to 45% by weight of the uncoated complex.
12. The formulation according to any one of claims 1 to 11, wherein the barrier coating is a cured coat.
13. The formulation according to any one of claims 1 to 12, wherein the complex further comprises a hydrophilic impregnating agent.
14. The formulation according to any one of claims 1 to 13, wherein the barrier coating comprises polyvinyl acetate polymer.
15. The formulation according to claim 14, wherein the polyvinyl acetate polymer comprises about 70 % to about 95% w/w of the coating layer.
16. The formulation according to any one of claims 1 to 15, wherein the barrier coating comprises a polyvinyl acetate polymer, a stabilizer, a surfactant and a plasticizer.

17. The formulation according to claim 16, wherein the stabilizer is a polyvinylpyrrolidone and the surfactant is sodium lauryl sulfate.
18. The formulation according to claim 17, wherein the polyvinyl pyrrolidone comprises about 5 to about 10% w/w of the coating.
19. The formulation according to any one of claims 16 to 18, wherein the plasticizer comprises about 2.5 to about 25% w/w of solids in the coating.
20. The formulation according to any one of claims 16 to 19, wherein the plasticizer is selected from the group consisting of dibutyl sebacate, propylene glycol, polyethylene glycol, polyvinyl alcohol, triethyl citrate, acetyl triethyl citrate, acetyl tributyl citrate, tributyl citrate, triacetin, Soluphor P, and mixtures thereof.
21. The formulation according to any one of claims 1 to 20, wherein the formulation comprises two or more pharmaceutically active drugs.
22. The formulation according to claim 21, wherein the formulation comprises the at least one coated drug-ion exchange resin complex comprising a first pharmaceutically active drug and a second drug-ion exchange resin complex comprising a second pharmaceutically active drug.
23. The formulation according to any one of claims 1 to 22, wherein the formulation further comprises a mixture of uncoated drug resin complex comprising a pharmaceutically active drug bound to an ion exchange resin.
24. The formulation according to claim 23, wherein the pharmaceutically active drug is dextromethorphan.

25. The formulation according to claim 23 or claim 24, wherein the uncoated drug resin complex and the coated drug resin complex are present in a ratio of 30:70 by weight.

26. The formulation according to any one of claims 1 to 25 which is a liquid suspension which comprises a pharmaceutically acceptable suspension base.

27. The formulation according to any one of claims 1 to 25 which is a solid formulation.

28. The formulation according to claim 27, wherein the solid formulation is an orally disintegrating tablet.

29. The formulation according to any one of claims 1 to 23, 25 - 28, wherein the drug is selected from the group consisting of morphine, oxycodone, albuterol, methylphenidate, dextromethorphan, codeine, tramadol, pseudoephedrine, phenylephrine, hydrocodone, venlafaxine, ibuprofen, oxybutynin, metformin, clonidine, dexchlorpheniramine, fexofenadine, diphenhydramine, phenylpropranolamine, chlorpheniramine, amphetamine, naproxene, diclofenac, selegiline, paroxetine, amoxicillin and pharmaceutically acceptable salts thereof.

30. The formulation according to any one of claims 1 to 29, wherein the pharmaceutically active drug in the at least one coated drug-ion exchange resin complex is morphine.

31. The formulation according to claim 30, wherein the morphine is morphine sulfate.

32. A coated drug - ion exchange resin complex useful in preparing modified release formulations, said complex comprising a pharmaceutically active drug bound to a pharmaceutically acceptable ion exchange resin and having a cured high tensile strength water-permeable, water-insoluble, non-ionic polymeric barrier coating.

33. The coated drug - ion exchange resin complex according to claim 32, further comprising a hydrophilic impregnating agent.

34. The coated drug - ion exchange resin complex according to claim 32, further comprising water insoluble release retardant.

35. A coated drug - ion exchange resin matrix complex useful in preparing modified release formulations, said complex comprising a pharmaceutically active drug bound to a pharmaceutically acceptable ion exchange resin and a cured high tensile strength water-permeable, water-insoluble, non-ionic polymeric barrier coating, and having a water-insoluble release retardant in a matrix with the drug-ion exchange resin complex.

36. The coated drug - ion exchange resin complex according to claim 34 or matrix according to claim 35, wherein the release retardant comprises an acrylic polymer.

37. The coated drug - ion exchange resin complex or matrix according to claim 36, wherein the release retardant is selected from the group consisting of a polyvinyl acetate polymer, ethyl cellulose, cellulose acetate, acrylic based polymers or copolymers, cellulose phthalate, and mixtures thereof.

38. The coated drug - ion exchange resin complex or matrix according to claim 37, wherein the release retardant comprises a polyvinyl acetate polymer.

39. The coated drug - ion exchange resin complex or matrix according to claim 37, wherein the release retardant comprises a neutral copolymer comprising ethyl acrylate and methyl methacrylate.

40. The coated drug-ion exchange resin complex or matrix according to claim 37, wherein the barrier coating comprises polyvinyl acetate polymer, a stabilizer, a surfactant and a plasticizer.

41. The coated drug-ion exchange resin complex or matrix according to claim 40 wherein the plasticizer is selected from the group consisting of dibutyl sebacate, propylene glycol, polyethylene glycol, polyvinyl alcohol, triethyl citrate, acetyl triethyl citrate, acetyl tributyl citrate, tributyl citrate, triacetin, Soluphor P, and mixtures thereof.

42. The coated drug - ion exchange resin complex or matrix according to claim 41, wherein the plasticizer is triacetin.

43. A method of preparing a coated drug - ion exchange resin complex useful in preparing modified release formulations, said method comprising the steps of:

forming a drug - ion exchange resin complex composed of a pharmaceutically acceptable drug and a pharmaceutically acceptable ion-exchange resin;

admixing a water insoluble release retardant;

applying to the drug - ion exchange resin complex a coating layer comprising a substantially tack-free, high tensile strength, water-permeable barrier coating; and

curing said coating layer.

44. The method according to claim 43, wherein said coating layer comprises a plasticizer.

45. The method according to claim 43, wherein the barrier coating is applied as an aqueous based dispersion.
46. The method according to claim 43, wherein the water-permeable barrier coating comprises a polyvinyl acetate polymer.
47. The method according to claim 43, wherein a drug - ion exchange resin complex is formed prior to addition of the water-insoluble release retardant.
48. A product for modified release of a drug, said product comprising packaging comprising the drug-resin complex or drug-resin complex matrix according to any of claims 32 to 42.
49. The product according to claim 48, wherein the product is a blister pack.
50. The product according to claim 49, wherein said packaging comprises a bottle.
51. The product according to claim 48, wherein said packaging comprises a metered dose apparatus.
52. The product according to claim 48 comprising a first container comprising a suspension base and a second container comprising a coated drug - ion exchange resin complex according to any of claims 32 to 42.