



(51) International Patent Classification:

C11D 17/00 (2006.01) C11D 1/72 (2006.01)
C11D 1/83 (2006.01) C11D 1/75 (2006.01)
C11D 3/18 (2006.01) C11D 1/722 (2006.01)
C11D 3/50 (2006.01) C11D 1/66 (2006.01)
C11D 1/825 (2006.01) C11D 1/12 (2006.01)
C11D 1/29 (2006.01)

(21) International Application Number:

PCT/US2009/001058

(22) International Filing Date:

19 February 2009 (19.02.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/064,181 21 February 2008 (21.02.2008) US

(71) Applicant (for all designated States except US): **S. C. JOHNSON & SON, INC.** [US/US]; 1525 Howe Street, Racine, Wisconsin 53403 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WORTLEY, Russell, B.** [US/US]; 1436 - 42nd Avenue, Kenosha, Wisconsin 53144 (US). **KLINKHAMMER, Michael, E.** [US/US]; 312 Augusta Street, Racine, Wisconsin 53402 (US). **WIETFELDT, John, R.** [US/US]; 7203 Brook Road, Franksville, Wisconsin 53126 (US). **RANDALL,**

Francis, J. [US/US]; 724 Hialeah Drive, Racine, Wisconsin 53402 (US).

(74) Agent: **NGUYEN, Peter, T.;** S. C. Johnson & Son, Inc., 1525 Howe Street, Racine, Wisconsin 53403 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CLEANING COMPOSITION THAT PROVIDES RESIDUAL BENEFITS




FIG. 1

(57) Abstract: A composition for use on a hard surface. The composition has: (i) at least 7.5 wt.% of at least one surfactant selected; (ii) a transport rate factor of less than about 55 seconds; and (iii) an adhesion time of greater than about 8 hours.

WO 2009/105232 A1

-1-

CLEANING COMPOSITION THAT PROVIDES RESIDUAL BENEFITS

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 This application claims the benefit of U.S. Provisional Application No. 61/064,181, filed February 21, 2008.

REFERENCE REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

10

Not applicable.

SEQUENTIAL LISTING

- 15 Not applicable.

FIELD OF INVENTION

- 20 In some embodiments, the invention is directed to a self-adhering composition that may provide residual benefits based on an extended spreading or coating provided by the composition upon exposure to a layer of water. In addition, the composition has improved stability under varying conditions of temperature and humidity, as well as improved self-adhesion to hard surfaces, for example a ceramic surface, such as toilet bowls, glass, windows, doors, shower or bath walls, and the like.

BACKGROUND OF INVENTION

30

It is known to hang cleaning and/or disinfecting and/or fragrancings agents in a container under the rim of a

-2-

toilet bowl by appropriate hanging devices from which the sanitary agents are released upon each flush into the toilet bowl.

5 While effective, some consumers do not use such devices because of reasons such as the need to remove a used device by hand. For example, consumers may perceive such requirement as unsanitary or generally unappealing. Additionally, only one device may be used at a time in a
10 toilet bowl and such devices tend to release composition locally, resulting in an effect that may be limited by the location and flow of the water.

In addition, consumers may shy away from using
15 conventional under-the-rim toilet bowl hanging devices because such devices may impede the consumer during the course of a regular cleaning. During cleaning with a toilet bowl brush, a hanging device may be easily displaced and then must be put back in place by using the
20 consumers' hands, which may be perceived as unhygienic or unappealing.

Exemplary sanitary agents for dispensing in toilet bowls may be in the form of solid blocks, liquids, and gel
25 form.

U.S. Patent No. 6,667,286 discloses a sanitary agent in paste or gel form which provides a long-lasting cleaning and/or deodorant-releasing and/or disinfecting effect and
30 which can be applied directly to the surface of a toilet bowl in a simple and hygienic manner. U.S. Pat. App. Pub. No. 2008/0190457 discloses a self-sticking cleansing

-3-

block that may be applied directly to the surface of a toilet bowl. The present invention provides an improvement to such a sanitary agent by providing greater stability, e.g. longevity in use, as well as improved self-adhesion to hard surfaces, especially ceramic surfaces such as a toilet bowl.

In some embodiments, the present invention provides consumers with the benefit of delivering a composition or active ingredient to a relatively wide area of a toilet bowl or other hard surface. In other nonlimiting embodiments, the present invention provides consumers with the benefit of efficiently delivering a composition or active ingredient to a relative wide area of the toilet bowl or other hard surface.

SUMMARY OF THE INVENTION

In a first nonlimiting embodiment, the present invention relates to a composition for use on a hard surface. The composition has: (i) at least 7.5 wt.% of at least one surfactant selected; (ii) a transport rate factor of less than about 55 seconds; and (iii) an adhesion time of greater than about 8 hours.

25

In a second nonlimiting embodiment, the present invention relates to a gel composition for use on a hard surface. The composition has: (i) less than 6 wt.% fragrance; and (ii) a transport rate factor of less than about 55 seconds.

30

-4-

In a third nonlimiting embodiment, the present invention relates to a solid composition for use on a hard surface. The composition has: (i) less than 10 wt.% fragrance; and (ii) a transport rate factor of less than about 55
5 seconds.

In a fourth nonlimiting embodiment, the present invention relates to a composition for use on a hard surface. The composition has: (i) at least 7.5 wt.% of at least one
10 surfactant; (ii) less than about 10 wt.% fragrance; and (iii) a transport rate factor of less than about 55 seconds.

BRIEF DESCRIPTION OF THE DRAWINGS

15

The following detailed description of specific nonlimiting embodiments of the present invention can be best understood when read in conjunction with the following drawings, where like structures are indicated
20 with like reference numerals and in which:

FIGURE 1 shows perspective view of an exemplary gel dispensing apparatus according to the present invention.

25 FIGURES 2A-E shows gel compositions having different mineral oil compositions at different times under test conditions as described below.

30

-5-

DETAILED DESCRIPTION OF THE INVENTION

Definitions

5 As used herein, "composition" refers to any solid, gel and/or paste substance having more than one component.

As used herein, "self adhesive" refers to the ability of a composition to stick onto a hard surface without the
10 need for a separate adhesive or other support device. In one embodiment, a self adhesive composition does not leave any residue or other substance (i.e., additional adhesive) once the composition is used up.

15 As used herein, "gel" refers to a disordered solid composed of a liquid with a network of interacting particles or polymers which has a non-zero yield stress.

As used herein, "fragrance" refers to any perfume, odor-
20 eliminator, odor masking agent, the like, and combinations thereof. In some embodiments, a fragrance is any substance which may have an effect on a consumer, or user's, olfactory senses.

25 As used herein, "wt.%" refers to the weight percentage of actual active ingredient in the total formula. For example, an off-the-shelf composition of Formula X may only contain 70% active ingredient X. Thus, 10 g. of the off-the-shelf composition only contains 7 g. of X. If 10
30 g. of the off-the-shelf composition is added to 90 g. of other ingredients, the wt.% of X in the final formula is thus only 7%.

-6-

As used herein, "hard surface" refers to any porous and/or non-porous surface. In one embodiment, a hard surface may be selected from the group consisting of:

5 ceramic, glass, metal, polymer, stone, and combinations thereof. In another embodiment, a hard surface does not include silicon wafers and/or other semiconductor materials. Nonlimiting examples of ceramic surfaces include: toilet bowl, sink, shower, tile, the like, and

10 combinations thereof. A nonlimiting example of a glass surfaces includes: window and the like. Nonlimiting examples of metal surfaces include: drain pipe, sink, automobiles, the like, and combinations thereof. Nonlimiting examples of a polymeric surface includes:

15 PVC piping, fiberglass, acrylic, Corian®, the like, and combinations thereof. A nonlimiting example of a stone hard surface includes: granite, marble, and the like.

A hard surface may be any shape, size, or have any

20 orientation that is suitable for its desired purpose. In one nonlimiting example, a hard surface may be a window which may be oriented in a vertical configuration. In another nonlimiting example, a hard surface may be the surface of a curved surface, such as a ceramic toilet

25 bowl. In yet another nonlimiting example, a hard surface may be the inside of a pipe, which has vertical and horizontal elements, and also may have curved elements. It is thought that the shape, size and/or orientation of the hard surface will not affect the compositions of the

30 present invention because of the unexpectedly strong transport properties of the compositions under the conditions described *infra*.

-7-

As used herein, "surfactant" refers to any agent that lowers the surface tension of a liquid, for example water. Exemplary surfactants which may be suitable for use with the present invention are described *infra*. In one embodiment, surfactants may be selected from the group consisting of anionic, non-ionic, cationic, amphoteric, zwitterionic, and combinations thereof. In one embodiment, the present invention does not comprise cationic surfactants. In other nonlimiting embodiments, the surfactant may be a superwetter. One of skill in the art will appreciate that in some embodiments, a substance which may be used as an adhesion promoter may also be a surfactant.

In use, the composition of the invention may be applied directly on the hard surface to be treated, e.g. cleaned, such as a toilet bowl, shower or bath enclosure, drain, window, or the like, and self-adheres thereto, including through a plurality of flows of water passing over the self-adhering composition and surface, e.g. flushes, showers, rinses or the like. Each time water flows over the composition, a portion of the composition is released into the water that flows over the composition. The portion of the composition released onto the water covered surface provides a continuous wet film to the surface to in turn provide for immediate and long term cleaning and/or disinfecting and/or fragrancing or other surface treatment depending on the active agent(s) present in the composition. It is thought that the composition, and thus the active agents of the composition, may spread out from or are delivered from

-8-

the initial composition placement in direct contact with the surface to coat continuously an extended area on the surface. The wet film acts as a coating and emanates from the self-adhering composition in all directions, i.e., 360°, from the composition, which includes in a direction against the flow of the rinse water. Motions of the surface of a liquid are coupled with those of the subsurface fluid or fluids, so that movements of the liquid normally produce stresses in the surface and vice versa. The mechanism for the movement of the gel and/or the active ingredients is discussed in greater detail *infra*.

Surprisingly, it is observed that the nonlimiting exemplary compositions of the present invention provide for a more rapid and extended self-spreading. Without wishing to be limited by theory, it is thought that the self-spreading effect may be modified through the addition of specific surfactants to the composition. Nonlimiting examples of factors which are thought to affect the speed and distance of the self spreading include: the amount of surfactant present, the type of surfactant present, the combination of surfactants present, the amount of spreading of the surfactant over the water flow, the ability of the surfactant to adsorb at the liquid / air interface, and the surface energy of the treated surface. It is thought that the surfactant of the composition serves to push other molecules, e.g. compounds, around so as to deliver these compounds to other parts of the surface. Compounds desirable for extended delivery over a treated surface are active agents, e.g. agents capable of activity as opposed to

-9-

being inert or static. Nonlimiting examples of active agents, or active ingredients, that may be used include: cleaning compounds, germicides, antimicrobials, bleaches, fragrances, surface modifiers, stain preventers (such as a chelator) the like, and combinations thereof. The composition is especially useful in treating the surface of a toilet bowl since it allows for delivery and retention of a desired active agent on a surface above the water line in the bowl as well as below the water line.

In some embodiments, the composition can be applied directly to a surface using any suitable applicator device, such as a pump or syringe-type device, manual, pressurized, or mechanized, aerosol, or sprayer. The consumer may activate the applicator for application of the composition directly to a surface without the need to touch the surface. In the case of a toilet bowl surface, this provides for a hygienic and easily accessible method of application. The amount and location(s) of the composition may be chosen by the user, e.g. one or more dollops or drops of composition, or one or more lines of composition. The composition self-adheres to a hard surface to which it is applied, such as the ceramic side wall of a toilet bowl or shower wall. A surprising and unique feature not provided by conventional devices is that the composition is delivered to surfaces located above the site of application of the composition to the surface.

30

-10-

Composition

In one embodiment, the composition has a gel or gel-like consistency. In the described embodiment, the
5 composition is, thus, firm but not rigid as a solid. In an alternative embodiment, the composition is a solid. In still another embodiment, the composition is a malleable solid.

10 The improved adhesion obtained by the composition of the invention allows application on a vertical surface without becoming detached through a plurality of streams of rinse water and the gradual washing away of a portion of the composition over time to provide the desired
15 cleaning and/or disinfecting and/or fragrance or other treatment action. Once the composition is completely washed away, nothing remains for removal and more composition is simply applied.

20 In some embodiments, the composition may include an adhesion promoter which causes a bond with water and gives the composition a dimensional stability even under the action of rinse water; at least one nonionic surfactant (which may serve all or in part as the
25 adhesion promoter), preferably an ethoxylated alcohol; at least one anionic surfactant, preferably an alkali metal alkyl ether sulfate or sulfonate; mineral oil; water; and optionally at least one solvent. More particularly, the hydrophilic polymer holds the composition to the surface
30 to enhance the maintenance and thereby extend the times of spreading and, thus, delivery of active agents for treatment of the surface and/or surrounding environment. In some embodiments, the composition may also include a

-11-

superwetter compound to enhance the spreading of the wet film. The composition displays extended durability without the necessity of an exterior hanging device or holder thereby only requiring a new application of the composition to the surface after a long lapse of time and no need to remove any device.

In some nonlimiting examples, there are a number of components of the present invention composition that are suitable for treating hard surfaces. In one embodiment, the composition comprises an adhesion promoter present in an amount of from about 20 wt.% to about 80 wt.%. In another embodiment, the composition comprises an adhesion promoter in the amount of from about 20 wt.% to about 60 wt.%. In another embodiment, the composition comprises an adhesion promoter in the amount of from about 40 wt.% to about 60 wt.%. In an alternative embodiment, the composition comprises an adhesion promoter in the amount of from about 20 wt.% to about 30 wt.%.

In another embodiment, the composition comprises at least one surfactant in an amount of greater than 7.5 wt.%. In another embodiment, the composition comprises at least one surfactant in an amount of from about 7.5 wt.% to about 20 wt.%. Surprisingly, it is discovered that providing an optimal amount of surfactant, in particular anionic surfactant, provides the product with a particularly strong "foaming" characteristic that greatly pleases consumers.

In one embodiment, the composition comprises a non-polar hydrocarbon such as mineral oil in an amount of less than

-12-

about 5 wt.%. In another embodiment, the composition comprises mineral oil in an amount of from greater than zero wt.% to about 5 wt.%. In another embodiment, the composition comprises mineral oil in an amount of from
5 about 0.5 wt.% to about 3 wt.%.

In some embodiments, the compositions may be brought to 100 wt.% using any suitable material for the intended application. One of skill in the art will appreciate
10 that this may include, but not be limited to, a balance of water, surface modifiers, germicides, bleaches, cleaners, foamers, the like, and combinations thereof.

Optionally, the compositions of the present invention may
15 further comprise at least one solvent in an amount of from 0 wt.% to about 15 wt.% and the composition may further comprise at least one fragrance in an amount of from 0 wt.% to about 15 wt.%. Additionally, the composition may optionally include a hydrophilic polymer
20 in an amount from 0 wt.% to about 5 wt.% to amplify transport effects of the composition. In one embodiment, "solvent" does not include water.

A further optional component is a superwetter. Without
25 wishing to be limited by theory, it is thought that a superwetter may enhance the wet film provided in use of the composition. Superwetters, as may be used in the present invention composition, are described in greater detail *infra*. In other nonlimiting embodiments,
30 additional optional components include conventional adjuvants, such as a preservative, colorant, foam

-13-

stabilizer, antimicrobial, germicide, or the like, present in an effective amount.

Exemplary components suitable for use as an adhesion promoter may have long or long-chained molecules, for the most part linear, that are at least in part hydrophilic and thus include at least a hydrophilic residual or a hydrophilic group so as to provide interaction with water molecules. Preferably, the adhesion promoter has unbranched molecules to form a desired network-like structure to form adhesion-promoting molecules. The adhesion promoter may be totally hydrophilic or partly hydrophilic, partly hydrophobic.

Exemplary pure adhesion hydrophilic promoters suitable for use in the present invention include, for example: polyethylene glycol, cellulose, especially sodium carboxymethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, or polysaccharides such as xanthan gum, agar, gellan gum, acacia gum, carob bean flour, guar gum or starch. Polysaccharides can form networks with the necessary solidity and a sufficient stickiness in concentrations of from 0 wt.% to about 10 wt.%; from 0 wt.% to about 5 wt.%; and from about 1 wt.% to about 2 wt.%.

The adhesion-promoting molecules can be synthetic or natural polymers, for instance, polyacrylates, polysaccharides, polyvinyl alcohols, or polyvinyl pyrrolidones. It is also possible to use alginates, diurethanes, gelatines, pectines, oleyl amines, alkyl dimethyl amine oxides, or alkyl ether sulfates.

-14-

Organic molecules with a hydrophilic and hydrophobic end may also be used as adhesion promoters. As hydrophilic residuals, for example, polyalkoxy groups, preferably polyethoxy, polypropoxy, or polybutyoxy or mixed polyalkoxy groups such as, for example, poly(ethoxypropoxy) groups can be used. Especially preferred for use as a hydrophilic end, for example, is a polyethoxy residual including from 15 to 55 ethoxy groups, preferably from 25 to 45 and more preferably from 30 to 40 ethoxy groups.

In some embodiments, anionic groups, for example, sulfonates, carbonates, or sulfates, can be used as hydrophilic ends. In other embodiments, stearates, especially sodium or potassium stearate, are suitable as adhesion promoters.

In embodiments wherein the adhesion-promoting molecules also have a hydrophobic end, straight-chained alkyl residuals are preferred for the hydrophobic residual, whereby in particular even-numbered alkyl residuals are preferred because of the better biological degradability. Without wishing to be limited by theory, it is thought that to obtain the desired network formation of the adhesion-promoting molecules, the molecules should be unbranched.

If alkyl residuals are chosen as hydrophobic residuals, alkyl residuals with at least 12 carbon atoms are preferred. More preferred are alkyl chain lengths of

-15-

from 16 to 30 carbon atoms, most preferred is from 20 to 22 carbon atoms.

Exemplary adhesion promoters are polyalkoxyalkanes,
5 preferably a mixture of C₂₀ to C₂₂ alkyl ethoxylate with
from 18 to 50 ethylene oxide groups (EO), preferably from
about 25 to about 35 EO, and also sodium dodecylbenzene
sulfonate. With a reduction of the number of alkoxy
10 groups the adhesion promoter becomes more lipophilic,
whereby, for example, the solubility of perfume and thus
the intensity of the fragrance can be raised.

Molecules that generally act like thickeners in aqueous
systems, for example, hydrophilic substances, can also be
15 used as adhesion promoters.

Without wishing to be limited by theory, it is thought
that the concentration of the adhesion promoter to be
used depends on its hydrophilicity and its power to form
20 a network. When using polysaccharides, for example,
concentrations from about 1 wt.% to about 2 wt.% of the
adhesion promoter can be sufficient, whereas in
embodiments comprising polyalkoxyalkanes the
concentrations may be from about 10 wt%. to about 40
25 wt.%; in another embodiment from about 15 wt.% to about
35 wt.%; and in another embodiment still from about 20
wt.% to about 30 wt.%.

Also without wishing to be limited by theory, it is
30 thought that in order to produce the desired number of
adhering sites with the adhesion-promoting molecules
through the absorption of water, the composition may

-16-

contain at least about 25% by weight water, and optionally additional solvent. In one embodiment, the composition comprises water from about 40 wt.% to about 65 wt.%. One of skill in the art will appreciate that
5 the amount of water that is to be used is dependent on, among other things, the adhesion promoter used and the amount of adjuvants also in the formula.

Exemplary anionic surfactants suitable for use include
10 alkali metal C₆-C₁₈ alkyl ether sulfates, e.g. sodium lauryl ether sulfate; α -olefin sulfonates or methyl taurides. Other suitable anionic surfactants include alkali metal salts of alkyl, alkenyl and alkylaryl sulfates and sulfonates. Some such anionic surfactants
15 have the general formula RSO₄M or RSO₃M, where R may be an alkyl or alkenyl group of about 8 to about 20 carbon atoms, or an alkylaryl group, the alkyl portion of which may be a straight- or branched-chain alkyl group of about 9 to about 15 carbon atoms, the aryl portion of which may
20 be phenyl or a derivative thereof, and M may be an alkali metal (e.g., ammonium, sodium, potassium or lithium).

Exemplary nonionic surfactants suitable for use include
25 C₂₀-C₂₂ alkyl ethoxylate with 18 to 50 ethylene oxide groups (EO). In another embodiment, C₂₀-C₂₂ alkyl ethoxylate comprise 25 to 35 ethylene oxide groups, preferably as an adhesion promoter and nonionic surfactant.

30 Additional nonlimiting examples of other nonionic surfactants suitable for use include alkylpolyglycosides such as those available under the trade name GLUCOPON

-17-

from Henkel, Cincinnati, Ohio, USA. The alkylpolyglycosides have the following formula: $RO-(R'O)_x-Z_n$ where R is a monovalent alkyl radical containing 8 to 20 carbon atoms (the alkyl group may be straight or branched, saturated or unsaturated), O is an oxygen atom, R' is a divalent alkyl radical containing 2 to 4 carbon atoms, preferably ethylene or propylene, x is a number having an average value of 0 to 12, Z is a reducing saccharide moiety containing 5 or 6 carbon atoms, preferably a glucose, galactose, glucosyl, or galactosyl residue, and n is a number having an average value of about 1 to 10. For a detailed discussion of various alkyl glycosides see U.S. Statutory Invention Registration H468 and U.S. Pat. No. 4,565,647, which are incorporated herein by reference. Some exemplary GLUCOPONS are as follows (where Z is a glucose moiety and x=0) in Table A.

Table A: Exemplary Glucopons

20

Product	N	R (# carbon atoms)
425N	2.5	8-14
425LF	2.5	8-14 (10 w/w % star-shaped alcohol added)
220UP	2.5	8-10
225DK	2.7	8-10
600UP	2.4	12-14
215CSUP	2.5	8-10

Other nonlimiting examples of nonionic surfactants suitable for use include alcohol ethoxylates such as those available under the trade name LUTENSOL from BASF,

25

-18-

Ludwigshafen, Germany. These surfactants have the general formula $C_{13}H_{25}/C_{15}H_{27}-OC_2H_4)_n-OH$ (the alkyl group being a mixture of C_{13}/C_{15}). Especially preferred are LUTENSOL AO3 (n=3), AO8 (n=8), and AO10 (n=10). Other
5 alcohol ethoxylates include secondary alkanols condensed with (OC_2H_4) such as TERGITOL 15-S-12, a $C_{11}-C_{15}$ secondary alkanol condensed with 12 (OC_2H_4) available from Dow Surfactants. Another example of a nonionic surfactant suitable for use is polyoxyethylene (4) lauryl ether.
10 Amine oxides are also suitable.

At least one solvent can be present in the composition to assist in blending of surfactants and other liquids. The solvent is present in an amount of from about 0 wt.% to
15 about 15 wt.%, preferably from about 1 wt.% to about 12 wt.%, and more preferably in an amount from about 5 wt.% to about 10 wt.%. Examples of solvents suitable for use are aliphatic alcohols of up to 8 carbon atoms; alkylene glycols of up to 6 carbon atoms; polyalkylene glycols
20 having up to 6 carbon atoms per alkylene group; mono- or dialkyl ethers of alkylene glycols or polyalkylene glycols having up to 6 carbon atoms per glycol group and up to 6 carbon atoms in each alkyl group; and mono- or diesters of alkylene glycols or polyalkylene glycols
25 having up to 6 carbon atoms per glycol group and up to 6 carbon atoms in each ester group. Specific examples of solvents include t-butanol, t-pentyl alcohol; 2,3-dimethyl-2-butanol, benzyl alcohol or 2-phenyl ethanol, ethylene glycol, propylene glycol, dipropylene glycol,
30 propylene glycol mono-n-butyl ether, dipropylene glycol mono-n-butyl ether, propylene glycol mono-n-propyl ether, dipropylene glycol mono-n-propyl ether, diethylene glycol

-19-

mono-n-butyl ether, diethylene glycol monomethyl ether,
dipropylene glycol monomethyl ether, triethylene glycol,
propylene glycol monoacetate, glycerin, ethanol,
isopropanol, and dipropylene glycol monoacetate. One
5 preferred solvent is polyethylene glycol.

It is thought that the inclusion of a non-polar
hydrocarbon, such as mineral oil, may serve to achieve
increased stability and self-adherence to a hard surface,
10 especially a ceramic surface. The mineral oil is present
in an amount of greater than 0% by weight to about 5% by
weight, based on the total weight of the composition. In
one embodiment, mineral oil is present in an amount of
from about 0.5% wt.% to about 3.5 wt.%. In another
15 embodiment, mineral oil is present in an amount of from
about 0.5 wt.% to about 2 wt.%. The amount of mineral
oil to be included will depend on the adhesion
performance of the balance of the formula.—Without
wishing to be limited by theory, it is thought that as
20 the amount of mineral oil is increased, the adhesion is
also increased.

Although it provides benefits when used in the
composition, it is also thought that the inclusion of the
mineral oil in higher amounts without decreasing the
25 amount of surfactant and/or thickener and/or adhesion
promoters will result in the composition being thickened
to a degree which makes processing of the composition
during manufacture and use difficult because the firmness
of the composition makes it difficult to process. In
30 manufacture, the processing can be carried out under
increased temperatures, but such also increases the cost

-20-

of manufacture and creates other difficulties due to the increased temperature level.

Nonlimiting examples of hydrophilic polymers useful

5 herein include those based on acrylic acid and acrylates, such as, for example, described in U.S. Patent Nos. 6,593,288, 6,767,410, 6,703,358 and 6,569,261. Suitable polymers are sold under the trade name of MIRAPOL SURF S by Rhodia. A preferred polymer is MIRAPOL SURF S-500.

10

A superwetter is optionally included in the composition to enhance the maintenance of the wet film provided. A superwetter may thereby assist in decreasing the time of spreading. Examples of superwetters suitable for

15

inclusion in the composition hydroxylated dimethylsiloxanes such as Dow Corning Q2-5211 (Dow Corning, Midland, MI). The superwetter(s) may be present (in addition to any other surfactant in the composition) in an amount of 0 to about 5 wt.%; preferably from about 20 0.01 to about 2 wt.%, and most preferably from about 0.1 wt.% to about 1 wt.%.

Fragrances and aromatic substances can be included in the composition to enhance the surrounding atmosphere.

25

In one embodiment, a gel composition comprises less than 6 wt.% fragrance. In another embodiment, the gel composition comprises from 0 wt.% to 6 wt.% fragrance.

In another embodiment still, the gel composition

30

comprises from 0 wt.% to about 5 wt.% fragrance. In yet another embodiment, the gel composition comprises from about 2 wt.% to about 5 wt.% fragrance.

-21-

In one embodiment, a solid composition comprises less than 10 wt.% fragrance. In another embodiment, the solid composition comprises from 0 wt.% to 10 wt.% fragrance.

5 In another embodiment still, the solid composition comprises from 2 wt.% to about 8 wt.% fragrance. In yet another embodiment, the gel composition comprises from about 4 wt.% to about 7 wt.% fragrance.

10

The composition according to the invention sticks to hard surfaces through self-adhesion. The solid, gel and gel-like materials are dimensionally stable so that they do not "run" or "drip" through a plurality of streams of

15 water flowing thereover. It is thought that consumers prefer such a composition because the adhesion and shape of the composition remain intact even through a plurality of water rinses. Exemplary compositions comprising mineral oil are described in Table B, below:

20

Table B: Exemplary Compositions Comprising Mineral Oil

INGREDIENTS	SAMPLE 1	SAMPLE 2	SAMPLE 3	SAMPLE 4
C ₂₂ Ethoxylated Alcohol (30 EO)	13	13	13	13
C ₁₆₋₁₈ Ethoxylated Alcohol (30 EO)	13	13	13	13
Preservative	0.15	0.15	0.15	0.15
Dionized Water	44.85	44.75	44.35	43.85
Mineral Oil	0	0.1	0.5	1.0
Glycerine	5	5	5	5
Polyethylene Glycol 6000	1	1	1	1
Sodium lauryl ether sulfate	18	18	18	18
Fragrance	5	5	5	5
Total Wt.%	100 Wt.%	100 Wt.%	100 Wt.%	100 Wt.%

Transport of Active Ingredients

5 As described *supra*, the composition of the invention may
be applied directly on the surface of a sanitary object
to be cleaned, such as a toilet bowl, shower or bath
enclosure, or the like, and self-adheres thereto through
a plurality of streams of water flowing over the self-
10 adhering composition, e.g. flushes or showers. Each time
water flows over the composition, a portion of the
composition is released onto the surface to which the
composition adheres as well as into the water to provide
long term cleaning, disinfecting, fragrancing, stain
15 prevention, surface modification, UV protection,
whitening, bleaching, and the like. It is thought that
any residual benefits may be obtained from the
composition through the inclusion of ingredients
described above which provide for the spreading and/or
20 transport of the composition along the hard surface to
areas wherein the composition was not originally
deposited. More specifically, the composition, and thus
the active agents of the composition, spread out from or
are delivered from the initial composition placement in
25 direct contact with the surface to coat an extended
adjoining area on the surface. Motions of the surface of
a liquid are coupled with those of the subsurface fluid
or fluids, so that movements of the liquid normally
produce stresses in the surface and vice versa. The
30 movement of the surface and of the entrained fluid(s)
caused by surface tension gradients is called the
Marangoni effect (IUPAC Compendium of Chemical

-23-

Terminology, 2nd Edition, 1994). Thus, the composition of the invention provides that liquid flows along a liquid-air interface from areas having low surface tension to areas having higher surface tension. The

5 Marangoni flow is macroconvection, i.e., the gradient in the interfacial tension is imposed on the system by an asymmetry, as opposed to microconvection where the flow is caused by a disturbance that is amplified in time (an instability). Thus, upon a flow of water over the

10 composition of the invention, the composition spreads outward to cover extended adjoining surface areas as opposed to only the local area covered by or immediately adjacent the composition.

15 More specifically, it is thought that this effect is observed due to mass transfer on, or in, a liquid layer due to differences in surface tension on that liquid layer. Without wishing to be limited by theory, it is thought that because a liquid with a relatively high

20 surface tension pulls more strongly on the surrounding liquid compared to a liquid with a relatively low surface tension, a surface tension gradient will cause liquid to flow away from regions of relatively low surface tension towards regions of relatively high surface tension. Such

25 property, the Marangoni effect, is used in high-tech semiconductor wafer processing. Nonlimiting examples include U.S. Pat. Nos. 7,343,922; 7,383,843; and 7,417,016.

30 Those of skill in the art will appreciate that a dimensionless unit often referred to as the Marangoni number may be used to estimate the Marangoni effect, and

-24-

other transport properties, of a material. One of the factors which may be used to estimate the Marangoni effect of a material, the Marangoni number, may be described by Eq. 1. One of skill in the art will appreciate that the Marangoni number provides a dimensionless parameter which represents a measure of the forces due to surface tension gradients relative to viscous forces.

10 Marangoni number, $M_a = \frac{\Gamma (d\sigma/dc)}{D \mu}$

Where M_a is the Marangoni number
 15 Γ is the surface excess concentration of surfactant (mol/m²)
 σ is the surface tension (N/m)
 c is the bulk surfactant concentration (mol/m³)
 μ is the bulk dynamic viscosity (Pascal seconds)
 20 D is the bulk surfactant diffusion coefficient (m²/s)

25 As described *supra*, there exist a number of compositions that are used to transport active ingredients around a surface. However, most of the aforementioned compositions rely on gravity or the adhesion-cohesion of liquids as the lone mechanisms for transporting the composition around the surface. Similarly, traditional liquid bathroom cleaners or similar compositions in the bath cleaning arts, for example, often require the user to use a brush, other implement, to manually spread the composition around the surface.

35 Surprisingly, it was discovered that, despite the complexity associated with transport phenomena, the

-25-

transport properties of a composition could be enhanced through the addition of specific surfactants and other ingredients, to the composition. Even more surprisingly, the composition may be used as a vehicle for active
5 ingredients when the composition is in the presence of a liquid layer.

With respect to a hard surface, such as a toilet bowl, it is thought that by providing a composition according to
10 the present invention, one may be able to provide consumers with additional benefits of limiting the amount of touching or other interaction between the consumer and the toilet bowl. Such minimal interaction may be achieved by taking advantage of the composition's ability
15 to move from one area of the toilet (or other hard surface) via gradients in surface tension which may be induced by the surfactants. Thus, it is thought that when a user flushes a toilet, the interaction of the liquid layer (from the flush) with the composition will
20 cause the gel composition to migrate along the surface tension gradient, thus moving the composition around the toilet.

One of skill in the art will appreciate that the
25 transport mechanism described above may be used with any hard surface that is provided with a liquid layer and is not necessarily limited to use in a toilet bowl. For example, it is hypothesized that a user may be able to provide a composition to the surface of a sink, window,
30 drain, or any other hard surface on which water, or other liquid, may be provided. Additional exemplary surfaces are described throughout.

Considerations for Treatment of Hard Surfaces

The self-spreading of the composition to provide a
5 coating effect and residual benefits from active treating
agents, is based on the surfactant(s) present in the
composition. Nonlimiting factors which may be thought to
affect the speed and distance of the self-spreading, in
addition to the essential requirements of direct contact
10 of the composition with the surface to be treated and a
flow of water over and around the composition, are the
amount and type of surfactant present, in addition to and
the amount or rate of dissolution of the surfactant in
the water flow.

15

It is surprisingly discovered that when the surfactant
amount and dissolution are controlled as described above,
the product is capable of covering an extended area
outward 360° from the area of initial product
20 application. Further, in embodiments including active
ingredients, also described above, the composition may
provide an initial and/or further residual treatment of a
surface. The speed of spreading is significant since the
extent of spreading as desired must be complete prior to
25 drying of the water on the surface since the water is a
necessary component in providing the continuous film.

Method of Use

30 As described above, the present invention compositions
may be used to provide immediate and/or residual benefits
to a hard surface upon application to that surface

-27-

wherein the surface will be subject to water or some other liquid which will provide a layer for a surface energy gradient.

- 5 In one embodiment the present invention composition may be comprised of the following steps: (1) Application of one or more doses of the composition onto a hard surface; (2) Exposure of the hard surface, and subsequently the one or more doses of composition, to a liquid layer to
10 provide a spread out and dissipated composition layer. The method for using the product may further comprise the optional steps: (3) Exposure of the hard surface, and subsequently the spread out and dissipated composition layer to a liquid layer to provide a further spread out
15 and dissipated composition layer. One of skill in the art will appreciate that (3) may be repeated indefinitely until the composition is completely dissipated. In some embodiments, the liquid layer is water.
- 20 As described *supra*, the hard surface may be selected from the group consisting of: ceramic, glass, metal, polymer, fiberglass, acrylic, stone, the like and combinations thereof.
- 25 A liquid layer may be provided through any means that is suitable for the intended function. For example, in a toilet bowl, a dose of composition may be applied to the inside surface of the toilet bowl (a ceramic hard surface) and the toilet may be flushed to provide the
30 liquid layer that is necessary to facilitate the transport of the composition around the toilet bowl. In another example, a dose of composition may be applied to

-28-

the outside surface of a window. The outside surface of the window may be sprayed with water by the user using a hose or power washer, or rain may deposit a layer of water to the window. In yet another example, a dose of composition may be applied to the inside of a sink or drain pipe. The user may simply activate the faucet to provide a layer of water to the sink or drain pipe. In still another example, a dose of composition may be applied to the wall of a shower. The user may activate the shower to provide a liquid layer to the surface. In yet another example, it is envisioned that the liquid layer may also be provided with steam or a relatively high humidity.

One of skill in the art will appreciate that the different applications and embodiments of the present invention composition may be provided with different active ingredients or benefit agents which may vary depending on the desired application.

20

Method of Use: Dispensing Considerations

There exist applicators for gel-like substances. For example, PCT Int. Pat. App. WO 03/043906 and WO 2004/043825 disclose exemplary dispensing devices. However, while the aforementioned dispensers succeed in applying an adhesive gel-like substance to a surface, some users may find that the inability to provide consistent dosing frustrating. Specifically, consumers realize that overapplication of the product may be wasteful and lead to the purchase of unnecessary refills,

-29-

while underapplication of the product may minimize the efficacy of the composition.

A nonlimiting exemplary dispenser that is capable of
5 providing metered doses of a composition that may be compatible with the present invention compositions is described in U.S. Pat. App. No. 2007/0007302A1. Without wishing to be limited by theory, it is thought that consumers may prefer to provide the compositions of the
10 present invention in unitized, discrete doses because such a device is relatively easy to use compared to devices wherein the consumer controls the dose size.

Further, one of skill in the art will appreciate that,
15 when used in conjunction with a metered dispenser, the dispenser may provide doses of the composition in any volume and/or size and/or dose that is suitable for the intended application. Similarly, the shape of the dispenser may be any shape that is desired. For example,
20 FIG. 1 illustrates an exemplary embodiment of a dispenser 10 that may be used to dispense gel composition 20 according to the present invention. The dispenser 10 comprises a cylindrical body 11 and a gel composition 20 contained therein. The dispenser 10 further comprises a
25 resistive push-button 13 which fits a user may push into a guide hole 14, and then slide a guide member 15 in the negative-y direction to push gel composition 20 towards the dispenser mouth 12. Upon moving the guide member 15 a predetermined distance, the push-button 13 may then
30 "pop" out of the next guide hole 14 to allow for a precise dose of composition 20 to be dispensed. The cross-section 17-17 of the dispenser 10 may be any shape

-30-

that is desirable for the intended purpose. In one embodiment, the cross section 17-17 may be annular. Nonlimiting examples of cross-sectional shapes may be selected from: squares, circles, triangles, ovals,
5 stars, the like, and combinations thereof.

In one embodiment, a composition according to the present invention may be provided in a dispenser wherein the dispenser provides unitized doses. In a particular
10 embodiment, the unitized dose is from about 4 g/dose to about 10 g/dose. In another embodiment, the unitized dose is from about 5 g/dose to about 9 g/dose. In yet another embodiment, the dispenser may provide from about 6 to about 8 g/dose unitized doses. In still another
15 embodiment, the dispenser may provide from about 3 to about 12 unitized doses. In some embodiments, the dispenser may be refilled with additional composition.

In embodiments wherein the composition is a solid, or a
20 malleable solid, an exemplary method and apparatus for dispensing is described in U.S. Pat. App. No. 2008/0190457.

Experimental Results and Data

25

Samples

Samples 1-13 comprise a base ingredient set in addition to a surfactant. It should be noted that the amount of deionized water in the base ingredient set is adjusted to
30 accommodate the additional surfactant in Samples 1-13. The Scrubbing Bubbles Sample describes an embodiment of a current product (Scrubbing Bubbles Toilet Gel "Citrus

-31-

Scent", S.C. Johnson & Son, Racine, WI). The 6,667,286 samples are derived from Example 1 of U.S. Pat. No. 6,667,286. '286 (1) includes the Rhodipol component. '286 (2) is a sample that is made with ingredients at the
 5 midpoint of the described ranges. Measurements are made to the samples for different properties. Surprisingly, the samples comprising the surfactant, and other ingredients according to the present invention samples provide an ideal combination of various properties which
 10 are described in greater detail below:

Base Ingredient Set ("Base"):

Ingredient	Wt. %
Deionized Water	64.000000
C ₂₂ Ethoxylated Alcohol (30 EO)	13.000000
C ₁₆₋₁₈ Ethoxylated Alcohol (30 EO)	13.000000
Glycerine, USP, 99.5%	5.000000
Quest® F560805	5.000000

Samples

Sample	Surfactant	Wt. %
1	Alkyl Polyglycoside 425 N	2.00
2	Pluronic® F127	1.00
3	Tergitol® 15-S-12	1.03
4	Sodium Lauryl Ether Sulfate 2EO, 70%	1.43
5	Q2-5211	1.67
6	Leutensol® XL140	1.00
7	Leutensol® XP 30	1.00
8	Aerosol® OT-NV	1.20
9	Macat® AO-12	3.33
10	Macat® AO-8	3.51
11	Tegopren® 6922	2.00
12	Alkyl Polyglycoside 425 N	4.00
13	Sodium Lauryl Ether Sulfate 2EO, 70%	8.00
'286 (1)	Example 1 of 6,667,286 -	6.00

-32-

	Rhodopol	
'286 (2)	Example 1 of 6,667,286 -	6.00
	Midpoints of ranges	
Scrubbing	Quest® F560805	12.60
Bubbles		

Surface Spreading

5 As described *supra*, the present invention compositions provides the unexpected benefit over existing compositions of, *inter alia*, increased mobility and transport. Exemplary compositions are made according to the Detailed Description and are tested for surface

10 spreading using the "Surface Spreading Method" described below.

Surprisingly, it is noticed that the addition of the surfactants provide a significant increase in transport

15 of the compositions. In one embodiment, the compositions of the present invention provide a transport rate factor of less than 55 seconds. In another embodiment, the compositions of the present invention provide a transport rate factor of less than about 50 seconds. In still

20 another embodiment, the compositions of the present invention provide a transport rate factor of from about 0 seconds to about 55 seconds. In another embodiment, the compositions of the present invention provide a transport rate factor of from about 30 seconds to about 55 seconds.

25 In yet still another embodiment, the compositions of the present invention provide a transport rate factor of from about 30 seconds to about 50 seconds. In still another embodiment, the compositions of the present invention

-33-

provide a transport rate factor of from about 30 seconds to about 40 seconds.

Results for the surface spreading (Transport Rate Factor) of a product is reported in Table C below.

The surface spreading of a product is measured by the Surface Spreading Test described below.

10 Table C: Surface Spreading Measurements

Sample	Transport Rate Factor
1	33.2
2	47.7
3	53.3
4	50.5
5	30.4
6	50.1
7	46.3
8	36.9
9	37.0
10	42.7
11	56.9
12	38.5
13	40.2
Base	50.1
'286 (1)	65.9
Scrubbing Bubbles	39.1

Composition Adhesion

In addition to the mobility of the composition, it is surprisingly discovered that the ability of the composition to adhere to a hard surface provides additional unexpected benefits, such as product longevity during use. A product must have an ability to adhere to a surface for a period of at least 5 hours, as measured by the adhesion test described below. In one embodiment, a product has a minimum adhesion of greater than about 8 hours. In another embodiment, a product has a minimum adhesion of from about 8 hours to about 70 hours.

Results for the minimum adhesion of a product is reported in Table D below.

The minimum adhesion of a product is measured by the Adhesion Test described below.

Table D: Minimum Adhesion Measurements

Sample	Adhesion Time (Hours)
1	> 64
2	> 64
3	> 64
4	> 64
5	> 64
6	> 64
7	> 64
8	> 64
9	> 64
10	> 64
11	> 64

-35-

12	> 64
13	> 64
Base	> 64
'286 (1)	6
'286 (2)	7.5
Scrubbing Bubbles	12

Composition Gel Temperature

It is thought that an additional property which is
 5 important to compositions is the ability to maintain its
 form despite being subject to relatively high
 temperatures. Similarly to adhesion, the ability to
 maintain its form, and being resistant to melting.
 Specifically, this metric measures the temperature at
 10 which the composition transitions to a viscosity of
 greater than 100 cps as the composition cools. Further,
 having a relatively high composition gel temperature may
 provide processing, manufacturing, transport, and
 packaging advantages to producers.

15

In one embodiment the composition has a gel temperature
 of greater than 50 °C. In another embodiment, the
 composition has a gel temperature of from about 50 °C to
 about 80 °C. In another embodiment still, the composition
 20 has a gel temperature of from about 50 °C to about 70 °C.

The composition gel temperature is measured by the Gel
 Temperature Test described below.

25 Results for the composition gel temperature of a product
 is reported in Table E below.

-36-

The minimum adhesion of a product is measured by the Gel Temperature Test described below.

Table E: Gel Temperature Measurements

5

Sample	Gel Temperature (°C)
1	67.9
2	72.9
3	72.2
4	70.0
5	67.4
6	71.8
7	65.6
8	68.0
9	71.4
10	75.3
11	72.2
12	62.1
13	70.5
Base	72.3
'286 (1)	68.9
'286 (2)	72.7
Scrubbing Bubbles	54.1

Composition Viscosity

- 10 In some nonlimiting embodiments, the composition of the invention is in the form of a self-adhering gel or gel-like composition for treating hard surfaces. In the embodiments wherein the compositions are self-adhering gels, the viscosity of the composition is from about

-37-

15,000 cps to about 100,000 cps. In another embodiment, the viscosity is from about 25,000 cps to about 80,000 cps. In yet another embodiment, the viscosity is from about 30,000 cps to about 60,000 cps.

5

The composition gel temperature is measured by the Viscosity Test described below.

Table F: Viscosity Measurements

10

Sample	Viscosity (cps)
1	22000
2	22000
3	26000
4	31000
5	31000
6	23000
7	22000
8	18000
9	28000
10	37000
11	25000
12	45000
13	51000
Base	21000
'286 (1)	47000
'286 (2)	62000
Scrubbing Bubbles	41000

Test Methods5 Surface Spreading Method

The "transport rate factor" is measured as described below.

10 A 12" X 12" pane of frosted or etched glass is mounted in a flat-bottomed basin that is large enough to support the pane of glass. The basin is provided with a means for drainage such that water does not accumulate on the surface of the pane of glass as the experiment is
15 performed at a room temperature of approximately 22 oC in ambient conditions. The pane of glass is supported on top of the bottom of the basin of water using 4" X by 4" ceramic tiles - one tile at each side of the bottom edge of the pane. The middle 4 inches of the pane is not
20 touching the bottom, so that water can run down and off the glass pane. The pane of glass is juxtaposed such that pane of glass is at an angle of approximately 39° from the bottom of the basin.

25 The glass pane is provided with 0.5 inch measurement markers from a first edge to the opposing edge.

A glass funnel (40 mm long X 15 mm ID exit, to contain > 100 ml) is provided approximately 3.5" over the 9" mark
30 of the pane of glass.

-39-

The pane of glass is cleaned with room temperature water to remove trace surface active agents. The cleaned pane of glass is rinsed until there is no observable wave spreading on the pane.

5

A sample of approximately 7 g. (approximately 1.5" diameter circle for gels) of composition is applied to the pane of glass at the 0 mark. Four beakers (approximately 200 mL each) of water (are slowly poured over the top of the glass pane at the 9" height point and is allowed to run down the pane of glass to condition the composition.

After about one minute, the funnel is then plugged and is provided with approximately 100 mL of water. An additional 100 mL of water is slowly poured onto the glass pane at approximately the 9" marker. After approximately 10 seconds, the stopper is removed and a timer is started as the water in the funnel drains onto the pane of glass.

A wave on the surface of the draining water film above the composition is observed to creep up the glass and the time for the composition to reach the 5" marker is recorded.

The test is repeated for 10 replicates and the time in seconds is averaged and reported as the "transport rate factor" (time in seconds).

30

-40-

Adhesion Test

5 The ability of a composition to adhere to an exemplary hard surface is measured as described below.

A workspace is provided at a temperature of from about 86 °F to about 90 °F. The relative
10 humidity of the workspace is set to from about 40% to about 60%.

A board comprising twelve 4.25" X 4.25" standard grade while glossy ceramic tiles arranged in a 3 (in the y-
15 direction) X 4 (in the x-direction) configuration (bonded and grouted) to a plexi-glass back is provided.

The board is rinsed with warm (about 75 °F to about 85 °F) tap water using a cellulose sponge. The board is then
20 re-rinsed thoroughly with warm tap water. A non-linting cloth (ex. Kimwipe®, Kimberly Clark Worldwide, Inc., Neenah, WI) saturated with isopropanol is used to wipe down the entire tile board.

25 The board is juxtaposed to be in a horizontal position (i.e., such that the plane of the board is flat on the floor or lab bench).

Samples approximately 1.5" in diameter and weighing from
30 about 5.5 g to about 8.0 g are provided to the surface of the board such that the bottom of the sample touches the top-most, horizontally oriented (i.e., in the x-

-41-

direction), grout line of the board. Samples are spaced approximately 2" apart from each other. A permanent marker is used to draw a straight line (parallel to the x-direction) approximately 0.75" below the top-most grout
5 line.

The board is juxtaposed to then be in the vertical position (i.e., such that the plane of the board is perpendicular with the floor or lab bench). A timer is
10 started as the board is moved to the vertical position. The time that a sample takes for the sample to slide down the tile a distance of about 1.5 times the diameter of the sample is measured, recorded as the "sample adhesion time."
15

Viscosity Test

A Brookfield temperature controlled Cone/Plate Viscometer (Brookfield Engineering Laboratories, Inc., Middleboro,
20 MA) is used according to the manufacturer's specifications. The specific parameters used on the device are: Shear rate of 10; C-25-1 Cone; and an 80 °C to 25 °C temperature ramp-down for 240 seconds. The device provides the viscosity measurement in centipoise
25 (cps).

Gel Temperature Test

A Brookfield temperature controlled Cone/Plate Viscometer
30 (Brookfield Engineering Laboratories, Inc., Middleboro, MA) is used according to the manufacturer's specifications. The specific parameters used on the

-42-

device are: Shear rate of 10; C-25-1 Cone; and an 80 °C
to 25 °C temperature ramp-down for 240 seconds. The gel
temperature is reported as the temperature at which the
composition transitions to a viscosity of greater than
5 100 cps as the composition cools.

Example 1: Transport Along Water Film

To illustrate the surprising range and speed of the
10 Marangoni effect provided by the composition of the
invention, an experiment is described below.

A conventional white toilet bowl (Kohler Co., Kohler, WI)
is cleaned twice using a conventional cleaner ("The
15 Works" Toilet and Bathroom Cleaner (20% HCl)) and brush
to insure that no material is present on the ceramic
surface of the toilet bowl. A 5% solution of blue dye in
water is sprayed onto the surface of the toilet bowl to
provide an essentially even blue coating over the entire
20 bowl surface above the water line. The dye remains a
substantially uniform blue and is substantially
stationary and non-moving upon visual observation for
about one minute. The toilet is flushed and the dye
rinsed away.

25

A sample of composition weighing approximately 7 g. as
set out above as "Sample 2" is applied as a single dollop
to one location in an upper side of the toilet bowl above
the water line. The toilet is flushed so water runs down
30 over the composition and along the inside surface of the
toilet. Thereafter, the blue dye solution was again
sprayed over the toilet bowl surface to cover the entire

-43-

area above the water line as indicated by the blue color. Upon visual observation for about two minutes, it is observed that the blue dye moved away from the applied composition in all directions by material emanating from
5 the composition as evident by the now visual white surface of the bowl. By the end of two minutes, the composition covered approximately one half of the bowl surface as evident from the essential absence of blue dye from the surface. Without wishing to be limited by
10 theory, it is thought that the spread of the composition occurred through the Marangoni effect.

Due to the spread of the composition over the bowl, the desired action sought by the active agent(s) (e.g.
15 cleaning, disinfecting and/or fragrancing) present in the composition is achieved over an extended area and provides residual benefit on the surface to prevent build up from subsequent use and prevent water stains.

20 Example 2: Effect of Mineral Oil on Adhesion of Gel Compositions

Samples of compositions (approximately 7 g.) according to the present invention containing 0, 0.1, 0.5 and 1 wt.%
25 (Samples E-H, respectively) are tested according to the Adhesion Test Method described herein. Two trials of each of Samples E-H is applied to a tile board according to the adhesion test method described below. FIGS. 2A-E are photographs of the tile board at times of 8.5 hours,
30 9.5 hours, 11 hours, 12.5 hours, and 15 hours, respectively. Surprisingly, it is discovered that the compositions with a relatively lower wt.% mineral oil

-44-

tend to have lower adhesion times than samples with a relatively higher wt.% mineral oil.

The exemplary embodiments herein disclosed are not
5 intended to be exhaustive or to unnecessarily limit the scope of the invention. The exemplary embodiments were chosen and described in order to explain the principles of the present invention so that others skilled in the art may practice the invention. As will be apparent to
10 one skilled in the art, various modifications can be made within the scope of the aforesaid description. Such modifications being within the ability of one skilled in the art form a part of the present invention.

15 It is noted that terms like "specifically," preferably," "typically," "generally," and "often" are not utilized herein to limit the scope of the claimed invention or to imply that certain features are critical, essential, or even important to the structure or function of the
20 claimed invention. Rather, these terms are merely intended to highlight alternative or additional features that may or may not be utilized in a particular embodiment of the present invention. It is also noted that terms like "substantially" and "about" are utilized
25 herein to represent the inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, or other representation.

The dimensions and values disclosed herein are not to be
30 understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both

-45-

the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "50 mm" is intended to mean "about 50 mm."

5 All documents cited in the Detailed Description of the invention are, in relevant part, incorporated herein by reference; the citation of any document is not to be construed as an admission that it is prior art with respect to the present invention. To the extent that any
10 meaning or definition of a term in this written document conflicts with any meaning or definition of the term in a document incorporated by reference, the meaning or definition assigned to the term in this written document shall govern.

15

20

25

30

-46-

CLAIMS

We claim:

5

1. A composition for use on a hard surface, the composition comprising:

(i) at least 7.5 wt.% of at least one surfactant selected;

10 (ii) a transport rate factor of less than about 55 seconds; and

(iii) an adhesion time of greater than about 8 hours.

15 2. A composition according to claim 1, the composition comprising a transport rate factor of from about 30 seconds to about 55 seconds.

20 3. A composition according to claim 2, the composition comprising a transport rate factor of from about 30 seconds to about 40 seconds.

25 4. A composition according to claim 1, the composition being selected from the group consisting of: gel and solid.

5. A composition according to claim 1, the composition comprising from about 7.5 wt.% to about 20 wt.% surfactant.

30

-47-

6. A composition according to claim 1, the surfactant being selected from the group consisting of: anionic, non-ionic, cationic, amphoteric, zwitterionic, and combinations thereof.
- 5
7. A composition according to claim 6, wherein the surfactant is anionic.
8. A composition according to claim 1, the composition further comprising a viscosity of from about 15,000 cps to about 100,000 cps.
- 10
9. A gel composition for use on a hard surface, the composition comprising:
- 15 (i) less than 6 wt.% fragrance; and
(ii) a transport rate factor of less than about 55 seconds.
10. A gel composition according to for claim 9, wherein the composition comprising a transport rate factor of from about 30 seconds to about 55 seconds.
- 20
11. A gel composition according to claim 9, the composition further comprising a viscosity of from about 15,000 cps to about 100,000 cps.
- 25
12. A gel composition according to claim 9, the composition further comprising a gel temperature of from about 50 °C to about 80 °C.

30

-48-

13. A gel composition according to claim 9, the composition further comprising a surfactant selected from the group consisting of: anionic, non-ionic, cationic, amphoteric, zwitterionic, and combinations thereof.

5

14. A solid composition for use on a hard surface, the composition comprising:

(i) less than 10 wt.% fragrance; and

(ii) a transport rate factor of less than about 55 seconds.

10

15. A composition according to claim 14, wherein the composition comprising a transport rate factor of from about 30 seconds to about 55 seconds.

15

16. A composition according to claim 14, wherein the composition is self-adhesive.

17. A gel composition according to claim 14, the composition further comprising a viscosity of from about 15,000 cps to about 100,000 cps.

20

18. A gel composition according to claim 14, the composition further comprising a gel temperature of from about 50 °C to about 80 °C.

25

19. A gel composition according to claim 14, the composition further comprising a surfactant selected from the group consisting of: anionic, non-ionic, cationic, amphoteric, zwitterionic, and combinations thereof.

30

-49-

20. A composition for use on a hard surface, the composition comprising:

- (i) at least 7.5 wt.% of at least one surfactant;
- (ii) less than about 10 wt.% fragrance; and
- 5 (iii) a transport rate factor of less than about 55 seconds.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E