



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G01R 31/36	A2	(11) International Publication Number: WO 00/45189 (43) International Publication Date: 3 August 2000 (03.08.00)
(21) International Application Number: PCT/SE00/00141 (22) International Filing Date: 24 January 2000 (24.01.00) (30) Priority Data: 60/117,497 27 January 1999 (27.01.99) US 09/466,654 20 December 1999 (20.12.99) US (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventors: BIRKLER, Jörgen; N. Skolgatan 29 B, S-214 22 Malmö (SE). AHLGREN, Kristina; V. Rönneholmsvägen 42A, S-217 41 Malmö (SE). SVENSSON, Magnus; Skansg. 5, S-211 32 Malmö (SE). WENDELUP, Heino; Rolfsgatan 12 C, S-214 34 Malmö (SE). HEYL, Christian; Mossavägen 30, S-247 32 Södra Sandby (SE). (74) Agent: ERICSSON MOBILE COMMUNICATIONS AB; IPR Department, S-221 83 Lund (SE).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: POWER CONSUMPTION REPORTING BY AN ACCESSORY OF AN ELECTRONIC DEVICE		
(57) Abstract A method, system, and apparatus enables an electronic device in communication with an accessory to accurately report a remaining battery life when the accessory provides information relating to a power usage to the electronic device. In one embodiment, the accessory draws power from a battery of the electronic device, and the electronic device is able to more accurately estimate a remaining battery life by considering the power usage information provided from the accessory. The electronic device may thereafter indicate to a user the remaining battery life. In one alternative of this embodiment, the information relating to the power usage is in the form of a current consumption of the accessory. In another embodiment, the electronic device indicates a remaining battery life of a battery of an accessory.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

POWER CONSUMPTION REPORTING BY AN ACCESSORY
OF AN ELECTRONIC DEVICE

BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates in general to the field of power consumption in portable electronic devices, and in particular, by way of example but not limitation, to determining remaining battery power when one or more accessories is connected to a mobile terminal or other electronic device.

Description of Related Art

Many types of electronic devices utilize battery power instead of or in addition to A/C power from a socket. For example, laptop computers, mobile terminals, camcorders, etc. usually operate on battery power. Some of these electronic devices (e.g., especially mobile terminals) attempt to communicate to the user the time remaining for which the electronic device may be operated using the current battery before the battery is completely (or virtually completely) depleted.

Users of mobile terminals and other electronic devices typically wish to know the operational time remaining with an installed battery in order to plan properly for the eventual depletion of the battery and consequential loss of functioning of the device. For example, a user of a mobile terminal may wish to finish a current call, reach a destination in a car, transmit a

document, or otherwise properly budget the remaining battery life in order to meet a desired objective. A user of a camcorder, as an additional example, may wish to complete the recording of a special event, the viewing of a tape at a remote location, etc.

Providing a user with an accurate estimate of remaining battery life requires that a current power drain be determined. Unfortunately, this determination can be difficult, especially as the number and type of power drains on a battery of an electronic device proliferate. There is therefore a need, that is heretofore unrecognized (much less satisfied), to determine an accurate current drain on a battery of an electronic device when the electronic device is connected to one or more accessories that also draw power from the battery of the electronic device in order for the remaining battery life to be accurately predicted. There is also a need, that is heretofore unrecognized (much less satisfied), to report a remaining battery life of a battery of an accessory, especially for those accessories that lack any ability to directly communicate a remaining battery life to a user.

SUMMARY OF THE INVENTION

The deficiencies of the prior art are overcome by the method, system, and apparatus of the present invention. For example, as heretofore unrecognized, it would be beneficial if an electronic device were aware of the current drain by a connected accessory in order to properly estimate an operational time remaining for the battery of the electronic device. In fact, it would be beneficial if the accessory connected to the electronic

device communicated to the electronic device information representative of the current drain by the connected accessory.

5 In one embodiment, the accessory(ies) are connected to an electronic device and derive power from a battery of the electronic device. The accessory reports information regarding the power consumed by the accessory to the electronic device. The electronic device may then include the information in a determination of remaining battery
10 life, which may be subsequently communicated to the user. In one alternative of this embodiment, the accessory monitors its operational parameters and derives a current draw therefrom. This current draw is reported to the electronic device. Other alternatives are described below
15 in the Detailed Description.

In another embodiment, accessory(ies) are connected to an electronic device, but the accessory(ies) have access to an independent power supply (e.g., include their own battery). If the accessory does not have an ability
20 to directly communicate to a user the remaining battery life of its battery, then the accessory may communicate information regarding the remaining battery life to the electronic device, which subsequently communicates the remaining battery life of the accessory to the user. This
25 information may be in any of many forms, as explained in greater detail below.

The technical advantages of the present invention include, but are not limited to, the following. It should be understood that particular embodiments may not involve
30 any, much less all, of the following exemplary technical advantages.

An important technical advantage of the present invention is that it enables a more accurate estimate of remaining battery life of an electronic device.

5 Another important technical advantage of the present invention is that it provides the ability to estimate the total power consumption for both the electronic device and an accessory connected to the electronic device.

10 Yet another important technical advantage of the present invention is that it improves the estimation of standby time in, for example, a mobile terminal electronic device.

Yet another important technical advantage of the present invention is the ability to optimally communicate to a user the remaining battery life for an accessory that
15 may be unable to directly communicate the remaining battery life to the user.

The above-described and other features of the present invention are explained in detail hereinafter with reference to the illustrative examples shown in the
20 accompanying drawings. Those skilled in the art will appreciate that the described embodiments are provided for purposes of illustration and understanding and that numerous equivalent embodiments are contemplated herein.

It shall be emphasized that the term
25 "comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps, components, etc., but the term does not preclude the presence or addition of one or more other features, integers, steps, components, groups thereof,
30 etc.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and system of the present invention may be had by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

FIGURE 1 illustrates an exemplary diagram of a mobile terminal connected to an exemplary accessory in accordance with the present invention;

FIGURE 2 illustrates exemplary internal circuitry of an exemplary mobile terminal in accordance with the present invention;

FIGURE 3A illustrates exemplary functional blocks of one exemplary mobile terminal in accordance with the present invention;

FIGURE 3B illustrates exemplary functional blocks of one exemplary accessory in accordance with the present invention;

FIGURE 3C illustrates exemplary functional blocks of another exemplary mobile terminal in accordance with the present invention;

FIGURE 3D illustrates exemplary functional blocks of another exemplary accessory in accordance with the present invention;

FIGURE 3E illustrates an exemplary memory element of the exemplary mobile terminal of FIGURE 3C in accordance with the present invention;

FIGURE 3F illustrates an exemplary memory element of the exemplary accessory of FIGURE 3D in accordance with the present invention;

FIGURE 4A illustrates an exemplary sequence diagram of signals/information exchanged between a mobile terminal

and an accessory in accordance with one embodiment of the present invention;

FIGURE 4B illustrates an exemplary command structure for exchanging signals/information between the mobile terminal and the accessory of FIGURE 4A in accordance with
5 certain embodiments of the present invention;

FIGURE 5 illustrates an exemplary method in flowchart form for accurately computing a remaining battery life in accordance with one embodiment of the present invention;

10 FIGURE 6A illustrates exemplary functional blocks of an exemplary accessory in accordance with another embodiment of the present invention; and

FIGURE 6B illustrates an exemplary method in flowchart form of the embodiment of FIGURE 6A in
15 accordance with the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

In the following description, for purposes of explanation and not limitation, specific details are set forth, such as particular circuits, logic modules
20 (implemented in, for example, software, hardware, firmware, etc.), techniques, etc. in order to provide a thorough understanding of the invention. However, it will be apparent to one of ordinary skill in the art that the present invention may be practiced in other embodiments
25 that depart from these specific details. In other instances, detailed descriptions of well-known methods, devices, logical code (hardware, software, firmware, etc.), etc. are omitted so as not to obscure the description of the present invention with unnecessary
30 detail.

A preferred embodiment of the present invention and its advantages are best understood by referring to FIGURES 1-6B of the drawings, like numerals being used for like and corresponding parts of the various drawings.

5 A deficiency with regard to an electronic device determining only the power that it consumes when estimating remaining battery life is that some accessories also use the electronic device's battery as a power supply. When the electronic device does not know how much
10 current the accessory(ies) consume(s), the accuracy of the estimated power consumption will consequently be too low. Certain embodiments of the present invention enable the estimation of the total power consumption for both the electronic device and an accessory connected to it.

15 It should be understood that although exemplary embodiment(s) are described in terms of a mobile terminal (e.g., a wireless mobile station, a computer with a wireless link, etc.), the present invention is equally applicable to electronic devices in general. Furthermore,
20 aspects of the Global System for Mobile Communications (GSM) wireless network standard will be used to describe an embodiment of the present invention. However, it should be understood that the principles of the present invention are applicable to (in addition to other wireless
25 communication standards (or systems)) electronic devices in general, including those that are battery-powered and to which accessories sharing the battery of the electronic device may be connected.

 It should be noted that accessories for a mobile
30 terminal may include, but are not limited to, portable handsfree implements, infrared (IR) plugs, vibrating notification implements, etc. It should also be noted

that the accessory (e.g., a pager, etc.) may alternatively be physically located within the housing of a battery that supplies power to the mobile terminal or other electronic device and is removably attached thereto.

5 In one embodiment, the accessory or accessories report how much power they are consuming to the electronic device. Each accessory that is consuming power from the battery of the electronic device reports this to the electronic device. The information may, for example, be
10 sent with AT commands, as described further below. Whenever the current power consumption of the accessory changes, a new report may be issued to the electronic device. Also, the accessory may send the mean value of the power consumption at some regular time interval. The
15 accessory may derive its power consumption information by monitoring its operational parameters and knowing the corresponding current required for each operation.

Referring now to FIGURE 1, an exemplary diagram of a mobile terminal 110 connected to an exemplary accessory
20 150 in accordance with the present invention is illustrated generally at 100. Although the mobile terminal 110 is illustrated as a hand-held mobile phone, the present invention is not to be so limited. The mobile terminal 110 includes an antenna 115, a speaker 120, a
25 display 125, a keypad 130, and four connection/interface points/ports 135 (e.g., an external connector with one or more input pins). Two of the four connection points 135 are power connection points 135c and 135d, and two of the connection points are communication connection points 135a
30 and 135b. It should be understood that the connection points 135 may number more or less than the four shown. Likewise, the number of communication and power connection

points 135a,135b and 135c,135d may be more or less than the two shown.

The accessory 150 may be, for example, an infrared adaptor unit, a portable hands-free unit, a vibrating
5 notification mechanism, etc. The accessory 150 is also shown as having four connection points 155, two of which are for communication (155a,155b) and the other two of which are for power (155c,155d). It should be understood that the accessory unit 150 may also have more or less
10 than four connection points 155, and they may be distributed differently. In other words, the connection points 155 may also be for another use (e.g., in addition to communication and power). Furthermore, the number of communication points 155a,155b (or, e.g., power points
15 155c,155d) may be more than or less than the two shown, for example. The accessory 150 may communicate with the mobile terminal 110 over communication connection lines 195a,195b. The accessory 150, in an embodiment, receives power from a battery (not shown in FIGURE 1) of the mobile
20 terminal 110 over power connection lines 195c,195d.

Referring now to FIGURE 2, exemplary internal circuitry for an exemplary mobile terminal 110 in accordance with the present invention are illustrated. The various exemplary circuitry may be interconnected via
25 one or more buses 205. The internal circuitry include a battery 210 that is connected to the power connection points 135c,135d and to the other internal circuitry. They also include an input/output unit 215 connected to the communication connection points 135a,135b. Also
30 included are a transceiver (TRX) 220, the speaker 120, the display 125, the keypad 130, a microphone 225, and perhaps various other circuits (represented generally at 230).

The mobile terminal 110 also includes one or more processors 235 and one or more memories 240. Within the memory 240, in accordance with one embodiment of the present invention, a battery life application part 245 is
5 stored. The battery life application part 245 may be, for example, encoded in hardware, software, firmware, or any combination thereof. The internal circuitry may also include a battery detector 250. The battery detector 250 includes an ability, among others, to determine a
10 remaining total charge in the battery 210 and the current power drain of the battery 210 from internal circuitry of the mobile telephone 110.

Referring now to FIGURE 3A, exemplary functional blocks of one exemplary mobile terminal in accordance with
15 the present invention are illustrated. The functional blocks of FIGURE 3A include a power source 305 (e.g., the battery 210 of FIGURE 2) connected to the power connection points 135c,135d and a communication unit 310 connected to the communication connection points 135a,135b. They also
20 include various internal power sinks 315 that are connected to the power source 305 and drain the power therefrom. The battery detector 250 (of FIGURE 2) may correspond to a battery level determiner functional block 320 as well as an (internal) power draw determiner
25 functional block 330. The battery level determiner 320 may determine the total charge remaining within the power source 305. The battery level determiner 320 may also include (or otherwise be associated with) a rate of change determiner functional block 325 that determines the rate
30 at which the charge remaining in the power source 305 is being drained. The internal power draw determiner 330 may determine the power being drawn from internal circuitry

by, for example, measuring the rate of consumption of current (e.g., in (milli)amps) by the internal circuitry (e.g., jointly (measure current draw by entire set of internal circuitry at once), piece-meal (measure one or
5 more internal circuits sequentially or in parallel and then sum), etc.). The functional blocks of the mobile terminal 110 may also include a battery life remaining computational unit(s) 335. The computational unit(s) 335 may be realized as part of the battery life application
10 part 245, the memory 240, and the processors 235 (as shown in FIGURE 2). Alternatively, the computational unit(s) 335 may be, for example, a separate set of firmware along with a digital signal processor (DSP).

Referring now to FIGURE 3B, exemplary functional
15 blocks of one exemplary accessory in accordance with the present invention are illustrated. The exemplary functional blocks include accessory sinks 355, which draw power from the power source 305 of the mobile terminal 110 (e.g., via the power connection points 155c,155d of the
20 accessory 150, the power connection lines 195c,195d, and the power connection points 135c,135d of the mobile terminal 110). They also include an accessory power draw determiner functional block 360. The accessory power draw determiner 360 may determine the power being extracted
25 from the power source 305 of the mobile terminal 110 by, for example, measuring a consumption of current (e.g., in (milli)amps). The exemplary accessory 150 may also include a communication unit 365. The communication unit 365 of the accessory 150 communicates (e.g., via the
30 communication connection points 155a,155b of the accessory 150, the communication connection lines 195a,195b (of FIGURE 1), and the communication connection points

135a, 135b of the mobile terminal 110) to inform the mobile terminal 110 of the current power draw of the accessory 150 (e.g., in current as measured in (milli)amps).

When the present invention is realized in conjunction
5 with a mobile terminal as illustrated in FIGURES 1-3, the remaining standby time of the mobile terminal is very important information to provide to the user. As alluded to above, it is especially difficult to produce an accurate prediction because the power consumption varies
10 all of the time (e.g., as a result of the distance between the mobile terminal and a base station). Nevertheless, the remaining standby time may be estimated in any of a number of ways. The technique addressed above with reference to FIGURES 3A and 3B measures the current power
15 consumption and, from that measurement, calculates the remaining standby time. This has, however, a side effect: power is "lost" in the measuring circuits (e.g., the (internal) power draw determiner 330 and the power draw determiner 360). An alternative technique is to calculate
20 power consumption by knowing current operation parameters (e.g., transmitter power, lights on/off, and so on). In other words, the current power consumption may be calculated from system operational parameters. From this calculation, the power consumption of only the mobile
25 terminal itself is obtained absent the teachings of the present invention. However, this alternative may be extended to the accessory connected to the mobile terminal in accordance with the present invention.

Referring now to FIGURE 3C, exemplary functional
30 blocks for another exemplary mobile terminal in accordance with the present invention are illustrated. In the mobile terminal 110 (of FIGURE 3C), the (internal) power draw

determiner 330 (of FIGURE 3A) is replaced with an (internal) operational parameter determiner 330'.

Referring now to FIGURE 3D, exemplary functional blocks of another exemplary accessory in accordance with the present invention are illustrated. In the accessory 150 (of FIGURE 3D), the power draw determiner 360 (of FIGURE 3B) is replaced with an operational parameter determiner 360'.

Referring now to FIGURE 3E, an exemplary memory element of the exemplary mobile terminal of FIGURE 3C in accordance with the present invention is illustrated generally at 370. The memory element 370, which is part of the mobile terminal 110 (of FIGURE 3C), may be, for example, nonvolatile random access memory that is read-only, re-writable memory, etc. The memory element 370 links various operational parameters of the mobile terminal 110 with the associated current draw. For example, a backlighting that is on may be associated with "x" mA.

Referring now to FIGURE 3F, an exemplary memory element of the exemplary accessory of FIGURE 3D in accordance with the present invention is illustrated generally at 375. The memory element 375, which is part of the accessory 150 (of FIGURE 3D), may be, for example, nonvolatile random access memory that is read-only, re-writable memory, etc. The memory element 375 links various operational parameters of the accessory 150 with the associated current draw and/or current code. For example, a given processing state for the accessory 150 may be associated with "y" mA and/or "z" code. The current code may be provided to the mobile terminal 110 in lieu of the current draw if, for example, the memory

element 370 includes an entry linking the current code of the accessory 150 to a current draw.

Referring now to FIGURE 4A, an exemplary sequence diagram of signals/information exchanged between a mobile terminal and an accessory in accordance with one embodiment of the present invention is illustrated generally at 400. The accessory 150 may (optionally) begin the exchange with an "AT*ECUR=?" signal/information (e.g., command, request, etc.) 410 transmitted to the mobile terminal 110. Referring now to FIGURE 4B, an exemplary command structure for exchanging signals/information between the mobile terminal and the accessory of FIGURE 4A in accordance with the present invention is illustrated generally at 450.

Specifically, an exemplary "AT*ECUR" command structure 450 that may be used in accordance with the principles of the present invention is illustrated. An exemplary command syntax is shown at 460. This command may be used to report to the mobile terminal the current consumption for a connected device (e.g., an accessory). The current value reported may be used to adjust the mobile terminal's charging parameters or to determine a total current drain. When the external device is connected, for example, the AT command may be initially generated. It may also be sent, for example, if the externally connected device changes current consumption. Furthermore, it may also be sent as a mean value at regular intervals. One command communicates the current consumption information while another command determines whether the "AT*ECUR" command is supported. Each command may cause either an "OK" or an "ERROR" response. An exemplary "<mamp>:parameter" definition is shown at 470.

This "AT*ECUR" command may be used to report to the mobile terminal the current consumption for a connected device as an integer. Dividing the reported integer by "10" provides the current consumption in milliamps, in this
5 exemplary embodiment. An example of an "AT*ECUR" command exchange communicating 12 mA from the connected device (e.g., accessory 150) to the mobile terminal 110 is shown at 480. It should be noted that the constant "10" may be any number, and that it depends, for example, on the
10 actual physical limitations and needs of a given apparatus or system.

Continuing now with FIGURE 4A, the mobile terminal 110, if configured in accordance with the present invention, may respond with an "OK" affirmative
15 signal/information 420. If the mobile terminal 110 is not so configured or fails to understand the request, the mobile terminal 110 may respond with an "ERROR" indication. If, however, the mobile terminal 110 responds with "OK", the accessory 150 then transmits an
20 "AT*ECUR=<mamp>" signal/information 430 to the mobile terminal 110. The "<mamp>" variable may correspond to, in one embodiment, the consumption of current (e.g., in amperage). The mobile terminal 110 responds with an "OK" signal/information 440 to the accessory 150 if the current
25 consumption was successfully received and understood. If the mobile terminal 110 does not understand a communication from the accessory 150, the mobile terminal 110 may transmit an "ERROR" indication. The signal/information 430 may be transmitted when, for
30 example, the accessory 150 is initially connected to the mobile terminal 110. Furthermore, the information/signal 430 may be transmitted whenever the current consumption of

the accessory 150 changes, at regular intervals in the form of a mean value, etc.

In another embodiment, the signal/information 430 may be transmitted to the mobile terminal 110 from the accessory 150 whenever the mobile terminal 110 requests such current consumption information/signal. In yet another embodiment, the accessory 150 may (e.g., as per an earlier request from the mobile terminal 110, automatically, etc.) transmit the current consumption information/signal 430 at periodic (e.g., scheduled, etc.) intervals.

Referring now to FIGURE 5, an exemplary method in flowchart form for accurately computing a remaining battery life in accordance with one embodiment of the present invention is illustrated generally at 500. An accessory is connected to an electronic device (block 510). In response, in this example, the accessory responds by transmitting a current consumption of the accessory to the electronic device (block 520). It should be noted that in block 520 the accessory may transmit any energy-related indicator(s). For example, instead of (or in addition to) current consumption, the accessory may transmit any general power-related consumption information, a set of operating parameters (e.g., in the form of a code, etc.) from which the electronic device (e.g., the mobile terminal 110) may calculate an energy consumption (e.g., because the mobile terminal 110 stores information linking a particular operating parameter with a particular energy consumption). In such alternative embodiments, the electronic device may determine current consumption from the received energy-related indicator(s).

The electronic device determines an internal current consumption (e.g., by measuring a current draw, by knowing current draw(s) of active operational parameter(s), etc.) (block 530). The electronic device includes both the
5 accessory current consumption and the internal current consumption in the calculation(s) for total current consumption (block 540). The electronic device then computes remaining battery life (block 550). The remaining battery life is subsequently displayed by the
10 electronic device (block 560). It should be noted that in block 560 the electronic device (e.g., a mobile terminal) may provide notification to the user in a manner other than a visual display. For example, the electronic device may vibrate at a predetermined level of remaining battery
15 time, it may sound a characteristic audible noise (e.g., such as a predetermined tone or a predetermined number of beeps, etc.), etc. In this example, if the accessory changes current consumption (and so notifies the electronic device) (at block 570), the method of the
20 flowchart 500 may return to block 520. If, on the other hand, the accessory does not change current consumption (at block 570), the method of the flowchart 500 may return to block 530.

Referring now to FIGURE 6A, exemplary functional
25 blocks of an exemplary accessory in accordance with another embodiment of the present invention is illustrated generally at 600. In this embodiment, the accessory may also have a battery 605. The accessory 600 may have no ability to directly communicate to a user the amount of
30 time remaining for the battery 605 to supply power. Consequently, in this embodiment, the accessory 600 transmits to a connected mobile terminal (not explicitly

shown) or any general electronic device information related to a remaining power supply. The transmission may be sent from the communication connection points 155a,155b to the mobile terminal. Especially in this
5 embodiment, the communication connection points 155a,155b may be realized (in addition to mechanical, metallic connection points, etc.) as an IR input/output port, a short range radio frequency transceiver (e.g., a Bluetooth transceiver), etc. The accessory may also include a power
10 draw determiner 360 and/or an operational parameter determiner 360' (e.g., along with a memory element 375) in order to determine a power consumption.

In one alternative of this embodiment, the information related to the remaining power supply may
15 correspond to the amount of time remaining in the life of the accessory's battery 605 so that the mobile terminal may communicate (e.g., display) the amount of time remaining in the life of the accessory's battery 605 to the user. In another alternative of this embodiment, the
20 accessory 600 may transmit the current consumption and (optionally) the remaining total charge in the battery 605 to the mobile terminal. The mobile terminal may thereafter determine the remaining life in the battery 605 and communicate such remaining life to the user.

25 Referring now to FIGURE 6B, an exemplary method in flowchart form of the embodiment of FIGURE 6A in accordance with the present invention is illustrated generally at 650. The accessory receives a command to report power information (block 655). The command may be
30 received from an electronic device, from a user directly commanding the accessory to report power information, from an integrated circuit internal to the accessory (e.g., at

regular intervals, when the current consumption changes, etc.), etc. The accessory reports power information to the electronic device (block 660). The power information may include remaining battery life, a total charge along
5 with a current consumption (e.g., as measured, as determined from operational parameters, etc.), a list of operational parameter(s), etc. After any appropriate calculation, memory look-up, etc. as needed, the electronic device indicates the remaining battery life to
10 the user (block 665). The indication may be, for example, visual, audible, feelable, etc.

Although preferred embodiment(s) of the method, system, and apparatus of the present invention have been illustrated in the accompanying Drawings and described in
15 the foregoing Detailed Description, it will be understood that the present invention is not limited to the embodiment(s) disclosed, but is capable of numerous rearrangements, modifications, and substitutions without departing from the spirit and scope of the present
20 invention as set forth and defined by the following claims.

WHAT IS CLAIMED IS:

1. A system for accurately determining remaining battery life for an electronic device, comprising:
an electronic device, said electronic device
5 including a battery and at least one logic module, said at least one logic module for computing remaining battery life;
at least one accessory, said at least one accessory operatively connected to said electronic device
10 and deriving power from said battery of said electronic device, said at least one accessory adapted for determining a current consumption of said at least one accessory and providing said current consumption of said at least one accessory to said electronic device; and
15 wherein said at least one logic module computes said remaining battery life based, at least in part, on said current consumption of said at least one accessory.
2. The system according to Claim 1, wherein said electronic device comprises a mobile terminal.
- 20 3. The system according to Claim 1, wherein said at least one logic module computes said remaining battery life based, at least in part, on said current consumption of said at least one accessory and an internal current consumption of said electronic device.
- 25 4. The system according to Claim 3, wherein said internal current consumption of said electronic device is determined by measuring.

5. The system according to Claim 3, wherein said internal current consumption of said electronic device is determined by considering at least one internal operation parameter, said at least one internal operation parameter comprising at least one of transceiving power, display status, and keypad lighting status.

6. The system according to Claim 1, wherein said electronic device further includes at least one memory element, said at least one memory element having at least one entry that links at least one operational parameter to a corresponding current consumption.

7. The system according to Claim 6, wherein said at least one operational parameter corresponds to an operational parameter of said at least one accessory.

8. The system according to Claim 6, wherein said at least one operational parameter corresponds to an operational parameter of said electronic device.

9. The system according to Claim 1, wherein said at least one accessory includes at least one memory element, said at least one memory element having at least one entry that links at least one operational parameter to a corresponding current consumption.

10. A method for accurately determining remaining battery life for an electronic device, comprising the steps of:

transmitting a power consumption of an accessory from said accessory to an electronic device, said electronic device having a battery; and

calculating a remaining life of said battery based, at least in part, on said power consumption of said accessory.

11. The method according to Claim 10, further comprising the step of:

determining a power consumption of said electronic device; and

wherein said step of calculating a remaining life of said battery based, at least in part, on said power consumption of said accessory further comprises the step of calculating said remaining life of said battery based, at least in part, on said power consumption of said electronic device.

12. The method according to Claim 10, further comprising the step of:

presenting said remaining life of said battery via an output of a man-machine interface (MMI) of said electronic device.

13. The method according to Claim 12, wherein said MMI of said electronic device comprises at least one of (i) a display and (ii) a recorded or a synthetic voice.

14. The method according to Claim 10, wherein said electronic device comprises a mobile terminal.

15. The method according to Claim 10, wherein said accessory comprises at least one of an infrared adapter unit, a portable handsfree unit, a vibrating notification unit, a radio frequency transceiver, and a Bluetooth adapter.

16. The method according to Claim 10, wherein said step of transmitting a power consumption of an accessory from said accessory to an electronic device comprises the step of transmitting a current consumption.

17. The method according to Claim 10, wherein said step of transmitting a power consumption of an accessory from said accessory to an electronic device comprises the step of transmitting said power consumption using a predetermined command format.

18. The method according to Claim 17, wherein said predetermined command format comprises an AT command format.

19. The method according to Claim 10, wherein said step of transmitting a power consumption of an accessory from said accessory to an electronic device is performed when at least one of (i) accessory connection to said electronic device and (ii) accessory power consumption change occur.

20. The method according to Claim 10, further comprising the steps of:

monitoring, by said accessory, at least one operational parameter of said accessory;

5 detecting that said at least one operational parameter is in an active state; and

determining said power consumption based, at least in part, on said at least one operational parameter.

21. The method according to Claim 10, further comprising the steps of:

10 monitoring, by said accessory, at least one operational parameter of said accessory;

detecting that said at least one operational parameter is in an inactive state; and

15 determining said power consumption with considering said at least one operational parameter.

22. The method according to Claim 10, further comprising the steps of:

monitoring, by said electronic device, at least one operational parameter of said electronic device;

5 detecting that said at least one operational parameter is in an active state;

determining a power consumption of said electronic device based, at least in part, on said at least one operational parameter; and

10 wherein said step of calculating a remaining life of said battery based, at least in part, on said power consumption of said accessory further comprises the step of calculating said remaining life of said battery based, at least in part, on said power consumption of said
15 electronic device.

23. The method according to Claim 10, wherein said step of transmitting a power consumption of an accessory from said accessory to an electronic device comprises the step of transmitting a mean current consumption at regular
20 intervals.

24. A method for reporting remaining battery life of an accessory, comprising the steps of:

transmitting a power indication associated with a battery of an accessory from said accessory to an
25 electronic device, said electronic device having an interface; and

providing at least one of said power indication and a derivation of said power indication to a user of said electronic device using said interface.

25. The method according to Claim 24, wherein said power indication associated with said battery of said accessory comprises a duration of remaining life of said battery and said step of providing comprises the step of
5 providing said power indication to said user of said electronic device using said interface.

26. The method according to Claim 24, wherein said power indication associated with said battery of said accessory comprises at least one of a current consumption
10 of said accessory and a total charge of said battery and said step of providing comprises the step of providing said derivation of said power indication to said user of said electronic device using said interface.

27. The method according to Claim 24, wherein said
15 interface comprises a display and said step of providing at least one of said power indication and a derivation of said power indication to a user of said electronic device using said interface comprises the step of displaying said
at least one of said power indication and said derivation
20 of said power indication on said display of said electronic device.

28. The method according to Claim 24, further comprising the step of measuring a value to determine said power indication associated with said battery of said
25 accessory.

29. The method according to Claim 24, further comprising the steps of:

monitoring, by said accessory, at least one operational parameter of said accessory;

5 detecting that said at least one operational parameter is in an active state;

measuring a remaining charge of said battery;

and

10 determining said power indication associated with said battery of said accessory based, at least in part, on said at least one operational parameter and said remaining charge of said battery.

30. A system for reporting remaining battery life of an accessory, comprising:

15 an electronic device, said electronic device including an interface;

at least one accessory, said at least one accessory having a battery and being in communication with said electronic device, said at least one accessory adapted for determining a current consumption of said at least one accessory and providing said current consumption or a derivative thereof to said electronic device; and

20 wherein said electronic device indicates a remaining battery life of said battery to a user via said interface.
25

31. The system according to Claim 30, wherein said at least one accessory provides said derivative to said electronic device, said derivation comprising said remaining battery life of said battery.

32. The system according to Claim 30, wherein said
at least one accessory provides said current consumption
and a total remaining charge of said battery to said
electronic device, said electronic device determining said
5 remaining battery life of said battery therefrom.

33. The system according to Claim 30, wherein said
current consumption is measured by said at least one
accessory.

34. The system according to Claim 30, wherein said
10 current consumption is determined from monitoring at least
one operational parameter of said at least one accessory,
said at least one operational parameter known to
correspond to a predetermined current consumption.

35. An accessory for an electronic device,
15 comprising:

at least one power drain;
a monitoring unit, said monitoring unit adapted
to monitor an operational parameter associated with said
at least one power drain and to determine when said at
20 least one power drain is draining power; and

at least one memory element, said at least one
memory element including at least one entry linking said
operational parameter with a corresponding current
consumption.

36. The accessory according to Claim 35, further
25 comprising a communication unit, said communication unit
adapted to transmit said corresponding current consumption
to said electronic device.

37. The accessory according to Claim 35, further comprising:

a battery;

5 a calculation unit, said calculation unit adapted to determine a remaining battery life of said battery based, at least in part, on said corresponding current consumption; and

a communication unit, said communication unit adapted to transmit said remaining battery life of said
10 battery to said electronic device.

1/8




FIG. 1

2/8




FIG. 2




FIG. 3A




FIG. 3B

4/8




FIG. 3C




FIG. 3D

370


OPERATIONAL PARAMETER	Current Draw
⋮	⋮

FIG. 3E

375

OPERATIONAL PARAMETER	Current Draw or Code
⋮	⋮

FIG. 3F

**FIG. 4A**

EXEMPLARY COMMAND SYNTAX

450

460

Description	Command	Possible Responses
Reports the contemporaneous current consumption to the mobile terminal	AT*ECUR=<mamp>	• OK • ERROR
Indicates if the command is supported or not	AT*ECUR=?	• OK • ERROR

<mamp> : parameter

470

<mamp>	Description
integer	Number of milliamps, multiplied by 10. (e.g., a value of 12 milliamps is reported as "120".) Exemplary Range : 0–65535. NOTE: The range may also be bound by physical limitations


Example of an AT Command Exchange

480

AT Command	Response	Comment
AT*ECUR=120	OK	Report 12mA to the mobile terminal

FIG. 4B

7/8

**FIG. 5**




FIG. 6A




FIG. 6B