

(12) UK Patent Application (19) GB (11) 2 418 382 (13) A

(43) Date of A Publication 29.03.2006

(21) Application No: 0421362.5

(22) Date of Filing: 24.09.2004

(71) Applicant(s):
Mortimer Technology Holdings Limited
(Incorporated in the United Kingdom)
Ferndale Court, West End Road, Mortimer,
READING, Berkshire, RG7 3SY,
United Kingdom

(72) Inventor(s):
Christopher Edward Dodson

(74) Agent and/or Address for Service:
Boulton Wade Tennant
Verulam Gardens, 70 Gray's Inn Road,
LONDON, WC1X 8BT, United Kingdom

(51) INT CL:
B01J 8/00 (2006.01)

(52) UK CL (Edition X):
B2P P4

(56) Documents Cited:
GB 2177616 A EP 1452224 A1
EP 0513563 A1 DE 003245393 A
US 4668441 A
WPI Abstract Accession No. 1986-047634 &

(58) Field of Search:
INT CL⁷ **B01J**
Other: **ONLINE: WPI, JAPIO, EPODOC**

(54) Abstract Title: **Particle treatment in an expanded toroidal bed reactor**

(57) A method of processing a fluid and/or a particulate material, the method comprising the steps of:
(a) introducing the particulate material into a chamber 1;
(b) providing a flow of fluid into said chamber for entraining the particulate material; and
(c) removing processed fluid and/or particulate material from the chamber;
wherein the chamber comprises a processing zone having a substantially circular transverse cross-section, the fluid flow being introduced into the processing zone at an angle (α , fig.1) of between 10° and 75° with respect to a tangent of the substantially circular transverse cross-section of the processing zone to establish a fluid flow following a substantially helical path in the processing chamber. The apparatus per se is also claimed. The apparatus may, in another embodiment, have a plurality of channels (15, fig.6b) leading to a plurality of openings for introducing fluid into the chamber.




FIG. 2




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B

IMPROVED PARTICLE TREATMENT IN AN EXPANDED
TOROIDAL BED REACTOR

The present application relates to a method of
5 processing a particulate material. The present
application also relates to apparatus for processing a
particulate material.

Treatment of particulate material commonly uses a
fluid stream and more particularly a gaseous stream. The
10 particulate material may function as a catalyst,
absorption medium or as a source of reactants which react
with or are treated by the fluid stream. It has been
thought for some time that the best mode for treating
beds of particulate material is to fluidise the bed with
15 a gaseous stream.

European patent No. 0382769 describes an annular
processing zone for a circumferentially circulating
turbulent bed of material. The system is commonly sold
under the trade name TORBED (RTM) and has been used in a
20 variety of particulate treatment applications such as
metal ore treatment and roasting; catalyst and catalytic
particle treatment; drying of a particulate matter;
reacting particles with the gaseous streams; combustion,
gasification/pyrolysis of gases and/or solids; tablet
25 coating; coffee bean roasting and the like.

A method and apparatus for processing matter in a
turbulent mass of particulate material is further known
from EP0068853. This application discloses a processing
chamber into which a hot gas is introduced in a generally
30 tangential manner. The hot gas thereafter tends to
follow the interior of the wall of the processing
chamber. A particulate material is supplied into the
chamber and under the influence of the hot gas is

displaced to the wall of the chamber and is caused to flow in a turbulent manner. Perlite is added to the processing chamber and expands as it is heated. The hot gas and expanded perlite are exhausted from the
5 processing chamber together.

Apparatus and a method of producing ash are known from International patent application No. PCT/CA01/01852. The apparatus comprises a housing into which a feed material is introduced through a feed tube. Gas is
10 introduced through an inlet pipe provided at the base of the cylindrical housing. The gas passes through an annular guide consisting of a series of spaced blades arranged to cause the gas to leave the guide in the form of an inner vortex. This inner vortex moves vertically
15 through a mixing zone provided in the housing. An outer vortex is created by gas supplied from a second gas inlet provided at the top of the cylindrical housing.

A further process for processing particulate material is known from US 6,108,935. This process
20 introduces a circumferentially directed flow of fluid into an annular processing zone to develop a circulating turbulent bed of particles.

The inventors in the present case have recognised the desirability of establishing a processing zone which
25 provides for a predictable particle flow path, both circumferentially and helically, in the processing zone to ensure more uniform particle treatment and gas/solid mixing for a given residence time. The present invention, at least in preferred embodiments, attempts to
30 provide at least some of this functionality.

Viewed from a first aspect, the present invention provides a method of processing a fluid and/or a particulate material comprising the steps of:

- (a) introducing particulate material into a chamber;
 - (b) providing a flow of fluid into said chamber for entraining the particulate material; and
 - (c) removing processed fluid and/or particulate material
- 5 from the chamber;

wherein the chamber comprises a processing zone having a substantially circular transverse cross-section, the fluid flow being introduced into the processing zone at an angle of between 10° and 75° with respect to a

10 tangent of the substantially circular transverse cross-section of the processing zone to establish a fluid flow following a substantially helical path in the processing zone.

It has been recognised that the introduction of the

15 fluid flow into the processing zone within the above-referenced parameters is particularly suitable for establishing a uniform particle flow path. Thus, uniform particle treatment and gas/solid mixing may be achieved.

The processed particulate material and/or fluid may,

20 for example, be removed at predetermined time intervals.

The particulate material and fluid are in contact with each other in the processing zone.

The fluid flow upon entry into the processing zone may define an angle of between 20° and 60° ; or between

25 30° and 45° with respect to said tangent.

The fluid flow upon entry into the processing zone is preferably inclined upwardly at an angle between 5° and 45° ; between 10° and 40° ; between 15° and 35° ; or between 20° and 30° with respect to a horizontal plane.

30 The velocity of the fluid flow is preferably controlled so as to be greater than the terminal velocity of particulate material in the chamber.

The direction of the fluid flow may be developed by at least one nozzle or tube. Alternatively, the direction of the fluid flow is developed by at least one vane or deflector. Preferably, however, a plurality of
5 vanes, deflectors or tubes are employed.

The fluid flow in the chamber preferably causes the particulate material to undergo both vertical and horizontal displacement. Thus, the mixing of the particulate material with the fluid may be maximised
10 within the chamber.

Although the processing zone may be defined by the walls of the chamber, it is preferably formed by fluid flow in a central region of the chamber to allow particulate material to exit the processing zone and be
15 deposited radially outwardly of the processing zone. The deposited particulate material preferably forms a flowing bed. The chamber preferably has a base inclined downwardly towards the centre of the chamber to bias particulate material in the flowing bed back towards the
20 processing zone.

The processing zone is preferably annular or toroidal in shape. This may be achieved by providing a central conduit or pillar in the chamber, but is preferably implemented by the helical movement of the
25 fluid flow inside the chamber.

Although the fluid may be introduced into the side or the top of the processing zone, it is preferably introduced at the base thereof.

Although in certain arrangements it may be desirable
30 for the fluid to be a liquid, it is more usually a gas.

The helical fluid flow is preferably either conical or cylindrical.

The present application further relates to apparatus for processing a fluid and/or a particulate material, the apparatus comprising a chamber, means for introducing particulate material into the chamber, and at least one fluid inlet for introducing a flow of fluid into the chamber; wherein the chamber comprises a processing zone having a substantially circular transverse cross-section, and the at least one fluid inlet being adapted, in use, to introduce the fluid flow into the processing zone at an angle of between 10° and 75° with respect to a tangent of the substantially circular transverse cross-section of the processing zone.

The fluid inlet is preferably adapted to introduce the fluid flow into the processing zone at an angle between 5° and 45° ; between 10° and 40° ; between 15° and 35° ; or between 20° and 30° with respect to a horizontal plane.

The apparatus may further comprise a flow controller suitable for controlling the velocity of the fluid introduced into the chamber.

The apparatus preferably comprises at least one vane and/or at least one deflector for controlling the flow of the fluid as it is introduced into the chamber. Alternatively, or additionally, the apparatus may comprise at least one nozzle for determining the direction of the fluid flow as it is introduced into the chamber.

The chamber preferably has a base inclined downwardly towards the centre thereof. This arrangement advantageously causes a flowing bed to be formed at the base of the chamber when the apparatus is in use.

The at least one fluid inlet is preferably arranged such that the processing zone is formed in a central

region of the chamber. The at least one fluid inlet may be provided in a side portion or a top portion of the chamber, but it is preferably provided at the bottom thereof.

5 Viewed from a further aspect, the present application relates to an assembly for directing a flow of fluid into a processing zone of a processor, the assembly having a plurality of channels for guiding the flow of fluid through a plurality of openings to an
10 interior of the assembly, each of the channels being arranged, in use, to direct the flow of fluid into the processing zone at an angle less than 90° relative to a radial line extending from a longitudinal axis of the assembly to the respective opening.

15 The assembly preferably comprises a plurality of guide members and at least one of said channels is preferably provided in each of said guide members. Although the channels may be defined by holes extending through the guide member, the channels may also be formed
20 as recesses or slots in a surface thereof.

 The guide members may be fixedly mounted in a frame, such that the frame determines the orientation of each guide member. Each of the guide members may be provided with an alignment surface for abutment against an
25 adjacent like guide member. The alignment surfaces preferably determine the orientation of each guide member relative to said adjacent guide member. The alignment surface may thereby determine the orientation of the at least one channel formed in each guide member and, thus,
30 determine the direction of the flow of fluid relative to said radial line.

The channels are preferably arranged, in use, to direct the flow of fluid at an angle between 15° and 80° ; or between 30° and 70° relative to said radial line.

5 The channels are preferably arranged, in use, also to direct the flow of fluid at an angle inclined relative to a plane perpendicular to the longitudinal axis of the assembly. The flow of fluid, in use, will be inclined at an angle between 5° and 45° ; 10° and 40° ; 15° and 35° ; or between 20° and 30° relative to said plane.

10 The guide members may be arranged in an oval or elliptical arrangement about said longitudinal axis. Preferably, however, the guide members are arranged in a substantially circular arrangement such that the openings are all equal distant to the longitudinal axis of the
15 assembly.

Viewed from a still further aspect, the present application relates to an assembly for directing a flow of fluid into a processor, the assembly having a longitudinal axis and comprising a plurality of guide
20 members each having at least one channel formed therein; wherein each channel is arranged, in use, to guide the flow of fluid through a respective opening provided in the guide member to an interior of the assembly at an angle relative to a plane perpendicular to the
25 longitudinal axis of the assembly. The guide members are preferably formed separately.

The flow of fluid, in use, will preferably be inclined at an angle between 5° and 45° ; 10° and 40° ; 15° and 35° ; or between 20° and 30° relative to said plane.
30 The channels are preferably all inclined at substantially the same angle to said plane.

The channels are preferably arranged, in use, also to direct the flow of fluid at an angle less than 90°

relative to a radial line extending from a longitudinal axis of the assembly to the respective opening. The channels are preferably arranged, in use, to direct the flow of fluid at an angle between 15° and 80°; between
5 30° and 70°; or between 45° and 60° relative to said radial line.

The guide members may be arranged about said longitudinal axis to form an oval or elliptical arrangement. Preferably, however, the guide members are
10 arranged substantially to form a circle (i.e. with the openings all displaced at equal distances from the longitudinal axis of the assembly).

Although the channels may be holes formed through the guide members, they are preferably slots or recesses
15 formed in a surface thereof.

The present application further relates to a particulate material processor comprising an assembly as described herein.

Viewed from a yet still further aspect, the present
20 application relates to a guide member for directing a flow of fluid into a processor, wherein the guide member has at least one passage formed therein and an alignment surface for abutment against an adjacent like guide member; wherein said alignment surface is adapted to
25 orient the at least one passage in a predetermined orientation relative to the at least one passage in said adjacent like guide member when said alignment surface abuts said adjacent guide member.

Viewed from a still further aspect, the present
30 invention provides a method of processing a fluid and/or a particulate material, the method comprising the steps of: (a) introducing the particulate material to be processed into a chamber; (b) providing a flow of fluid

into said chamber for entraining the particulate material; and (c) removing processed fluid and/or particulate material from the chamber; wherein the chamber comprises a processing zone, the fluid flow being
5 introduced through at least one inlet into said processing zone at an angle between 15° and 80° relative to a radial line extending from a longitudinal axis of the chamber to the respective inlet.

Viewed from a yet further aspect, the present
10 invention provides apparatus for processing a fluid and/or a particulate material, the apparatus comprising a chamber, a device for introducing particulate material into the chamber, and at least one fluid inlet for introducing a flow of fluid into the chamber; wherein the
15 chamber comprises a processing zone and the at least one fluid inlet is adapted, in use, to introduce the fluid flow into the processing zone at an angle between 15° and 80° relative to a radial line extending from a longitudinal axis of the chamber to the respective inlet.

20 According to a further aspect of the present invention, there is provided a process for processing a fluid and/or a particulate material with a stream of fluid in an annular processing zone:

supplying the particulate material for processing in
25 the zone;

discharging processed particulate material from the processing zone;

generating in the zone a circumferentially directed flow of fluid to develop a circumferentially circulating
30 turbulent bed of material within the processing zone;

an improved processing zone in which particulate material is circulated in a controlled manner to provide a predictable particle flow path both circumferentially

of the processing zone and helically of the zone, the improvement comprising:

- 5 i) directing the flow of fluid to entrain particulate material such that the resulting direction of flow is:
 - a. between an angle of 5° and 45° with respect to the horizontal plane, more particularly between 20° and 30° , and
 - 10 b. between an angle of 10° and 75° , more particularly between 20° and 60° , at the point of entry into the process zone with respect to the tangent to the radius from the centre of a substantially circular process zone;
- 15 ii) controlling fluid velocity so that it is greater than the terminal velocity of particles at point of impact on the bed base.

According to a still further aspect of the invention, there is provided an apparatus for processing
20 a fluid and/or a particulate material with a stream of fluid in an annular processing zone, said apparatus comprises:

means defining an annular processing zone with a fluid inlet means beneath the zone;

25 said fluid inlet including means for directing circumferentially process fluid around the annular treatment zone;

means for admitting particulate material to be processed into the processing zone;

30 means for discharging processed particulate material from the processing zone;

the means for defining said processing zone being configured to maintain a circumferentially circulating

turbulent band within the processing zone in response to fluid flow therein;

an improved processing zone in which particulate material is circulated in a controlled manner to provide
5 a predictable particle flow path both circumferentially of the processing zone and helically of the zone, the improvement comprising:

- 10 ii) directing the flow of fluid to entrain particulate material such that the resulting direction of flow is:
 - a. between an angle of 5° and 45° with respect to the horizontal plane, more particularly between 20° and 30° , and
 - 15 b. between an angle of 10° and 75° , more particularly between 20° and 60° , at the point of entry into the process zone with respect to the tangent to the radius from the centre of the substantially circular process zone;
- 20 ii) controlling fluid velocity so that it is greater than the terminal velocity of particles at point of impact on the bed base.

It will be appreciated that the fluid flow in the processing zone may be clockwise or anticlockwise. The
25 orientation of the guide members determining the flow direction.

A preferred embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

30 Figure 1 is a transverse cross-sectional view of a particulate material reactor in accordance with the present invention;

Figure 2 is a longitudinal cross-sectional view a lower portion of the reactor shown in Figure 1;

Figure 3 illustrates the flow path of fluid and particles in a reactor without the benefit of the present invention;

Figure 4 illustrates the flow path of fluid and particles in a reactor employing the present invention;

Figures 5A, 5B and 5C show bottom, front and end views respectively of angled vanes provided at the base of the processing zone to direct the flow of fluid as it enters the processing zone; and

Figures 6A and 6B are top and side views respectively of an assembly of the vanes shown in figure 5.

A cross-sectional view of a toroidal bed reactor (1) in accordance with a preferred embodiment of the present invention is shown in Figure 1. The reactor (1) comprises a cylindrical housing (3) inside of which a processing zone (5) is formed. The processing zone (5) is annular in shape and extends co-axially with the housing (3).

A cross-sectional view of the lower portion of the reactor (1) is shown in Figure 2. A tapered section (7) is provided at the base of the housing (3). The tapered section (7) is inclined downwardly towards the centre of the reactor (1). Gas is introduced into the reactor (1) through a series of vanes (9) provided at the base of the tapered section (7). The vanes (9) establish a desired fluid flow path (A) within the housing (3).

The vanes (9) direct the gas flow so that it enters the processing zone (5) at an angle α with respect to a tangent (B) of the substantially circular transverse

cross-section of the processing zone, as shown in Figure 1. The angle α is approximately 30° in this embodiment.

Furthermore, the vanes (9) cause the gas to enter the processing zone at an angle β inclined upwardly with respect to a horizontal plane (C), as shown in Figure 2. The angle β is approximately 15° in this embodiment.

The path followed by particulate material (11) introduced into the reactor (1) will now be described for different gas flow paths with reference to Figures 3 and 4.

Figure 3 shows a gas flow path (D) inside the reactor (1) when the gas enters the base of the housing (3) in a radial direction (i.e. α is 90° , and β is 0°). The gas tends to travel up the inside of the tapered section (7) and causes the particulate material (11) to collect in an annular region (9) around the inside wall of the housing (3). The gas travels towards the centre of the housing (3), around the base of the annular region (9), and up towards the top of the housing (3). Thus, the particulate material (11) comes into limited contact with the gas as it travels through the reactor (1).

In contrast, when the gas is introduced into the reactor (1) in accordance with the present invention (e.g. α is 30° and β is 15°), it follows a helical flow path (E), as shown in Figure 4. The processing zone (5) is defined by the helical flow of the gas in the housing (3). The particulate material is entrained in the vortex formed by the gas in the processing zone (5) and is transported vertically before being progressively separated from the fluid stream due to centrifugal force. By this means, the processing zone (5) utilising the present invention contains a rapidly and uniformly circulating mass of particulate material evenly

distributed in the processing zone (5). A path (F) followed by the particulate material (11) introduced into the reactor (1) is shown in Figure 4.

5 The even distribution of particles in the fluid flow is important to help prevent undesirable effects that may occur when the gas follows the flow path (D) shown in Figure 3. For example, when combusting particulates in air where the control of the temperature achieved by the particulate material needs to be carefully controlled,
10 the aggregation experienced with the flow patterns shown in Figure 3 causes ash sintering. This sintering occurs because the combusting particles are not entrained and dispersed in the fluid inlet, in this case air or oxygen, and as a result are not cooled to remove the heat being
15 released. This lack of cooling allows the temperature of the combusting particles to exceed that at which they become molten and aggregate. In such a situation, the form of the ash may be hazardous to health, as is experienced with rice husk ash when overheated and forms
20 crystalline silica, as described in PCT/CA01/01852.

As shown in Figure 4, the particulate material (11) is displaced upwardly by the fluid flow in the processing zone (5) and then expelled radially outwardly. The particulate material (11) then falls to the base of the
25 housing (3) and a moving bed of particulate material is formed by the tapered portion (7) of the reactor (1). The moving bed returns the particulate material to the processing zone (5) under the action of gravity. The cycle is thereby repeated. This cyclical motion of the
30 particulate material allows the reaction in the reactor (1) to be carefully controlled.

The velocity of the gas entering into the processing zone (5) is advantageously controlled to ensure that it

is greater than the terminal velocity of the particulate material. This control of the fluid flow helps to reduce or prevent the collection of particulate material at the base of the reactor (1).

5 It has been found that if the angle β of entry of the gas into the processing zone is 10° or more above a horizontal plane, and it is inclined at an angle α of 10° or more relative to a tangent to a radial line at the point of entry, the fluid and particulate material follow
10 the fluid path illustrated in Figure 4. The mass of particulate material is suspended in a coherent rotating mass with particles aggregated without incipient fluidisation.

The arrangement of the vanes (9) at the base of the
15 reactor (1) will now be described in greater detail. A single vane (9) is shown in Figure 5A, 5B and 5C. The vanes (9) each have a leading edge (13), a trailing edge (14) and three slots (15) formed in the surface thereof. As shown in Figure 5B, the vanes (9) are tapered towards
20 the leading edge (13) to form a tapered region (17) which serves to align the vanes (9) relative to each other. The slots (15) each extend from the leading edge (13) in a transverse direction across the tapered region (17). A chamfered region (19) is provided at the trailing edge of
25 each vane (9), diametrically opposed from the tapered region (17). A front view of a vane (9) is shown in Figure 5C.

The slots (15) extend at an angle β relative to a reference axis perpendicular to the leading edge (13) of
30 the vane (9), as shown in Figures 5A and 5C. The angular offset of the slots (15) causes the gas to be introduced into the reactor (1) upwardly, at said angle β , relative to a horizontal plane, as described above.

A top view of the vanes (9) arranged in an assembly (21) ready for use is shown in Figure 6A. A side view of the assembly (21) is shown in Figure 6B. The tapered region (17) of each of the vanes (9) determines the angular orientation of the vanes relative to each other and, thereby, the angular orientation of the slots (15). Thus, the taper angle of the tapered region (17) defines the angle α at which the gas is introduced into the processing zone (5).

The processing zone (5) is generally annular in shape because of the helical fluid flow inside the housing (3).

By controlling the angle of entry of the fluid into the processing zone to maintain it larger than 10° but less than 75° relative to the tangent to the radial line at the point of entry; and to be greater than 5° but less than 45° relative to said horizontal plane, as shown in Figures 1 and 2 respectively, the fluid and particulate flows can be made to circulate along a helical path, as shown in Figure 4.

The circulating particles are accelerated by the gas flow in the processing zone (5) in both horizontal and vertical directions to travel tangentially of said circumferential flow until such accelerated particles lose their energy and settle into the flowing bed arranged circumferentially of the processing zone (5). By displacement in the flowing bed, the circulating particles are returned to the base of the processing zone (5) thereby ensuring that all of the particles in the bed are exposed to the processing gases to provide for uniform and rapid processing of said particles.

The present invention may further be understood as relating to a process for processing particulate material

with a stream of fluid in an annular processing zone.

The process includes the steps of supplying the particulate material for processing into the processing zone, discharging processed material from the zone and
5 generating in the processing zone a circumferentially directed flow of fluid to develop a circulating turbulent band of particles. The present invention advantageously provides a predictable particle flow path both circumferentially and helically, within the processing
10 zone. The process preferably comprises directing the flow of fluid to develop a circulating bed, a flow of fluid directed at an angle relative to the tangent to the radial line to the point of fluid and to the horizontal plane at entry into the processing zone base. The
15 process may also comprise controlling fluid velocity so that it is greater than the terminal velocity of larger particles at their point of impact on the bed base and less than the terminal velocity of smaller particles in the superficial space above the bed upper surface.

20 The toroidal bed reactor of the present invention may be used to process minerals such as kaolin, lime or silicates; soils; carbon; alumina for dry scrubbing; biomass such as wood or rice husks; or sewage sludge.

The gas introduced into the reactor of the present
25 invention may, for example, be air, steam, carbon monoxide or nitrogen. Of course, neutral, oxidizing or reducing gases may be used depending on the process.

Although the embodiment described herein has been directed to a method of processing a particulate
30 material, it will be appreciated that the process and apparatus may equally be employed to process a fluid, such as a gas.

In accordance with this invention, at least in preferred embodiments, an improvement is provided in respect of the system for developing an annular processing bed to achieve controlled predictable movement
5 of particles within the circulating bed.

Although preferred embodiments of the invention have been described herein in detail, it will be understood by those skilled in the art that variations may be made thereto without departing from the scope of the invention
10 or of the appended claims.

CLAIMS:

1. A method of processing a fluid and/or a particulate material, the method comprising the steps of:
 - 5 (a) introducing the particulate material into a chamber;
 - (b) providing a flow of fluid into said chamber for entraining the particulate material; and
 - (c) removing processed fluid and/or particulate material form the chamber;
- 10 wherein the chamber comprises a processing zone having a substantially circular transverse cross-section, the fluid flow being introduced into the processing zone at an angle of between 10° and 75° with respect to a tangent of the substantially circular transverse cross-
15 section of the processing zone to establish a fluid flow following a substantially helical path in the processing chamber.
2. A method as claimed in claim 1, wherein the velocity
20 of the fluid flow is controlled so as to be greater than the terminal velocity of individual or a mass of particulate material in the chamber.
3. A method as claimed in claim 1 or 2, wherein the
25 fluid flow upon entry into the processing zone defines an angle of between 20° and 60° with respect to a tangent of the substantially circular transverse cross-section of the processing zone.
- 30 4. A method as claimed in any one of claims 1, 2 or 3, wherein the fluid flow upon entry into the processing zone is inclined upwardly at an angle between 5° and 45° with respect to a horizontal plane.

5. A method as claimed claim 4, wherein the fluid flow upon entry into the processing zone is inclined upwardly at an angle between 20° and 30° with respect to said horizontal plane.

6. A method as claimed in any one of the preceding claims, wherein said fluid flow is developed by at least one vane or deflector.

7. A method as claimed in any one of the preceding claims, wherein said fluid flow is developed by at least one nozzle.

8. A method as claimed in any one of the preceding claims, wherein said fluid flow causes said particulate material to undergo vertical and horizontal displacement.

9. A method as claimed in any one of the preceding claims, wherein said processing zone is provided in a central region of said chamber and individual particulate material exits the processing zone in a radially outward direction.

10. A method as claimed in claim 9, wherein the chamber has a base inclined downwardly towards the centre of the chamber to bias particulate material towards the processing zone.

11. A method as claimed in any one of the preceding claims, wherein the processing zone is annular in shape.

12. A method as claimed in any one of the preceding claims, wherein the fluid is introduced at the base of the processing zone.
- 5 13. A method as claimed in any one of the preceding claims, wherein the fluid is a gas.
14. A method as claimed in any one of the preceding claims, wherein the helical fluid flow is conical or
10 cylindrical.
15. Apparatus for processing a fluid and/or a particulate material, the apparatus comprising a chamber, means for introducing particulate material into the
15 chamber, and at least one fluid inlet for introducing a flow of fluid into the chamber; wherein the chamber comprises a processing zone having a substantially circular transverse cross-section, and the at least one fluid inlet being adapted, in use, to introduce the fluid
20 flow into the processing zone at an angle of between 10° and 75° with respect to a tangent of the substantially circular transverse cross-section of the processing zone.
16. Apparatus as claimed in claim 17 further comprising
25 a flow controller for controlling the velocity of the fluid introduced into the chamber.
17. Apparatus as claimed in claim 15 or 16, wherein the or each fluid inlet is adapted so as to introduce the
30 fluid flow into the processing zone at an angle of between 20° and 60° with respect to said tangent.

18. Apparatus as claimed in any one of claims 15, 16 or 17, wherein the fluid inlet is adapted to introduce the fluid flow into the processing zone at an angle of between 5° and 45° with respect to a horizontal plane.

5

19. Apparatus as claimed in claim 18, wherein the fluid inlet is adapted to introduce the fluid flow into the processing zone at an angle between 20° and 30° with respect to said horizontal plane.

10

20. Apparatus as claimed in any one of claims 15 to 19 further comprising at least one vane and/or at least one deflector for controlling the flow of the fluid as it is introduced into the chamber.

15

21. Apparatus as claimed in any one of claims 15 to 20 further comprising at least one nozzle for controlling the flow of the fluid as it is introduced into the chamber.

20

22. Apparatus as claimed in any one of claims 15 to 21, wherein the chamber has a base inclined downwardly towards the centre thereof.

25

23. Apparatus as claimed in any one of claims 15 to 22, wherein fluid inlet is arranged such that the processing zone is formed in a central region of said chamber.

30

24. Apparatus as claimed in any one of claims 15 to 23, wherein said fluid inlet is provided at the bottom of said chamber.

25. An assembly for directing a flow of fluid into a processing zone of a processor, the assembly having a plurality of channels for guiding the flow of fluid through a plurality of openings to an interior of the assembly, each of the channels being arranged, in use, to direct the flow of fluid into the processing zone at an angle less than 90° relative to a radial line extending from a longitudinal axis of the assembly to the respective opening.

10

26. An assembly as claimed in claim 25, wherein the assembly comprises a plurality of guide members and at least one of said channels is provided in each of said guide members.

15

27. An assembly as claimed in claim 26, wherein each guide member has an alignment surface which abuts against an adjacent guide member.

20 28. An assembly as claimed in claim 27, wherein said alignment surfaces each determine the orientation of the associated guide member and, in use, the direction of the flow of fluid relative to said radial line.

25 29. An assembly as claimed in any one of claims 25 to 28, wherein the channels are arranged, in use, to direct the flow of fluid at an angle between 15° and 80° ; or between 30° and 70° relative to said radial line.

30 30. An assembly as claimed in any one of claims 25 to 29, wherein the channels are arranged, in use, also to direct the flow of fluid at an angle inclined upwardly

relative to a plane perpendicular to the longitudinal axis of the assembly.

31. An assembly as claimed in claim 30, wherein the
5 channels are arranged, in use, to direct the flow of fluid at an angle between 5° and 45° ; or between 20° and 30° relative to said plane.

32. An assembly as claimed in any one of claims 26 to
10 31, wherein said guide members are arranged about said longitudinal axis substantially to form a circle.

33. An assembly for directing a flow of fluid into a processor, the assembly having a longitudinal axis and
15 comprising a plurality of guide members each having at least one channel formed therein; wherein each channel is arranged, in use, to guide the flow of fluid through a respective opening to an interior of the assembly at an angle relative to a plane perpendicular to the
20 longitudinal axis of the assembly.

34. An assembly as claimed in claim 33, wherein each channel is arranged to direct the flow of fluid at an angle between 5° and 45° ; or between 20° and 30° relative
25 to said plane.

35. An assembly as claimed in claim 33 or 34, wherein the channels are arranged, in use, also to direct the flow of fluid at an angle less than 90° relative to a
30 radial line extending from a longitudinal axis of the assembly to the respective opening.

36. An assembly as claimed in claim 35, wherein the channels are arranged, in use, to direct the flow of fluid at an angle between 15° and 80°; or between 30° and 70° relative to said radial line.

5

37. An assembly as claimed in any one of claims 33 to 36, wherein said guide members are arranged about said longitudinal axis substantially to form a circle.

10 38. An assembly as claimed in any one of claims 33 to 37, wherein said at least one channel is a slot formed in a surface of the respective guide member.

15 39. A particulate material processor or a fluid processor comprising an assembly as claimed in any one of claims 25 to 38.

20 40. A guide member for directing a flow of fluid into a processor, wherein the guide member has at least one passage formed therein and an alignment surface for abutment against an adjacent like guide member; wherein said alignment surface is adapted to orient the at least one passage in a predetermined orientation relative to the at least one passage in said adjacent like guide member when said alignment surface abuts said adjacent guide member.

25 41. A process for contacting a fluid and a particulate material substantially as herein described with reference to the accompanying figures.

30 42. A processor substantially as herein described with reference to the accompanying figures.

43. A guide member substantially as herein described with reference to the accompanying figures.

Doc #571114



INVESTOR IN PEOPLE

Application No: GB0421362.5

Examiner: Mr Jason Scott

Claims searched: 1-24

Date of search: 1 March 2005

Patents Act 1977: Search Report under Section 17**Documents considered to be relevant:**

Category	Relevant to claims	Identity of document and passage or figure of particular relevance
X	1-5, 7, 8, 11-19 & 21-23 at least	EP 0513563 A1 FREUNT IND CO LTD See whole document and especially the helical flow path of figures 2 & 3 caused by angle of the inlet nozzle 13.
X	1-24	GB 2177616 A TOUBORG JORN See whole document and especially claim 1 in conjunction with reactor 1 of the figures.
X	1-6, 8, 11-20, 23 & 24	WPI Abstract Accession No. 1986-047634 & TAMBOVSK I KHIM MASH See abstract and figure.
X	1-5, 9, 12-19, 21, 23 & 24	DE 3245393 A DEGUSSA See whole document and especially claim 1 and the helical follow path depicted in figure 1.
X	1, 3-8 & 10-23	US 4668441 A RHONE POULENC SPEC CHIM See whole document and especially the figures and claim 1.
X	1-5, 7-9, 11-21, 23 & 24	EP 1452224 A1 HUETTLIN HERBERT See whole document and especially claim 1 and the flow paths in figure 2.

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^x :Worldwide search of patent documents classified in the following areas of the IPC⁰⁷

B01J



INVESTOR IN PEOPLE

The following online and other databases have been used in the preparation of this search report

WPI, JAPIO, EPODOC