

(74) **Agent:** SMART & BIGGAR

(54) Title: SUPERCOOLED LARGE DROP ICING CONDITION SIMULATION SYSTEM



ABSTRACT

A method and apparatus for an icing simulation system (111). The icing simulation system (111) comprises a wind tunnel (116), a nozzle system (122), and a controller (128). The nozzle system (122) is configured to spray drops (132) of water (130) within the wind tunnel (116). The controller (128) is configured to control a number of properties of the water (130) in the nozzle system (122) such that the nozzle system (122) sprays the drops (132) of the water (130) with different sizes for a desired type of icing condition (111).

5

10

SUPERCOOLED LARGE DROP ICING CONDITION SIMULATION SYSTEM

BACKGROUND

5 The present disclosure relates generally to icing conditions and, in particular, to simulating icing conditions. Still more particularly, the present disclosure relates to a method and apparatus for simulating icing conditions in which supercooled large drops are present.

10 In aviation, icing on an aircraft may occur when the atmospheric conditions lead to the formation of ice on the surfaces of the aircraft. Further, this ice also may occur within the engine. Ice formation on the surfaces of the aircraft, on inlets of an engine, and other locations is undesirable and potentially unsafe for operating the aircraft.

15 Icing conditions may occur when drops of supercooled liquid water are present. In these illustrative examples, water is considered to be supercooled when the water is cooled below the stated freezing point for water but the water is still in a liquid form. Icing conditions may be characterized by the size of the drops, the liquid water content, the air temperature, and/or other parameters. These parameters may affect the rate and extent at which ice forms on an
20 aircraft.

 Drops of water may be supercooled in various environments. For example, drops of water may be supercooled in stratiform clouds and in cumulous clouds.

25 When icing occurs, the aircraft may not operate as desired. For example, ice on the wing of an aircraft will cause the aircraft to stall at a lower angle of attack and have an increased drag.

 Aircraft may have mechanisms to prevent icing, remove ice, or some combination thereof to handle these icing conditions. For example, aircraft may include icing detection, prevention, and removal systems. Ice may be removed
30 using bleed air, infrared heating, and other suitable mechanisms.

Aircraft may have sensor systems designed to detect icing conditions. As new regulations are developed with respect to icing conditions that should be detected, manufacturers design and test sensor systems for detecting the icing conditions. For example, aircraft may be required to be certified to operate in normal icing conditions and in supercooled large drop icing conditions.

In designing and testing sensor systems, currently available test environments may not provide an ability to simulate supercooled large drop icing conditions in the manner desired to test new sensor systems. Therefore, it would be desirable to have a method and apparatus that takes into account at least some of the issues discussed above as well as possibly other issues.

SUMMARY

In accordance with one aspect of the invention there is provided an icing simulation system. The system includes a wind tunnel, a nozzle system configured to spray drops of water within the wind tunnel, and a controller configured to control a number of properties of the water in the nozzle system such that the nozzle system sprays the drops of the water with different sizes for a desired type of icing condition.

The number of properties may be selected from at least one of a water pressure, an air pressure, and a temperature.

The nozzle system may further include a plurality of spray bars and each spray bar of the plurality of spray bars may include a group of nozzles, and the controller may be configured to individually control the spray bars such that the spray bars spray drops of the water in different size ranges and to control the temperature of the water in the nozzle system such that the water in the nozzle system does not freeze within nozzles of the nozzle system, and the two ranges of sizes of the drops of water may include a supercooled large drop bimodal distribution, and the desired type of icing condition may include drops of the

water having a diameter in a range from about 0.112 millimeters to about 2.2 millimeters.

The nozzle system may include groups of nozzles.

5 In being configured to control the number of properties of the water in the nozzle system such that the nozzle system sprays the drops of the water with the different sizes for the desired type of icing condition, the controller may be configured to select at least one of a water pressure, an air pressure, and a temperature for the water for each group of nozzles in the groups of nozzles such that the groups of nozzles spray the drops of the water with the different sizes for
10 the desired type of icing condition.

A group of nozzles in the groups of nozzles may be associated with a spray bar.

The icing simulation system may include a spray bar balancing system configured to reduce a time for the spray bar to spray the drops of the water with
15 a desired size.

The icing simulation system may include a plurality of valves configured to control at least one of a water pressure, an air pressure, and a temperature for the water, and a computer system configured to control an operation of the plurality of valves.

20 The icing simulation system may include a sensor system configured to detect a size of the drops of the water.

The desired type of icing condition may be a supercooled large drop icing condition.

25 A second type of icing condition may include the drops of the water having a diameter greater than about 0.111 millimeters.

The desired type of icing condition further may include additional drops of the water having a diameter that is less than or equal to about 0.111 millimeters.

The wind tunnel may include a test section configured to hold a test object.

30

The test object may be selected from one of an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

5 In accordance with another aspect of the invention there is provided a method for simulating a desired type of icing condition in a wind tunnel. The method involves controlling a number of properties for water sent to a nozzle system. The number of properties is controlled such that drops of the water have different sizes associated with the desired type of icing condition. The method
10 also involves spraying the drops of the water from the nozzle system in the wind tunnel. The drops of the water sprayed by the nozzle system have the different sizes for the desired type of icing condition.

 Controlling the number of properties for the water sent to the nozzle system may involve controlling at least one of a water pressure, an air pressure,
15 and a temperature for the water sent to the nozzle system.

 Spraying the drops of the water from the nozzle system in the wind tunnel may involve spraying the drops of the water from groups of nozzles in the nozzle system in the wind tunnel.

 Controlling the number of properties for the water sent to the nozzle
20 system may involve selecting at least one of a water pressure, an air pressure, and a temperature for the water for each group of nozzles in the groups of nozzles.

 Spraying the drops of the water from the groups of nozzles in the nozzle system in the wind tunnel may involve spraying the drops of the water from the
25 groups of nozzles in the nozzle system in the wind tunnel, and a group of nozzles in the groups of nozzles may be associated with a spray bar.

 Controlling the number of properties for the water sent to the nozzle system may involve controlling the number of properties such that the drops of the water have the different sizes associated with a supercooled large drop icing
30 condition.

The method may involve placing a test object in a test section of the wind tunnel, the test object being selected from one an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and features thereof will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a block diagram of an icing simulation environment in accordance with an illustrative embodiment;

Figure 2 is an illustration of a block diagram of properties controlled by a controller in accordance with an illustrative embodiment;

Figure 3 is an illustration of a block diagram of a nozzle system in accordance with an illustrative embodiment;

Figure 4 is an illustration of a block diagram of an infrastructure in an icing simulation system in accordance with an illustrative embodiment;

Figure 5 is an illustration of an icing simulation system in accordance with an illustrative embodiment;

Figure 6 is an illustration of a spray bar balancing system in accordance with an illustrative embodiment;

Figure 7 is an illustration of a flowchart of a process for simulating icing conditions in accordance with an illustrative embodiment;

Figure 8 is an illustration of a flowchart of a process for calibrating an icing simulation system in accordance with an illustrative embodiment;

Figure 9 is an illustration of a data processing system in accordance with an illustrative embodiment;

Figure 10 is an illustration of an aircraft manufacturing and service method in accordance with an illustrative embodiment; and

Figure 11 is an illustration of an aircraft in which an illustrative embodiment may be implemented.

DETAILED DESCRIPTION

The illustrative embodiments recognize and take into account one or more different considerations. For example, the illustrative embodiments recognize and take into account that currently available systems for simulating icing conditions are unable to simulate supercooled large drop icing conditions. In particular, the illustrative embodiments recognize and take into account that simulating this type of icing condition involves generating drops of water having two ranges of sizes. These ranges may be two different distributions of water drop sizes. This type of distribution may take the form of a supercooled large drop bimodal distribution.

For example, the illustrative embodiments recognize and take into account that currently available wind tunnels used to simulate icing conditions are unable to generate drops of water having the two ranges of sizes for supercooled large drop icing conditions.

Thus, one or more illustrative embodiments provide a method and apparatus for simulating icing conditions. In one illustrative embodiment, an icing simulation system comprises a wind tunnel, a nozzle system, and a controller. The nozzle system is configured to spray drops of water within the wind tunnel. The controller is configured to control a number of properties of the water in the nozzle system such that the nozzle system sprays the drops of water with different sizes for a desired type of icing condition.

With reference now to the figures and, in particular, with reference to **Figure 1**, an illustration of a block diagram of an icing simulation environment is depicted in accordance with an illustrative embodiment. In this illustrative example, icing simulation environment **100** may be used to simulate types of icing conditions **102**.

In particular, types of icing conditions **102** may be simulated for test object **103**. Test object **103** may be, for example, structure **104**, platform **106**, or both. Structure **104** may be a structure in platform **106**. When platform **106** takes the form of aircraft **108**, structure **104** may be a structure in aircraft **108**. For

example, structure **104** may be a wing, a horizontal stabilizer, a vertical stabilizer, an engine, a landing gear system, a fuselage, a flap, an aircraft windshield, or some other suitable structure.

5 In one illustrative embodiment, icing simulation system **110** may be used to simulate desired type of icing condition **111** in one or more of types of icing conditions **102** for test object **103**. Desired type of icing condition **111** is a type of icing condition for which testing is desired with respect to test object **103**.

10 In particular, icing simulation system **110** may be used to simulate desired type of icing condition **111** as first type of icing condition **112**, second type of icing condition **114**, or both.

15 In these illustrative examples, first type of icing condition **112** and second type of icing condition **114** in types of icing conditions **102** may differ from each other based on drop size. The drop size may differ based on a mean volumetric diameter. More specifically, the drop sizes may differ based on ranges of sizes. In other words, first type of icing condition **112** may have one range of sizes, and second type of icing condition **114** may have another range of sizes. The distribution of sizes within the ranges also may be used to define different types of icing conditions.

20 In these illustrative examples, first type of icing condition **112** may be present when the size of the drops is from about **0.00465** millimeters in diameter to about **0.111** millimeters in diameter. Drops with these sizes may be referred to as normal drops.

25 Second type of icing condition **114** may be present when the size of the drops includes drops that have a diameter greater than about **0.111** millimeters. Drops having a size greater than about **0.111** millimeters may be referred to as large drops and, in particular, may be called supercooled large drops under the altitude, temperature, and liquid water content conditions described above. For example, the drops may have a diameter in a range from about **0.112** millimeters to about **2.2** millimeters. In addition, second type of icing condition **114** may include drops that are **0.111** millimeters or less when drops greater than **0.111**

30

millimeters are present. In other words, second type of icing condition **114** includes both normal drops and large drops of water.

In simulating desired type of icing condition **111**, liquid water content in the drops may also be used to characterize the type of icing condition. For example, first type of icing condition **112** may have liquid water content in the range of about **0.04** grams per cubic meter to about **2.8** grams per cubic meter. On the other hand, second type of icing condition **114** may have liquid water content in the range of about **0.19** grams per cubic meter to about **0.44** grams per cubic meter.

In the depicted examples, icing simulation system **110** is a physical system that also may include software. Icing simulation system **110** includes wind tunnel **116**, air drive system **118**, cooling system **120**, nozzle system **122**, sensor system **123**, water source **124**, air source **126**, infrastructure **127**, controller **128**, and other suitable components.

As depicted, air drive system **118** causes air **129** to flow within wind tunnel **116**. Cooling system **120** may cool the temperature of air **129** within wind tunnel **116**.

Infrastructure **127** comprises components that carry water **130** and air **134** to nozzle system **122**. In particular, infrastructure **127** connects water source **124** and air source **126** to nozzle system **122**. Additionally, infrastructure **127** also may be connected to cooling system **120**. The connection to cooling system **120** may be used to cool water **130**, air **134**, or both. Additionally, infrastructure **127** also may be connected to cooling system **120**. The connection to cooling system **120** may be used to cool water **130**, air **134**, or both.

Nozzle system **122** receives water **130** from water source **124** through infrastructure **127** and generates drops **132** of water **130**. In other words, drops **132** of water **130** are generated by water **130** flowing through nozzle system **122**.

In some illustrative examples, air **134** received through infrastructure **127** may be introduced into water **130** as water **130** flows through nozzle system **122** to form drops **132** of water **130**. In these illustrative examples, air source **126** also may send air **134** to nozzle system **122** via infrastructure **127**. Within nozzle

system **122**, air **134** may be mixed with water **130** to form drops **132** of water **130** sprayed by nozzle system **122**.

In these illustrative examples, drops **132** of water **130** generated by nozzle system **122** may have properties **136** to simulate first type of icing condition **112**, second type of icing condition **114**, or both. In these illustrative examples, properties **136** of drops **132** of water **130** may include, for example, without limitation, size, water content, temperature, and other suitable properties.

Sensor system **123** is configured to generate data about one or more of properties **136** of drops **132** of water **130**. In other words, sensor system **123** identifies properties **136** of drops **132** of water **130** generated by nozzle system **122** within wind tunnel **116**.

Controller **128** is configured to control properties **140** of water **130** to simulate at least one of first type of icing condition **112**, second type of icing condition **114**, or both.

Controller **128** may use data from sensor system **123** to adjust values for a number of properties in properties **140** of water **130** to obtain desired type of icing condition **111** within types of icing conditions **102**. In other words, sensor system **123** provides feedback to controller **128** about drops **132** of water **130**. The data received from sensor system **123** may be used to adjust properties **140** of water **130** if properties **136** for drops **132** of water **130** do not have desired values for desired type of icing condition **111**.

The adjustment of properties **140** of water **130** made by controller **128** may be made at different times during testing. For example, the adjustment may be made prior to placing test object **103** into wind tunnel **116** for testing of desired type of icing condition **111**. Additionally, these adjustments may be made while the simulation of desired type of icing condition **111** is performed on test object **103**. In other words, adjustments may be made dynamically during the testing to maintain desired type of icing condition **111**.

In these illustrative examples, controller **128** is comprised of hardware, software, or both. For example, controller **128** may be a computer system. The computer system may include one or more computers. When more than one

computer is present in the computer system, those computers may be in communication with each other through a network. In other illustrative examples, controller **128** may be implemented using hardware with circuits configured to perform operations to simulate types of icing conditions **102**.

5 In these illustrative examples, the hardware may take the form of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be
10 reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. Additionally, the processes may be implemented in organic
15 components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being.

 As depicted, test object **103** may be placed in test area **142** in wind tunnel **116** for exposure to drops **132** of water **130**. By controlling properties **140** for water **130**, drops **132** of water **130** may be generated by properties **136** to
20 simulate desired type of icing condition **111**.

 This simulation of desired type of icing condition **111** may be used to determine how test object **103** may function. For example, test object **103** may be an airfoil with sensors configured to detect icing conditions. By simulating desired type of icing condition **111**, a determination may be made as to whether
25 the sensors are able to detect desired type of icing condition **111**. In these illustrative examples, desired type of icing condition **111** may be a supercooled large drop icing condition.

 Turning now to **Figure 2**, an illustration of a block diagram of properties controlled by a controller is depicted in accordance with an illustrative
30 embodiment. Examples of properties **140** of water **130** that may be controlled by controller **128** to obtain properties **136** for drops **132** to simulate desired type of

icing condition **111** in types of icing conditions **102** in **Figure 1** are shown in this illustrative example.

In these illustrative examples, properties **140** include at least one of water pressure **202**, air pressure **204**, air flow **206**, temperature **208**, and other suitable properties. Properties **140** controlled by controller **128** may be selected from one or more of properties **140**.

Water pressure **202** is the pressure of water **130** in nozzle system **122** in **Figure 1**. Air pressure **204** is the pressure of air **134** introduced into nozzle system **122**. Air flow **206** is the speed at which air moves within wind tunnel **116**. Temperature **208** is the temperature of water **130** in nozzle system **122**. Temperature **208** may be selected to be near or below freezing for water **130** prior to water **130** being sprayed as drops **132** from nozzle system **122**. The selection of temperature **208** is such that water **130** does not freeze within nozzles in nozzle system **122**.

In these illustrative examples, values for at least one of water pressure **202**, air pressure **204**, and air flow **206** of properties **140** may be selected to obtain properties **136** of drops **132** that are desired for desired type of icing condition **111**. These properties may include at least one of, for example, without limitation, size, water content, temperature, and other suitable properties for drops **132** of water **130** in a manner that produces desired type of icing condition **111** in types of icing conditions **102**.

The values for properties **140** may change, depending on the particular type of icing condition in types of icing conditions **102**. In other words, the values of properties **140** selected for first type of icing condition **112** are different from the values of properties **140** selected for second type of icing condition **114**.

For example, air pressure **204** may be from about **10** psi to about **60** psi, and water pressure **202** may be from about **20** psi to about **240** psi. This combination of air pressure **204** and water pressure **202** may produce water drops having sizes of up to about **0.050** millimeters. The size of the water drops may be increased by changing the pressure of the water relative to the pressure of the air.

For example, air pressure **204** may be changed by a magnitude relative to water pressure **202**. For example, water pressure **202** may be about **80** psi, and air pressure **204** may be about **8** psi. With this setting, the drops of water may be about **0.500** millimeters.

5 In some illustrative examples, air pressure **204** may be from about **10** psi to about **60** psi. Water pressure **202** may be from about **10** psi to about **240** psi. Of course, the values of water pressure **202** and air pressure **204** may change, depending on the types of nozzles used.

10 With reference now to **Figure 3**, an illustration of a block diagram of a nozzle system is depicted in accordance with an illustrative embodiment. Examples of components for nozzle system **122** are illustrated in this figure.

 As depicted, nozzle system **122** is comprised of groups of nozzles **300** and support structures **301**. In these illustrative examples, a group of nozzles within groups of nozzles **300** includes one or more nozzles. Further, one group
15 of nozzles within groups of nozzles **300** may have a different number of nozzles than another group of nozzles within groups of nozzles **300**.

 Support structures **301** are configured to be associated with groups of nozzles **300**. When one component is “associated” with another component, the association is a physical association in these depicted examples. For example, a
20 first component, group of nozzles **304** in groups of nozzles **300**, may be considered to be associated with a second component, support structure **306** in support structures **301**, by being secured to the second component, bonded to the second component, mounted to the second component, welded to the second component, fastened to the second component, and/or connected to the
25 second component in some other suitable manner. The first component also may be connected to the second component using a third component. The first component may also be considered to be associated with the second component by being formed as part of and/or an extension of the second component. Further, the association may be a temporary association in which the first
30 component may be removed from the second component or vice versa.

Support structures **301** may also be configured to receive water and direct water to groups of nozzles **300**. In these illustrative examples, support structures **301** may include lines, valves, or other components that may be used to control the flow of water within support structures **301**. In some illustrative examples, support structures **301** also may include sensors used to generate data about water flowing through support structures **301**.

As depicted, the association of groups of nozzles **300** with support structures **301** forms plurality of spray bars **302**. Each group of nozzles in groups of nozzles **300** is associated with a support structure in support structures **301**. For example, the association of group of nozzles **304** with support structure **306** forms spray bar **308**.

In these illustrative examples, properties **140** in **Figure 2** may be controlled with different levels of granularity. For example, each group of nozzles in groups of nozzles **300** may have different values for properties **140** as compared to other groups of nozzles.

In still other illustrative examples, when more than one nozzle is in group of nozzles **304**, values for properties **140** may be controlled individually for each nozzle in group of nozzles **304**. In other words, one group of nozzles in groups of nozzles **300** may spray drops **132** of water **130** in **Figure 1** with a different size or range of sizes as compared to another group of nozzles in groups of nozzles **300** through the control of properties **140** for these two groups of nozzles. In this manner, the sizes of drops **132** of water **130** may be achieved using groups of nozzles **300** to obtain a desired type of icing condition within types of icing conditions **102** in **Figure 1**.

Turning now to **Figure 4**, an illustration of a block diagram of an infrastructure in an icing simulation system is depicted in accordance with an illustrative embodiment. In this illustrative example, examples of some components that may be present in infrastructure **127** include lines **400**, valves **402**, and sensors **403** are shown. Lines **400** may include, for example, flexible lines **404** and rigid lines **406**.

In these illustrative examples, lines **400** may be used to connect water source **124** and air source **126** to nozzle system **122** in **Figure 1**. Further, some of lines **400** may be connected to cooling system **120** in **Figure 1**.

Valves **402** are associated with lines **400**. Valves **402** may be operated to control the flow of fluids through lines **400**. In these illustrative examples, these fluids may be water **130** and air **134** in **Figure 1**. In these illustrative examples, the operation of valves **402** is controlled by controller **128**. Controller **128** operates valves **402** to select values for properties **140** in **Figure 1**.

Sensors **403** are configured to detect the values of properties **140**. Additionally, sensors **403** also may be configured to detect the position of valves **402**, the flow of liquids through lines **400**, and other suitable parameters.

As depicted, sensors **403** may be associated with lines **400** and valves **402**. Further, sensors **403** also may be associated with nozzle system **122**.

Sensors **403** generate data **408** that is sent to controller **128**. Controller **128** operates valves **402** to adjust the values of properties **140**.

The illustration of icing simulation environment **100** in **Figure 1** and the components of icing simulation environment **100** in **Figures 1-4** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

In some illustrative examples, one or more test objects in addition to test object **103** may be placed in test area **142** during simulation of desired type of icing condition **111** using icing simulation system **110**. Also, test object **103** may take other forms other than an aircraft or objects that are for or part of an aircraft. For example, test object **103** may be selected from one of an automobile windshield, automobile, a ship, an engine hood, a deck of a ship, and other suitable test objects.

In still other illustrative examples, valves **402**, sensors **403**, or both may be considered part of controller **128**. In still other illustrative examples, additional types of icing conditions in addition to or in place of first type of icing condition **112** and second type of icing condition **114** in types of icing conditions **102** may be present. For example, in some types of icing conditions, three or more ranges of sizes for drops **132** of water **130** may be present for those types of icing conditions.

Turning now to **Figure 5**, an illustration of an icing simulation system is depicted in accordance with an illustrative embodiment. In this depicted example, icing simulation system **500** is one example of a physical implementation for icing simulation system **110** shown in block form in **Figure 1**.

In this illustrative example, a top view of icing simulation system **500** is shown. As depicted, icing simulation system **500** includes wind tunnel **502**, air drive system **504**, nozzle system **506**, cooling system **508**, and controller **510**.

In this depicted example, wind tunnel **502** has turning vane **512**, turning vane **514**, turning vane **516**, and turning vane **518**. These turning vanes aid in directing air flow **520** generated by air drive system **504** to turn or curve within wind tunnel **502**.

As depicted, air flow **520** is generated by air drive system **504**. In this illustrative example, air drive system **504** comprises fan system **522**. In this illustrative example, nozzle system **506** comprises spray bars **524**.

In these illustrative examples, spray bars **524** are configured to spray drops of water **526** within wind tunnel **502**. Drops of water **526** are carried by air flow **520** through test section **528** within wind tunnel **502**.

In these illustrative examples, air flow **520** is cooled using cooling system **508**. As depicted, cooling system **508** comprises refrigeration system **530** and heat exchanger **532**. Refrigeration system **530** and heat exchanger **532** operate to cool air within air flow **520** passing by or through heat exchanger **532**.

In this illustrative example, sensor system **509** takes the form of laser sensor system **534**. Laser sensor system **534** sends laser beam **536** into wind tunnel **502** where drops of water **526** are generated by spray bars **524** in nozzle

system **506**. Laser sensor system **534** sends data about sizes of drops of water **526** to controller **510** in control room **538**.

With feedback from laser sensor system **534** in sensor system **509**, controller **510** may adjust properties of water sent through spray bars **524** in nozzle system **506** to obtain desired sizes for drops of water **526** to simulate a desired type of icing condition.

In these illustrative examples, drops of water **526** may have two ranges of sizes for the desired icing condition. In particular, the desired icing condition may be a supercooled large drop icing condition. In these illustrative examples, drops of water **526** may include sizes for normal drops and sizes for supercooled large drops.

Turning now to **Figure 6**, an illustration of a spray bar balancing system is depicted in accordance with an illustrative embodiment. As depicted, spray bar balancing system **600** may be implemented in a number of different places within icing simulation system **110** in **Figure 1**. For example, spray bar balancing system **600** may be implemented as part of infrastructure **127**, nozzle system **122**, or a combination of the two in **Figure 1**.

In this illustrative example, spray bar balancing system **600** may be used to control spray bar **602** in a manner that allows for drops **604** of water to be produced with a desired size and temperature more quickly to form a desired icing cloud for a desired type of icing condition.

As described above, the drop size may be defined by the mean volumetric diameter of the drops of water and/or the liquid water content in the drops of water. These parameters are functions of the pressure of air in spray bar **602** and the change in pressure of air in spray bar **602**, as well as the velocity of the drops of water within the tunnel.

In this illustrative example, spray bar **602** is comprised of support structure **605** and nozzles **606**. In this example, nozzles **606** include nozzle **608**, nozzle **610**, nozzle **612**, and nozzle **614**. Support structure **605** contains water line **618** and air line **620**. Water line **618** supplies water to nozzles **606**, and air line **620** supplies air to nozzles **606**.

In these illustrative examples, valves **622** in support structure **605** control water that passes through nozzles **606**. As depicted, valves **622** include valve **624**, valve **626**, valve **628**, and valve **630**. These valves are associated with nozzle **608**, nozzle **610**, nozzle **612**, and nozzle **614**, respectively.

5 In these illustrative examples, support structure **605** in spray bar **602** has water input **632** and water return output **634**. Additionally, support structure **605** has air input **636**. Water input **632** is connected to water supply **638** by line **640**. Water return output **634** is connected to water return **642** by line **644**. Air input **636** is connected to air supply **646** by line **648**. Needle valve **650** and bypass
10 valve **652** are associated with line **644**. Air valve **654** is associated with line **648**. Pressure valve **656** is associated with line **640**.

In this illustrative example, spray bar **602** may operate in a spray mode and a bypass mode. In bypass mode, spray bar **602** does not spray drops **604** of water. In this mode, valves **622** are closed and bypass valve **652** is open. In this
15 manner, water flowing from water supply **638** may flow through water line **618** in support structure **605** of spray bar **602**. This water may flow out of spray bar **602** at water return output **634** and through line **644** to water return **642**.

When in the bypass mode, pressure valve **656** may be adjusted to supply water at a desired pressure level for a desired type of icing condition. In this
20 manner, the desired pressure may be present before switching to a spray mode.

When spray bar **602** is placed into a spray mode, valves **622** are opened, and bypass valve **652** is closed. In the spray mode, drops **604** of water are sprayed out of nozzles **606** from spray bar **602**. Drops **604** of water form an icing cloud in these illustrative examples. Drops **604** of water have properties that
25 simulate a desired icing condition.

In spray mode, valves **622** are open to allow drops **604** of water to be sprayed out of nozzles **606**. Additionally, air valve **654** and pressure valve **656** are also open. Bypass valve **652** is closed.

With air valve **654** open, air may flow from air supply **646** through line **648**
30 into air line **620** through air input **636** to reach nozzles **606**. Additionally, water

may flow from water supply **638** through line **640** into water input **632** to reach nozzles **606**.

In these illustrative examples, this operation of the valves may cause a change in the pressure of the water flowing to nozzles **606**. Needle valve **650** is located downstream of bypass valve **652** and is configured to balance the flow of water during the change from a bypass mode to a spray mode. In this manner, any change in the pressure of the water may be reduced such that the change does not affect the spraying of drops **604** of water in a manner that affects simulating the desired icing condition. In other words, the properties of drops **604** of water may reach desired properties for the desired icing condition more quickly with this configuration.

The different components shown in **Figures 5-6** may be combined with components in **Figures 1-4**, used with components in **Figures 1-4**, or a combination of the two. Additionally, some of the components in **Figures 5-6** may be illustrative examples of how components shown in block form in **Figures 1-4** can be implemented as physical structures.

With reference now to **Figure 7**, an illustration of a flowchart of a process for simulating icing conditions is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 7** may be implemented in icing simulation environment **100** in **Figure 1**. In particular, the process may be implemented in icing simulation system **110**.

The process begins by identifying a desired type of icing condition (operation **700**). The process identifies a number of properties for water sent to a nozzle system for the desired type of icing condition (operation **702**).

Next, a test object is placed into a wind tunnel (operation **704**). A number of properties for the water sent to the nozzle system is controlled (operation **706**). In these illustrative examples, the number of properties is controlled such that drops of water have sizes associated with the type of icing condition. In other words, the values for the properties are selected such that drops of water have sizes that are characteristic of the type of icing condition to be simulated.

For example, with a supercooled large drop icing condition, the drops of water may include normal drops and large drops as described above. Further, the water also may have a desired temperature that can be reached as the drops of water travel in the wind tunnel.

5 Drops of water are then sprayed from the nozzle system in the wind tunnel (operation **708**), with the process terminating thereafter. The drops of water sprayed by the nozzle system have different sizes that correspond to the desired type of icing condition. These different sizes may be different ranges, depending on the type of icing condition.

10 In this manner, the simulation of the icing condition in a wind tunnel allows for a test object to be tested to see how the test object performs in the desired icing condition. For example, sensor systems for detecting icing conditions may be tested using this process without placing the sensors on an aircraft and flying the aircraft into weather with the desired icing condition.

15 With reference now to **Figure 8**, an illustration of a flowchart of a process for calibrating an icing simulation system is depicted in accordance with an illustrative embodiment. This process may be used to set icing simulation system **110** to produce drops **132** of water **130** with desired sizes for desired type of icing condition **111** in **Figure 1**.

20 The process begins by identifying groups of nozzles to be processed (operation **800**). The process then selects a group of nozzles from the groups of nozzles for processing (operation **802**).

 The process identifies a desired size for drops sprayed by the group of nozzles (operation **804**). Next, the process identifies values for one or more
25 properties of water to be sent through the group of nozzles (operation **806**). The properties of the water are controlled to meet those values for the group of nozzles (operation **808**). Drops of water are then sprayed from the group of nozzles using the values (operation **810**).

 Next, the size of the drops of water is identified (operation **812**). The size
30 of the drops of water may be identified using a sensor system, such as sensor system **123** in **Figure 1**. A determination is made as to whether the size of the

drops of water meet the desired size (operation **814**). The desired size may be met if the size of the drops of water identified are the same as the desired size. In these illustrative examples, the desired size also may be met, in some cases, if the size of the drops of water are within a range of the desired size.

5 If the size of the drops of water does not meet the desired size, an adjustment to the values of the properties needed to reach the desired size is identified (operation **816**). The process then returns to operation **808**.

10 With reference again to operation **814**, if the desired size of the drops of water is met, a determination is made as to whether an additional unprocessed group of nozzles is present in the groups of nozzles (operation **818**). If an additional unprocessed group of nozzles is present, the process returns to operation **802**. Otherwise, the process terminates.

15 Although this process may be used to calibrate the groups of nozzles prior to simulating a desired type of icing condition, this process may also be used at other times. For example, this process also may be used while the desired type of icing condition is being simulated. The process may be used to adjust the manner in which drops of water are sprayed such that the desired type of icing condition can be maintained even though other parameters in the icing simulation environment may change.

20 The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, function, and/or a portion of an operation or step. For
25 example, one or more of the blocks may be implemented as program code, in hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams.

30 In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the

figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

Turning now to **Figure 9**, an illustration of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **900** may be used to implement controller **128** in **Figure 1**. In this illustrative example, data processing system **900** includes communications framework **902**, which provides communications between processor unit **904**, memory **906**, persistent storage **908**, communications unit **910**, input/output (I/O) unit **912**, and display **914**. In this example, communications framework **902** may take the form of a bus system.

Processor unit **904** serves to execute instructions for software that may be loaded into memory **906**. Processor unit **904** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation.

Memory **906** and persistent storage **908** are examples of storage devices **916**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage devices **916** may also be referred to as computer readable storage devices in these illustrative examples. Memory **906**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **908** may take various forms, depending on the particular implementation.

For example, persistent storage **908** may contain one or more components or devices. For example, persistent storage **908** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **908** also

may be removable. For example, a removable hard drive may be used for persistent storage **908**.

Communications unit **910**, in these illustrative examples, provides for communications with other data processing systems or devices. In these illustrative examples, communications unit **910** is a network interface card.

Input/output unit **912** allows for input and output of data with other devices that may be connected to data processing system **900**. For example, input/output unit **912** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output unit **912** may send output to a printer. Display **914** provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices **916**, which are in communication with processor unit **904** through communications framework **902**. The processes of the different embodiments may be performed by processor unit **904** using computer-implemented instructions, which may be located in a memory, such as memory **906**.

These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **904**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **906** or persistent storage **908**.

Program code **918** is located in a functional form on computer readable media **920** that is selectively removable and may be loaded onto or transferred to data processing system **900** for execution by processor unit **904**. Program code **918** and computer readable media **920** form computer program product **922** in these illustrative examples. In one example, computer readable media **920** may be computer readable storage media **924** or computer readable signal media **926**.

In these illustrative examples, computer readable storage media **924** is a physical or tangible storage device used to store program code **918** rather than a medium that propagates or transmits program code **918**.

Alternatively, program code **918** may be transferred to data processing system **900** using computer readable signal media **926**. Computer readable signal media **926** may be, for example, a propagated data signal containing program code **918**. For example, computer readable signal media **926** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link.

The different components illustrated for data processing system **900** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **900**. Other components shown in **Figure 9** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code **918**.

Illustrative embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **1000** as shown in **Figure 10** and aircraft **1100** as shown in **Figure 11**. Turning first to **Figure 10**, an illustration of an aircraft manufacturing and service method is depicted in accordance with an illustrative embodiment. During pre-production, aircraft manufacturing and service method **1000** may include specification and design **1002** of aircraft **1100** in **Figure 11** and material procurement **1004**.

During production, component and subassembly manufacturing **1006** and system integration **1008** of aircraft **1100** takes place. Thereafter, aircraft **1100** may go through certification and delivery **1010** in order to be placed in service **1012**. While in service **1012** by a customer, aircraft **1100** is scheduled for routine

maintenance and service **1014**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

Each of the processes of aircraft manufacturing and service method **1000** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

With reference now to **Figure 11**, an illustration of an aircraft is depicted in which an illustrative embodiment may be implemented. In this example, aircraft **1100** is produced by aircraft manufacturing and service method **1000** in **Figure 10** and may include airframe **1102** with plurality of systems **1104** and interior **1106**. Examples of systems **1104** include one or more of propulsion system **1108**, electrical system **1110**, hydraulic system **1112**, and environmental system **1114**. Any number of other systems may be included. Although an aerospace example is shown, different illustrative embodiments may be applied to other industries, such as the automotive industry.

Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **1000** in **Figure 10**. In one illustrative example, components or subassemblies produced in component and subassembly manufacturing **1006** in **Figure 10** may be fabricated or manufactured in a manner similar to components or subassemblies produced while aircraft **1100** is in service **1012** in **Figure 10**.

As yet another example, one or more apparatus embodiments, method embodiments, or a combination thereof may be utilized during production stages, such as specification and design **1002** and system integration **1008** in **Figure 10**. For example, icing simulation system **110** may be used to test various prototypes of components or structures during specification and design **1002**.

One or more apparatus embodiments, method embodiments, or a combination thereof may be utilized while aircraft **1100** is in service **1012** and/or during maintenance and service **1014**. For example, icing simulation system **110** may be used to test upgrades or changes to aircraft **1100** made during maintenance and service **1014**. For example, if new or different sensor systems for detecting icing conditions are added to aircraft **1100**, icing simulation system **110** may be used to determine whether those sensors perform as desired. The use of a number of the different illustrative embodiments may substantially expedite the assembly of and/or reduce the cost of aircraft **1100**.

Thus, one or more illustrative embodiments provide a method and apparatus for simulating icing conditions. The simulation of the icing conditions may be used to determine whether a test object performs as desired during different types of icing conditions. For example, as requirements change on what types of icing conditions are required to be detected by an aircraft, sensor systems for those types of icing conditions may be designed and tested using an illustrative embodiment.

For example, icing simulation system **110** provides an ability to generate water drops having different sizes. In particular, the water drops may have two ranges of sizes. These ranges may be ranges that represent supercooled large drop icing conditions. The ranges may be generated by controlling different spray bars within icing simulation system **110** to spray drops of water with different sizes. In this manner, the spray bars may generate drops of water having the two desired ranges of drop sizes for supercooled large drop icing conditions.

With icing simulation system **110**, recreating a desired icing condition may reduce the amount of time needed to meet regulations regarding the icing conditions. Further, with the use of icing simulation system **110**, the time, effort, and/or expense needed to certify an aircraft or icing detection system may be reduced.

Of course, icing simulation system **110** may be used to generate icing conditions other than those described in the illustrative examples. For example, other icing conditions may include three or more ranges of drop sizes.

In the text and the figures, in one aspect, an icing simulation system **110** is disclosed including: a wind tunnel **116**; a nozzle system **122** configured to spray drops **132** of water within the wind tunnel **116**; and a controller **128** configured to control a number of properties **140** of the water **130** in the nozzle system **122** such that the nozzle system **122** sprays the drops **132** of the water **130** with different sizes for a desired type of icing condition **131**. In one variant, the icing simulation system **110** includes wherein the number of properties **140** is selected from at least one of a water pressure **202**, an air pressure **204**, and a temperature **208**. In another variant, the icing simulation system **110** includes wherein the nozzle system **122** comprises groups of nozzles **300**.

In yet another variant, the icing simulation system **110** includes wherein in being configured to control the number of properties **140** of the water **130** in the nozzle system **122** such that the nozzle system **122** sprays the drops **132** of the water **130** with the different sizes for the desired type of icing condition **111**, the controller **128** is configured to select at least one of a water pressure **202**, an air pressure **204**, and a temperature **208** for the water **130** for each group of nozzles in the groups of nozzles **300** such that the groups of nozzles **300** spray the drops **132** of the water **130** with the different sizes for the desired type of icing condition **111**. In still another variant, the icing simulation system **110** includes wherein a group of nozzles **300** in the groups of nozzles is associated with a spray bar **308**.

In one instance, the icing simulation system **110** further includes: a spray bar balancing system **600** configured to reduce a time for the spray bar **308** to spray the drops **132** of the water **130** with a desired size. In another instance, the icing simulation system **110** further includes: a plurality of valves **402** configured to control at least one of a water pressure **202**, an air pressure **204**, and a temperature **208** for the water **130**; and a computer system configured to control an operation of the plurality of valves **402**. In yet another instance, the icing simulation system **110** further includes: a sensor system **123** configured to detect a size of the drops **132** of the water **130**. In still yet another instance, the icing simulation system **110** includes wherein the desired type of icing condition **111** is a supercooled large drop icing condition.

In one example, the icing simulation system **110** includes wherein a second type of icing condition **111** includes the drops **132** of the water **130** having a diameter greater than about **0.111** millimeters. In another example, the icing simulation system **110** includes wherein the desired type of icing condition

5 **111** further includes additional drops of the water **130** having a diameter that is less than or equal to about **0.111** millimeters. In yet another example, the icing simulation system **110** includes wherein the wind tunnel **116** includes a test section **528** configured to hold a test object **103**. In still yet another example, the

10 icing simulation system **110** of claim **12**, wherein the test object **103** is selected from one of an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

In one aspect, a method is disclosed for simulating a desired type of icing

15 condition **111** in a wind tunnel **116**, the method including: controlling a number of properties **140** for water **130** sent to a nozzle system **122**, wherein the number of properties **140** is controlled such that drops **132** of the water **130** have different sizes associated with the desired type of icing condition **111**; and spraying the drops **132** of the water **130** from the nozzle system **122** in the wind tunnel **116**,

20 wherein the drops **132** of the water **130** sprayed by the nozzle system **122** have the different sizes for the desired type of icing condition **111**. In one variant, the method includes wherein controlling the number of properties **140** for the water **130** sent to the nozzle system **122**, wherein the number of properties **140** is controlled such that the drops **132** of the water **130** have the different sizes

25 associated with the desired type of icing condition **111** includes: controlling at least one of a water pressure **202**, an air pressure **204**, and a temperature **208** for the water **130** sent to the nozzle system **122**, wherein the number of properties **140** is controlled such that the drops **132** of the water **130** have the different sizes associated with the desired type of icing condition **111**.

30 In another variant, the method includes wherein spraying the drops **132** of the water **130** from the nozzle system **122** in the wind tunnel **116**, wherein the

drops **132** of the water **130** sprayed by the nozzle system **122** have the different sizes for the desired type of icing condition **111** includes: spraying the drops **132** of the water **130** from groups of nozzles **300** in the nozzle system **122** in the wind tunnel **116**, wherein the drops **132** of the water **130** sprayed by the nozzle system have the different sizes for the desired type of icing condition **111**. In yet another variant, the method includes wherein controlling the number of properties **140** for the water **130** sent to the nozzle system **122**, wherein the number of properties is controlled such that the drops **132** of the water **130** have the different sizes associated with the desired type of icing condition **111** includes: selecting at least one of a water pressure **202**, an air pressure **204**, and a temperature **208** for the water **130** for each group of nozzles **300** in the groups of nozzles **300** such that the groups of nozzles **300** spray the drops **132** of the water **130** with the different sizes for the desired type of icing condition **111**.

In yet another variant, the method includes wherein spraying the drops **132** of the water **130** from the groups of nozzles **300** in the nozzle system **122** in the wind tunnel **116**, wherein the drops **132** of the water **130** sprayed by the nozzle system **1220** have the different sizes for the desired type of icing condition **111** includes: spraying the drops **132** of the water **130** from the groups of nozzles **300** in the nozzle system **122** in the wind tunnel **122**, wherein the drops **132** of the water **130** sprayed by the nozzle system **122** have the different sizes for the desired type of icing condition **111**, wherein a group of nozzles in the groups of nozzles **300** is associated with a spray bar. In still yet another variant, the method includes wherein controlling the number of properties **140** for the water **130** sent to the nozzle system **122**, wherein the number of properties **140** is controlled such that the drops **132** of the water **130** have the different sizes associated with the desired type of icing condition **111** includes: controlling the number of properties **140** for the water **130** sent to the nozzle system **122**, wherein the number of properties **140** is controlled such that the drops **132** of the water **130** have the different sizes associated with a supercooled large drop icing condition. In one instance, the method of further includes: placing a test object **103** in a test section **528** of the wind tunnel **116**, wherein the test object **103** is

selected from one an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

5 The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art.

10 Although an illustrative embodiment has been described with respect to aircraft, the illustrative embodiment may be applied to other types of platforms and structures for those platforms. For example, without limitation, other illustrative embodiments may be applied to a mobile platform, a stationary platform, a land-based structure, an aquatic-based structure, a space-based structure, and/or some other suitable platform or structure for those platforms.

15 More specifically, the different illustrative embodiments may be applied to, for example, without limitation, a submarine, a bus, a personnel carrier, a tank, a train, an automobile, a spacecraft, a space station, a satellite, a surface ship, and/or some other suitable platform.

20 Further, different illustrative embodiments may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**

1. An icing simulation system comprising:

a wind tunnel;

a nozzle system configured to spray drops of water within the wind
tunnel; and

a controller configured to control a number of properties of the
water in the nozzle system such that the nozzle system sprays the
drops of the water with different sizes for a desired type of icing
condition.

2. The icing simulation system of claim 1, wherein the number of properties is
selected from at least one of a water pressure, an air pressure, and a
temperature.

3. The icing simulation system of claim 2, wherein the nozzle system further
comprises a plurality of spray bars and each spray bar of the plurality of
spray bars comprises a group of nozzles, wherein the controller is
configured to individually control the spray bars such that the spray bars
spray drops of the water in different size ranges and to control the
temperature of the water in the nozzle system such that the water in the
nozzle system does not freeze within nozzles of the nozzle system, wherein
the two ranges of sizes of the drops of water comprise a supercooled large
drop bimodal distribution, and wherein the desired type of icing condition
includes drops of the water having a diameter in a range from about 0.112
millimeters to about 2.2 millimeters.

4. The icing simulation system of any one of claims 1 or 2, wherein the nozzle system comprises groups of nozzles.
- 5 5. The icing simulation system of claim 4, wherein in being configured to control the number of properties of the water in the nozzle system such that the nozzle system sprays the drops of the water with the different sizes for the desired type of icing condition, the controller is configured to select at least one of a water pressure, an air pressure, and a temperature for the water for each group of nozzles in the groups of nozzles such that the groups of nozzles spray the drops of the water with the different sizes for the desired type of icing condition.
- 10
6. The icing simulation system of claim 4, wherein a group of nozzles in the groups of nozzles is associated with a spray bar.
- 15
7. The icing simulation system of claim 6 further comprising:
- a spray bar balancing system configured to reduce a time for the spray bar to spray the drops of the water with a desired size.
- 20
8. The icing simulation system of any one of claims 1-7 further comprising:
- a plurality of valves configured to control at least one of a water pressure, an air pressure, and a temperature for the water; and
- 25
- a computer system configured to control an operation of the plurality of valves.

9. The icing simulation system of any one of claims 1-8 further comprising:

a sensor system configured to detect a size of the drops of the water.

5

10. The icing simulation system of any one of claims 1-9, wherein the desired type of icing condition is a supercooled large drop icing condition.

10

11. The icing simulation system of any one of claims 1-10, wherein a second type of icing condition includes the drops of the water having a diameter greater than about 0.111 millimeters.

15

12. The icing simulation system of claim 11, wherein the desired type of icing condition further includes additional drops of the water having a diameter that is less than or equal to about 0.111 millimeters.

20

13. The icing simulation system of any one of claims 1 - 12, wherein the wind tunnel includes a test section configured to hold a test object.

25

14. The icing simulation system of claim 13, wherein the test object is selected from one of an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

30

15. A method for simulating a desired type of icing condition in a wind tunnel, the method comprising:

controlling a number of properties for water sent to a nozzle system, wherein the number of properties is controlled such that

drops of the water have different sizes associated with the desired type of icing condition; and

5 spraying the drops of the water from the nozzle system in the wind tunnel, wherein the drops of the water sprayed by the nozzle system have the different sizes for the desired type of icing condition.

10 **16.** The method of claim **15**, wherein controlling the number of properties for the water sent to the nozzle system comprises:

controlling at least one of a water pressure, an air pressure, and a temperature for the water sent to the nozzle system.

15 **17.** The method of any one of claims **15** or **16**, wherein spraying the drops of the water from the nozzle system in the wind tunnel comprises:

spraying the drops of the water from groups of nozzles in the nozzle system in the wind tunnel.

20 **18.** The method of claim **17**, wherein controlling the number of properties for the water sent to the nozzle system comprises:

25 selecting at least one of a water pressure, an air pressure, and a temperature for the water for each group of nozzles in the groups of nozzles.

30 **19.** The method of claim **17**, wherein spraying the drops of the water from the groups of nozzles in the nozzle system in the wind tunnel comprises:

spraying the drops of the water from the groups of nozzles in the nozzle system in the wind tunnel, wherein a group of nozzles in the groups of nozzles is associated with a spray bar.

- 5 **20.** The method of claim **15**, wherein controlling the number of properties for the water sent to the nozzle system comprises:


10 controlling the number of properties such that the drops of the water have the different sizes associated with a supercooled large drop icing condition.

- 21.** The method of any one of claims **15-20** further comprising:




15 placing a test object in a test section of the wind tunnel, wherein the test object is selected from one an airfoil, an aircraft, an engine, a wing, a horizontal stabilizer, a vertical stabilizer, a landing gear system, a fuselage, a flap, an aircraft windshield, an automobile windshield, an automobile, a ship, an engine hood, and a deck of a ship.

20

FIG. 1



2/8







FIG. 5

4/8

FIG. 6



5/8




FIG. 7

6/8





FIG. 8



8/8

