

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2011243210 B2

(54) Title
Method and apparatus for re-attaching the labrum to the acetabulum, including the provision and use of a novel suture anchor system

(51) International Patent Classification(s)
A61B 17/04 (2006.01)

(21) Application No: **2011243210** (22) Date of Filing: **2011.01.13**

(87) WIPO No: **WO11/133233**

(30) Priority Data

| | | |
|-------------------|-------------------|--------------|
| (31) Number | (32) Date | (33) Country |
| 61/326,709 | 2010.04.22 | US |
| 12/839,246 | 2010.07.19 | US |

(43) Publication Date: **2011.10.27**
(44) Accepted Journal Date: **2015.12.24**

(71) Applicant(s)
Pivot Medical, Inc.

(72) Inventor(s)
Pamichev, Chris;Burley, J. Brook;Nikolchev, Julian;Flom, James

(74) Agent / Attorney
Pizzeys Patent and Trade Mark Attorneys, GPO Box 1374, BRISBANE, QLD, 4001

(56) Related Art
US 2009/0112214 A1 (PHILIPPON et al.) 30 April 2009
US 2007/0060922 A1 (DREYFUSS) 15 March 2007
US 5948000 A (Larsen et al.) 7 September 1999
US 2006/0052788 A1 (THELEN et al.) 9 March 2006

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 October 2011 (27.10.2011)

(10) International Publication Number
WO 2011/133233 A1

(51) International Patent Classification:
A61B 17/04 (2006.01)

(74) Agent: PANDISCIO, Mark, J.; Pandiscio & Pandiscio,
470 Totten Pond Road, Waltham, MA 02451 (US).

(21) International Application Number:
PCT/US2011/021173

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
13 January 2011 (13.01.2011)

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

Published:

(26) Publication Language: English

— with international search report (Art. 21(3))

(30) Priority Data:
61/326,709 22 April 2010 (22.04.2010) US
12/839,246 19 July 2010 (19.07.2010) US

(71) Applicant (for all designated States except US): PIVOT
MEDICAL, INC. [US/US]; 247 Humboldt Court, Sun-
nyvale, CA 94089 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PAMICHEV, Chris
[US/US]; 10450 Corte de Seville, Cupertino, CA 95014
(US). BURLEY, J., Brook [US/US]; 18334A South
Springer Road, Mountain View, CA 94040 (US).
NIKOLCHEV, Julian [US/US]; 251 Durazna Way, Port-
ola Valley, CA 94208 (US). FLOM, James [US/US];
1717 Saint Francis Way, San Carlos, CA 94070 (US).



(54) Title: METHOD AND APPARATUS FOR RE-ATTACHING THE LABRUM TO THE ACETABULUM, INCLUDING
THE PROVISION AND USE OF A NOVEL SUTURE ANCHOR SYSTEM




FIG. 57

(57) Abstract: Apparatus for securing a first object to a second object, the apparatus comprising: an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section and a second section, the first section of the lumen being disposed distal to the second section of the lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen; at least one longitudinally-extending slit extending through the side wall of the elongated body and communicating with the lumen, the at least one longitudinally-extending slit having a distal end and a proximal end, with the distal end of the at least one longitudinally-extending slit being spaced from the distal end of the elongated body; and an elongated element extending through the lumen of the elongated body.

WO 2011/133233 A1

METHOD AND APPARATUS FOR RE-ATTACHING THE LABRUM TO
THE ACETABULUM, INCLUDING THE PROVISION AND USE OF A
NOVEL SUTURE ANCHOR SYSTEM

5

Inventors

Chris Pamichev

J. Brook Burley

Julian Nikolchev

James Flom

10

Reference To Pending Prior Patent Applications

This patent application:

(i) is a continuation-in-part of pending prior U.S. Patent Application Serial No. 12/839,246, filed 07/19/2010 by Chris Pamichev et al. for METHOD AND APPARATUS FOR RE-ATTACHING THE LABRUM TO THE ACETABULUM, INCLUDING THE PROVISION AND USE OF A NOVEL SUTURE ANCHOR SYSTEM (Attorney's Docket No. FIAN-4655), which in turn claims benefit of (1) prior U.S. Provisional Patent Application Serial No. 61/271,205, filed 07/17/2009 by Chris Pamichev et al. for METHOD

15

20

AND APPARATUS FOR RE-SECURING THE LABRUM TO THE ACETABULUM, INCLUDING THE PROVISION AND USE OF A NOVEL NANO TACK SYSTEM (Attorney's Docket No. FIAN-46 PROV), and (2) pending prior U.S. Provisional Patent

5 Application Serial No. 61/326,709, filed 04/22/2010 by Chris Pamichev et al. for METHOD AND APPARATUS FOR RE-SECURING THE LABRUM TO THE ACETABULUM, INCLUDING THE PROVISION AND USE OF A NOVEL SUTURE ANCHOR SYSTEM (Attorney's Docket No. FIAN-55 PROV); and

10 (ii) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 61/326,709, filed 04/22/2010 by Chris Pamichev et al. for METHOD AND APPARATUS FOR RE-SECURING THE LABRUM TO THE ACETABULUM, INCLUDING THE PROVISION AND USE OF A NOVEL SUTURE ANCHOR SYSTEM (Attorney's Docket No. FIAN-55 PROV).

15 The three (3) above-identified patent applications are hereby incorporated herein by reference.

20

Field Of The Invention

This invention relates to surgical methods and apparatus in general, and more particularly to surgical methods and apparatus for treating a hip joint.

5

Background Of The Invention

The Hip Joint In General

The hip joint is a ball-and-socket joint which movably connects the leg to the torso. The hip joint is capable of a wide range of different motions, e.g., flexion and extension, abduction and adduction, medial and lateral rotation, etc. See Figs. 1A, 1B, 1C and 1D.

With the possible exception of the shoulder joint, the hip joint is perhaps the most mobile joint in the body. Significantly, and unlike the shoulder joint, the hip joint carries substantial weight loads during most of the day, in both static (e.g., standing and sitting) and dynamic (e.g., walking and running) conditions.

20

The hip joint is susceptible to a number of different pathologies. These pathologies can have both congenital and injury-related origins. In some cases, the pathology can be substantial at the outset.

5 In other cases, the pathology may be minor at the outset but, if left untreated, may worsen over time. More particularly, in many cases, an existing pathology may be exacerbated by the dynamic nature of the hip joint and the substantial weight loads imposed 10 on the hip joint.

The pathology may, either initially or thereafter, significantly interfere with patient comfort and lifestyle. In some cases, the pathology can be so severe as to require partial or total hip replacement. A number of procedures have been 15 developed for treating hip pathologies short of partial or total hip replacement, but these procedures are generally limited in scope due to the significant difficulties associated with treating the hip joint.

20 A better understanding of various hip joint pathologies, and also the current limitations

associated with their treatment, can be gained from a more thorough understanding of the anatomy of the hip joint.

5

Anatomy Of The Hip Joint

The hip joint is formed at the junction of the leg and the torso. More particularly, and looking now at Fig. 2, the head of the femur is received in the acetabular cup of the hip, with a plurality of ligaments and other soft tissue serving to hold the bones in articulating condition.

More particularly, and looking now at Fig. 3, the femur is generally characterized by an elongated body terminating, at its top end, in an angled neck which supports a hemispherical head (also sometimes referred to as "the ball"). As seen in Figs. 3 and 4, a large projection known as the greater trochanter protrudes laterally and posteriorly from the elongated body adjacent to the neck of the femur. A second, somewhat smaller projection known as the lesser trochanter protrudes medially and posteriorly from the elongated

10

15

20

body adjacent to the neck. An intertrochanteric crest (Figs. 3 and 4) extends along the periphery of the femur, between the greater trochanter and the lesser trochanter.

5 Looking next at Fig. 5, the hip socket is made up of three constituent bones: the ilium, the ischium and the pubis. These three bones cooperate with one another (they typically ossify into a single "hip bone" structure by the age of 25 or so) in order to 10 collectively form the acetabular cup. The acetabular cup receives the head of the femur.

Both the head of the femur and the acetabular cup are covered with a layer of articular cartilage which protects the underlying bone and facilitates motion.

15 See Fig. 6.

Various ligaments and soft tissue serve to hold the ball of the femur in place within the acetabular cup. More particularly, and looking now at Figs. 7 and 8, the ligamentum teres extends between the ball 20 of the femur and the base of the acetabular cup. As seen in Figs. 8 and 9, a labrum is disposed about the

perimeter of the acetabular cup. The labrum serves to increase the depth of the acetabular cup and effectively establishes a suction seal between the ball of the femur and the rim of the acetabular cup, thereby helping to hold the head of the femur in the acetabular cup. In addition to the foregoing, and looking now at Fig. 10, a fibrous capsule extends between the neck of the femur and the rim of the acetabular cup, effectively sealing off the ball-and-socket members of the hip joint from the remainder of the body. The foregoing structures (i.e., the ligamentum teres, the labrum and the fibrous capsule) are encompassed and reinforced by a set of three main ligaments (i.e., the iliofemoral ligament, the ischiofemoral ligament and the pubofemoral ligament) which extend between the femur and the perimeter of the hip socket. See, for example, Figs. 11 and 12, which show the iliofemoral ligament, with Fig. 11 being an anterior view and Fig. 12 being a posterior view.

Pathologies Of The Hip Joint

As noted above, the hip joint is susceptible to a number of different pathologies. These pathologies can have both congenital and injury-related origins.

5 By way of example but not limitation, one important type of congenital pathology of the hip joint involves impingement between the neck of the femur and the rim of the acetabular cup. In some cases, and looking now at Fig. 13, this impingement can occur due to irregularities in the geometry of the femur. This type of impingement is sometimes referred to as cam-type femoroacetabular impingement (i.e., cam-type FAI). In other cases, and looking now at Fig. 14, the impingement can occur due to irregularities in the geometry of the acetabular cup. This latter type of impingement is sometimes referred to as pincer-type femoroacetabular impingement (i.e., pincer-type FAI). Impingement can result in a reduced range of motion, substantial pain and, in some cases, 10 significant deterioration of the hip joint.

15

20

By way of further example but not limitation, another important type of congenital pathology of the hip joint involves defects in the articular surface of the ball and/or the articular surface of the acetabular cup. Defects of this type sometimes start out fairly small but often increase in size over time, generally due to the dynamic nature of the hip joint and also due to the weight-bearing nature of the hip joint. Articular defects can result in substantial pain, induce and/or exacerbate arthritic conditions and, in some cases, cause significant deterioration of the hip joint.

By way of further example but not limitation, one important type of injury-related pathology of the hip joint involves trauma to the labrum. More particularly, in many cases, an accident or sports-related injury can result in the labrum being torn away from the rim of the acetabular cup, typically with a tear running through the body of the labrum. See Fig. 15. These types of injuries can be very painful for the patient and, if left untreated,

can lead to substantial deterioration of the hip joint.

The General Trend Toward Treating Joint Pathologies

Using Minimally-Invasive, And Earlier, Interventions

The current trend in orthopedic surgery is to treat joint pathologies using minimally-invasive techniques. Such minimally-invasive, "keyhole" surgeries generally offer numerous advantages over traditional, "open" surgeries, including reduced trauma to tissue, less pain for the patient, faster recuperation times, etc.

By way of example but not limitation, it is common to re-attach ligaments in the shoulder joint using minimally-invasive, "keyhole" techniques which do not require large incisions into the interior of the shoulder joint. By way of further example but not limitation, it is common to repair torn meniscal cartilage in the knee joint, and/or to replace ruptured ACL ligaments in the knee joint, using minimally-invasive techniques.

5

While such minimally-invasive approaches can require additional training on the part of the surgeon, such procedures generally offer substantial advantages for the patient and have now become the standard of care for many shoulder joint and knee joint pathologies.

10

In addition to the foregoing, in view of the inherent advantages and widespread availability of minimally-invasive approaches for treating pathologies of the shoulder joint and knee joint, the current trend is to provide such treatment much earlier in the lifecycle of the pathology, so as to address patient pain as soon as possible and so as to minimize any exacerbation of the pathology itself. This is in marked contrast to traditional surgical practices, which have generally dictated postponing surgical procedures as long as possible so as to spare the patient from the substantial trauma generally associated with invasive surgery.

15

20

Treatment For Pathologies Of The Hip Joint

5

Unfortunately, minimally-invasive treatments for pathologies of the hip joint have lagged far behind minimally-invasive treatments for pathologies of the shoulder joint and the knee joint. This is generally due to (i) the constrained geometry of the hip joint itself, and (ii) the nature and location of the pathologies which must typically be addressed in the hip joint.

10

More particularly, the hip joint is generally considered to be a "tight" joint, in the sense that there is relatively little room to maneuver within the confines of the joint itself. This is in marked contrast to the shoulder joint and the knee joint, which are generally considered to be relatively "spacious" joints (at least when compared to the hip joint). As a result, it is relatively difficult for surgeons to perform minimally-invasive procedures on the hip joint.

15

20

Furthermore, the pathways for entering the interior of the hip joint (i.e., the natural pathways which exist between adjacent bones and/or delicate

5

neurovascular structures) are generally much more constraining for the hip joint than for the shoulder joint or the knee joint. This limited access further complicates effectively performing minimally-invasive procedures on the hip joint.

10

In addition to the foregoing, the nature and location of the pathologies of the hip joint also complicate performing minimally-invasive procedures on the hip joint. By way of example but not limitation, consider a typical detachment of the labrum in the hip joint. In this situation, instruments must generally be introduced into the joint space using an angle of approach which is offset from the angle at which the instrument addresses the tissue. This makes drilling into bone, for example, significantly more complicated than where the angle of approach is effectively aligned with the angle at which the instrument addresses the tissue, such as is frequently the case in the shoulder joint. Furthermore, the working space within the hip joint is typically extremely limited, further complicating repairs where the angle of

15

20

approach is not aligned with the angle at which the instrument addresses the tissue.

As a result of the foregoing, minimally-invasive hip joint procedures are still relatively difficult to perform and relatively uncommon in practice.

Consequently, patients are typically forced to manage their hip pain for as long as possible, until a resurfacing procedure or a partial or total hip replacement procedure can no longer be avoided. These procedures are generally then performed as a highly-invasive, open procedure, with all of the disadvantages associated with highly-invasive, open procedures.

As a result, there is, in general, a pressing need for improved methods and apparatus for treating pathologies of the hip joint.

Re-attaching The Labrum Of The Hip Joint

As noted above, hip arthroscopy is becoming increasingly more common in the diagnosis and treatment of various hip pathologies. However, due to

5

the anatomy of the hip joint and the pathologies associated with the same, hip arthroscopy is currently practical for only selected pathologies and, even then, hip arthroscopy has generally met with limited success.

10

One procedure which is sometimes attempted arthroscopically relates to the repair of a torn and/or detached labrum. This procedure may be attempted (i) when the labrum has been damaged but is still sufficiently healthy and intact as to be capable of repair and/or re-attachment, and (ii) when the labrum has been deliberately detached (e.g., so as to allow for acetabular rim trimming to treat a pathology such as a pincer-type FAI) and needs to be subsequently re-attached. See, for example, Fig. 16, which shows a normal labrum which has its base securely attached to the acetabulum, and Fig. 17, which shows a portion of the labrum (in this case the tip) detached from the acetabulum. In this respect it should also be appreciated that repairing the labrum rather than removing the labrum is generally

15

20

desirable, inasmuch as studies have shown that patients whose labrum has been repaired tend to have better long-term outcomes than patients whose labrum has been removed.

5 Unfortunately, current methods and apparatus for arthroscopically repairing (e.g., re-attaching) the labrum are somewhat problematic. The present invention is intended to improve upon the current approaches for labrum repair.

10 More particularly, current approaches for arthroscopically repairing the labrum typically use apparatus originally designed for use in re-attaching ligaments to bone. For example, one such approach utilizes a screw-type bone anchor, with two sutures extending therefrom, and involves deploying the bone anchor in the acetabulum above the labrum re-attachment site. A first one of the sutures is passed either through the detached labrum or, alternatively, around the detached labrum. Then the 15 first suture is tied to the second suture so as to

support the labrum against the acetabular rim. See Fig. 18.

Unfortunately, bone anchors of the sort described above are traditionally used for re-attaching 5 ligaments to bone and, as a result, tend to be relatively large, since they must carry the substantial pull-out forces normally associated with ligament reconstruction. However, this large anchor size is generally unnecessary for labrum 10 re-attachment, since the labrum is not subjected to substantial pull-out forces, and the large anchor size typically causes unnecessary trauma to the patient.

Furthermore, the large size of traditional bone anchors can be problematic when the anchors are used 15 for labrum re-attachment, since the bone anchors generally require a substantial bone mass for secure anchoring, and such a large bone mass is generally available only a substantial distance up the acetabular shelf. In addition, the large size of the 20 bone anchors generally makes it necessary to set the bone anchor a substantial distance up the acetabular

shelf, in order to ensure that the distal tip of the bone anchor does not inadvertently break through the acetabular shelf and contact the articulating surfaces of the joint. However, labral re-attachment utilizing a bone anchor set high up into the acetabular shelf creates a suture path, and hence a labral draw force, which is not directly aligned with the portion of the acetabular rim where the labrum is to be re-attached. As a result, an "indirect" draw force (also known as eversion) is typically applied to the labrum, i.e., the labrum is drawn around the rim of the acetabulum rather than directly into the acetabulum. See Fig. 18. This can sometimes result in a problematic labral re-attachment and, ultimately, can lead to a loss of the suction seal between the labrum and femoral head, which is a desired outcome of the labral re-attachment procedure.

20 Alternatively, the suture path can also surround the labrum, thus placing a suture on both sides of the labrum, including the articular side of the labrum, and thus exposing the articular surface of the femur

to a foreign body, which could in turn cause damage to the articular surface (i.e., the articular cartilage) of the femur.

Accordingly, a new approach is needed for
5 arthroscopically re-attaching the labrum to the acetabulum.

Summary Of The Invention

The present invention provides a novel method and
10 apparatus for re-attaching the labrum to the acetabulum. Among other things, the present invention comprises the provision and use of a novel suture anchor system.

In one form of the invention, there is provided
15 apparatus for securing a first object to a second object, the apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section
20 and a second section, the first section of the lumen being disposed distal to the second section of the

lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen;

at least one longitudinally-extending slit

extending through the side wall of the elongated body

5 and communicating with the lumen, the at least one

longitudinally-extending slit having a distal end and

a proximal end, with the distal end of the at least

one longitudinally-extending slit being spaced from

the distal end of the elongated body; and

10 an elongated element extending through the lumen

of the elongated body, the elongated element

comprising a proximal end and a distal end and having

an enlargement at its distal end, the enlargement

having a diameter greater than the second section of

15 the lumen.

In another form of the invention, there is provided apparatus for securing a first object to a second object, the apparatus comprising:

an elongated body having a distal end, a proximal

20 end, and a lumen extending between the distal end and

the proximal end, the lumen comprising a first section

5

and a second section, the first section of the lumen being disposed distal to the second section of the lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen; and

10

a suture extending through the lumen of the elongated body, the suture comprising a proximal end and a distal end and having a suture knot at its distal end, the suture knot having a diameter greater than the second section of the lumen.

In another form of the invention, there is provided apparatus for securing a first object to a second object, the apparatus comprising:

15

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section and a second section, the first section of the lumen being disposed distal to the second section of the lumen and with the first section of the lumen having a wider diameter than the second section of the lumen;

20

the side wall of the elongated body having a weakened section therein adjacent to the second section of the lumen; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second section of the lumen.

10 In another form of the invention, there is provided a method for securing a first object to a second object, the method comprising:

providing apparatus comprising:
an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section and a second section, the first section of the lumen being disposed distal to the second section of the lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen;

at least one longitudinally-extending slit extending through the side wall of the elongated body and communicating with the lumen, the at least one longitudinally-extending slit having a distal end and a proximal end, with the distal end of the at least one longitudinally-extending slit being spaced from the distal end of the elongated body; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second section of the lumen;

inserting the elongated body into the second object;

moving the enlargement proximally so as to expand the elongated body; and

securing the first object to the second object with the elongated element.

In another form of the invention, there is provided a method for securing a first object to a second object, the method comprising:

providing apparatus comprising:

5 an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section and a second section, the first section of the lumen being disposed distal to the second section of the lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen; and

10 a suture extending through the lumen of the elongated body, the suture comprising a proximal end and a distal end and having a suture knot at its distal end, the suture knot having a diameter greater than the second section of the lumen;

15 inserting the elongated body into the second object;

20 moving the suture knot proximally so as to expand the elongated body; and

securing the first object to the second object with the suture.

In another form of the invention, there is provided a method for securing a first object to a second object, the method comprising:

5 providing apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first section and a second section, the first section of the 10 lumen being disposed distal to the second section of the lumen, and with the first section of the lumen having a wider diameter than the second section of the lumen;

15 the side wall of the elongated body having a weakened section therein adjacent to the second section of the lumen; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having 20 an enlargement at its distal end, the enlargement

having a diameter greater than the second section of the lumen;

inserting the elongated body into the second object;

5 moving the enlargement proximally so as to expand the elongated body; and

securing the first object to the second object with the elongated element.

10 Brief Description Of The Drawings

These and other objects and features of the present invention will be more fully disclosed or rendered obvious by the following detailed description of the preferred embodiments of the invention, which is to be considered together with the accompanying drawings wherein like numbers refer to like parts, and further wherein:

Figs. 1A-1D are schematic views showing various aspects of hip motion;

20 Fig. 2 is a schematic view showing bone structures in the region of the hip joint;

Fig. 3 is a schematic anterior view of the femur;

Fig. 4 is a schematic posterior view of the top end of the femur;

Fig. 5 is a schematic view of the pelvis;

5 Figs. 6-12 are schematic views showing bone and soft tissue structures in the region of the hip joint;

Fig. 13 is a schematic view showing cam-type femoroacetabular impingement (i.e., cam-type FAI);

10 Fig. 14 is a schematic view showing pincer-type femoroacetabular impingement (i.e., pincer-type FAI);

Fig. 15 is a schematic view showing a labral tear;

15 Fig. 16 is a schematic view showing a normal labrum which has its base securely attached to the acetabulum;

Fig. 17 is a schematic view showing a portion of the labrum detached from the acetabulum;

Fig. 18 is a schematic view showing a bone anchor being used to re-attach the labrum to the acetabulum;

Figs. 19-27 are schematic views showing a novel suture anchor system for use in arthroscopically re-attaching a detached labrum to the acetabulum;

5 Figs. 28 and 28A are schematic views showing the suture anchor system of Figs. 19-27 being used to re-attach the labrum to the acetabulum;

Figs. 29-31 are schematic views showing an alternative form of the suture anchor system of the present invention;

10 Fig. 32 is a schematic view showing another alternative form of the suture anchor system of the present invention;

15 Figs. 33-38 are schematic views showing alternative arrangements for coupling the anchor of the suture anchor system of Figs. 19-27 to the inserter of the suture anchor system of Figs. 19-27;

Figs. 39-41 are schematic views showing still another alternative form of the suture anchor system of the present invention;

Fig. 42 is a schematic view showing yet another alternative form of the suture anchor system of the present invention;

5 Figs. 43-45 are schematic views showing another alternative form of the suture anchor system of the present invention;

Figs. 46-48 are schematic views showing still another alternative form of the suture anchor system of the present invention;

10 Figs. 49-50 are schematic views showing yet another alternative form of the suture anchor system of the present invention;

15 Fig. 51 is a schematic view showing another alternative form of the suture anchor system of the present invention; and

Figs. 52-54 are schematic views showing still another alternative form of the suture anchor system of the present invention; and

20 Figs. 55-60 are schematic views showing yet another alternative form of the present invention.

Detailed Description Of The InventionThe Novel Suture Anchor System Of
The Present Invention In General

5 The present invention provides a novel method and apparatus for arthroscopically re-attaching the labrum to the acetabulum. Among other things, the present invention comprises the provision and use of a novel suture anchor system.

10 More particularly, and looking now at Fig. 19, there is shown a novel suture anchor system 5 for use in arthroscopically re-attaching a detached labrum to the acetabulum. Suture anchor system 5 generally comprises an anchor 10, a suture 15 secured to anchor 10, and an inserter 20 for delivering anchor 10 into the acetabulum, whereby suture 15 may be used to secure a detached labrum to the acetabular rim as will hereinafter be discussed in further detail. Suture anchor system 5 preferably also comprises a hollow guide 25 for delivering components from outside of the body to the acetabulum, and a punch (or drill) 30

which may be used to prepare a seat for anchor 10 in the acetabulum.

Looking next at Figs. 19-23, anchor 10 comprises a generally cylindrical body 35 having a distal end 40, a proximal end 45, and a lumen 50 extending between distal end 40 and proximal end 45. In one preferred form of the present invention, lumen 50 comprises a distal end reservoir 55, a short intermediate portion 60, and an elongated proximal portion 65. As seen in Fig. 23, distal end reservoir 55 has a diameter which is greater than the diameter of short intermediate portion 60, and short intermediate portion 60 has a diameter which is greater than the diameter of elongated proximal portion 65. And in one preferred form of the present invention, the outer surface of generally cylindrical body 35 comprises a plurality of ribs 70 spaced along the length of generally cylindrical body 35, so as to enhance the "holding power" of anchor 10 in bone. In one particularly preferred form of the present invention, ribs 70 sub-divide the length of generally

cylindrical body 35 into a plurality of segments, with each segment having a generally frusto-conical configuration (Figs. 21 and 22).

Near (but spaced from) the distal end 40 of generally cylindrical body 35, there is provided a longitudinally-extending slit 75 which extends completely through one side wall (but not the other) of generally cylindrical body 35. Thus, longitudinally-extending slit 75 communicates with lumen 50 of anchor 10. The distal end of longitudinally-extending slit 75 terminates in a distal relief hole 80, and the proximal end of longitudinally-extending slit 75 terminates in a proximal relief hole 85. It will be appreciated that distal relief hole 80 is spaced from distal end 40 of generally cylindrical body 35, so that a solid distal ring 90 is located at the distal end of generally cylindrical body 35, whereby to provide the distal end of generally cylindrical body 35 with a degree of structural integrity.

Looking now at Figs. 20 and 24-26, suture 15 generally comprises a distal loop 95 terminating in an enlargement 100 at its distal end and connected to a proximal open loop 105 at its proximal end. More particularly, distal loop 95 extends through short intermediate portion 60 and elongated proximal portion 65 of lumen 50. Enlargement 100 may comprise a solid member (e.g., cylindrical, conical, etc.) attached to the distal end of distal loop 95, or it may comprise a suture knot formed by knotting off the distal ends of distal loop 95 of suture 15, etc. Where enlargement 100 comprises a suture knot, this suture knot may or may not be hardened, shaped or stabilized with cement, heat, etc. For purposes of illustration, enlargement 100 is shown in the drawings schematically, i.e., as a generally cylindrical structure, but it should be appreciated that this is being done solely for clarity of illustration, and enlargement 100 may assume any other shapes and/or configurations (including that of a suture knot) consistent with the present invention.

Enlargement 100 is sized so that it is small enough to

be seated in distal end reservoir 55 of generally cylindrical body 35 (see, for example, Figs. 24 and 25), but large enough so that it may not enter short intermediate portion 60 of generally cylindrical body 35 without causing radial expansion of generally cylindrical body 35 (see, for example, Fig. 26).
5 Proximal open loop 105 extends back through the interior of inserter 20 (Figs. 19 and 20) and provides a pair of free suture ends emanating from the proximal 10 end of inserter 20 (Fig. 19), as will hereinafter be discussed.

Looking now at Figs. 19 and 20, inserter 20 generally comprises a hollow push tube 110 having a lumen 115 extending therethrough. Inserter 20 15 terminates at its distal end in a drive surface 120 for engaging the proximal end 45 of anchor 10, and terminates at its proximal end in a handle 125. Handle 125 may include features to secure the free 20 ends of suture 15, e.g., one or more suture cleats, suture slots, suture clamps, etc. Where such features are provided, and where appropriate, handle 125 may

also include one or more release mechanisms to release the free ends of suture 15. Handle 125 may also have one or more mechanisms to apply tension to the secured free ends of suture 15. Suture 15 (i.e., proximal 5 open loop 105 of suture 15) extends through lumen 115 of hollow push tube 110. By maintaining a slight proximally-directed tension on the proximal end of suture 15 (e.g., by maintaining a slight proximally-directed tension on the free suture ends of 10 proximal open loop 105), anchor 10 can be held against the drive surface 120 of hollow push tube 110, thereby providing a degree of control for maneuvering the anchor.

Preferably anchor 10, suture 15 and inserter 20 15 are pre-assembled into a single unit, with suture 15 extending back through lumen 115 of inserter 20 with a slight proximal tension so as to hold anchor 10 on the distal end of inserter 20.

Suture anchor system 5 preferably also comprises 20 a hollow guide 25 for guiding components from outside of the body to the acetabulum. More particularly,

hollow guide 25 generally comprises a lumen 130 for slidably receiving anchor 10 and inserter 20 therein, as will hereinafter be discussed. The internal diameter of hollow guide 25 is preferably 5 approximately equal to the largest external feature of anchor 10 (e.g., one or more of the barbs 70), so that anchor 10 can make a close sliding fit within the interior of hollow guide 25. Alternatively, the internal diameter of hollow guide 25 may be slightly 10 smaller or larger than the largest external feature of anchor 10 if desired. Where suture anchor system 5 also comprises a punch (or drill) 30, lumen 130 of hollow guide 25 is preferably sized to slidably receive punch (or drill) 30, as will hereinafter be 15 discussed. The distal end of hollow guide 25 preferably includes a sharp tip/edge for penetrating the labrum and engaging the acetabulum, as will hereinafter be discussed.

If desired, and looking now at Figs. 19 and 27, 20 suture anchor system 5 may also comprise a punch (or drill) 30 having a sharp distal end 135 and a proximal

end 140 having a handle 145 mounted thereto. Where element 30 is a drill, handle 145 could comprise a mount for the drill so as to facilitate turning the drill with a powered driver, etc. Again, the sharp 5 distal end 135 of punch (or drill) 30 is adapted to penetrate the acetabulum, as will hereinafter be discussed.

Method For Arthroscopically Re-Attaching The

10 Labrum To The Acetabulum Using The Novel

Suture Anchor System Of The Present Invention

Suture anchor system 5 is preferably used as follows to secure a detached labrum to the acetabulum.

First, the sharp distal end 136 of hollow guide 15 25 is passed through the labrum and positioned against the acetabulum at the location where anchor 10 is to be deployed. Preferably the sharp distal end of hollow guide 25 penetrates through the labrum and a short distance into the acetabulum so as to stabilize 20 the hollow guide vis-à-vis the acetabulum. A stylet (e.g., an obturator) may be used to fill the hollow

5

guide 25 during such insertion and thus prevent tissue coring of the labrum during insertion. The distal portion of the punch (or drill) 30 may also be used to fill the hollow tip of the hollow guide 25 during such insertion.

10

Next, if desired, punch (or drill) 30 may be used to prepare a seat in the acetabulum to receive anchor 10. More particularly, if punch (or drill) 30 is used, the sharp distal end 135 of punch (or drill) 30 is passed through hollow guide 25 (thereby also passing through the labrum) and advanced into the acetabulum so as to form an opening (i.e., a seat) in the bone to receive anchor 10. Then, while hollow guide 25 remains stationary, punch (or drill) 30 is removed from hollow guide 25.

15

Next, inserter 20, carrying anchor 10 thereon, is passed through hollow guide 25 (thereby also passing through the labrum) and into the seat formed in the acetabulum. As anchor 10 is advanced into the bone, the body of anchor 10 (e.g., ribs 70) makes an interference fit with the surrounding bone, whereby to

initially bind the anchor to the bone. At the same time, the solid distal ring 90 located at the distal end of the anchor provides the structural integrity needed to keep the anchor intact while it penetrates 5 into the bone. When anchor 10 has been advanced an appropriate distance into the acetabulum, the proximal end of suture 15 (i.e., proximal open loop 105) is pulled proximally while the distal end of inserter 20 is held in position, thereby causing enlargement 100 10 to move proximally relative to the generally cylindrical body 35, forcing the distal end of generally cylindrical body 35 to split and expand, in the manner shown in Fig. 26, whereby to further bind anchor 10, and hence suture 15, to the bone. In one 15 preferred form of the present invention, expansion of generally cylindrical body 35 occurs along some or all of the circumference of the generally cylindrical body, and there may be variations in the amount of expansion about the circumference of the generally 20 cylindrical body, e.g., with the construction shown in Fig. 26, there may be greater expansion in a direction

perpendicular to the direction of longitudinally-extending slits 75 (for example, in the direction of the arrows shown in Fig. 26). It will be appreciated that the location and magnitude of expansion of generally cylindrical body 35 can be controlled by the number and location of longitudinally-extending slits 75, the configuration of enlargement 100, the configuration of generally cylindrical body 35 (e.g., its lumen 50 and the associated side wall of the cylindrical body 35 adjacent the lumen), etc. In one preferred form of the present invention, expansion of generally cylindrical body 35 occurs at the zone where distal end reservoir 55 meets short intermediate portion 60, with expansion occurring as enlargement 100 moves out of the comparatively larger diameter distal end reservoir 55 and into the comparatively smaller diameter intermediate portion 60.

Significantly, in view of the modest holding power required to secure the labrum in place, anchor 10 can have a very small size, much smaller than a typical bone anchor of the sort used to hold a

ligament in place. By way of example but not limitation, anchor 10 may have a length of 0.325 inches, an outer diameter (unexpanded) of 0.063 inches, and an outer diameter (expanded) of 0.080 inches. This small size enables a minimal puncture to be made in the labrum (and hence a minimal hole to be made in the labrum), thus reducing potential damage to the labral tissue and enabling a more accurate puncture location through the labrum. The small size of anchor 10 also allows the anchor to be placed closer to, or directly into, the rim of the acetabular cup, without fear of the anchor penetrating into the articulating surfaces of the joint. See, for example, Fig. 28, which shows anchor 10 placed close to the rim of the acetabular cup, and Fig. 28A, which shows anchor 10 placed directly into the rim of the acetabular cup. This significantly reduces, or entirely eliminates, the labrum eversion problems discussed above. Furthermore, the small size of the anchor significantly reduces trauma to the tissue of the patient.

Once anchor 10 has been set in the acetabulum, guide 25 is removed from the surgical site, leaving anchor 10 deployed in the acetabulum and suture 15 extending out through the labrum.

5 This process may then be repeated as desired so as to deploy additional anchors through the labrum and into the acetabulum, with each anchor having a pair of associated free suture ends extending out through the labrum.

10 Finally, the labrum may be secured to the acetabular cup by tying the labrum down to the acetabulum using the free suture ends emanating from the one or more anchors.

15 Some Alternative Constructions For The Novel

Suture Anchor System Of The Present Invention

If desired, and looking now at Figs. 29-31, a deployment cylinder 150 may be disposed on distal loop 95 of suture 15 just proximal to enlargement 100.

20 Deployment cylinder 150 can be advantageous where enlargement 100 comprises a suture knot, since the

deployment cylinder can ensure the uniform application of a radial expansion force to the wall of the anchor body even where the suture knot has a non-uniform configuration. Deployment cylinder 150 may have a 5 beveled proximal end 155 to facilitate expansion of anchor 10 when suture 15 is pulled proximally. Fig. 29 depicts anchor 10 in an unexpanded state, while Figs. 30-31 depict the anchor 10 in an expanded state.

Furthermore, one or more of the ribs 70 may 10 utilize a different construction than that shown in Figs. 21-23. More particularly, in Figs. 21-23, each of the ribs 70 comprises a proximal portion which comprises a cylindrical surface 160. Such a cylindrical surface provides increased surface area 15 contact for engaging the adjacent bone when anchor 10 is disposed in the acetabulum. However, if desired, one or more of the ribs 70 may terminate in a sharp proximal rim 165 (Figs. 29-31) for biting into adjacent bone when suture 15 is pulled proximally.

20 Or one or more of the ribs 70 may be slotted as shown in Fig. 32 so as to provide a rib with increased

5

flexibility. Such a construction can be useful since it allows the slotted rib 70 to be radially compressed so as to fit within inserter 20 and then radially expanded, in a spring-like manner, when deployed in the acetabulum.

10

If desired, alternative arrangements can be provided for coupling anchor 10 to the distal end of inserter 20. More particularly, in Figs. 33 and 34, a male-female connection is used to couple anchor 10 to inserter 20, with anchor 10 having a male projection 170 and inserter 20 having a corresponding female recess 175. In Figs. 35 and 36, inserter 20 includes the male projection 170 and anchor 10 has the corresponding female recess 175. In Figs. 37 and 38, inserter 20 has a convex surface 180 and anchor 10 has a corresponding concave surface 185. Still other constructions of this type will be apparent to those skilled in the art in view of the present disclosure.

15

Looking next at Figs. 39-41, in another form of present invention, suture 15 is intended to exit anchor 10 at proximal relief hole 85 and extend along

20

the exterior of the generally cylindrical body 35. If desired, slots 190 may be provided in ribs 70 so as to accommodate suture 15 therein.

In another form of the present invention, and looking now at Fig. 42, suture 15 can be replaced by a solid shaft 195. More particularly, solid shaft 195 extends through lumen 50 of anchor 10 and lumen 115 of inserter 20, and has enlargement 100 formed on its distal end. Proximal movement of solid shaft 195 causes enlargement 100 to expand the distal end of anchor 10 so as to cause anchor 10 to grip adjacent bone.

If desired, one or both of distal relief hole 80 and proximal relief hole 85 may be omitted, with longitudinally-extending slit 75 terminating in a blind surface at one or both ends.

Furthermore, if desired more than one longitudinally-extending slit 75 may be provided in anchor 10, e.g., two diametrically-opposed longitudinally-extending slits 75 may be provided. Additionally, if desired, longitudinally-extending

slit 75 may extend all the way to the distal end of the anchor body, rather than stopping short of the distal end of the anchor body. See, for example, Figs. 43 and 44, which show two diametrically-opposed, longitudinally-extending slits 75, wherein the slits extend all the way to the distal end of anchor 10, and with the two figures showing exemplary rib configurations. See also Fig. 45, which shows an anchor 10 having a single longitudinally-extending slit 75, wherein the slit extends all the way to the distal end of the anchor.

If desired, and looking now at Figs. 46-48, lumen 50 may extend along a longitudinal axis 200 which is eccentric to the longitudinal axis 205 of generally cylindrical body 35. Such an eccentric construction can provide a thinner side wall on one side of the anchor and a thicker side wall on another side of the anchor, so as to create preferential body expansion.

Or anchor 10 may be provided with an angled through-hole to create varying wall thicknesses and non-symmetric effects as shown in Figs. 49 and 50.

5

If desired, and looking now at Fig. 51, anchor 10 can be constructed so that longitudinally-extending slit 75 is omitted entirely. In this form of the invention, anchor 10 is preferably formed with one or more thin-walled sections 210 (Figs. 52-54) which fracture when enlargement 100 is forced proximally.

10

Alternatively, in another form of the invention, anchor 10 is constructed so that its generally cylindrical body 35 expands radially when enlargement 100 moves proximally, but the distal end of the anchor does not split open. See Figs. 55-58. Again, the direction and extent of the expansion of cylindrical body 35 may be controlled by the number and location of the longitudinally-extending slits 75, the configuration of enlargement 100, the configuration of generally cylindrical body 35 (e.g., its lumen 50 and the associated side wall of the cylindrical body 35 adjacent the lumen), etc.

15

20 Additional Construction Details

5

Anchor 10 can be made out of any material consistent with the present invention, e.g., anchor 10 can be made out of a biocompatible plastic (such as PEEK), an absorbable polymer (such as poly-L-lactic acid, PLLA), bio-active materials such as hydrogels, or metal (such as stainless steel or titanium).

10

Suture 15 can be made out of any material consistent with the present invention, e.g., common surgical suture materials. One such material is woven polymer such as PE or UHMWPE. Another material is a co-polymer material such as UHMWPE/polyester. Yet another material is an absorbable polymer such as polyglycolic acid, polylactic acid, polydioxanone, or caprolactone. Proximal loop 105 is preferably a #1 suture size; alternatively, it is a #2 suture size, a #0 suture size, or a #2-0 suture size. Distal loop 95 is preferably a #2-0 suture size; alternatively, it is a #2 suture size, a #1 suture size, or a #0 suture size.

15

20

As noted above, enlargement 100 may comprise a solid member attached to the distal end of distal loop

95, or it may comprise a suture knot formed by knotting off the distal ends of distal loop 95 of suture 15. In this latter construction, enlargement 100 can be formed out of a single knot or multiple 5 knots. It can be an overhand knot or other knot such as a "Figure 8" knot. Suture 15 can also be heat formed so as to create the enlargement 100. This will create a more rigid feature that better enables movement of enlargement 100 from its distal position 10 to its more proximal position. Such heat forming could also be done on a knot or to seal the suture ends distal to the knot.

Alternative Construction And Method Of Use

15 In one form of the present invention, anchor 10 of suture anchor system 5 may be delivered trans-labrally, i.e., through the labrum and into the acetabular bone, e.g., such as was described above.

20 In an alternative embodiment of the present invention, anchor 10 may be placed directly into the acetabular bone, without passing through the labrum

first, and then suture 15 may be passed through the labrum. In this form of the invention, the components of suture anchor system 5 may remain the same.

Alternatively, in this form of the invention, the 5 distal end of hollow guide 25 need not have a sharp tip/edge 136 for penetrating the labrum as described above, and may instead have engagement features for engaging the acetabular bone. One such feature may be a tooth or a plurality of teeth. In this form of the 10 invention, the distal end of the hollow guide may also include a window for confirming that the anchor is properly placed into the bone.

Curved Or Angled Configuration And Method Of Use

15 Suture anchor system 5 may also comprise a curved or angled configuration. More particularly, hollow guide 25 may comprise a curve or angle at its distal end. In this form of the invention, the punch (or drill) 30, inserter 20 and anchor 10 are adapted to 20 pass through the curved or angled hollow guide 25 so as to permit a curved or angled delivery of anchor 10.

Use Of The Novel Suture Anchor SystemFor Other Tissue Re-attachment

It should be appreciated that suture anchor

5 system 5 may also be used for re-attaching other soft tissue of the hip joint, or for re-attaching tissue of other joints, or for re-attaching tissue elsewhere in the body. In this respect it should be appreciated that suture anchor system 5 may be used to attach soft tissue to bone or soft tissue to other soft tissue, or 10 for attaching objects (e.g., prostheses) to bone other tissue.

Modifications Of The Preferred Embodiments

15 It should be understood that many additional changes in the details, materials, steps and arrangements of parts, which have been herein described and illustrated in order to explain the nature of the present invention, may be made by those 20 skilled in the art while still remaining within the principles and scope of the invention.

Claims:

1. Apparatus for securing a first object to a second object, the apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section, a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second cylindrical section of the lumen, the elongated body and the elongated element being constructed such that proximal movement of the elongated element causes proximal movement of the enlargement into the second cylindrical section of the lumen, whereby to laterally expand the elongated body.

2. Apparatus according to claim 1 wherein the first object comprises tissue and the second object comprises bone.

3. Apparatus according to claim 2 wherein the tissue comprises the labrum and the bone comprises the acetabulum.

4. Apparatus according to claim 1 wherein the elongated body is generally cylindrical.

5. Apparatus according to claim 52 wherein the distal end of the longitudinally-extending slit terminates in a distal relief hole and the proximal end of the longitudinally-extending slit terminates in a proximal relief hole.

6. Apparatus according to claim 52 wherein there are two longitudinally-extending slits, and further wherein the two longitudinally-extending slits are diametrically opposed to one another.

7. Apparatus according to claim 1 wherein the elongated element comprises a suture.

8. Apparatus according to claim 7 wherein the suture comprises a distal loop connected to the enlargement, and a proximal open loop connected to the distal loop.

9. Apparatus according to claim 7 wherein the enlargement comprises a solid member.

10. Apparatus according to claim 7 wherein the enlargement comprises a suture knot.

11. Apparatus according to claim 10 wherein the enlargement comprises a solid member and a suture knot, the solid member being disposed proximal to the suture knot.

12. Apparatus according to claim 1 wherein the elongated element comprises a rod.

13. Apparatus according to claim 1 wherein generally cylindrical body comprises ribs.

14. Apparatus according to claim 13 wherein the ribs are slotted.

15. Apparatus according to claim 13 wherein the ribs are resilient.

16. Apparatus according to claim 1 further comprising an inserter for manipulating the elongated body.

17. Apparatus according to claim 16 wherein the inserter comprises a hollow push tube having a lumen extending therethrough.

18. Apparatus according to claim 17 wherein the elongated element extends through the lumen of the push tube.

19. Apparatus according to claim 18 wherein the elongated body is held to the inserter by applying proximally-directed tension to the elongated element.

20. Apparatus according to claim 18 wherein the elongated body is held to the inserter with a male-female connection.

21. Apparatus according to claim 1 wherein the elongated element exits the lumen of the elongated body at the proximal end of the elongated body.

22. Apparatus according to claim 52 wherein the elongated element exits the lumen of the elongated body intermediate the length of the elongated body.

23. Apparatus according to claim 22 wherein the proximal end of the longitudinally-extending slit terminates in a proximal relief hole, and further wherein the elongated element exits the lumen of the elongated body via the proximal relief hole.

24. Apparatus according to claim 23 wherein the outside surface of the elongated body comprises at least one surface groove for receiving the elongated element.

25. Apparatus according to claim 1 wherein the lumen of the elongated body is eccentric to the longitudinal axis of the elongated body.

26. Apparatus for securing a first object to a second object, the apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section, a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder; and

a suture extending through the lumen of the elongated body, the suture comprising a proximal end and a distal end and having a suture knot at its distal end, the suture knot having a diameter greater than the second cylindrical section of the lumen, the elongated body and the suture being constructed such that proximal movement of the suture causes proximal movement of the suture knot into the second cylindrical section of the lumen, whereby to laterally expand the elongated body.

27. Apparatus according to claim 26 wherein a solid member is disposed proximal to the suture knot.

28. Apparatus according to claim 26 wherein the elongated body is generally cylindrical.

29. Apparatus according to claim 26 wherein the elongated body comprises ribs.

30. Apparatus according to claim 26 wherein the elongated body comprises at least one longitudinally-extending slit extending through the side wall of the elongated body and communicating with the lumen.

31. Apparatus according to claim 28 wherein the at least one longitudinally-extending slit has a distal end and a proximal end, with the distal end of the at least one longitudinally-extending slit being spaced from the distal end of the elongated body.

32. Apparatus according to claim 30 wherein the at least one longitudinally-extending slit has a distal end and a proximal end, with the distal end of the at least one longitudinally-extending slit opening on the distal end of the elongated body.

33. Apparatus for securing a first object to a second object, the apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section, a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the

second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder;

the side wall of the elongated body having a weakened section therein adjacent to the second cylindrical section of the lumen; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second cylindrical section of the lumen, the elongated body and the elongated element being constructed such that proximal movement of the elongated element causes proximal movement of the enlargement into the second cylindrical section of the lumen, whereby to laterally expand the elongated body.

34. A method for securing a first object to a second object, the method comprising:

providing apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section,

a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second cylindrical section of the lumen, the elongated body and the elongated element being constructed such that proximal movement of the elongated element causes proximal movement of the enlargement into the second cylindrical section of the lumen, whereby to laterally expand the elongated body;

inserting the elongated body into the second object;

moving the enlargement proximally so as to expand the elongated body; and

securing the first object to the second object with the elongated element.

35. A method according to claim 34 wherein the elongated body is passed through the first object before the elongated body is inserted into the second object.

36. A method according to claim 34 wherein the elongated element is passed through the first object after the elongated body is inserted into the second object.

37. A method according to claim 34 wherein the first object comprises tissue and the second object comprises bone.

38. A method for securing a first object to a second object, the method comprising:

providing apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section, a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder; and

a suture extending through the lumen of the elongated body, the suture comprising a proximal end and a distal end and having a suture knot at its distal end, the suture knot having a diameter greater than the second cylindrical section of the lumen, the elongated body and the suture being constructed such that proximal movement of the suture causes proximal movement of the suture knot into the second cylindrical section of the lumen, whereby to laterally expand the elongated body;

inserting the elongated body into the second object;

moving the suture knot proximally so as to expand the elongated body; and

securing the first object to the second object with the suture.

39. A method according to claim 38 wherein the elongated body is passed through the first object before the elongated body is inserted into the second object.

40. A method according to claim 38 wherein the suture is passed through the first object after the elongated body is inserted into the second object.

41. A method according to claim 38 wherein the first object comprises tissue and the second object comprises bone.

42. A method according to claim 38 wherein the tissue comprises the labrum and the bone comprises the acetabulum.

43. A method for securing a first object to a second object, the method comprising:

providing apparatus comprising:

an elongated body having a distal end, a proximal end, and a lumen extending between the distal end and the proximal end, the lumen comprising a first cylindrical section, a second cylindrical section and a third cylindrical section, the first cylindrical section of the lumen being disposed distal to the second cylindrical section of the lumen, with the first cylindrical section of the lumen having a wider diameter than the second cylindrical section of the lumen, and the second cylindrical section of the lumen being disposed distal to the third cylindrical section, with the second cylindrical section of the lumen having a wider diameter than the third cylindrical section of the lumen, wherein the first cylindrical section of the lumen is separated from the second cylindrical section of the lumen by a first shoulder, and the second cylindrical section of the lumen is separated from the third cylindrical section of the lumen by a second shoulder;

the side wall of the elongated body having a weakened section therein adjacent to the second cylindrical section of the lumen; and

an elongated element extending through the lumen of the elongated body, the elongated element comprising a proximal end and a distal end and having an enlargement at its distal end, the enlargement having a diameter greater than the second cylindrical section of the lumen, the elongated body and the elongated element being constructed such that proximal movement of the elongated element causes proximal movement of the enlargement into the second cylindrical section of the lumen, whereby to laterally expand the elongated body;

inserting the elongated body into the second object;

moving the enlargement proximally so as to expand the elongated body; and

securing the first object to the second object with the elongated element.

44. A method according to claim 43 wherein the elongated body is passed through the first object before the elongated body is inserted into the second object.

45. A method according to claim 43 wherein the elongated element is passed through the first object after the elongated body is inserted into the second object.

46. A method according to claim 43 wherein the first object comprises tissue and the second object comprises bone.

47. A method according to claim 43 wherein the tissue comprises the labrum and the bone comprises the acetabulum.

48. A method according to claim 34 wherein expansion of the elongated body causes the distal end of the elongated body to split open.

49. A method according to claim 38 wherein expansion of the elongated body causes the distal end of the elongated body to split open.

50. A method according to claim 43 wherein expansion of the elongated body causes the distal end of the elongated body to split open.

51. A method according to claim 43 wherein expansion of the elongated body does not cause the distal end of the elongated body to split open.

52. Apparatus according to claim 1 wherein the elongated body comprises at least one longitudinally-extending slit extending through the side wall of the elongated body and communicating with the lumen, the at least one longitudinally-extending slit having a distal end and a proximal end, with the distal end of the at least one longitudinally-extending slit being spaced from the distal end of the elongated body.

1/42




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D

2/42





FIG. 2

3/42



4/42




FIG. 4

5/42




FIG. 5

6/42

HIP JOINT




FIG. 6

7/42




FIG. 7

8/42




FIG. 8

9/42




FIG. 9

10/42




FIG. 10

11/42




FIG. 11

12/42





FIG. 12

13/42

CAM-TYPE FEMOROACETABULAR IMPINGEMENT (FAI)



CAM INJURY TO THE LABRUM





FIG. 13

14/42

PINCH-TYPE FEMOROACETABULAR IMPINGEMENT (FAI)



PINCH INJURY TO THE LABRUM




FIG. 14

15/42




FIG. 15

16/42




FIG. 16

17/42




FIG. 17

18/42




FIG. 18

19/42




FIG. 19




FIG. 20

20/42




FIG. 23




FIG. 22

FIG. 21

21/42




FIG. 26




FIG. 25




FIG. 24

22/42





FIG. 27



24/42




FIG. 28A

25/42




FIG. 31




FIG. 30





FIG. 29

ANCHOR WITH DEPLOYMENT CYLINDER



CROWN FEATURE FLEXES TO FIT IN DELIVERY TUBE
AND EXPANDS IN AN ELASTIC MANNER TO A
DIAMETER LARGER THAN THE DELIVERY TUBE
WHEN INSERTED INTO BONE

FIG. 32

27/42




FIG. 33






FIG. 34
CAPTURE COUPLING FOR INSERTION

28/42



T-NOTCH COUPLING FOR INSERTION

29/42




FIG. 37







FIG. 38

BALL AND SOCKET COUPLING FOR
INSERTION (ESPECIALLY HELPS WITH
CURVED SYSTEM)



30/42



SUTURE (NOT SHOWN) PASSES OUTSIDE OF
THE PROXIMAL SECTION OF THE ANCHOR

FIG. 39

FIG. 40

FIG. 41

31/42





FIG. 42

32/42



33/42




FIG. 48
NON-CONCENTRIC
THROUGH HOLE




FIG. 47




FIG. 46

34/42




FIG. 49




FIG. 50

ANGLED THROUGH HOLE

35/42




FIG. 51

NO SLIT
PLUS MATERIAL
BARB

36/42




FIG. 54




FIG. 53




FIG. 52

37/42




FIG. 55

38/42




FIG. 56

39/42




FIG. 57

40/42




FIG. 58

41/42




FIG. 59

42/42




FIG. 60