



Office de la Propriété

Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2911995 C 2016/12/20

(11)(21) **2 911 995**

(12) **BREVET CANADIEN**
CANADIAN PATENT

(13) **C**

(22) Date de dépôt/Filing Date: 2010/03/25

(41) Mise à la disp. pub./Open to Public Insp.: 2010/09/27

(45) Date de délivrance/Issue Date: 2016/12/20

(62) Demande originale/Original Application: 2 697 823

(30) Priorité/Priority: 2009/03/27 (EP09250901.7)

(51) CI.Int./Int.Cl. **A23L 2/52** (2006.01),
A23L 2/00 (2006.01), **A23L 2/385** (2006.01),
A23L 29/20 (2016.01), **A23L 29/256** (2016.01),
A47J 31/00 (2006.01), **A47J 31/44** (2006.01),
B65D 85/804 (2006.01)

(72) Inventeurs/Inventors:

MASSEY, ADRIAN, GB;
MASSEY, TULAY, GB;
MICHAUT, CLEMENCE, GB;
BLANGY, HELENE, GB


(73) Propriétaire/Owner:

KONINKLIJKE DOUWE EGBERTS B.V., NL

(74) Agent: OSLER, HOSKIN & HARCOURT LLP

(54) Titre : CARTOUCHE POUR CONCENTRES DE BOISSON

(54) Title: A CARTRIDGE FOR BEVERAGE CONCENTRATES



(57) Abrégé/Abstract:

A method of dispensing a beverage from a cartridge containing a beverage liquid concentrate comprising an alginate and / or a thermally reversible gelling thickener dissolved in the concentrate. The method comprises the steps of: passing an aqueous medium through the cartridge to form a beverage by dilution of the beverage concentrate, and dispensing the beverage into a receptacle, wherein the overall weight ratio of the beverage concentrate to the aqueous medium is from about 10:1 to about 1:10.

ABSTRACT

A method of dispensing a beverage from a cartridge containing a beverage liquid concentrate comprising an alginate and / or a thermally reversible gelling thickener dissolved in the concentrate. The method comprises the steps of: passing an aqueous medium through the cartridge to form a beverage by dilution of the beverage concentrate, and dispensing the beverage into a receptacle, wherein the overall weight ratio of the beverage concentrate to the aqueous medium is from about 10:1 to about 1:10.

- 1 -

A Cartridge for Beverage Concentrates

This application is a division of Canadian Serial No. 2,697,823 filed March 25, 2010.

5

The present invention relates to beverage concentrates comprising thickeners. More particularly, the present invention relates to beverage concentrates comprising thickeners for use in beverage preparation systems and to beverage concentrates having a mixture of thickeners that provides enhanced organoleptic properties.

10

Background to the invention

15

Beverage dispensing systems rely on the use of beverage concentrates to provide beverages. A beverage dispensing system may comprise or consist of a beverage dispensing machine and a cartridge comprising a beverage concentrate. In use, the beverage concentrate is typically diluted with between 0.1 part and 10 parts by weight of an aqueous medium inside the beverage dispensing system to provide a beverage that is then dispensed from the beverage dispensing system from an outlet. The beverage may sometimes be further diluted with additional aqueous fluids, for example milk. Thus, beverage concentrates provide a convenient and efficient way of providing a consumer with a beverage.

20

25

30

Cartridges for use in a beverage dispensing systems typically comprise one or more chambers containing beverage concentrate. The cartridge and beverage dispensing system may be configured so that the beverage concentrate is mixed with the aqueous medium inside the cartridge; alternatively (or additionally), mixing with an aqueous medium may take place outside the cartridge within the beverage dispenser itself. In either case, the beverage dispensing system

- 2 -

comprises an outlet downstream of the chamber(s) containing the beverage concentrate for the discharge of a beverage and a flow path connecting the concentrate chamber(s) to the outlet. The system may be further provided with a means for 5 mixing the beverage concentrate with an aqueous medium to form the beverage either in the cartridge itself or elsewhere in the beverage preparation system. The aqueous medium may typically be a fluid or liquid such as water or milk.

10

One type of beverage dispensing system makes use of single-serving cartridges to provide the beverage concentrate. The cartridges may be sealed and formed of substantially air- and water-impermeable materials. In order to allow the 15 beverage to brew and / or be diluted within the cartridges, the cartridges may comprise an inlet for the introduction of an aqueous medium into the cartridge, an outlet downstream of the inlet for the discharge of a beverage from the cartridge and a flow path connecting the inlet to the 20 outlet. By providing the beverage concentrate within the flow path connecting the inlet and outlet of the cartridge, for example within a chamber, the cartridges conveniently provide an integrated means for mixing the beverage concentrate with an aqueous fluid.

25

Previously, certain thickeners have been used in beverage concentrates for beverage dispensing devices. For example, WO 02/074143 describes the use of a number of gums and starches in a beverage brewing device. These gums and 30 starches appear to be contained in a solid concentrate, for example one in which different ingredients have been agglomerated together. Separately, US 2008/0014315

-3-

describes a fountain syrup comprising a foam-creating composition comprising a dairy composition and a hydrocolloid composition, a 5 flavouring agent and a sweetening agent.

Summary of the Invention

The present invention provides, in one embodiment, a cartridge for a beverage preparation system, the cartridge comprising an inlet for the introduction of an aqueous medium into the cartridge, an outlet 10 downstream of the inlet for the discharge of a beverage from the cartridge and a flow path connecting the inlet to the outlet, wherein the flow path includes within it a non-gelled beverage liquid concentrate containing about 0.01 to about 5 weight% in total of one or more thickeners, the flow path comprising a constriction downstream 15 from the non-gelled beverage liquid concentrate, and the one or more thickeners configured to provide delayed thickening so that the non-gelled beverage liquid concentrate is non-gelled when in the sealed cartridge but capable of flowing through the constriction and thickening the brewed beverage after introduction of the aqueous 20 medium into the cartridge.

In a preferred embodiment of the present invention, there is provided a sealed machine-insertable cartridge for a beverage preparation system with a beverage dispenser for producing a brewed beverage, the sealed cartridge comprising: an inlet for the introduction of an 25 aqueous medium into the cartridge, an outlet downstream of the inlet for the discharge of the brewed beverage from the cartridge, and a flow path connecting the inlet to the outlet, wherein the flow path includes within it a non-gelled beverage liquid concentrate comprising

-3a-

5 a liquid beverage concentrate and about 0.01 to about 5 weight% in
total of one or more thickeners, the flow path comprising a
constriction downstream from the non-gelled beverage liquid
concentrate and, the beverage liquid concentrate is non-gelled when in
the sealed cartridge so that the beverage liquid concentrate can flow
through the constriction and wherein the thickeners provide for the
10 brewed beverage to thicken after the beverage is dispensed from the
beverage dispenser.

In another embodiment of the present invention, there is provided a
sealed cartridge for a beverage preparation system having a beverage
15 dispenser for producing a brewed beverage, the sealed cartridge
comprising: an inlet for the introduction of an aqueous medium into
the cartridge, an outlet downstream of the inlet for the discharge of
the brewed beverage from the cartridge, a non-gelled beverage liquid
comprising a liquid concentrate and about 0.01 to about 5 weight% in
20 total of one or more thickeners, and a flow path connecting the inlet
to the outlet and having a maximum cross-sectional area of 5 mm^2 to
1000 mm^2 , the flow path comprising a chamber including the non-gelled
beverage liquid concentrate, and a constriction downstream from the
chamber, the constriction having a cross-sectional area from 0.05 mm^2
25 to 2 mm^2 , wherein the beverage liquid concentrate is non-gelled when in
the sealed cartridge so that the beverage liquid concentrate can flow
through the constriction and wherein the thickeners provide for the
brewed beverage to thicken after the brewed beverage is dispensed from
the beverage dispenser.

30

35

-3b-

A further embodiment of the present invention provides a sealed
5 cartridge for a beverage preparation system for producing a brewed
beverage, the sealed cartridge comprising: an inlet for the
introduction of an aqueous medium into the cartridge, an outlet
downstream of the inlet for the discharge of the brewed beverage from
the cartridge, a flow path connecting the inlet to the outlet, a
10 chamber comprising a beverage liquid concentrate in fluid
communication with the inlet and outlet, the beverage liquid
concentrate comprising a liquid concentrate and one or more thickeners
comprising at least one of an alginate and a thermally reversible
gelling thickener, the total concentration of the thickener in the
15 concentrate being about 0.01 to about 5 weight%, and an aperture
downstream from the chamber and having a cross-sectional area less
than a cross-sectional area of the chamber, wherein the beverage
liquid concentrate is non-gelled when in the sealed cartridge so that
the beverage liquid concentrate can flow through the aperture, and
20 wherein the thickeners delay thickening of the brewed beverage so that
the brewed beverage thickens after being dispensed from the beverage
dispenser.

The present invention further provides a method of dispensing a
25 beverage from a cartridge containing a beverage liquid concentrate
comprising an alginate and/or a thermally reversible gelling thickener
dissolved in the concentrate, the method comprising the steps of:
passing an aqueous medium through the cartridge to form a beverage by
dilution of the beverage concentrate, and dispensing the beverage into
30 a receptacle, wherein the overall weight ratio of the beverage
concentrate to the aqueous medium is from about 10:1 to about 1:10.

-3c-

A further embodiment of the present invention provides a method of
5 dispensing beverage from the sealed cartridge according to the present
invention, the method comprising the steps of: passing the aqueous
medium through the sealed cartridge to form a beverage by dilution of
the non-gelled beverage liquid concentrate, wherein the non-gelled
beverage liquid concentrate is non-gelled when in the sealed cartridge
10 and when flowing through the constriction, and dispensing the beverage
into a receptacle, wherein the beverage thickens after it is dispensed
into the receptacle, and wherein the overall weight ratio of the non-
gelled beverage liquid concentrate to the aqueous medium is from about
10:1 to about 1:10.

15

The present invention further provides a beverage dispensing system
comprising a cartridge containing a concentrate chamber comprising
beverage concentrate, an outlet downstream of the concentrate chamber
for the discharge of a beverage, a flow path connecting the
20 concentrate chamber and the outlet, the flow path containing a means
for mixing the beverage concentrate with an aqueous medium, wherein
the flow path has a maximum cross-section area of X and a minimum
cross-section area of Y, wherein the ratio of X to Y is about 20 or
greater, and wherein the beverage concentrate is a non-gelled
25 beverage liquid concentrate or a solid beverage concentrate comprising
an alginate and / or a thermally reversible gelling thickener.

A further embodiment of the present invention provides a beverage
dispensing system comprising: the sealed cartridge according to the
30 present invention, the sealed cartridge containing a concentrate
chamber comprising the non-gelled beverage liquid concentrate, an
outlet downstream of the concentrate chamber for the discharge of a
beverage, a flow path connecting the concentrate chamber and the

-4-

outlet, the flow path containing a means for mixing the non-gelled beverage liquid concentrate with an aqueous medium, wherein the 5 constriction is downstream of the concentrate chamber, and wherein the flow path has a maximum cross-section area of X and a minimum cross - section area of Y, wherein the ratio of X to Y is 20 or greater.

The present invention further provides a beverage concentrate comprising a thickener, wherein the thickener comprises methyl 10 cellulose and at least one alginate in a weight ratio of 1:5 to 5:1, wherein the methyl cellulose and the at least one alginate are present in a combined amount of about 0.01 to about 5 weight%. The invention further provides the use of a sodium alginate and methyl cellulose to 15 improve the organoleptic properties, preferably the mouthfeel, of a beverage prepared from a beverage concentrate, wherein the methyl cellulose and at least one alginate are in a weight ratio of 1:5 to 5:1.

Description of the Figures

Figure 1 shows the viscosity / temperature relationship for a 20 thermally reversible gelling thickener (methyl cellulose).

Figure 2 shows the results of trials investigating the mouthfeel of a particular combination of thickeners.

- 5 -

Detailed description of the invention

The present invention will now be further described. In the following passages different aspects of the invention are

5 defined in more detail. Each aspect so defined may be combined with any other aspect or aspects unless clearly indicated to the contrary. In particular, any feature indicated as being preferred or advantageous may be combined with any other feature or features indicated as being

10 preferred or advantageous.

The inventors of the present invention have investigated the use of thickeners in beverage concentrates. During these investigations, the inventors recognised that the selection

15 of a specific thickener or mixture of thickeners can contribute to advantageous properties of the beverage concentrate.

In particular, the inventors have found that it is

20 advantageous for a thickener to contribute to the thickness and texture of a final prepared beverage but, in some systems, it is desirable for the thickener not to have the same thickening effect in the beverage concentrate and / or before the beverage is dispensed from the beverage

25 dispensing system. The inventors have also found that a combination of thickeners achieves these advantageous thickness properties while at the same time contributing to a surprising mouthfeel of a final prepared beverage.

30 These advantages of the present invention will now be described in relation to three aspects. It is to be understood that the features of each of these aspects may

- 6 -

be, unless specifically stated, freely combined with any of the other aspects.

In a first aspect, the inventors have found that a thickener 5 that causes a beverage liquid concentrate to form a gel and / or have an excessive thickness can render the beverage concentrate impossible to brew and / or dilute. This may result in a weak, watery drink being dispensed from the dispenser, which lacks the advantageous mouthfeel that was 10 the original reason for adding the thickener to the beverage concentrate. The inventors have also found difficulty in loading beverage concentrates into single-serving cartridges if the beverage liquid concentrate takes the form of a gel and / or has an excessive thickness.

15

In a second aspect, the inventors have found that, if a thickener that causes a beverage liquid concentrate to form a gel and / or have an excessive thickness, gel pieces can be formed when the beverage concentrate mixes with an 20 aqueous fluid. These gel pieces can block narrow constrictions in the flow path, thereby causing an increase in the pressure required to dispense the beverage from the beverage system. The inventors have further found that it is possible to provide a solid beverage concentrate that 25 thickens once dispensed from the beverage dispensing system, thereby reducing the pressure needed to cause a prepared beverage to flow through narrow constrictions in the flow path between the point of mixing of the aqueous fluid and the beverage concentrate and the outlet of beverage 30 dispensing system.

- 7 -

In a third aspect, the inventors have found a combination of two thickeners that have all the advantages of the first two aspects of the invention and further provides a surprising mouthfeel to a prepared beverage.

5

Each of these aspects will now be described in greater detail.

In a first aspect of the invention, the inventors have
10 recognised the convenience to the consumer of providing a
beverage concentrate in a cartridge in which the beverage is
diluted and / or brewed. In use, these cartridges may be
placed inside a beverage preparation machine. An aqueous
medium, for example water and / or steam, is then introduced
15 into the cartridge from the beverage preparation machine.
The aqueous medium mixes with the beverage concentrate
within the cartridge and then the mixed beverage is
dispensed from the cartridge. Optionally, other ingredients
may be added to produce the final beverage, such as milk.
20 The combination of the cartridge and beverage preparation
machine may be termed a beverage preparation system.

Beverages that are prepared in this way include, but are not
limited to, coffee, tea and hot chocolate. It is to be
25 noted that the terms "brewed" and "diluted" are used
interchangeably herein to refer both to the brewing of, for
example, coffee and tea and to the dilution of, for example,
a chocolate concentrate.

30 The inventors have recognised that some beverages may
benefit from having thickeners added to them. For example,
some flavoured coffees may benefit from the addition of

- 8 -

thickeners to the beverage. Examples of flavours added to coffee include, but are not limited to, cocoa (including chocolate), vanilla, alcoholic (including liqueur flavour), caramel, mint, dairy, herbs, spices (including cinnamon),
5 nuts and / or berries.

The inventors have then investigated the possibility of using thickeners in beverage concentrates contained in cartridges so that beverages with thicker, luxurious
10 mouthfeel may be easily and reliably prepared using a beverage preparation system.

In a first aspect of the invention, the inventors have investigated the use of a thickener in a beverage liquid
15 concentrate in a cartridge for a beverage dispensing device. However, the inventors have found that most thickeners are unsuitable for use with a beverage concentrate comprising a liquid ingredient.

20 Without wishing to be bound by theory, the inventors have found that food thickeners tend to dissolve in a liquid ingredient contained in a beverage concentrate. When dissolved, the thickener acts to thicken the composition and tend to form a gel. The inventors have found that, when an
25 aqueous medium is added to a viscous concentrate or gel beverage concentrate, it takes a significant time for the aqueous medium to mix with the beverage concentrate. For example, diffusion mixing of the aqueous medium with the beverage concentrate may be prevented or significantly
30 slowed and mixing may instead be required to be preceded by thermal transfer from the aqueous medium to the beverage concentrate in order to reduce the thickness of the beverage

- 9 -

concentrate. This may not only increase the time taken to brew / dilute a drink to a pre-determined strength, but it may also result in not all of the beverage concentrate being mixed with the aqueous medium, resulting in not all of the 5 beverage concentrate being transferred to the receptacle when dispensed. This problem is aggravated if the beverage concentrate contains any solids, when inadequate mixing may result in not all of the solids being dissolved (if the solids are soluble solids) or not all of the solids 10 contributing to the taste of the final beverage.

The inventors have then surprisingly found a beverage liquid concentrate comprising a thickener may be provided in a non-gel form. The inventors have found this to be advantageous 15 because it allows the beverage liquid concentrate to easily mix with an aqueous fluid introduced into the cartridge, thereby decreasing the time taken to brew / dilute a drink to a pre-determined strength and increasing the reliability of the brew.

20

Therefore, in a first aspect, the present invention provides a cartridge adapted for use in a beverage preparation system, the cartridge containing a beverage concentrate and the cartridge being configured so that, in use, the beverage 25 concentrate mixes with the an aqueous medium to brew a beverage. The cartridge may be configure for use with a beverage preparation machine. The beverage concentrate is a non-gelled beverage liquid concentrate containing a thickener in an amount sufficient to provide a pre- 30 determined thickening effect to the final beverage.

- 10 -

As noted above, the beverage concentrate in the first aspect of the invention is a liquid beverage concentrate. "Liquid concentrate" refers to a concentrate comprising one or more liquid ingredients. "A liquid ingredient" refers to one 5 ingredient that is liquid at ambient temperature (e.g. room temperature, such as 20°C). The liquid ingredient contained in the beverage concentrate may, for example, comprise water; alternatively or additionally, the liquid ingredient may, for example, comprise corn syrup (e.g. glucose syrup) 10 and / or other syrups containing mono-, di- or polysaccharides. An example of a liquid ingredient that is used for the preparation of a chocolate-based drink is liquid chocolate, such as the liquid chocolate described in EP 1440910. Preferably, the total amount of liquid 15 ingredients contained in the beverage concentrate is from about 40 to about 100% by weight, for example about 60 to about 99% by weight, such as about 80 to about 97% by weight, for example about 90 to about 95%. These weight percentages are given as a percentage of the total weight of 20 the beverage concentrate, i.e. as percentage of the combined weight of the liquid and solid ingredients. In particular, the brew / dilution time and reliability of the brew may be increased with a greater amount of liquid ingredients. However, sometimes some ingredients are preferably provided 25 as solids in order to preserve their flavour until brewing dilution. For example, a coffee extract may be provided in solid form, for example as soluble coffee. Partially insoluble solids may also be provided to improve brew flavour, such as roast and ground coffee. Thus, the 30 beverage liquid concentrate may comprise, for example, from about 0 to about 60 weight % solids contents, for example

- 11 -

about 2 to about 40 weight %, such as about 3 to about 20 weight %, for example about 5 to about 10 weight%.

The beverage liquid concentrate is non-gelled. The terms 5 "gel" and "gelled" are well-known to the person skilled in the art as referring to a system that exhibits no flow under steady-state conditions at 20°C. More preferably, the viscosity of the beverage liquid concentrate is about 4000 mPa.s or less, more preferably about 1000 mPa.s or less, 10 more preferably about 500 mPa.s or less, such as about 200 mPa.s or less. The inventors have found these viscosities contribute to the facile mixing of the beverage concentrate with the aqueous fluid. On the other hand, the viscosity of the beverage liquid concentrate may be about 1 mPa.s or 15 more, more preferably about 10 mPa.s or more or more, more preferably about 50 mPa.s or more. The inventors have found that these minimum viscosities tend to result from a concentration of ingredients in the beverage concentrate apart from the thickener that allows the beverage 20 concentrate to be able to be diluted and still provide a final beverage of desired brew strength.

Accordingly, preferred ranges of viscosities at 20°C and 100 rpm include about 1 to about 4000 mPa.s, for example about 25 10 to about 1000 mPa.s, such as about 10 mPa.s to about 500 mPa.s.

Viscosity is measured by a Brookfield DVII viscometer. The thickeners may be selected so that the beverage concentrate 30 has these viscosities at 20°C. For example, the concentration of the preferred thickeners discussed below (an alginate and / or a thermally reversible gelling

- 12 -

thickener) may be selected to achieve these viscosities. Viscosity may be measured at 100 rpm using spindle 3.

Preferably, the thickener may be partially or fully

5 dissolved in the liquid ingredient(s) and / or be contained in colloidal form in the liquid ingredient. For example, if the beverage concentrate contains both solid and liquid ingredients, it may be described as having a continuous phase (the liquid ingredient(s)) and a discontinuous phase

10 (the solid ingredient(s)) and the thickener is partially or completely contained in the continuous phase, either completely dissolved or as a colloid. If the thickener is contained in a colloidal form, it may not separate from the beverage concentrate over time (e.g. one in which no or

15 substantially no separation of the thickener from the liquid ingredient and / or settling of the thickener to the bottom of the container occurs when left in a sealed container at 20°C for 7 days).

20 Preferably, about 50% to about 100% by weight of the thickener may be contained in the liquid ingredient(s) / continuous phase, either dissolved or in colloidal form, more preferably about 80% to about 100% by weight, for example about 100% by weight. In particular, a greater

25 amount of thickener dissolved in the liquid ingredients may result in a quicker and more reliable beverage brew. The thickener may be dissolved in the beverage concentrate by mixing the ingredients of the beverage concentrate before they are added to the cartridge, for example in a mixer,

30 such as in a vacuum mixer.

The thickeners may be provided in the continuous phase of the liquid concentrate in a number of ways known in the art. For example the thickeners may be provided in a substantially or fully hydrated form. In particular, the 5 thickener may be subject to a hydration technique, such as sugar hydration. The thickener and the liquid ingredients of the concentrate may also be subject to high-shear mixing. The inventors have found that, by pre-hydrating the thickeners, all the thickeners are more likely to dissolve 10 in the time before the brewed beverage is dispensed from the beverage cartridge.

Preferably, the beverage concentrate comprises about 0.01 to about 5 weight% of thickener. These weight percentages 15 indicate the total concentration of thickeners and / or the total concentration of the two preferred thickeners (an alginate and / or a thermally reversible gelling thickener, discussed in greater detail below). More preferably, the beverage concentrate comprises about 0.01 weight% to about 2 20 weight% of thickener, more preferably about 0.1 to about 1 weight% of thickener, for example about 0.2 weight% to about 0.8 weight%, even more preferably about 0.5 weight%. The inventors have found that, at too low concentration, the thickening effect of the thickener is reduced, while at high 25 concentration, the thickener tends to become less easy to dissolve in the liquid ingredient.

"Thickeners" are well-known in the art. They are thickening agents that increase the thickness of a beverage. They may 30 be provided in solid form (at 20°C) and then dissolved or dispersed in a liquid or they may be provided with the solid thickener pre-dissolved or pre-dispersed in a liquid. They

may be used, for example, to enhance the body and mouthfeel characteristics of a beverage.

The inventors have further found that certain thickeners 5 have preferable properties for overcoming the problem of over-thickening the beverage liquid concentrate. These thickeners include an alginate and / or a thermally reversible gelling thickener. For example, the beverage liquid concentrate may comprise one or both of an alginate 10 and / or a thermally reversible gelling thickener. The inventors have found that these thickeners may be incorporated into a cartridge without resulting in a beverage concentrate that does not easily mix with an aqueous medium when introduced into the cartridge.

15 The thickener may be or may comprise an alginate. Without wishing to be bound by theory, the inventors have found that alginates may thicken when mixed with calcium ions (Ca^{2+}). Accordingly, the alginate may be dissolved in the beverage 20 liquid concentrate in an unbound form to produce a non-gelled concentrate. Then, on addition of an aqueous fluid comprising calcium ions, the aqueous fluid mixes with the beverage concentrate and only then does it thicken. For example, calcium ions may be intentionally added to the 25 aqueous fluid; or the calcium ions may already exist in the aqueous fluid, for example as 'hard' impurities in tap water. Alternatively, the alginate may be dissolved in an aqueous fluid that does not include calcium ions. The beverage dispensed from the cartridge may then be mixed with 30 a source of calcium ions in a receptacle in which it is served, for example with milk.

- 15 -

The term "alginate" is well-known in the art. Commercial alginates are derived from a variety of seaweed sources. Different seaweeds produce alginates of different monomeric composition and block structure and therefore the calcium

5 reactivity of an alginate may depend on its source. In particular, alginates may comprise a linear co-polymer comprising-D-mannuronic acid and L-guluronic acid monomeric units. These monomers may occur in the alginate molecule as blocks of individual monomer units (M-blocks or G-blocks),

10 or as regions in which the monomers approximate an alternating sequence. Alginates may be referred to as "high M" or "high G", depending on the proportions of mannuronic acid and guluronic acid they contain. An example of a high M alginate is that obtained from giant kelp, *Macrocystis pyrifera*, harvested off the California coast. One mechanism of thickening of the alginates is thought to be the alignment of two buckled G-block regions resulting in a diamond shaped hole having dimensions that are ideal for the cooperative binding of divalent ions, such as calcium ions.

15 20 In the present invention, high M alginates (e.g. ones having a M content as a proportion of the total number of M and G units of over 50%) may be used because of their controllable thickening characteristics.

25 The alginate may be a soluble alginate and, as such, is preferably soluble in water at 20°C. As such, preferably the alginate completely dissolves in water at 20°C. Examples of soluble alginates are well-known in the art. They include sodium, potassium and ammonium alginate.

30 However, pre-gelled calcium alginate may not be soluble in water. A particularly preferred alginate is sodium alginate, which the inventors have found to be particularly

versatile in its properties and its reliability in thickening.

The inventors have found alginates to be preferable in use

5 over other thickeners because of their thickening properties. In particular, alginates have been found to rapidly and controllably thicken in the presence of calcium ions. In contrast, the inventors have found other thickeners, for example carrageenan thickeners, to only

10 thicken slowly, as the beverage cools. Therefore, by using an alginate, the final beverage may not substantially change its viscosity over time, which is advantageous for consumers.

15 The alginate may be provided in a form that is substantially unbound to a divalent cation but capable of binding to a divalent cation, for example calcium (Ca^{2+}). For example, the alginate may be provided in a form having about 70% to about 100% by weight unbound to a divalent cation (e.g.

20 calcium), for example 90% to 100% by weight, such as about 100% by weight. The amount unbound to a divalent cation (e.g. calcium) may be for example measured by titrating the composition at room temperature with a calcium ion solution (for example, one having a 1 molar concentration of calcium ions); recording the point at which the viscosity of the

25 composition no longer increases with addition of new calcium ions; and then expressing this amount as a fraction of the amount of the calcium ion solution required to thicken the concentration of a control sodium alginate solution to the

30 point at which its viscosity no longer increases.

- 17 -

The thickener may be or may comprise a thermally reversible gelling thickener. These thickeners exhibit the property of increased viscosity at higher temperature. This property is called reversible thermal gellation. For example, these 5 thickeners may exhibit a higher viscosity at 80°C than 20°C when dissolved in the beverage concentrate, for example twice as viscous, such as three times as viscous using the conditions to measure viscosity previously described (but varying the temperature).

10

The inventors have found these thickeners to be advantageous because they tend not to form a gel or very viscous composition at room temperature in concentrated form, but increase their viscosity at higher temperature. As such, 15 these thickeners are particularly advantageous when the aqueous fluid added to the cartridge is provided 'hot', i.e. from about 50°C to about 100°C, for example from about 70°C to about 90°C, such as about 80°C. Alternatively, the aqueous fluid may be introduced into the cartridge 'cold' 20 (i.e. at 5 to 50°C, for example about 20°C) and then the beverage dispensed from the cartridge heated up afterwards, for example by adding to a hot liquid (e.g. milk). In this way, at the point when the aqueous fluid comes into contact with the beverage concentrate, the concentrate is not a gel 25 or highly viscous. While the beverage concentrate heats up quickly, the beverage concentrate has time to fully mix with the aqueous fluid before the thickening effect of the thermally reversible thickener at the higher temperature has time to prevent the mixing of the beverage concentrate with 30 the aqueous fluid.

Examples of two thermally reversible thickeners are methyl cellulose and hydroxypropylmethyl cellulose (HPMC). These are available under the trade name of MethoCel from Dow Chemicals. Methylcellulose is a particularly preferred 5 thermally reversible gelling thickener because of its mouthfeel properties. Its thermal / viscosity profile is illustrated in Figure 1.

In a preferred embodiment, the beverage liquid concentrate 10 comprises both methyl cellulose and an alginate. As described herein, the inventors have found this combination of thickeners to provide an advantageous mouthfeel to the final prepared beverage.

15 If the beverage concentrate contains an alginate, the concentrate may be provided with a calcium ion sequesterant. Calcium ion sequesterants complex to calcium ions, thereby reducing the concentration of calcium ions available to complex with the alginate. For example, a calcium ion 20 sequesterant may be used to complex to calcium ions present in the aqueous fluid, for example as 'hard' impurities in water.

Examples of calcium ion sequesterants include tri-sodium 25 citrate, di-sodium phosphate, di-potassium phosphate, sodium orthophosphate, tetra sodium pyrophosphate and sodium hexameta phosphate.

30 Preferably, the calcium ion sequesterant is present in a ratio relative to the alginate of 1:10 to 10:1, for example 1:5 to 5:1, such as 1:2 to 2:1. The inventors have found that a calcium ion sequesterant may work effectively inside

these limits. If the concentration is low, the effectiveness of the action of the sequesterant may be reduced; if the concentration is too high, the amount of calcium required to cause a thickening effect of the 5 alginates may be significantly increased.

Examples of further additional ingredients that may be included in the beverage concentrate include, but are not limited to, ground coffee, coffee extracts (including 10 instant coffee), tea leaves, tea extracts, chocolate solids, and flavourings. For example, the beverage concentrate may further comprise flavour syrups, cocoa (including any part derived from the cocoa bean, such as cocoa mass, cocoa nibs, 15 cocoa powder), herbs, spices and flavourings such as vanilla, strawberry, raspberry, orange, melon, caramel, cream and biscuit.

Preferably, one of the liquid ingredients in the beverage concentrate is a liquid comprising one or more saccharide 20 (mono-, di- or poly-saccharide). For example, a suitable liquid ingredient may be a monosaccharide syrup or a disaccharide syrup. For example, the liquid ingredient may be a corn syrup (e.g. glucose syrup). Preferably, this liquid ingredient is provided in an amount of about 10 25 weight% to about 90 weight%, for example about 30 weight% to about 75 weight%, for example about 60 weight%. In particular, the inventors have found that, by pre-blending the thickeners with the liquid comprising one or more saccharides, the thickeners may be advantageously dispersed 30 and / or dissolved in the liquid. In other words, the liquid separates the powder particles so that they do not aggregate together when an aqueous medium is added to them.

In a preferred embodiment, the beverage concentrate thickener may comprise 80 to 99% by weight liquid ingredients and 1 to 20 weight% solid ingredients. The 5 liquid ingredients may comprise 0.01 to 5% by weight of dissolved thickener. This thickener may comprise or may be an alginate and / or a thermally reversible gelling thickener. The alginate and / or the thermally reversible gelling thickener may be at a concentration, either 10 singularly or in combination, of 0.01 to 5% by weight. The liquid ingredients and / or solid ingredients may further comprise one or more flavourings, such as cocoa (including chocolate), vanilla, alcoholic (including liqueur flavour), caramel, mint, cinnamon, nuts and / or berries. The solid 15 ingredients may be or may comprise a coffee extract, such as a soluble coffee.

Turning to the actual cartridge that may be used in the first aspect of the invention, the cartridge comprises an 20 inlet for the introduction of an aqueous medium into the cartridge, an outlet downstream of the inlet for the discharge of a beverage from the cartridge and a beverage flow path linking the inlet to the outlet. It will be understood that by the term "cartridge" as used herein is 25 meant any package, container, sachet, receptacle or brewing or dilution device which contains a beverage concentrate as described herein. The cartridge may be rigid, semi-rigid or flexible. The cartridge may be formed from substantially air- and water-impermeable materials. The cartridge may be 30 provided sealed. For example, the inlet and outlet may be covered by a membrane (for example, a laminate), which may be pierced in use to allow introduction of an aqueous fluid

and the dispensing of a beverage. The beverage concentrate may, for example, be provided within a chamber contained in the flow path. Other components may optionally be included in the cartridge, such as a filter. A suitable cartridge 5 for use in the present invention is described in EP 1440908.

In one embodiment, the cartridge of the present invention is 10 preferably a single-serving cartridge. In particular, the inventors have further found difficulty in loading pre-gelled or very viscous beverage concentrates into cartridges without heating the beverage concentrates to modulate their viscosities. Loading a cartridge with beverage concentrate 15 at from about 0°C about 50°C, for example about 10°C to about 35°C, is preferred so that a simpler loading apparatus may be used without the requirement for specialist heating equipment to be incorporated into the loading apparatus. The inventors have found the beverage concentrates of the 20 present invention to overcome this problem because of their particular thickening properties.

Accordingly, preferably the beverage flow path containing 25 the beverage concentrate has a volume of about 5 ml to about 500 ml, more preferably about 10 ml to about 100 ml. Thus, the consumer can be provided with the convenience of being provided with a single serving of a beverage and being able to dispose of the cartridge after its single use. In addition, preferably the amount of beverage concentrate 30 provided in the cartridge is between about 1 g and 50 g, more preferably between about 5g and 25g.

Preferably, the ratio of the volume of the beverage concentrate to the volume of beverage flow path containing the beverage concentrate is from about 1:1 to about 1:100, such as about 1:2 to about 1:40, more preferably from about 5 2:5 to about 1:20, such as from about 1:3 to about 1:10. Thus, an aqueous fluid may be conveniently introduced into the cartridge for brewing the beverage.

10 In use, a beverage may be dispensed from the cartridge containing a non-gelled beverage liquid concentrate comprising a thickener by a method comprising the steps of:

15 passing an aqueous medium through the cartridge to form a beverage by dilution of said beverage concentrate, and dispensing the beverage into a receptacle, wherein the overall weight ratio of the beverage concentrate to the aqueous medium introduced into the cartridge is about 10:1 to about 1:10.

20 In particular, the inventors have found the range of dilution of about 10:1 to about 1:10 to provide a convenient and reliable way of providing a consumer with a beverage in a cartridge that is small and convenient for a consumer, for example about 5:1 to about 1:10, such as about 1:1 or about 1.2 to about 1:8.

25 In use, the aqueous medium may be introduced into the cartridge above room temperature. For example, the temperature of the aqueous medium when introduced into the cartridge may be from about 50°C to about 100°C, for example from about 70°C to about 95°C, such as about 85°C. The 30 aqueous medium may be heated to this temperature by a heater provided in the beverage dispenser.

The method may comprise the additional step mixing the mixture of beverage concentrate and the aqueous medium with another aqueous medium, such as milk. This may occur, for example, either in the receptacle. If the aqueous medium is

5 not added to the cartridge hot, the method may also comprise heating the mixture of beverage concentrate and the aqueous medium to a temperature of from 50°C to about 100°C, for example from about 70°C to about 95°C, such as about 85°C after it has passed through the constriction. This may be

10 achieved, for example, either in the beverage dispenser itself or in the receptacle, for example by adding the mixture of beverage concentrate and the aqueous medium to a heated fluid, such as milk.

15 The beverage dispenser used in the first aspect of the present invention may comprise a housing containing a water heater, a water pump, optionally an air compressor, a control processor, a user interface and a head. The head may comprise a holder for holding, in use, the cartridge.

20 The beverage preparation machine may also be provided with a water tank.

The housing of the beverage dispenser may comprise a dispense station where dispensation of the beverage takes

25 place. The dispense station may comprise a receptacle stand having a hollow interior forming a drip tray.

The head of the beverage dispenser may be located towards the top of the housing above the receptacle stand. The

30 holder of the head may be shaped to receive the cartridge of the first aspect and to hold the cartridge in the correct orientation such that water may be passed through the

cartridge. The holder and head may be provided with sealing means for sealing around a periphery of the cartridge to prevent by-pass flow of water in use. The head may be designed to direct flow of water downwardly through the

5 cartridge so that beverage exits the cartridge through a lowermost surface of the cartridge. Alternatively, the head may be designed to direct flow of water upwardly through the cartridge so that beverage initially exits the cartridge through an uppermost surface of the cartridge before being

10 ultimately directed downwardly to a receptacle.

The user interface may be located on the front of the housing and comprises a start/stop button, and a plurality of status indicators. The water tank may be located to the

15 rear of the housing and is connected in use to a water tank station located at a rear half of the housing. The water pump may be operatively connected between the water tank and the water heater and controlled by the control processor.

20 The water heater may be located in the interior of the housing. The heater is preferable capable of heating water received from the water pump from a starting temperature of approximately 20°C to an operating temperature of around 85°C in under 1 minute.

25

The control processor of the beverage preparation machine may comprise a processing module and a memory. The control processor is operatively connected to, and controls operation of, the water heater, water pump, air compressor

30 and user interface.

- 25 -

An example of a beverage dispenser that may be used in the present invention is described in PCT/GB2005/004113.

5 During their investigations, the inventors recognised a further problem associated with the use of a beverage concentrate comprising a thickener in a beverage dispenser. In particular, the inventors have recognised that some 10 beverage dispensers contain a constriction in the flow path between the point at which a liquid beverage concentrate is mixed with an aqueous fluid and the outlet of the beverage dispenser. In use, the inventors have found that, if a gelled concentrate is not fully dissolved in the aqueous fluid and some gel remains, the gel can be caught by the 15 constriction in the flow path to block the beverage dispenser. Additionally or alternatively, if the beverage is too thick, the pressure required to force the mixture of the beverage concentrate and the aqueous fluid through the constriction becomes too great.

20 Accordingly, in a second aspect, the present invention provides a beverage dispensing system comprising:

25 a cartridge containing a concentrate chamber comprising beverage concentrate,

30 an outlet downstream of the concentrate chamber for the discharge of a beverage,

35 a flow path connecting the concentrate chamber and the outlet, the flow path containing a means for mixing the beverage concentrate with an aqueous medium to form the beverage,

40 wherein the flow path has a maximum cross-section area of X and a minimum cross-section area of Y, wherein the

ratio of X to Y is about 20 or greater, and wherein the beverage concentrate is a non-gelled beverage liquid concentrate or a solid beverage concentrate comprising an alginate and / or a thermally reversible gelling thickener.

5

The preferred features of the non-gelled concentrate of this second aspect are the same as those previously described in the first aspect of the invention.

- 10 The cartridge used in this second aspect may be provided connected to a flow path, for example by being provided with an outlet connected to the beverage flow path. It may be provided in single-serving or multiple-serving form. However, in a preferred embodiment of this second aspect,
- 15 the beverage concentrate is provided in a cartridge according to the first aspect. In other words, the cartridge may be provided with an inlet and outlet and a means for mixing the concentrate with an aqueous fluid and, as such, the cartridge may be the cartridge defined in the
- 20 first aspect. In this case, the cartridge may be further provided with a constriction or aperture having a ratio of X to Y as defined above. Thus, the constriction or aperture may be provided downstream of a chamber that contains (pre-brewing / pre-dilution) the beverage concentrate contained
- 25 in the flow path between the inlet and outlet of the cartridge.

As well as a non-gelled beverage liquid concentrate, the second aspect of the invention may provide a cartridge

- 30 containing a solid beverage concentrate comprising an alginate (as previously defined). While the use of solid concentrates may have disadvantages over liquid concentrates

such as increased brew / dilution times and less reliable brewing, the inventors have found that a solid alginate and / or a solid thermally reversible gelling thickener may be used to provide the delayed-thickening of the beverage until 5 after the beverage is dispensed from the beverage dispenser.

In particular, an alginate may thicken in the presence of calcium ions. Thus, when provided in a solid concentrate, the alginate may be dissolved in the aqueous fluid and be 10 dispensed into a receptacle. Then, a liquid comprising calcium ions may be added to the receptacle, for example milk. Only then does the alginate thicken by complexing to the calcium ions. Therefore, the thickening of the beverage may be delayed until it is dispensed out of the beverage 15 dispenser into a receptacle. In this way, the beverage is not thickened before it passes through the constriction in the flow pathway, only afterwards. Therefore, the pressure needed to pass the beverage through the constriction is reduced, facilitating the passage of the beverage through 20 the beverage dispenser.

In addition, the inventors have recognised that thermally reversible gelling thickeners increase their viscosity at higher temperature. Therefore, if provided in solid form 25 the thickener may, for example, be dissolved (e.g. into colloidal form) in a cold fluid (e.g. one having a temperature of 5°C to 50°C), passed through a constriction and then mixed (either in the beverage preparation system or in the receptacle itself) with a hot fluid to provide 30 thickness after the dissolved thickener has passed through the constriction.

As used herein, the term "solid concentrate" refers to a concentrate that contains substantially no liquid ingredients (i.e. liquid at 20°C). For example, the solids content may be about 95 weight% or greater, such as about 98 5 weight% or greater, for example 99 weight% or greater, such as about 100 weight%. While less convenient for brewing / dilution, solid concentrates tend to have a longer shelf-life than liquid concentrates unless the liquid concentrates are suitably packaged.

10

The preferred features (for example, the weight % of the alginate, preferred additional ingredients and the inclusion of a calcium ion sequesterant) of the solid concentrate are the same as those previously described for the beverage 15 liquid concentrate of the first aspect.

Thus, the second aspect may further provide a cartridge according to the first aspect of the invention provided with a solid concentrate comprising an alginate and / or a 20 thermally reversible gelling thickener in the place of the liquid beverage concentrate of the first aspect.

Whatever form the concentrate takes, preferably, the beverage concentrate comprises about 0.01 to about 5 weight% 25 of thickener. More preferably, the beverage concentrate comprises about 0.01 weight% to about 2 weight% of thickener, more preferably about 0.1 to about 1 weight% of thickener, for example about 0.2 weight% to about 0.8 weight%, even more preferably about 0.5 weight%. The 30 inventors have found that, at too low concentration, the thickening effect of the thickener is reduced, while at high concentration, the thickener tends to become less easy to

- 29 -

dissolve in the liquid ingredient. Preferably, if an alginate and / or a thermally reversible gelling thickener are provided, they are provided having the above ranges of weight.

5

The cartridge of this second aspect may be rigid, semi-rigid or flexible. The cartridge may be formed from substantially air- and water-impermeable materials. The cartridge may be provided sealed except for its connections to the beverage preparation system. For example, the inlet and outlet (if present) of the cartridge may be covered by a membrane (for example, a laminate), which may be pierced in use to allow introduction of an aqueous fluid and the dispensing of a beverage.

15

The cartridge may also be separated from the means for mixing the beverage concentrate with the aqueous fluid. Thus, the beverage concentrate may be conveniently provided in greater than a single-serving quantity. For example, the beverage dispenser may be provided with a cartridge containing multiple servings of the beverage concentrate and a metering device for providing a metered amount of beverage concentrate to the flow path for mixing with an aqueous fluid.

25

The ratio of X to Y measures the constriction in the flow path. It is noted that the cross-section of the flow path is measured perpendicular to the flow path itself. If the flow path splits into a series of parallel flow paths and the flow path is configured so that, in use, the beverage concentrate / prepared beverage passes through all of the parallel flow paths, then the total cross-section of the

- 30 -

flow path is taken to be the sum of the cross-sections of the individual parallel flow paths.

Preferably, the ratio of X to Y is about 50 or greater, such 5 as about 100 or greater, for example about 150 or greater. In particular, as the constriction becomes more significant, the benefit of using a thickener according to the second aspect becomes even greater. However, preferably the ratio of X to Y is about 2000 or less, such as 1000 or less, such 10 as about 500 or less, for example about 350 or less. This is so that an excessive pressure is not required to force liquids to flow through the beverage dispenser. Thus, a preferred range of the ratio of X to Y is about 20 to about 2000, for example about 50 to about 500, more preferably 150 15 to 350, such as about 250.

The second aspect may also be expressed in terms of the actual cross-section area constriction. Thus, the inventors have found that, if other thickeners are used in beverage 20 systems having an aperture in the flow path of cross-sectional area of about 2 mm² or less, gel pieces may become stuck in the aperture and / or a greater pressure may be required to force liquid through the aperture. However, the thickeners of this second aspect facilitate the use of such 25 an aperture.

Accordingly, the second aspect may provide a beverage dispensing system comprising:

30 a cartridge of beverage concentrate,
an outlet downstream of the cartridge of beverage concentrate for the discharge of a beverage,

a flow path connecting the cartridge of beverage concentrate to the outlet, and

a means for mixing the beverage concentrate with an aqueous medium to form the beverage, the means for mixing 5 being either integrated into the cartridge of beverage concentrate or contained in the flow path,

wherein the flow path comprises an aperture having a cross-sectional area of 2 mm² or less, and wherein the beverage concentrate is a non-gelled beverage liquid 10 concentrate or a beverage concentrate comprising an alginate and / or a thermally reversible gelling thickener.

Preferably, the aperture has a cross-sectional area (X) of about 1 mm² or less, for example about 0.5 mm² or less. In 15 particular, as the aperture becomes smaller, the benefit of using a thickener according to the second aspect becomes even greater. However, preferably the aperture has a cross-sectional area of about 0.05 mm² or greater so that an excessive pressure is not required to force liquids to flow 20 through the beverage dispenser. For example, the aperture may have a cross-sectional area of about 0.1 mm² or greater, such as about 0.2 mm² or greater. Thus a preferred range of minimum cross-sectional areas is about 0.05 mm² to about 2 mm², such as about 0.1 mm² to about 0.5 mm².

25

For example the aperture may have a cross-sectional area of 0.36 mm² (e.g. a square aperture with sides of 0.6 mm); the aperture may also have a cross-sectional area of 0.24 36 mm² (e.g. a rectangular aperture with sides of 0.6 mm and 0.4 30 mm). For example, such an aperture may be a foaming means, such as eductor. It will be understood that the aperture may take other shapes other than square and rectangular.

Preferably, the maximum cross-section area (Y) of the flow path is 1000 mm² or less, such as 500 mm² or less, such as 200 mm² or less, more preferably 100 mm² or less. For 5 example, the flow path may have a maximum cross section of 87.8 mm². However, the flow path may have a maximum cross-section area (Y) of 5 mm² or more, such as 10 mm² or more, preferably 20 mm² or more, for example 50 mm² or more. Within these limits, the inventors have found it convenient 10 to work a beverage preparation system, for example facilitating the transport of liquids through the beverage preparation system. For example the maximum cross-section area (Y) may be 5 to 1000 mm², such as 10 to 500 mm².

15 The aperture or constriction may be a foaming means, such as an eductor, to provide optional foaming of a beverage dispensed from the beverage dispenser. For example, the foaming means, such as the eductor, may be provided in a cartridge (e.g. within the flow path of the cartridge) for a 20 beverage dispenser as described herein, for example downstream of a chamber containing (pre-brewing / pre-dilution) the beverage concentrate.

For example, the second aspect of the invention may provide 25 a beverage dispensing system comprising:

- a cartridge of beverage concentrate,
- an outlet downstream of the cartridge of beverage concentrate for the discharge of a beverage,
- a flow path connecting the cartridge of beverage 30 concentrate to the outlet, and
- a means for mixing the beverage concentrate with an aqueous medium to form the beverage, the means for mixing

being either integrated into the cartridge or beverage concentrate or contained in the flow path,

wherein the flow path comprises an eductor, and wherein the beverage concentrate is a non-gelled beverage liquid

5 concentrate or a beverage concentrate comprising an alginate and / or a thermally reversible gelling thickener.

The second aspect of the invention also extends to a method of dispensing a beverage from a beverage system,

10 wherein the beverage system contains a cartridge, the cartridge comprising one or more chambers containing a non-gelled beverage liquid concentrate comprising a thickener, and the chamber is connected to an outlet of the beverage system by a flow path,

15 the method comprising the steps of:

mixing the beverage concentrate with an aqueous medium, either in the chamber(s) of the cartridge or in the flow path of the beverage system connecting the chamber(s) to the outlet;

20 passing the mixture of beverage concentrate and the aqueous medium through an aperture or constriction (such as an eductor) as previously defined, and

dispensing the beverage into a receptacle,

25 wherein the overall weight ratio of the beverage concentrate to the aqueous medium introduced into the cartridge is about 10:1 to about 1:10.

The method may comprise the additional step of providing or adding a liquid containing calcium, for example a milk-based liquid to the receptacle and / or mixing it with the mixture of beverage concentrate and the aqueous medium within the beverage preparation system. The method may also comprise

heating the mixture of beverage concentrate and the aqueous medium to a temperature of from 50°C to about 100°C, for example from about 70°C to about 95°C, such as about 85°C after it has passed through the constriction. This may be

5 achieved, for example, either in the beverage dispenser itself or in the receptacle, for example by adding the mixture of beverage concentrate and the aqueous medium to a heated fluid, such as milk.

10 The inventors have further investigated combinations of thickeners that provide advantageous mouthfeel to a beverage prepared from a beverage concentrate. Of all the thickeners tested, alone and in combination, the inventors have found that a combination of methyl cellulose and an alginate

15 provide a mouthfeel that is surprisingly advantageous to the consumer.

Accordingly, the present invention provides in a third aspect a beverage concentrate comprising a thickener,

20 wherein the thickener comprises methyl cellulose and at least one alginate in a weight ratio of 1:5 to 5:1, wherein the methyl cellulose and the at least one alginate are present in a combined amount of about 0.01 to about 5 weight%.

25 The preferred features of the beverage concentrate (for example, the weight % of the alginate, preferred additional ingredients and the inclusion of a calcium ion sequesterant) of this third aspect are the same as those of the liquid

30 beverage concentrate of the first aspect. It should be noted that, while the beverage concentrate of the third

- 35 -

aspect may be a liquid concentrate as defined in the first aspect, it may also be a solid concentrate.

EXAMPLES

5

Example 1

The following working example demonstrates the benefits of this invention in an on-demand beverage prepared with two capsules: one capsule containing 21.5g of milk brewed with 10 50mL of hot water at 94°C and one capsule containing 20g of concentrated liquid base recipe brewed with 50mL of hot water at 94°C to create a final 100-150 mL beverage.

Reference concentrated liquid base recipe, comprising:

15

- ~63% of Iso-glucose
- ~30% of water,
- ~5.% of 100% soluble coffee
- ~1.2 % of flavours

20

Example 1: The inventive liquid beverage concentrate was prepared by the addition of Sodium Alginate and Methyl Cellulose into the above described recipe. The inventive concentrated liquid concentrate was prepared by pre-blending 25 0.25% of commercial Alginate, which consists of mixtures of Sodium Alginate and di-sodium phosphate; 0.25% of commercial Methyl cellulose; 0.20% of tri-sodium citrate with 2.02% of extra fine sugar in a separate vessel to have a homogenous blend to help their dispersion and dissolution. Water was 30 supplied to a vacuum mixer. Once the pressure in the mixer reached -160mPa, the blend was fed under vacuum into the mixer through a pipe. Mixing at this pressure prevents the

incorporation of air in the mix, otherwise it would form a mousse. Agitation and recirculation were programmed to help gum dissolution and avoid lump formation. The pressure was then increased to -500mPa before the Iso Glucose was added.

5 Soluble coffee was then fed into the vacuum mixer at the same pressure, agitation and recirculation conditions. Recirculation and vacuum were then stopped before the addition of the flavours. A final mixing with all the ingredients, at -500mPa with agitation and recirculation was 10 conducted before sending the product to the next process step. To control the quality of the mixing, viscosity was measured with a Brookfield DVII viscometer. at 20°C with spindle S3, at a speed of 100rpm and Torque between 30-70%.

15 On drinking, after brewing, the overall beverage was thicker and smoother in texture with creamier mouthfeel and offered enhanced organoleptic properties in the inventive liquid beverage concentrate compared to the reference concentrated liquid base recipe.

20

The flavour variability between four different samples was evaluated using DOD (Degree of Difference methodology in which the DOD from the reference is rated on a scale of 1-11, where 1 is the same as control and 11 is very different

25 to control. The different samples contained:

1. a mixture of sodium alginate (0.25%) and methyl cellulose (0.25%) (control, inventive recipe as described in example 1)
- 30 2. no thickeners;
3. methyl cellulose only (0.25%); and
4. sodium alginate only (0.25%).

The DOD test was conducted including a blind control and a random presentation of samples. The blind control was the mix of 2 thickeners. The test was conducted with 5 trained 5 panelists and 2 repetitions. The calculations of the significance level are made on the average of 10 measures with a Two-way ANOVA with replication and Dunnett test at 10% risk level.

10 The results of the DOD test are shown in Figure 2 and in Table 1:

Sample	1	2	3	4
Mouthfeel	-0.11	-0.78	-1.22	-0.56
Creaminess	0	-0.89	-0.89	0.22
Thickness	0.22	-1	-1.44	-0.44
Mouthcoating	0.11	-0.44	-0.78	-0.56
Coat Throat	0	-0.44	-0.78	0
Overall DOD	2	4.11	4.67	4.22

Formatierte Tabelle

Table 1

15

The results show that:

- the sample without thickeners is perceived as being significantly different in overall DOD and it is directionally less thick, coats less mouth and throat;
- the sample with methyl cellulose only is significantly different with significantly less thickness and less mouthcoating than the reference sample containing the combination of the two thickeners; and
- the sample with alginate only is perceived as being significantly different in overall DOD and it is

directionally less thick, less mouthcoating, slightly more creamy in texture than the reference sample containing the combination of the two thickeners.

5 Example 2

The following examples demonstrate how thickeners may be used so as to allow efficient mixing of a beverage concentrate with an aqueous medium within a cartridge. The examples also show how certain thickeners may cause 10 difficulties in using a concentrate comprising a thickener and a constriction in the flow path to the outlet of the beverage system.

A cartridge of about 50 ml volume was provided. It was 15 attempted to be filled with the beverage liquid concentrates as described in example 1 containing the following thickeners:

1.1 Xathan gum (from CP Kelco) 0.05 - 0.2% weight total
20 beverage
1.2 low-methoxyl pectin (from CP Kelco) 0.05- 0.5%
1.3 kappa-carrageenan gum (from CP Kelco) 0.05 - 0.35%
1.4 iota carrageenan (from CP Kelco) 0.05 - 0.35%
1.5 lambda carrageenan (from CP Kelco) 0.05 - 0.6%
25 1.6 sodium alginate (from Grinstead) 0.045 - 0.5%
1.7 methyl cellulose (from Dow) 0.045 - 0.25%
1.8 hydroxy propylmethyl cellulose (from Dow) 0.1 - 0.5%

Xathan gum was found to considerably thicken the 30 concentrate, making it difficult to fill the beverage cartridge and causing high capsule residues. Further, it was found that it became difficult to force the brewed

- 39 -

beverage through an eductor provided at the outlet of the capsule.

Low methoxy pectin was found to form a gel, making it

5 difficult to fill the beverage cartridge and causing a slow brewing process. Further, it was found that it became difficult to force the brewed beverage through an eductor provided at the outlet of the capsule.

10 Kappa-Carrageenan and iota-Carrageenan were found to considerably thicken the concentrate, making it difficult to fill the beverage cartridge and causing a slow brewing process. Further, it was found that it became difficult to force the brewed beverage through an eductor provided at the

15 outlet of the capsule.

Lambda Carrageenan was found not to gel; however, it was found not to give the same texture to a beverage as either an alginate or methyl cellulose, either alone or in

20 combination.

Sodium alginate, methyl cellulose and hydroxy propylmethyl cellulose could be successfully loaded into and brewed in the cartridge.

The embodiments of the present invention for which an exclusive property or privilege is claimed are defined as follows:

1. A method of dispensing a beverage from a cartridge containing a beverage liquid concentrate comprising an alginate and / or a thermally reversible gelling thickener dissolved in the concentrate, the method comprising the steps of:

passing an aqueous medium through the cartridge to form a beverage by dilution of said beverage concentrate, and

dispensing the beverage into a receptacle,

wherein the overall weight ratio of the beverage concentrate to the aqueous medium is from about 10:1 to about 1:10.

2. The method of claim 1, wherein the aqueous medium is introduced into the cartridge at a temperature of from about 50°C to about 100°C.

3. A beverage dispensing system comprising:

a cartridge containing a concentrate chamber comprising beverage concentrate,

an outlet downstream of the concentrate chamber for the discharge of a beverage,

a flow path connecting the concentrate chamber and the outlet, the flow path containing a means for mixing the beverage concentrate with an aqueous medium,

wherein the flow path comprises an aperture downstream of the concentrate chamber having a cross-sectional area of 2 mm² or less and wherein the beverage concentrate is a non-gelled beverage liquid concentrate containing about 0.01 to about 5 weight% in total of one or more thickeners or a solid concentrate containing about 0.01 to about 5 weight% in total of an alginate and / or a thermally reversible gelling thickener.

4. A beverage dispensing system comprising:

a cartridge containing a concentrate chamber comprising beverage concentrate,

an outlet downstream of the concentrate chamber for the discharge of a beverage,

a flow path connecting the concentrate chamber and the outlet, the flow path containing a means for mixing the beverage concentrate with an aqueous medium,

wherein the flow path has a maximum cross-section area of X and a minimum cross-section area of Y, wherein the ratio of X to Y is about 20 or greater, and wherein the beverage concentrate is a non-gelled beverage liquid concentrate or a solid beverage concentrate comprising an alginate and / or a thermally reversible gelling thickener.

- 1 / 2 -




Figure 1

- 2 / 2 -




Figure 2

