



(51) International Patent Classification:

F02M 35/10 (2006.01) *F02B 37/013* (2006.01)
F02B 29/04 (2006.01) *F02B 67/10* (2006.01)
F02M 35/112 (2006.01) *F16M 5/00* (2006.01)

(21) International Application Number:

PCT/EP2012/001499

(22) International Filing Date:

4 April 2012 (04.04.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

11162617.2 15 April 2011 (15.04.2011) EP

(71) Applicant (for all designated States except US): **CATERPILLAR MOTOREN GMBH & CO. KG** [DE/DE]; Falkensteiner Strasse 2, 24159 Kiel (DE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SCHLEMMER-KELLING, Udo** [DE/DE]; Im Wiessengrund 15, 24113 Molfsee (DE).

(74) Agent: **KRAMER - BARSKE - SCHMIDTCHEN**; Landsberger Str. 300, 80687 Munich (DE).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ENGINE BLOCK AND INTERNAL COMBUSTION ENGINE WITH AN ENGINE BLOCK



(57) Abstract: An engine block (10, 110) for an internal combustion engine (1, 100) with a two-stage turbocharged system (12, 112) may comprise a top side (21), a first end side (18L), and a second end side (18H), the second end side (18H) opposing the first end side (18L), and a compressor connection (34) is formed within the engine block (10, 110), the compressor connection (34) having a low-pressure side opening (50L) at the first end side (18L) for having charge air entered and a high-pressure side opening (50H) at the second end side (18H) for having charge air discharged.

DescriptionENGINE BLOCK AND
INTERNAL COMBUSTION ENGINE WITH AN ENGINE BLOCKTechnical Field

- [01] The present disclosure generally refers to a turbocharged engine system and more particularly to a configuration of a two-stage turbocharged system with exhaust gas recycling.

Background

- [02] For medium speed internal combustion engines, two-stage turbocharged systems having a low-pressure stage turbocharger and high-pressure stage turbocharger may be used to pre-compress the charge air being provided to the combustion chambers. The turbocharged systems may be mounted to an engine block at the same or at opposing sides.
- [03] Internal combustion engines exhaust a complex mixture of air pollutants. These air pollutants are composed of gaseous compounds such as nitrogen oxides (NO_x), and solid particulate matter also known as soot. Due to increased environmental awareness, exhaust emission standards have become more stringent, and the amount of NO_x and soot emitted to the atmosphere by an engine may be regulated depending on the type of engine, size of engine, and/or class of engine.
- [04] In order to ensure compliance with the regulation of NO_x, a strategy called exhaust gas recycling (EGR) for mixing the exhaust gas into the charge air may be implemented. EGR may reduce NO_x emission. As an exemplary EGR system, the not yet published EP application 09002111 (filed by Caterpillar Motoren GmbH & Co. KG on 16 February 2009) discloses a turbocharged engine with EGR. In particular, the EP application discloses an

engine having end sides being opposite in a lengthwise direction of a crankshaft. On each side, a single-stage turbocharger system, i.e. an exhaust turbocharger with a turbine and a compressor, is arranged. The turbines are fluidly connected to a common exhaust manifold of the engine, while the compressors are fluidly connected to a common intake manifold of the engine.

- [05] As another example, the not yet published EP application 09015247 (filed by Caterpillar Motoren GmbH & Co. KG on 9 December 2009) discloses a two-stage turbocharged engine with exhaust gas recycling using a specifically shaped mixing pipe configuration.
- [06] The large dimensions of medium speed internal combustion engines may result in large charge air systems and large exhaust gas systems of similar dimensions as the combustion engine. For example, charge air or exhaust gas pipes may extend along the sides of the internal combustion engines from one turbocharger to the other.
- [07] Medium speed internal combustion engines may moreover be adapted for the use with fuels such as diesel fuel, light fuel oil (LFO), heavy fuel oil (HFO), alternative fuels of first generation biofuels (e.g. palm oil, canola oil, oils based on animal fat) and second generation biofuels (e.g. oils made of non food corps, i.e. waste biomass) that produce an exhaust gas that is destructive, e.g. corrosive, to the components with which the exhaust gas gets in contact.
- [08] In addition to the conventional exhaust gas system, which is inherently subjected to any corrosiveness of the exhaust gas, an EGR system subjects also components of the charge air system to the corrosiveness of the exhaust gas by adding the corrosive exhaust gas to the charge air.
- [09] The present disclosure is directed, at least in part, to improving or overcoming one or more aspects of prior systems.

Summary of the Disclosure

- [10] According to an aspect of the present disclosure, an engine block for an internal combustion engine with a two-stage turbocharged system may

comprise a top side, a first end side, and a second end side, the second end side opposing the first end side, and a compressor connection is formed within the engine block, the compressor connection having a low-pressure side opening at the first end side for having charge air entered and a high-pressure side opening at the second end side for having charge air discharged, wherein the top side is configured for mounting a charge air inlet manifold thereon and there is no opening through the top side for guiding charge air there through.

[11] According to another aspect of the present disclosure, an internal combustion engine may comprise an engine block as described herein having a top side, a first end side, and a second end side, the second end side opposing the first end side; a two-stage turbocharged system comprising a low-pressure turbocharger with a low-pressure compressor and a high-pressure turbocharger with a high-pressure compressor mounted at the first end side and the second end side of the engine block, respectively; a plurality of cylinder units mounted at the top side and reaching into the engine block; and a charge air system comprising a compressor connection being integrated in the one-piece cast engine block for connecting the low-pressure compressor and the high-pressure compressor of the two-stage turbocharged system, and an inlet manifold for distributing charge air to each of the plurality of cylinder units, wherein the inlet manifold comprises a plurality of charge air guide elements as e.g. described above and each charge air guide element includes a mounting section and a charge air guide section.

[12] According to another aspect of the present disclosure, a method for manufacturing an engine block for an internal combustion engine may comprise casting of the engine block to comprise a top side, a first end side, and a second end side, the second end side opposing the first end side, wherein during the casting, a compressor connection is formed within the engine block, the compressor connection having a low-pressure side opening at the first end side for having charge air entered and a high-pressure side opening at the second end side for having charge air discharged.

- [13] In some embodiments, the engine block may be a one-piece cast and the compressor connection may be formed within the one-piece cast. There may be no fluid connection through the top side, e.g. to the compressor connection or another charge air conduit within the engine block. In particular, the compressor connection may be the only charge air guiding conduit casted into the engine block.
- [14] In some embodiments, the compressor connection may comprise an air tight side wall connecting low-pressure side opening and high-pressure side opening. The air tight side wall may comprise only a single charge air inlet opening and a single charge air outlet opening. The air tight side wall may additionally comprise an opening configured for mounting a drain valve, e.g. at the bottom side of the compressor connection next to the high-pressure side opening.
- [15] The following advantages may apply to turbocharged internal combustion engines as disclosed herein.
- [16] An inlet manifold external to the engine block may provide better access and may be easier to mount, operate, and replace than an internal inlet manifold being integrated within the engine block. In addition, an internal low-pressure compressor connection arranged within the engine block may not be prone to service.
- [17] For example, corrosion caused by exhaust gas supplemented to the charge air may cause damage components of the charge air system such as the air guide elements of the inlet manifold or the mixing pipe. An exchange of a damaged component located at the outside may be easily serviced and may not affect the engine block, as, e.g., air guide elements and mixing pipes may be formed as separate cast parts that then may be replaced if damaged.
- [18] Other features and aspects of this disclosure will be apparent from the following description and the accompanying drawings.

Brief Description of the Drawings

- [19] Fig. 1 is a schematic perspective view of an internal combustion engine with a two-stage turbocharged system;
- [20] Fig. 2 is a schematic cut view of the internal combustion engine of Fig. 1;
- [21] Fig. 3 is a schematic perspective view of a charge air guide element of the internal combustion engine of Fig. 1;
- [22] Fig. 4 is a schematic perspective view of an engine block of the internal combustion engine of Fig. 1;
- [23] Fig. 5 is a schematic illustration of the flow of the charge air within the internal combustion engine of Fig. 1;
- [24] Fig. 6 is a schematic perspective view of an internal combustion engine with a two-stage turbocharged system in V configuration;
- [25] Fig. 7 is a schematic perspective view of charge air guide elements of the internal combustion engine of Fig. 6; and
- [26] Fig. 8 is a schematic perspective view of a mixing pipe.

Detailed Description

- [27] The following is a detailed description of exemplary embodiments of the present disclosure. The exemplary embodiments described therein and illustrated in the drawings are intended to teach the principles of the present disclosure, enabling those of ordinary skill in the art to implement and use the present disclosure in many different environments and for many different applications. Therefore, the exemplary embodiments are not intended to be, and should not be considered as, a limiting description of the scope of patent protection. Rather, the scope of patent protection shall be defined by the appended claims.
- [28] The present disclosure may be based in part on the realization that EGR may result in damages to the charge air system, which results in the potential requirement to ease replacement of damaged components of the charge air system. As a result, new configurations for medium speed internal combustion

engines are disclosed that may improve accessibility of those components being affected by ECR and, in particular, allow the implementation of those affected components as replacement parts.

[29] For large air systems of two-stage turbocharged systems with turbochargers positioned at opposing ends of the engine block, the present disclosure discloses as an example a medium speed internal combustion engine having a low-pressure charge air connection between the opposed turbochargers integrated in a casted engine frame (hereinafter referred to as engine block) and providing an high-pressure charge air connection from the second stage turbocharger to the cylinders at the outside, e.g., on top of the casted engine block by composing a charge air inlet manifold from modularized casted engine parts.

[30] Moreover, the present disclosure discloses an engine block, e.g., a one-piece casted engine block, for internal combustion engines.

[31] In addition, the present disclosure discloses a mixing pipe for connecting a turbocharged system with an inlet manifold for implementing EGR in a compact manner.

[32] Figs. 1 to 5 refer to an in-line configuration of an internal combustion engine. However, the new concepts may be applied similarly to different engine configurations such as a V-configuration as illustrated in Figs. 6 and 7.

[33] Referring to Figs. 1 to 5, an internal combustion engine 1 may comprise several cylinder units 16A-16I arranged in-line. As an example, Fig. 1 shows nine cylinder units. Internal combustion engine 1 may comprise an engine block 10 housing the crankshaft and providing support for cylinder units 16A-16I being mounted thereon and reaching through cylinder openings 11A-11I at a top side 21 of engine block 10 into the inside of engine block 10.

[34] Internal combustion engine 1 may further comprise a two-stage turbocharged system 12 having a low-pressure stage turbocharger 26 and a high-

pressure stage turbocharger 28. Internal combustion engine 1 may further comprise a fuel tank, one or more catalyst systems, and an engine control unit, which are not shown.

[35] Cylinder units 16A-16I may each comprise a cylinder head part 17, a combustion chamber, and a cylinder associated for guiding a piston within a cylinder liner. The piston may be connected to a crankshaft. A cover 48 may cover and protect the top of cylinder head part 17 as well as mechanical parts and fluid connection parts being arranged thereon. Internal components of cylinder units 16A-16I are not shown in detail.

[36] In addition to top side 21, engine block 10 may have end sides 18L and 18H, being opposite in a lengthwise direction 19 defined by the longitudinal arrangement of cylinder units 16A-16I. Engine block 10 may further have opposing long sides 20A, 20B being opposite in a direction orthogonal to lengthwise direction 19. Cylinder units 16A-16I may linearly be arranged between end sides 18L and 18H and parallel to long sides 20A, 20B.

[37] Internal combustion engine 1 may comprise a charge air system, which includes, e.g., an intake manifold 22, and an exhaust gas system, which includes, e.g., an exhaust manifold 24. For EGR, a fluid connection 36 between the exhaust gas system and the charge air system may be provided such that in a controlled manner exhaust gas can be mixed with the charge air before charging the combustion chamber. In Fig. 1, fluid connection 36 may leak into a mixing pipe 29 that may be provided before the charge air enters intake manifold 22.

[38] Intake manifold 22 may extend on top of top side 21 in lengthwise direction 19 and may be fluidly connected to each of cylinder units 16A-16I. Accordingly, top side 21 may be configured for mounting a charge air inlet manifold thereon. Top side 21 may be free of any charge air openings that would provide a fluid connection from a fluid charge air passage within the engine block to intake manifold. Accordingly, there may be no opening through top side 21 for guiding charge air there through. In other words, the top side is configured to

fluidly separate the inside of the engine block, in particular the charge air passage within the engine block from the top side. Thus, only openings and mounting means for mounting the cylinder unit and/or the charge air guide element may be provided in the top side. Then, the top side may be configured fluid tight with the exception of the cylinder unit opening, screw holes etc. regarding charge air originating from one or both of the turbocharger units. Intake manifold 22 may be connected to high-pressure turbocharger 28 via mixing pipe 29 and to inlet openings of cylinder units 16A-16I. Each of cylinder units 16A-16I may be provided with at least one inlet valve (not shown) configured to open or close the fluid connection between intake manifold 22 and the combustion chamber of the respective cylinder unit.

[39] Intake manifold 22 may not be casted into engine block 10 and may instead be mounted as one or more separately configured parts on top of top side 21. For example, top side 21 may be configured for having mounted the one or more separately configured parts thereon. Separately configured parts may have the advantage that replacement of each part can be performed without affecting the engine block.

[40] In Fig. 2, exhaust manifold 24 may be provided above intake manifold 22. Exhaust manifold 24 may be fluidly connected to each of cylinder units 16A-16I. Each of cylinder units 16A-16I may include an exhaust valve (not shown) configured to open and close the fluid connection between the combustion chamber of a respective cylinder unit 16A-16I and exhaust manifold 24.

[41] Generally, when internal combustion engine 1 is operated, combustion chambers may be charged with charge air provided via intake manifold 22. After combustion, exhaust gas generated by the combustion process may be released from cylinder units 16A-16I via exhaust manifold 24.

[42] Two-stage turbocharged system 12 may comprise low-pressure stage turbocharger 26 and high-pressure stage turbocharger 28, turbochargers 26,

28 forming a sequential turbocharging system. Generally, turbochargers may be applied to use the heat and pressure of the exhaust gas of an engine to drive a compressor for compressing the charge air for the engine.

[43] In Fig. 1, low-pressure stage turbocharger 26 may comprise a compressor C_L and a turbine T_L that are mechanically connected via a common shaft. Similarly, high-pressure stage turbocharger 28 may comprise a compressor C_H and a turbine T_H that are connected via a common shaft.

[44] At end side 18L (also referred to as low-pressure side), low-pressure stage turbocharger 26 may be fixedly attached to engine block 10, e.g. directly or as a unit in combination with other components such as a charge air coolant block, e.g. a first cooler 30 etc.

[45] At end side 18H (also referred to as high-pressure side), high-pressure stage turbocharger 28 may be fixedly attached to engine block 10, e.g. directly or as a unit in combination with other components such as a charge air coolant block, e.g. a second cooler 32 etc.

[46] By mounting the turbochargers 26, 28 at opposite sides of engine block 10, mounting may be simplified and space may be used effectively, while providing easy access to the engine's components from long sides 20A, 20B.

[47] An inlet of compressor C_L may be configured to suck in charge air for the combustion process. Generally, an outlet of compressor C_L may be fluidly connected via a compressor connection 34 with an inlet of compressor C_H .

[48] Compressor connection 34 may be a fluid connection provided within engine block 10 and that provides a passage from end side 18L to end side 18H within the one-piece casted engine block 10 but is otherwise closed air tight (see Fig. 4). The passage may include an opening 51L at end side 18L and an opening 51H at end side 18H. The pressure within compressor connection 34 may be, e.g., 3 bar.

[49] The outlet of compressor C_L may be connected via first cooler 30 to opening 51L and opening 51H may be connected to an inlet of compressor C_H .

An outlet of compressor C_H may be connected via a second cooler 32 and mixing pipe 29 with intake manifold 22. Intake manifold 22 may be comprised of charge air guide elements 23A-23I and configured to distribute the charge air to cylinder units 16A-16I. An exemplary embodiment for charge air guide elements 23A-23I is described below in connection with Fig. 3.

[50] Low-pressure stage turbocharger 26 and first cooler 30 may form a first unit that may be mounted to end side 18L of engine block 10. High-pressure stage turbocharger 28 and second cooler 32 may form a second unit that may be mounted to end side 18H of engine block 10.

[51] In the mounted state, one may access the engine components, e.g. cylinder units 16A-16I and manifolds 22, 24, from long sides 20A, 20B and top side 21 while the side faces of engine block 10 at end sides 18L and 18H may be specifically configured and shaped for mounting the large components of two-stage turbocharged system 12, e.g. cooler/turbocharger units including turbochargers 26, 28 and first and second coolers 30, 32.

[52] During operation of engine 1, the charge air may be twice compressed and cooled before charging of the combustion chambers of cylinder units 16A-16I. Within the combustion chambers, further compression of the charge air may be caused through the movement of the pistons. Then, an appropriate amount of fuel, e.g. diesel oil, marine diesel oil, heavy fuel oil, alternative fuels, or a mixture thereof, may be injected into the combustion chambers. Then, the fuel may be combusted with the compressed charged air and produce exhaust gas, which may be discharged via exhaust manifold 24.

[53] An outlet of exhaust manifold 24 may be connected to an inlet of turbine T_H . An outlet of turbine T_H may be fluidly connected with an inlet of turbine T_L via a turbine pipe connection 35 and an outlet of turbine T_L may release the exhaust gas. The exhaust gas system may additionally comprise one or more catalyst systems and/or one or more exhaust gas filtering systems that may be arranged, e.g., externally or within turbine pipe connection 35.

- [54] For medium speed large internal combustion engines, compressor C_L may compress the charge air to 3-5 bar at 180°C. Cooler 30 may cool the charge air from about 180°C to 45°C. Compressor C_H may compress the charge air to 7-8 bar at 180°C and cooler 32 may cool the charge air from about 180°C to 45°C. After combustion, the exhaust gas may have a pressure of about 5 to 6 bar at a temperature in the range of about 450°C to 500°C. Within turbine pipe connection 35, the pressure droops to 3-4 bar at a temperature in the range of about 350°C to 400°C. After turbine T_L , the temperature at ambient pressure may be in the range of or below 250°C.
- [55] The above described operation of internal combustion engine 1 may provide power to turn the crankshaft, e.g., to drive a generator.
- [56] Referring to piston diameter, number of pistons and piston stroke, the dimensions of the engine block 10 may be as follows: a length of the engine block 10 may be in the range of 1.5 to 2.5 times the piston diameter and times the number of pistons; a width of the engine block 10 may be in the range of 3 to 5 times the piston diameter; and a height of the engine block 10 may be in the range of 4 to 5 times the piston stroke.
- [57] Within engine block 10, compressor connection 34 may extend along long sides 20A, 20B. Thus, in the case of a medium speed large internal combustion engine, compressor connection 34 may have a length of several meters, e.g. 5 m. Compressor connection 34 may be, e.g., a rectangular shaped, pipe-like conduit having inner dimensions of several tenth of a meter. Generally, compressor connection 34 may have an inner dimension of about 0.2 to 1 m, e.g. 0.5 m.
- [58] Within the charge air system, there may be an inlet for adding an additive (e.g. water) to the pre-compressed charge air.
- [59] Referring to Fig. 1, intake manifold 22 may be provided externally to engine block 10 and may be made of a sequence of charge air guide elements 23A-23I for guiding charge air from high-pressure stage turbocharger 28 to

cylinder units 16A-16I. Charge air guide elements 23a-23I may be formed as a cast part that is mounted on top of engine block 10 with, e.g., six screws.

[60] As shown in Fig. 3, an exemplary charge air guide element 23 may be configured to have a charge air section 40 and a mounting section 41. Within charge air section 40, air guide element 23 may comprise an air channel system having an inlet opening 44A on a first side of the charge air guide element, a first outlet opening 44B at a second side being opposite to the first side, thereby providing a fluid connection (first passage 48A) from the first side to the second side (specifically, to first outlet opening 44B) in lengthwise direction 19 when mounted on top side 21.

[61] As shown in Fig. 1, neighbouring charge air guide elements 23A-23I may be connected via bellows 46, thereby linearly extending the fluid connections of the sequence of charge air guide elements 23A-23I.

[62] Each charge air guide element 23 may further comprise a second outlet opening 44C that is fluidly connected to first passage 48A from the first side to the second side, thereby providing a fluid connection (second passage 48B) from the first side to the second outlet 44C. Second outlet opening 44C may be configured for providing a charge air connection to a charge air inlet of the respective cylinder unit.

[63] Mounting section 41 of the cast part may provide screw holes for mounting charge air guide element 23, for example, together with the respective cylinder unit onto top side 21 of engine block 10.

[64] Mounting section 41 may further be configured as a water ring part 42 of the respective cylinder unit for cooling the cylinder unit. For example, water ring part 42 may be configured for guiding coolant (e.g. cooling water) for cooling the cylinder during operation. Specifically, water ring part 42 may surround the respective cylinder unit and provide a water path around the cylinder liner. For that purpose, water ring part 42 may comprise a through hole for having a cylinder liner passed there through from cylinder head part 17 into engine block

10, wherein in the mounted state, a gap may exist between water ring part 42 and the cylinder liner.

[65] Mounting section 41 may moreover be the basis for mounting cylinder head part 17 thereon. Cylinder head part 17 may comprise a first tube-like extension 17A and a second tube-like extension 17B. First tube-like extension 17A may form the charge air inlet of the cylinder unit and connect to second outlet opening 44C of the respective charge air guide element 23. Second tube-like extension 17B may form the exhaust gas outlet of cylinder head part 17 and connect to exhaust manifold 24.

[66] As shown in the schematic perspective view of engine block 10 in Fig. 4, engine block 10 may be casted to provide an integrated low-pressure compressor connection 34 for connecting compressors C_L and compressor C_H .

[67] Specifically, compressor connection 34 may extend from low-pressure side 18L to high-pressure side 18H. Compressor connection 34 may be integrated in casted engine block 10, which is configured as a one piece cast, e.g. as a compact nodular cast iron component. Compressor connection 34 may comprise opening 51L at low-pressure side 18L and opening 51H at high-pressure side 18H, i.e. at the end faces of engine block 10. Compressor connection 34 may be fluid tight with the exception of these openings. Compressor connection 34 may be adapted for pressures of charge air guided there through in the range of 3-5 bar.

[68] As shown in Fig. 4, compressor connection 34 may not include charge air outlets at top side 21 of engine block 10, as compressor connection 34 may not function as a charge air manifold that distributes charge air to the various cylinder units. Compressor connection 34 may be fluid tight with respect to charge air except for the openings 51L and 51H. Instead, compressor connection 34 may provide a direct fluid connection of turbochargers 26, 28 of the two-stage turbocharged system 12 and charge air manifold 22 may be arranged downstream

of high-pressure stage turbocharger 28. Thus, there may be no fluid connection through top side 21 to compressor connection 34.

[69] Top side 21 may include primarily piston openings 11A-11I for cylinder units 16A-16I. For example, a cylinder liner may reach from a respective cylinder head part 17 through a respective mounting section 42 of respective charge air guide element 23 and further through the top side 21 into engine block 10. In Fig. 4, six screw holes 13 for mounting the charge air guide elements are exemplarily indicated for each piston opening 11A-11I on top side 21 of engine block 10. Top side 21 may not include openings for having charge air being guided there through.

[70] It is noted that piston openings 11A-11I and compressor connection 34 may be arranged with respect to the cross-section of engine block such that the pistons may pass by compressor connection 34 and accordingly not interfere space-wise.

[71] As shown in Fig. 4, compressor connection 34 may be a duct system integrated into casted engine block 10, which may be configured to withstand a charge air pressure of at least 3, 4, or 5 bar.

[72] Compressor connection 34 may comprise an air tight side wall 50S connecting the low-pressure side opening 51L and the high-pressure side opening 51H. Air tight side wall 50S may comprises an opening configured for mounting a drain valve, e.g. at the bottom side of compressor connection 34 next to high-pressure side opening 51H.

[73] Thus, air tight side wall 50S may comprise only a single charge air inlet opening and a single charge air outlet opening and air tight side wall 50S does not comprise a charge air outlet opening for each of the cylinder units, in particular not for each of the cylinder units.

[74] Top side 21 of engine block 10 may comprise at least one series of piston openings 11A-11I linearly arranged in the direction from first end side 18L to second end side 18H.

- [75] To manufacture engine block 10 for an internal combustion engine 1, one may cast engine block 10, e.g. grey cast with using sand as a mold material. During casting, compressor connection 34 may be formed within engine block 10 to have low-pressure side opening 51L at first end side 18L for having charge air entered and high-pressure side opening 51H at second end side 18H for having charge air discharged.
- [76] During casting, air tight side wall 50S may be formed to connect low-pressure side opening 51L and high-pressure side opening 51H.
- [77] As can be seen in Fig. 1, external pipe work for, e.g., high-pressure components such as mixing pipe 29, intake manifold 22, and/or exhaust manifold 24 may be mounted external to engine block 10, which may have the advantage to allow easy replacement of those high-pressure components.
- [78] Fig. 5 shows a schematic flow diagram of an exemplary charge air system. From compressor C_L , which may suck in charge air from the outside, charge air may pass cooler 30 and compressor connection 34 before being further compressed by compressor C_H . From compressor C_H , charge air may pass cooler 32 and mixing pipe 29 before being distributed by intake manifold 22 to the cylinder units. Intake manifold 22 may be composed of charge air guide elements 23. Specifically, charge air guide elements 23 may be connected to respective charge air inlets 17A of cylinder head parts of cylinder units 16A-16I.
- [79] Mixing pipe 29 may be fluidly connected via a valve (not shown) with fluid connection 36 for connecting the charge air system with the exhaust gas system. Thereby, exhaust gas may be mixed with charge air in a controlled manner before being distributed to the combustion chambers via inlet manifold 22.
- [80] The above new disclosed configuration of a two-stage turbocharged system may be applied in a similar manner to internal combustion engines in V-configuration. Fig. 6 shows exemplarily an internal combustion engine 100 with two cylinder banks 105. While one of the cylinder banks can be

seen in Fig. 6, the cylinder bank, which may be mirrored with respect to a vertical central plane of an engine block 110 is hidden by tubes of the exhaust system.

[81] The general configuration and operation of internal combustion engine 100 may be (besides the V-configuration) similar to the above described configuration of internal combustion engine 10 having a linear configuration.

[82] The embodiment shown in Fig. 6 may further include for each of cylinder banks 105 a two-staged turbocharged system 120 as discussed above in connection with Fig. 1 for a linear configuration. The top side in case of a V-configuration may include several sections, e.g. two cylinder sections through which openings for the cylinder units extend and a middle section connecting the cylinder sections (in contrast to the linear configuration, which may usually comprise only one section through which openings for the cylinder units extend.

[83] One or two compressor connections (not shown) may be integrated within engine block 110 between cylinder banks 105. The compressor connection may be casted within engine block 110 to guide charge air from the low-pressure compressor/cooler unit to the high-pressure compressor/cooler unit.

[84] Each of cylinder banks 105 may further be provided with a charge air manifold 122 and an exhaust gas manifold 124. From the high-pressure compressor/cooler unit, the charge air may be guided to charge air manifolds 122. Similar to the linear configuration discussed in Fig. 1, a sequence of charge air guide elements 123 may guide the charge air to respective charge air inlets of cylinder heads 117.

[85] A common turbine pipe connection 135 (or two separated turbine pipe connections) may connect the four turbines of the two two-stage turbocharged systems 112.

[86] As shown in Fig. 7, bellows 146 may connect neighbouring charge air inlet openings and charge air outlet openings of neighbouring charge air guide element 123.

- [87] A further aspect of the new configuration relates to the mixing pipe for EGR. The mixing pipe described below in connection with Fig. 8 may in particular be used in combination with the herein disclosed two-stage turbocharged engines but may also be used for mixing charge air and exhaust gas in different types of medium speed internal combustion engines.
- [88] Both of the linear configurations shown in Fig. 1 and the V-configuration shown in Fig. 6 may be used in combination with a specifically shaped mixing pipe that may allow EGR in a simple manner within the charge air system, specifically after the high-pressure compressor and the inlet manifold.
- [89] Fig. 8 shows exemplarily mixing pipe 29 of Fig. 1. Mixing pipe 29 may have a specific design that allows implementing EGR despite the rather short available stream length for achieving an acceptable rate of mixing of the exhaust gas and the charge air. The mixing may, for example, be acceptable if it provides essentially similar mixing conditions for all cylinder units.
- [90] Referring to the piston diameter, mixing pipe 29 may have a diameter of 40 % - 80 % of the piston diameter and a length of about 2 to 6 times the piston diameter. Thus, for 0.2 m to 0.6 m pistons, the length may be in the range from about 0.4 m to 3.6 m, e.g. at least about 0.5 m, 1 m, 1.5 m, or 2 m.
- [91] Referring to Fig. 8 and Fig. 1, mixing pipe 29 may have a first opening 70 for fluidly connecting mixing pipe 29 to a high-pressure component, e.g. cooler 32 of the two-stage turbocharged system 12, a second opening 72 for fluidly connecting mixing pipe 29 to a connecting port of inlet manifold 22, and an exhaust gas inlet port 74 for supplying exhaust gas into the mixing pipe. Exhaust gas inlet port 74 may be configured for providing a fluid connection to the exhaust gas system of the internal combustion engine.
- [92] Mixing pipe 29 may be configured to have at least one sharp bend between the first opening 70 and the second opening 72. The sharp bend may be configured to cause, during operation of the internal combustion engine 1, a turbulent stream within mixing pipe 29 to perform a mixing of exhaust gas and

charge air. For example, the at least one sharp bend may be a bend of at least 70°, 75°, 80°, 85°, 90°, 95°, 100°, or 110°.

[93] As shown in Fig. 8, mixing pipe 29 may be designed to have a first section 76A having a length in the range of 10 % of the length of mixing pipe 29. First section 76A may include exhaust gas inlet port 74. Mixing pipe 29 may be designed further to have a first sharp bend 50A of about 90°, a second section 76B, e.g., having a length in the range of 70 % of the length of mixing pipe 29, a second bend 50B of at least 70°, a third section 76C having a length in the range of 20% of the length of mixing pipe 29, a third bend 50C of at least 70°. The bending angles are measured from the deviation of the bent section from a linear direction (i.e. a linear pipe had a bending angle of 0°).

[94] The lengths of the various sections may vary for the various engine types and sizes.

[95] Exhaust gas inlet port 74 may be positioned close to the first opening 70 upstream of the first sharp bend 50A. For example, exhaust gas inlet port 74 may be arranged downstream of the first opening 50A at a distance of not more than 0.1, 0.2, 0.3, 0.4 or 0.5 m.

[96] In the configurations of Figs. 1 and 6, a flange defining the first opening 70 may be arranged to be orthogonal to a flange defining the second opening 72. Also the orientation may vary for the various engine types and sizes.

[97] In summary, to achieve the mixing of charge air and exhaust despite the limited length of mixing pipe 29, mixing pipe 29 may have at least one sharp bend 50A-50C that may enforce a turbulent stream within mixing pipe 29. In addition, to provide a mixing path of maximal length under the restricted conditions, exhaust gas inlet port 74 and the first sharp bend downstream of exhaust gas inlet port 74 may be located close to first opening 70. As shown in Figs. 1 and 8, exhaust gas may be supplied to the mixing pipe close to the connection of mixing pipe 29 and cooler 32, e.g., via two separate openings.

- [98] In the embodiment shown in Fig. 6, for each of cylinder banks 105, three sharp bends 150A, 150B, 150C may be provided. In flow direction of charge air, first sharp bend 150A may be positioned directly after an inlet opening 152 of a mixing pipe 129. At least one of sharp bends 150A, 150B, 150C may be a bend of at least 70°, 75°, 80°, 85°, 90°, 95°, 100°, or 110°.
- [99] During operation, mixing pipes 29, 129 may become damaged due to corrosive effects caused by the added exhaust in the high pressure environment. As mixing pipes may be accessible from the long sides, a replacement of the damaged mixing pipe may easily be performed when servicing the engine.

Industrial Applicability

- [100] Herein, the term “internal combustion engine” may refer to internal combustion engines which may be used as main or auxiliary engines of stationary power providing systems such as power plants for production of heat and/or electricity as well as in ships/vessels such as cruiser liners, cargo ships, container ships, and tankers. Fuels for internal combustion engines may include diesel oil, marine diesel oil, heavy fuel oil, alternative fuels or a mixture thereof, and natural gas.
- [101] In addition, the term “internal combustion engine” as used herein is not specifically restricted and comprises any engine, in which the combustion of a fuel occurs with an oxidizer to produce high temperature and pressure gases, which are directly applied to a movable component of the engine, such as pistons or turbine blades, and move it over a distance thereby generating mechanical energy. Thus, as used herein, the term “internal combustion engine” comprises piston engines and turbines.
- [102] Examples of internal combustion engines for the herein disclosed configuration of a two-stage turbocharged system include medium speed internal combustion diesel engines, like inline and V-type engines of the series M20,

M25, M32, M43 manufactured by Caterpillar Motoren GmbH & Co. KG, Kiel, Germany, operated in a range of 500 to 1000 rpm.

[103] Medium speed internal combustion engines may be large stand-alone engines that therefore provide reasonable access to the end sides of the engine block.

[104] Herein a fluid connection generally may correspond to a component providing a fluid connection, e.g., via an internal pathway having at least two openings connected by a side wall, such as e.g. a pipe. Components providing fluid pathways of the charge air system and the exhaust gas system may be connected with each other, for example, by flange connections as indicated in some of the figures.

[105] Although the preferred embodiments of this invention have been described herein, improvements and modifications may be incorporated without departing from the scope of the following claims.

Claims

1. An engine block (10, 110) for an internal combustion engine (1, 100) with a two-stage turbocharged system (12, 112), the engine block (10, 110) comprising:

a top side (21), a first end side (18L), and a second end side (18H), the second end side (18H) opposing the first end side (18L), and

a compressor connection (34) is formed within the engine block (10, 110), the compressor connection (34) having a low-pressure side opening (50L) at the first end side (18L) for having charge air entered and a high-pressure side opening (50H) at the second end side (18H) for having charge air discharged,

wherein the top side (21) is configured for mounting a charge air inlet manifold and/or a cylinder unit thereon and the top side (21) is free of openings for guiding charge air through the top side (21).

2. The engine block (10, 110) of claim 1, wherein at the first end side (18L), the engine block is configured for mounting a coolant system of a low-pressure stage of the two-stage turbocharged system (12, 112) and at the second end side (18H), the engine block is configured for mounting a coolant system of a high-pressure stage of the two-stage turbocharged system (12, 112).

3. The engine block (10, 110) of claim 1 or 2, wherein the engine block is a one-piece cast and the compressor connection (34) is formed within the one-piece cast as the only charge air guiding conduit.

4. The engine block (10, 110) of any one of claims 1-3, wherein the compressor connection (34) is configured to withstand a charge air pressure of at least 3, 4, or 5 bar.

5. The engine block (10, 110) of any one of claims 1-4, wherein there is fluid tightness in the mounted state between the inside of the engine block (10, 110), in particular the compressor connection (34), through the top side (21) to the charge air inlet manifold.

6. The engine block (10, 110) of any one of claims 1-5, wherein the compressor connection (34) comprises a fluid tight side wall connecting the low-pressure side opening (50L) and the high-pressure side opening (50H).

7. The engine block (10, 110) of claim 6, wherein the fluid tight side wall comprises an opening configured for mounting a drain valve, e.g. at the bottom side of the compressor connection (34) next to the high-pressure side opening (50H).

8. The engine block (10, 110) of claim 6 or 7, wherein the fluid tight side wall comprises only a single charge air inlet opening in form of the low-pressure side opening and a single charge air outlet opening in form of the high-pressure side opening.

9. The engine block (10, 110) of any one of claims 6-8, wherein the fluid tight side wall is free of a charge air outlet opening for each of the cylinder units, in particular not for each of the cylinder units.

10. The engine block (10, 110) of any one of the preceding claims, wherein the top side (21) comprises at least one series of piston openings (11A-11I) linearly arranged in the direction from the first end side (18L) to the

second end side (18H), in particular two series of piston openings in the case of a V-configuration.

11. The engine block (10, 110) of any one of the preceding claims, wherein for piston diameters of 0.2 m to 0.6 m, a length of the engine block (10, 110) is in the range of 1.5 to 2.5 times the piston diameter and times the number of pistons, a width of the engine block (10, 110) is in the range of 3 to 5 times the piston diameter, and a height of the engine block (10, 110) is in the range of 4 to 5 times the piston stroke.

12. An internal combustion engine (1, 100) comprising:
an engine block (10, 110) according to any one of claims 1-11 having a top side (21), a first end side (18L), and a second end side (18H), the second end side (18H) opposing the first end side (18L);

a two-stage turbocharged system (12, 112) comprising a low-pressure turbocharger (26) with a low-pressure compressor (C_L) and a high-pressure turbocharger (28) with a high-pressure compressor (C_H) mounted at the first end side (18L) and the second end side (18H) of the engine block (10, 110), respectively;

a plurality of cylinder units (16A-16I) mounted at the top side (21) and reaching into the engine block (10, 110); and

a charge air system comprising

a compressor connection (34) being integrated in the one-piece cast engine block (10, 110) for connecting the low-pressure compressor (C_L) and the high-pressure compressor (C_H) of the two-stage turbocharged system (12, 112) as the only charge air guiding conduit within the engine block (10), and

an inlet manifold (22, 122) for distributing charge air to each of the plurality of cylinder units (16A-16I), wherein the inlet manifold (22, 122) comprises a plurality of charge air guide elements (23A-23I) and each

charge air guide element (23A-23I) is a part separate from the engine block (10) and includes a mounting section (41) for mounting onto the top side (21) of the engine block (10) and a charge air guide section (40) for connecting to one of the plurality of the cylinder units (16A-16I).

13. A method for manufacturing an engine block (10, 110) for an internal combustion engine (1, 100), the method comprising:


casting of the engine block (10, 110) to comprise a top side (21), a first end side (18L), and a second end side (18H), the second end side (18H) opposing the first end side (18L),

wherein during the casting, a compressor connection (34) is formed within the engine block (10, 110) as the only charge air guiding conduit, the compressor connection (34) having a low-pressure side opening (50L) at the first end side (18L) for having charge air entered and a high-pressure side opening (50H) at the second end side (18H) for having charge air discharged.

14. The method of claim 13, wherein during the casting an air tight side wall connecting the low-pressure side opening (50L) and the high-pressure side opening (50H) is formed and the top side (21) is formed free of charge air opening.

15. The method of claim 13 or 14, wherein casting comprises grey casting, e.g., with using sand as a mold material.

Fig. 1






Fig. 2




Fig. 3





Fig. 5






Fig. 6




Fig. 7

8 / 8




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2012/001499

A. CLASSIFICATION OF SUBJECT MATTER

INV. F02M35/10 F02B29/04 F02M35/112 F02B37/013 F02B67/10
F16M5/00

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

F16M F02B F02M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	EP 2 333 292 A1 (CATERPILLAR MOTOREN GMBH & CO KG [DE]) 15 June 2011 (2011-06-15) paragraph [0025] - paragraph [0034]; figures 1,3	1-10, 12-15
X	----- WO 2009/147287 A1 (WAERTSILAE FINLAND OY [FI]; WIDJESKOG KLAUS [FI]; RAIKIO TERO [FI]) 10 December 2009 (2009-12-10) page 4, line 8 - page 5, line 12; figures 2-6	1-15
A	----- WO 2010/076383 A1 (WAERTSILAE FINLAND OY [FI]; HJORT ANDREAS [FI]; RAIKIO TERO [FI]; RAUN) 8 July 2010 (2010-07-08) page 4, line 5 - page 5, line 21; figures 1-3	1,13
	----- -/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 June 2012

Date of mailing of the international search report

12/07/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Marsano, Flavio

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2012/001499

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 019 489 A (MASCHF AUGSBURG NUERNBERG AG) 31 October 1979 (1979-10-31) page 2, line 4 - page 2, line 60; figure 1 -----	1,13
A	CH 241 269 A (SCHWEIZERISCHE LOKOMOTIV [CH]) 28 February 1946 (1946-02-28) page 2, line 12 - page 2, line 50; figures 1-3 -----	1,13

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2012/001499

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2333292	A1	15-06-2011	AT 556212 T 15-05-2012
		EP 2333292 A1	15-06-2011
		EP 2461011 A1	06-06-2012
		WO 2011069566 A1	16-06-2011
WO 2009147287	A1	10-12-2009	AT 546626 T 15-03-2012
		CN 102119267 A	06-07-2011
		EP 2307684 A1	13-04-2011
		KR 20110014245 A	10-02-2011
		WO 2009147287 A1	10-12-2009
WO 2010076383	A1	08-07-2010	CN 102265010 A 30-11-2011
		EP 2376756 A1	19-10-2011
		KR 20110099788 A	08-09-2011
		WO 2010076383 A1	08-07-2010
GB 2019489	A	31-10-1979	DE 2817486 A1 31-10-1979
		ES 479603 A1	01-01-1980
		FR 2423634 A1	16-11-1979
		GB 2019489 A	31-10-1979
		IT 1112246 B	13-01-1986
		JP 1420453 C	14-01-1988
		JP 54140017 A	30-10-1979
		JP 62028291 B	19-06-1987
		NL 7902553 A	23-10-1979
CH 241269	A	28-02-1946	NONE