

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2002 (27.12.2002)

PCT

(10) International Publication Number
WO 02/102298 A2

(51) International Patent Classification⁷: **A61K**

(21) International Application Number: PCT/EP02/06328

(22) International Filing Date: 10 June 2002 (10.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01114619.8 19 June 2001 (19.06.2001) EP

(71) Applicant (for all designated States except US): **ROCHE VITAMINS AG** [CH/CH]; Grenzacherstrasse 124, CH-4070 Basle (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SCHAFFNER, David** [CH/CH]; Fledermausgasse 3, CH-4310 Rheinfelden (CH).

(74) Agent: **MUELLER, Ingrid**; Grenzacherstrasse 124, CH-4070 Basle (CH).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR THE PREPARATION OF DISPERSIONS

(57) Abstract: The present invention relates to a process of a dispersion of an active substance or composition in an aqueous phase which comprises dispersing in an aqueous phase a solution of such substance or composition in dimethylether or in a C₄-hydrocarbon or mixtures thereof in super- or nearcritical state, decompressing the mixture and separating the dispersion from the gaseous solvent.



WO 02/102298 A2

Process for the preparation of dispersions

The present invention relates to a process for the preparations of aqueous dispersions. More particularly, the present invention relates to a process for the preparation of a dispersion of an active substance or composition in an aqueous phase. In accordance with the present invention, aqueous dispersions of an active substance or
5 composition are prepared by a process which comprises dispersing in an aqueous phase a solution of such substance or composition in dimethylether or in a C₄-hydrocarbon or mixtures thereof in super- or nearcritical state, decompressing the mixture and separating the dispersion from gaseous solvent.

10 The term "dispersion" as used herein encompasses emulsions and suspensions and refers to systems wherein the dispersed particles are in the micro or nano size range and, preferably, have a mean particle diameter of about 50 to about 300 nm. The term "active substance or composition" denotes any substance or composition which is soluble in dimethylether or C₄-hydrocarbons and substantially water-insoluble and which may be
15 solid or liquid under ambient conditions and which usually exerts a physiological activity. Examples of such active substances are especially the fat-soluble vitamins A, D, E, K; and the carotenoids like β -carotene, canthaxanthin, apocarotenal, astaxanthin, apoester, lutein, lycopene, zeaxanthin, citranaxanthin, torularhodin; fat-soluble pharmaceuticals; other fat-soluble (health care) ingredients like PUFA (polyunsaturated fatty acids), curcumin,
20 coenzyme Q10, α -lipoic acid.

Examples of C₄-hydrocarbons are hydrocarbons having four carbon atoms which can be saturated such as n-butane and isobutane, or unsaturated such as 1-butene, trans-butene and isobutene. Of these, trans-butene, 1-butene and dimethylether, especially 1-
25 butene, are preferred, particularly for the preparation of aqueous β -carotene dispersions.

The process of the present invention is suitably carried out by individually feeding an aqueous phase and a solution of an active substance or composition in the appropriate solvent in super- or nearcritical state into a mixing chamber and decompressing the mixture. Schematically, the process of this invention can be carried out as depicted in Figure 1. The active substance or composition is dispersed in an appropriate pressurized solvent, e.g., dimethylether, in an autoclave 1. The pressure of the solvent in autoclave 1 should be above the saturation vapor pressure. The dispersion obtained is fed by means of a high pressure pump 2 (e.g., a diaphragm pump Lewa Typ EL-3; supplier: HERBERT OTT AG, Missionsstrasse 22, CH-4003 Basel) into a mixing chamber 4 via a heat exchanger (e.g., a double-pipe heat exchanger) 3 in such a manner that temperature and pressure are close to or exceed the critical constants of the solvent, i.e., the solvent reaches the super- or nearcritical state. For instance, the pressure is about 45 bar to about 2000 bar, conveniently about 45 bar to about 300 bar, and preferably about 80 bar to about 200 bar. In a second autoclave 5 the aqueous phase which may contain additional agents such as stabilizers or surfactants is fed through a high pressure pump 6 (e.g., a piston pump LABOMATIC HD-300; supplier: LABOMATIC Instruments AG, Ringstr.13, CH-4123 Allschwil) and a heat exchanger (e.g., a double-pipe heat exchanger) 7 to the mixing chamber 4 at a pressure substantially corresponding to that build up by pumps 2 and 6 and at a temperature sufficient to maintain super- or nearcritical conditions in the mixing chamber 4. In the mixing chamber 4 the phases are mixed and decompressed through an aperture 8, then pass a residence zone 9 thus producing a finely dispersed aqueous, solvent-free suspension or emulsion.

The pumps 2 and 6 may be any pump conventionally used in high-pressure technology such as diaphragm or piston pumps. For the heat-exchangers 3 and 7 conventional heat exchangers such as tubular or double-pipe exchangers may be used. The autoclaves 1 and 5 (e.g., METIMEX Typ HPM, supplier: PREMEX REACTOR AG, Industriestrasse 11, Postfach 444) are suitably designed to permit pre-heating of their contents. The mixing chamber 4 comprises at least one inlet for the aqueous phase, at least one inlet for the non-aqueous (solvent) phase, and an outlet comprising an expansion aperture. The inlets for the aqueous phase and the solvent phase may be arranged at an angle of between 0 degree and 180 degree, i.e., parallel or opposite to each other, or in such a manner that the two streams meet at an angle different from 0 degree and 180 degree, e.g., at an angle of about 30 to 90 degree. The

mixing chamber is suitably tubular and has a dimension to secure turbulent conditions, i.e., is sufficiently small.

The aperture 8 suitably is circular and suitably has a diameter of about 0.05 mm to about 1.0 mm and preferably about 0.1 mm to 0.4 mm. By passing the aperture the dispersion will be expanded. By the expansion the compressed solvent will be evaporated and simultaneously the particle will be precipitated. After the residence time in the pipe the final dispersion can be easily separated from the gaseous solvent.

Figure 2 shows an exemplary expansion unit consisting of mixing chamber 4 and expansion aperture 8. By mixing of the solvent phase 10 with the aqueous phase 11 in the mixing chamber a pre-emulsion (i.e., an emulsion wherein the particle size is above the ultimately desired size) results. By passing the aperture 8, the emulsion will be expanded. By the expansion the compressed solvent will be evaporated and simultaneously the particles will be precipitated. After the residence time in the residence zone 9 the final dispersion exits (12) the unit and can be easily separated from the gaseous solvent.

As will be readily understood, temperature and pressure will have to be adjusted to the particular solvent used in the process of the present invention to make sure that the system achieves the hypercritical state. Thus, when using dimethylether which has the critical constants T_k 126.9°C and p_k 53.7 bar, the temperature of the fed streams to the mixing chamber will have to be at least 80°C. Preferably, when using dimethylether, the temperature is adjusted to a temperature of 80 to 160°C. The residence time of the solution of the active substance in the heat exchanger is not narrowly critical and generally is within the range of seconds. The residence time of the solution of the mixture in the mixing chamber is also not narrowly critical but is preferably no more than about 0.01 to about 0.1 seconds.

The ratio between the active substance or composition and the solvent is not narrowly critical and depends on the particular choice of the components involved. As will

be readily apparent, the amount of solvent must be such to secure complete dissolution of the active substance or composition in the supercritical solvent. The ratio between the aqueous phase and the solvent phase, i.e., the ratio between the fed stream of aqueous phase and the hypercritical solvent which contains the active substance or composition is also not narrowly critical. The upper limit of the concentration of active substance or composition in the final dispersion than can be prepared by the process of the invention ultimately depends on the solubility of the active substance or composition in the solvent. Dispersions containing up to about 50% by weight may be prepared. Suitably, the process conditions are adjusted in such a manner that the final dispersion contains about 0.1 to 20% by weight of active substance or composition, e.g., about 10% by weight.

The aqueous phase, and to some extent also the solvent phase, may contain additional ingredients, such as carriers, e.g. bovine, swine or fish gelatin, gum acacia, modified food starches, cellulose derivatives, pectins, ligninsulfonates; surfactants, e.g. sugar esters, polyglycerol fatty acid esters, Tween; stabilizers or antioxidants, e.g. sodium ascorbate, ascorbyl palmitate, dl- α -tocopherol, mixed tocopherols, BHT, BHA, or EMQ.

The dispersion or emulsion obtained can be further converted into a solid powder by means known per se, e.g. spray-drying or in a fluidized bed.

The emulsions or dispersions provided by the present invention can find use for all purposes where finely dispersed forms of substantially water-insoluble and fat-soluble substances or compositions are required, e.g., for coloring foodstuff or animal feed with carotenoids.

The invention is further illustrated by the following Examples.

Example 1

In this Example, an installation as depicted schematically in Fig. 1 was used. A 2 liter stainless steel autoclave 5 was charged with 1100 g of water, 80 g of ascorbyl palmitate, 258 g of fish gelatin and 550 g of sugar. The aqueous phase in autoclave 5 (pre-heated to 60°C / 6 bar N₂) was passed to heat exchanger 7 by piston pump 6 (LABOMATIC HD 300) at a flow rate of 90 g/min under a pressure of 150 bar where it was heated to 68.5°C within a residence time of 6-12 sec. Autoclave 1 was charged with 50 g of β-carotene, 6 g of α-tocopherol, 22.9 g of corn oil and 740 g of dimethylether. The oily phase in autoclave 1 (pre-heated to 30°C/ 30 bar N₂) was passed to heat-exchanger 3 by diaphragm pump 2 (Lewa Typ EL 3) under a pressure of 150 bar where it was heated to 155°C within a residence time of 5-10 sec. Aqueous phase and oily phase were simultaneously passed through mixing chamber 4 and aperture 8 having an orifice diameter of 0.25 mm to residence zone 9 where the mixture was decompressed to atmospheric pressure, producing about 5-6 kg per hour of aqueous, solvent-free dispersion of β-carotene in a gelatin/sugar matrix. The mean particle size of the dispersion was 117 nm (variance 20 nm).

15

Example 2

In this Example, an installation as described in Example 1 was used. A 2 liter stainless steel autoclave 5 was charged with 1100 g of water, 80 g ascorbyl palmitate, 258 g of fish gelatin and 550 g of sugar. The aqueous phase in autoclave 5 (pre-heated to 60°C / 6 bar N₂) was passed to heat exchanger 7 by piston pump 6 at a flow rate of 120 g/min under a pressure of 149 bar where it was heated to 64°C within a residence time of 6-12 sec. Autoclave 1 was charged with 50 g of β-carotene, 6 g of α-tocopherol, 22.9 g of corn oil and 570 g of 1-butene. The oily phase in autoclave 1 (pre-heated to 30°C/ 30 bar N₂) was passed to heat-exchanger 3 by diaphragm pump 2 under a pressure of 149 bar where it was heated to 127°C within a residence time of 5-10 sec. Aqueous phase and oily phase were simultaneously passed through mixing chamber 4 and aperture 8 having an orifice diameter of 0.25 mm to residence zone 9 where the mixture was decompressed to atmospheric pressure, producing about 7-8 kg per hour of aqueous, solvent-free dispersion of β-carotene in a gelatin/sugar matrix. The mean particle size of the dispersion was 223 nm (variance 87 nm).

30

Example 3

In this Example, an installation as described in Example 1 was used. A 2 liter
5 stainless steel autoclave 5 was charged with 1100 g of water, 80 g of ascorbyl palmitate, 258
g of fish gelatin and 550 g of sugar. The aqueous phase in autoclave 5 (pre-heated to 60°C /
6 bar N₂) was passed to heat exchanger 7 by piston pump 6 at a flow rate of 115 g/min
under a pressure of 148 bar where it was heated to 63.7°C within a residence time of 6-12
sec. Autoclave 1 was charged with 100 g of β-carotene, 12.5 g of α-tocopherol, 45.9 g of
10 corn oil and 590 g of trans-butene. The oily phase in autoclave 1 (pre-heated to 30°C/ 30
bar N₂) was passed to heat-exchanger 3 by diaphragm pump 2 under a pressure of 148 bar
where it was heated to 137°C within a residence time of 5-10 sec. Aqueous phase and oily
phase were simultaneously passed through mixing chamber 4 and aperture 8 having an
orifice diameter of 0.2 mm to residence zone 9 where the mixture was decompressed to
15 atmospheric pressure, producing about 6-7 kg per hour of aqueous, solvent-free dispersion
of β-carotene in a gelatin/sugar matrix. The produced mean particle size of the dispersion
was 223 nm (variance 73 nm).

Example 4

20

In this Example, an installation as described in Example 1 was used. A 2 liter
stainless steel autoclave 5 was charged with 130 g of water, 62 g of ascorbyl palmitate, 242 g
of fish gelatin and 384 g of sugar. The aqueous phase in autoclave 5 (pre-heated to 60°C / 6
bar N₂) was passed to heat exchanger 7 by piston pump 6 at a flow rate of 60 g/min under a
25 pressure of 109 bar where it was heated to 75.8°C within a residence time of 6-12 sec.
Autoclave 1 was charged with 25 g of lycopene, 3.1 g of α-tocopherol, 11.5 g of corn oil and
740 g of dimethylether. The oily phase in autoclave 1 (pre-heated to 30°C/ 30 bar N₂) was
passed to heat-exchanger 3 by diaphragm pump 2 under a pressure of 109 bar where it was
heated to 137°C within a residence time of 5-10 sec. Aqueous phase and oily phase were
30 simultaneously passed through mixing chamber 4 and aperture 8 having an orifice

- 7 -

diameter of 0.25 mm to residence zone 9 where the mixture was decompressed to atmospheric pressure, producing about 3-4 kg of aqueous, solvent-free dispersion of lycopene in a gelatin/sugar matrix per hour. The produced mean particle size of the dispersion was 171 nm (variance 60 nm).

5

Example 5

In this Example, an installation as described in Example 1 was used. A 2 liter stainless steel autoclave 5 was charged with 330 g of water, 68 g of ascorbyl palmitate, 188 g of lecithin and 1412 g of lebboline. The aqueous phase in autoclave 5 (pre-heated to 60°C / 6 bar N₂) was passed to heat exchanger 7 by piston pump 6 at a flow rate of 120 g/min under a pressure of 192 bar where it was heated to 67°C within a residence time of 6-12 sec. Autoclave 1 was charged with 50 g of β -carotene, 9.4 g of α -tocopherol, 34.4 g of corn oil and 740 g of dimethylether. The oily phase in autoclave 1 (pre-heated to 30°C/ 30 bar N₂) was passed to heat-exchanger 3 by diaphragm pump 2 under a pressure of 192 bar where it was heated to 170°C within a residence time of 5-10 sec. Aqueous phase and oily phase were simultaneously passed through mixing chamber 4 and aperture 8 having an orifice diameter of 0.2 mm to residence zone 9 where the mixture was decompressed to atmospheric pressure, producing about 7-8 kg per hour of aqueous, solvent-free dispersion of β -carotene in a lecithin/lebboline matrix. The mean particle size of the dispersion was 174 nm (variance 36 nm).

Claims

1. A process for the preparation of a dispersion which comprises dispersing in an aqueous phase a solution of an active substance or composition in dimethylether or in a C₄-hydrocarbon or mixtures thereof in super- or nearcritical state, decompressing the mixture and separating the dispersion from gaseous solvent.
2. A process according to claim 1 wherein the active substance or composition is selected from the group consisting of a fat-soluble vitamin, a pharmaceutical, a carotenoid, and a polyunsaturated fatty acid.
3. A process according to claim 1 or 2 wherein the active substance or composition is a carotenoid.
4. A process according to claim 3 wherein the carotenoid is β -carotene.
5. A process according to any one of claims 1 to 4 wherein the solvent is dimethylether.
6. A process according to any one of claims 1 to 4 wherein the solvent is 1-butene.
7. A process according to any one of claims 1 to 4 wherein the solvent is trans-butene.
8. A process according to any one of claims 1 to 7 wherein the mean diameter of the dispersed particles is about 20 to about 300 nm.

- 9 -

9. A process according to any one of claims 1 to 8 substantially as described herein, especially with reference to the Figures and Examples.

Figure 1




Figure 2

