



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 749 039 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
08.08.2001 Bulletin 2001/32

(51) Int Cl.7: **G03C 1/76, G03C 1/95**

(21) Application number: **96201617.6**

(22) Date of filing: **10.06.1996**

(54) **A method of forming an imaging element comprising an auxiliary layer containing solvent-dispersible polymer particles**

Verfahren zur Herstellung eines Bildaufzeichnungselements enthaltend eine Hilfsschicht, die in einem Lösungsmittel dispergierbare polymere Teilchen enthält

Procédé de formation d' un élément formateur d' image comprenant une couche auxiliaire contenant des particules polymères dispersables dans un solvant

(84) Designated Contracting States:
DE FR GB

(30) Priority: **15.06.1995 US 1917**
05.12.1995 US 567788

(43) Date of publication of application:
18.12.1996 Bulletin 1996/51

(73) Proprietor: **EASTMAN KODAK COMPANY**
Rochester, New York 14650-2201 (US)

(72) Inventors:
• **Wang, Yongcai**
Rochester, New York 14650-2201 (US)

- **Anderson, Charles Chester**
Rochester, New York 14650-2201 (US)
- **Bello, James Lee**
Rochester, New York 14650-2201 (US)
- **DeLaura, Mario Dennis**
Rochester, New York 14650-2201 (US)

(74) Representative:
Nunney, Ronald Frederick Adolphe et al
Kodak Limited
Patent Department
Headstone Drive
Harrow Middlesex HA1 4TY (GB)

(56) References cited:
US-A- 4 714 671 **US-A- 4 977 071**

EP 0 749 039 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

DescriptionFIELD OF THE INVENTION

5 **[0001]** This invention relates in general to a method of forming imaging elements, such as photographic films and papers, and in particular imaging elements comprising a support, an image-forming layer and one or more auxiliary layers. More specifically, this invention relates to a method of forming such imaging elements which have an improved auxiliary layer exhibiting superior chemical, physical and manufacturability characteristics.

BACKGROUND OF THE INVENTION

10 **[0002]** Support materials for an imaging element often employ layers comprising glassy, hydrophobic polymers such as acrylics, styrenics, and cellulose esters, for example. One typical application is as a backing layer to provide resistance to abrasion, scratching, blocking, and ferrotyping. For coating applications, the glassy polymers are normally dissolved in a solvent at very low solids to ensure low coating solution viscosities for good coatability at high coating speeds. Coating techniques employed include one to three layer extrusion dies (commonly referred to as X-hoppers), air knife, roller coating devices, meyer rods, knife over roll.

15 **[0003]** For coating solutions comprising soluble polymers of reasonably high molecular weights, for example, larger than 50,000, the solution viscosity is a strong function of polymer concentration. For example, Elvacite 2041, a methyl methacrylate polymer sold by E. I. DuPont de Nemours and Co., has been described in the photographic art to form scratch protective layers for photographic materials. The polymer is normally dissolved in an organic solvent such as methylene chloride to form a clear solution. At concentrations above, for example, 4 to 5 wt%, the Elvacite 2041 solution viscosity is at least 20 cps at ambient temperature. Such viscosity values are too high for coating applications commonly used in photographic support manufacture, for example, roll coater and skim-pan air-knife coating techniques, which require a coating solution viscosity in the range of from one to a few centipoises. Therefore, photographic manufacturers have to keep the solids below 3 wt% for low solution viscosities and good coatability at high coating speeds.

20 **[0004]** Polymer solutions of low solids are useful for applications where low dry coating coverages (<500 mg/m²) can meet the requirements of physical and mechanical properties of an imaging system. More advanced imaging applications need higher dry coating coverages for better physical and mechanical properties. To obtain high dry coating coverages, more coating solution per unit area (wet coverage) has to be applied by using low viscosity/low solids polymer solutions since high viscosity/ high solids polymer solutions cannot be coated at low wet coverages at high coating speeds (some coating methods may allow one to coat high viscosity polymer solutions at high wet coverages, but they still suffer from the disadvantages mentioned below). In general, higher wet coverages mean more solvent recovery and higher cost for drying. Furthermore, due to both manufacturing limitations and requirements of an imaging element for other physical and mechanical properties, the wet coverages cannot be increased under certain conditions and for certain applications. For example, high coating wet coverages and the high levels of solvent retained in the film support as a result of these high wet coverages may have a big impact on both dimensional stability and sensitometric properties of an imaging element. One may use resins of low molecular weight to lower the solution viscosity; however, the resultant dry coatings may not have adequate physical and mechanical properties.

25 **[0005]** Alternative approaches employing low viscosity, dispersed polymer particle-containing coating compositions have been described for paint and automotive coating industries. The use of such compositions in photographic applications has not been disclosed. For example, U. S. Patent No 4,336,177 describes a solvent coating composition comprising non-aqueous dispersible composite polymer particles larger than 0.1 μm . The particle has a core with a glass transition temperature (T_g) of about 10 °C less than the polymerization reaction temperature. The particles are stabilized by block or grafting copolymers and can be transferred directly from aqueous medium to a non-aqueous medium. U.S. Patent No 4,829,127 describes a coating composition comprising composite resin particles. Such particles are prepared by solution polymerization techniques in reaction vessels containing initiator, solvent, polymerizable monomers, and crosslinked particles. U. S. Patent No 3,929,693 describes a coating composition comprising a solution polymer and polymer particles, where the polymer particles have a crosslinked rubbery core below 60 °C and a grafted shell having molecular weight of 1,000 to 150,000. Reportedly, such coating compositions are more stable toward premature separation and flocculation. U.S Patent No. 3,880,796 describes a coating composition comprising thermo-setting polymer particles containing insoluble microgel particles having a particle size of from 1 to 10 μm . U.S. Patent No 4,147,688 describes a dispersion polymerization process of making crosslinked acrylic polymer microparticles having a particle size of from 0.1 to 10 μm . U.S. Patent No. 4,025,474 describes a coating composition comprising a hydroxyfunctional oil-modified or oil-free polyester resin, aminoplast resin, and 2 to 50% of crosslinked polymer microparticles (0.1 to 10 μm) made by a dispersion polymerization process. U.S. Patent No. 4,115,472 describes a polyurethane coating composition comprising an ungelled hydroxy-containing urethane reaction product and insoluble crosslinked acrylic polymer microparticles (0.1 to 10 μm) made by a dispersion polymerization process. Such coatings

are reportedly useful for automotive industries.

[0006] There are significant differences in designing coating compositions for photographic applications from those for paint and automotive coating industries. The coating techniques and coating delivery systems are different so that they need different coating rheologies. The drying time in exterior and interior paint and architectural coating applications is on the order of hours and days, and in the automobile industry on the order of 10 to 30 min. However, in the photographic support manufacturing process the drying time for coatings is typically on the order of seconds. Often the drying time for solvent-borne coatings is as brief as 10 - 30 seconds for high speed coating applications. These differences put additional stringencies on the coating composition for photographic materials. For example, the coating viscosity needs to be on the order of less than 10 cps, and more often less than 5 cps, instead of on the order of one hundred to several thousand cps as in other coating industries. A typical dry coating thickness for photographic materials is on the order of less than 2 μm , and more often less than 1 μm . The film formation and film quality are especially critical. The tolerance on defects caused by polymer gel slugs, gelled particles, dust, and dirt is extremely low. This requires special precautions in delivery processes. The coating solutions need to be very stable toward, for example, high speed filtration and high shear.

[0007] Aqueous coating compositions comprising water dispersible polymer particles have been reported to be useful for some photographic applications. For example, they have been used as "priming" or subbing layers on film support to act as adhesion promotion layers for photographic emulsion layers, and used as barrier layers over, for example, a vanadium pentoxide antistatic subbing layer to prevent the loss of antistatic properties after film processing as described in U.S. Patent No. 5,006,451. While these coating compositions are attractive from environmental considerations, the slow evaporation rate of water coupled with its extremely high heat of vaporization causes drying problems which are either not normally encountered or can be easily overcome in solvent-borne systems. Therefore, for manufacturing processes with conventional organic solvent drying capacity, the use of water-borne coating compositions often leads to very unsatisfactory results. In addition, challenges still exist to develop water-based coatings that provide similar physical and chemical properties in the dried film that can be obtained with organic solvent-based coatings.

[0008] Aqueous coating compositions comprising core/shell polymer particles have been disclosed for photographic materials as ferrotyping resistance layers in U.S. Patent No. 4,497,917, where the polymers are described as having a core with a Tg of greater than 70°C and a shell with a Tg from 25 to 60°C, and as subbing layers in U.S. Patent No. 4,977,071 and US Reg. No. H1016, where the polymers are described as a vinylidene chloride copolymer core/shell latex. U.S. Patent 5,366,855, issued November 22, 1994, describes for imaging elements a coalesced layer comprising film-forming colloidal polymer particles and non-film forming colloidal polymer particles. This layer is coated from an aqueous medium and contains polymer particles of both high and low glass transition temperatures. Other aqueous coating compositions that comprise core/shell polymer particles are described in U.S. Patents Nos. 4,683,269, 4,613,633, 4,567,099, 4,478,974, and 4,134,872. The use of these compositions in photographic films has not been disclosed.

[0009] It can be seen that various approaches have been attempted to obtain useful organic solvent-based coating compositions with low viscosity and high percent solids. However, the aforementioned prior art references are deficient with regard to simultaneously satisfying all the physical, chemical, and manufacturing requirements for a solvent-borne coating for more advanced imaging applications. The present invention provides a coating composition which meets all of these requirements while avoiding the problems and limitations of the prior art.

SUMMARY OF THE INVENTION

[0010] In accordance with this invention, there is provided a method of forming an imaging element for use in an image-forming process; said imaging element comprising a support, an image-forming layer and an auxiliary layer; the method comprising coating said auxiliary layer from a dispersion of polymer particles in a continuous liquid organic medium; characterized in that said polymer particles comprise a core portion which is insoluble in said organic medium and a shell portion which is physically or chemically attached to the core portion, and the shell portion is dispersible in said organic medium; wherein said continuous liquid organic medium is selected from the group consisting of alcohols, esters, ketones, aromatic hydrocarbons, chlorinated solvents, glycols and mixtures thereof; wherein said shell polymer particles are formed by polymerization of ethylenically unsaturated monomers selected from the group consisting of acrylic acid, methacrylic acid, acrylamide, methacrylamide, itaconic acid and its half esters and diesters, styrene and substituted styrenes, acrylonitrile, methacrylonitrile, vinyl acetate, vinyl and vinylidene halides, and mixtures thereof; and wherein the core polymer is formed by polymerizing monomers selected from the group consisting of acrylic acid, methacrylic acid, methyl methacrylate, ethyl methacrylate, butyl methacrylate, ethyl acrylate, butyl acrylate, hexyl acrylate, n-octyl acrylate, lauryl methacrylate, 2-ethylhexyl methacrylate, nonylacrylate, benzyl methacrylate, 2-hydroxyethyl acrylate, 2-hydroxyethyl methacrylate, and hydroxypropyl methacrylate, acrylonitrile, methacrylonitrile, acrylamide, methacrylamide, vinyl acetate, vinyl propionate, vinylidene chloride, vinyl chloride, styrene, t-butyl styrene, vinyl toluene, dialkyl maleates, dialkyl itaconates, dialkyl methylene-malonates, isoprene, butadiene and mixtures thereof.

[0011] The polymer particles employed in the auxiliary layer of the imaging element can be described as "solvent-dispersible polymer particles".

[0012] Coating compositions containing such solvent-dispersible polymer particles exhibit unique coating rheologies and form high quality films with excellent physical and mechanical properties that are especially well adapted to meeting the requirements of auxiliary layers of imaging elements.

DETAILED DESCRIPTION OF THE INVENTION

[0013] The imaging elements can be of many different types depending on the particular use for which they are intended. Such elements include, for example, photographic, electrophoto-graphic, electrostatographic, photothermographic, migration, electrothermographic, dielectric recording and thermal-dye-transfer imaging elements. Photographic elements can comprise various polymeric films, papers, glass, and the like, but both acetate and polyester supports well known in the art are preferred. The thickness of the support is not critical. Support thickness of 2 to 10 mil (0.06 to 0.30 millimeters) can be used. The supports typically employ an undercoat or subbing layer well known in the art that comprises, for example, for polyester support a vinylidene chloride/methyl acrylate/itaconic acid terpolymer or vinylidene chloride/acrylonitrile/ acrylic acid terpolymer.

[0014] Details with respect to the composition and function of a wide variety of different imaging elements are provided in U.S. Patent 5,340,676 and references described therein. The present invention can be effectively employed in conjunction with any of the imaging elements described in the '676 patent.

[0015] The coating compositions utilized herein to form an auxiliary layer of an imaging element comprise a continuous solvent medium having dispersed therein organic polymer particles. The polymer particles comprise a core portion which is insoluble (but may be swellable) in the medium and a polymeric shell portion which is physically or chemically attached to the core portion and which is dispersible in said organic medium. The weight of core portion to shell portion is preferably 90:10 to 30:70, more preferably 80:20 to 40:60, and most preferably 75:25 to 50:50. The core portion preferably has a mean particle size of from about 10 to about 500 nm, more preferably about 10 to about 200 nm, as measured at its dry state, for example, by electron microscopy.

[0016] The coating composition described herein is useful for various applications. It can be used in subbing layers, backing layers, interlayers, overcoat layers, receiving layers, barrier layers, stripping layers, mordanting layers, scavenger layers, antikinking layers and transparent magnetic layers. When used for such layers, the coating composition is particularly advantageous due to its unique rheological properties and good coatability in addition to environmental considerations such as the preparation of layers at considerably less solvent loads which lead to easy drying and less solvent recovery. The resultant layers are equivalent to those coated from polymer solutions in terms of the layer transparency and toughness necessary for providing resistance to scratches, abrasion, blocking, and ferrotyping.

[0017] The coating compositions utilized in the present invention may contain mixtures of the dispersible polymer particles described above. For example, it may be preferred in some applications to use a mixture consisting of one type of particle having a glassy core and another type of particle having a rubbery core. Such a mixture is desired for obtaining, for example, a strong (hard) and tough coating with good optical clarity. The coating composition can also contain up to 50% by weight, preferably up to 30% by weight of solution polymer(s). The solution polymer is defined as those soluble in the desired solvent medium.

[0018] In one of the preferred embodiments of the invention, the polymer particles are composed of a core portion which is crosslinked by using about 1 to 20 parts of crosslinking agent and a shell portion which is grafted to the core portion by covalent bonding. Such particles can be made as core/shell particles by using, for example, emulsion polymerization processes. One useful technique is the so called sequential emulsion polymerization process (see, for example, Padget, J. C. in Journal of Coating Technology, Vol 66, No. 839, pages 89 to 105, 1994). In this process, the core portion is made with the use of di/trifunctional and grafting comonomers, and the shell portion is made by conducting the polymerization in a monomer starved manner so that the monomer swelling of the core particles is limited. The use of grafting comonomers in the core ensures the formation of sufficient covalent bonds between shell and crosslinked core polymers. The resultant core/shell particles can be isolated by conventional techniques and redispersed in appropriate solvent media.

[0019] When the dispersible particles are made by sequential polymerization processes, the system is preferably designed such that the desired particle morphology exhibits low total interfacial free energy. This, however, cannot always be the case, as exemplified, for example, by dispersible particles consisting of a highly carboxylated core portion and a much less carboxylated and less hydrophilic shell portion. The overall step in the particle formation process with the desired morphology is thermodynamically unfavorable because the core portion is significantly more hydrophilic than the shell portion. In such cases, techniques by Vanderhoff, Park, and El-Aasser (ACS Symposium Series, 492, 272, 1992), and Lee and Rudin (J. Polym. Sci. Polym. Chem. Ed. 30, 2211, 1992) may be used. For example, the shell portion can be prepared by second stage polymerization at low temperature so that the mobility can be substantially reduced and thermodynamically unfavorable structures obtained.

[0020] The dispersible particles can also be prepared by an inverted core/shell polymerization process, in which the shell portion is prepared first, followed by polymerization of the core monomer in the presence of the shell materials; by attaching preformed shell polymers to the preformed core portion; by grafting polymerization of shell monomers on the core surface, and by dispersing the core polymers in the presence of shell polymers which have affinity for both the core polymers and the solvent medium.

[0021] Ethylenically unsaturated monomers which are used in the core portion of the polymer particles include acrylic monomers, such as acrylic acid, or methacrylic acid, and their alkyl esters such as methyl methacrylate, ethyl methacrylate, butyl methacrylate, ethyl acrylate, butyl acrylate, hexyl acrylate, n-octyl acrylate, lauryl methacrylate, 2-ethylhexyl methacrylate, nonyl acrylate, benzyl methacrylate, the hydroxyalkyl esters of the same acids such as 2-hydroxyethyl acrylate, 2-hydroxyethyl methacrylate, and 2-hydroxypropyl methacrylate, and the nitriles and amides of the same acids such as acrylonitrile, methacrylonitrile, acrylamide and methacrylamide. Other monomers which may be used, either alone or in admixture with these acrylic monomers, include vinyl acetate, vinyl propionate, vinylidene chloride, vinyl chloride, and vinyl aromatic compounds such as styrene, t-butyl styrene and vinyl toluene. Other comonomers which may be used in conjunction with any of the foregoing monomers include dialkyl maleates, dialkyl itaconates, dialkyl methylene-malonates, isoprene, and butadiene.

[0022] Preferred crosslinking and grafting comonomers which may be used, in order to effect crosslinking of the core portion of the polymer particles and grafting of the shell portion to the core portion, are monomers which are polyfunctional with respect to the polymerization reaction, including esters of unsaturated monohydric alcohols with unsaturated monocarboxylic acids, such as allyl methacrylate, allyl acrylate, butenyl acrylate, undecenyl acrylate, undecenyl methacrylate, vinyl acrylate, and vinyl methacrylate, dienes such as butadiene and isoprene, esters of saturated glycols or diols with unsaturated monocarboxylic acids, such as ethylene glycol diacrylate, ethylene glycol dimethacrylate, triethylene glycol dimethacrylate, 1,4-butanediol dimethacrylate, 1,3-butanediol dimethacrylate, and polyfunctional aromatic compounds such as divinyl benzene.

[0023] The core portion of the dispersible particles used in the present invention can be made in the presence of a certain amount of pre-polymers, or functionalized oligomers, or macromonomers, which may include, for example, functionalized organosiloxanes prepared by reactions between organohydrosiloxane and multifunctional unsaturated monomers, fluorine-containing prepolymers, polyester urethanes, polyether urethanes and polyacrylourethanes.

[0024] The core portion of the dispersible particles used in the present invention can be rubbery or glassy at room temperature, that is, the glass transition temperature of the core portion can be higher or lower than room temperature. The core portion can contain one phase or two or more incompatible phases. The incompatibility may be determined in various ways known in the art. The use of scanning electron microscopy using staining techniques to emphasize the differences between the appearance of the phases, for example, is such a technique.

[0025] The shell portion of the dispersible particle used in the present invention is formed from polymers which have affinity with both the core portion of the particle and the solvent medium. The role of such polymers is to keep the particles apart so that the attraction force between the particles become insignificant and the stability of the dispersion is retained during storage and under shear (see, for example, Sato T. in *Journal of Coating Technology*, Vol. 65, No. 825, pages 113 to 121, 1993). The types of polymers that can be used include both homopolymers and copolymers. The copolymers can be random, graft or block copolymers. The shell polymers can be physically attached to the core portion or be chemically attached to the core portion by post polymerization reactions. For example, carboxylic acid groups may be introduced to the core portion through polymerization, and epoxy group-containing monomers may be introduced to the shell portion. The shell polymers are attached to the core portion by ring opening reaction of epoxy groups with carboxylic acid groups. The shell portion can also be introduced by the aforementioned sequential emulsion polymerization process with ethylenically unsaturated monomers. Such monomers may include acrylates including acrylic acid, methacrylates including methacrylic acid, acrylamide and methacrylamide, itoconic acid and its half esters and diesters, styrene including substituted styrenes, acrylonitrile and methacrylonitrile, vinyl acetate, vinyl and vinylidene halides.

[0026] The shell polymer is properly designed to have good compatibility in the solvent medium. Defining compatibility of the shell molecules in the solvent medium can be achieved by using the concept of "polymer solubility map" (see, for example, Ramsbotham, J. in *Progress in Organic Coatings*, Vol 8, Pages 113-141, 1980, and Wicks, Jr. Z. W., Jones, F. N., and Papas, S. P. in *Organic Coatings*, pages 229-239, 1992, John Wiley & Sons, Inc.). The solvents for the practice of the present invention include alcohols, esters, ketones, aromatic hydrocarbons, chlorinated solvents, glycols, and their mixtures.

[0027] The shell portion of the particles used in the present invention may include reactive functional groups capable of forming covalent bonds by intermolecular crosslinking or by reaction with a crosslinking agent. Suitable reactive functional groups include: hydroxyl, carboxyl, carbodiimide, epoxide, aziridine, vinyl sulfone, sulfinic acid, active methylene, amino, amide and allyl.

[0028] The coating composition used in accordance with the invention may also contain suitable crosslinking agents including aldehydes, epoxy compounds, polyfunctional aziridines, vinyl sulfones, methoxyalkyl melamines, triazines,

polyisocyanates, dioxane derivatives such as dihydroxydioxane and carbodiimides. The crosslinking agents may react with functional groups present on the dispersible polymer particle, and/or the solution polymer present in the coating composition.

5 [0029] Matte particles well known in the art may also be used in the coating composition of the invention, such matting agents having been described in Research Disclosure No. 308, published Dec 1989, pages 1008 to 1009. When polymer matte particles are employed, the polymer may contain reactive functional groups capable of forming covalent bonds with the binder polymer by intermolecular crosslinking or by reaction with a crosslinking agent in order to promote improved adhesion of the matte particles to the coated layers. Suitable reactive functional groups include: hydroxyl, carboxyl, carbodiimide, epoxide, aziridine, vinyl sulfone, sulfinic acid, active methylene, amino, amide and allyl.

10 [0030] The coating composition used in the present invention may also include lubricants or combinations of lubricants to reduce sliding friction of the imaging elements in accordance with the invention. Typical lubricants include (1) silicone based materials disclosed, for example, in US Patent Nos. 3,489,567, 3,080,317, 3,042,522, 4,004,927, and 4,047,958, and in British Patent Nos. 955,061 and 1,143,118; (2) higher fatty acids and derivatives, higher alcohols and derivatives, metal salts of higher fatty acids, higher fatty acid esters, higher fatty acid amides, polyhydric alcohol esters of higher fatty acids disclosed in US Patent Nos. 2,454,043, 2,732,305, 2,976,148, 3,206,311, 3,933,516, 2,588,765, 3,121,060, 3,502,473, 3,042,222, and 4,427,964, in British Patent Nos. 1,263,722, 1,198,387, 1,430,997, 1,466,304, 1,320,757, 1,320,565, and 1,320,756, and in German Patent Nos. 1,284,295 and 1,284,294; (3) liquid paraffin and paraffin or wax like materials such as carnauba wax, natural and synthetic waxes, petroleum waxes and mineral waxes; (4) perfluoro- or fluoro- or fluorochloro-containing materials, which include poly(tetrafluoroethylene), poly(trifluorochloroethylene), poly(vinylidene fluoride), poly(trifluorochloroethylene-co-vinyl chloride), poly(meth)acrylates, poly(itaconates), or poly(meth)acrylamides containing perfluoroalkyl side groups. Lubricants useful in the present invention are described in further detail in Research Disclosure No.308, published Dec. 1989, page 1006.

15 [0031] The composition used in the present invention may be applied as solvent coating formulations containing up to 20% total solids by coating methods well known in the art. For example, hopper coating, gravure coating, skim pan/air knife coating, spray coating, and other methods may be used with very satisfactory results. The coatings are dried at temperatures up to 150°C to give dry coating weights of 20 mg/m² to 10 g/m².

20 [0032] In a particularly preferred embodiment, the imaging elements formed by this invention are photographic elements, such as photographic films, photographic papers or photographic glass plates, in which the image-forming layer is a radiation-sensitive silver halide emulsion layer. Such emulsion layers typically comprise a film-forming hydrophilic colloid. The most commonly used of these is gelatin and gelatin is a particularly preferred material for use in this invention. Useful gelatins include alkali-treated gelatin (cattle bone or hide gelatin), acid-treated gelatin (pigskin gelatin) and gelatin derivatives such as acetylated gelatin and phthalated gelatin. Other hydrophilic colloids that can be utilized alone or in combination with gelatin include dextran, gum arabic, zein, casein, pectin, collagen derivatives, collodion, agar-agar, arrowroot and albumin. Still other useful hydrophilic colloids are water-soluble polyvinyl compounds such as polyvinyl alcohol, polyacrylamide and poly(vinylpyrrolidone).

25 [0033] The photographic elements can be simple black-and-white or monochrome elements comprising a support bearing a layer of light-sensitive silver halide emulsion or they can be multilayer and/or multicolor elements.

30 [0034] Color photographic elements typically contain dye image-forming units sensitive to each of the three primary regions of the spectrum. Each unit can be comprised of a single silver halide emulsion layer or of multiple emulsion layers sensitive to a given region of the spectrum. The layers of the element, including the layers of the image-forming units, can be arranged in various orders as is well known in the art.

35 [0035] A preferred photographic element formed by this invention comprises a support bearing at least one blue-sensitive silver halide emulsion layer having associated therewith a yellow image dye-providing material, at least one green-sensitive silver halide emulsion layer having associated therewith a magenta image dye-providing material and at least one red-sensitive silver halide emulsion layer having associated therewith a cyan image dye-providing material.

40 [0036] In addition to emulsion layers, the elements formed by the present invention can contain auxiliary layers conventional in photographic elements, such as overcoat layers, spacer layers, filter layers, interlayers, antihalation layers, pH lowering layers (sometimes referred to as acid layers and neutralizing layers), timing layers, opaque reflecting layers and opaque light-absorbing layers. The support can be any suitable support used with photographic elements. Typical supports include polymeric films, paper (including polymer-coated paper) and glass. Details regarding supports and other layers of the photographic elements of this invention are contained in Research Disclosure, Item 36544, September, 1994.

45 [0037] The light-sensitive silver halide emulsions employed in the photographic elements can include coarse, regular or fine grain silver halide crystals or mixtures thereof and can be comprised of such silver halides as silver chloride, silver bromide, silver bromiodide, silver chlorobromide, silver chloriodide, silver chorobromiodide, and mixtures thereof. The emulsions can be, for example, tabular grain light-sensitive silver halide emulsions. The emulsions can be negative-working or direct positive emulsions. They can form latent images predominantly on the surface of the silver halide grains or in the interior of the silver halide grains. They can be chemically and spectrally sensitized in

accordance with usual practices. The emulsions typically will be gelatin emulsions although other hydrophilic colloids can be used in accordance with usual practice. Details regarding the silver halide emulsions are contained in Research Disclosure, Item 36544, September, 1994, and the references listed therein.

[0038] The photographic silver halide emulsions utilized in this invention can contain other addenda conventional in the photographic art. Useful addenda are described, for example, in Research Disclosure, Item 36544, September, 1994. Useful addenda include spectral sensitizing dyes, desensitizers, antifoggants, masking couplers, DIR couplers, DIR compounds, antistain agents, image dye stabilizers, absorbing materials such as filter dyes and UV absorbers, light-scattering materials, coating aids, plasticizers and lubricants.

[0039] Depending upon the dye-image-providing material employed in the photographic element, it can be incorporated in the silver halide emulsion layer or in a separate layer associated with the emulsion layer. The dye-image-providing material can be any of a number known in the art, such as dye-forming couplers, bleachable dyes, dye developers and redox dye-releasers, and the particular one employed will depend on the nature of the element, and the type of image desired.

[0040] Dye-image-providing materials employed with conventional color materials designed for processing with separate solutions are preferably dye-forming couplers; i.e., compounds which couple with oxidized developing agent to form a dye. Preferred couplers which form cyan dye images are phenols and naphthols. Preferred couplers which form magenta dye images are pyrazolones and pyrazolotriazoles. Preferred couplers which form yellow dye images are benzoylacetanilides and pivalylacetanilides.

[0041] The following examples are intended to illustrate the present invention. However, it should be understood that the invention is not limited to these illustrative examples.

[0042] The examples demonstrate the benefits of coating compositions comprising dispersible polymer particles of the present invention, and in particular show that the coating compositions of the invention have excellent stability against phase separation and flocculation, superior rheological properties for coating at lower wet coverages for high dry coating weight, good optical clarity, good barrier properties, and excellent abrasion resistance.

Preparative Examples 1-6

[0043] Preparative examples 1-6 describe the synthesis of core/shell polymer particles which are dispersible in organic media to form coating compositions useful in this invention.

[0044] A stirred reactor containing 714.3 g of deionized water and 2.7 g of sodium lauryl sulfate was heated to 80 °C and purged with N₂ for 1 hour. After addition of 0.788 g of potassium persulfate, an emulsion containing 130.3 g of deionized water, 153 g of methyl methacrylate, 18 g of ethylene glycol dimethacrylate, 9 g of allyl methacrylate, and 0.25 g of potassium persulfate was slowly added over a period of 1 hour. The reaction was allowed to continue for an additional 2 hours. 0.35 g of benzoyl peroxide in 5 g of toluene was then added to the reactor. An emulsion containing 326.4 g of deionized water, 3.6 g of sodium lauryl sulfate, 108 g of ethyl acrylate, 12 g of methacrylic acid, and 0.15 g of benzoyl peroxide was added continuously for 1 hour. The reaction was allowed to continue for 3 more hours before the reactor was cooled down to room temperature. The latex prepared was filtered through glass fibre to remove any coagulum.

[0045] The latex described above was mixed with acetone at 1:1 ratio to isolate the polymer particles. The precipitate was washed several times with distilled water to remove any residual surfactants and salts. Final drying was in an oven heated to 50 °C. The particles prepared contained about 60% core portion and 40% shell portion. The core contained about 85% methyl methacrylate (MMA), 10% ethylene glycol dimethacrylate (EGD), and 5 % allyl methacrylate (AM). The shell contained about 90% ethyl acrylate (EA) and 10 % methacrylic acid (MA). The resultant polymer particles are designated as p-1.

[0046] Polymer particles p-2 to p-6 were prepared in a similar manner. Their compositions and other parameters are listed in Table 1.

Table 1

Example	Particle	Core/Shell	Diameter(nm)	Core Composition	Shell Composition
Example 1	P-1	60/40	46.2	MMA:EGD:AM =85:10:5	EA:MA=90/10
Example 2	P-2	70/30	38.6	MMA:EGD:AM =85:10:5	MMA:MA=90/10
Example 3	P-3	67/33	48.8	MMA:EGD:AM =90:5:5	MMA=100
Example 4	P-4	67/33	48.1	EA:EGD:AM =90:5:5	MMA=100
Example 5	p-5	67/33	-	MMA:EGD:AM =90:5:5	EA=100
Example 6	p-6	65/35	-	MMA:EGD:AM =85:10:5	MMA:MA=65:35

Preparative Examples 7-25:

[0047] Preparative examples 7-25 describe solvent selection for the formulation of dispersions comprised of core/shell polymer particles dispersed in organic media.

[0048] The polymer particles isolated in Preparative Examples 2 and 4 were tested for their dispersibility in some common solvents used in forming useful layers for photographic materials. The dispersions were made at room temperature at 1% solids. The quality of the dispersions and their stability were assessed by visual appearance. The particles of the present invention are readily dispersible in a range of solvents with very good stability. Table 2 lists examples of solvents which can be used for dispersing p-2 and p-4 particles.

Table 2

Dispersions	solvent system	p-2 particle		p-4 particle	
		dispersion	stability	dispersion	stability
Example 7	diacetone alcohol	y*	good	y	good
Example 8	60/40 methanol/toluene	y	good	y	good
Example 9	80/20 MEK**/ethylene glycol	y	good	y	good
Example 10	90/10 butyrolactone/methanol	y	good	y	good
Example 11	60/40 toluene/methanol	y	good	y	good
Example 12	60/40 toluene/cyclohexanol	y	good	y	good
Example 13	MEK	y	good	y	good
Example 14	25/75 methylene chloride/butyrolactone	y	good	y	good
Example 15	25/75 methylene chloride dioxane	y	good	y	good
Example 16	60/40 cyclohexanol/toluene	y	good	n***	-
Example 17	70/30 butyrolactone ethylene glycol	y	good	n	-
Example 18	80/20 toluene/cyclohexanol	y	good	y	good
Example 19	60/40 THF****/MEK	y	good	y	good
Example 20	toluene	n	-	y	good
Example 21	methylene chloride	n	-	y	good
Example 22	50/50 acetone/methanol	y	good	n	-
Example 23	60/40 methylene chloride dioxane	y	good	y	good
Example 24	60/40 methylene chloride butyrolactone	y	good	y	good
Example 25	70/30 THF/cyclohexane	y	good	y	good

* y = dispersible

** MEK = methyl ethyl ketone

*** n = non-dispersible

**** THF = tetrahydrofuran

Preparative Example 26-34

[0049] Preparative examples 26-34 relate to particle size measurements for polymer particle dispersions useful in this invention.

[0050] The mean size of the dispersed particles was determined by an Ultrafine Particle Sizer. As shown in Table 3, the particles have mean particle sizes in the range of 10 to 60 nm. The small particle size demonstrate that the polymer particles of the present invention are readily dispersed in these solvents and the dispersions are free of large aggregates and clumps (>1 μm) which are detrimental to both manufacturing processes and coating physical properties. On the other hand, the size of the dispersed particles is large enough to ensure good coating rheological properties at high solids.

Table 3

Dispersions	polymer particles	Solvent	Size (nm)
Example 26	p-3	methyl ethyl ketone	40.9
Example 27	p-3	acetone	59.4
Example 28	p-3	methylene chloride	13.3

Table 3 (continued)

Dispersions	polymer particles	Solvent	Size (nm)
Example 29	p-4	methyl ethyl ketone	46.7
Example 30	p-4	acetone	56.2
Example 31	p-4	methylene chloride	19.2
Example 32	p-5	methyl ethyl ketone	47.8
Example 33	p-5	acetone	55.2
Example 34	p-5	methylene chloride	31.3

Preparative Examples 35 -48 and Comparative Sample A

[0051] Preparative examples 35-48 relate to viscosity measurements for polymer particle dispersions useful in this invention while Comparative Sample A relates to viscosity measurements for a solution polymer.

[0052] The viscosity of the particle dispersions was measured by a Brookfield Viscometer at 23 °C and compared to that of Elvacite 2041 (methyl methacrylate polymer sold by E. I. DuPont de Nemours and Co.) in methylene chloride. The concentration of the particles in the various solvents used was 10 vol%. The data are listed in Table 4. These examples demonstrate that the coating compositions comprising dispersible particles have much lower viscosity compared to those comprising solution polymers. These low viscosity coating compositions are excellent for coating delivery, coating filtration, coating application and drying, and organic solvent waste recovery.

Table 4

Dispersions	polymer particles	solvent	viscosity(cps)
Sample A	Elvacite 2041	methylene chloride	47.5
Example 35	p-3	acetone	2.63
Example 36	p-3	MEK	4.13
Example 37	p-3	toluene	15.4
Example 38	p-3	methylene chloride	20
Example 39	p-4	acetone	1.09
Example 40	p-4	MEK	1.71
Example 41	p-4	toluene	3.20
Example 42	p-4	methylene chloride	7.0
Example 43	p-5	acetone	1.38
Example 43	p-5	MEK	2.05
Example 45	p-5	toluene	3.90
Example 46	p-5	methylene chloride	6.72
Example 47	p-5	acetone/methanol 50/50	1.37
Example 48	p-5	acetone/ethanol 50/50	1.34

Invention Examples 49-64 and Comparative Samples B-F

[0053] Examples 49-64 illustrate the resistivity of imaging elements within the scope of the present invention. Comparative Samples B-F relate to similar elements utilizing solution polymers.

[0054] The following examples show that the coating compositions of the present invention provide void-free, impermeable films that are comparable with layers applied using soluble polymers. A polyethylene terephthalate film support that had been subbed with a terpolymer latex of vinylidene chloride, methyl acrylate, and itaconic acid was coated with an aqueous antistatic formulation comprising 0.025 weight % of silver-doped vanadium pentoxide, 0.075 weight % of a terpolymer latex of methylacrylate, vinylidene chloride, and itaconic acid (15/83/2) and dried at 100 °C to yield an antistatic layer having a dry weight of about 8 mg/m². Coating compositions of the invention containing 2, 4, 5, and 10% solids in different organic solvents were applied over the antistatic layer and dried for one minute at 100 °C to yield transparent coatings having a dry weight of 500 to 1000 mg/m². It is known (described in U.S. Patents 5,006,451 and 5,221,598) that the antistatic properties of the vanadium pentoxide layer are destroyed after photographic processing if not protected by an impermeable barrier. Thus the permeability of the example coatings can be evaluated by measuring the antistatic properties of the elements after processing in conventional photographic developing and fixing solutions.

[0055] The elements were soaked in high pH (11.3) developing and fixing solutions as described in U.S. Patent 4,269,929, at 38 °C for 60 seconds each and then rinsed in distilled water. The internal resistivity (using the salt bridge method, described in R. A. Elder, "Resistivity Measurements on Buried Conductive Layers", EOS/ESD Symposium Proceedings, Sept. 1990, pages 251-254.) of the processed elements at 20% relative humidity was measured and compared with the internal resistivity before processing. The coating compositions and results are reported in Table 5.

Table 5

Coatings	Description	Solvent	Resistivity I log Ω/\square	
			Before Process	After Process
Sample B	Elvacite 2041, 500 mg/m ²	methylene chloride	7.1	6.9
Sample C	Elvacite 2041, 1000 mg/m ²	methylene chloride	7.1	7.2
Sample D	Elvacite 2041, 1000 mg/m ²	acetone	7.5	7.5
Sample E	Elvacite 2041, 1000 mg/m ²	methyl ethyl ketone	7.5	7.5
Sample F	Elvacite 2009*, 800 mg/m ²	acetone/methanol 89/11	7.1	7.1
Example 49	p-3, 500 mg/m ²	methylene chloride	7.1	6.8
Example 50	p-3, 1000 mg/m ²	methylene chloride	7.2	7.2
Example 51	p-3/Elvacite 2041 70/30 500 mg/m ²	methylene chloride	7.1	7.2
Example 52	p-3/Elvacite 2041 70/30 1000 mg/m ²	methylene chloride	7.2	6.9
Example 53	p-3, 1000 mg/m ²	acetone	7.8	7.2
Example 54	p-3, 800 mg/m ²	acetone/methanol 89/11	6.9	6.8
Example 55	p-3/NC** 70/30 80 mg/m ²	acetone/methanol 89/11	7.0	6.9
Example 56	p-4, 1000 mg/m ²	acetone	7.5	7.4
Example 57	p-4/Elvacite 2041 75/25 1000 mg/m ²	methyl ethyl ketone	7.7	7.5
Example 58	p-5, 1000 mg/m ²	methylene chloride	7.1	6.8
Example 59	p-5, 1000 mg/m ²	acetone/ethanol 50/50	7.1	6.8
Example 60	p-5, 1000 mg/m ²	acetone/methanol 50/50	7.1	6.7
Example 61	p-5, 1000 mg/m ²	acetone	7.8	7.2
Example 62	p-4/Elvacite 2041 50/50 1000 mg/m ²	acetone	7.8	7.8
Example 63	p-4/Elvacite 2041 75/25 1000 mg/m ²	acetone	7.8	7.6
Example 64	p-2/PFAZ322***, 800 mg/m ²	acetone/methanol 89/11	7.1	7.1

* Elvacite 2009: methyl methacrylate polymer sold by E. I. DuPont de Nemours and Co.

** NC: Nitrocellulose, R.S. 1/2 second

*** PFAZ322: polyfunctional aziridine, (Sybron Chemicals Inc.) added at 10 wt% of solids.

[0056] The results reported in Table 5 demonstrate that the coating compositions for examples 49-64 of the present invention have permanency of the antistatic properties comparable to that obtained from samples B-F which are polymer solution applied protective overcoats (Elvacite 2041 and 2009).

Invention Examples 65-68 and Comparative Samples G-H

[0057] The following examples demonstrate the excellent physical properties that are obtained with the coating compositions of the present invention. Coating formulations in methylene chloride comprising 1.25 to 4.0 wt% total solids were applied onto polyethylene terephthalate film support that had been subbed with a terpolymer latex of vinylidene chloride, methyl acrylate, and itaconic acid. The coatings were dried at 100 °C for one minute to give transparent films with a dry coating weight of 650 and 1300 mg/m². Taber abrasion values for the coatings were measured and compared with those for Elvacite 2041 coated from methylene chloride solutions at dry coating weights of 650 and 1300 mg/m², respectively. The Taber abrasion tests were performed in accordance with the procedures set forth in ASTM D1044. The results are given in Table 6.

Table 6

Coating	Description	Taber Abrasion (% haze)
Sample G	Elvacite 2041 650 mg/m ²	12.2
Sample H	Elvacite 2041 1300 mg/m ²	10.7

Table 6 (continued)

Coating	Description	Taber Abrasion (% haze)
Example 65	p-4 650 mg/m ²	11.0
Example 66	p-4 1300 mg/m ²	10.6
Example 67	p-4/Elvacite 2041 70/30 650 mg/m ²	10.3
Example 68	p-4/Elvacite 2041 70/30 1300 mg/m ²	9.6

Invention Examples 69 - 71

[0058] The following examples demonstrate the utility of the dispersible polymers as binders for conductive metal oxides and conductive polymers in antistatic coating compositions. The antistatic coating compositions were coated onto subbed polyethylene terephthalate support and dried at 80 °C. The conductive material used in Example 69 was the conductive metal antimonate (ZnSb₂O₆) described in U.S. Patent No. 5,368,995 and was supplied by Nissan Chemical Industries, Inc. The conductive polymer in Examples 70 and 71 was the crosslinked vinylbenzyl quaternary ammonium polymer described in U.S. Patent No. 4,070,189. The surface resistivities of the coatings were measured with a two-point probe at 50% relative humidity. The results are listed in Table 7.

Table 7

Example	Binder	Conductive Material	Surface Resistivity log Ω/□
69	p-4/160mg/m ²	ZnSb ₂ O ₆	9.3
70	1/1p-4/nitrocellulose/175mg/m ²	polyvinylbenzyl-ammonium chloride	7.1
71	p-4/175mg/m ²	polyvinylbenzyl-ammonium chloride	7.3

[0059] As shown by the above examples, the coating compositions employed in this invention, namely compositions comprising a liquid organic medium as a continuous phase and core/shell polymer particles as a disperse phase, are capable of forming a continuous film under rapid drying conditions such as are typically utilized in the manufacture of imaging elements. Any of a wide variety of auxiliary layers commonly incorporated in imaging elements can be improved in performance characteristics by use of the dispersed core/shell particles.

Claims

1. A method of forming an imaging element for use in an image-forming process; said imaging element comprising a support, an image-forming layer and an auxiliary layer; the method comprising coating said auxiliary layer from a dispersion of polymer particles in a continuous liquid organic medium; characterized in that said polymer particles comprise a core portion which is insoluble in said organic medium and a shell portion which is physically or chemically attached to the core portion, and the shell portion is dispersible in said organic medium; wherein said continuous liquid organic medium is selected from the group consisting of alcohols, esters, ketones, aromatic hydrocarbons, chlorinated solvents, glycols and mixtures thereof; wherein said shell polymer particles are formed by polymerization of ethylenically unsaturated monomers selected from the group consisting of acrylic acid, methacrylic acid, acrylamide, methacrylamide, itaconic acid and its half esters and diesters, styrene and substituted styrenes, acrylonitrile, methacrylonitrile, vinyl acetate, vinyl and vinylidene halides, and mixtures thereof; and wherein the core polymer is formed by polymerizing monomers selected from the group consisting of acrylic acid, methacrylic acid, methyl methacrylate, ethyl methacrylate, butyl methacrylate, ethyl acrylate, butyl acrylate, hexyl acrylate, n-octyl acrylate, lauryl methacrylate, 2-ethylhexyl methacrylate, nonylacrylate, benzyl methacrylate, 2-hydroxyethyl acrylate, 2-hydroxyethyl methacrylate, and 2-hydroxypropyl methacrylate, acrylonitrile, methacrylonitrile, acrylamide, methacrylamide, vinyl acetate, vinyl propionate, vinylidene chloride, vinyl chloride, styrene, t-butyl styrene, vinyl toluene, dialkyl maleates, dialkyl itaconates, dialkyl methylene-malonates, isoprene, butadiene and mixtures thereof.
2. A method as claimed in claim 1, wherein said element is a photographic element.
3. A method as claimed in claims 1 or 2, wherein said auxiliary layer is a subbing layer, backing layer, interlayer, overcoat layer, receiving layer, barrier layer, stripping layer, mordanting layer, scavenger layer, antikinking layer

or transparent magnetic layer.

4. A method as claimed in any of claims 1 to 3, wherein said image-forming layer is a silver halide emulsion layer.
- 5 5. A method as claimed in any of claims 1 to 4, wherein the weight ratio of the core portion to the shell portion of said polymer particles is 75:25 to 50:50.
6. A method as claimed in any of claims 1 to 5, wherein the core portion of said polymer particles has a mean particle size of 10 to 200 nm.
- 10 7. A method as claimed in any of claims 1 to 5, wherein said auxiliary layer comprises a mixture of polymer particles having a glassy core and polymer particles having a rubbery core.
8. A method as claimed in claim 1, wherein said dispersion of polymer particles contains up to 50 percent by weight of solution polymer.
- 15 9. A method as claimed in claim 1, wherein said polymer particles are composed of a core portion which is crosslinked by a crosslinking agent and a shell portion which is grafted to said core portion by covalent bonding.
- 20 10. A method as claimed in claim 1, wherein said dispersion includes a crosslinking agent.

Patentansprüche

- 25 1. Verfahren zur Herstellung eines Bildaufzeichnungs-Elementes für die Verwendung in einem Bildaufzeichnungs-Verfahren, wobei das Bildaufzeichnungs-Element einen Träger, eine, ein Bild erzeugende Schicht und eine Hilfsschicht aufweist, wobei das Verfahren umfaßt das Auftragen der Hilfsschicht aus einer Dispersion von Polymer-Teilchen in einem kontinuierlichen, flüssigen, organischen Medium; dadurch **gekennzeichnet**, daß
 - 30 die Polymer-Teilchen einen Kernteil aufweisen, der in dem organischen Medium unlöslich ist, und einen Hüllenteil, der physikalisch oder chemisch an den Kernteil gebunden ist, wobei der Hüllenteil in dem organischen Medium dispergierbar ist; worin das kontinuierliche, flüssige, organische Medium ausgewählt ist aus der Gruppe bestehend aus Alkoholen, Estern, Ketonen, aromatischen Kohlenwasserstoffen, chlorierten Lösungsmitteln, Glykolen und Mischungen hiervon; worin die Hüllen-Polymer-Teilchen erzeugt werden durch Polymerisation von ethylenisch ungesättigten Monomeren, ausgewählt aus der Gruppe bestehend aus Acrylsäure, Methacrylsäure, Acrylamid, Methacrylamid, Itaconsäure und ihren Halbestern und Diestern, Styrol und substituierten Styrolen, Acrylonitril, Methacrylonitril, Vinylacetat, Vinyl- und Vinylidenhalogeniden und Mischungen hiervon; und worin das Kern-Polymer erzeugt wird durch Polymerisation von Monomeren, ausgewählt aus der Gruppe bestehend aus Acrylsäure, Methacrylsäure, Methylmethacrylat, Ethylmethacrylat, Butylmethacrylat, Ethylacrylat, Butylacrylat, Hexylacrylat, n-Octylacrylat, Laurylmethacrylat, 2-Ethylhexylmethacrylat, Nonylacrylat, Benzylmethacrylat, 2-Hydroxyethylacrylat, 2-Hydroxyethylmethacrylat und 2-Hydroxypropylmethacrylat, Acrylonitril, Methacrylonitril, Acrylamid, Methacrylamid, Vinylacetat, Vinylpropionat, Vinylidenchlorid, Vinylchlorid, Styrol, t-Butylstyrol, Vinyltoluol, Dialkylmaleaten, Dialkylitaconaten, Dialkylmethylen-malonaten, Isopren, Butadien und Mischungen hiervon.
- 45 2. Verfahren nach Anspruch 1, worin das Element ein fotografisches Element ist.
3. Verfahren nach den Ansprüchen 1 oder 2, worin die Hilfsschicht eine die Haftung verbessernde Schicht ist, eine Rückschicht, Zwischenschicht, Deckschicht, Empfangsschicht, Trennschicht, Abstreifschicht, Beizmittelschicht, Abfangschicht, Anti-Knickschicht oder eine transparente, magnetische Schicht.
- 50 4. Verfahren nach einem der Ansprüche 1 bis 3, worin die Bild-erzeugende Schicht eine Silberhalogenid-Emulsionsschicht ist.
- 55 5. Verfahren nach einem der Ansprüche 1 bis 4, worin das Gewichtsverhältnis des Kernteiles zum Hüllenteil der Polymer-Teilchen bei 75:25 bis 50:50 liegt.
6. Verfahren nach einem der Ansprüche 1 bis 5, worin der Kernteil der Polymer-Teilchen eine mittlere Teilchengröße von 10 bis 200 nm hat.

7. Verfahren nach einem der Ansprüche 1 bis 5, worin die Hilfsschicht eine Mischung aus Polymer-Teilchen mit einem glasartigen Kern und Polymer-Teilchen mit einem gummiartigen Kern umfaßt.
- 5 8. Verfahren nach Anspruch 1, worin die Dispersion von Polymer-Teilchen bis zu 50 Gew.-% Lösungs-Polymer umfaßt.
9. Verfahren nach Anspruch 1, worin die Polymer-Teilchen bestehen aus einem Kernteil, der durch ein Quer-Vernetzungsmittel quer-venetzt ist, und einem Hüllenteil, der durch kovalente Bindung auf den Kernteil aufgepfropft ist.
- 10 10. Verfahren nach Anspruch 1, worin die Dispersion ein Quer-Vernetzungsmittel enthält.

Revendications

- 15 1. Procédé de formation d'un élément formateur d'image utilisé dans un procédé de formation d'image ; ledit élément formateur d'image comprenant un support, une couche formatrice d'image et une couche auxiliaire ; ledit procédé comprenant le couchage de ladite couche auxiliaire à partir d'une dispersion de particules de polymères dans un milieu organique liquide continu et
- 20 caractérisé en ce que lesdites particules de polymères comprennent un coeur insoluble dans ledit milieu organique et une coque physiquement ou chimiquement liée au coeur et où la coque est dispersible dans ledit milieu organique ; ledit milieu organique liquide continu est choisi parmi le groupe comprenant les alcools, les esters, les cétones, les hydrocarbures aromatiques, les solvants chlorés, les glycols et leurs mélanges ; lesdites particules de polymères formant la coque sont préparées par polymérisation de monomères éthyléniquement insaturés choisis parmi le groupe comprenant l'acide acrylique, l'acide méthacrylique, l'acrylamide, le méthacrylamide, l'acide itaconique et ses demi-esters et diesters, le styrène et les styrènes substitués, l'acrylonitrile, le méthacrylonitrile, l'acétate de vinyle, les halogénures de vinyle et de vinylidène et leurs mélanges ; le polymère du coeur est formé en polymérisant des monomères choisis parmi le groupe comprenant l'acide acrylique, l'acide méthacrylique, le méthacrylate de méthyle, le méthacrylate d'éthyle, le méthacrylate de butyle, l'acrylate d'éthyle, l'acrylate de butyle, l'acrylate d'hexyle, l'acrylate de n-octyle, le méthacrylate de lauryle, le méthacrylate de 2-éthylhexyle, l'acrylate de nonyle, le méthacrylate de benzyle, l'acrylate de 2-hydroxyéthyle, le méthacrylate de 2-hydroxyéthyle et le méthacrylate de 2-hydroxypropyle, l'acrylonitrile, le méthacrylonitrile, l'acrylamide, le méthacrylamide, l'acétate de vinyle, le propionate de vinyle, le chlorure de vinylidène, le chlorure de vinyle, le styrène, le t-butyl styrène, le vinyl toluène, les maléates de dialkyle, les itaconates de dialkyle, les dialkyl-méthylène malonates, l'isoprène, le butadiène et leurs mélanges.
- 25 35 2. Procédé selon la revendication 1, dans lequel ledit élément est un élément photographique.
3. Procédé selon les revendications 1 ou 2, dans lequel ladite couche auxiliaire est une couche substratante, une couche dorsale, une intercouche, une surcouche, une couche réceptrice, une couche barrière, une couche de pelliculage, une couche de mordantage, une couche d'immobilisation du développeur oxydé, une couche limitant la sensibilisation à la pression ou une couche magnétique transparente.
- 40 4. Procédé selon l'une quelconque des revendications 1 à 3, dans lequel ladite couche formatrice d'image est une couche d'émulsion aux halogénures d'argent.
- 45 5. Procédé selon l'une quelconque des revendications 1 à 4, dans lequel le rapport en poids du coeur à la coque desdites particules de polymères est compris entre 75:25 et 50:50.
- 50 6. Procédé selon l'une quelconque des revendications 1 à 5, dans lequel lesdites particules de polymères formant le coeur ont une taille moyenne de particules comprise entre 10 et 200 nm.
7. Procédé selon l'une quelconque des revendications 1 à 5, dans lequel ladite couche auxiliaire comprend un mélange de particules de polymères ayant un coeur vitreux et de particules de polymères ayant un coeur caoutchouteux.
- 55 8. Procédé selon la revendication 1, dans lequel ladite dispersion de particules de polymères contient jusqu'à 50% en poids de polymère en solution.

EP 0 749 039 B1

9. Procédé selon la revendication 1, dans lequel lesdites particules de polymères sont composées d'un coeur réticulé au moyen d'un agent réticulant et d'une coque greffée sur ledit coeur par liaison covalente.
10. Procédé selon la revendication 1, dans lequel ladite dispersion comprend un agent réticulant.

5

10

15

20

25

30

35

40

45

50

55