

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2011325913 B2

(54) Title
Wide area positioning system

(51) International Patent Classification(s)
G01C 9/00 (2006.01) **G01R 5/08** (2006.01)

(21) Application No: **2011325913** (22) Date of Filing: **2011.11.14**

(87) WIPO No: **WO12/065184**

(30) Priority Data

(31) Number **61/413,170** (32) Date **2010.11.12** (33) Country **US**

(43) Publication Date: **2012.05.18**
(44) Accepted Journal Date: **2015.08.20**

(71) Applicant(s)
NextNav, LLC

(72) Inventor(s)
Wolf, Tom;Raghupathy, Arun;Sendonaris, Andrew;Meiyappan, Subramanian;Pattabiraman, Ganesh;Tang, Haochen;Vajjhala, Prasad;Singh, Rajendra

(74) Agent / Attorney
Spruson & Ferguson, L 35 St Martins Tower 31 Market St, Sydney, NSW, 2000

(56) Related Art
US 2005/0176441
WO 00/058744
US 2009/0286556
US 2010/0073229
US 5,65,592
US 2007/0016346
US 6,518,918

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 May 2012 (18.05.2012)

(10) International Publication Number
WO 2012/065184 A3

(51) International Patent Classification:
G01C 9/00 (2006.01)

Oakmead Parkway, Sunnyvale, CA 94085 (US). **PATTABIRAMAN, Ganesh** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **TANG, Haochen** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **VAJJHALA, Prasad** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **SINGH, Rajendra** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US).

(21) International Application Number:
PCT/US2011/060655

(74) Agents: **GREGORY, Richard, L.** et al.; Gregory & Sawrie LLP, 2018 Bissonnet Street, Houston, TX 77005 (US).

(22) International Filing Date:
14 November 2011 (14.11.2011)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, IIR, IIU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PII, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
61/413,170 12 November 2010 (12.11.2010) US

(71) Applicant (for all designated States except US): **NEXT-NAV, LLC** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WOLF, Tom** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **RAGHUPATHY, Arun** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **SENDONARIS, Andrew** [US/US]; 484 Oakmead Parkway, Sunnyvale, CA 94085 (US). **MEIYAPPAN, Subramanian** [US/US]; 484

[Continued on next page]

(54) Title: WIDE AREA POSITIONING SYSTEM




FIG. 28

(57) Abstract: Positioning systems and methods comprise a network of transmitters that broadcast positioning signals comprising ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. A reference sensor array comprising at least one reference sensor unit is positioned at a known location. A remote receiver includes an atmospheric sensor collecting atmospheric data at a position of the remote receiver. A positioning application is coupled to the remote receiver and generates a reference pressure estimate at the position of the remote receiver using the atmospheric and reference data from the reference sensor array. The positioning application computes the position of the remote receiver using the reference pressure estimate and information derived from at least one of the positioning signals and satellite signals that are signals of a satellite-based positioning system. The position includes an elevation.



(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:
5 July 2012

UNITED STATES PATENT APPLICATION
FOR
WIDE AREA POSITIONING SYSTEM

5

10

15 RELATED APPLICATIONS

This application claims the benefit of United States (US) Patent Application Number 61/413,170, filed November 12, 2010.

This application is a continuation in part of US Patent Application Number 12/557,479, filed September 10, 2009.

20

TECHNICAL FIELD

The disclosure herein relates generally to positioning systems. In particular, this disclosure relates to a wide area positioning system.

25 BACKGROUND

Positioning systems like Global Positioning System (GPS) have been in use for many years. In poor signal conditions, however, these conventional positioning system can have degraded performance.

30 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram of a wide area positioning system, under an embodiment.

Figure 2 is a block diagram of a synchronized beacon, under an embodiment.

Figure 3 is a block diagram of a positioning system using a repeater configuration, under an embodiment.

Figure 4 is a block diagram of a positioning system using a repeater configuration, under an alternative embodiment.

5 **Figure 5** shows tower synchronization, under an embodiment.

Figure 6 is a block diagram of a GPS disciplined PPS generator, under an embodiment.

Figure 7 is a GPS disciplined oscillator, under an embodiment.

10 **Figure 8** shows a signal diagram for counting the time difference between the PPS and the signal that enables the analog sections of the transmitter to transmit the data, under an embodiment.

Figure 9 is a block diagram of the differential WAPS system, under an embodiment.

Figure 10 shows common view time transfer, under an embodiment.

15 **Figure 11** shows the two-way time transfer, under an embodiment.

Figure 12 is a block diagram of a receiver unit, under an embodiment.

Figure 13 is a block diagram of an RF module, under an embodiment.

Figure 14 shows signal upconversion and/or downconversion, under an embodiment.

20 **Figure 15** is a block diagram of a receiver system having multiple receive chains in which one of the receive chains can be used temporarily for receiving and processing WAPS signals, under an embodiment.

Figure 16 is a block diagram showing clock sharing in a positioning system, under an embodiment.

25 **Figure 17** is a block diagram of assistance transfer from WAPS to GNSS receiver, under an embodiment.

Figure 18 is a block diagram showing transfer of aiding information from the GNSS receiver to the WAPS receiver, under an embodiment.

30 **Figure 19** is an example configuration in which WAPS assistance information is provided from a WAPS server, under an embodiment.

Figure 20 is a flow diagram for estimating an earliest arriving path in $h[n]$, under an embodiment.

Figure 21 is a flow diagram for estimating reference correlation function, under an embodiment.

5 **Figure 22** is a flow diagram for estimating noise sub-space, under an embodiment.

Figure 23 is a flow diagram for estimating noise sub-space, under an alternative embodiment.

Figure 24 is a flow diagram for estimating noise sub-space, under another alternative embodiment.

10 **Figure 25** is a flow diagram for estimating noise sub-space, under yet another alternative embodiment.

Figure 26 is a flow diagram for estimating noise sub-space, under still another alternative embodiment.

15 **Figure 27** is a block diagram of a reference elevation pressure system, under an embodiment.

Figure 28 is a block diagram of the WAPS integrating the reference elevation pressure system, under an embodiment.

Figure 29 is a block diagram of hybrid position estimation using range measurements from various systems, under an embodiment.

20 **Figure 30** is a block diagram of hybrid position estimation using position estimates from various systems, under an embodiment.

Figure 31 is a block diagram of hybrid position estimation using a combination of range and position estimates from various systems, under an embodiment.

25 **Figure 32** is a flow diagram for determining a hybrid position solution in which position/velocity estimates from the WAPS/GNSS systems are fed back to help calibrate the drifting bias of the sensors at times when the quality of the GNSS/WAPS position and/or velocity estimates are good, under an embodiment.

Figure 33 is a flow diagram for determining a hybrid position solution in which sensor parameters (such as bias, scale and drift) are estimated as part of the

position/velocity computation in the GNSS and/or WAPS units without need for explicit feedback, under an embodiment.

5 **Figure 34** is a flow diagram for determining a hybrid position solution in which sensor calibration is separated from the individual position computation units, under an embodiment.

Figure 35 is a flow diagram for determining a hybrid position solution in which the sensor parameter estimation is done as part of the state of the individual position computation units, under an embodiment.

10 **Figure 36** shows the exchange of information between the WAPS and other systems, under an embodiment.

Figure 37 is a block diagram showing exchange of location, frequency and time estimates between FM receiver and WAPS receiver, under an embodiment.

15 **Figure 38** is a block diagram showing exchange of location, time and frequency estimates between WLAN/BT transceiver and WAPS Receiver, under an embodiment.

Figure 39 is a block diagram showing exchange of location, time and frequency estimates between cellular transceiver and WAPS receiver, under an embodiment.

Figure 40 shows a parallel complex correlator architecture, under an embodiment.

20 **Figure 41** shows a 32-bit shift register implementation derived from two 16-bit shift register primitives with parallel random access read capabilities, under an embodiment.

Figure 42 shows shift operation and readout operation rate, under an embodiment.

Figure 43 shows a structure for an adder tree that implements a 1023 x n-bit adder, under an embodiment.

Figure 44 is a block diagram of session key setup, under an embodiment.

25 **Figure 45** is a flow diagram for encryption, under an embodiment.

Figure 46 is a block diagram of the security architecture for encryption, under an alternative embodiment.

DETAILED DESCRIPTION

Systems and methods are described for determining position of a receiver. The positioning system of an embodiment comprises a transmitter network including transmitters that broadcast positioning signals. The positioning system comprises a remote receiver that acquires and tracks the positioning signals and/or satellite signals. The 5 satellite signals are signals of a satellite-based positioning system. A first mode of the remote receiver uses terminal-based positioning in which the remote receiver computes a position using the positioning signals and/or the satellite signals. The positioning system comprises a server coupled to the remote receiver. A second operating mode of the remote 10 receiver comprises network-based positioning in which the server computes a position of the remote receiver from the positioning signals and/or satellite signals, where the remote receiver receives and transfers to the server the positioning signals and/or satellite signals.

A method of determining position of an embodiment comprises receiving at a remote receiver at least one of positioning signals and satellite signals. The positioning 15 signals are received from a transmitter network comprising a plurality of transmitters. The satellite signals are received from a satellite-based positioning system. The method comprises determining a position of the remote receiver using one of terminal-based positioning and network-based positioning. The terminal-based positioning comprises computing a position of the remote receiver at the remote receiver using at least one of the 20 positioning signals and the satellite signals. The network-based positioning comprises computing a position of the remote receiver at a remote server using at least one of the positioning signals and the satellite signals.

In the following description, numerous specific details are introduced to provide a thorough understanding of, and enabling description for, the systems and methods 25 described. One skilled in the relevant art, however, will recognize that these embodiments can be practiced without one or more of the specific details, or with other components, systems, etc. In other instances, well-known structures or operations are not shown, or are not described in detail, to avoid obscuring aspects of the disclosed embodiments.

Figure 1 is a block diagram of a positioning system, under an embodiment. The 30 positioning system, also referred to herein as the wide area positioning system (WAPS), or

“system”, includes a network of synchronized beacons, receiver units that acquire and track the beacons and/or Global Positioning System (GPS) satellites (and optionally have a location computation engine), and a server that comprises an index of the towers, a billing interface, a proprietary encryption algorithm (and optionally a location computation engine). The system operates in the licensed/unlicensed bands of operation and transmits a proprietary waveform for the purposes of location and navigation purposes. The WAPS system can be used in conjunction with other positioning systems for better location solution or the WAPS system can be used to aid other positioning systems. In the context of this document, a positioning system is one that localizes one or more of latitude, longitude and altitude coordinates.

In this document, whenever the ‘GPS’ is referred to, it is done so in the broader sense of GNSS (Global Navigation Satellite System) which may include other existing satellite positioning systems such as Glonass as well as future positioning systems such as Galileo and Compass/Beidou.

15 **Figure 2** is a block diagram of a synchronized beacon, under an embodiment. The synchronized beacons of an embodiment, also referred to herein as beacons, form a CDMA network, and each beacon transmits a Pseudo Random Number (PRN) sequence with good cross-correlation properties such as a Gold Code sequence with a data stream of assistance data. Alternatively, the sequences from each beacon transmitter can be
20 staggered in time into separate slots in a TDMA format.

In a terrestrial positioning system, one of the main challenges to overcome is the near-far problem wherein, at the receiver, a far-away transmitter will get jammed by a nearby transmitter. To address this issue, beacons of an embodiment use a combination of CDMA and TDMA techniques in which local transmitters can use separate slots (TDMA)
25 (and optionally different codes (CDMA)) to alleviate the near-far problem. Transmitters further afield would be allowed to use the same TDMA slots while using different CDMA codes. This allows wide-area scalability of the system. The TDMA slotting can be deterministic for guaranteed near-far performance or randomized to provide good average near-far performance. The carrier signal can also be offset by some number of hertz (for
30 example, a fraction of the Gold code repeat frequency) to improve cross-correlation

performance of the codes to address any 'near-far' issues. When two towers use the same TDMA slot but different codes, the cross-correlation in the receiver can be further rejected by using interference cancellation of the stronger signal before detecting the weaker signal.

Another important parameter in the TDMA system is the TDMA slotting period 5 (also called a TDMA frame). Specifically, in the WAPS system, the TDMA frame duration is time period between two consecutive slots of the same transmitter. The TDMA frame duration is determined by the product of the number of transmitter slots required for positioning in the coverage area and the TDMA slot duration. The TDMA slot duration is determined by the sensitivity requirements, though sensitivity is not necessarily limited by 10 a single TDMA slot. One example configuration may use 1 second as the TDMA frame duration and 100ms as the TDMA slot duration.

Additionally, the beacons of an embodiment can use a preamble including assistance data or information can be used for channel estimation and Forward Error Detection and/or Correction to help make the data robust. The assistance data of an 15 embodiment includes, but is not limited to, one or more of the following: precise system time at either the rising or falling edge of a pulse of the waveform; Geocode data (Latitude, Longitude and Altitude) of the towers; geocode information about adjacent towers and index of the sequence used by various transmitters in the area; clock timing corrections for the transmitter (optional) and neighboring transmitters; local atmospheric corrections 20 (optional); relationship of WAPS timing to GNSS time (optional); indication of urban, semi-urban, rural environment to aid the receiver in pseudorange resolution (optional); and, offset from base index of the PN sequence or the index to the Gold code sequence. In the transmit data frame that is broadcast, a field may be included that includes information to disable a single or a set of receivers for safety and/or license management reasons.

25 The transmit waveform timing of the transmissions from the different beacons and towers of an embodiment are synchronized to a common timing reference. Alternatively, the timing difference between the transmissions from different towers should be known and transmitted. The assistance data is repeated at an interval determined by the number and size of the data blocks, with the exception of the timing message which will be 30 incremented at regular intervals. The assistance data maybe encrypted using a proprietary

encryption algorithm, as described in detail herein. The spreading code may also be encrypted for additional security. The signal is up-converted and broadcast at the predefined frequency. The end-to-end delay in the transmitter is accurately calibrated to ensure that the differential delay between the beacons is less than approximately 3
5 nanoseconds. Using a differential WAPS receiver at a surveyed location listening to a set of transmitters, relative clock corrections for transmitters in that set can be found.

The tower arrangement of an embodiment is optimized for coverage and location accuracy. The deployment of the towers will be arranged in such a way as to receive signals from 3 or more towers in most of the locations within the network and at the edge of the
10 network, such that the geometric dilution of precision (GDOP) in each of these locations is less than a predetermined threshold based on the accuracy requirement. Software programs that do RF planning studies will be augmented to include the analysis for GDOP in and around the network. GDOP is a function of receiver position and transmitter positions. One method of incorporating the GDOP in the network planning is to set up an
15 optimization as follows. Function to be minimized is volume integral of the square of GDOP over the coverage volume. The volume integration is with respect to the (x, y, z) coordinates of the receiver position. The minimization is with respect to the n transmitter position coordinates $(x_1, y_1, z_1), (x_2, y_2, z_2), \dots (x_n, y_n, z_n)$ in a given coverage area subject to the constraints that they are in the coverage volume: $x_{min} < x < x_{max}$,
20 $y_{min} < y < y_{max}$, $z_{min} < z < z_{max}$ for $i = 1, \dots, n$ with x_{min} , y_{min} and z_{min} being the lower limits and with x_{max} , y_{max} and z_{max} being the upper limits of the coverage volume. The function to be minimized can be written as

$$f(x_i, y_i, z_i; i = 1, 2, \dots, n) = \iiint_{x \in (x_l, x_u), y \in (y_l, y_u), z \in (z_l, z_u)} GDOP^2(x, y, z, x_i, y_i, z_i; i = 1, 2, \dots, n)$$

Additionally, the function to be minimized may be weighted according to the importance (i.e. performance quality required) of the coverage region R_j .

$$f(x_i, y_i, z_i; i = 1, 2, \dots, n) = \sum_j W_j \iiint_{x, y, z \in R_j} GDOP^2(x, y, z, x_i, y_i, z_i; i = 1, 2, \dots, n)$$

An additional constraint on the tower coordinate locations can be based on location of already available towers in the given area. The coordinatization of all coordinates can typically be done in local level coordinate system with average east as positive x, average north as positive y and average vertical up as positive z. The software which solves the 5 above constrained minimization problem will output optimized transmitter positions $(x_1, y_1, z_1), (x_2, y_2, z_2), \dots (x_n, y_n, z_n)$ that would minimize the function f .

$$\arg \min_{x_i, y_i, z_i; i=1, 2, \dots, n} (f(x_i, y_i, z_i; i = 1, 2, \dots, n))$$

This technique can be applied for both wide area networks (like in a city) or in a local deployment (like in a mall). In one example configuration, the network of transmitters is separated by a distance of approximately 30 km in a triangular/hexagonal 10 arrangement around each metropolitan area. Each tower can radiate via a corresponding antenna up to a maximum power in a range of approximately 20W to 1 kW EIRP. In another embodiment, the towers can be localized and can transmit at power levels as low as 1W. The frequency bands of operation include any licensed or unlicensed band in the radio spectrum. The transmit antenna of an embodiment includes an omni-directional antenna, 15 or multiple antennas/arrays that can help with diversity, sectoring etc.

Adjacent towers are differentiated by using different sequences with good cross-correlation properties to transmit or alternatively to transmit the same sequences at different times. These differentiation techniques can be combined and applied to only a given geographical area. For instance the same sequences could be reused over the 20 networks in a different geographical area.

Local towers can be placed in a given geographical area to augment the wide area network towers of an embodiment. The local towers, when used, can improve the accuracy of the positioning. The local towers may be deployed in a campus like environment or, for public safety needs, separated by a distance in a range of few 10s of meters up to a few 25 kilometers.

The towers will preferably be placed on a diversity of heights (rather than on similar heights) to facilitate a better quality altitude estimate from the position solution. In addition to transmitters at different latitude/longitude having different heights, another method to add height diversity to the towers is to have multiple WAPS transmitters (using

different code sequences) on the same physical tower (with identical latitude and longitude) at different heights. Note that the different code sequences on the same physical tower can use the same slots, because transmitters on the same tower do not cause a near-far problem.

5 WAPS transmitters can be placed on pre-existing or new towers used for one or more other systems (such as cellular towers). WAPS transmitter deployment costs can be minimized by sharing the same physical tower or location.

In order to improve performance in a localized area (such as, for example, a warehouse or mall), additional towers can be placed in that area to augment the transmitters

10 used for wide area coverage. Alternatively, to lower costs of installing full transmitters, repeaters can be placed in the area of interest.

Note that the transmit beacon signals used for positioning discussed above need not be transmitters built exclusively for WAPS, but can be signals from any other system which are originally synchronized in time or systems for which synchronization is

15 augmented through additional timing modules. Alternately, the signals can be from systems whose relative synchronization can be determined through a reference receiver. These systems can be, for example, already deployed or newly deployed with additional synchronization capability. Examples of such systems can be broadcast systems such as digital and analog TV or MediaFlo.

20 When the WAPS network is configured, some transmit locations may be better than some others in the network (height of the beacon above clutter, power levels) either determined by design or by field measurements. Such beacons can be identified to the receivers either directly or indirectly or by encoding data bits which indicate the "quality" of the beacon which the receivers can then use to weight the signal received from such

25 beacons.

Figure 3 is a block diagram of a positioning system using a repeater configuration, under an embodiment. The repeater configuration comprises the following components:

- 1) A common WAPS receive antenna (Antenna 1)
- 2) An RF power amplifier and a splitter/switch connects to various WAPS

30 transmitter antennas (Local Antennas 1-4).

3) WAPS User Receiver

Antennal receives, amplifies and distributes (switches) the composite signal to Local Antennas 1-4. The switching should be done (preferably) in a manner such that there is no overlap (collision) of transmissions from different repeaters at the user receiver.

5 Collision of transmissions can be avoided through the use of guard intervals. The known cable delays from the switch to the transmit antenna should be compensated either by adding delays at the repeater-amplifier-transmitter to equalize the overall delay for all local repeaters or by adjusting the estimated time of arrival from a particular repeater by the cable delay at the user-receiver. When TDMA is used in the wide area WAPS network, the

10 repeater slot switching rate is chosen such that each wide area slot (each slot will contain one wide area WAPS tower) occurs in all repeater slots. One example configuration would use the repeater slot duration equal to a multiple of the wide area TDMA frame duration. Specifically, if the wide area TDMA frame is 1 second, then the repeater slots can be integer seconds. This configuration is the simplest, but is suitable only for deployment in a

15 small, limited area because of requirement of RF signal distribution on cables. The user WAPS receiver uses time-difference of arrival when listening to repeater towers to compute position and works under a static (or quasi static) assumption during the repeater slotting period. The fact that the transmission is from a repeater can be detected automatically by the fact that each WAPS tower signal shows the same timing difference

20 (jump) from one repeater slot to the next one.

Figure 4 is a block diagram of a positioning system using a repeater configuration, under an alternative embodiment. In this configuration each repeater comprises a WAPS repeater-receiver and an associated coverage-augmentation WAPS transmitter with local antenna (which can be indoors, for example). The WAPS repeater receiver should be able

25 to extract WAPS system timing information as well as WAPS data stream corresponding to one wide area WAPS transmitter. The WAPS system timing and data corresponding to one wide area WAPS transmitter are passed to the corresponding local area WAPS transmitters which can then re-transmit the WAPS signal (for example, using a different code and the same slot). The transmitter will include additional data in its transmission such as latitude,

30 longitude and altitude of the local antenna. In this configuration, the WAPS user receiver

operation (range measurement and position measurement) can be transparent to the fact that the signals are coming from repeaters. Note that the transmitter used in the repeater is cheaper than a full WAPS beacon in that it does not need to have a GNSS timing unit to extract GNSS timing.

- 5 Depending on the mode of operation of the receiver unit, either terminal-based positioning or network-based positioning is provided by the system. In terminal based positioning, the receiver unit computes the position of the user on the receiver itself. This is useful in applications like turn-by-turn directions, geo-fencing etc. In network based positioning, the receiver unit receives the signals from the towers and communicates or
- 10 transmits the received signal to a server to compute the location of the user. This is useful in applications like E911, and asset tracking and management by a centralized server. Position computation in the server can be done in near real time or post-processed with data from many sources (e.g., GNSS, differential WAPS etc.) to improve accuracy at the server. The WAPS receiver can also provide and obtain information from a server (similar, for
- 15 example, to a SUPL Secure User PLane server) to facilitate network based positioning.

The towers of an embodiment maintain synchronization with each other autonomously or using network-based synchronization. **Figure 5** shows tower synchronization, under an embodiment. The following parameters are used in describing aspects of synchronization:

20

System transmitter time = $t_{WAPS-tx}$

Absolute time reference = t_{WAPS_abs}

25

Time Adjustment = $\Delta_{system} = t_{WAPS-tx} - t_{WAPS_abs}$

- 30 Note that it is not essential to synchronize WAPS system time to an absolute time reference. However, all WAPS transmitters are synchronized to a common WAPS system time (i.e. relative timing synchronization of all WAPS transmitter). Timing corrections of each transmitter relative to WAPS system time (if any) should be computed. The timing corrections should be made available to the receivers either directly through over the air WAPS assistance transmission or through some other communication means. The

assistance can be delivered, for example, to the WAPS receiver through a cellular (or other) modem or through a broadcast data from a system (such as Iridium or digital TV or MediaFlo or broadcast channels of cellular systems). Alternatively, the timing correction can be sent to the server and used when computing position at the server. A description of 5 tower synchronization of an embodiment follows.

Under network based synchronization, the towers synchronize with each other in a local area. The synchronization between towers generally includes transmission of a pulse (which can be modulated using any form of modulation onto a carrier and/or spread using a spreading code for better time resolution which in turn modulates a carrier) and 10 synchronizing to the pulse edge on the receiver, as described in detail herein.

In the autonomous synchronization mode of an embodiment, the towers are synchronized using a local timing reference. The timing reference can be one of the following, for example: GPS receivers; highly accurate clock sources (e.g., Atomic); a local time source (e.g., GPS disciplined clock); and, any other network of reliable clock 15 sources. Use of signals from XM satellite radio, LORAN, eLORAN, TV signals etc. which are precisely time synchronized can be used as a coarse timing reference for the towers. As an example in one embodiment, **Figure 6** is a block diagram of a PPS pulse source from a GPS receiver being used to discipline an accurate/stable timing source such as a Rubidium, Caesium or a hydrogen master, under an embodiment. Alternatively, a GPS disciplined 20 Rubidium clock oscillator can be used, as shown in **Figure 7**.

With reference to **Figure 6**, the time constant of the PLL in the accurate clock source is set to a large enough number (e.g., in the range of 0.5-2 hours) which provides for better short term stability (or equivalently, filtering of the short term GPS PPS variations) and the GPS-PPS provides for longer term stability and wider area ‘coarse’ 25 synchronization. The transmitter system continuously monitors these two PPS pulses (from the GPS unit and from the accurate clock source) and reports any anomaly. The anomalies could be that after the two PPS sources being in lock for several hours, one of the PPS sources drifts away from the other source by a given time-threshold determined by the tower network administrator. A third local clock source can be used to detect 30 anomalies. In case of anomalous behavior, the PPS signal which exhibits the correct

behavior is chosen by the transmitter system and reported back to the monitoring station. In addition, the instantaneous time difference between the PPS input and PPS output of the accurate time source (as reported by the time source) can either be broadcast by the transmitter or can be sent to the server to be used when post processing.

- 5 In the transmitter system, the time difference between the rising edge of the PPS pulse input and the rising edge of the signal that enables the analog sections of the transmitter to transmit the data is measured using an internally generated high speed clock. **Figure 8** shows a signal diagram for counting the time difference between the PPS and the signal that enables the analog sections of the transmitter to transmit the data, under an
- 10 embodiment. The count that signifies that difference is sent to each of the receivers as a part of the data stream. Use of a highly stable clock reference such as a Rubidium clock (the clock is stable over hours/days) allows the system to store/transmit this correction per tower on the device, just in case the device cannot modulate the specific tower data anymore. This correction data can also be sent via the communication medium to the
- 15 device, if there is one available. The correction data from the towers can be monitored by either reference receivers or receivers mounted on the towers that listen to other tower broadcasts and can be conveyed to a centralized server. Towers can also periodically send this count information to a centralized server which can then disseminate this information to the devices in the vicinity of those towers through a communication link to the devices.
- 20 Alternatively, the server can pass the information from towers (e.g., in a locale) to neighboring towers so that this information can be broadcast as assistance information for the neighboring towers. The assistance information for neighboring towers may include position (since the towers are static) and timing correction information about towers in the vicinity.
- 25 Similar to the transmitter timing correction of an embodiment, when a true PPS is available it can be used to estimate multipath bias and precise true range. The receiver estimates range using samples of the signal, for example from the ADC. The receiver of an embodiment uses a high speed clock to determine the difference between the occurrence of the PPS and the first edge of the sample ADC clock. This allows the range estimated by the
- 30 receiver based on the ADC samples to be corrected for the difference between when true

PPS occurs and when the ADC samples the data, thus allowing for estimation of the true range of the receiver to a precision better than the sample clock resolution of the ADC. In the context of the discussion in the paragraph above, the PPS refers to a pulse whose edge is aligned to or has known offset from a standard timing base such as GPS

5 pulse-per-second (PPS) timing.

In another embodiment, a wide area differential positioning system can be used to correct for timing errors from the towers. **Figure 9** is a block diagram of the differential WAPS system, under an embodiment. A reference receiver (located at a pre-surveyed location) is used to receive signals from all the towers in the vicinity. Although the 10 principles of differential GPS are applied in this method, dealing with the effects of non-line-of-sight in the terrestrial case makes it unique. The reference receiver's pseudorange (code phase) measurements for each tower are time-tagged and then sent to the server. The received code phase-based ranges measured at the reference receiver for towers j and i can be written as follows:

$$15 \quad R_{ref}^j(t) = \rho_{ref}^j + c(dt_{ref} - dt^j) + \varepsilon_{R,ref}^j$$

$$R_{ref}^i(t) = \rho_{ref}^i + c(dt_{ref} - dt^i) + \varepsilon_{R,ref}^i,$$

where ρ_{ref}^j is the reference receiver to transmit tower j geometric range, dt_{ref} and dt^j are respectively the reference receiver and transmitter clock offsets referred to their respective antennas with respect to a common reference time (say, GPS time), c is the speed of light, 20 and $\varepsilon_{R,ref}^j$ is the measurement noise.

The differences in clock timing between the towers i and j , $dt^i - dt^j$ are computed at the server by subtracting the two equations above and using the known geometric ranges from reference receiver to the transmit towers. This allows for elimination of the timing differences between the transmitters in the rover/mobile station measurements. Note that 25 averaging over time can be used to get better (e.g., less noisy) estimates of the time difference $dt^i - dt^j$ when the clocks used in the transmit towers are relatively stable.

The rover/mobile station's pseudorange measurements are also time tagged and sent to a server. The received code phase based ranges measured at the rover/mobile station can be written as:

$$R_m^i(t) = \rho_m^i + c(dt_m - dt^i) + \varepsilon_{R,m}^i$$

$$R_m^j(t) = \rho_m^j + c(dt_m - dt^j) + \varepsilon_{R,m}^j.$$

By subtracting the two equations above and re-arranging, the result is

$$(\rho_m^j - \rho_m^i) = (R_m^j(t) - R_m^i(t)) - c(dt^i - dt^j) + (\varepsilon_{R,m}^i - \varepsilon_{R,m}^j).$$

5 Note that $R_m^i(t)$ and $R_m^j(t)$ are measured quantities and the quantity $dt^i - dt^j$ is computed from the reference receiver measurements. Each of ρ_{ref}^i and ρ_{ref}^j can be written in terms of the unknown coordinates of the receiver and the known coordinates of the transmit towers i and j . With three range measurements, two range difference equations can be formed as above to obtain a two-dimensional position solution or with four range measurements, 10 three range difference equations can be formed as above to obtain a three-dimensional position. With additional measurements, a least square solution can be used to minimize the effect of the noise quantities $\varepsilon_{R,m}^i$ and $\varepsilon_{R,m}^j$.

Alternatively, the timing difference corrections can be sent back to the mobile station to correct for the errors in-situ and to facilitate position computation at the mobile 15 station. The differential correction can be applied for as many transmitters as can be viewed by both the reference and the mobile stations. This method can conceptually allow the system to operate without tower synchronization or alternatively to correct for any residual clock errors in a loosely synchronized system.

Another approach is a standalone timing approach as opposed to the differential 20 approach above. One way of establishing timing synchronization is by having GPS timing receivers at each Transmit tower in a specific area receive DGPS corrections from a DGPS reference receiver in the same area. A DGPS reference receiver installed at a known position considers its own clock as a reference clock and finds corrections to pseudo-range measurements to the GPS satellites it tracks. The DGPS correction for a particular GPS 25 satellite typically comprises total error due to satellite position and clock errors and ionospheric and tropospheric delays. This total error would be the same for any pseudo-range measurement made by other GPS receivers in the neighborhood of the DGPS reference receiver (typically with an area of about 100 Km radius with the DGPS receiver

at the center) because line of sight between DGPS reference receiver and GPS satellite does not change much in direction within this neighborhood. Thus, a GPS receiver using DGPS correction transmitted by a DGPS reference receiver for a particular GPS satellite uses the correction to remove this total error from its pseudo-range measurement for that 5 satellite. However in the process it would add the DGPS reference receiver's clock bias with respect to GPS time to its pseudo-range measurement. But, since this clock bias is common for all DGPS pseudo-range corrections, its effect on the timing solutions of different GPS receivers would be a common bias. But this common bias gives no relative timing errors in the timings of different GPS receivers. In particular, if these GPS receivers 10 are timing GPS receivers (at known positions) then all of them get synced to the clock of DGPS reference receiver. When these GPS timing receivers drive different transmitters, the transmissions also get synchronized.

Instead of using corrections from a DGPS reference receiver, similar corrections transmitted by Wide Area Augmentation System (WAAS) satellites can be used by GPS 15 timing receivers to synchronize transmissions of the transmitters which they drive. An advantage of WAAS is that the reference time is not that of the DGPS reference system but it is the GPS time itself as maintained by the set of accurate atomic clocks.

Another approach to achieving accurate time synchronization between the towers across a wide area is to use time transfer techniques to establish timing between pairs of 20 towers. One technique that can be applied is referred to as "common view time transfer". **Figure 10** shows common view time transfer, under an embodiment. The GPS receivers in the transmitters that have the view of a common satellite are used for this purpose. Code phase and/or carrier phase measurements from each of the towers for the satellites that are in common view are time tagged periodically (e.g., minimum of once every second) by the 25 GPS receivers and sent to a server where these measurements are analyzed.

The GPS code observable R_p^i (signal emitted by satellite "i" and observed by a receiver "p") can be written as:

$$R_p^i(t) = \rho_p^i + c(\delta_{R,p}^i + \delta_{R,p} + T_p^i + I_p^i) + c(dt_p - dt^i) + \varepsilon_{R,p},$$

where ρ_p^i , is the receiver-satellite geometric range equal to $|\bar{X}_p - \bar{X}^i|$, \bar{X}_p is the receiver antenna position at signal reception time, \bar{X}^i represents the satellite position at signal emission time, I_p^i and T_p^i are respectively the ionospheric and tropospheric delays, and δ_{R_p} and δ_R^i are the receiver and satellite hardware group delays. The variable δ_{R_p} includes

5 the effect of the delays within the antenna, the cable connecting it to the receiver, and the receiver itself. Further, dt_p and dt^i are respectively the receiver and satellite clock offsets with respect to GPS time, c is the speed of light, and ε_R is the measurement noise.

The common view time transfer method computes the single difference code observable R_{pq}^i , which is the difference between code observables simultaneously

10 measured at two receivers (called "p" and "q") as

$$R_{pq}^i = \underbrace{\rho_p^i - \rho_q^i}_{\text{geometrical range difference}} + \underbrace{c(dt_p - dt_q)}_{\text{time difference between clocks}} + \underbrace{c(T_p^i - T_q^i)}_{\text{Troposphere & ionosphere delay difference}} + \underbrace{c(I_p^i - I_q^i)}_{\text{Group delay difference between receivers}} + c(\delta_{R,p} - \delta_{R,q}) + (\varepsilon_{R,p} - \varepsilon_{R,q})$$

In calculating the single difference observable, the group delay in the satellite as well as the clock error of the satellite gets cancelled. Also, note that in the above equation the

15 tropospheric and ionospheric perturbations cancel (or, can be modeled, for example in cases where the receiver separation is large). Once the group delay differences between the receivers are calibrated, the desired time difference $c(dt_p - dt_q)$ between the receiver clocks can be found from the equation. The single difference across multiple time and satellite measurements can be combined to further improve the quality of the estimated

20 time difference.

In a similar manner, the single difference carrier phase equation for common view time transfer can be written as:

$$\begin{aligned} \Phi_{pq}^i = & \underbrace{\rho_p^i - \rho_q^i}_{\text{geometrical range difference}} + \underbrace{c(dt_p - dt_q)}_{\text{time difference between clocks}} + \underbrace{c(T_p^i - T_q^i)}_{\text{Troposphere & ionosphere delay difference}} + \underbrace{c(\delta_{\phi,p} - \delta_{\phi,q})}_{\text{Group delay difference between receivers}} \\ & + \underbrace{\lambda(\phi_p^i - \phi_q^i)}_{\text{initial ambiguity in phase}} + \underbrace{\lambda(N_p^i - N_q^i)}_{\text{integer ambiguity in phase measurement}} + (\varepsilon_{\phi,p} - \varepsilon_{\phi,q}) \end{aligned}$$

Note that since initial phase ambiguity and integer ambiguity are present in the above equation, the phase single difference cannot be used to determine the time transfer directly. A combined use of the code and phase observations allows for advantage to be taken of the absolute information about time difference from the codes and the precise information

5 about the evolution of time difference from the carrier phases. The error variance in the carrier phase single difference is significantly better than the code phase single difference leading to better time transfer tracking.

The resulting errors per tower for a given satellite are either sent back to the tower for correction, applied at the tower, sent to the receivers over the communication link for

10 the additional corrections to be done by the receiver, or sent as a broadcast message along with other timing corrections from the tower. In specific instances, it might be such that the measurements from the towers and the receiver are post-processed on the server for better location accuracy. A single channel GPS timing receiver or a multiple channel timing receiver that produces C/A code measurements and/or carrier phase measurements

15 from L1 and/or L2 or from other satellite systems such as Galileo/Glonass can be used for this purpose of common view time transfer. In multiple channel systems, information from multiple satellites in common view are captured at the same instant by the receivers.

An alternative mechanism in “common view time transfer” is to ensure that different timing GPS receivers in the local area (each feeding to its corresponding

20 transmitter) use only common satellites in their timing pulse derivation (e.g., one pulse per second) but no attempt is made to correct the timing pulses to be aligned to the GPS (or UTC) second. The use of common view satellites ensure that common errors in timing pulses (such as common GPS satellite position and clock errors and ionospheric and tropospheric delay compensation errors) pull the errors in timing pulse by about same

25 magnitude and relative errors in timing pulses are reduced. Since, in positioning, only relative timing errors matter, there is no need for any server-based timing error correction. However, a server can give commands to different GPS receivers on which GPS satellites are to be used in deriving timing pulses.

An alternative method of time transfer is the “two-way time transfer” technique.

30 **Figure 11** shows the two-way time transfer, under an embodiment. Consider two towers

that are used to time against each other. Transmissions from each of the two transmitters starts on the PPS pulse and a time interval counter is started on the receive section (WAPS Receiver) of the transmit towers. The received signal is used to stop the time interval counter on either side. The results from the time interval counter are sent over the data

5 modem link to the WAPS server where these results along with transmit times are compared and the errors in timing between the two towers can be computed. This can then be extended to any number of towers. In this method, the relationship between the counter measurements ΔT_i at tower i and ΔT_j at tower j, and the time difference dt_{ij} between the clock in i and j can be represented as

10
$$dt_{ij} = T_i - T_j = \frac{1}{2}(\Delta T_i - \Delta T_j) + \frac{1}{2}[(\tau_i^{rx} + \tau_j^{rx}) - (\tau_j^{rx} + \tau_i^{rx})],$$

where τ_i^{rx} & τ_j^{rx} are the transmitter delays of the towers, and τ_i^{rs} & τ_j^{rs} are the receiver delays of towers. The time difference can be estimated once the transmitter and receiver delays are calibrated.

In addition to the time transfer between towers, the timing of the towers relative to
15 GPS time can be found by the GPS timing receivers used in common view time transfer.
Using the range measurement as

$$R_p^i(t) = \rho_p^i + c(\delta_R^i + \delta_{R,p} + T_p^i + I_p^i) + c(dt_p - dt^i) + \varepsilon_{R,p},$$

the time correction of local clock relative to GPS time dt_p is computed, after accounting
for the delay of the receiver, satellite clock errors and ionospheric/tropospheric errors. The
20 delay of the receiver $\delta_{R,p}$ can be calibrated by measurement of the group delay.

Information from the GPS satellite navigation message (either obtained through
demodulation or from a server) can be used to compute the satellite timing correction
which eliminates the effect of dt^i and δ_R^i . Similarly, troposphere and ionosphere delay
effects are minimized using the corrections from an external model. Ionospheric
25 corrections can be obtained for example from WAAS messages. Alternatively, a
combination of clock and ionospheric/tropospheric corrections can be obtained from
RTCM DGPS corrections for the pseudorange, when available.

The offset relative to GPS time can also be sent as part of the data stream from the towers. This enables any WAPS receiver that acquires the WAPS signal to provide accurate GPS time and frequency aiding to significantly reduce GNSS search requirements in a GNSS receiver.

5 In an embodiment of the system, the broadcast transmitters can be employed ad hoc to provide localized indoor position determination. For example, in a fire-safety application, the WAPS transmitters would be placed on three or more broadcast stations (could be fire trucks, for example). The towers would synchronize to each other by one of the many means described earlier and broadcast signals. The bandwidth and chipping rates
10 would be scaled based on spectrum availability and accuracy requirements in that area for that application at that time. The receivers would be notified of the system parameters through the communication link to the devices.

Figure 12 is a block diagram of a receiver unit, under an embodiment. The beacon signal is received at the antenna on the receiver unit, down-converted, demodulated and
15 decrypted and fed to the positioning engine. The receiver provides all information to reconstruct the signal accurately. The receive antenna can be an omni-directional antenna or, alternatively, a number of antennas/arrays providing diversity etc. In another embodiment, the mixing and down conversion can be done in the digital domain. Each receiver unit includes or uses a unique hardware identification number and a computer
20 generated private key. Each receiver unit, in general, stores the last few locations in non volatile memory and can be later queried remotely for the last few stored locations. Based on the availability of the spectrum in a given area, the transmitters and receivers can adapt to the available bandwidth and change the chipping rate and filter bandwidths for better accuracy and multipath resolution.

25 In one embodiment, the digital baseband processing of the received signals is accomplished using commercially-available GPS receivers by multiplexing/feeding the signal from a GPS RF section with the WAPS RF module. **Figure 13** is a block diagram of the receiver with a WAPS RF module, under an embodiment. The RF module includes one or more of Low noise amplifiers (LNAs), filters, down-converter, and analog to digital
30 converters, to name a few. In addition to these components, the signal can be further

conditioned to fit the input requirements of the GPS receiver using additional processing on chip or a custom ASIC or on an FPGA or on a DSP or on a microprocessor. The signal conditioning can include digital filtering for in-band or out-of band noise (such as ACI – adjacent channel interference), translating intermediate or baseband frequencies of the

- 5 input to the GPS IC from the frequencies of the WAPS receiver, adjusting the digital signal strength so that the GPS IC will be able to process the WAPS signal, automatic gain control (AGC) algorithms to control the WAPS frontend etc. In particular, the frequency translation is a very useful feature because this allows the WAPS RF module to work with any commercially available GPS receiver. In another embodiment, the entire RF frontend
- 10 chain including the signal conditioning circuits for the WAPS system can be integrated onto an existing GPS die that contains a GPS RF chain.

In another embodiment, if access to the digital baseband input is not available, the signal can be up-converted/down-converted from any band to the GPS band and fed into the RF section of the GPS receiver. **Figure 14** shows signal up-conversion and/or

- 15 down-conversion, under an embodiment.

In another embodiment, multiple RF chains or tunable RF chains can be added to both the transmitter and receiver of the WAPS system so as to use the most effective frequency of operation in a given area, be it wide or local. The choice of frequency can be determined by cleanliness of the spectrum, propagation requirements, etc.

- 20 Similarly, WAPS can temporarily use a receive chain in a receiver system that includes multiple receive chains. For example, a wideband CDMA (W-CDMA) receiver system includes two receive chains to improve receive diversity. Thus, when WAPS is used in a W-CDMA receiver system one of the two native receive chains of the W-CDMA can be used temporarily for receiving and processing WAPS signals. **Figure 15** is a block
- 25 diagram of a receiver system having multiple receive chains in which one of the receive chains can be used temporarily for receiving and processing WAPS signals, under an embodiment. In this example, the diversity receive chain can be used to temporarily receive and process the WAPS signals. Alternatively, the GPS receive chain can be used to temporarily receive and process the WAPS signals.

The radio front-end can be shared between WAPS and another application. Some parts of the frontend can be shared and some may be used on a mutually exclusive basis. For example, if the die/system already has a TV (NTSC or ATSC or systems like DVB-H, MediaFLO) tuner front-end including the antenna, the TV tuner radio and antenna can be

5 shared with the WAPS system. They can operate on a mutually exclusive basis in that, either the system receives TV signals or receives WAPS signals at any given time. In another embodiment, if it makes it easier to add a WAPS RF section to such a system, the antenna can be shared between the TV tuner and the WAPS system allowing both systems to operate simultaneously. In cases where the system/die has a radio like an FM radio, the

10 RF front-end can be modified to accommodate both the WAPS system and the FM radio and these radios can operate on a mutually exclusive basis. Similar modifications can be done for systems that have some RF frontends that operate in close frequency proximity to the WAPS RF band.

The clock source reference such as crystal, crystal oscillator (XO), Voltage

15 Controlled Temperature Compensated Crystal Oscillator (VCTCXO), Digitally-controlled Crystal Oscillator (DCXO), Temperature Compensated Crystal Oscillator (TCXO), that is used for a GNSS sub-system can be shared with the WAPS receiver to provide the reference clock to the WAPS receiver. This sharing can be done on the die or off-chip. Alternatively, the TCXO/VCTCXO used by any other system on a cellular phone can

20 shared with the WAPS system. **Figure 16** is a block diagram showing clock sharing in a positioning system, under an embodiment. Note that the transceiver or processor system block can refer to a variety of systems. The transceiver system that shares the clock with the WAPS system can be a modem transceiver (for example, a cellular or WLAN or BT modem) or a receiver (for example, a GNSS, FM or DTV receiver). These transceiver

25 systems may optionally control the VCTCXO or DCXO for frequency control. Note that the transceiver system and the WAPS system may be integrated into a single die or may be separate dies and does not impact the clock sharing. The processor can be any CPU system (such as an ARM sub-system, Digital Signal Processor system) that uses a clock source. In general, when a VCTCXO/DCXO is shared, the frequency correction applied by the other

30 system may be slowed down as much as possible to facilitate WAPS operation.

Specifically, the frequency updates within the maximum integration times being used in WAPS receiver may be limited to permit better performance (i.e. minimizing SNR loss) for the WAPS receiver. Information regarding the state of the WAPS receiver (specifically, the level of integration being used, acquisition versus tracking state of the WAPS system)

5 can be exchanged with the other system for better coordination of the frequency updates. For example, frequency updates could be suspended during WAPS acquisition phase or frequency updates can be scheduled when the WAPS receiver is in sleep state. The communication could be in the form of control signals or alternatively in the form of messages exchanged between the transceiver system and the WAPS system.

10 The WAPS broadcasts signals and messages from the towers in such a way that a conventional GPS receiver's baseband hardware need not be modified to support both a WAPS and a traditional GPS system. The significance of this lies in the fact that although the WAPS system has only half the available bandwidth as the GPS C/A code system (which affects the chip rate), the WAPS broadcast signal is configured to operate within the 15 bounds of a commercial grade C/A code GPS receiver. Further, based on signal availability, the algorithms will decide whether GPS signals should be used to determine position or WAPS signals or a combination thereof should be used to get the most accurate location.

20 The data transmitted on top of the gold codes on the WAPS system can be used to send assistance information for GNSS in the cases of a hybrid GNSS-WAPS usage scenario. The assistance can be in the form of SV orbit parameters (for example, ephemeris and almanac). The assistance may also be specialized to SVs visible in the local area.

25 In addition, the timing information obtained from the WAPS system can be used as fine time aiding for the GNSS system. Since the WAPS system timing is aligned to GPS (or GNSS) time, aligning to the code and bit of WAPS signal and reading the data stream from any tower provides coarse knowledge of GNSS time. In addition, the position solution (the receiver's clock bias is a by-product of the position solution) determines the WAPS system time accurately. Once the WAPS system time is known, fine time aiding can be provided to the GNSS receiver. The timing information can be transferred using a 30 single hardware signal pulse whose edge is tied to the internal time base of WAPS. Note

that the WAPS system time is directly mapped onto GPS time (more generally, with GNSS time, since the time bases of GNSS systems are directly related). The GNSS should be able to latch its internal GNSS time base count upon receipt of this edge. Alternatively, the GNSS system should be able to generate a pulse whose edge is aligned to its internal time base and the WAPS system should be capable of latching its internal WAPS time base. The WAPS receiver then sends a message with this information to the GNSS receiver allowing the GNSS receiver to map its time base to WAPS time base.

5 Similarly, the frequency estimate for the local clock can be used to provide frequency aiding to the GNSS receiver. Note that frequency estimate from WAPS receiver
10 can be used to refine the frequency estimate of the GNSS receiver whether or not they share a common clock. When the two receivers have a separate clock, an additional calibration hardware or software block is required to measure the clock frequency of one system against the other. The hardware or software block can be in the WAPS Receiver section or in the GNSS receiver section. Then, the frequency estimate from the WAPS receiver can be used to refine the frequency estimate of the GNSS receiver.

15 The information that can be sent from the WAPS system to the GNSS system can also include an estimate of location. The estimate of location may be approximate (for example, determined by the PN code of the WAPS tower) or more accurate based on an actual position estimate in the WAPS system. Note that the location estimate available
20 from the WAPS system may be combined with another estimate of position from a different system (for example, a coarse position estimate from cellular ID based positioning) to provide a more accurate estimate of position that can be used to better aid the GNSS system. **Figure 17** is a block diagram of assistance transfer from WAPS to GNSS receiver, under an embodiment.

25 The GNSS receiver can also help improve the performance of the WAPS receiver in terms of Time-To-First-Fix (TTFF), sensitivity and location quality by providing location, frequency and GNSS time estimates to the WAPS receiver. As an example, **Figure 18** is a block diagram showing transfer of aiding information from the GNSS receiver to the WAPS receiver, under an embodiment. Note that the GNSS system can be
30 replaced by LORAN, e-LORAN or similar terrestrial positioning system as well. The

location estimate can be partial (eg. Altitude or 2-D position), or complete (eg. 3-D position) or raw range/pseudo-range data). The range/pseudo-range data should be provided along with the location of SV (or means to compute the location of the SV such as SV orbit parameters) to enable usage of this range information in a hybrid solution. All

- 5 location aiding information should be provided along with a metric indicating its quality. When providing GNSS time information (which may be transferred to the WAPS system using a hardware signal), the offset of GNSS time relative to GPS time (if any) should be provided to enable usage in the WAPS receiver. Frequency estimates, can be provided as an estimate of the clock frequency along with a confidence metric (indicating the estimated
- 10 quality of the estimate, for example, the maximum expected error in the estimate). This is sufficient when the GNSS and WAPS systems share the same clock source. When the GNSS and WAPS systems use a separate clock, the GNSS clock should also be provided to the WAPS system to enable the WAPS system to calibrate (i.e. estimate the relative clock bias of WAPS with respect to GNSS clock) or, alternatively, the WAPS system should
- 15 provide its clock to the GNSS system and the GNSS system should provide a calibration estimate (i.e. an estimate the relative clock bias of WAPS with respect to GNSS clock).

To further improve the sensitivity and TTFF of a WAPS receiver, assistance information (such as that would otherwise be decoded from the information transmitted by the towers) can be provided to the WAPS receiver from a WAPS server by other

- 20 communication media (such as cellular phone, WiFi, SMS etc). With the “almanac” information already available, the WAPS receiver’s job becomes simple since the receiver just needs to time align to the transmit waveform (without requirement of bit alignment or decoding). The elimination of the need to decode the data bits reduces TTFF and therefore saves power since the receiver does not need to be continuously powered on to decode all
- 25 the bits. **Figure 19** is an example configuration in which WAPS assistance information is provided from a WAPS server, under an embodiment.

A beacon may be added to the receiver to further improve local positioning. The beacon can include a low power RF transmitter that periodically transmits a waveform with a signature based on a device ID. For example, the signature can be a code that uniquely

- 30 identifies the transmitter. An associated receiver would be able to find a location of the

transmitter with a relatively higher accuracy through either signal energy peak finding as it scans in all directions, or through direction finding (using signals from multiple-antenna elements to determine direction of signal arrival).

5 RESOLUTION OF MULTIPATH SIGNALS

Resolution of multipath is critical in positioning systems. Wireless channel is often characterized by a set of randomly varying multipath components with random phases and amplitudes. For positioning to be accurate, it is imperative that the receiver algorithm resolves the line-of-sight (LOS) path if present (it will be the first arriving path) or the path

10 that arrives first (which may not necessarily be the LOS component).

Traditional methods often work as follows: (1) the received signal is cross-correlated with the transmitted pseudo-random sequence (e.g. Gold code sequence, which is known at the receiver); (2) the receiver locates the first peak of the resulting cross-correlation function and estimates that the timing of the path that arrived first is the same as the timing indicated by the position of this peak. These methods work effectively as long as the lowest multipath separation is much larger than inverse of the bandwidth available which is often not the case. Bandwidth is a precious commodity and a method which can resolve multipath with the minimal amount of bandwidth is highly desired to improve the efficiency of the system.

15 20 Depending on the channel environment (including multipath and signal strength), an appropriate method for obtaining an estimate of the earliest arriving path is used. For best resolvability, high-resolution methods are used whereas for reasonable performance at low SNRs more traditional methods that directly use the cross-correlation peak samples and some properties of the correlation function around the peak are applied.

25 Consider the quantized received signal $y[n]$ sampled at a rate f_s given by:

$$y[n] = h_{eff}[n] \otimes x[n]$$

$$y[n] = \sum_{i=n_0}^{\infty} h_{eff}[i] \cdot x[n-i]$$

where $y[n]$ is the received signal which is the convolution of the transmitted pseudo-random sequence $x[n]$ with the effective channel $h_{eff}[n] = h[n] \otimes h_{tx}[n] \otimes$

$h_{rx}[n]$, where $h_{tx}[n]$ is the transmit filter, $h_{rx}[n]$ is the receive filter and $h[n]$ is the multi-path channel.

One method to find the peak position is by peak interpolation using the values surrounding the apparent peak position. The interpolation may be quadratic using one value on either side of the peak or may use a higher order polynomial using two or more samples around the peak or may use a best fit for the actual pulse shape. In the case of quadratic interpolation, a quadratic is fitted to the peak value and the values immediately surrounding the peak. The peak of the quadratic determines the peak position that is used for ranging. This method is quite robust and can work well at low SNR.

10 An alternative embodiment may use a value other than the peak position as the reference position. Note that the DLL actually uses the peak position as reference position on the correlation function whereas this method uses a point different from the peak as reference. This method is motivated by the fact that the early edge of the correlation peak is less affected by multi-path than the trailing edge. For example, a point 75% of chip T_c from the peak on the undistorted (without channel effects) correlation function may be used as a reference point. In this case, the portion of the interpolated $z[n]$ function that matches this 75% point is selected and the peak is found as 25% of T_c away from this point.

15 Another alternative peak correlation function based method may use the peak shape (such as a measure of distortion of the peak, for example, peak width). Starting from the peak location and based on the shape of the peak, a correction to the peak location is determined to estimate the earliest arriving path.

20 High-resolution methods are a class of efficient multipath-resolution methods which use Eigen-space decompositions to locate the multipath components. Methods such as MUSIC, ESPRIT fall under this class of resolution schemes. They are highly powerful schemes as they can resolve effectively much more closely spaced multipath components than traditional methods, for the same given bandwidth. The high resolution earliest time of arrival method attempts to estimate directly the time of arrival of earliest path rather than inferring the peak position from the peak values. The below assumes that a coarse-acquisition of the transmitted signal is already available at the receiver and the start 25 of the pseudo-random sequence is known roughly at the receiver.

30

Figure 20 is a flow diagram for estimating an earliest arriving path in $h[n]$, under an embodiment. The method to determine the earliest path comprises the following operations, but is not so limited:

1. Cross-correlate the received samples $y[n]$ with the transmit sequence $x[n]$ to obtain the result $z[n]$. When the cross-correlation is written in terms of a convolution,

$$z[n] = y[n] \otimes x^*[-n]$$

The equation can be re-written as

$$z[n] = h_{eff}[n] \otimes \phi_{xx}[n]$$

where $\phi_{xx}[n]$ is the autocorrelation function of the pseudo-random sequence

2. Locate the first peak of $z[n]$ and denote it as n_{peak} . Extract wL samples to the left of the peak and wR samples to the right of the peak of $z[n]$ and denote this vector as pV .

$$pV = [z[n_{peak} - wL + 1] \cdots z[n_{peak} + wR]]$$

The vector pV denotes the useful part of the cross-correlation result $z[n]$. In the ideal case, in the absence of channel distortion and when the channel BW is not limited, the choosing $wL = wR = f_s T_c$ would be sufficient to determine the timing of the received signal. In the presence of limited BW, for the case when the

- 15 pseudo-random code $x[n]$ is a sequence of +1/-1's, the optimal method to choose wL and wR are to choose them as the non-zero values (or, more generally, values > a certain threshold defined as a fraction of the peak value are selected) present on the left and right side of the peak of $p[n] = h_{tx}[n] \otimes h_{rx}[n]$ respectively. One other consideration in the choice of wL and wR is to select enough uncorrelated noise samples to obtain enough information regarding the noise sub-space. In addition, the integers wL and wR should be chosen to include all possible multipath components especially on the left side (i.e. through choice of wL) to help resolve far-out multipath components. Including too many samples beyond $f_s T_c$ increases the amount of noise introduced in the pV vector and hence has to be curtailed.
- 20 Through simulation and experiments, a typical set of values for wL and wR are $3f_s T_c$ and $3f_s T_c$, respectively.
- 25

5 Note that $z[n]$ (and in turn pV) contains the effect of the channel $h[n]$, the transmit filter $h_{tx}[n]$, the receive filter $h_{rx}[n]$ and the autocorrelation function of the pseudo-random sequence $\phi_{xx}[n]$. In order to estimate the earliest arriving path in the channel, the other effects need to be eliminated. In many cases the transmit and receive pulse-shapes are matched for best noise performance, but that constraint is not required for this algorithm to work. The reference correlation function is defined as $\phi_{ref}[n] = \phi_{xx}[n] \otimes h_{tx}[n] \otimes h_{rx}[n]$ which needs to be estimated and eliminated before pV can be used for estimation of earliest arriving path.

10

3. The Reference correlation function $\phi_{ref}[n]$ is estimated next.

One method to obtain the reference cross-correlation is as follows: perform steps 1-2 on a ideal channel (a so called “cabled link”) to obtain the corresponding peak vector pV_{Ref} . pV_{Ref} contains the useful samples of the reference correlation function $\phi_{ref}[n]$. **Figure 21** is a flow diagram for estimating reference correlation function, under an embodiment.

20

The “Cabled link” method involves sending the modulated signal from the transmitter front-end (power-amplifier and transmit antenna is by-passed) through an ‘ideal’ channel (for example, a cable) to the receiver front-end (bypass the receive antenna). Note that the ‘ideal’ channel can have some delay and attenuation, but should not add any other distortion and must have high SNR. For the best performance, the ‘cabled’ reference needs to be generated separately for each pseudo-random sequence as they have different autocorrelation functions and hence different references. It is also then critical to choose PRNs properly for the best autocorrelation functions (specifically, their close in autocorrelation side-lobes should be well suppressed compared to the peak) which will result in the best overall performance of the timing-resolution method, since autocorrelation sidelobes can get mistaken for multipath unless sufficiently attenuated.

25

30

Assuming transmit filter responses are controlled, one calibration of the response on cabled link is required per receiver during production. If receiver filter characteristics can be controlled (for example, for a bunch of receivers), then the calibration on cabled link of the response can be further reduced to one calibration measurement for a set of receivers.

An alternative method for determining the reference correlation function $\phi_{ref}[n]$ is to compute the individual components $\phi_{xx}[n]$, $h_{tx}[n]$ and $h_{rx}[n]$ analytically and to convolve them to arrive at the reference correlation function $\phi_{ref}[n]$. Note that this method depends on the extent to which transmit and receive filter impulse responses can be controlled in an actual implementation.

4. Improve the SNR in the estimate of pV by coherently averaging across multiple gold codes and even across multiple bits. Averaging across multiple bits can be done coherently after decisions on the individual bits being transmitted have been made. In other words using decision feedback before integration across bits. Note that improved SNR can be obtained equivalently by performing averaging in the cross-correlation function estimation in Step1.
5. Calculate the Fast Fourier Transform (FFT) of length N_{fft} of pV and pV_{Ref} with zero padding of $N_{fft} - (wL + wR)$ zeros to obtain the length N_{fft} vectors pV_{Freq} and $pV_{Ref,Freq}$ respectively. An optimal value for N_{fft} is obtained by checking resolvability of multipath through simulations using both synthetic and real measured channels. A typical value of N_{fft} was found to be greater than or equal to 4096. The

$$pV_{Freq} = FFT[pV \text{ zeropad}]$$

$$pV_{Ref,Freq} = FFT[pV_{Ref} \text{ zeropad}]$$

6. Calculate $H_{full}[k] = \frac{pV_{Freq}[k]}{pV_{Ref,Freq}[k]}$ to obtain the frequency domain estimate

(corrupted with noise) of the channel $h[n]$. If the received sequence $y[n]$ is oversampled by N_{os} (i.e. $N_{os} = \frac{f_s T_c}{2}$ for a transmit pulse shape band-limited to $+\/-1/T_c$) and if the transmit and receive pulse-shaping filters are perfectly band-limited with BW=1/Tc, then exactly $N = \frac{N_{fft}}{2N_{os}}$ positive and negative samples around DC of $H_{full}[k]$ are non-zero (i.e. usable) for estimation of the real channel, $H_{real}[k]$. From our studies, we have concluded that $\frac{N_{fft}}{2\alpha N_{os}}$ samples on either side of DC should be picked for the best performance of the resolution algorithm, where $\alpha > 1$ is chosen based on the actual pulse-shaping filters used at the transmitter and receiver and the autocorrelation function $\phi_{xx}[n]$. Note that including the frequency transition band of $\phi_{ref}[n]$ causes noise enhancement and α is chosen large enough to exclude these frequencies in the selected samples. However, choosing α too large will cause loss of signal information. A preferred choice of $\alpha = 1.25$ for real band-limited functions based on raised-cosine filter shapes with small excess bandwidth has been used in the implementation.

15

7. If the DC component of $H_{full}[k]$ is at index 0, the reduced H vector, $H[J]$ is defined as:

$$H = [H_{full}[N_{fft} - N + 1] \cdots H_{full}[N_{fft}] H_{full}[0] H_{full}[1] \cdots H_{full}[N]]$$

20

8. Construct the matrix P from the reduced channel estimate vector $H[k]$,

$$P = \begin{bmatrix} H(M) & \cdots & H(2N-1) & H'(0) & \cdots & H'(2N-M+1) \\ H(M-1) & \cdots & H(2N-2) & H'(1) & \cdots & H'(2N-M+2) \\ \vdots & \ddots & \vdots & \vdots & \ddots & \vdots \\ H(0) & \cdots & H(2N-M+1) & H'(M) & \cdots & H'(2N-1) \end{bmatrix}$$

where $1 < M < 2N$ is a parameter and $(\cdot)'$ represents conjugate of the complex number.

Define the estimated covariance matrix R of the reduced channel estimate vector

H[k] as

$$R = P \times P'$$

If M is chosen to be too small (close to 1), then the eigen-values of R are very limited in number and, as a result, the high-resolution algorithm cannot delineate between the signal and noise. If M is chosen too large (close to 2N), then the covariance matrix estimate R is unreliable as the amount of averaging in obtaining the covariance is inadequate and also the covariance matrix R obtained is rank-deficient. Thus, a value of M which is right in the middle of its allowable range i.e. M=N is a good choice. This has also been verified empirically.

5. 9. Perform singular value decomposition (SVD) on R as

$$R = UDV'$$

10. Where U is a matrix of the left singular vectors, V is the matrix of the right singular vectors and D is the diagonal matrix of singular values.

10. Construct the vector of sorted singular values sV as

sV = diagonal elements of D sorted in descending order

11. The next key step is to separate the signal and noise subspaces. In other words, to 15. select an index ns in the vector sV such that the singular values sV[ns+1]...sV[N] correspond to noise. Define a vector of noise singular values as sV_{noise}.

There are a number of methods possible to separate the singular values corresponding to the noise subspace and find a representation for the basis vectors of the noise sup-space:

20. a) All singular values which are smaller than $\frac{\max(sV)}{T_1}$ where T_1 is a threshold value which is a function of the signal-noise ratio (e.g. SNR on the chip)
 $T_1 = f(SNR)$.

Figure 22 is a flow diagram for estimating noise sub-space, under an embodiment.

25. b) All singular values less than $\min\left(\frac{\max(sV)}{T_1}, \text{mean}(sV(L:M)) \times T_2\right)$, where L is a parameter which can be chosen greater than delay-spread (e.g. N/2) and

T_2 is another threshold value determined empirically (typical value can be 1000).

Figure 23 is a flow diagram for estimating noise sub-space, under an alternative embodiment.

5 c) Another method involves determining the noise subspace by repeatedly estimating the SNR for different partitions of noise and signal-plus-noise subspaces and comparing with another estimate of SNR. **Figure 24** is a flow diagram for estimating noise sub-space, under another alternative embodiment.

1) Calculate estimate of SNR as follows:

10 i. Assume that the noise is represented by the $sV(n_s, n_s+1 \dots M)$, Calculate noise variance as:

$$\sigma_{est}^2(n_s) = \frac{\sum_{i=n_s}^M sV(i)}{M - n_s + 1}$$

ii. Calculate the signal power as $P_{sig}(n_s) = \sum_{i=1}^{n_s-1} (sV(i) - \sigma_{est}^2(n_s))$

$$iii. \text{ Estimate of SNR: } SNR_{est}(n_s) = \frac{P_{sig}(n_s)}{\sigma_{est}^2(n_s)}$$

2) An alternative estimate of SNR is obtained through other methods (e.g. SNR on chip). One method of estimating SNR directly is as follows:

15 i. If the received data samples (after frequency error removal and re-sampling to T_c -spaced samples and code de-correlation) are given by X_i (where the X_i are chip-spaced starting from the interpolated peak position).

20 $X_i = S + N_i$

ii. The signal is estimated as $\hat{S} = \frac{1}{N} \sum_{i=0}^{N-1} X_i$

iii. The noise is estimated as $\hat{N} = \frac{1}{N-1} \sum_{i=0}^{N-1} (X_i - \hat{S})^2$

iv. The SNR is estimated as $SNR_c = \frac{\hat{S}}{\hat{N}}$

3) Choose the noise singular values as $sV(ns, ns+1, \dots, M)$ which satisfy the following condition:

$$n_{start} = [smallest n_s : SNR_{est}(n_s) > \overline{SNR_c}]$$

d) Another method involves determining the noise subspace by repeatedly estimating the SNR for different partitions of noise and signal subspaces using c)1) and choosing a partition n_{start} such that

$$n_{start} = argmax_{n_s} [SNR_{est}(n_s) - SNR_{est}(n_s - 1)]_{n_s=2}^K.$$

Figure 25 is a flow diagram for estimating noise sub-space, under yet another alternative embodiment.

e) **Figure 26** is a flow diagram for estimating noise sub-space, under still another alternative embodiment.

1) Define $wLen = \frac{wL+wR}{f_s T_c}$. Then the first $wLen$ singular values represent the significant signal-plus-noise subspace or noise subspace singular values (the rest of the singular values represent correlated noise and signal and quantization effects).

2) Calculate estimate of SNR as follows:

i. Assume that the noise is represented by the $sV(i); i = n_s, n_s + 1 \dots wLen; 1 < n_s \leq wLen$, calculate noise variance as:

$$\sigma_{est}^2(n_s) = \frac{\sum_{i=n_s}^{wLen} sV(i)}{wLen - n_s + 1}$$

ii. Calculate the signal power as $P_{sig}(n_s) = \sum_{i=1}^{n_s-1} [sV(i) - \sigma_{est}^2(n_s)]$

$$iii. Estimate of SNR: SNR_{est}(n_s) = \frac{P_{sig}(n_s)}{\sigma_{est}^2(n_s)}$$

3) Define $n_{start} = [smallest n_s : SNR_{est}(n_s) > (SNR_{est}(wLen) - thresDB)]$. Then n_{start} up to $wLen$ represent the noise singular values. A typical value of $thresDB$ is 10.

12. Choose the corresponding noise right-singular vectors to build V_N i.e. choose all

vectors in V which correspond to the noise singular values and build the noise subspace matrix V_N .

13. Estimate Time of Arrival of the first path:

a) Define

$$\omega(\tau) = \begin{bmatrix} 1 & e^{\frac{j2\pi}{N_{fft}}\tau} & e^{\frac{j2\pi}{N_{fft}}2\tau} & e^{\frac{j2\pi}{N_{fft}}3\tau} & \dots & e^{\frac{j2\pi}{N_{fft}}(M-1)\tau} \end{bmatrix}^H$$

5

b) Calculate $\Omega(\tau) = \frac{1}{\omega(\tau)^H V_N V_N^H \omega(\tau)}$ for a range of values of τ ($\tau \in [\tau_{\max}, -\tau_{\max}]$).

The resolution of search $\Delta\tau$ can be chosen as small as required. As an example, $\tau_{\max} = 5$ and $\Delta\tau = 0.05$ so that τ is searched for in the range [-5,5] in steps of 0.05.

10 14. Peaks of $\Omega(\tau)$ will provide the positions of channel impulses relative to the coarse peak, n_{peak} . Theoretically, first peak will correspond to LOS path. Based on information about the propagation environment which could be encoded in the transmission from the base-station, it is possible to control τ_{\max} . For example, if the delay-spread is large, then τ_{\max} can be chosen to be larger (e.g. 10) and if it is less 15 then τ_{\max} can be chosen as a smaller value (e.g. 4).

Combination Methods:

Apart from the standalone methods discussed above, numerous other combination methods are possible. Combination of schemes based on SNR on chip is an effective method. The following describes a list of combination schemes that can be realized in practice:

20 1. For chipSNR less than chipSNRRef, pick method 12(d) to choose noise singular values. Otherwise choose method 12(a).

2. For chipSNR greater than chipSNRRef, pick method 12(d) to choose noise singular values and estimate peak position. Otherwise, use direct peak estimation techniques (such as peak interpolation, peak shape) starting from the cross-correlation function 25 $z[n]$.

3. For chipSNR less than chipSNRRef, pick method 12(e) to choose noise singular

values. Otherwise choose method 12(a).

A typical value of chipSNRRef is 10dB.

COMPUTATION OF POSITION

5 The location of the receiver unit is determined by the positioning engine available either on the terminal unit or the server. The receiver can use the range measurements from the system or combine the system range measurements with any of the measurements from other signals of opportunity. A sufficient set of range measurements yields a position fix provided that the measurements derive from known locations. The range equation in 3D
 10 space is given by

$$r_i = \sqrt{(x_i - X)^2 + (y_i - Y)^2 + (z_i - Z)^2}.$$

15 The location of the transmitters is given by (x_i, y_i, z_i) and the unknown location of the mobile units is given by (X, Y, Z) in some local coordinate frame. Three or more transmitters produce three or more range measurements that are used to compute a fix. The measurement has a receiver time bias additive term as well, because the receiver time is not synchronized to the WAPS timing.

20 $R_i = r_i + c \Delta t$.
 25 This equation is referred to later as "Pseudorange Measurement Equation". Note that the time bias is common because the transmitters are timing synchronized. The pseudoranges must be corrected for transmit timing corrections which are available from the data stream embedded in the transmission from each transmitter. This delta time bias creates a new unknown parameter, so a minimum of four measurements are used for a solution. A barometric altimeter measurement provides the needed information for a solution as

$$\text{Baro} = (z_b - Z).$$

One method of solving these non-linear simultaneous equations is to linearize the problem at an arbitrary initial point and then iteratively finding corrections to this initial position to iteratively leads to the final solution.

5 This method uses an initial guess for the X, Y, Z solution, so the centroid of the transmitters is used as

$$(X_0, Y_0, Z_0) = (1/n) \sum_{i=1}^n (x_i, y_i, z_i).$$

The final position solution is assumed to be of the form

$$(X, Y, Z, \Delta t) = (X_0, Y_0, Z_0, \Delta t_0) + (dX, dY, dZ, d\Delta t)$$

The geometric range can be expanded in a Taylor series about $(X, Y, Z, \Delta t) = (X_0, Y_0, Z_0, \Delta t_0)$

$$\begin{aligned} R_i &= \sqrt{(x_i - X)^2 + (y_i - Y)^2 + (z_i - Z)^2} + c\Delta t \\ 10 &= \sqrt{(x_i - X_0)^2 + (y_i - Y_0)^2 + (z_i - Z_0)^2} + c\Delta t_0 + \left. \frac{\partial}{\partial X} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dX + \left. \frac{\partial}{\partial Y} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dY + \left. \frac{\partial}{\partial Z} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dZ + c\Delta t \\ &= \hat{r}_i + \left. \frac{\partial}{\partial X} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dX + \left. \frac{\partial}{\partial Y} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dY + \left. \frac{\partial}{\partial Z} \right|_{(X_0, Y_0, Z_0, \Delta t_0)} dZ + c\Delta t \end{aligned}$$

where the estimated ranges are computed as

$$\hat{r}_i = \sqrt{(x_i - X_0)^2 + (y_i - Y_0)^2 + (z_i - Z_0)^2}.$$

15

and the partial derivatives are given by

$$\begin{aligned} 20 \quad \frac{\partial R}{\partial x} &= \frac{\partial r}{\partial x} = (x_i - X) / \hat{r}_i & \frac{\partial R}{\partial \Delta t} &= c \\ \frac{\partial R}{\partial y} &= \frac{\partial r}{\partial y} = (y_i - Y) / \hat{r}_i \\ \frac{\partial R}{\partial z} &= \frac{\partial r}{\partial z} = (z_i - Z) / \hat{r}_i. \end{aligned}$$

In this embodiment, four linear equations with four unknowns are shown.

Additional range estimates would produce more rows in the matrix. The result is the set of

25 equations

$$\begin{bmatrix} (x_1 - X_0)/\hat{r}_1 & (y_1 - Y_0)/\hat{r}_1 & (z_1 - Z_0)/\hat{r}_1 & 1 \\ (x_2 - X_0)/\hat{r}_2 & (y_2 - Y_0)/\hat{r}_2 & (z_2 - Z_0)/\hat{r}_2 & 1 \\ (x_3 - X_0)/\hat{r}_3 & (y_3 - Y_0)/\hat{r}_3 & (z_3 - Z_0)/\hat{r}_3 & 1 \\ 0 & 0 & 1 & 0 \end{bmatrix} \times \begin{bmatrix} \delta X \\ \delta Y \\ \delta Z \\ c \delta \Delta t \end{bmatrix} = \begin{bmatrix} R_1 - \hat{r}_1 \\ R_2 - \hat{r}_2 \\ R_3 - \hat{r}_3 \\ z_b - Z_0 \end{bmatrix}$$

The last row of the observation matrix represents the barometric altimeter measurement.

The column of three 1 represents the same time bias on all three ranges. These equation are

5 in the form of $Ax = b$. The solution $x = A^{-1} * b$. Note that in the absence of a barometer measurement, one more additional measurement would add an additional row similar to rows 1 to 3 of the matrix above. This additional measurement would enable estimation of the altitude of the receiver. Note that when there are more measurements available than the number of unknowns, then the solution would be based on the pseudoinverse of A given by

10 $A_{+} = (A^T A)^{-1} A^T$ and the least square solution is given by $x = A_{+}^{-1} b$. When the quality of measurements are not equal, the optimal way of solving the equations $Ax=b$ in the least square sense is to use a weight proportional to the SNR for the error from each equation. This leads to a solution $x = A_{+}^{-1} b$ with $A_{+} = (A^T W A)^{-1} A^T W$. The diagonal weighting matrix W formed by the weight proportional to the noise variance of the measurements. The

15 solution of these equations produces a delta correction to the X, Y, Z and delta time estimates, such that

$$\begin{bmatrix} X_1 \\ Y_1 \\ Z_1 \\ \Delta t_1 \end{bmatrix} = \begin{bmatrix} X_0 \\ Y_0 \\ Z_0 \\ \Delta t_0 \end{bmatrix} + \begin{bmatrix} \delta X \\ \delta Y \\ \delta Z \\ \delta \Delta t \end{bmatrix}.$$

20 This completes the first iteration of the method. The updated position and time bias estimates replace initial guess and the algorithm continue until the delta parameters are below some threshold value. A typical stopping point would be for the norm of the delta values are below a certain threshold (for example, one meter).

25 The system of linearized equations in the GPS is solved using least squares and an initial guess about the location of the user such that the algorithm converges to the final

user location. The linearization is based on the fundamental assumption that the distance between the satellites and the user position is larger than the distance between the user position on the earth and the guessed position. For the same set of equations to work in a terrestrial environment (with small geometry), the initial guess can be based on the

- 5 centroid (as above), a point close to the transmitter from which the received signal is the strongest, or obtained by a direct method which gives a closed form solution by means of a sequence of formulae with no iterations. When the initial guess is a centroid or a point close to the transmitter from which the received signal is the strongest, the initial guess is improved using a least squares method. When the initial guess is obtained by a direct
- 10 method which gives a closed form solution by means of a sequence of formulae with no iterations, the initial solution itself is the final solution and it is improved using least squares only when there are more measurements (and hence equations) than unknowns with individual measurements weighted by using the expected errors in those measurements (which are obtained from such parameters as signal strength and elevation
- 15 angle). Further, if a sequence of measurements is to be processed in time, a solution obtained as above may be fed to a Kalman filter to obtain an optimal solution "trajectory".

Another approach that overcomes the linearization problem in terrestrial cases involves formulating the set of equations as a non-linear minimization problem (specifically as a weighted non-linear least squares problem). Specifically, the non-linear 20 objective function to be minimized is defined as

$$f(X, Y, Z, \Delta t) = \sum_{i=0}^{N-1} W_i \times \left[R_i - \sqrt{(x_i - X)^2 + (y_i - Y)^2 + (z_i - Z)^2} - \Delta t \right]^2$$

The weights W_i are chosen to be inversely proportional to the SNR of the measured ranges R_i . The best estimate of the receiver location is obtained as the set of $(X, Y, Z, \Delta t)$ that minimizes the objective function. When barometer or other altitude aiding is available then 25 the objective function gets modified to

$$f(X, Y, Z = Z_{baro}, \Delta t) = \sum_{i=0}^{N-1} W_i \times \left[R_i - \sqrt{(x_i - X)^2 + (y_i - Y)^2 + (z_i - Z_{baro})^2} - \Delta t \right]^2$$

The position solution based on this method will be more stable and robust, particularly under small geometry terrestrial system configuration. In this configuration,

small changes in receiver coordinates significantly changes the observation matrix and sometimes leads to lack of convergence of the linearized iterations. Convergence to a local minimum or divergence occurs more often due to residual bias in the measurements which affects the shape of the objective function so that local minima can be present. Residual bias can be quite common in indoor/urban canyon environments. The non-linear formulation above makes the position algorithm robust to measurement bias besides overcoming the small geometry linearization problem.

One approach to perform the minimization of the function f to obtain optimal X, Y, Z is to use a genetic algorithm (such as differential evolution) to find the global minimum of the function. The use of such an algorithm enables the solution to avoid local minima that occur in small geometry terrestrial positioning when multi-path bias is present in the range measurements.

Irrespective of whether linearized least squares or non-linear least squares method is used to solve the pseudo-range measurement equations, it is important for a quality metric to be provided along with a position estimate. The position quality metric should be a function of the pseudo-range measurement equation residuals, the quality of the measurements as well as the geometry of the towers relative to the estimated position. The pseudo-range measurement residual for the i th tower measurement is given by

$$PR_{res,i} = R_i - \sqrt{(x_i - X)^2 + (y_i - Y)^2 + (z_i - Z)^2 + c \Delta t}$$

The average weighted rms pseudo-range residual is given by

$$PR_{res} = \sqrt{\frac{\sum_i W_i \times PR_{res,i}^2}{\sum_i W_i}}$$

The HDOP, VDOP, PDOP are defined from the diagonal elements of $H = (A^T A)^{-1} A^T$ as

$$HDOP = \sqrt{H(1,1) + H(2,2)}$$

$$VDOP = H(3,3)$$

$$PDOP = \sqrt{H(1,1) + H(2,2) + H(3,3)}$$

The pseudo-range RMS (root-mean-square) error at a particular SNR is given by

$$PRE_{th} = f(\sqrt{SNR})$$

where f is generally a non-linear monotonic decreasing function of its argument. The function f can be derived analytically for a particular receiver configuration as a function of signal BW and receiver BW or alternatively, found from simulation as a table mapping SNR to range error.

The quality metric for 2-D position is defined as

$$QM_{2-D} = HDOP \times \sqrt{PR_{res}^2 + PRE_{th}^2} \times \alpha$$

Similarly, the quality metric for the altitude and 3-D position is given by

$$QM_{alt} = VDOP \times \sqrt{PR_{res}^2 + PRE_{th}^2} \times \alpha$$

$$QM_{3-D} = PDOP \times \sqrt{PR_{res}^2 + PRE_{th}^2} \times \alpha$$

The quantity α is chosen based on the level of confidence desired. For example, a value of 3 would be used to obtain 95% confidence, while a value of 1 would be used for 68% confidence.

Another method of positioning using the WAPS system involves the use of a WAPS reference receiver in a differential scheme. As shown in "Differential Wide Area Positioning System" and discussed in the context of timing synchronization, the time-stamped reference receiver measurements along with the latitude, longitude, altitude of the WAPS towers and the reference receiver can be used to determine the timing delta between WAPS tower transmissions at the specific time-stamp. Once the timing delta between transmitters is known, the range equations can be reduced to have a single common time bias again. The WAPS receiver then can avoid demodulation of the WAPS data stream (for example, to extract the timing corrections from the data stream). The WAPS receiver measurements can be sent to the server and the position can then be computed at the server or, alternatively, the reference receiver measurements can be relayed to the WAPS receiver and the position can be computed there. It is assumed that the latitude, longitude and altitude of the WAPS towers is already known/available for use in the position computation. In the case that the WAPS data stream is secure, this

differential system can avoid the need to extract data from the secure data stream for timing correction purposes.

Another alternative method for obtaining positioning from the WAPS system uses RSSI finger-printing techniques. A database of WAPS tower transmit powers/locations and RSSI levels is built up for a given target area based on training measurements in the area for which positioning is required. Note that RSSI database can also be augmented with Angle of Arrival (AOA) information to improve the solution. The WAPS receiver RSSI measurements (and possibly AOA measurements) are then used to look up this database to obtain a location estimate. An alternative method of using the WAPS RSSI measurements would be to translate the measurements into a range estimate using a propagation model (or simple extrapolation/interpolation techniques) and then use tri-lateration to determine the position. Note that the RSSI measurements in these finger-printing techniques can be replaced by any other measurements that can be translated to range.

An alternative method of computing position using the WAPS infrastructure uses a blind method for obtaining positioning from the WAPS system without prior knowledge of the WAPS tower locations. In this method, the approximate location of the WAPS towers are determined by field measurement (for example, by measuring RSSI from many angles around the WAPS tower at GNSS tagged locations and then using a weighted average based on RSSI of these locations to estimate WAPS tower locations). Then, any of the RSSI finger-printing methods can be used to determine position (for example, as described in the above paragraph).

An alternative method of computing position using the WAPS infrastructure can be used for computing position offline. The position computation involves storing the sample segments of the WAPS signal (for example, the stored data maybe I data at low IF or IQ data at baseband) from the WAPS receiver along with optionally an approximate position and a WAPS time tag. Note that it is enough to store enough samples to be able to acquire the signal. The samples are processed at a later time to search, acquire and compute range to WAPS towers. The method may use offline data to look-up tower locations and timing correction information that may be stored in a central database on a server. This method of offline position computation provides the ability to support WAPS positioning at the cost

of only memory on the device. The other advantage of this method is the time taken for storing the WAPS IQ data is very short, making it convenient for applications that need to tag position quickly, but the exact position is not required instantaneously. One possible application for this method can be for geo-tagging of photographs.

5 Another approach to positioning uses carrier phase measurements in addition to the code phase measurements indicated above. The carrier phase measurements can be written as:

$$\phi_i(t_0) = r_i(t_0) + N_i \lambda + \Delta t$$

Various techniques can be used to resolve the integer ambiguity N_i in the carrier phase

10 measurements. Code phase measurements, measurements at multiple frequencies and/or other methods can be used to resolve the ambiguities. Subsequently, the carrier phase measurements at time t_k can provide accurate tracking of position starting from an accurate initial position. The carrier phase measurements at future times can be written as

$$\phi_i(t_k) = r_i(t_k) + N_i \lambda + \Delta t$$

15 The N_i do not change as long as the carrier phase measurements do not have cycle slips (i.e. the signals should be tracked with continuous phase lock) and the new locations can be computed using least squares. Alternatively, these measurements can be used in a Kalman filter to update the new position state. If phase lock is lost, new values of integer ambiguity need to be calculated.

20 Another approach uses differential positioning relative to a reference receiver as described above. Differential positioning can be done using either code or carrier measurements or a combination of both. Single difference observables are computed for code and carrier phase by subtracting measurements of the same towers from reference receiver r and receiver s as

$$25 \quad R_{sr}^i = \underbrace{\rho_s^i - \rho_r^i}_{\text{geometrical range difference}} + \underbrace{c(dt_s - dt_r)}_{\text{time difference between clocks}} + (c_{R,s} - c_{R,r})$$

$$\Phi_{sr}^i = \underbrace{\rho_s^i - \rho_r^i}_{\text{geometrical range difference}} + \underbrace{c(dt_s - dt_r)}_{\text{time difference between clocks}} + \underbrace{\lambda(N_s^i - N_r^i)}_{\text{integer ambiguity in phase measurement}} + (\varepsilon_{\phi,s} - \varepsilon_{\phi,r}).$$

Note that any timing error in the transmitter does not appear in these observables and thus allows position solutions even when the system is asynchronous or imperfectly synchronized. In addition, any tropospheric delay error in measurements nearly cancels out since the tropospheric delay is likely to be correlated in the local area for short

5 baselines (e.g., distances between reference receiver r and receiver s). A communication channel is used to send the range and carrier measurements from the reference receiver r to the receiver s for position computation. Or, alternatively, the receiver s and receiver r need to communicate the range and carrier to the server for position computation.

In any position solution method, the height of a receiver can be determined using
10 placement on a terrain map or barometric sensing. Using placement on a map, during trilateration the location of the user can be constrained to be on a terrain based on a terrain database and the height of the user determined. The height of the user can also be constrained to be within a certain height above the terrain. For example, based on the tallest building in the area, the maximum altitude above terrain can be constrained. This type of
15 constraint can improve the quality of the height solution (for example, by eliminating the ambiguous solution that is sometimes produced when using biased range measurements).

In addition, if indoor building maps are available, the information (along with
10 associated constraints on possible user locations) can be used to aid the position solution. For example, physical restrictions can be used to constrain the user motion model, and
15 thereby improve the quality of the tracking Kalman position filter. Another usage of building maps is to determine/estimate the quality of a particular tower's range measurement based on the physical environment from the tower to the indoor location. A better estimate of range quality can be used to weight the position computation leading to better position estimates.

20 When using a barometric sensor, a calibrated barometric sensor can be used to measure the pressure differences as the receiver terminal is moved up or down in altitude. This is compared with a calibrated value for the pressure on different altitudes or an average value to determine the height of the receiver.

25 In computing the position solution, when additional measurements greater than the
30 minimum three measurements required for two-dimensional position are available,

receiver integrity monitoring based on a check of consistency of measurements is used to eliminate “outlier” measurements. The “outlier” measurements could be due to loss of timing synchronization at the transmitter or due to the channel effects such as multipath.

5 ALTIMETER-BASED APPROACH FOR DETERMINING ELEVATION

The WAPS system of an embodiment includes altimeters (pressure sensor) to aid in the determination of user elevation. The only information available from a pressure sensor is the atmospheric pressure at the time and place of the measurement. In order to translate this into an estimate of the elevation of the sensor, a number of additional pieces of

10 information are required. There is a standard formula for relating pressure to elevation, based upon the weight of a column of air, as follows:

$$z_1 - z_2 = -\frac{RT}{g} \ln\left(\frac{P_1}{P_2}\right)$$

where z_1 and z_2 are two elevations, and P_1 and P_2 are the pressures at those elevations, and T is the temperature of the air (in K). $R = 287.052 \text{ m}^2/\text{Ks}^2$ is the gas constant and

15 $g = 9.80665 \text{ m/s}^2$ is the acceleration due to gravity. Note that this formula provides relative information, determining the difference in elevation for a difference in pressure. This formula is generally used with $z_2 = 0$, so that P_2 is the sea level pressure. Because sea level air pressure varies significantly with weather conditions and with location, the sea level pressure is needed in addition to the temperature and pressure at the site where elevation is

20 to be determined. When applying standard atmosphere conditions, with $T = 15 \text{ C}$ and $P = 101,325 \text{ Pa}$, it is found that a 1 m increase in elevation corresponds to a 12.01 Pa decrease in pressure.

Thus, to determine elevation with a resolution of 1 m, sea level pressure must be known with accuracy significantly finer than 36 Pa. It is also worth noting that because T is measured in Kelvin, a 3° C (or K) error in temperature will correspond to approximately a 1% error in elevation. This can become significant when determining elevation significantly above sea level, and when trying to resolve upper floors in a high rise building. Thus, for determining elevation with a resolution of 1m, pressure sensors with high accuracy and resolution are needed. In order to fit in a mobile device, these sensors

should be low cost, low power and small size. Note that commercial weather grade sensors do not provide this level of accuracy or resolution and are not updated at a rate required for determining elevation.

The key to determining elevation to 1 m accuracy is to have a system for providing 5 reference pressure information that is local enough and accurate enough. It must be able to provide measurements that are close to the unknown location in temperature, and close in distance and time – to capture changing weather conditions; and finally, must be sufficiently accurate. Thus, the elevation determining system of an embodiment includes but is not limited to the following elements: a mobile sensor that determines pressure and 10 temperature at the unknown location with sufficient accuracy; an array of reference sensors that determine pressure and temperature at known locations with sufficient accuracy, and are sufficiently close to the unknown location; an interpolation-based estimation algorithm which inputs all reference sensor data, reference sensor locations and other augmenting information, and generates an accurate reference pressure estimation at a location of 15 interest within the WAPS network; a communications link between the reference sensors and the mobile sensors to provide the reference information in a sufficiently timely fashion. Each of these elements is described in detail below.

Figure 27 is a block diagram of a reference elevation pressure system, under an embodiment. Generally, the reference elevation pressure system, or reference system, 20 includes a reference sensor array comprising at least one set of reference sensor units. Each set of reference sensor units includes at least one reference sensor unit positioned at a known location. The system also includes a remote receiver comprising or coupled to an atmospheric sensor that collects atmospheric data at a position of the remote receiver. A positioning application running on a processor is coupled to or is a component of the 25 remote receiver. The positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from the reference sensor unit(s) of the reference sensor array. The positioning application computes an elevation of the remote receiver using the reference pressure estimate.

More specifically, the reference elevation pressure system includes a mobile sensor 30 that determines pressure and temperature at the unknown location with sufficient accuracy,

and the mobile sensor is a component of or coupled to the remote receiver. The system includes a reference sensor array that comprises at least one reference sensor unit that accurately determines pressure and temperature at a known location that is appropriate to a location of the remote receiver. The reference sensor units communicate with the remote receiver and/or an intermediate device (e.g., server, repeater, etc.) (not shown) to provide the reference information. The system comprises a positioning application that, in an embodiment, is an interpolation-based estimation algorithm which inputs all reference sensor data, reference sensor locations and other augmenting information, and generates a relatively accurate reference pressure estimation at a location of interest. The positioning application can be a component of the remote receiver, can be hosted on a remote server or other processing device, or can be distributed between the remote receiver and a remote processing device.

Figure 28 is a block diagram of the WAPS integrating the reference elevation pressure system, under an embodiment. As described herein, the WAPS includes a network of synchronized beacons, receiver units that acquire and track the beacons and/or Global Positioning System (GPS) satellites (and optionally have a location computation engine), and a server that comprises an index of the towers, a billing interface, a proprietary encryption algorithm (and optionally a location computation engine). The system operates in the licensed/unlicensed bands of operation and transmits a proprietary waveform for the purposes of location and navigation purposes. The WAPS system can be used in conjunction with other positioning systems or sensor systems in order to provide more accurate location solutions. Note that the elevation of the remote receiver computed using the reference pressure estimate can be used either explicitly as an altitude estimate or implicitly to aid the position calculation in any position location system.

One example system integrates the reference elevation pressure system with the WAPS. Generally, the integrated system comprises a terrestrial transmitter network including transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a reference sensor array comprising at least one reference sensor unit positioned at a known

location. The remote receiver comprises or is coupled to an atmospheric sensor that collects atmospheric data at a position of the remote receiver. A positioning application running on a processor is coupled to or is a component of the remote receiver. The positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from a set of reference sensor units of the reference sensor array. The positioning application computes the position of the remote receiver, which includes an elevation, using the reference pressure estimate and information derived from at least one of the positioning signals and satellite signals that are signals of a satellite-based positioning system.

5 More specifically, this integrated system includes a mobile sensor that determines pressure and temperature at the unknown location with sufficient accuracy. The mobile sensor is a component of or coupled to the remote receiver, but is not so limited. The system includes a reference sensor array that comprises at least one reference sensor unit that accurately determines pressure and temperature at a known location that is appropriate to a location of the remote receiver. The reference sensor units communicate with the remote receiver and/or an intermediate device (e.g., server, repeater, etc.) (not shown) to provide the reference information. The reference sensor units can be collocated with one or more WAPS transmitters and/or can be separately located at other known locations. The system comprises a positioning application that, in an embodiment, is an

10 interpolation-based estimation algorithm which inputs all reference sensor data, reference sensor locations and other augmenting information, and generates a reference pressure estimation at a location of interest. The positioning application can be a component of the remote receiver, can be hosted on the WAPS server or other processing device, or can be distributed between the remote receiver and the WAPS server.

15

20 As noted above, the mobile sensor should be able to determine pressure with a resolution and accuracy that is significantly finer than 36 Pa. Many pressure sensors have built-in temperature sensors in order to provide compensation for non-ideal sensor performance, but due to self-heating effects, these sensors may not provide a sufficiently accurate measure of outside air temperature. Even in cases where accurate sensors are not

25 available commercially, if sensors with adequate resolution are available, they can be used

for the purposes of altitude estimation at the floor level. The mobile sensor of an embodiment determines the reference pressure data with a resolution approximately less than 36 Pascal, and determines the temperature data with a resolution at least one of equal to and less than approximately 3 degrees Celsius.

5 These sensors have inherent short term and long term stability issues which may be corrected by modest filtering techniques such as averaging a few samples. Each sensor may also have an offset that may vary with temperature which needs to be calibrated or compensated by means of a look up table, for example.

With sufficient calibration, these sensors should provide the accuracy needed.

10 Some sensors may also be sensitive to high rates of motion. Some heuristic rules may be used to limit use of pressure information when high velocities or acceleration are recognized. However, high velocities are rarely experienced in indoor environments. When traveling at high speeds, GPS positioning and map data will typically provide sufficient vertical position information.

15 It should also be noted that the sensor should be mounted in a manner that exposes it to outside air, but not wind, draft, or other air movement. A mounting or positioning internal to a typical consumer product should produce acceptable results. The battery compartment and connectors provide an indirect path for outside air to get to the sensor, while preventing any direct air movement. However, a water proof device would need 20 special provisions to provide the sensor with access to the outside.

The reference sensors will be deployed in much smaller volumes, and at dedicated sites, so relatively better accuracy can be obtained in the reference system, making it possible to allocate the bulk of the overall error budget to the mobile sensors. Existing markets for absolute pressure sensors, such as weather and aircraft altimeters, do not have 25 the same high accuracy requirements as the application of an embodiment. In the reference application, an embodiment uses multiple sensors, both for redundancy and for improved accuracy by averaging their measurements. In addition, the sensors may be packaged so as to limit the temperature range to which the sensor is exposed and optimally calibrate the sensor for this limited temperature range.

The reference system should average or otherwise filter individual measurements to improve accuracy with a time scale in the order of a few seconds to a few minutes. The height of the reference sensor should be measured to a 'cm' level accuracy; the outside air temperature should be continuously measured and logged; the sensor should be exposed to outside air in order to measure the air pressure, but must not be subject to wind, drafts, or other significant air movement (baffles or other packaging can be used to direct air along an indirect path to the sensor); the sensor should not be sealed in a water proof enclosure, as this can prevent measurement of outside air pressure. The reference sensor of an embodiment determines the reference pressure data with a resolution approximately less than 36 Pascal, and determines the temperature data with a resolution at least one of equal to and less than approximately 3 degrees Celsius.

An embodiment enables interpolation-based reference pressure estimation. Given the pressure and temperature measurements at each WAPS transmitter tower, as well as the tower location and other augmenting information, an embodiment predicts the sea level atmospheric pressure at the mobile user location as the reference value for user height estimation. Therefore, an atmospheric pressure surface gradient model is generated and the pressure measurements at each tower site serve as the sample data for local modification of the model. Therefore, this estimation algorithm calibrates comparable reference pressure accuracy at the user location as the direct measurements captured at the beacon tower.

A description of a formulation of this interpolation is described below. Within one of the WAPS network, given reference barometric pressure sensors at n transmitter towers, the equivalent sea level atmospheric pressure is estimated based on the reference sensor outputs. This is done in two steps, but is not so limited.

As a first step, given the reference sensor height h_i (in meters) above sea level at transmitter tower i , and the pressure p_i (in Pascal) and temperature T_i (in Kelvin) readings from the reference sensor, the equivalent sea level atmospheric pressure P_i (in Pascal) is calculated at location with latitude x_i and longitude y_i (in degrees), using the formula below:

$$P_i = p_i e^{\frac{gh_i}{RT_i}}$$

where g is the gravitational acceleration constant and R is the specific gas constant for air. As a second step, after calculating the equivalent sea level atmospheric pressures at all n transmitter locations of the WAPS network, and obtaining the latitude x_0 and longitude y_0

5 information of the user with WAPS, the equivalent sea level pressure is estimated at the user location P_0 with the formula below:

$$P_0 = \sum_{i=1}^n W_i P_i$$

where $W_i = W_i(x_0, y_0, x_i, y_i)$ is the weighting function depending on both the user location and the reference site i location.

10 The communications link of an embodiment provides the information used by the mobile sensor. An embodiment broadcasts pressure updates once every few seconds to few minutes but is not so limited.

If the reference system broadcasts reference information infrequently, the mobile unit performs at least one of the following: continuously monitors the broadcasts to receive 15 and store the last information in case it is needed before the next broadcast; waits for the next broadcast before computing a new elevation; “pulls” or queries the reference system for the latest information when needed. The Pull approach of an embodiment, rather than having the reference systems broadcast the information, minimizes system bandwidth. However, the Pull uses two-way communications between the reference system and the 20 mobile, and since multiple reference sites would be used for any mobile calculation, so it requires the mobile to determine which reference sites it should query. A good compromise to minimize monitoring by the mobile, while keeping latency low, has the reference system broadcast its data more frequently than the time it takes to update the measurement.

An embodiment includes two possible approaches for the information content. A 25 first approach has the mobile perform all of the calculations, in which case the information sent by the reference includes but is not limited to the following: reference location (latitude and longitude) with one meter accuracy; height of reference sensor with 0.1-0.2 m accuracy; measured temperature of air at reference site (after some filtering); measured

pressure of air at reference site (after filtering, sensor temperature compensation, and any other local calibration such as offset), with one Pa accuracy; and a measure of confidence.

Alternatively, the reference site can use its temperature and pressure measurements to compute an equivalent sea level pressure. If this approach is used, the list of information

5 to be broadcast includes but is not limited to the following: reference location (latitude and longitude) with one meter accuracy; height of reference sensor with 0.1-0.2 m accuracy; computed equivalent sea level pressure at reference site (with one Pa accuracy); a measure of confidence.

An embodiment also reduces the bits of data transmitted but broadcasts each piece

10 of data relative to some known constant. For example, the reference sites are relatively close to the mobile site, so only the fractional degrees of latitude and longitude may be transmitted, leaving the integer part to be assumed. Similarly, air pressure, although typically on the order of 10^5 Pascals, only varies by a few thousand Pa from the standard atmosphere. Thus, an embodiment broadcasts the offset from standard atmospheric

15 pressure to reduce the bandwidth over broadcasting the absolute pressure.

Latitude and longitude, as obtained from GPS or similar systems, are not particularly useful in urban applications. Instead a database is needed to map latitude and longitude into street addresses. Elevation has a similar limitation in the vertical dimension.

20 The useful parameter is which floor a person is on. This can be determined accurately from elevation information if there is access to a database of the ground level elevation and the height of each floor in a building. For low buildings up to approximately 3 stories, it may be sufficient to know ground level elevation from mapping or similar databases, and estimate floor height. For taller buildings more accurate information about floor height will be needed.

25 This presents an opportunity to implement smart learning algorithms. For example, one can assume that cell phones will be carried between 1 m and 2 m from the floor. Thus, the system of an embodiment can accumulate the elevations of many cell phones in a building, wherein the data is expected to cluster around 1.5 m from each floor. With enough data, it is possible to develop confidence as to the height of each floor in the

30 building. Thus, the database could be learned and refined over time. Such an algorithm

becomes more complicated in buildings with ramps, or mezzanines between floors, but may still generate useful data for the majority of buildings.

The sensor offsets, and potentially other parameters, can be calibrated at the time of manufacture. This should be possible by cycling the sensors through a range of

- 5 temperature and pressure with a known good sensor providing reference information. It is likely that these calibration parameters will slowly drift with age. Therefore, an embodiment uses an algorithm to gradually update the calibration over time (e.g., algorithm recognizes when a sensor is stationary at a known height and updates the calibration table under those conditions).
- 10 In addition to the general application of determining a person's location, an embodiment may include specialized applications that use more precise relative elevation information, while not needing absolute elevation information. For example, finding a downed firefighter in a building requires that the position of the downed person relative to the rescue party be known precisely, but neither absolute position is as important.
- 15 Additional precision in relative positioning would be possible by having an extra manual step at the beginning of the application. For example, all firefighters could initialize their trackers at a known location, such as the entrance to the building, before they enter. Their position relative to that point, and thus relative to each other could be determined quite accurately for a period of time, even if absolute elevation is not accurate, and weather
- 20 related pressure changes cannot be completely compensated for. Similarly, a shopping related application that requires more precision than available from the absolute measurements could be implemented by having the user press a button at a known point in the mall. Their position relative to that point could then be determined quite accurately for a period of time.
- 25 Alternatively, a mobile beacon can be utilized as a local reference to provide more accuracy in a particular location. For example, a shopping mall could have its own reference sensor, to provide more accuracy within the mall. Similarly, a fire truck could be equipped with a reference sensor to provide local reference information at the scene of a fire.

Low cost pressure sensors have a problem in that they have an offset from the correct reading. Experiments have shown that this offset is quite stable on time scales of weeks to months. However, it is likely that this offset will slowly drift with time over a period of many months to years. While it is straightforward to measure this offset, and 5 compensate for it at the time of manufacture, it is unlikely that the compensation will stay accurate for the life of the product. Therefore, a means of recalibrating in the field is required.

The sensor of an embodiment can be recalibrated if it is at a known elevation and the atmospheric pressure is known. The embodiment identifies practical situations where 10 the sensor will be at a known elevation. For example, if the sensor is in a device that has GPS capability, and the GPS satellites are being received with high signal strength, the GPS derived altitude should be quite accurate. Accumulating the deviations from GPS altitude over time, under good signal conditions, can provide an estimate of the correction needed to the sensor calibration.

15 Similarly, the sensor system can learn the user's habits and use this information to later correct the calibration. For example, if the user consistently places her phone in one place at night, the sensor can start tracking the altitude at this location, perhaps at specific times, such as late night. Initially, these values would be accumulated and stored as the true altitude at that location. After several months, when the sensor determines that it is in the 20 same location at the same time of night, it could start to track deviations from the true altitude determined earlier. These deviations could then be accumulated to slowly generate a correction to the calibration. Because these approaches also use knowledge of current atmospheric pressure, they use reference pressure measurements provided by the WAPS network.

25 The standard process for determining altitude from pressure readings involves converting the measurements at a reference location to the equivalent sea level pressure, and then using that to determine the altitude of the unknown pressure sensor. The standard formula is:

$$z = -\frac{RT}{g} \ln\left(\frac{P}{P_0}\right)$$

Note that a minus sign has been added, since height is conventionally measured as positive moving away from the surface of the earth. In addition, the logarithm has been corrected to 'ln' since this is a natural logarithm. This formula relates, z , the height above sea level, to the atmospheric temperature (T) and pressure (P) at that point, and the sea level air pressure (P_0) below that point.

5 One additional problem with applying this formula is that the height is directly proportional to the temperature, a measured quantity not known precisely. This means that a 1% error in temperature will result in a 1% error in height. When used near sea level this will not be a significant problem. However, when this formula is applied in tall buildings
 10 and especially in higher elevation areas, such as Denver, a 1% error in height may be significant when attempting to resolve floor level elevation. For example, the elevation of Denver is about 1608 m. Thus, a 1% error in temperature will result in an error in height above sea level of 16 m. This is nearly 5 floors.

One way to avoid this sensitivity to temperature accuracy is to recognize that the
 15 formula above is actually a relative formula. That is the formula can be generalized to:

$$z_1 - z_2 = -\frac{RT}{g} \ln\left(\frac{P_1}{P_2}\right)$$

where z_1 and z_2 are any two elevations, and P_1 and P_2 are the pressures at those elevations. It was only a matter of convention that z_2 was set to 0, and thus P_2 became the sea level
 20 pressure.

Instead of using sea level as the reference point, any convenient elevation could be used. For example, the mean elevation of the city would be reasonable, or the mean elevation of the reference sensors used for collecting pressure data would work. As long as a reference elevation is used that keeps the height differences small, the impact of
 25 temperature error will be insignificant. The only requirement is that all devices involved in the system know what reference elevation is being used.

There is a standard formula that relates elevation of a point above the earth (z), the atmospheric temperature (T) and pressure (P) at that point, and the sea level air pressure (P_0) below that point as

$$z = \frac{RT}{g} \log\left(\frac{P}{P_0}\right)$$

This formula assumes that there is a column of air at constant temperature between sea level and the point of interest. Therefore, the sea level pressure used is a virtual construct, and not necessarily the real pressure at sea level, since the point of interest may not be near a true sea level.

5 The standard process for determining elevation of an object is a two step process. First sea level pressure is determined by measuring temperature and pressure at a point of known elevation, and then inverting this formula to solve for P_0 . Next, the temperature and pressure at the point of unknown elevation are measured, and this formula is applied to 10 determine the unknown elevation.

Implicit in this process is the assumption that only parameter of interest is the height of other objects above the same horizontal location, as is typical for aircraft approaching an airfield, using measurements at the airfield for reference. Typically, people interested in height determination for other purposes have extended this concept to 15 determining the height in the general vicinity of a reference location, but not directly above it. This extension assumes that the sea level pressure does not change between the location of interest in the vicinity and the reference location.

Thus, there are three assumptions in this process. A first assumption is that the 20 temperature is constant from the reference location to the virtual sea level point below it. A second assumption is that the temperature is constant from the point of interest to the virtual sea level point below it. A third assumption is that the sea level pressure is the same at the reference location and the point of interest. However, since sea level pressure depends upon temperature, assuming that the sea level pressure is the same at two locations implies that the temperature is the same at those locations. Thus, if different temperatures 25 are measured at the reference location and point of interest, one of these assumptions has been violated. Measurements have shown that even over distances of a few kilometers, there are differences in temperature and in pressure that can be significant for elevation determination.

The assumption of constant temperature over elevation changes at a given location is part of the equilibrium model for the atmosphere, and is probably necessary. The only alternative would be a full dynamic model of the atmosphere, including the effects of wind, surface heating, convection, and turbulence. Atmospheric data suggest that at least on large 5 distance scales, the constant temperature model is a very good approximation at elevations below 1 km. At higher elevations, a linear lapse rate is often applied.

An embodiment relaxes the assumption of constant sea level pressure between the reference location and the point of interest. A first approach of an embodiment takes the sea level pressure for the reference location determined as above, but further applies the 10 ideal gas law to convert this to a sea level pressure at a standard temperature. Then assume that this sea level pressure at a standard temperature would be the same at the point of interest. The temperature at the new location would then be used to convert this to the sea level pressure for that location, and then apply the formula above to determine the elevation.

15 A second approach of an embodiment uses a network of reference locations to determine the variation of equivalent sea level pressure with horizontal location in real time. These multiple measurements are then combined to determine a best estimate of the sea level pressure at the point of interest. There are at least two possible ways of determining the best estimate: a weighted average approach in which the weighting is a 20 function of the horizontal distance from the particular reference point to the point of interest; a least square fit to create a second order surface that best fits the computed sea level pressures at the reference locations and can then be used to interpolate an estimate of the sea level pressure at the point of interest.

The two approaches described above can also be combined. That is, at each 25 reference location the sea level pressure at standard temperature is determined, and these data are combined using one of the techniques above to generate a best estimate of the sea level pressure at standard temperature at the point of interest.

Additionally, when using the altimeter, an embodiment recognizes sudden movements in pressure such as the air conditioner changing state (e.g., turning ON, etc.) or

windows opening in a car by using application level data into the hardware or software filters that operate continuously on the location and altimeter data.

Further, a wind gauge can be used at the beacon to determine the direction of the wind flow, which is believed to be a indicator of atmospheric pressure gradient. A wind 5 gauge along with a compass can be used to determine the precise direction and level of wind flow which can then be used to correct and/or filter our variations in the user's sensor.

The per floor height of a given building can be determined by various methods including but not limited to a user walking the building through the stairs and collecting information about each floor, ramps etc. In addition an electronic diagram can be used to 10 determine the relative height of each floor.

When the height is estimated based on either WAPS or the altimeter, information such as terrain, height of the building, height of surrounding buildings, etc. can be used to constrain the height solution.

Once an average pressure is known at a given location, along with historical 15 reference pressure data collected from the reference sensors over a long period of time (days, months, year), it can be used to predictably determine the height based on the pressure at that location (without calibration or user input).

In one embodiment, the height of the user can be computed on a remote server by using the data from the user's sensor and combining it with the data from reference sensors.

20 In this method, other information such as building information, crowd sourced information, etc. can also be used to determine the user's precise altitude.

In case a user is in close proximity to another user whose height is known, this information can be used to determine the unknown user's height.

25 In one embodiment of the network, the reference sensors need not necessarily be co-located with the WAPS beacon. A finer or a coarser grid of independent sensors with data connection to the server can be used for reference pressure measurement. The centralized server can either send reference pressure information to the mobile or can instruct the transmitters with data that needs to be sent to the mobile as a part of the WAPS data stream.

In another embodiment, the WAPS system uses an additional simplified beacon (supplemental beacon) that provides additional sensor information such as pressure, temperature in a smaller area such as a building. This transmission may be synchronous or asynchronous to the main WAPS timing beacons. Additionally, the supplemental beacon 5 may either upload the sensor data to a centralized server from which it is disseminated to the mobile units or transmit the data over a predefined set of PRN codes which can be demodulated by the WAPS mobile receiver.

The reference pressure network can be optimized based on accuracy requirements and historic pressure variation data for a given local area. For example, in cases where very 10 accurate measurement is a must, a reference sensor can be deployed in that building or a mall.

The WAPS beacon network along with the reference pressure data forms a close network of accurate pressure and temperature measurement with very short time intervals which can be harnessed by other applications such as geodesy.

15 The rate of change of pressure combined with data from other sensors can be used to determine vertical velocity which can then be used to determine if a user went through an elevator. This can be very useful in emergency situations and/or tracking applications.

In cases of sensors with lower resolution than needed to estimate floor height, under static conditions, averaging the pressure measurements over time can be used to 20 obtain the user height based on reference data.

HYBRID POSITIONING AND INFORMATION EXCHANGE WITH OTHER SYSTEMS

The system of an embodiment can be combined with any 'signal of opportunity', in 25 order to provide positioning. Examples of a signal of opportunity include, but are not limited to, one or more of the following: GPS receivers; Galileo; Glonass; Analog or Digital TV Signal; signals from systems such as MediaFLO, Wi-Fi; FM signals; WiMax; cellular (UMTS, LTE, CDMA, GSM etc); bluetooth, and, LORAN and e-LORAN receivers.

Regardless of signal type, the signal of opportunity provides a range measurement or a proxy for a range measurement, such as signal strength. This proxy for a range is weighed and combined appropriately to get an estimate for the location. The weighting may use the signal-to-noise ratio (SNR) of the received signals or, alternatively, use a metric that defines the environment of the receiver (e.g., knowledge of urban, suburban, rural environment from assistance data, whether the receiver is indoor or outdoor based on input from the application). This is typically done in those environments where the system of an embodiment is unavailable or signal coverage is limited. When using the SNR for a weight for a particular measurement the weight may simply be an inverse function of the SNR (or any other function that provides lower weight to signals with lower SNR) to allow optimal combination of the WAPS measurements as well as other system measurements to obtain a position. The final positioning solution may be calculated either by taking range measurements from the additional signal sources and combining with the WAPS range measurements and deriving a position solution for latitude, longitude and height, or by taking the position measurements from the additional sources/devices and the position measurements from the WAPS system and providing an optimized location solution using a combination of these location measurements based on the position quality metric from different systems. The various configurations of obtaining a hybrid solution using WAPS measurements/WAPS position estimates are shown in **Figure 29**, **Figure 30**, and **Figure 31**. Any of the architectures described below can be selected for use depending on the hardware and software partitioning of the system.

Figure 29 is a block diagram of hybrid position estimation using range measurements from various systems, under an embodiment. The range measurements (along with associated range quality metrics) are used from GNSS and other positioning systems and combined in a single optimal position solution by a hybrid position engine. This architecture is the most optimal in terms of using the available data to get the best position estimate out of them.

Figure 30 is a block diagram of hybrid position estimation using position estimates from various systems, under an embodiment. Independent position estimates from different systems along with position quality are used to choose the one with the best

quality. This architecture is the easiest to implement and integrate since the different positioning system are well isolated.

Figure 31 is a block diagram of hybrid position estimation using a combination of range and position estimates from various systems, under an embodiment. For example, a 5 position estimate from a WLAN positioning system can be compared with position estimate from range measurements from GNSS and WAPS systems to arrive at the best solution.

Inertial Navigation Sensors (INS) such as accelerometers and gyros, magnetic sensors such as e-compass, pressure sensors such as altimeters can be used to provide 10 location aiding information (referred to as loose coupling) or raw sensor measurements (referred to as tight coupling) to the WAPS system for usage in tracking mode.

An accelerometer can be used in the receiver of an embodiment to determine a frequency for updating the position reporting to the server. A combination of sequence of position solutions and accelerometer measurements can be used to detect static position, 15 constant velocity and/or other movement. This movement data or information can then be used to determine the frequency of the updates such that, for example, when there is non-uniform motion the frequency of updates can be set to a relatively high frequency, and when the receiver is at a constant velocity or stationary for a pre-determined period of time the frequency of the updates can be reduced to save power.

20 The sensor or position measurements can be combined into a position solution in a position filter (such as a Kalman filter). Two types of tight coupling architectures, where the sensor measurements are combined with GNSS and WAPS measurements in the WAPS hybrid position engine, are illustrated in Figure 32 and Figure 33. Figure 32 is a flow diagram for determining a hybrid position solution in which position/velocity 25 estimates from the WAPS/GNSS systems are fed back to help calibrate the drifting bias of the sensors at times when the quality of the GNSS/WAPS position and/or velocity estimates are good, under an embodiment. This architecture simplifies the algorithm formulation by partitioning the sensor calibration and position calculation parts of the algorithm. However, the drawback of this method is the complexity in deciding when are 30 the good times to re-calibrate the sensors using WAPS/GNSS estimates.

Figure 33 is a flow diagram for determining a hybrid position solution in which sensor parameters (such as bias, scale and drift) are estimated as part of the position/velocity computation in the GNSS and/or WAPS units without need for explicit feedback, under an embodiment. For example, the sensor parameters can be included as 5 part of the state vector of the Kalman filter used for tracking the position/ velocity of the receiver. This architecture provides an optimal solution in that the information is used in one combined filter to update both position and sensor parameters.

Loose coupling is illustrated in **Figure 34** and **Figure 35** where a selection unit selects between position estimate from the GNSS engine and the WAPS engine. Note that 10 10 the selection unit may be part of the WAPS or GNSS position units. **Figure 34** is a flow diagram for determining a hybrid position solution in which sensor calibration is separated from the individual position computation units, under an embodiment. **Figure 35** is a flow diagram for determining a hybrid position solution in which the sensor parameter estimation is done as part of the state of the individual position computation units, under an 15 embodiment.

The loose coupling methods are generally worse than the tight coupling methods since a selection uses information only from one system. Amongst loose coupling or tight coupling methods, the method that uses the ranges along with raw sensor measurements to determine position and sensor parameters in one optimal filter are better than when sensor 20 parameters and position are computed separately. As a result, the preferred method from a performance perspective is the tight coupling system with implicit sensor parameter estimation. However, depending on the hardware / software platform partitioning, one or more of these methods may be easily implemented and may be selected for that reason.

Information can also be exchanged between the WAPS system and other 25 transceiver systems on the same platform (such as cell-phone, laptop, PND). The transceiver systems can be, for example, Bluetooth transceiver, WLAN transceiver, FM receiver/transmitter, digital or analog TV system, MediaFLO, satellite communication system such as XM radio/Iridium, Cellular modem transceivers such as GSM/ UMTS/ cdma2000 1x/EVDO or WiMax). **Figure 36** shows the exchange of information between 30 the WAPS and other systems, under an embodiment. The exchange of information

between systems can improve the performance of either system. Since the WAPS system time is aligned to GPS time, the WAPS system can provide good quality timing and frequency estimates to any other system. Time and frequency estimates into the WAPS system can reduce the WAPS acquisition search space in code and frequency. In addition,

- 5 the WAPS system can provide location information to the other transceiver systems. Similarly, if the other system has location information (partial position eg. Altitude or 2-D position, or full position eg. 3-D position or raw range/pseudo-range/range-difference) available, that location information can be provided with or without a location quality metric to the WAPS system. The range/pseudo-range data should be provided along with
- 10 the location of transmitter (or other means to compute the range from the transmitter location to any receiver location) to enable usage of this range information in a hybrid solution. The range difference corresponding to two transmitters should be provided along with location of the two transmitters. The WAPS system will use the information to aid its position solution. Alternatively, location information can be provided in the form of ranges
- 15 (or pseudo-ranges) from known transmitter locations to the receiver device. These ranges (or pseudo-ranges) would be combined with WAPS ranges by the positioning algorithm to compute a hybrid position.

Examples of specific systems and information that can be exchanged between them are shown in **Figure 37**, **Figure 38**, and **Figure 39**.

- 20 **Figure 37** is a block diagram showing exchange of location, frequency and time estimates between FM receiver and WAPS receiver, under an embodiment. The location estimates from WAPS system can be provided to an FM Receiver. This location estimate may then be used, for example, to automatically determine active FM radio stations in the local region. The FM signal may include a RDS – Radio Data Service) transmission as
- 25 well. If the location of the FM station is included in the RDS/RBDS data-stream (for example, the Location and Navigation (LN) feature that provide data about the transmitter site, giving city and state name and provide DGPS navigation data) then this information can be used to provide location aiding to the WAPS Receiver. The frequency estimate from the WAPS system can be easily used to reduce the FM Receiver tuning time for a particular
- 30 station. In the other direction, the frequency quality of the estimate in the FM Receiver is

based on the FM radio station transmit quality. The time estimate in the WAPS system is based on GPS time and time can be transferred to the FM Receiver to aid timing alignment. Clock Time (CT) feature on RDS/RBDS transmissions may be used to determine timing relative to the RDS data stream and can be transferred to the WAPS receiver.

5 **Figure 38** is a block diagram showing exchange of location, time and frequency estimates between WLAN/BT transceiver and WAPS Receiver, under an embodiment. In general, these WLAN/BT transceivers do not have an accurate frequency estimate and as a result the frequency estimates would be quite coarse, so the transfer of such an estimate from WLAN/BT transceiver to WAPS receiver may have limited value. In the reverse
10 direction, a WAPS frequency estimate can reduce the time taken for frequency acquisition on the WLAN system. The timing information that is extracted, for example, from the timestamp on the wireless LAN AP (Access Point) beacons can be transferred to the WAPS system to aid WAPS acquisition. Note that some reference of the WLAN timing relative to GPS time is needed to make this useful for the WAPS system. Similarly, if the
15 WLAN/BT system has a location estimate (partial position eg. Altitude or 2-D position, or full position eg. 3-D position or raw range/pseudo-range) available, that location information can be provided with or without a location quality metric to the WAPS system. The WLAN position estimate could simply be the geo-location of the serving AP or other “audible” APs in the vicinity. The WLAN position estimate could also be partial, for
20 example, the altitude estimate based on the floor of the AP in question. The WLAN location information can also be a range estimate to a known transmitter AP location (for example, the WLAN system may use Round Trip Time measurements to determine range estimate) or a range difference estimate between two transmit APs.

Figure 39 is a block diagram showing exchange of location, time and frequency estimates between cellular transceiver and WAPS receiver, under an embodiment.
25 Location estimates (partial, complete or raw ranges/range-differences) from cellular systems (such as from TDOA, AFLT or other similar cellular signal FL or RL based positioning method) can be provided to the WAPS system which will use these measurements to obtain a better position estimate. Frequency estimates from the frequency
30 tracking loops of the cellular modem can be provided to the WAPS system to reduce the

frequency search space and thus improve WAPS acquisition time (i.e. TTFF). Time estimates from the cellular system can also be provided to the WAPS system to reduce the code search space or to aid bit and frame alignment. For example, systems that are synchronized to GPS time such as cdma2000/1x EVDO can provide fine time estimates for the WAPS system whereas asynchronous (transmissions not synchronized finely to time scale such as GPS) cellular systems such as GSM/GPRS/EGPRS/UMTS may provide coarse time estimates.

5 Since the WAPS system time is aligned to GPS time, the WAPS system can provide good quality timing and frequency estimates to any other system even if not on the same platform. For example, the WAPS system can be used to provide timing information to a pico/femto-cell BTS through a periodic hardware signal such as a pps (pulse-per-second) aligned with GPS second-boundaries or a single pulse signal with an associated GPS time.

10 As described above, the spectrum used by the WAPS system of an embodiment can include licensed or unlicensed bands or frequencies. Alternatively, the WAPS system can use the "White Space" spectrum. The white space spectrum is defined as any spectrum that the WAPS system senses or determines to be free in a local area (not limited to TV White Space) and transmits location beacons in that spectrum. The transmitters of an embodiment can use spectrum-sensing technology to detect unused spectrum and/or communicate geo-location (can be readily obtained from the GPS timing receiver) to a 15 centralized database that coordinates the spectrum. The receivers can include spectrum-sensing technology to listen to these beacons, or in another embodiment, may be notified of the frequency to which to tune using the communication medium. The WAPS system can adapt to dynamic white space availability or allocation (in cases where the transmitters are required to broadcast their geo-location to a centralized database which 20 25 then allocates either the spectrum to transmit in and/or the time duration for which it needs to transmit). The WAPS system can continuously broadcast in this spectrum or can share the spectrum with other systems as controlled by a centralized coordination service for the spectrum. The chipping rate and the data rate of the WAPS system components can be modified dynamically to suit the accuracy requirements and/or signal power and 30 bandwidth availability at any given time. The system parameters can be sensed by the

receiver or can be communicated to the receiver through the communication medium. The transmitters can form a local network or in cases of spectrum availability in a wider geographical area, can form a continuous network.

The transmitter of an embodiment can also coexist with other networks on the same 5 transmit system in a time-shared fashion. For example, the same spectrum can be used in a time-shared fashion between location and smart grid applications. The transmitter is a broadcast transmitter using the maximum available power levels and can adjust its power levels dynamically based on spectrum sensing or as requested by a centralized 10 coordinating server. The receiver can employ spectrum sensing or can be communicated by a communication medium (which can also be a white space spectrum) of the system parameters and wake up times at that time.

Based on spectrum availability, the WAPS system of an embodiment can use one channel of the TV White space (6MHz bandwidth) or, if multiple channels are available, can use the multiple frequency bands for better multipath resolution. If adjacent channels 15 are available, channel bonding (e.g., combining adjacent channels) can be used. The increased bandwidth can be used for better multipath resolution, higher chipping rate for higher accuracy, etc. Alternatively, the available bandwidth can be used under FDMA to help solve the near far problem and/or multipath resolution.

White space transmission/reception of WAPS waveforms in two or more 20 white-space bands can enable better and faster integer ambiguity resolution for WAPS carrier phase measurements. This will enable relatively high accuracy (of the order of < 1 wavelength) single point positioning using WAPS.

The whitespace bandwidth can also be used as a communication channel in the 25 WAPS (in cases where a reference receiver is used) between the reference receiver at surveyed location and the receiver whose position is to be found.

When a WAPS system in the licensed band is available in a wide area network, a White-Space based local network of towers can be used to augment the location accuracies of the WAPS receiver. The receiver can be designed to listen to both frequencies simultaneously or switch between the licensed band and white space band and tune to the 30 appropriate frequencies.

The White-space bands can also be used to send assistance information to the WAPS, GPS or AGPS systems for location aiding and other assistance information like clock bias, satellite ephemeris etc.

5 In cases where multiple frequencies with wide separation are available, the WAPS system can be designed to take advantage of the diversity in frequencies to provide better multipath performance.

CORRELATOR IMPLEMENTATION

10 In any CDMA receiver (or a receiver that uses Pseudo Random codes as a part of the transmit bit stream), correlation of the received signal with its PRN code is essential. The more parallel correlations that can be done, the faster is the time to acquire the channel. A brute force implementation of a parallel complex correlator architecture for signals that use a maximal length sequence of length 1023, input signal oversampled by 2x, is shown in Figure 40. The even and odd samples correspond to the 2x oversampled data. The shift 15 registers get shifted at the rate of the 'clk'. The PRN generator generates the reference PRN and gets shifted at the rate of clk/2. The correlation sum at each cycle is calculated using the equation

$$\text{corrsum}[n] = \sum_{k=0}^{2045} gcref[k] * x[k - n]$$

where $x[n]$ is the complex input, $gcref[k]$ is the PRN reference waveform, and $\text{corrsum}[n]$ is the complex output from the correlator. Figure 37 shows one optimization 20 where the even and odd samples share the same multiplier and adder trees.

An implementation like the one shown above requires $2046 * 2 * n$ -input bits flip flops for the shift registers, 1023 of 1xn-input multiplier and an adder that sums the 1023 products. As an example, if the input bit width were 2-bit samples, then 1023 of 1x2 multipliers are required, and 1023 of these multiplications would have to be summed in one 25 clock cycle. This could be an onerous implementation in terms of area, timing and power in hardware. In particular, in an FPGA implementation a brute force implementation of the multiplier and adder structure may be impossible to implement given the limited resources.

An embodiment includes a novel approach to this implementation which takes advantage of the structures available in state of the art FPGAs. Modern FPGAs include several configurable logic blocks (CLBs) that implement logic and storage elements. The lookup tables that form an essential part of the CLBs can also be reprogrammed as shift registers with a serial shift in, but have parallel random access to the storage elements. This implementation can also be used in an ASIC implementation as an efficient approach to computing the correlation and as an easy migration path from FPGAs (used to prototyping) to ASICs (for mass production volumes).

Turning to shift register implementation, particular FPGAs have shift register primitives which are mapped onto the CLBs. Some FPGAs have a 16-bit shift register while some have a 32-bit shift register mapping. **Figure 41** shows a 32-bit shift register implementation derived from two 16-bit shift register primitives with parallel random access read capabilities. In this example implementation a 16-bit shift register group primitive is used to build a 32-bit shift register. 32 of such 32-bit shift registers are strung in series to form the 1024-bit shift register. The shift operations occur at 'clk' rate, and the readout operations occur at 32 times the clock rate, as shown in **Figure 42**.

The adder tree can also be complex to implement a 1023 x n-bit adder. In the case of a particular FPGA, a 48-bit DSP slice is available which can be used as 1023xn-bit sequential adder. The hardware structure for this implementation is shown in **Figure 43**.
20 The 32 values from the 32 groups of shift registers are split into 4 groups of 8 additions. In this example, a 2-bit input is used. Each 8-number adder produces a 10-bit output which is then aligned in a 12-bit group in the 48-bit adder. Room is allowed for the growth of the sum. After 32 cycles, the 1024 bit sum is obtained by adding the 4 groups of the 12-bit adders into one 14-bit sum.

25

ENCRYPTION AND SECURITY

The overhead information in the system of an embodiment can be encrypted using an encryption algorithm. This allows users to use the system and be billed for usage of the system and provide a means to control information security. Keys can be applied to
30 decrypt the signal. The keys can be obtained using a PC, wireless network, hardware

dongle or can be burnt into the non volatile memory of the device in a way that it is inaccessible by any unintended sources.

The encryption of an embodiment provides both data security and authentication. The key components that are secured using encryption are the transmitters, the receivers 5 and the server communication. Transmitter Authentication includes unambiguously identifying transmitters so that malicious transmitters can be rejected. Receiver Authentication is such that only authentic receivers should be able to utilize the transmitted information. Receiver Authorization is such that only receivers that are authorized (authentic receiver) should be permitted to operate. Server Communication is encrypted 10 such that communication between the receivers and the server and between the transmitters and the server has to be secure. User data protection is also encrypted because location tracking user databases require protection from unauthorized access.

Encryption methods of an embodiment can be broadly classified into two types: symmetric key cryptography and asymmetric key cryptography. Symmetric Key 15 encryption provides both authentication and encryption, whereas asymmetric key encryption provides authentication of the private key owner, since the public key is available to anyone. Symmetric Key encryption of data is an order of magnitude faster given similar resources. 3DES and AES are examples of symmetric key cryptography. A combination of both methods is used as part of the encryption architecture of an 20 embodiment.

Over-the-air (OTA) broadcast messages can comprise general broadcast messages or system messages. General broadcast messages contain data specific to each transmitter such as location information, transmitter timing counts and other pertinent information that assist a receiver in determining its location. System messages are used to configure 25 encryption keys, enable/disable receivers or for targeted one-way private information exchange to a specific set of receivers.

The general format of a message of an embodiment includes: Message type (parity/ECC protected); Encrypted Message; and Encrypted Message ECC. The ECC for the encrypted message is computed after the message is encrypted.

The OTA broadcast comprises frames that are transmitted periodically, possibly every second. Depending on the channel data rate, a message could be split up (segmented) over multiple frames. Each frame comprises a frame type and frame data. Frame type (parity protected) indicates whether this is the first frame of a message or if it is a

5 continuing frame; it can also indicate a low level format frame that may be used for other purposes. Frame Data is essentially a segmented Message or a low level data frame.

OTA system messages can be encrypted either by the session key or by the transmitter's private key depending upon the system message type. OTA general broadcast messages are encrypted using a symmetric key algorithm with a session key that

10 both the transmitter and receiver have negotiated as described herein. This provides mutual authentication i.e., transmitters can be authenticated by receivers and only authenticated receivers can decode the OTA broadcast. The session key is known to all transmitters and receivers and it is changed periodically. Key change messages are encrypted using the past few session keys, allowing receivers that were not active at a

15 certain time period to sync up to the current session key.

OTA broadcasts also include periodic system messages encrypted by the transmitter's private key. The receivers can unambiguously identify the authenticity of the transmitter by using the associated public key. In the event the session key is compromised, this mechanism ensures that unauthorized transmitters cannot be

20 implemented.

Figure 44 is a block diagram of session key setup, under an embodiment. Each receiver is equipped with a unique device ID and a device specific key. **Figure 45** is a flow diagram for encryption, under an embodiment. The WAPS System data servers maintain a database of the device ID/device specific key pairing. Receiver initialization between a

25 receiver and the WAPS data servers is facilitated using a data connection (GPRS/USB/Modem, etc.) specific to the receiver type. This connection is encrypted using the device specific key after the device identifies itself with the device ID. During this initialization, the current session key, the transmitter public key and licensing terms (i.e., duration the receiver is authorized) are exchanged. Receiver initialization can be

30 performed when the receiver has lost the current session key (initial power up) or if its

session key is out of sync (extended power off). The session key is periodically updated, and the new key used for the updating is encrypted using the previous N keys.

The OTA data rate may be inadequate for being the sole mechanism to authorize receivers. However, the system message protocol of an embodiment supports device ID specific and device ID range-based receiver authorization.

A compromised session key requires all receivers to re-initialize. Therefore the session key storage should be tamper-proof in the device. Session key stored outside the device crypto boundary (i.e., attached storage of any kind) will be encrypted using the device's secure key.

10 A compromised session key cannot be used to masquerade a transmitter because the transmitter periodically transmits authentication information using its private key. Therefore, the transmitter's private key should never be compromised.

15 In an alternative embodiment, shown in **Figure 46**, the keys can be directly delivered to the receiver over the communication link from the WAPS server or can be routed through a third party application or service provider. The keys can have a certain validity period. The keys can be made available on a per-application basis or a per device basis based on a contractual agreement with the customer. Everytime a position request is made either by an application on the receiver or by an application on the network, the keys are checked for validity before retrieving the position or parameters to compute position
20 from the WAPS engine. The key and information exchange to a WAPS server can happen using proprietary protocols or through standard protocols such as OMA SUPL.

The security architecture of the system can be implemented as combination of architectures shown in Figure 44 and Figure 46.

25 Parameter sensors can be integrated into receivers of the WAPS system to time tag and/or location tag the measurements from the sensors. The parameter sensors can include, but are not limited to, temperature sensors, humidity sensors, weight sensors, and sensors for scanner types to name a few. For example, an X-ray detector can be used to determine if a tracked receiver, or device including a tracked receiver, passes through an X-ray machine. The time of the X-ray event and location of the X-ray machine can be tagged by

the detector. In addition, other parameter sensors can be integrated into the WAPS system to both time tag and location tag measurements from the sensors.

Users can be billed for the system on a per use, per application on the device, hourly, daily, weekly, monthly and annual basis for an individual or asset.

- 5 The location and height of the receiver unit can be sent to any application on the terminal or to the network server using a communication protocol. Alternatively, the raw range measurement can be sent to the network through a communication protocol. The communication protocol can be a standard serial or other digital interface to the application on the terminal or through a standard or proprietary wireless protocol to the server.
- 10 Possible methods of coupling or connecting to a server through a standard protocol includes the use of SMS messaging to another phone connected to the server or, alternatively, through a wireless data service to a web server. The information sent includes one or more of latitude/longitude, height (if available), and timestamp. The application on the server or the terminal unit can initiate a position fix. The location of the user can be communicated directly from the server or by the application on the server.

The WAPS standalone system independent of a GPS receiver can be used for determining the location of a device. The WAPS system by itself or integrated WAPS and GPS and/or other positioning system can be implemented to co-exist with media storage cards (such as SD cards) on the media cards. The WAPS system by itself or integrated

- 20 WAPS and GPS system and/or other positioning systems can be implemented to co-exist on a cellular phone Subscriber Identity Module (SIM) card so that the SIM cards can be tracked.

PRECISE POSITIONING WITH CARRIER PHASE

- 25 One method to augment the WAPS system performance to further improve accuracy (upto <1m) is to implement a carrier phase positioning system as described below. The beacons are set up as usual WAPS transmitters. For this method, it may be desirable (but not essential) to not use TDMA slotting to facilitate easy continuous phase tracking. When TDMA is not used, the near-far problem can be overcome through
- 30 interference cancellation and increased dynamic range in the receiver. The WAPS receiver

to support such a method is capable of measuring and time-stamping code and carrier phase in a continuous manner for all visible satellites. In addition, there is a reference receiver at a known surveyed location that can also make similar measurements of code and carrier phase in a continuous manner. The measurements from the WAPS receiver and 5 the reference receiver may be combined to compute a position either on the device or on the server. The configuration of such a system would be identical to a differential WAPS system.

Carrier phase measurement is more accurate than code phase measurement but contains unknown integer number of carrier phase cycles called integer ambiguity.

10 However there are ways to find integer ambiguities called ambiguity resolution. One method will be considered here that uses extension of local minima search algorithm to iteratively solve for user receiver position and uses measurements at multiple epochs for improved accuracy.

Consider carrier phase measurement at user receiver at a single epoch first as follows.

15

$$(1) \quad \phi_u^{(k)} = \lambda^{-1} \cdot r_u^{(k)} + N_u^{(k)} + f \cdot (dt_u - dt^{(k)}) + \varepsilon_u^{(k)}$$

where ϕ , λ , f and N are carrier phase, wavelength, frequency and integer cycles respectively, dt is clock bias, r is range, ε is measurement error and subscript u

20 represents user receiver k represents transmitter number.

Range is given in terms of user and transmitter positions p_u and $p^{(k)}$ as

$$(2) \quad r_u^{(k)} = \|p_u - p^{(k)}\| = \sqrt{(p_{ux} - p_x^{(k)})^2 + (p_{uy} - p_y^{(k)})^2 + (p_{uz} - p_z^{(k)})^2}$$

25

To eliminate error in the knowledge of transmitter clock bias consider another receiver at known position (called reference receiver) with corresponding carrier phase equation

$$(3) \quad \phi_r^{(k)} = \lambda^{-1} \cdot r_r^{(k)} + N_r^{(k)} + f \cdot (dt_r - dt^{(k)}) + \varepsilon_r^{(k)}$$

where subscript r stands for reference receiver and subtract (2) from (1) to get

$$(4) \quad \phi_u^{(k)} - \phi_r^{(k)} = \lambda^{-1} \cdot (r_u^{(k)} - r_r^{(k)}) + (N_u^{(k)} - N_r^{(k)}) + f \cdot (dt_u - dt_r) + (\varepsilon_u^{(k)} - \varepsilon_r^{(k)})$$

5

which is written as

$$(5) \quad \phi_{ur}^{(k)} = \lambda^{-1} \cdot r_{ur}^{(k)} + N_{ur}^{(k)} + f \cdot dt_{ur} + \varepsilon_{ur}^{(k)}$$

10 where $(\bullet)_{ur} = (\bullet)_u - (\bullet)_r$.

Since dt_{ur} is not of interest it can be eliminated by differencing (5) for different values of index (k) to get so called double difference observable equation

$$15 \quad (6) \quad \phi_{ur}^{(kl)} = \lambda^{-1} \cdot r_{ur}^{(kl)} + N_{ur}^{(kl)} + \varepsilon_{ur}^{(kl)}$$

where $(\bullet)_{ur}^{(kl)} = (\bullet)_{ur}^{(k)} - (\bullet)_{ur}^{(l)}$.

Equation (6) then is an equation in the unknown user position p_u through $r_{ur}^{(kl)}$ as

20

$$(7) \quad r_{ur}^{(kl)} = (r_u^{(k)} - r_r^{(k)}) - (r_u^{(l)} - r_r^{(l)}) = \|p_u - p^{(k)}\| - \|p_u - p^{(l)}\| - \gamma^{(kl)}$$

where

$$(8) \quad \gamma^{(kl)} = \|p_r - p^{(k)}\| - \|p_r - p^{(l)}\|$$

Typically transmitter l used in double differencing is one of the transmitters and labeling it

25

as 1 for convenience leads to equation in the matrix form as

$$(9) \quad \begin{bmatrix} \phi_{ur}^{(21)} \\ \phi_{ur}^{(31)} \\ \vdots \\ \phi_{ur}^{(n)} \end{bmatrix} = \lambda^{-1} \cdot \begin{bmatrix} \left\| p_u - p^{(2)} \right\| - \left\| p_u - p^{(1)} \right\| - \gamma^{(21)} \\ \left\| p_u - p^{(3)} \right\| - \left\| p_u - p^{(1)} \right\| - \gamma^{(31)} \\ \vdots \\ \left\| p_u - p^{(n)} \right\| - \left\| p_u - p^{(1)} \right\| - \gamma^{(n1)} \end{bmatrix} + \begin{bmatrix} N_{ur}^{(21)} \\ N_{ur}^{(31)} \\ \vdots \\ N_{ur}^{(n1)} \end{bmatrix} + \begin{bmatrix} \varepsilon_{ur}^{(21)} \\ \varepsilon_{ur}^{(31)} \\ \vdots \\ \varepsilon_{ur}^{(n1)} \end{bmatrix} \quad \text{or}$$

$$(10) \quad \phi = \lambda^{-1} \cdot f(p_u) + N + \varepsilon$$

Equation (10) is a nonlinear equation in unknown user position p_u . Local minima search

5 algorithm works on linear equations and so (10) is linearized and solved iteratively as follows. Let at iteration m , approximation to p_u is p_u^m where

$$(11) \quad p_u = p_u^m + \Delta p_u$$

and

$$(12) \quad f(p_u) = f(p_u^m + \Delta p_u) \approx f(p_u^m) + \frac{\partial f}{\partial p_u}(p_u^m) \cdot \Delta p_u$$

10 where

$$(13) \quad \frac{\partial f}{\partial p_u}(p_u) = \begin{bmatrix} l^{(2)} - l^{(1)} \\ l^{(3)} - l^{(1)} \\ \vdots \\ l^{(n)} - l^{(1)} \end{bmatrix}, \text{ where } l^{(k)} \text{ is line-of-sight row vector } l^{(k)} = \frac{p_u - p^{(k)}}{\|p_u - p^{(k)}\|}$$

Then equation (10) is written as,

$$(13) \quad y = G \cdot x + N + \varepsilon \quad \text{where } y = \phi - \lambda^{-1} \cdot f(p_u^m), G = \lambda^{-1} \cdot \frac{\partial f}{\partial p_u}(p_u^m), \text{ and } x = \Delta p_u$$

Equation (13) is linear in $x = \Delta p_u$ and is solved for Δp_u using local minima search

15 algorithm given below. Using so obtained solution of Δp_u equation (11) is used to get p_u at iteration m and then so obtained p_u is used as p_u^{m+1} at the next iteration $(m+1)$. The iterations are continued till Δp_u becomes small enough to decide convergence. At the beginning of iterations p_u^0 can be taken from code phase based solution.

Now consider solving equation (13). Let \mathcal{Q}_{dd} be covariance matrix of double

20 difference carrier phase error vector. It is obtained as follows. Variance of error in single

difference observable $\phi_{ur}^{(k)} = \phi_u^{(k)} - \phi_r^{(k)}$ is $\mathcal{Q}_u + \mathcal{Q}_r$ where \mathcal{Q}_u and \mathcal{Q}_r are respective

carrier phase error variances which are assumed to be independent of transmitter k .

Variance of $\phi_{ur}^{(k)} = \phi_{ur}^{(k)} - \phi_{ur}^{(1)}$ is $2 \cdot (\mathcal{Q}_u + \mathcal{Q}_r)$ and cross-variance between

$\phi_{ur}^{(j)} = \phi_{ur}^{(j)} - \phi_{ur}^{(1)}$ and $\phi_{ur}^{(k)} = \phi_{ur}^{(k)} - \phi_{ur}^{(1)}$, $j \neq k$ is $\mathcal{Q}_u + \mathcal{Q}_r$ which is variance of the

5 common term $\phi_{ur}^{(1)}$. So,

$$(14) \quad \mathcal{Q}_{dd} = (\mathcal{Q}_u + \mathcal{Q}_r) \cdot \begin{bmatrix} 2 & 1 & \cdots & 1 \\ 1 & 2 & \cdots & 1 \\ \vdots & \vdots & \ddots & \vdots \\ 1 & 1 & \cdots & 2 \end{bmatrix}$$

Weighted least squares solution of (13) is:

$$(15) \quad \hat{x} = G^L \cdot (y - N) \text{ where } G^L \text{ is left inverse of } G, G^L = (G^T \cdot \mathcal{Q}_{dd}^{-1} \cdot G)^{-1} \cdot G^T \cdot \mathcal{Q}_{dd}^{-1}$$

Vector of residuals is then

$$10 \quad (16) \quad (y - N) - G \cdot \hat{x} = (y - N) - G \cdot G^L \cdot (y - N) = (I - G \cdot G^L) \cdot (y - N) = S \cdot (y - N)$$

which is a function of N and local minima search tries to minimize weighted norm square of residuals with respect to N as

$$(17) \quad \min c(N) = (y - N)^T \cdot W \cdot (y - N), \text{ where } W = S^T \cdot \mathcal{Q}_{dd}^{-1} \cdot S \text{ and } S = I - G \cdot G^L$$

To solve (17) consider solving

$$15 \quad (18) \quad W \cdot N \approx W \cdot y$$

under the constraint that N is integer. Then $W \cdot (y - N) \approx 0$ and

$(y - N)^T \cdot W^T \cdot W \cdot (y - N) = (y - N)^T \cdot W \cdot (y - N) = c(N) \approx 0$ because W is idempotent ($W^T = W$ and $W \cdot W = W$). Thus search for N is limited to those N which satisfy (18).

Once N is solved for estimate of $x = \Lambda p_u$ is obtained from equation (15).

20 Matrices G and G^L , of dimensions $(n-1) \times 3$ and $3 \times (n-1)$ respectively have rank 3 each since $(n-1) > 3$ and so $(n-1) \times (n-1)$ matrices S and W will fall short from full rank of $(n-1)$ by 3.

Using QR decomposition of W (LU decomposition could also be used) on equation

25 (18),

$$(19) \quad R \cdot N = Q^T \cdot W \cdot y$$

where Q is ortho-normal matrix ($Q^{-1} = Q^T$) and R is upper triangular so that

$$(20) \quad \begin{bmatrix} R_{11} & R_{12} \\ 0 & 0 \end{bmatrix} \cdot \begin{bmatrix} N_1 \\ N_2 \end{bmatrix} = \begin{bmatrix} (Q^T \cdot W \cdot y)_{11} \\ \approx 0 \end{bmatrix}$$

and then

$$5 \quad (21) \quad N_1 = \text{round}\{R_{11}^{-1} \cdot ((Q^T \cdot W \cdot y)_{11} - R_{12} \cdot N_2)\}$$

Thus solution of $N = \begin{bmatrix} N_1 \\ N_2 \end{bmatrix}$ is obtained by searching for N_2 in 3 dimensional box

with integer values, obtaining N_1 from (21), and picking that N which minimizes $c(N)$ in

(17). Search for N_2 is centered on the value of N_2 from the previous iteration. At the

zero-th iteration N_2 latter part of N which is obtained as fractional part of $\lambda^{-1} \cdot f(p_u^0)$;

10 p_u^0 being the code phase based solution. The size of the 3 dimensional search box depends on the uncertainty in the code phase based solution. This box can be divided into smaller sub-boxes and center of each smaller size sub-box can be tried as initial p_u^0 .

The above method used a single epoch (instant) of measurement to determine position. The description below explains an extension to the single epoch method. Multiple

15 epoch measurements are taken close enough in time wherein user receiver movement is negligible. Further, integer ambiguities of the initial epoch remain the same for subsequent epochs so that no new unknown integer ambiguities are introduced at subsequent epochs. Multiple epoch measurements do not give independent equations because transmitter locations are fixed (unlike in the GNSS case where motion of satellite transmitters change

20 line-of-sight and thus give independent equations). So multiple epoch measurements do not help in solving for integer ambiguities as float ambiguities (unlike in GNSS case when number of independent equations become greater than number of unknown ambiguities plus three position coordinates). However, multiple epoch measurements allow more carrier phase measurement errors and still allow successful ambiguity resolution. In the

25 multiple epoch case equation (13) becomes

$$(22) \quad y = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix} = \begin{bmatrix} G \\ G \\ \vdots \\ G \end{bmatrix} \cdot x + \begin{bmatrix} N \\ N \\ \vdots \\ N \end{bmatrix} + \begin{bmatrix} \varepsilon_1 \\ \varepsilon_2 \\ \vdots \\ \varepsilon_m \end{bmatrix}$$

Following development for single epoch case as above equation, the problem reduces to problem of finding N such that

$$(23) \quad \min c(N) = \left(y - \begin{bmatrix} N \\ N \\ \vdots \\ N \end{bmatrix} \right)^T \cdot \bar{W} \cdot \left(y - \begin{bmatrix} N \\ N \\ \vdots \\ N \end{bmatrix} \right),$$

5 where $\bar{W} = \bar{S}^T \cdot \bar{Q}_{dd}^{-1} \cdot \bar{S}$, $\bar{S} = I - \bar{G} \cdot \bar{G}^L$, $\bar{G}^L = (\bar{G}^T \cdot \bar{Q}_{dd}^{-1} \cdot \bar{G})^{-1} \cdot \bar{G}^T \cdot \bar{Q}_{dd}^{-1}$

$$\bar{G} = \begin{bmatrix} G \\ G \\ \vdots \\ G \end{bmatrix} \quad \bar{Q}_{dd}^{-1} = \begin{bmatrix} \bar{Q}_{dd}^{-1} & 0 & \cdots & 0 \\ 0 & \bar{Q}_{dd}^{-1} & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \bar{Q}_{dd}^{-1} \end{bmatrix}$$

And to solve (23) for N consider solving

$$(24) \quad \bar{W} \cdot \bar{I} \cdot N \approx \bar{W} \cdot y \quad \text{where } \bar{I} = \begin{bmatrix} I \\ I \\ \vdots \\ I \end{bmatrix}$$

using QR decomposition of $\bar{W} \cdot \bar{I}$ (LU decomposition could also be used) and following

10 equations of (19) to (21) as above. Again, once N is solved for estimate of $x = \Delta p_u$ is obtained from equation (15). If this estimate of $x = \Delta p_u$ is small then iterations in equation (11) are stopped to obtain user position p_u . Typically if each component of x is less than 1e-6 in magnitude then convergence is declared and iterations are stopped.

The next step is to verify whether the converged user position p_u is the right one.

15 This is done based on residuals obtained from (10) as $\text{mod}(\phi - \lambda^{-1} \cdot f(p_u) - N, \lambda)$. If maximum of absolute values of residuals for each epoch is less than $\kappa \cdot \sqrt{Q_r}$ then converged solution is accepted as a solution otherwise the search is continued by selecting

a new sub-box. Typically scale factor κ in the verification test can be chosen to be 5. Once the solution is verified, the differential WAPS system described above can achieve accuracy close to or better than 1m.

This differential WAPS carrier phase system may be overlaid on top of the 5 traditional WAPS system through the addition of reference receivers or can be standalone. The differential WAPS carrier phasc system can be used to deliver high accuracy positioning in certain localized target areas (such as malls, warehouses etc.).

In W-CDMA systems, two receive chains are used to improve the receive diversity. When WAPS co-exists with W-CDMA, one of the receive chains can be used temporarily 10 for receiving and processing the WAPS signal. In certain cases of W-CDMA and CDMA architectures, the entire receive chain can be reused to receive WAPS signal by tuning the receiver to WAPS band and processing the WAPS signal while temporarily suspending the processing of the W-CDMA/CDMA signals. In certain other embodiments where the GSM receive chain is multiplexed with the W-CDMA receive chain, the receiver can be further 15 time-shared to be used for WAPS reception.

Once it is determined which signals are used from which towers for position determination in WAPS or any other TDMA system, in order to save power, most of the receiver of an embodiment is turned off during the slots at which either signal is not detected and/or signals from towers that radiate in those slots are not used for position 20 determination. In case of detection of motion or change in position or change in signal conditions, then the receiver of an embodiment is turned ON for all the slots to determine which slots can be used for next set of position calculations.

Embodiments described herein include a positioning system comprising a terrestrial transmitter network including a plurality of transmitters that broadcast 25 positioning signals comprising at least ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a reference sensor array comprising at least one reference sensor unit positioned at a known location. The system includes a remote receiver comprising an atmospheric sensor that collects atmospheric data at a 30 location of the remote receiver. The system includes a positioning application running on a

processor and coupled to the remote receiver. The positioning application computes a position of the remote receiver using the atmospheric data, reference data from a set of reference sensor units of the reference sensor array, and information derived from at least one of the positioning signals and satellite signals that are signals of a satellite-based

5 positioning system. The position includes an elevation.

Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information, wherein a ranging signal comprises information used to measure a distance to a transmitter

10 broadcasting the ranging signal; a reference sensor array comprising at least one reference sensor unit positioned at a known location; a remote receiver comprising an atmospheric sensor that collects atmospheric data at a location of the remote receiver; and a positioning application running on a processor and coupled to the remote receiver, wherein the positioning application computes a position of the remote receiver using the atmospheric

15 data, reference data from a set of reference sensor units of the reference sensor array, and information derived from at least one of the positioning signals and satellite signals that are signals of a satellite-based positioning system, wherein the position includes an elevation.

Embodiments described herein include a positioning system comprising a terrestrial transmitter network including a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a reference sensor array comprising at least one reference sensor unit positioned at a known location. The system includes a remote receiver comprising an atmospheric sensor that collects atmospheric data at a

25 position of the remote receiver. The system includes a positioning application running on a processor and coupled to the remote receiver. The positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from a set of reference sensor units of the reference sensor array. The positioning application computes the position of the remote receiver using the

30 reference pressure estimate and information derived from at least one of the positioning

signals and satellite signals that are signals of a satellite-based positioning system. The position includes an elevation.

Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast

5 positioning signals comprising at least ranging signals and positioning system information, wherein a ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal; a reference sensor array comprising at least one reference sensor unit positioned at a known location; a remote receiver comprising an atmospheric sensor that collects atmospheric data at a position of the remote receiver; and a positioning

10 application running on a processor and coupled to the remote receiver, wherein the positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from a set of reference sensor units of the reference sensor array, wherein the positioning application computes the position of the remote receiver using the reference pressure estimate and information derived from at

15 least one of the positioning signals and satellite signals that are signals of a satellite-based positioning system, wherein the position includes an elevation.

The positioning application of an embodiment is hosted on the remote receiver and the remote receiver computes the position.

The remote receiver of an embodiment is operated in a reduced-power state when

20 the positioning signals are at least one of not detected and unusable.

The remote receiver of an embodiment uses a set of positioning signals from a set of the plurality of transmitters to determine position, wherein the remote receiver is operated in a reduced-power state when the set of positioning signals are at least one of not detected and unusable.

25 The remote receiver of an embodiment transitions from the reduced-power state to a full-power state in response to detecting at least one of motion of the remote receiver, change in position of the remote receiver, and change in signal conditions of the positioning signals.

The system of an embodiment comprises a server coupled to the remote receiver, wherein the positioning application is hosted on the server and the server computes the position.

The system of an embodiment comprises a server coupled to the remote receiver, 5 wherein the positioning application is distributed between the remote receiver and the server.

A first operating mode of the remote receiver of an embodiment comprises terminal-based positioning in which the remote receiver computes the position.

A second operating mode of the remote receiver of an embodiment comprises 10 network-based positioning in which the server computes the position.

The known location of an embodiment is a location of a set of transmitters of the plurality of transmitters.

The positioning application of an embodiment includes a pressure surface gradient model that uses the reference data from the set of reference sensor units to generate an 15 equivalent reference elevation pressure at the position of the remote receiver.

The positioning application of an embodiment uses the equivalent reference elevation pressure as a reference value for generating the elevation.

The positioning application of an embodiment generates an equivalent reference elevation pressure for each reference sensor unit of the set of reference sensor units using 20 the reference data from each reference sensor unit.

The reference data of an embodiment comprises pressure, temperature and location data of each reference sensor unit of the set of reference sensor units, wherein the location data includes elevation.

The positioning application of an embodiment generates the equivalent reference 25 elevation pressure at the position of the remote receiver using the equivalent reference elevation pressure for each reference sensor unit of the set of reference sensor units and latitude and longitude of the remote receiver.

The positioning application of an embodiment generates the elevation of the remote receiver using the atmospheric data and the equivalent reference elevation pressure at the 30 position of the remote receiver.

The at least one reference sensor unit of an embodiment is collocated with at least one transmitter of the plurality of transmitters.

The at least one reference sensor unit of an embodiment comprises a plurality of reference sensor units, wherein a first set of the plurality of reference sensor units are

5 collocated with a first set of the plurality of transmitters, and a second set of the plurality of reference sensor units are in locations different from locations of the plurality of transmitters.

The at least one reference sensor unit of an embodiment is in a location different from locations of the plurality of transmitters.

10 The atmospheric sensor of an embodiment collects pressure and temperature data at the position of the remote receiver.

The atmospheric sensor of an embodiment determines the pressure data with a resolution approximately in a range of less than 36 Pascal.

The remote receiver of an embodiment detects rate of change of the pressure data.

15 The positioning application of an embodiment determines a vertical velocity of the remote receiver using the rate of change.

The temperature data of an embodiment includes an outside air temperature at the position of the remote receiver, and the atmospheric sensor determines the temperature data with a resolution at least one of equal to and less than approximately 3 degrees

20 Celsius.

Each reference sensor unit of an embodiment comprises at least one atmospheric reference sensor that collects reference pressure and reference temperature data at a known location of the atmospheric reference unit.

The at least one atmospheric reference sensor of an embodiment determines the reference pressure data with a resolution approximately in a range of 2-36 Pascal.

The reference temperature data of an embodiment includes an outside air temperature at the known location, and the atmospheric reference sensor determines the temperature data with a resolution at least one of equal to and less than approximately 3 degrees Celsius.

The atmospheric reference sensor of an embodiment is calibrated for a limited temperature range, wherein the limited temperature range is determined based on temperatures to which the atmospheric reference sensor is exposed.

5 Each atmospheric reference sensor of an embodiment continuously collects the reference pressure and the reference temperature data at the known location.

The atmospheric reference sensor of an embodiment is positioned to collect the reference pressure and the reference temperature in relatively still air.

The atmospheric reference sensor of an embodiment filters the reference pressure and reference temperature data.

10 The atmospheric reference sensor of an embodiment filters the reference pressure and reference temperature data using an adaptive time scale.

Each reference sensor unit of an embodiment comprises a wind detector that determines wind data, wherein the wind data includes a direction and magnitude of the local wind.

15 The positioning application of an embodiment uses the wind data to at least one of correct and filter variations in the atmospheric sensor.

The at least one reference sensor unit of an embodiment comprises a plurality of atmospheric reference sensors.

20 The system of an embodiment comprises a communication link coupled between the reference sensor array and the remote receiver.

The reference sensor array of an embodiment broadcasts the atmospheric reference data.

The reference sensor array of an embodiment broadcasts raw data of the atmospheric reference data.

25 The reference sensor array of an embodiment broadcasts differential data of the reference data.

The differential data of an embodiment is derived relative to at least one constant value.

30 The differential data of an embodiment comprises differential pressure data derived as an offset value of a standard atmosphere.

The remote receiver of an embodiment receives the reference data via the broadcasts.

The reference sensor array of an embodiment broadcasts the reference data in a plurality of times per second.

5 The reference sensor array of an embodiment broadcasts the reference data in a plurality of times per measurement.

The remote receiver of an embodiment determines a set of atmospheric reference sensors to query, and pulls the reference data from the set of atmospheric reference sensors via the communication link.

10 The positioning application of an embodiment processes the reference data and determines an equivalent reference elevation pressure of each reference sensor unit of the set of reference sensor units.

The reference data of an embodiment comprises location of each atmospheric reference unit.

15 The location of an embodiment comprises latitude and longitude.

The location of an embodiment comprises a height.

The reference data of an embodiment comprises a measured outside air temperature from each atmospheric reference unit.

The reference data of an embodiment comprises a confidence measure.

20 Each reference sensor unit of an embodiment processes the reference data of that reference sensor unit and determines an equivalent reference elevation pressure of the reference sensor unit.

The reference data of an embodiment comprises location of each atmospheric reference sensor.

25 The location of an embodiment comprises latitude and longitude.

The location of an embodiment comprises a height.

The reference data of an embodiment comprises the equivalent reference elevation pressure.

The reference data of an embodiment comprises a confidence measure.

The elevation of an embodiment includes an estimated elevation of each floor in at least one structure.

The system of an embodiment comprises a database coupled to a plurality of remote receivers that includes the remote receiver, wherein the database includes the 5 estimated elevations received from the plurality of remote receivers.

The system of an embodiment comprises a learning application coupled to the server, where the learning application processes the estimated elevations of the plurality of remote receivers and revises the database using the estimated elevations.

The at least one reference sensor unit of an embodiment comprises at least one local 10 reference sensor unit that is local to at least one of a location and a structure.

The reference data of an embodiment includes data of the at least one local reference sensor unit.

The system of an embodiment comprises automatically calibrating the atmospheric sensor of the remote receiver using aggregated reference data over a specified time period.

15 The system of an embodiment comprises generating the aggregated reference data by identifying when the remote receiver is at a known location, accumulating deviations in the atmospheric data corresponding to the known location, and generating a corrected calibration from the accumulated deviations.

The system of an embodiment comprises automatically calibrating the atmospheric 20 sensor of the remote receiver when an elevation and atmospheric pressure of the position of the remote receiver is known.

The position of the remote receiver of an embodiment is determined using the satellite signals.

25 The system of an embodiment comprises determining the elevation using a reference elevation.

The reference elevation of an embodiment minimizes elevation differences among elevations computed using at least one of the atmospheric data and the reference data.

The reference elevation of an embodiment comprises a mean elevation of the atmospheric reference units.

The reference elevation of an embodiment comprises a mean elevation of an area in which the remote receiver is located.

The elevation of an embodiment includes an estimated elevation derived using local constraint data.

5 The local constraint data of an embodiment includes terrain data of terrain in a vicinity of the position of the remote receiver.

The local constraint data of an embodiment includes height of at least one structure in a vicinity of the position of the remote receiver.

10 The local constraint data of an embodiment includes the elevation of at least one other remote receiver in a vicinity of the position of the remote receiver.

The positioning application of an embodiment determines the elevation using the atmospheric data, the reference data, and the local constraint data.

15 The system of an embodiment comprises a database coupled to the positioning application, wherein the database includes historical data measured during a time period, wherein the historical data comprises the reference data of the reference sensor array and the atmospheric data of a plurality of remote receivers.

The positioning application of an embodiment determines the elevation using the historical data.

20 The system of an embodiment comprises optimizing the at least one reference sensor unit of the reference sensor array using the historical data.

The system of an embodiment comprises determining the elevation by relaxing the assumption of constant equivalent reference elevation pressure between a reference location of a reference sensor unit and a current position of the remote receiver.

25 The system of an embodiment comprises converting a first equivalent reference elevation pressure at the reference location to a second equivalent reference elevation pressure at a standard temperature. The system of an embodiment comprises determining a local temperature at the current position and converting the second equivalent reference elevation pressure to a third equivalent reference elevation pressure using the local temperature. The system of an embodiment comprises determining the elevation at the 30 current position using the third equivalent reference elevation pressure.

The system of an embodiment comprises determining a variation of equivalent reference elevation pressure with horizontal location using the reference data at each reference sensor unit of the set of reference sensor units. The system of an embodiment comprises determining a best estimate of reference elevation pressure at the current

5 position by combining the equivalent reference elevation pressures of the set of reference sensor units.

The best estimate of equivalent reference elevation pressure of an embodiment comprises using a weighted average technique, wherein a weighting is a function of a horizontal distance between a location of a reference sensor unit and the current position.

10 Determining the best estimate of equivalent reference elevation pressure of an embodiment comprises using a least squares fit to create a second order surface that best fits computed sea level pressures at each reference sensor unit of the set of reference sensor unit, and interpolating the best estimate of equivalent reference elevation pressure at the current position using the n-order surface.

15 The system of an embodiment comprises converting a first equivalent reference elevation pressure at each reference sensor unit of the set of reference sensor unit to a second equivalent reference elevation pressure at a standard temperature. The system of an embodiment comprises determining a best estimate of an equivalent reference elevation pressure at the current position by combining the second equivalent reference elevation pressure from each reference unit.

20 Determining the best estimate of an equivalent reference elevation pressure of an embodiment comprises using a weighted average technique, wherein a weighting is a function of a horizontal distance between a location of a reference sensor unit and the current position.

25 Determining the best estimate of an equivalent reference elevation pressure of an embodiment comprises using a least squares fit to create a second order surface that best fits computed equivalent reference elevation pressures at each reference sensor unit of the set of reference sensor units, and interpolating the best estimate of sea level pressure at the current position using the n-order surface.

30 The remote receiver of an embodiment comprises a high-speed clock.

The remote receiver of an embodiment receives a pulse edge from a common time reference, wherein the remote receiver uses the high-speed clock to determine a time difference between an occurrence of the pulse edge and a rising edge of a sample clock.

5 The remote receiver of an embodiment applies a correction to the estimated range based on the time difference, wherein the correction improves accuracy of the estimated range.

The remote receiver of an embodiment includes a correlator that correlates a received signal with a pseudorandom code, wherein the correlator comprises a first shift register that includes a series plurality of sets of second shift registers having parallel 10 random access read capabilities.

Each set of the plurality of sets of second shift registers of an embodiment comprises a series plurality of shift register group primitives.

Each shift register group primitive of an embodiment includes an n-bit shift register group primitive.

15 Each shift register group primitive of an embodiment includes a 16-bit shift register group primitive.

Each set of second shift registers of an embodiment forms a 32-bit shift register.

The series plurality of sets of second shift registers of an embodiment comprises a plurality of sets of n-bit shift registers.

20 The series plurality of sets of second shift registers of an embodiment comprises 32 sets of second shift registers, wherein the first shift register is a 1024-bit shift register.

Shift operations of the first shift register of an embodiment occur at a clock rate of a clock coupled to the correlator.

Readout operations of the first shift register of an embodiment occur at a speed that 25 is at least two times the clock rate.

Readout operations of the first shift register of an embodiment occur at 32-times the clock rate.

The system of an embodiment comprises a series plurality of adders coupled to outputs of the series plurality of sets of second shift registers.

The series plurality of adders of an embodiment comprise an adder tree, wherein the adder tree comprises a wider bit-width adder primitive.

The series plurality of adders of an embodiment comprises an adder coupled to each set of the plurality of sets of n-bit shift registers.

5 The series plurality of adders of an embodiment comprises a first adder coupled to outputs of a first plurality of sets of second shift registers, a second adder coupled to outputs of a second plurality of sets of second shift registers, a third adder coupled to outputs of a third plurality of sets of second shift registers, and a fourth adder coupled to outputs of a fourth plurality of sets of second shift registers.

10 The system of an embodiment comprises a terminal adder coupled to outputs of the series plurality of adders.

The system of an embodiment comprises aligning outputs of the series plurality of adders in a series plurality of groups in the terminal adder.

15 An output of a first adder of an embodiment is aligned in a first group, an output of a second adder is aligned in a second group, an output of a third adder is aligned in a third group, and an output of a fourth adder is aligned in a fourth group in the terminal adder.

The terminal adder of an embodiment forms a sum by adding contents of the series plurality of groups.

20 The remote receiver of an embodiment temporarily uses a native receive chain of a plurality of native receive chains of the remote receiver to acquire the at least one of the positioning signals and satellite signals.

The plurality of native receive chains of an embodiment includes a diversity receive chain that improves receive diversity.

The remote receiver of an embodiment comprises a wide bandwidth receiver.

25 The remote receiver of an embodiment comprises a wide bandwidth cellular band receiver.

The remote receiver of an embodiment at least one of temporarily and permanently uses the diversity receive chain to acquire the positioning signals.

104. The positioning system of claim 2, comprising a communication system coupled to at least one of the remote receiver and the plurality of transmitters, wherein the communication system is a cellular communication system.

5 The plurality of transmitters of an embodiment is synchronized, wherein each transmitter of the plurality of transmitters transmits a signal including a pseudorandom number sequence and assistance data.

The assistance data of an embodiment comprises at least one of system time at a rising edge of a pulse of a waveform, system time at a falling edge of a pulse of a waveform, geocode data of the plurality of transmitters, geocode data of adjacent 10 transmitters adjacent to the plurality of transmitters, index of a sequence used by at least one transmitter in proximity of the plurality of transmitters, clock timing corrections for at least one transmitter, local atmospheric corrections, relationship of WAPS timing to GNSS time, indication of local environment to aid the remote receiver in pseudorange resolution, and at least one of an offset from base index of a set of pseudorandom sequences, a list of 15 pseudorandom number sequences from a set of transmitters, and a list of transmitters that utilize a particular pseudorandom number sequence.

The positioning application of an embodiment computes the position of the remote receiver by formulating a set of equations as a non-linear objective function and generating a best estimate of the position as a set of position parameters that minimize the objective 20 function.

The positioning application of an embodiment computes the position of the remote receiver by formulating a set of linearized equations and solving the set of linearized equations using least squares.

The positioning application of an embodiment computes the position of the remote 25 receiver using an approximate location of a set of transmitters of the plurality of transmitters and received signal strength (RSS) data of the set of transmitters.

The positioning application of an embodiment computes the position of the remote receiver by storing sample segments of the positioning signal in the remote receiver, and subsequently processing the sample segments to search, acquire, and compute range to the 30 plurality of transmitters.

The positioning application of an embodiment computes the position of the remote receiver using received signal strength data of the remote receiver.

The positioning application of an embodiment computes the position of the remote receiver using at least one of carrier phase data and code phase data of the positioning signals.

The positioning application of an embodiment computes the position of the remote receiver using differential positioning relative to at least one reference receiver.

The positioning application of an embodiment computes the position of the remote receiver using at least one of a range measurement and a proxy for a range measurement from a signal of opportunity, wherein the signal of opportunity is received from a positioning system, a Global Navigation Satellite System (GNSS), a Global Positioning System (GPS), a differential positioning system, a radio signal, a television signal, a wireless network system, a WiFi system, a cellular system, and a Bluetooth system.

The positioning application of an embodiment computes a final position of the remote receiver using a range measurement from at least one additional signal source combined with a range measurement determined using the positioning signals, wherein the final position comprises at least one of latitude, longitude and height.

The positioning application of an embodiment computes an optimized location solution of the remote receiver using a position measurement from at least one additional signal source combined with a position measurement determined using the positioning signals and a position quality metric from the at least one additional signal source.

The positioning application of an embodiment computes the position of the remote receiver using hybrid positioning, the hybrid positioning comprising a measurement from the positioning signals and a measurement from at least one additional source.

The positioning system information of an embodiment comprises timing synchronization and corresponding correction information.

Embodiments described herein include a reference system comprising a reference sensor array including at least one set of reference sensor units. Each set includes at least one reference sensor unit positioned at a known location. The system includes a remote receiver comprising an atmospheric sensor that collects atmospheric data at a position of

the remote receiver. The system includes a positioning application running on a processor and coupled to the remote receiver, wherein the positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from the at least one set of reference sensor units of the reference sensor array. The positioning application computes an elevation of the remote receiver using the reference pressure estimate.

5 Embodiments described herein include a reference system comprising: a reference sensor array comprising at least one set of reference sensor units, wherein each set includes at least one reference sensor unit positioned at a known location; a remote receiver comprising an atmospheric sensor that collects atmospheric data at a position of the remote receiver; and a positioning application running on a processor and coupled to the remote receiver, wherein the positioning application generates a reference pressure estimate at the position of the remote receiver using the atmospheric data and reference data from the at least one set of reference sensor units of the reference sensor array, wherein the positioning application computes an elevation of the remote receiver using the reference pressure estimate.

10 15

Embodiments described herein include a positioning system comprising a terrestrial transmitter network including a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information.

20 A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a remote receiver that acquires at least one of the positioning signals and satellite signals. The satellite signals are signals of a satellite-based positioning system. A first operating mode of the remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals.

25 The remote receiver includes a correlator that correlates a received signal with a pseudorandom code; and a server coupled to the remote receiver. A second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from information derived from at least one of the positioning signals and the satellite signals. The remote receiver receives and transfers

30

to the server information derived from at least one of the positioning signals and the satellite signals.

Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast 5 positioning signals comprising at least ranging signals and positioning system information, wherein a ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal; a remote receiver that acquires at least one of the positioning signals and satellite signals, wherein the satellite signals are signals of a satellite-based positioning system, wherein a first operating mode of the remote receiver 10 comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals, wherein the remote receiver includes a correlator that correlates a received signal with a pseudorandom code; and a server coupled to the remote receiver, wherein a second operating mode of the remote receiver comprises network-based positioning in which the 15 server computes a position of the remote receiver from information derived from at least one of the positioning signals and the satellite signals, wherein the remote receiver receives and transfers to the server information derived from at least one of the positioning signals and the satellite signals.

The correlator of an embodiment comprises a first shift register that includes a 20 series plurality of sets of second shift registers having parallel random access read capabilities.

Each set of the plurality of sets of second shift registers of an embodiment comprises a series plurality of shift register group primitives.

Each shift register group primitive of an embodiment includes an n-bit shift register 25 group primitive.

Each shift register group primitive of an embodiment includes a 16-bit shift register group primitive.

Each set of second shift registers of an embodiment forms a 32-bit shift register.

The series plurality of sets of second shift registers of an embodiment comprises a 30 plurality of sets of n-bit shift registers.

The series plurality of sets of second shift registers of an embodiment comprises 32 sets of second shift registers, wherein the first shift register is a 1024-bit shift register.

Shift operations of the first shift register of an embodiment occur at a clock rate of a clock coupled to the correlator.

5 Readout operations of the first shift register of an embodiment occur at a speed that is at least two times the clock rate.

Readout operations of the first shift register of an embodiment occur at 32-times the clock rate.

The system of an embodiment comprises a series plurality of adders coupled to 10 outputs of the series plurality of sets of second shift registers.

The series plurality of adders of an embodiment comprise an adder tree, wherein the adder tree comprises a wider bit-width adder primitive.

The series plurality of adders of an embodiment comprises an adder coupled to each set of the plurality of sets of n-bit shift registers.

15 The series plurality of adders of an embodiment comprises a first adder coupled to outputs of a first plurality of sets of second shift registers, a second adder coupled to outputs of a second plurality of sets of second shift registers, a third adder coupled to outputs of a third plurality of sets of second shift registers, and a fourth adder coupled to outputs of a fourth plurality of sets of second shift registers.

20 The system of an embodiment comprises a terminal adder coupled to outputs of the series plurality of adders.

The system of an embodiment comprises aligning outputs of the series plurality of adders in a series plurality of groups in the terminal adder.

An output of a first adder of an embodiment is aligned in a first group, an output of 25 a second adder is aligned in a second group, an output of a third adder is aligned in a third group, and an output of a fourth adder is aligned in a fourth group in the terminal adder.

The terminal adder of an embodiment forms a sum by adding contents of the series plurality of groups.

30 Embodiments described herein include a positioning system comprising a terrestrial transmitter network including a plurality of transmitters that broadcast

positioning signals comprising at least ranging signals and positioning system information.

A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a remote receiver that acquires at least one of the positioning signals and satellite signals. The satellite signals are signals of

5 a satellite-based positioning system. A first operating mode of the remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals.

The remote receiver operates in a reduced-power state when the positioning signals are not detected. The system includes a server coupled to the remote receiver. A second operating

10 mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from information derived from at least one of the positioning signals and the satellite signals. The remote receiver receives and transfers to the server information derived from at least one of the positioning signals and the satellite signals.

15 Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information, wherein a ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal; a remote receiver that acquires at least one of the

20 positioning signals and satellite signals, wherein the satellite signals are signals of a satellite-based positioning system, wherein a first operating mode of the remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals, wherein the remote receiver operates in a reduced-power state when the positioning signals

25 are not detected; and a server coupled to the remote receiver, wherein a second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from information derived from at least one of the positioning signals and the satellite signals, wherein the remote receiver receives and transfers to the server information derived from at least one of the positioning signals and

30 the satellite signals.

The positioning application of an embodiment is hosted on the remote receiver and the remote receiver computes the position.

The remote receiver of an embodiment is operated in a reduced-power state when the positioning signals are at least one of not detected and unusable.

5 The remote receiver of an embodiment uses a set of positioning signals from a set of the plurality of transmitters to determine position, wherein the remote receiver is operated in a reduced-power state when the set of positioning signals are at least one of not detected and unusable.

10 The remote receiver of an embodiment transitions from the reduced-power state to a full-power state in response to detecting at least one of motion of the remote receiver, change in position of the remote receiver, and change in signal conditions of the positioning signals.

15 Embodiments described herein include a positioning system comprising a terrestrial transmitter network including a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a remote receiver that acquires at least one of the positioning signals and satellite signals. The satellite signals are signals of a satellite-based positioning system. A first operating mode of the remote receiver 20 comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals. The remote receiver comprises a high-speed clock. The system includes a server coupled to the remote receiver. A second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver 25 from information derived from at least one of the positioning signals and the satellite signals. The remote receiver receives and transfers to the server information derived from at least one of the positioning signals and the satellite signals.

30 Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information,

wherein a ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal; a remote receiver that acquires at least one of the positioning signals and satellite signals, wherein the satellite signals are signals of a satellite-based positioning system, wherein a first operating mode of the remote receiver

5 comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals, wherein the remote receiver comprises a high-speed clock; and a server coupled to the remote receiver, wherein a second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver

10 from information derived from at least one of the positioning signals and the satellite signals, wherein the remote receiver receives and transfers to the server information derived from at least one of the positioning signals and the satellite signals.

The remote receiver of an embodiment receives a pulse edge from a common time reference, wherein the remote receiver uses the high-speed clock to determine a time difference between an occurrence of the pulse edge and a rising edge of a sample clock.

The remote receiver of an embodiment applies a correction to the estimated range based on the time difference, wherein the correction improves accuracy of the estimated range.

Embodiments described herein include a positioning system comprising a

20 terrestrial transmitter network including a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information. A ranging signal comprises information used to measure a distance to a transmitter broadcasting the ranging signal. The system includes a remote receiver that acquires at least one of the positioning signals and satellite signals. The remote receiver temporarily

25 uses a native receive chain of a plurality of native receive chains of the remote receiver to acquire the at least one of the positioning signals and satellite signals. The satellite signals are signals of a satellite-based positioning system. A first operating mode of the remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite

30 signals. The system includes a server coupled to the remote receiver, wherein a second

operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from information derived from at least one of the positioning signals and the satellite signals. The remote receiver receives and transfers to the server information derived from at least one of the positioning signals and

5 the satellite signals.

Embodiments described herein include a positioning system comprising: a terrestrial transmitter network comprising a plurality of transmitters that broadcast positioning signals comprising at least ranging signals and positioning system information, wherein a ranging signal comprises information used to measure a distance to a transmitter

10 broadcasting the ranging signal; a remote receiver that acquires at least one of the positioning signals and satellite signals, wherein the remote receiver temporarily uses a native receive chain of a plurality of native receive chains of the remote receiver to acquire the at least one of the positioning signals and satellite signals, wherein the satellite signals are signals of a satellite-based positioning system, wherein a first operating mode of the

15 remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals; and a server coupled to the remote receiver, wherein a second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from information derived from at least

20 one of the positioning signals and the satellite signals, wherein the remote receiver receives and transfers to the server information derived from at least one of the positioning signals and the satellite signals.

The remote receiver of an embodiment temporarily uses a native receive chain of a plurality of native receive chains of the remote receiver to acquire the at least one of the

25 positioning signals and satellite signals.

The plurality of native receive chains of an embodiment includes a diversity receive chain that improves receive diversity.

The remote receiver of an embodiment comprises a wide bandwidth receiver.

The remote receiver of an embodiment comprises a wide bandwidth cellular band

30 receiver.

The remote receiver of an embodiment at least one of temporarily and permanently uses the diversity receive chain to acquire the positioning signals.

The system described herein for use in position/timing accuracy can be used in one or more of the following applications in both local areas and wide areas, but is not limited to the following applications: asset tracking; people tracking; pet tracking; fire safety; mobile advertising; ad hoc position determination for public safety applications (e.g., a set of "mobile" transmitters can be moved to the location (for example, location of a fire) and those transmitters would form a local network to provide location signals to a set of receivers in that vicinity); military applications (e.g., transmitters can be deployed in an ad hoc fashion on the land or over the air to get precise indoor positions); adaptable bandwidth for applications that can provide the bandwidth to meet the accuracy needs; container tracking and vehicles that move containers around in indoor environments; geo-tagging; geo-fencing; E911 applications; palette tracking for medical applications and other applications that require palette tracking; femto-cells; timing references for femto-cells, timing receivers; providing location for security applications that authenticates based on location both indoors and outdoors; homing application (e.g., pet/asset tracking using WAPS and providing pedestrian navigation to the asset/pet using mobile phone). The WAPS system by itself or integrated with other location technologies can be further integrated into existing local area and/or wide area asset tracking and/or positioning systems.

The embodiments described herein include a positioning system comprising: a transmitter network comprising a plurality of transmitters that broadcast positioning signals; a remote receiver that acquires and tracks at least one of the positioning signals and satellite signals, wherein the satellite signals are signals of a satellite-based positioning system, wherein a first operating mode of the remote receiver comprises terminal-based positioning in which the remote receiver computes a position of the remote receiver from at least one of the positioning signals and the satellite signals; and a server coupled to the remote receiver, wherein a second operating mode of the remote receiver comprises network-based positioning in which the server computes a position of the remote receiver from at least one of the positioning signals and the satellite signals, wherein the remote

receiver receives and transfers to the server at least one of the positioning signals and the satellite signals.

The embodiments described herein include a method of determining position, comprising: receiving at a remote receiver at least one of positioning signals and satellite signals, wherein the positioning signals are received from a transmitter network comprising a plurality of transmitters, wherein the satellite signals are received from a satellite-based positioning system; and determining a position of the remote receiver using one of terminal-based positioning and network based positioning, wherein terminal-based positioning comprises computing a position of the remote receiver at the remote receiver using at least one of the positioning signals and the satellite signals, wherein network-based positioning comprises computing a position of the remote receiver at a remote server using at least one of the positioning signals and the satellite signals.

The components described herein can be located together or in separate locations. Communication paths couple the components and include any medium for communicating or transferring files among the components. The communication paths include wireless connections, wired connections, and hybrid wireless/wired connections. The communication paths also include couplings or connections to networks including local area networks (LANs), metropolitan area networks (MANs), wide area networks (WANs), proprietary networks, interoffice or backend networks, and the Internet. Furthermore, the communication paths include removable fixed mediums like floppy disks, hard disk drives, and CD-ROM disks, as well as flash RAM, Universal Serial Bus (USB) connections, RS-232 connections, telephone lines, buses, and electronic mail messages.

Aspects of the systems and methods described herein may be implemented as functionality programmed into any of a variety of circuitry, including programmable logic devices (PLDs), such as field programmable gate arrays (FPGAs), programmable array logic (PAL) devices, electrically programmable logic and memory devices and standard cell-based devices, as well as application specific integrated circuits (ASICs). Some other possibilities for implementing aspects of the systems and methods include: microcontrollers with memory (such as electronically erasable programmable read only memory (EEPROM)), embedded microprocessors, firmware, software, etc. Furthermore,

aspects of the systems and methods may be embodied in microprocessors having software-based circuit emulation, discrete logic (sequential and combinatorial), custom devices, fuzzy (neural) logic, quantum devices, and hybrids of any of the above device types. Of course the underlying device technologies may be provided in a variety of

5 component types, e.g., metal-oxide semiconductor field-effect transistor (MOSFET) technologies like complementary metal-oxide semiconductor (CMOS), bipolar technologies like emitter-coupled logic (ECL), polymer technologies (e.g., silicon-conjugated polymer and metal-conjugated polymer-metal structures), mixed analog and digital, etc.

10 It should be noted that any system, method, and/or other components disclosed herein may be described using computer aided design tools and expressed (or represented), as data and/or instructions embodied in various computer-readable media, in terms of their behavioral, register transfer, logic component, transistor, layout geometries, and/or other characteristics. Computer-readable media in which such formatted data and/or instructions

15 may be embodied include, but are not limited to, non-volatile storage media in various forms (e.g., optical, magnetic or semiconductor storage media) and carrier waves that may be used to transfer such formatted data and/or instructions through wireless, optical, or wired signaling media or any combination thereof. Examples of transfers of such

20 formatted data and/or instructions by carrier waves include, but are not limited to, transfers (uploads, downloads, e-mail, etc.) over the Internet and/or other computer networks via one or more data transfer protocols (e.g., HTTP, HTTPs, FTP, SMTP, WAP, etc.). When received within a computer system via one or more computer-readable media, such data and/or instruction-based expressions of the above described components may be processed by a processing entity (e.g., one or more processors) within the computer system in

25 conjunction with execution of one or more other computer programs.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise," "comprising," and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in a sense of "including, but not limited to." Words using the singular or plural number also include the 30 plural or singular number respectively. Additionally, the words "herein," "hereunder,"

“above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. When the word “or” is used in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list

5 and any combination of the items in the list.

The above description of embodiments of the systems and methods is not intended to be exhaustive or to limit the systems and methods to the precise forms disclosed. While specific embodiments of, and examples for, the systems and methods are described herein for illustrative purposes, various equivalent modifications are possible within the scope of

10 the systems and methods, as those skilled in the relevant art will recognize. The teachings of the systems and methods provided herein can be applied to other systems and methods, not only for the systems and methods described above. The elements and acts of the various embodiments described above can be combined to provide further embodiments. These and other changes can be made to the systems and methods in light of the above

15 detailed description.

In general, in the following claims, the terms used should not be construed to limit the systems and methods to the specific embodiments disclosed in the specification and the claims, but should be construed to include all systems and methods that operate under the claims. Accordingly, the systems and methods are not limited by the disclosure, but

20 instead the scope is to be determined entirely by the claims. While certain aspects of the systems and methods are presented below in certain claim forms, the inventors contemplate the various aspects of the systems and methods in any number of claim forms. Accordingly, the inventors reserve the right to add additional claims after filing the application to pursue such additional claim forms for other aspects of the systems and

25 methods.

CLAIMS:

1. A method for computing an elevation estimate of a mobile device, the method comprising:

generating a reference pressure estimate based on a pressure surface gradient model that uses reference data from one or more reference sensor units of a reference sensor array that are positioned at respective known locations; and

computing an elevation estimate of a mobile device at the position of the mobile device using the reference pressure estimate, and atmospheric data collected by an atmospheric sensor of the mobile device.

2. The method of claim 1, further comprising:

receiving, at one or more input components, one or more broadcast positioning signals from one or more transmitters of a terrestrial network, including at least one ranging signal comprising information used to measure a distance to a transmitter broadcasting the ranging signal;

determine whether the broadcast positioning signals are at least one of not detected, unusable, and both detectable and usable;

upon determining that the broadcast positioning signals are at least one of not detected and unusable, causing the mobile device to operate in a reduced-power state;

upon determining that the broadcast positioning signals are detectable and usable, causing the mobile device to operate in a full-power state and compute the elevation estimate based on the one or more broadcast positioning signals from the one or more transmitters of the terrestrial network to determine the position of the mobile device; and

causing the mobile device to transition from the reduced-power state to the full-power state in response to detecting at least one of motion of the mobile device, and change in the position of the mobile device.

3. The method of claim 1, further comprising:

determining whether the mobile device is operating in a first operating mode or a second operating mode;

upon determining that the mobile device is operating in the first operating mode, computing the elevation estimate using a first processor at the mobile device, wherein the mobile device includes the atmospheric sensor; and

upon determining that the mobile device is operating in the second operating mode, computing the elevation estimate using a second processor at a server.

4. The method of claim 1, wherein the reference data includes a reference elevation pressure for each of the one or more reference sensor units, wherein the reference elevation pressure for each reference sensor unit is based on a temperature at that reference sensor unit, a pressure at that reference sensor unit, and a known height of that reference sensor unit above a reference altitude.

5. The method of claim 1, wherein the reference data includes pressure and temperature data collected by each of the one or more reference sensor units, and the reference data further includes a known height above a reference altitude of each of the one or more reference sensor units.

6. The method of claim 1, wherein the reference data includes a first reference elevation pressure based on first pressure and temperature data collected at a first reference sensor unit of the one or more reference sensor units at a first location and a first known height in relation to a reference altitude, wherein the reference data includes a second reference elevation pressure for a second reference sensor unit based on second pressure and temperature data collected at the second reference sensor unit at a second location and a second known height in relation to the reference altitude, and wherein the reference pressure estimate is generated based on the first reference elevation pressure and the second reference elevation pressure.

7. The method of claim 6, further comprising:
collecting, at the atmospheric sensor, pressure and temperature data at the position of the mobile device;
detecting at the mobile device, rate of change of the pressure data; and
determining a vertical velocity of the mobile device using the rate of change.

8. The method of claim 1, wherein the reference pressure estimate is generated by:

receiving, from a first reference sensor unit of the one or more reference sensor units, a first reference elevation pressure associated with a reference height, wherein the first reference elevation pressure is based on a first known height of the first reference sensor unit, a first pressure measured by the first reference sensor unit, and a first temperature measured by the first reference sensor unit;

receiving, from a second reference sensor unit of the one or more reference sensor units, a second reference elevation pressure associated with the reference height, wherein the second reference elevation pressure is based on a second known height of the second reference sensor unit, a second pressure measured by the second reference sensor unit, and a second temperature measured by the second reference sensor unit; and

generating the reference pressure estimate based on the first reference elevation pressure and the second reference elevation pressure.

9. The method of claim 1, wherein the reference pressure estimate is generated by:

receiving, from a first reference sensor unit of the one or more reference sensor units, a first reference elevation pressure associated with a reference height, wherein the first reference elevation pressure is based on a first known height of the first reference sensor unit, a first pressure measured by the first reference sensor unit, and a first temperature measured by the first reference sensor unit;

receiving, from a second reference sensor unit of the one or more reference sensor units, a second reference elevation pressure associated with a reference height, wherein the second reference elevation pressure is based on a second known height of the second reference sensor unit, a second pressure measured by the second reference sensor unit, and a second temperature measured by the second reference sensor unit;

generating the reference pressure estimate based on a weighted average of the first reference elevation pressure and the second reference elevation pressure.

10. The method of claim 1, wherein the reference pressure estimate is generated by:

computing a first reference elevation pressure for a first reference sensor unit of the one or more reference sensor units, at a first known location based on a first known height of the first

reference sensor unit, a first pressure measured by the first reference sensor unit, and a first temperature measured by the first reference sensor unit;

computing a second reference elevation pressure for a second reference sensor unit of the one or more reference sensor units, at a second known location based on a second known height of the second reference sensor unit, a second pressure measured by the second reference sensor unit, and a second temperature measured by the second reference sensor unit;

generating the reference pressure estimate based on a weighted average of the first reference elevation pressure and the second reference elevation pressure, wherein a first weighting for the first reference elevation pressure is a function of a first horizontal distance between the first known location and a position of interest, and wherein a second weighting for the second reference elevation pressure is a function of a second horizontal distance between the second known location and the position of interest.

11. The method of claim 6, wherein the first pressure and temperature data, and the second pressure and temperature data, are filtered using an adaptive time scale.

12. The method of claim 1,

wherein the reference sensor array broadcasts the reference data using a communication link between the reference sensory array and the mobile device,

wherein the reference data comprises respective reference elevation pressure data for two or more reference sensor units based on pressure, temperature and elevation data for each of the two or more reference sensor units, and

wherein the reference data further includes differential pressure data derived as an offset value of a standard atmosphere.

13. The method of claim 1, wherein the method comprises:

recognizing when the position of the mobile device is approximately at a known position; upon recognizing that the position of the mobile device is approximately at the known position, obtaining an elevation estimate;

determining a difference between the elevation estimate and a known height of the known position; and

calculating, based on the difference between the elevation estimate and the known height, a correction value associated with drift related to the atmospheric sensor.

14. The method of claim 1,

wherein the reference data includes a first reference elevation pressure for a first reference sensor unit of the one or more reference sensor units,

wherein the first reference elevation pressure is based on a first pressure measured by the first reference sensor unit, a first temperature measured by the first reference sensor unit, and a first height of the first reference sensor unit,

wherein the reference data further includes a second reference elevation pressure for a second reference sensor unit of the one or more reference sensor units,

wherein the second reference elevation pressure is based on a second pressure measured by the second reference sensor unit, a second temperature measured by the second reference sensor unit, and a second height of the second reference sensor unit, and

wherein the reference data further includes one or more confidence measures.

15. The method of claim 1, wherein the reference data includes a first pressure measured by a first reference sensor unit of the one or more reference sensor units, a first temperature measured by the first reference sensor unit, a first height of the first reference sensor unit, a second pressure measured by a second reference sensor unit of the one or more reference sensor units, a second temperature measured by the second reference sensor unit, and a second height of the second reference sensor unit, and wherein the method comprises:

generating the reference elevation pressure estimate based on the first pressure, the first temperature, the first height, the second pressure, the second temperature, the second height, and a reference elevation that is different than elevations corresponding to the first and second heights.

16. The method of claim 1, further comprising:

identifying a first set of two or more elevation estimates from a first set of one or more mobile devices that are within a threshold difference in elevation from each other; and

determining, based on the first set of two or more elevation estimates, a first estimated elevation of a first floor in a structure.

17. The method of claim 1, wherein the method comprises:

generating aggregated reference data over a time period by identifying a plurality of different instances when the mobile device is at a known location;

accumulating deviations in the atmospheric data corresponding to the known location, and

generating a calibration correction from the accumulated deviations; and

calibrating the atmospheric sensor of the mobile device using the calibration correction.

18. The method of claim 1, wherein the reference pressure estimate is generated based on an interpolation using a first reference elevation pressure and a second reference elevation pressure, wherein the first reference elevation pressure is derived from pressure and temperature measurements at a first reference sensor unit of the one or more reference sensor units, and an elevation of the first reference sensor unit, and wherein the second reference elevation pressure is derived from pressure and temperature measurements at a second reference sensor unit of the one or more reference sensor units, and an elevation of the second reference sensor unit.

19. The method of claim 1, wherein the elevation estimate is computed using a reference elevation, wherein the reference elevation minimizes error due to elevation differences among elevations included in the reference data, and wherein the reference elevation comprises a mean elevation of respective elevations for two or more of the reference sensor units.

20. The method of claim 1, wherein the elevation estimate is derived using local constraint data, and

wherein the local constraint data includes any of: an elevation of at least one other mobile device in a vicinity of the position of the mobile device, terrain data of terrain in a vicinity of the position of the mobile device, and height of at least one level in of a structure in a vicinity of the position of the mobile device.

21. The method of claim 1, further comprises: storing, at a database, historical data measured during a time period, wherein the historical data comprises reference pressure data collected by the reference sensor array during the time period; and

determining the elevation estimate based on the historical data.

22. The method of claim 1, further comprising:

determining the elevation by relaxing the assumption of constant equivalent reference elevation pressure between a reference location of a reference sensor unit of the one or more reference sensor units, and a current position of the mobile device;

converting a first reference pressure at a reference location of a first reference sensor unit to a second reference pressure at a standard temperature;

determining a local temperature at the position of the mobile device;

converting the second reference pressure to a third reference pressure using the local temperature; and

determining the elevation estimate at the position using the third reference pressure.

23. The method of claim 1, further comprising:

determining a variation of reference elevation pressure with horizontal location using the reference data from each of at least two reference sensor units, wherein the reference pressure estimate is determined based on either:

a) a weighted average technique, wherein a weighting is a function of a horizontal distance between a respective location of a respective reference sensor unit and the position of the mobile device; or

b) a least squares fit to create a second order surface that best fits computed reference level pressures at each reference sensor unit, and interpolating the best estimate of equivalent reference elevation pressure at the position of the mobile device using the n-order surface.

NextNav, LLC

Patent Attorneys for the Applicant/Nominated Person

SPRUSON & FERGUSON





FIG.2






FIG.3







FIG.4






FIG.8




FIG.9




FIG.10




FIG. 11




FIG.12




FIG.13




FIG.14




FIGURE 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 24





FIGURE 27






FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46