




US 20190196660A1

(19) **United States**(12) **Patent Application Publication**
Skagmo et al.(10) **Pub. No.: US 2019/0196660 A1**(43) **Pub. Date: Jun. 27, 2019**(54) **TOUCH SENSING APPARATUS AND
METHOD FOR ASSEMBLY****Publication Classification**(51) **Int. Cl.**
G06F 3/042 (2006.01)(52) **U.S. Cl.**
CPC .. **G06F 3/0428** (2013.01); **G06F 2203/04103**
(2013.01); **G06F 3/0421** (2013.01)(71) Applicant: **FlatFrog Laboratories AB**, Lund (SE)(72) Inventors: **Daniel Skagmo**, Malmö (SE); **Robert Ehn**, Lund (SE); **Hakan Bergstrom**,
Torna-Hallestad (SE)(21) Appl. No.: **16/191,255**(22) Filed: **Nov. 14, 2018****Related U.S. Application Data**(63) Continuation of application No. PCT/SE2018/
050109, filed on Feb. 6, 2018.(30) **Foreign Application Priority Data**

Mar. 28, 2017 (SE) 1730085-6

(57) **ABSTRACT**

A touch sensing apparatus is disclosed comprising a panel that defines a touch surface, a plurality of light emitters and detectors arranged along a perimeter of the panel. The light emitters are arranged to emit a respective beam of emitted light that travels above the touch surface, wherein the light detectors are arranged to receive detection light from the emitted light. The plurality of light emitters and detectors are arranged above the touch surface and are connected to a substrate extending in a direction parallel with a normal axis of a plane in which the panel extends. A method of assembling a touch sensing apparatus is also disclosed.






FIG. 1A




FIG. 1B

FIG. 2




FIG. 3




FIG. 4A




FIG. 4B





FIG. 4C



200




FIG. 6




FIG. 7






FIG. 8



১৫৮৫



OF
THE
CITY OF
NEW YORK




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15A




FIG. 15C




FIG. 15B





FIG. 15D



உள்ளே

TOUCH SENSING APPARATUS AND METHOD FOR ASSEMBLY

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

[0001] Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND

Field of the Invention

[0002] The present invention relates to touch-sensing apparatus that operate by propagating light by diffusive light scattering above a panel, and in particular to optical and mechanical solutions for defining the light paths and control of curvature of the panel. The present invention relates furthermore to a method of assembling a touch sensing apparatus.

Background of the Invention

[0003] In one category of touch-sensitive panels known as ‘above surface optical touch systems’, a set of optical emitters are arranged around the periphery of a touch surface to emit light that is reflected to travel above the touch surface. A set of light detectors are also arranged around the periphery of the touch surface to receive light from the set of emitters from above the touch surface. An object that touches the touch surface will attenuate the light on one or more propagation paths of the light and cause a change in the light received by one or more of the detectors. The location (coordinates), shape or area of the object may be determined by analysing the received light at the detectors.

[0004] In a variant of such ‘above surface optical touch system’, illustrated in FIG. 1a in cross-section, the emitters **301** are arranged on a substrate **304**, and light from the emitters travel above the touch surface **302** of the panel **305** via reflection or scattering on an edge reflector or diffuser **303**. As shown in top-down view FIG. 1b, the light will then continue until deflected by a corresponding edge reflector at an opposing edge of the light transmissive panel, where the light will be scattered back down through the transmissive panel and onto the detectors **306**.

[0005] Detectors **306** are distributed around the periphery of touch surface **302**, to receive part of the propagating light. The light from each of emitters **301** will thereby propagate inside the transmissive panel **305** to a number of different detectors **306** on a plurality of light paths D. In the illustrated example, the apparatus **300** also includes a controller **320** which is connected to selectively control the activation of the emitters **301** and, possibly, the readout of data from the detectors **306**. Depending on implementation, the emitters **301** and/or detectors **306** may be activated in sequence or concurrently. The signal processor **330** and the controller **320** may be configured as separate units, or they may be incorporated in a single unit. One or both of the signal processor **330** and the controller **320** may be at least partially implemented by software executed by a processing unit **340**.

[0006] A problem with such previous systems is the cumbersome alignment between the components thereof, which makes assembly more difficult and costly. Sub-optimal alignment results in signal loss, which moreover is an

inherent problem in previous solutions due to the multiple components involved in the light scattering process. Another issue affecting the signal and scattering of the light in the touch sensing apparatus is uncontrolled glass warpage, i.e. distortions of the curvature of the light transmissive panel which will affect the light path and the detection process. While it is critical to accurately control such distortions, previous solutions incorporate complex solutions that may not allow to fully optimize glass warpage control in a mass production line without limiting the throughput of the production.

[0007] Some prior art systems rely on coupling and propagation of collimated light across the light transmissive panel. Such systems are however cumbersome to reliably implement due to the small tolerances with respect to the alignment of the components thereof. E.g. the light emitters- and detectors need to be precisely aligned in relation to various lenses and reflect the light via concave and/or convex reflection and/or refraction to get the desired collimation. Such precise alignment may be difficult to achieve in mass production. The use of collimated light, or light reflected by means of specular reflection, also adds to this complexity, which in turn results in a more expensive and less compact system. Furthermore, to reduce system cost, it may be desirable to minimize the number of electro-optical components.

SUMMARY OF THE INVENTION

[0008] An objective is to at least partly overcome one or more of the above identified limitations of the prior art.

[0009] One objective is to provide a touch-sensitive apparatus based on “above-surface” light propagation which is robust and easy to assemble.

[0010] Another objective is to provide an “above-surface”-based touch-sensitive apparatus with efficient use of light.

[0011] One or more of these objectives, and other objectives that may appear from the description below, are at least partly achieved by means of touch-sensitive apparatuses according to the independent claims, embodiments thereof being defined by the dependent claims.

[0012] According to a first aspect, a touch sensing apparatus is provided comprising a panel that defines a touch surface, a plurality of light emitters and detectors arranged along a perimeter of the panel. The light emitters are arranged to emit a respective beam of emitted light above the touch surface, wherein the light detectors are arranged to receive detection light from the emitted light. The plurality of light emitters and detectors are connected to a substrate extending in a direction parallel with a normal axis of a plane in which the panel extends.

[0013] Preferably the plurality of light emitters and detectors are arranged above the touch surface.

[0014] Preferably the substrate extends at least partly above the touch surface, whereby the plurality of light emitters and detectors are connected to a portion of the substrate extending above the touch surface.

[0015] Preferably the substrate is fixed to a carrier mounted around the perimeter of the panel.

[0016] Preferably the carrier is arranged to at least partly enclose edges the panel.

[0017] Preferably the carrier comprises fixing elements configured to attach the carrier to a display unit.

[0018] Preferably the fixing elements are configured to attach the position of the substrate in relation to the carrier and/or in relation to the display unit.

[0019] Preferably the fixing elements are configured to interlock with a mounting element for locking the position of the carrier and/or the substrate to the display unit.

[0020] Preferably the fixing elements comprise openings, wherein the carrier forms a cavity having walls at least partly enclosing the substrate, and wherein at least one of the walls comprises at least one of said openings.

[0021] Preferably the fixing elements comprise openings arranged in the carrier and in the substrate, wherein first openings of the carrier are aligned with second openings of the substrate, the first and second openings being configured to receive a mounting element configured to lock the position of the carrier and/or the substrate to the display unit.

[0022] Preferably the carrier is configured to be attachable to the display unit at an adjustable position along a direction parallel to the normal axis, whereby a distance between the panel and the display unit along the normal axis is variable upon attaching the carrier to the display unit at at least two different adjustable positions.

[0023] Preferably the fixing elements are configured to attach the carrier to the display unit at the adjustable positions along the direction parallel to the normal axis.

[0024] Preferably the openings are separated along a direction parallel to the normal axis, and/or wherein the carrier is attachable to a plurality of second openings in a display support of the display unit, the plurality of second openings being separated along the normal axis.

[0025] Preferably the carrier is formed from a single monolithic piece of material.

[0026] Preferably the substrate extends in a longitudinal direction along the perimeter of the panel, the substrate comprising secondary fixing units configured for variably attaching the position of the substrate on the carrier along the longitudinal direction and/or in the direction of the normal axis.

[0027] Preferably vertical alignment units are arranged between adjacent substrates extending in a longitudinal direction along the perimeter of the panel, wherein the vertical alignment units are configured to variably position the adjacent substrates in the direction of the normal axis so that an angle between the adjacent substrates is adjustable.

[0028] Preferably a plurality of substrates extend in a longitudinal direction along the perimeter of the panel, wherein a first substrate of said plurality of substrates comprises a connection unit configured to directly interlock with a subsequent connection unit of a subsequent substrate when arranged adjacent said subsequent substrate.

[0029] Preferably a sealing window is arranged around the perimeter of the panel, wherein the sealing window comprises a first surface facing the light emitters or the light detectors and an opposite second surface arranged adjacent the touch surface, whereby the emitted or detected light propagates between the first and second surface, and wherein at least one of the first and second surfaces comprises a light collimating surface configured to collimate light propagating above the touch surface.

[0030] Preferably the second surface extends in the direction of the normal axis between a base surface of the sealing window, facing the panel, and an opposite top surface of the sealing window, wherein the base surface is offset from the top surface along the direction of the plane with an offset

distance so that the second surface forms an angle relative the normal axis, and wherein the second surface comprises a light collimating surface.

[0031] According to a second aspect, a touch sensing apparatus is provided comprising a panel extending in a plane having a normal axis, the panel defining a touch surface, a plurality of light emitters and detectors arranged along a perimeter of the panel, wherein the light emitters are arranged to emit a respective beam of emitted light above the touch surface, wherein the light detectors are arranged to receive detection light from the emitted light. The touch sensing apparatus comprises a sealing window arranged around the perimeter, wherein the sealing window comprises a first surface facing the light emitters or the light detectors and an opposite second surface arranged adjacent the touch surface, whereby the emitted or detected light propagates between the first and second surface, wherein the second surface extends in the direction of the normal axis between a base surface of the sealing window, facing the panel, and an opposite top surface of the sealing window, wherein the base surface is offset from the top surface along the direction of the plane with an offset distance so that the second surface forms an angle relative the normal axis, and wherein the second surface comprises a light collimating surface configured to collimate light propagating above the touch surface.

[0032] Preferably the first surface and/or second surface form a curved edge convex to the sealing window.

[0033] According to a third aspect, a method of assembling a touch sensing apparatus is provided comprising; attaching a substrate having a plurality of light emitters and detectors to a carrier; attaching the carrier around a perimeter of a panel and arranging the substrate to extend in a direction parallel with a normal axis of a plane in which the panel extends.

[0034] Preferably the plurality of light emitters and detectors are arranged above the touch surface.

[0035] Preferably the carrier if formed from a single monolithic piece of material, the carrier forming a cavity having walls at least partly enclosing the substrate, wherein at least one of the walls comprise openings, the method comprising fixing the carrier to a display unit by fixing mounting elements through said openings.

[0036] Preferably the method comprises adjusting a distance between the panel and a display unit along the normal axis by attaching the carrier to the display unit at at least two different adjustable positions along a direction parallel to the normal axis.

[0037] Preferably the method comprises adjusting a radius of curvature of the panel in the direction of the normal axis by attaching the carrier to a display unit at at least two different adjustable positions along a direction parallel to the normal axis.

[0038] According to a fourth aspect there is provided a touch sensing apparatus, comprising: a panel that defines a touch surface, a plurality of light emitters and detectors arranged along a perimeter of the panel and the light emitters are arranged to emit a respective beam of emitted light above the touch surface, and the light emitters are arranged to receive detection light from the emitted light, a substrate on which the plurality of light emitters and detectors are mountable; and a sealing window sealable against at least one surface of the touch sensing apparatus for sealing a cavity around the plurality of light emitters and detectors

wherein the sealing window comprises at least one reference surface for aligning the substrate with respect to the sealing window.

[0039] Preferably the sealing window is sealable between the touch surface and a surface of the substrate.

[0040] Preferably the surface of substrate is a surface of a carrier for protecting components of the touch sensing apparatus.

[0041] Preferably the carrier comprises an upper portion which overlaps a portion of the perimeter of the panel and the sealing window is sealable between the touch surface and the underside of the overlapping upper portion.

[0042] Preferably the at least one reference surface is arranged to engage with a reciprocal reference surface on the substrate.

[0043] Preferably the at least one reference surface comprises a first portion for aligning in a first direction and a second portion for aligning in a second direction.

[0044] Preferably the at least one reference surface aligns the sealing window with respect to the substrate in a plane parallel with the touch surface.

[0045] Preferably the at least one reference surface aligns the sealing window with respect to the substrate at a height above the touch surface.

[0046] Preferably the sealing window comprises at least one resiliently deformable seal engagable with the substrate.

[0047] Preferably the resiliently deformable seal comprises the at least one reference surface.

[0048] Preferably the seal is extrudable along one or more surfaces of the sealing window.

[0049] Preferably the at least one reference surface substantially extends the entire length of the sealing window.

[0050] Preferably the sealing window and/or the substrate comprise a projection having a cross-sectional shape for positive engagement with a reciprocal hole in the substrate and/or sealing window and the at least one reference surface is part of the projection.

[0051] Preferably the sealing window and/or the substrate comprise a resiliently deformable projection wherein the projection comprises the at least one reference surface comprises and the projection is deformable on engagement with the substrate and/or sealing window and forms a snap-fit engagement therebetween.

[0052] Preferably the sealing window comprises a plurality of reference surfaces.

[0053] Preferably the at least one reference surface comprises at least one discrete upstanding projection for engagement with reciprocal hole in the substrate.

[0054] Preferably the at least one upstanding projection is one or more of, pegs, hooks, latches, clamps or fasteners.

[0055] According to a fifth aspect there is provided a method of manufacture of the touch sensing apparatus comprising: mounting a plurality of light emitters and detectors to a substrate, attaching the substrate around a perimeter of a panel; and mounting a sealing window against at least one surface of the touch sensing apparatus for sealing a cavity around the plurality of light emitters and detectors wherein the sealing window comprises at least one reference surface for aligning the substrate with respect to the sealing window.

[0056] Further examples of the invention are defined in the dependent claims, wherein features for the second aspect of the disclosure are as for the first aspect mutatis mutandis.

[0057] Some examples of the disclosure provide for a touch sensing apparatus that is easier to manufacture and assemble.

[0058] Some examples of the disclosure provide for a touch sensing apparatus with fewer steps of assembly.

[0059] Some examples of the disclosure provide for a touch sensing apparatus that is less costly to manufacture.

[0060] Some examples of the disclosure provide for a facilitated alignment of emitters and detectors of touch sensing apparatus.

[0061] Some examples of the disclosure provide for facilitated control of the curvature of the touch surface of a touch sensing apparatus.

[0062] Some examples of the disclosure provide for a more robust touch sensing apparatus.

[0063] Some examples of the disclosure provide for a touch sensing apparatus that is more reliable to use.

[0064] Some examples of the disclosure provide for a touch sensing apparatus that has a better signal-to-noise ratio of the detected light.

[0065] Some examples of the disclosure provide for a more compact touch sensing apparatus.

[0066] Still other objectives, features, aspects and advantages of the present disclosure will appear from the following detailed description, from the attached claims as well as from the drawings.

[0067] It should be emphasized that the term “comprises/comprising” when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

[0068] These and other aspects, features and advantages of which examples of the invention are capable of will be apparent and elucidated from the following description of examples of the present invention, reference being made to the accompanying drawings, in which;

[0069] FIG. 1a is a section view of a touch sensing apparatus according to the prior art;

[0070] FIG. 1b is a top-down view of a touch sensing apparatus according to the prior art;

[0071] FIG. 2 is a schematic illustration, in a cross-sectional side view, of a touch sensing apparatus according to one example;

[0072] FIG. 3 is a schematic illustration, in a perspective side view, of a touch sensing apparatus according to one example;

[0073] FIG. 4a is a schematic illustration, in a side view of FIG. 2, of a touch sensing apparatus according to one example;

[0074] FIG. 4b is a schematic illustration of a magnified section of FIG. 4a, according to one example;

[0075] FIG. 4c is a schematic illustration of a magnified section of FIG. 4a, according to one example;

[0076] FIG. 5a is a schematic illustration, in a cross-sectional side view, of a touch sensing apparatus according to one example;

[0077] FIG. 5b is a schematic illustration of a magnified section of FIG. 5a, according to one example;

[0078] FIG. 6 is a flow chart of a method of assembling a touch sensing apparatus according to one example;

[0079] FIG. 7 is a schematic exploded perspective view of different layers of the touch-sensing apparatus according to one example;

[0080] FIG. 8 is a perspective schematic view of through a cross section of the touch sensing apparatus according to one example;

[0081] FIG. 9 is a cross sectional view of the touch sensing apparatus according to one example;

[0082] FIG. 10 is a cross sectional view of the touch sensing apparatus according to one example;

[0083] FIG. 11 is a cross sectional view of the touch sensing apparatus according to one example;

[0084] FIG. 12 is a perspective schematic view of through a cross section of the touch sensing apparatus according to one example;

[0085] FIG. 13 is a schematic perspective view of the touch sensing apparatus according to one example;

[0086] FIG. 14 is a cross sectional view of the touch sensing apparatus according to one example;

[0087] FIGS. 15a, 15b, 15c, and 15d show magnified cross-sectional views of the touch sensing apparatus according to different examples; and

[0088] FIG. 16 is a schematic perspective view of the touch sensing apparatus according to one example.

DETAILED DESCRIPTION

[0089] In the following, embodiments of the present invention will be presented for a specific example of a touch-sensitive apparatus 100. Throughout the description, the same reference numerals are used to identify corresponding elements.

[0090] FIG. 1a schematically illustrates a variant of an 'above surface optical touch system', as discussed in the Background Art section above, where the light from the emitters 301 travel above the touch surface 302 of the panel 305 via reflection on an edge reflector 303. FIG. 1b illustrates a top plan view of FIG. 1a in an example of a touch-sensitive apparatus 100.

[0091] FIG. 2 schematically illustrate a touch sensing apparatus 100 comprising a light transmissive panel 101 that defines a touch surface 102. In some embodiments the light transmissive panel 101 is located above a display 130 and permits light generated by the display 130 to propagate therethrough. However in other embodiments the light transmissive panel 101 can comprise light blocking material and does not permit the transmission of light therethrough. For example, the touch sensing apparatus 100, can be a trackpad or another touch interface which is remote from the display unit 130. Hereinafter the term "light transmissive panel" 101 will be used to describe either a light transmissive panel 101 or a solid, opaque panel 101.

[0092] A plurality of light emitters 103 and detectors 103' are arranged along a perimeter 104 of the light transmissive panel 101. The light emitters 103 are arranged to emit a respective beam of emitted light 105 above the touch surface 102. I.e. while the touch surface 102 extends along a plane 108, having a normal axis 107 directed towards a user performing touch operations on the touch surface 102, the emitted light 105 travels parallel with plane 108 and at a certain distance from the touch surface 102 in the direction of the normal axis 107, as schematically illustrated with respect to light beam 105, 105', in e.g. FIG. 2. Light 105, 105', can thus travel across the touch surface 102, between

opposite sides thereof, without being reflected inside the light transmissive panel 101 itself.

[0093] In other embodiments, the plurality of light emitters 103 and detectors 103' are optionally arranged along a perimeter 104 of the light transmissive panel 101 at a different height. In some embodiments, the light emitters 103 and/or detectors 103' are arranged to emit a respective beam of emitted light 105 below the touch surface 102 and the light beams are guided around the light transmissive panel 101. The light beams can be guided around the light transmissive panel 101 with additional reflective components (not shown). For the purposes of brevity, the embodiments discussed hereinafter refer to the plurality of light emitters 103 and detectors 103' being arranged above the touch surface 102, but the embodiments also include the arrangement where the plurality of light emitters 103 and detectors 103' are mounted below the touch surface 102.

[0094] The light detectors 103' are arranged to receive detection light 105' from the emitted light 105. FIG. 2 illustrates a section of the touch sensing apparatus 100 adjacent the perimeter 104 of the light transmissive panel 101. In this section, the emitters and detectors 103, 103', are shown in the same view, as well as the emitted and detected light 105, 105', for clarity of presentation. The plurality of light emitters and detectors 103, 103', are arranged above the touch surface 102 and are connected to a substrate 106 extending in a direction 107' parallel with a normal axis 107 of a plane 108 in which the light transmissive panel extends. By having the substrate 106 extending in parallel with the normal axis 107, the plurality of emitters and detectors 103, 103' are conveniently arranged, above the touch surface 102 to achieve a compact footprint in the direction of the plane 108 of the touch sensing apparatus 100 around the perimeter 104, while achieving a direct light path for the emitted or detected light 105, 105', above and across and touch surface 102. Thus, the emitted light 105 does not have to be reflected in order to diffusively spread above and across the touch surface 102, and a detector 103' may directly receive detection light 105' by being correspondingly positioned above the touch surface 102 at an opposite position anywhere around the perimeter 104. The amount of available light that can be utilized for the detection and characterization of an object touching the touch surface 102 can thus be maximized, and the signal to noise ratio can be improved. The touch sensing apparatus 100 may comprise a sealing window 126 as illustrated in FIG. 2, shielding the emitters and detectors 103, 103', from the outside. The emitted and detected light 105, 105', may thus only have to propagate through the sealing window 126 along the light path between the emitters and detectors 103, 103'. The sealing window 126 provides sealing around the perimeter 104 of the light transmissive panel 101 and protects the emitters and detectors 103, 103' and the display.

[0095] Having the substrate extending in the direction 107' being parallel with the normal axis 107 and the emitters and detectors 103, 103', arranged above the touch surface 102 provides for a less complex alignment to maximize the detection performance of the touch sensing apparatus 100. The position of the substrate 106 in the direction of the normal axis 107 can be accurately varied to achieve optical alignment with respect to the emitters and detectors 103, 103'. The ability to achieve an accurate positioning of the substrate 106, and consequently the emitters and detectors 103, 103', attached thereto, is also due to the increased

accuracy by which the dimensions of the substrate 106 can be defined along the direction of the substrate 106 aligned with the normal axis 107 in FIG. 2. I.e. the substrate 106 is elongated and extends in a longitudinal direction 123 (FIG. 4a) around the perimeter 104 of the light transmissive panel 101, and it has a short-side extending in parallel with the normal axis 107. The short-side of the substrate 106, illustrated in the cross-sectional view of FIG. 2, may be manufactured to smaller tolerances, and by aligning this side with the normal axis 107, the tolerances for the alignment of the emitters and detectors 103, 103', along the normal axis 107 can be improved. The alignment can thus be both improved, and facilitated as discussed above. The latter advantage also provides for facilitated and less costly mass production of the touch sensing apparatus 100 and the various touch base display systems in which it may be implemented.

[0096] The substrate 106 may extend at least partly above the touch surface 102, whereby the plurality of light emitters and detectors 103, 103', are connected to a portion 109 of the substrate extending above the touch surface 102. This further provides for achieving a more robust alignment of the emitters and detectors 103, 103', relative to the light transmissive panel 101, by being directly joined to the substrate 106, and thereby simultaneously arranged above the touch surface 102. It may be conceivable however that the emitters and detectors 103, 103', are connected to the substrate 106 via connection elements (not shown) extending between the substrate 106 and to a position above the touch surface 102.

[0097] The substrate 106 may be fixed to a carrier 110 mounted around the perimeter 104 of the light transmissive panel 101, as schematically illustrated in FIGS. 1a, 1b and 2. By directly joining the substrate 106 to the carrier 110 provided around the perimeter 104, the assembly of the touch sensing apparatus 100 may be further facilitated, as the amount of components can be kept at a minimum. For example, the substrate 106 can be accurately fixed in relation to the carrier 110, due to the small tolerances possible in the direction of the substrate 106 aligned in parallel with the normal axis 107 in FIG. 2, as discussed above. The carrier 110 may for example comprise a cavity 116, as discussed further below, being precisely dimensioned to accommodate the width of the substrate 106 along the direction 107', i.e. the short-side of the substrate 106. Then, accurate positioning of the emitters and detectors 103, 103', in relation to the light transmissive panel 101 is possible as the carrier 110 is mounted around the perimeter 104 thereof. The carrier 110 may extend substantially in the direction 107' parallel with the normal axis 107, as with the substrate 107, to achieve a compact mounting around the perimeter 104. In some embodiments the carrier 110 may also be the substrate 106 or the emitters and detectors 103, 103' are mounted directly to the carrier 110.

[0098] Having the substrate 106 fixed to the carrier 110 allows also for having the carrier 110 wired as an electrical ground reference layer of the substrate 106.

[0099] The carrier 110 may be arranged to at least partly enclose edges 111 of the light transmissive panel 101, as shown in the example of FIG. 2. This provides for further increasing the robustness of the touch sensing apparatus 100, and improving the accuracy of the alignment of the emitters and detectors 103, 103', in relation to the light transmissive panel 101 since the carrier 110, having the emitters and detectors 103, 103', fixed thereto, may also be directly supporting the light transmissive panel 101 around

the perimeter 104. The carrier 110 may comprise a slot in which the light transmissive panel 101 is fitted around the perimeter 104.

[0100] The carrier 110 may comprise fixing elements 112 configured to attach the carrier 110 to a display unit 113, 121. The display unit may comprise a display support 121 and a display panel 113, which collectively is referred to as a display unit in the present disclosure. Having the carrier 110 attachable to the display unit 113, 121, by fixing elements 112, advantageously provides for further facilitating the assembly of the touch sensing apparatus 100 to a display unit, since the carrier 110 can be directly joined to the latter. Alignment is thus facilitated, due to the minimum amount of components needing such alignment to each other. The robustness of the touch sensing apparatus 100 is further improved, while mass production is made less complex due to the minimized number of assembly steps. The fixing elements 112 may comprise any elements configured to provide for fixing of the position of the carrier 110 to the display unit 113, 121. In the example shown in FIG. 2, the carrier 110 has openings 115, 115', 115'', discussed further below, which may be aligned with corresponding openings 127 of a support of the display unit 121, through which mounting elements 114 may be positioned for the fixing. It is conceivable however that the carrier 110 has other types of recesses or protrusions which may interlock with a corresponding mating surface of the display unit 113, 121.

[0101] The fixing elements 112 may be configured to fix the position of the substrate 106 in relation to the carrier 110. Thus, besides from fixing the position of the carrier 110 relative to the display unit 113, 121, the fixing elements 112 may also fix or at least support the position of the substrate 106 in relation to the carrier 110. It is conceivable that the substrate 106 may first be arranged in relation to the carrier 110, and the fixing elements 112 may be arranged to support and strengthen the fixing therebetween, while simultaneously fixing the carrier 110 to the display unit 113, 121. This may further provide for increasing the stability and ultimately accuracy of the touch sensing apparatus 100. From a similar aspect, the fixing elements 112 may be configured to fix the position of the substrate 106 in relation to the display unit 113, 121. This may be seen as a consequence from the above, i.e. the fixing elements 112 contributing to the fixing of the substrate 106 to the carrier 110, which in turn is fixed to the display unit 113, 121. It is however conceivable that the fixing elements 112 may fix the substrate 106 directly to the display unit 113, 121, in which case the carrier 110 may act as a further support for the substrate 106.

[0102] In one example, as discussed further below, the substrate 106 may comprise second openings 118 which provides for such fixing or support. As mentioned, this may further provide for increasing the stability and ultimately accuracy of the touch sensing apparatus 100.

[0103] The fixing elements 112 may be configured to interlock with a mounting element 114 for locking the position of the carrier 110 and/or the substrate 106 to the display unit 113, 121. FIGS. 2-3 show examples of having an elongated mounting element 114 joining the carrier 110 and/or the substrate 106 to the display unit 113, 121. The mounting element 112 may however comprise any fastening element configured to exert a force between the carrier 110 and/or the substrate 106 to the display unit 113, 121, such as pins, bolts, screws, clips, clamps, locks, bars, rods, anchors, latches, clasps.

[0104] The fixing elements 112 may comprise openings 115, 115', 115'', as illustrated in FIGS. 2-3. The carrier 110 may form a cavity 116 having walls 117 at least partly enclosing the substrate 106, illustrated in the example of FIG. 2. This may provide for increased stability of the fixing of the position of the substrate 106 in relation to the carrier 110. At least one of the walls 117 may comprise at least one of the openings 115, 115', 115'', as further illustrated in FIG. 2. Being able to directly fix the walls 117 of the carrier 110 enclosing the substrate 106 to the display unit 121, 113, provides for further simplifying manufacturing, and at the same time further increase the accuracy of the alignment of e.g. the emitters and detectors 103, 103', in relation to the light transmissive panel 101, since the minimized number of intermediate mounting components improves tolerance control. I.e. build-up of mounting errors in each assembly step is reduced and controlled. It is conceivable that the walls 117 may be fixed to the display unit 113, 121, by other fixing elements 112, such as recesses or protrusions interlocking with correspondingly mating surfaces of the display unit 113, 121, and/or fastening elements as exemplified above.

[0105] The fixing elements 112 may comprise openings 115, 115', 115'', 118, arranged in the carrier 110 and in the substrate 106. First openings 115, 115', 115'' of the carrier 110 may be aligned with second openings 118 of the substrate 106, as illustrated in the example of FIG. 2. The first and second openings 115, 115', 115'', 118 may be configured to receive a mounting element 114 configured to lock the position of the carrier 110 and/or the substrate 106 to the display unit 113, 121. This provides for further facilitated and improved alignment and assembly, and increased robustness. In the example of FIG. 2, the carrier 110 encloses the substrate 106 such that two opposite openings 115, 115'', of the carrier are arranged on either side of the substrate 106, but it is conceivable that the carrier 110 may be arranged on one side only of the substrate 106.

[0106] The carrier 110 may be configured to be attachable to the display unit 121, 113, at an adjustable position 119, 119', along a direction 117'' parallel to the normal axis. A distance 120 between the light transmissive panel 101 and the display unit 113 along the normal axis 107 may thus be variable upon attaching the carrier to the display unit 113, 121 at at least two different adjustable positions 119, 119'. For example, turning to FIG. 3, the carrier 110 is attached at a first position 119 to the support of the display unit 121, via fixing unit 112. The first position 119 provides for the given distance 120 between the panel of the display unit 113. The distance 120 may then be decreased by instead attaching the carrier 110 at a second position 119' which is off-set with respect to the first position 119 in the positive direction of the normal axis 107, or the direction 107'' as illustrated in FIG. 3. If the fixing point to the support of the display unit 121 remains constant, e.g. at the opening 127 of a support 121 as illustrated, the carrier 110 will be moved in the opposite direction to the normal axis 107 and the distance 120 will be decreased. Having the carrier 110 being attachable to the display unit 121, 113, at an adjustable position 119, 119', along a direction 117'' parallel to the normal axis 107, thus provides for simple and efficient adjustment of the position of the light transmissive panel 101.

[0107] Besides from overall controlling the distance 120, as discussed, such adjustment provides for efficiently controlling and varying the curvature of the light transmissive panel 101. I.e. varying the distance 120 as discussed at a

second intermediate location 128', between opposite ends of the carrier 110, along the longitudinal direction 123, while maintaining the distance 120 at the opposite ends, such as at a first location 128, will affect the curvature of the carrier 110, and thereby the curvature of the light transmissive panel 101. E.g. decreasing the distance 120 at the second location 128' can produce a more concave shape, i.e. a decreased radius of curvature, of the carrier 110 and the light transmissive panel 101, in the direction of the normal axis 107. Increasing the distance 120 between the mentioned opposite ends can instead increase the radius of curvature in the direction of the normal axis 107. The curvature or warping of the light transmissive panel 101 can thus be controlled efficiently in a facilitated manner, which is advantageous for increasing throughput in mass-production of displays incorporating the touch sensing apparatus 100 while keeping the warp of the light transmissive panel 101 under control. An optimized curvature of the light transmissive panel 101 increases the reliability and accuracy of the touch sensing apparatus 100.

[0108] The fixing elements 112 may be configured to attach the carrier 110 to the display unit 121 at the adjustable positions 119, 119', along the direction 117'' parallel to the normal axis 107. Thus, the fixing units 112 be arranged at the different adjustable positions 119, 119', to adjust the distance 120 and the curvature of the a light transmissive panel 101 while providing for securely attaching the carrier to the display unit 113, 121. The fixing elements 112 may thus be arranged at least at the first and second locations 128, 128', along the longitudinal direction 123 as discussed above, where each of the locations in the longitudinal direction 123 may have at least two adjustable positions 119, 119', as illustrated in the example of FIG. 3.

[0109] The openings 115, 115', of the carrier 110 may be separated along a direction 117'' parallel to the normal axis 107, as illustrated in FIG. 3. Alternatively, or in addition, the carrier 110 may be attachable to a plurality of second openings 122 in a display support 121 of the display unit, where the plurality of second openings 122 are separated along the normal axis 107. Thus, the position 119, 119', may be remained fixed while the carrier 110 is attached to the support 121 at the various second openings 122, to adjust the curvature of the light transmissive panel 101 and/or the distance 120 as discussed above. Although the examples in FIGS. 2-3, show openings 115, 115', 115'', 127, it is conceivable that the attachment between the carrier 110 and the display unit 121, 113, is provided by other fixing elements 112 as exemplified above.

[0110] The carrier 110 may be formed from a single monolithic piece of material. The structural integrity and the stability of the carrier 110 can thereby be increased, which further optimizes the parameters discussed above with respect to alignment, robustness, ease of assembly etc. One example of a possible process by which the carrier can be formed as a single piece of material is an extrusion process, but it is conceivable that the carrier 110 may be formed from other hot or cold metal or polymer working processes such as drawing, rolling, or molding processes.

[0111] The substrate 106 may extend in a longitudinal direction 123 along the perimeter 104 of the light transmissive panel 101. FIG. 4a illustrates a view of a plurality of substrates 106, 106', extending along the longitudinal direction 123. The light transmissive panel 101 and the carrier 110 holding the substrates have been excluded in the view

for clarity of presentation. The substrates **106**, **106'**, may comprise secondary fixing units **124**, **124'**, configured for variably attaching the position of each of the substrates **106**, **106'**, on the carrier **110** along the longitudinal direction **123** and/or in the direction of the normal axis **107**. This provides for more accurately adjusting the position of the substrates **106**, **106'**, in relation to the light transmissive panel **101**. While each of the substrates **106**, **106'**, may be within tolerances, the accumulated error obtained when several substrates **106**, **106'** are connected along the longitudinal direction **123** may exceed the total tolerance of the full length of the light transmissive panel **101**. Such accumulation of errors may be effectively prevented by having secondary fixing units **124**, **124'**, as elucidated above. The secondary fixing units **124**, **124'**, may be provided on various locations on the substrates **106**, **106'**, to allow for adjusting the position, such as on opposite ends thereof.

[0112] The touch sensing apparatus **100** may comprise vertical alignment units **135** arranged between adjacent substrates **106**, **106'**, extending in a longitudinal direction **123** along the perimeter **104** of the light transmissive panel **101**. The vertical alignment units **135** are configured to variably position the adjacent substrates **106**, **106'**, in the direction of the normal axis **107** so that an angle **136** between the adjacent substrates **106**, **106'**, can be adjusted. FIG. **4b** schematically illustrates a vertical alignment unit **135** positioned between adjacent substrates **106**, **106'**, to vary the position thereof in the direction of the normal axis **107**, i.e. along arrows **137**, so that the angle **136** may be set to a desired value. The vertical alignment unit **135** thus provides for facilitating the alignment of the plurality of substrates **106**, **106'**, to e.g. the curvature of the light transmissive panel **101**. For example, if the light transmissive panel **101** is concave in the direction of the normal axis **107**, initially parallel substrates **106**, **106'**, may be angled to closely follow the concave shape of the light transmissive panel **101** by increasing the angle **136** between the substrates **106**, **106'**, as schematically illustrated in FIG. **4b**. The position of the emitters and detectors **103**, **103'**, on the substrates **106**, **106'**, may thus remain at an optimized vertical position relative to the light transmissive panel **101** for various curvatures thereof. The vertical alignment unit **135** may comprise various units configured to change the position of the adjacent substrates **106**, **106'**, in the direction of the normal axis **107**, such as bolts, screws, pins, or any other elements that can provide an offset at the ends of the substrates **106**, **106'**.

[0113] The touch sensing apparatus **100** may comprise force distributing units **138** positioned between adjacent substrates **106**, **106'**, configured to provide a fixing force therebetween, as schematically illustrated in FIG. **4c**. The force distributing units **138** may provide for improving and facilitating the fixing of the substrates **106**, **106'**, to the carrier, without the need for dedicated fixing elements such as screws, bolts, etc to each end of respective substrates **106**, **106'**, thereby reducing the amount of such fixing elements, which facilitates the assembly of the touch sensing apparatus **100**.

[0114] The touch sensing apparatus may thus comprise a plurality of substrates **106**, **106'**, extending in a longitudinal direction **123** along the perimeter **104** of the light transmissive panel **101**. A first substrate **106** of the plurality of substrates may comprise a connection unit **125** configured to directly interlock with a subsequent connection unit **125'**

of a subsequent substrate **106'** when arranged adjacent said subsequent substrate, as schematically illustrated in FIG. **4a**. It is thereby possible to directly connect subsequent substrates **106**, **106'**, and eliminate the need for intermediate connectors, which further provides for facilitating the assembly of the touch sensing apparatus **100**.

[0115] The touch sensing apparatus **100** may comprise a sealing window **126** as schematically illustrated in FIGS. **5a-b**. The sealing window **126** may be arranged around the perimeter **104** of the light transmissive panel **101**. The sealing window **126** may comprise a first surface **129** facing the light emitters **103** or the light detectors **103'**, and an opposite second surface **130** arranged adjacent the touch surface **102**. Emitted or detected light thus propagates between the first and second surface **129**, **130**. At least one of the first and second surfaces **129**, **130**, may comprise a light collimating surface **129**, **130**, configured to collimate light propagating above the touch surface **102**. I.e. emitted light **105** will be collimated by the sealing window **126**, so that the light propagating above the touch surface **102** will be collimated. Detectors **103'** will receive the collimated light which will be focused through a corresponding sealing window **126**. As the emitters and detectors **103**, **103'**, are arranged above the touch surface **102** and are connected to a substrate **106** extending in a direction parallel with a normal axis **107**, it is possible to provide for a very precise and improved alignment thereof in relation to the sealing window **126**, which allows for achieving collimated light in a highly optimized manner, and an associated increase in signal strength since more of the emitted light can be collected by the detectors **103'**. The emitted light is collimated in a direction parallel with the plane **108** in which the light transmissive panel **101** extends. Collimating the light with sealing window **126** also allows for reducing the aperture of the sealing window **126**, i.e. the thickness of the sealing window **126** in the direction of the normal axis **107**, while still detecting a sufficient amount of light. This provides for reducing the amount of ambient light reaching the detectors **103'**, thus improving the signal to noise ratio.

[0116] Turning to FIG. **5b**, the second surface **130** may extend in the direction of the normal axis **107** between a base surface **131** of the sealing window **126**, facing the light transmissive panel **101**, and an opposite top surface **132** of the sealing window **126**. The base surface **131** may be offset from the top surface **132** along the direction of the plane **108** with an offset distance **133** so that the second surface **130** forms an angle **134** relative to the normal axis **107**. As further illustrated in FIG. **5b**, the second surface may comprise the light collimating surface **130**. Thus, in addition to having a convex shape as illustrated in FIG. **5b**, the second surface **130** is arranged to assume a tilted configuration as provided by the offset distance **133**. Having such angled configuration provides for reducing the impact of Fresnel reflexes. The Fresnel reflexes otherwise generate additional unwanted light paths that will reduce the apparent attenuation on some detection lines, especially when they run parallel to and near a sealing window **126**. These Fresnel reflexes may also result in artifacts and false touch information. By having an angled and/or curved second surface **130** of the sealing window **126**, the light may instead bounce off the second surface **130** with such an angle so that it leaves the plane **108**, and thereby not interfere with the detection of the remaining light.

[0117] A sealing window 126 as described above can provide for the advantageous effects as described for touch sensing apparatuses having a plurality of light emitters and detectors arranged in a multitude of configurations, not limited to the configurations described in relation to FIGS. 2 and 3 exemplified above. A touch sensing apparatus 100 is thus provided comprising a light transmissive panel 101 extending in a plane 108 having a normal axis 107, wherein the light transmissive panel defines a touch surface 102. The touch sensing apparatus 100 comprises a plurality of light emitters 103 and detectors 103' arranged along a perimeter 104 of the light transmissive panel, wherein the light emitters are arranged to emit a respective beam of emitted light 105 above the touch surface, wherein the light detectors are arranged to receive detection light 105' from the emitted light. The touch sensing apparatus 100 comprises a sealing window 126 arranged around the perimeter, wherein the sealing window comprises a first surface 129 facing the light emitters or the light detectors and an opposite second surface 130 arranged adjacent the touch surface, whereby the emitted or detected light propagates between the first and second surface, wherein the second surface extends in the direction of the normal axis between a base surface 131 of the sealing window, facing the light transmissive panel, and an opposite top surface 132 of the sealing window, wherein the base surface is offset from the top surface along the direction of the plane with an offset distance 133 so that the second surface forms an angle 134 relative the normal axis, and wherein the second surface comprises a light collimating surface 130 configured to collimate light propagating above the touch surface.

[0118] The first surface 129, facing the emitters or detectors 103, 103', may also be angled, with an angle 134', as schematically illustrated in FIG. 5a, to provide for the desired light path from or towards the emitters or detectors 103, 103', respectively. The first surface 129 may also comprise a light collimating surface and have a convex shape towards the emitters or detectors 103, 103', as illustrated in FIG. 5a, in addition to being arranged at an angle 134'. The angles 134, 134', may be in the range of 2-10 degrees relative to the normal axis 107 to provide for a particularly advantageous reduction of Fresnel reflexes. An angle greater than 2 degrees avoids Fresnel reflexes and an angle of less than 10 degrees reduces the light field height.

[0119] The sealing window 126 may comprise a fixing element 139 configured to interlock to carrier 110. In the example in FIG. 5a, the fixing element comprises a protrusion 139 arranged to interlock with a corresponding recess in the carrier 110. Mounting and fixing of the sealing window 126 may thus be facilitated and improved since the fixing element 139 may snap into the carrier 110, without needing to have separate fixing units or adhesives joining the sealing window 126 to the carrier 110. In some circumstances, it is preferable not to use an adhesive because the adhesive may not be resilient in high temperatures. Use of an adhesive for fixing the sealing window 126 can be problematic because the uncured adhesive allows for relative movement between the components and precise alignment may be difficult. It is conceivable that the fixing element 139 may comprise any other shape, such as a recess, for interlocking with a corresponding mating surface of the carrier 110.

[0120] Alternative embodiments of the sealing window 126 will now be described in reference to FIGS. 7 to 16.

[0121] FIG. 7 shows an exploded perspective schematic view of the touch sensing apparatus 100. The dotted line shows the normal axis 107 of the touch surface 102 at the center of the light transmissive panel 101. For the purposes of clarity, the exploded perspective view in FIG. 7 shows the separate components side by side, but the dotted line of the normal axis 107 represents the order of how the components stack together. As mentioned previously the carrier 110 may extend substantially in the direction parallel with the normal axis 107. In this way the carrier 110 comprises a downwardly projecting skirt 700 from the upper surface 702.

[0122] The sealing window 126 is mountable on the carrier 110 and this will be discussed in further detail below. The sealing window 126 comprises a similar shape to the arrangement of the plurality of light emitters 103 and detectors 103' (not shown in FIG. 7 for the purposes of clarity). The sealing window 126 is mounted such that the plurality of light emitters 103 and detectors 103' are between the sealing window 126 and the skirt 700. As shown in FIG. 7, the sealing window 126 is a rectangular loop structure.

[0123] In some embodiments, the sealing window 126 may be formed from a single monolithic piece of material, thus providing for a robust sealing window 126 and a stable attachment to the carrier 110 and the light transmissive panel 101. The sealing window 126 may be formed by an extrusion process. In one embodiment, the sealing window is formed from two separate materials. A first material, such as a dyed PMMA or similar NIR transparent material, is used for a transparent section and a second material, such as a compressible light blocking material, is used for sealing off the E/D compartment. This may be achieved by e.g. using a co-extrusion process.

[0124] In other embodiments, the sealing window 126 is formed from a plurality of longitudinal pieces (not shown) and joined together to form a rectangular arrangement. Each longitudinal piece may be a single monolithic piece of material. Considering the sealing window 126 in FIG. 7, the arrangement as shown in FIG. 7 is formed from four pieces of extruded sealing window material 126. The four pieces are then joined together to construct the rectangular loop as shown in FIG. 7. The four pieces of the extruded sealing window 126 can be adhered together with glue, or fastened together with screws, clips, clamps or any other suitable fastener. The glue can be applied and cured before the sealing window 126 is slid into the carrier 110 or the glue can be left to cure once the sealing window 126 is positioned in the carrier 110. Alternatively the four pieces are not fastened or glued together and are held in position with a friction fit.

[0125] The sealing window 126, once assembled, is sandwiched between the upper surface 702 of the carrier 110 and the light transmissive panel 101. In some embodiments, the sealing window 126 is slid into position between the carrier 110 and the light transmissive panel 101. FIG. 8 shows the direction A in which the sealing window 126 is moved with respect to the carrier 110 and the light transmissive panel 101. In this embodiment the sealing window 126 is slid in a direction parallel with the plane of the light transmissive panel 101. In other embodiments, discussed in more detail below, the sealing window 126 can be inserted into the carrier 110 in a different direction such as parallel to the normal axis 107 and perpendicular to the touch surface 102.

[0126] In some embodiments the light transmissive panel 101 is not required to be light transmissive. For example the

touch surface **102** can be on a medium through which light does not propagate. In some embodiments the touch surface **102** can be part of a surface which does not require light from a display unit **113, 121** to be visible there through. That is, the touch sensing apparatus **100** is remote from the display unit **113, 121** and the display unit **113, 121** is not stacked together with the other components as shown in FIG. 7. In this way the light transmissive panel **101** can be considered to be a panel **101**. For the purposes of clarity, the panel **101** has been referred to as a light transmissive panel **101**, but all the embodiments are also applicable to a panel comprising an opaque or light blocking material.

[0127] Turning to FIG. 8, the construction of the carrier **110**, the sealing window **126** and the light transmissive panel will now be discussed in more detail. FIG. 8 shows a partial perspective cross-sectional view of the touch sensing apparatus **100**. In particular FIG. 8 is magnified to show the arrangement between the carrier **110**, the sealing window **126** and the light transmissive panel **101**.

[0128] The sealing window **126** comprises a dual purpose. Firstly, the sealing window **126** provides sealing around the perimeter **104** of the light transmissive panel **101** and protects the emitters and detectors **103, 103'** and the edge of the light transmissive panel **101**. This means that the sealing window **126** prevents ingress of dirt, water and other contaminants into the interior of the touch sensing apparatus **100**. This helps protect the internal components such as the plurality of emitters and detectors **103, 103'**. Secondly, the sealing window **126** allows light from the emitters and detectors **103, 103'** to propagate therethrough. In some embodiments, as discussed in reference to FIG. 5a, the sealing window can optionally comprise optical elements for refracting, deflecting, diverting or focusing the light beams therethrough. However in other embodiments, the sealing window is optically passive and does not comprise any optical elements for refracting, deflecting, diverting or focusing the light beams therethrough.

[0129] As can be seen from FIG. 8, an upper sealing surface **800** of the sealing window **126** engages with an interior underside surface **802** of the carrier **110**. The upper surface **702** of the carrier **110** is arranged to project over the light transmissive panel **101**. In this way the carrier **110** overlaps a portion of the light transmissive panel **101** around the perimeter of the light transmissive panel **101**. The portion **810** of the upper surface **702** that overlaps with the light transmissive panel **101** is indicated by a bracket in FIG. 8. The overlapping portion **810** of the carrier **110** provides protection for the perimeter light transmissive panel **101** from shock and other physical forces. The overlapping portion **810** also provides an overhang on which the sealing window **126** can be mounted. The interior underside surface **802** of the carrier is an opposite face to the upper surface **702**. A lower sealing surface **804** of the sealing window **126** engages with the touch surface **102**.

[0130] In order to aid the sealing, the sealing window **126** optionally comprises one or more deformable seals or integral gaskets **806, 808** mounted on the upper sealing surface **800** and the lower sealing surface **804** respectively. The deformable seals **806, 808** are arranged to deform when the light transmissive panel **101** is urged towards the carrier **110**. The deformable seals **806, 808** are extruded along the longitudinal length of the sealing window **126**. In some embodiments the deformable seals **806, 808** are integral with the sealing window **126**. As mentioned previously, in

some embodiments the deformable seals **806, 808** can be manufactured at the same time as the sealing window **126** in a co-extrusion process. Alternatively the deformable seals **806, 808** are mounted and adhered to the sealing window **126** after the sealing window **126** has been extruded. In some embodiments the deformable seals **806, 808** are made from a thermoplastic elastomer (TPE). The deformable seals **806, 808** can be colored black to block transmission of light from the sealing window **126**. The deformable seals **806, 808** can be any suitable color or material for absorbing light and minimizing light in-coupling.

[0131] In some embodiments the sealing window **126** is configured to be mounted between two surfaces for sealing and protecting the emitters and detectors **103, 103'** from the outside environment. In some embodiments the sealing window **126** is arranged to seal against the touch surface **102** and the interior underside surface **802** of the carrier **110**. In other embodiments the sealing window **126** can be mounted between any other surface to provide a sealed cavity **116** around the emitters and detectors **103, 103'**. In some embodiments the sealing window **126** seals between the interior underside surface **802** and other surface. The other surface does not need to be the touch surface **102**. Instead the other surface is another interior surface of the carrier **110** such as a surface on which the substrate **106** is mounted on. In some other embodiments the sealing window **126** is mounted and sealed against another components and neither of the touch surface **102** and the interior underside surface **802**. In some embodiments the sealing window **126** is sealable against at least one surface of the touch sensing apparatus **100** for sealing a cavity **116** around the plurality of light emitters and detectors **103, 103'**. In some embodiments the carrier **110** may also be the substrate **106** or the emitters and detectors **103, 103'** are mounted directly to the carrier **110**.

[0132] In some embodiments the sealing window **126** comprises at least one reference surface **812** for aligning the sealing window **126** with respect to the carrier **110**. The reference surface **812** will be discussed in further detail with respect to FIG. 9 for the purposes of clarity.

[0133] FIG. 9 is a schematic cross-sectional view of the touch sensing apparatus **100**. The sealing window **126** is inserted between the light transmissive panel **101** and the carrier **110**. The upper deformable seal **806** comprises a reference surface **812** for aligning the sealing window **126** with respect to the carrier **110**. The upper deformable seal **806** comprises a projection **814** which projects upwardly from the upper deformable seal **806** and the sealing window **126**. In this way, the reference surface **812** is upright with respect to the sealing window **126**. The projection **814** also optionally comprises a chamfer **816** in addition to the reference surface **812**.

[0134] The chamfer **816** means that the deformable upper seal **806** does not snag on the carrier **110** when the sealing window **126** is inserted between the carrier **110** and the light transmissive panel **101**. Accordingly as the sealing window **126** is pushed into place, the chamfer **816** urges against the interior underside surface **802** of the carrier **110**. Initially, the deformable upper seal **806** is squashed between the carrier **110** and the light transmissive panel **101** when the sealing window **126** is being forced between the carrier **110** and the light transmissive panel **101**.

[0135] The sealing window **126** is pushed towards a notch **820** located in the interior underside surface **802** of the

carrier **110**. In some embodiments, the notch **820** is a groove that extends around the periphery of the carrier **110**. The notch **820** comprises a reciprocal reference surface **818** for aligning with the reference surface **812** of the projection **814**. In particular, the notch **820** is a reference point for indicating that the sealing window **126** is inserted underneath the overlapping portion **810** sufficiently to form a seal and protect the internal components of the touch sensing apparatus **100**. The notch **820** is positioned a predetermined distance from the edge **822** of the carrier **110**. In some embodiments the predetermined distance is at least half the width of the sealing window **126**.

[0136] When the sealing window **126** pushed sufficiently between the carrier **110** and the light transmissive panel **101**, the deformed projection **814** is located within the notch **820**. At this point when the sealing window **126** is located in the correct position with respect to the carrier **110**, the reference surface **812** abuts against a reciprocal reference surface **818** in the notch **820** in the carrier **110**.

[0137] The compressed projection **814** resiles and expands once located in the notch **820**. In this way, the project **814** snaps into position and positively engages with the notch **820**. When the sealing window **126** is located and the projection **814** snaps into place, the sealing window **126** makes an audible “click”. Additionally or alternatively the snapping of the projection **814** into position provides a tactile feedback during assembly that the sealing window **126** is seated correctly.

[0138] The size of the notch **820** is slightly larger than the dimensions of the projection **814**. Accordingly the projection **814** fits snugly within the notch **820**. This means that the frictional forces between the carrier **110**, the light transmissive panel **101** and the sealing window **126** are sufficient to hold the sealing window **126** in place. Adhesive is not required to fix the sealing window **126** in place. However in some embodiments adhesive is optionally used in addition to the snap-fit positive engagement.

[0139] In some embodiments the reference surface **812** abuts against the reciprocal reference surface **818**. This means that the sealing window **126** opposes the direction **A** by virtue of the engaged reference surfaces **812**, **818**. Removal of the sealing window **126** may only be achieved with a special tool which compresses the projection **814**.

[0140] Once the sealing window **126** has been seated correctly in the carrier **110**, the reference surfaces **812**, **818** maintain the alignment between the carrier **110** and the sealing window **126**. The deformable seals **806**, **808** maintain the relative position of the sealing window **126** with respect to the carrier and prevents lateral movement in a plane parallel to the light transmissive panel **101**. Furthermore, the reference surfaces **812**, **818** ensure that the sealing window **126** is maintained at a certain height above the touch surface **102**.

[0141] The shape and size of the deformable seal **806**, **808** can be varied. Another embodiment with such a variation is shown in FIG. **10**. FIG. **10** shows a cross sectional side view of the touch sensing apparatus **100**. The arrangement is the same as shown in reference to FIGS. **8** and **9**, except the cross sectional shape of the deformable seal **806**, **808** is different. In this embodiment the projection **1002** comprises a curved upwardly projecting bulge **1002** on the upper deformable seal **806**. The bulge **1002** comprises a curved reference surface **1004** which engages with one or more reciprocal reference surfaces **818** of the notch **820**. The

curved reference surface **1004** functions in a similar way to the chamfer **814** as described in reference to the previous embodiment when inserting the sealing window **126** between the light transmissive panel **101** and the carrier **110**. The bulge **1002** has dimensions which are substantially the same width as the width of the notch **820** so that the sealing window **126** does not experience lateral movement in a direction parallel with the plane of the light transmissive panel **101**. The lower seal **808** optionally comprises a similar bulge **1006** for engaging and sealing against the touch surface **102**. By making the upper seal **806** and the lower seal **808** have the same cross section, manufacture can be simplified because the same die (not shown) can be used during extrusion of the deformable seals **806**, **808**.

[0142] Advantageously the shape of the projection **1002** means that the sealing window **126** can be removed with a similar magnitude of force to the force needed for insertion during assembly. Accordingly removal of the sealing window **126** may not require a tool. This can make maintenance which requires removal of the sealing window **126** easier.

[0143] Another embodiment is shown in FIG. **11**. FIG. **11** shows a cross sectional side view of the touch sensing apparatus **100**. FIG. **11** is the same as shown in FIG. **10** except that there is an additional projection and notch. The first notch **1100** and first bulge **1104** are substantially the same as the notch **820** and the bulge **1002** as discussed in reference to FIG. **10**. In addition, there is a second notch **1102** and a second bulge **1106**. Likewise the lower seal **808** comprises similar first and second bulges **1108**, **1110**. Having two projecting bulges **1104**, **1106** means that there are two points of sealing engagement between the sealing window **126** and the light transmissive panel **101** and the carrier **110** respectively. This means that there will be less rotation of the sealing window **126** about the deformable seal **806**, **808**. Accordingly, the tolerances needed to accommodate rotational movement of the sealing window about the longitudinal axis of the sealing window can be lower. There is also an increased surface area of the deformable seals **806**, **808** and therefore the deformable seals will cool quicker during manufacture.

[0144] In another embodiment, the first and second bulges **1104**, **1106** engage with a single notch **820** as shown in FIG. **10**. The dotted line between the first and second notches **1100**, **1102** represents a single notch, similar to the notch **820** in FIG. **10**. In this case the first bulge **1104** engages a first reciprocal reference surface **1114** and the second bulge **1106** engages with a second reciprocal reference surface **1112**. The first and second reciprocal reference surfaces **1114**, **1112** are walls of the notch **820**.

[0145] Another embodiment will now be discussed in reference to FIG. **12**. FIG. **12** shows a schematic perspective and cross-sectional view of the touch sensing apparatus **100**. The arrangement as shown in FIG. **12** is the same as shown in FIGS. **8** and **9** except that the deformable seal **806** comprises a plurality of discrete projections **1200**, **1202**, **1204**. Each of the projections is deformable and is inserted between the light transmissive panel **101** and the carrier **110** in the same way as described with respect to the previous embodiments. The carrier **110** comprises a series of reciprocal recesses (not shown for clarity) to receive a respective projection **1200**, **1202**, **1204**. In this way less deformable material is required to perform the alignment function. The projections may be adhered to the deformable seal material **806** or the projections can be extruded. Each of the projec-

tions **1200**, **1202**, **1204** comprise a reference surface for aligning the projection and the sealing window **126** with the reciprocal recess in the carrier **110**. In some embodiments the projections **1200**, **1202**, **1204** can comprise any suitable cross sectional shape. For example, the projections can comprise an oval curved cross section, similar to the bulges shown in the embodiments discussed in reference to FIGS. **10** and **11**.

[0146] FIG. **13** shows yet another embodiment. FIG. **13** shows a schematic exploded perspective view of the touch sensing apparatus **100**. For the purposes of clarity the light transmissive panel **101** is not shown. The sealing window **126** is the same as described in reference to the previous embodiments. The upper deformable seal **806** is mounted on the upper sealing surface **800**. In contrast to the previous embodiments, the deformable seal **806** does not comprise upward projections comprising a reference surface. Instead the sealing window **126** comprises positioning pegs **1300**, **1302** for engagement in the reciprocal positioning holes **1304**, **1306** located in the carrier **110**. In this way the reference surfaces are separate from the deformable seal **806**. Each of the positioning pegs **1300**, **1302** comprises a reference surface **1308**, **1310** for aligning the sealing window **126**. In this way as the sealing window is slid underneath the carrier **110** in the direction A, the pegs **1300**, **1302** slot into the positioning holes **1304**, **1306**. The holes **1304**, **1306** are blind holes and when the reference surfaces **1308**, **1310** abut the end of the blind holes **1304**, **1306**, the sealing window **126** is in the correct position. The holes **1304**, **1306** are deep enough such that the sealing window **126** is completely under the carrier **110**, similar to the arrangement shown in the previous embodiments.

[0147] FIG. **14** shows another embodiment. FIG. **14** shows a cross sectional side view of the touch sensing apparatus **100**. The arrangement as shown in FIG. **14** is the same as shown in FIGS. **8** and **9** except that the projection **1400** is formed on the carrier **110** and the notch **1402** is formed in the upper deformable seal **806**. In this embodiment the projection **1400** is rigid and downwardly projects from the carrier **110**. The notch **1402** is deformable and snaps into position when the notch **1402** is in positive engagement with the projection **1400** and reference surfaces are in engagement. The sealing window **126** is inserted between the carrier and the light transmissive panel **101** in the same way as discussed previously.

[0148] In alternative embodiments, the carrier **110**, the light transmissive panel **101** and the sealing window **126** are assembled in a different order. The components are the same as described in reference to the previous embodiments. Turning to FIGS. **15a-15d** and FIG. **16** the alternative method of assembly will now be discussed.

[0149] FIGS. **15a-15d** show a side cross section of the touch sensing apparatus **100**. The light transmissive panel **101** has been omitted for clarity. The sealing window **126** is pushed towards the carrier **110** in direction B. That is, a direction which is parallel to normal axis **107**. FIG. **15a** shows two deformable projections **1500**, **1502** which have a snap-fit engagement with reciprocal grooves in the carrier. The deformable projections **1500**, **1502** have a cross sectional shape that snaps into the reciprocal holes when the sealing window is seated correctly in the carrier **110**.

[0150] FIG. **15b** shows a similar arrangement to FIG. **15a** except that there is a single projection **1504** which does not have a snap-fit engagement. Optionally, positive engage-

ment is provided by the projection **1504** having a snug friction fit. When the sealing window **126** cannot move any further with respect to the carrier **110**, the projection **1504** will abut the reciprocal surface of the hole in the carrier **110** and the sealing window will be seated correctly.

[0151] FIGS. **15c** and **15d** show stepwise engagement of the same arrangement. The deformable seal **806** comprises snap-fit latches **1506**, **1508** which bend and snap into place once the sealing window is fully seated in the carrier **110**.

[0152] Once the sealing window **126** and the carrier **110** are assembled, then the light transmissive panel **101** is mounted in the carrier **110**.

[0153] FIG. **16** shows a schematic exploded perspective view of the carrier **110** and the sealing window **126**. The arrangement as shown in FIG. **16** is the same as shown in FIG. **13**, except that the relative movement of the sealing window **126** with the respect to the carrier **110** during assembly is perpendicular. That is, along direction B parallel with the normal axis **107**. Similar to the embodiment as shown in FIG. **13**, the sealing window **126** comprises a plurality of reference surfaces which are not part of the deformable seal **806**. Each of pegs **1600**, **1606** and snap-fit latches **1602**, **1604** comprises a reference surface for alignment. FIG. **16** shows pegs **1600**, **1606** for engagement with holes **1608**, **1610**. FIG. **16** also shows resiliently deformable latches **1604**, **1602** for snap-fit engagement with holes **1612** and **1614**.

[0154] A further mounting unit **140** may be provided between the sealing window **126** and the light transmissive panel **101**, as schematically illustrated in FIG. **5a**. The mounting unit **140** may comprise a resilient material that allows the sealing window **126** to assume a secure fixed position relative the light transmissive panel **101**. The sealing window **126** may have a corresponding groove into which the mounting unit **140** may be securely positioned.

[0155] A method **200** of assembling a touch sensing apparatus **100** is provided. FIG. **6** illustrates steps of the method **200**. The order in which the steps of the method **200** are described and illustrated should not be construed as limiting and it is conceivable that the steps can be performed in varying order. The method **200** comprises fixing **201** a substrate **106** having a plurality of light emitters **103** and detectors **103'** to a carrier **110**, and attaching **202** the carrier **110** around a perimeter **104** of a light transmissive panel **101**. The method further comprises arranging **203** the substrate to extend in a direction **107'** parallel with a normal axis **107** of a plane **108** in which the light transmissive panel **101** extends, whereby the plurality of light emitters and detectors **103**, **103'**, are arranged above the touch surface **102**. The method **200** thus provides for a facilitated assembly of the touch sensing apparatus **100** while achieving optimal alignment, robustness, and accuracy as described above in relation to FIGS. **2-3**.

[0156] As mentioned, the carrier **110** may be formed from a single monolithic piece of material, and the carrier may form a cavity **116** having walls **117** at least partly enclosing the substrate **106**. At least one of the walls **117** may comprise openings **115**, **115'**, **115''**. The method **200** may comprise fixing **204** the carrier **106** to a display unit **121**, **113**, by fixing mounting elements **114** through the openings **115**, **115'**, **115''**, thereby providing for the above mentioned advantages.

[0157] The method **200** may comprise adjusting **205** a distance **120** between the light transmissive panel **101** and a

display unit **113, 121**, along the normal axis **107** by attaching **207** the carrier **110** to the display unit **113, 121**, at at least two different adjustable positions **119, 119'**, along a direction **117"** parallel to the normal axis **107**. Control of the distance **120** is improved and facilitated, and may thereby be more easily optimized to various applications of the touch sensing apparatus **100**.

[0158] The method **200** may comprise adjusting **208** a radius of curvature of the light transmissive panel **101** in the direction of the normal axis **107** by attaching **209** the carrier **110** to a display unit **113, 121**, at at least two different adjustable positions **119, 119'**, along a direction **117"** parallel to the normal axis **107**. Control of the curvature of the light transmissive panel **101** is thus improved as described above.

[0159] The invention has mainly been described above with reference to a few embodiments. However, as is readily appreciated by a person skilled in the art, other embodiments than the ones disclosed above are equally possible within the scope and spirit of the invention, which is defined and limited only by the appended patent claims.

[0160] For example, the specific arrangement of emitters and detectors as illustrated and discussed in the foregoing is merely given as an example. The inventive coupling structure is useful in any touch-sensing system that operates by transmitting light, generated by a number of emitters, inside a light transmissive panel and detecting, at a number of detectors, a change in the received light caused by an interaction with the transmitted light at the point of touch.

What is claimed is:

1. A touch sensing apparatus, comprising:
 - a plate comprising a touch surface, a back surface, and an edge surface;
 - a support structure extending parallel to the edge surface of the plate, said support structure extending above the touch surface, said support structure configured to

support an emitter, wherein the emitter is positioned on the support structure to transmit light in a plane above the touch surface and perpendicular to a normal of the touch surface; and

an optical element positioned above the touch surface, said optical element comprising a first surface configured to receive the transmitted light directly from the emitter and a second surface configured to receive light propagating across a touch interacting portion of the touch surface.

2. The touch sensing apparatus of claim 1, wherein the first surface of the optical element comprises a light collimating surface.

3. The touch sensing apparatus of claim 1, wherein the optical element comprises glass or plastic.

4. The touch sensing apparatus of claim 1, wherein the support structure is one element of a frame assembly, wherein the frame assembly comprises a plurality of frame elements.

5. The touch sensing apparatus of claim 4, wherein the plurality of frame elements comprise a first element including:

- a first portion extending parallel to the edge surface of the plate in a direction perpendicular to a normal of the touch surface;
- a second portion extending parallel to the touch surface and covering a portion of the touch surface, wherein the second portion is separated from the touch surface by a spacing; and
- a retaining member in the second portion, wherein the retaining member is configured to secure the optical element in the spacing between the first element and the touch surface.

* * * * *